

COMP3206/6229 (2015/16): Machine Learning Lab 5 (of 6)

5%

Issue	Wednesday 11 November 2015
Deadline	Thursday 19 November 2015 (12:00 Noon)

This task is worth 5% of your total assessment. Please work independently. Submit a report of no more than two pages describing your work. Marking Scheme: Three marks for doing correctly what you are asked to do; five marks for showing some insight and/or initiative in completing the tasks.

Construct a radial basis functions (RBF) model to predict house prices using the “Boston Housing Data,” used in Lab 4. The RBF model is given by

$$g(\mathbf{x}) = \sum_{k=1}^K \lambda_k \phi(\|\mathbf{x} - \mathbf{c}_k\|).$$

We will use a Gaussian RBF $\phi(\alpha) = \exp(-\alpha/\sigma^2)$.

1. Load the data, normalize it as done in Lab 4 and get random partitions of training and test sets. Say variable **Xtr**, a matrix of **Ntr** × **p** is inputs of your training set and **ytr**, the corresponding outputs (targets).
2. Set the widths of the basis functions to a sensible scale

```
sig = norm(Xtr(ceil(rand*Ntr),:)-Xtr(ceil(rand*Ntr,:),));
```

3. Perform K -means clustering to find centres for the basis functions. Use $K = Ntr/10$.

```
help kmeans  
[C] = kmeans(Xtr, round(Ntr/10))
```

4. Construct the design matrix

```
for i=1:Ntr  
    for j=1:K  
        A(i,j)=exp(-norm(Xtr(i,:) - C(j,:))/sigma^2);  
    end  
end
```

5. Solve for the weights

```
lambda = A \ ytr;
```

6. What does the model predict at each of the training data?

```

yh = zeros(Ntr,1);
u = zeros(Ntr,1);
for n=1:Ntr
    for j=1:K
        u(j) = exp(-norm(Xtr(n,:) - C(j,:))/sigma^2);
    end
    yh(n) = lambda'*u;
end
plot(y, yh, 'rx', 'LineWidth', 2), grid on
title('RBF Prediction on Training Data', 'FontSize', 16);
xlabel('Target', 'FontSize', 14);
ylabel('Prediction', 'FontSize', 14);

```

7. Adapt the above to calculate what the model predicts at the unseen data (test data) and draw a similar scatter plot. How do the training and test errors compare? Compute the difference between training and test errors at different values of the number of basis functions, K . Briefly comment on any observation you make.
8. Compare your results with the linear regression model of Lab 4. Does the use of a nonlinear model improve predictions?
9. Carry out a similar comparison between linear and nonlinear (RBF) models on a different dataset of your choice taken from the UCI Machine Learning repository.

Note: When comparing performances of the linear and RBF models, partition the data into training / test sets multiple times (say 20), evaluate the test set prediction errors, and present your results as two boxplots drawn side by side, as in Fig. .




Figure 1: Comparison of linear and radial basis functions (RBF) models on predicting house prices. The mean squared error on test data is obtained from 20 random partitionings.