
How Foveated Vision Shapes Cognitive Maps in Navigation Agents

Anonymous authors

Paper under double-blind review

Abstract

Spatial memory in primates is not a sensor-independent module. Hippocampal cells code joint place–view–action state in part because the primate eye samples the world through a foveated sensor that resolves a small high-acuity region per glance; rodents with near-panoramic vision instead develop classic place fields, and individuals deprived of vision recruit hippocampal circuits to compensate. The biological pattern is consistent: *the structure of the sensor shapes the structure of spatial memory*. Whether the same holds for artificial navigation agents — whose recurrent memories also develop cognitive-map-like representations under task pressure alone — has not been tested directly, because prior work has either removed vision entirely or used spatially uniform input, never varying sensor structure as an independent variable. We isolate the principle in a controlled silicon model: five navigation agents are trained with everything but the visual pathway held identical, spanning a sensor-structure spectrum from no vision through a resolution-collapsed encoder, foveated vision (with fixed and learned gaze), and full uniform vision. Probing their recurrent state reveals an *encoder–memory race*: the recurrent state maintains a linearly-decodable world-frame spatial code when the visual encoder cannot supply enough spatial-feature variety per step, while the code dissipates in conditions where the encoder is rich enough to substitute. Independently, agents that solve the same task at comparable competence develop hidden states in linearly disjoint subspaces, and cross-condition memory transplants are asymmetric: bottleneck-donor states hurt rich-encoder recipients more than vice versa. The often-asserted intuition that “richer perception begets richer memory” fails in this regime — the relationship across our five conditions is inverse — making encoder capacity a candidate training-time lever for inducing cognitive-map-like internal representations (pending the resolution scaling sweep that would test the mechanism causally; the cross-condition pattern is itself single-seed, with multi-seed replication in flight). The agent pattern echoes — without depending on — biological findings on hippocampal compensation under sensory deprivation and cross-modality remapping, suggesting a sensor–memory coupling principle whose generality across architectures is open.

1 Introduction

Primate spatial memory is shaped by how primates see. Hippocampal cells code joint place–view–action state in part because the primate eye samples the scene through a foveated sensor [Wirth et al., 2017, Rolls, 2024]; rodents with near-panoramic vision instead show classic place fields. Sensor structure also reorganises memory *within* a single animal — bats produce non-overlapping hippocampal populations under vision vs. echolocation [Geva-Sagiv et al., 2016], and congenitally blind humans develop enhanced hippocampal coupling on non-visual spatial tasks [Kupers and Ptito, 2014]. The biological pattern is consistent: *the structure of the sensor reshapes the structure of spatial memory*. We ask whether the same is true of artificial navigation agents.

The emergent-cognitive-maps literature has shown that map-like structure arises in the recurrent state of navigation agents trained with deep RL, including agents with no vision at all [Wijmans et al., 2023, Banino et al., 2018, Cueva and Wei, 2018]. These results establish that *some* map-like structure is learned without being designed in. They leave open the complementary question we take up here: holding task and architecture fixed, does the structure of the visual sensor reshape *what* recurrent memory encodes? We isolate sensor structure as the only varied component across five conditions spanning a sensor-structure spectrum (Figure 1): no vision, a resolution-collapsed encoder, foveated vision with fixed gaze, foveated vision with learned gaze, and uniform full-resolution vision. The resolution-collapsed control separates “no vision” from “vision the encoder cannot resolve”; foveation occupies a biologically motivated point in between.

We test three hypotheses. *H1 (encoder-memory race)*: when the visual encoder supplies little spatial-feature variety per step, the recurrent state should compensate by carrying a world-frame spatial code; richer encoder output should let memory rely on visual features instead. *H2 (format divergence)*: different sensor conditions should produce hidden-state representations in distinct linear subspaces, not scaled versions of a common code. *H3 (gaze location)*: within the rich-encoder regime, where a foveated sensor is centred should act as a second content axis independent of the sensor transform. Each has a direct biological analog (§5.2).

Three findings emerge with the strongest evidence. An encoder-memory race along the sensor-structure spectrum (H1) that lives inside the recurrent state, not at the encoder. The five agents solve the task at comparable competence but develop hidden states in linearly disjoint subspaces, with measurable cross-condition memory-transplant cost (H2). And probe-readable vs. policy-used memory dissociates in opposite directions for two specific conditions, suggesting that “has a cognitive map” and “uses a cognitive map” need not coincide. Foveation under our blur model converges with uniform on H1 but diverges on H2, behaviour, and dataset shift. H3 (gaze location) is tested by a foveated-shifted control in training at submission.


The cross-condition pattern is correlation-level; a scaling-sweep experiment that would test the H1 mechanism causally is in progress (Appendix H). Foveation-specific predictions involving alternative foveation models depend on experiments still in training (§4.4, Appendix G). Each finding has a direct biological precedent which we discuss as convergent (not conclusive) evidence in §5.2.

2 Related Work


Cognitive maps in RL navigation agents Wijmans et al. [Wijmans et al., 2023] demonstrated that map-like representations emerge in the recurrent memories of DD-PPO agents even without visual input; Dwivedi et al. [Dwivedi et al., 2022] probed sighted agents for related spatial concepts; Banino et al. [Banino et al., 2018] and Cueva & Wei [Cueva and Wei, 2018] found grid-cell-like units in recurrent networks trained on path integration; Gornet & Thomson [Gornet and Thomson, 2024] extended this via visual predictive coding. Hennig et al. [Hennig et al., 2023] showed that RL under partial observability can induce belief-state-like representations without explicit probabilistic objectives. Ramakrishnan et al. [Ramakrishnan et al., 2025] examined spatial cognition in frontier models. All these studies use either absent or spatially uniform perception; none vary input quality spatially, and none test whether different sensors produce different representational formats.

Foveated vision and gaze policies in deep learning Foveated rendering [Strasburger et al., 2011, Rosenholtz, 2016] exploits eccentricity-dependent acuity falloff for efficiency. Learned glimpse policies appear in recurrent attention models [Mnih et al., 2014]; Atanov et al. [Atanov et al., 2024] showed that sensor layout changes downstream task performance. Pourrahimi & Bashivan [Pourrahimi and Bashivan, 2025] probed a foveated visual-search model for neuroscience-predicted features; Shang & Ryoo [Shang and Ryoo, 2023] jointly learned gaze and motor policies following the Sprague & Ballard [Sprague and Ballard, 2003] framework. These address visual search or task performance; none asks how sensor structure reshapes the learned spatial memory of a downstream navigation policy.

Probing neural representations Belinkov [Belinkov, 2022] surveys probing classifiers; Hewitt & Liang [Hewitt and Liang, 2019] introduced control tasks to distinguish genuine structure from probe memorisation; Kornblith et al. [Kornblith et al., 2019] introduced linear CKA for cross-model similarity. We adopt linear probing, the Hewitt-Liang selectivity metric, and unaligned linear CKA, and complement them with two behavioural interventions directly on the recurrent state (memory



Same Gibson val episode (scene E9uDofAP3SH, ep 414)



(d) The 5 conditions on the same MP3D-train episode (scene E9uDofAP3SH, ep 40422 in the env iterator; same paired index 414 across our probing data), trajectories overlaid on the Habitat-rendered top-down occupancy map. Each condition's SPL on this episode is within ± 0.10 of its per-condition median, so all five are typical successful runs. Bottleneck conditions (blind 231 steps, matched 146) take longer paths through the corridor; rich-encoder conditions (uniform / foveated / fov-learned, 77–80 steps) take near-direct paths along the same corridor.

Figure 1: The five visual conditions differ only in what reaches the agent's encoder, but produce visibly different navigation behaviours. *Inputs:* (a) Blind: no visual input; only the non-visual sensor stack (goal-in-start-frame, GPS, compass, close-to-goal scalar) — the Wijmans [Wijmans et al., 2023] configuration. (b) Uniform: 256×256 full-resolution RGB. (c) Foveated (fixed gaze): eccentricity-dependent Gaussian blur centred on the image middle ($\sigma_{\max} = 8$, quadratic falloff). Two additional conditions not pictured: *matched-compute* (a down-sampled uniform view at 48×48 , whose total pixel budget matches foveated and whose ResNet-18 encoder produces a 1×1 feature map) and *foveated (learned gaze)*, which adds a learned (x, y) gaze offset to (c). *Behaviour:* (d) all five conditions solve the same PointGoal navigation task; the trajectory shape and length differ systematically, previewing the encoder–memory race finding (§4.2).

transplant and shortcut discovery) to validate the probe-based findings outside the linear-probe framework.

What is new here Three things distinguish this work. (i) A *controlled* five-condition ablation with everything but the visual pathway held identical, including the matched-compute condition that decouples “no vision” from “vision the encoder cannot resolve”. (ii) A protocol-corrected probing methodology (deterministic action selection at probe time; stochastic sampling inflates probe R^2 via a 4-step quasi-static-trajectory artefact, Appendix A). (iii) Convergent behavioural validation via memory transplant and shortcut discovery, outside the linear-probe framework. Biological motivation and the parallel to animal-navigation research are integrated in §5.2 rather than recapitulated here.

3 Methods

3.1 Setup

All agents are trained on PointGoal navigation in Habitat [Savva et al., 2019] using DD-PPO [Wijmans et al., 2020] on a merged pool of Gibson-0+ [Xia et al., 2018] (411 scenes) and Matterport3D train (61 scenes), totalling 472 training scenes; evaluation uses 18 held-out MP3D test scenes (1008 episodes). All agents share an identical 3-layer LSTM (512-d) backbone and the Wijmans non-visual sensor stack (goal-in-start-frame, GPS, compass, close-to-goal scalar), each projected to 32-d and concatenated with a 32-d previous-action embedding. All sighted conditions train to ~ 250 M environment frames; the blind baseline trains to 342M to allow slower convergence from proprioception alone.

The five visual conditions (Figure 1): *blind* (no visual input); *uniform* (full 256×256 RGB encoded by ResNet-18); *foveated (fixed)* (eccentricity-dependent Gaussian blur, $\sigma_{\max} = 8$ quadratic falloff, gaze locked at image centre, same ResNet-18 encoder); *matched-compute* (48×48 uniform RGB; at this resolution ResNet-18’s 32-fold spatial downsampling collapses the feature map to 1×1 , removing spatial structure but preserving channel information); *foveated (learned)* (same blur model, gaze centre predicted by a lightweight MLP trained end-to-end). Matched-compute is the spatial-bandwidth lower bound for our encoder; it has visual input but its encoder output cannot resolve world-frame position. The 48×48 input also has lower spatial resolution than uniform’s 256×256 , so this single condition cannot fully separate the 1×1 collapse from low input resolution; the encoder-resolution scaling sweep (Appendix H) addresses this directly. The foveated conditions disable the running-mean-and-variance input normaliser to avoid an in-place autograd conflict along the gaze-decoder gradient path; an invariance control is in training. We also discovered and patched a silent NaN-gradient corruption mode in DD-PPO (Appendix F).

3.2 Probes

After training, all weights are frozen. We collect per-step top-layer LSTM hidden states (512-d) paired with ground-truth labels from $n=500$ Gibson held-out episodes under *deterministic* argmax-action rollouts (matching our shortcut / transplant / standard eval protocols; the alternative stochastic protocol gives trivial ~ 4 -step rollouts and is documented in Appendix A). We train Ridge probes ($\alpha = 10$) with episode-level 5-fold cross-validation, report mean $\pm \sigma$ across folds, and verify probe specificity with Hewitt–Liang label-permutation selectivity [Hewitt and Liang, 2019]. Probed variables: GPS position, compass heading, distance-to-goal, lag- k path history ($k \in \{0, \dots, 20\}$), visited-region occupancy, full occupancy grid, per-unit spatial information, ego-frame goal vector. For H2 representational geometry we additionally use linear CKA [Kornblith et al., 2019] and cross-condition probe transfer.

We complement probes with two interventions on the LSTM state. *Memory transplant*: paste a donor’s hidden state into the recipient at step 30 and compare baseline / self-transplant / cross-transplant SPL across 150 episodes per pair. *Shortcut discovery*: run paired same-scene-different-goal episodes (20 scenes $\times$ 10 pairs) and compare second-episode SPL under reset vs. persistent LSTM. For foveated-fixed, all analyses use ckpt.36 at ~ 174 M frames (last clean intermediate before the silent-corruption window).

4 Results

4.1 Five conditions, same task

Table 1 collects the headline per-condition numbers. All sighted conditions solve PointGoal at 96–99% success; blind reaches 93% at a longer training budget, reproducing Wijmans et al. [Wijmans et al., 2023]. Success is tightly bunched, so a skill-gap account for the encoded-content differences below is unlikely. The probe is calibrated: distance-to-goal decodes everywhere ($R^2 \in [0.81, 0.90]$); Hewitt–Liang label-permutation selectivity is high precisely where GPS is high (Appendix A).

Table 1: Per-condition headline. Probe R^2 columns are the 5-fold episode-level CV mean $\pm$ std on full-length deterministic-rollout trajectories (no per-episode step cap). *GPS* and *Compass* are world-frame. The bottleneck-vs-rich-encoder gap is in temporal *stability* of the code, not its mid-episode existence (Figure 2b): all five conditions decode top-layer GPS at $R^2 \in [0.6, 0.95]$ in the typical-episode window (steps 50–200); the rich-encoder long-tail collapse is what produces the sub-chance numbers below. Bold marks the H1-relevant ordering (blind > matched $\gg$ rich-encoder).

Condition	Frames	SPL	Success	GPS R^2 (no-cap)	Compass R^2 (no-cap)
Blind	342M	0.59	0.93	+0.95$\pm$0.02	+0.81$\pm$0.08
Matched-compute	250M	0.67	0.98	+0.78$\pm$0.10	+0.64$\pm$0.10
Uniform	250M	0.85	0.99	−0.31 $\pm$ 0.86	+0.36 $\pm$ 0.23
Foveated (fix)	174M	0.78	0.96	+0.06 $\pm$ 0.88	+0.07 $\pm$ 0.69
Fov-learned	250M	0.82	0.98	−2.43 $\pm$ 3.98	−1.34 $\pm$ 3.14

4.2 Encoder–memory race: a temporal-stability claim (H1)

Visual-encoder capacity inversely tracks LSTM spatial encoding across our five conditions: bottleneck conditions (blind, matched) encode GPS / compass at the top layer; rich-encoder conditions (uniform, foveated, foveated-learned) decode at chance (Figure 2a, Table 1). DtG decodes robustly in every condition because every agent must track it. **[TODO: Whether the correlation reflects causation is what the §4.4 experiments and the Appendix H resolution sweep test; multi-seed gap-fills are in progress.]**

Temporal stability is the precise claim The no-cap probe conflates “does the LSTM ever encode GPS” with “does it maintain the encoding across episode duration.” Step-binned out-of-fold probing separates them (Figure 2b): all five conditions encode top-layer GPS in the typical-episode window; in rich-encoder conditions the code is then no longer linearly readable in the long-tail (negative R^2 in the 800+ step bin), while bottleneck conditions hold it stable to step 800+. The Table 1 “rich-encoder $\approx$ chance” headline is therefore long-tail behaviour, not mid-episode. *H1 is most precisely a temporal-stability claim about the linearly-decodable top-layer GPS code.* A lag- k probe corroborates: blind GPS decodes at $R^2 = 0.92$ at $k = 20$, matched > 0.5 ; rich-encoder conditions are at chance for every $k \leq 10$. *All numerical claims in this section are single-seed; multi-seed replication of all five conditions is in flight and would tighten the H1 ordering and the long-tail decay characterisation.*

Layer specificity and non-linear probe. All five conditions have GPS at LSTM Layer 0 because the GPS-sensor embedding enters there (Figure 2c). The H1 distinction is what happens through Layers 1–2: bottleneck retain to Layer 2, rich-encoder discard. Since the DD-PPO action head is a linear projection from $\mathbf{h}_2$, this maps to “policy-accessible”. A 2-layer MLP on the same top-layer states recovers GPS for rich-encoder conditions ($R^2 \in [0.51, 0.73]$); H1 is therefore precisely about *linear* top-layer decodability, not whether *any* probe can recover position. The MLP result alone cannot exclude exploitation of position-correlated features (wall distance, scene identifiers); Appendix B discusses both. The bottleneck-vs-pass-through partition is preserved on held-out MP3D (Figure 2a); two single-seed cross-dataset shifts (foveated GPS chance $\rightarrow +0.35$; foveated-learned compass $-1.34 \rightarrow +0.41$) await multi-seed replication.

Proposed mechanism We *propose* the following account, consistent with the data but not directly tested by a causal intervention. In PointNav, GPS and compass enter the LSTM input at Layer 0 directly, via a 32-d sensor embedding concatenated with the visual encoder’s flattened output (Figure 2c shows GPS at Layer 0 across all five conditions, $R^2 > 0.91$). The encoder feature-map




Figure 2: H1 evidence in four panels. (a) Top-layer GPS R^2 (5-fold CV, deterministic rollouts) on Gibson and held-out MP3D (300 episodes/condition). Blind and matched-compute (bottleneck) decode world-frame GPS on both datasets; uniform / foveated / foveated-learned (rich-encoder) do not, except foveated recovering on MP3D. (b) Top-layer GPS R^2 binned by step-in-episode: all five conditions encode top-layer GPS in the typical window (steps ~ 25 –200); the code becomes no longer linearly readable in the rich-encoder long-tail (negative R^2 in the 800+ step bin), while bottleneck conditions hold $R^2 > 0.7$ to step 800+. The headline in (a) is therefore primarily long-tail behaviour. (c) Per-LSTM-layer GPS R^2 : all five conditions have GPS at Layer 0 (the GPS sensor embedding enters the LSTM input vector here — a sensor pass-through, not the network “computing” position); divergence is at Layer 2, the policy readout. (d) Encoder feature-map probe (grey bars; post-ResNet-18, pre-LSTM) vs LSTM top-layer probe (coloured bars). Blind and fov-learned have no encoder probe (no encoder / no encoder-probe data resp.). The grey bars sit near or below zero everywhere, so *no sighted encoder linearly carries GPS*; the coloured-grey gap is the “LSTM gain”. Matched gains ~ 3.9 , uniform ~ 0 , foveated ~ 0.7 .

probe (§4.4, Figure 2d) shows that none of the three sighted encoders linearly re-derive GPS from their visual stream: matched $R^2 = -3.14$, uniform -0.32 , foveated -0.65 . The encoder–memory race is therefore not about whether the encoder *re-derives* position; it is about how much *visual feature variety* the encoder hands to the LSTM, and whether that variety is enough to substitute for integrating the Layer-0 GPS-sensor signal across time. Bottleneck conditions (blind, no encoder; matched-compute, 1×1 spatial output $\rightarrow$ minimal feature variety per step) leave the LSTM with little visual structure to substitute, so it integrates the Layer-0 GPS signal across time and *maintains* a top-layer linearly-readable GPS code. Rich-encoder conditions (uniform / foveated / foveated-learned, 8×8 spatial output $\rightarrow$ many position-correlated visual features) give the LSTM enough visual variety to base actions on those features instead, and the top-layer GPS code drifts off as the episode progresses. Task success is tightly bunched, so a skill-gap artefact is unlikely to explain the encoding gap. The temporal dynamic in Figure 2b (rich-encoder GPS code emerging early at Layer 0 then decaying through Layers 1–2 to chance at the top layer) is the direct fingerprint of this account. **[TODO: A direct causal test of the mechanism — ablating the visual stream mid-rollout in rich-encoder agents to see whether the top-layer GPS code re-emerges, or perturbing the GPS sensor input mid-rollout in bottleneck agents to see whether SPL collapses — is left for future work.]**

Relation to Wijmans et al. [Wijmans et al., 2023]. They showed blind agents develop spatial representations; our blind result ($R^2 = 0.95$) replicates this and matched-compute extends it to a condition that has visual input but 1×1 spatial encoder output. The shared trigger is therefore minimal

visual-feature variety per step, not absence of vision. The parallel to animal-navigation findings is treated separately as convergent (not mechanistic) evidence in §5.2.

4.3 Format-level divergence across conditions (H2)




Figure 3: H2 convergent evidence, two views. *Left*: cross-condition probe transfer for GPS R^2 (train probe on row, test on column; signed-log colour scale). The diagonal is +0.89+0.99 (self-probe), every off-diagonal predicts off-manifold ($R^2 \ll -800$, often $\ll -10^4$). *Right*: 5x5 cross-condition memory-transplant matrix at midpoint $t=30$. Cells off-diagonal: cross-transplant SPL minus recipient’s self-transplant SPL (isolated condition-mismatch effect). Cells with “—” (matched as recipient): not yet measured. Both heatmaps are asymmetric: bottleneck-donor states hurt rich-encoder recipients far more than the reverse, and probes trained on bottleneck states fail catastrophically on rich-encoder hidden states. A midpoint-sweep companion across $\{0, 15, 30, 60, 90\}$ is in Appendix D.

Behavioural test (memory transplant) The most direct test of “do these representations matter?” is to paste a donor’s mid-episode hidden state into a recipient’s policy at step 30 and let the recipient drive the rest (Figure 3, right). The isolated condition-mismatch cost shows three patterns. *Asymmetry*. Blind→uniform incurs -0.38 SPL while uniform→blind is neutral within self-noise; bottleneck-donor states hurt rich-encoder recipients far more than the reverse. *Recipient ranking*. Uniform suffers most from *any* foreign donor (column mean ~ -0.20); blind least (~ -0.02 to -0.05). *Linear-similarity blind spot*. Pairs that are indistinguishable under unaligned linear CKA [Kornblith et al., 2019] ($< 10^{-4}$ across all off-diagonals; supplementary Figure 7) differ by 0.01–0.38 SPL under transplant. **[TODO: 4 matched-recipient cells are queued; asymmetry will be tested for completeness on landing.]**

Convergent linear-similarity evidence. Cross-condition probe transfer (Figure 3, left) is catastrophically negative in every off-diagonal cell, with the same asymmetric pattern: probes trained on bottleneck states predict off-manifold by a wider margin on rich-encoder hidden states than the reverse. 1-NN purity among 1500×5 pooled top-layer states is 1.000 (chance 0.20); t-SNE projection in Appendix D confirms visually. CKA at the noise floor (split-half within-condition CKA ≈ 1 rules out estimator noise) is consistent with everything else but the least informative on its own — transplant and probe-transfer carry the same asymmetric structure that CKA cannot read.

Ruling out alternatives. Probe capacity is not the bottleneck (self-probes succeed everywhere); sample-size asymmetry is ruled out by common-sample truncation; task competence is bunched (96–99%), so the divergence is not a skill difference; probe transfer fails symmetrically, ruling out one condition’s code simply embedding another’s.

Boundaries. Our similarity tests are linear or near-linear; non-linear measures could reveal higher-order shared structure. Our five sensors are diverse but not exhaustive; hybrid sensors (sharp fovea + coarse periphery, depth-only) might produce intermediate geometries.

4.4 Foveation: convergence on H1, divergence on H2 + behaviour

Foveated-fixed and uniform fall in the same rich-encoder pass-through regime on the headline H1 metric (top-layer GPS R^2 at chance), but they are not interchangeable on H2 / behavioural / dataset-shift axes (Table 2). The take-away: *within the rich-encoder regime defined by H1, foveation and uniform produce internally distinct representations whose differences only the H2-and-beyond machinery makes visible.*

Table 2: Foveation vs. uniform at $\sigma_{\max} = 8$ Gaussian blur with the same ResNet-18 encoder. Same on H1, different on H2 / behavioural / generalisation. Sources: Table 1, Figure 3, Figure 4, Figure 2d. Data are deterministic-rollout single-seed.

Measure	Foveated (fix)	Uniform	Verdict
LSTM GPS R^2 (Gibson)	$+0.06 \pm 0.88$	-0.31 ± 0.86	both chance, <i>indistinguishable</i>
Encoder $\rightarrow$ GPS R^2	-0.65 ± 0.28	-0.32 ± 0.08	both negative, overlapping
LSTM compass R^2 (Gibson)	$+0.07 \pm 0.69$	$+0.36 \pm 0.23$	uniform $\sim 5\times$ better
LSTM GPS R^2 (MP3D, held out)	$+0.35 \pm 0.27$	-0.36 ± 1.38	differ by 0.71
Shortcut SPL drop %	21%	41%	uniform $2\times$ more brittle
Memory-transplant cost (fov $\rightarrow$ uni)	-0.10 SPL beyond self-noise		not interchangeable
Pairwise CKA(fov, uni)	$< 10^{-4}$		near-orthogonal subspaces
1-NN purity (pooled)	1.000 vs. chance 0.20		linearly separable

Four in-flight experiments target specific predictions of the encoder-memory race within the foveation slot (designs in Appendix G). One result has landed and is pivotal: probing the visual encoder’s output directly (post ResNet-18, pre-LSTM) shows that *none of the three sighted encoders linearly decode GPS* (Figure 2d, grey bars). *This sharpens the H1 phenomenon*: the divergence between bottleneck and rich-encoder LSTMs is not explained by encoder-level GPS retention. The “LSTM gain” — the gap between LSTM and encoder bars in Figure 2d — orders the conditions: matched ~ 3.9 , foveated ~ 0.7 , uniform ~ 0 . We *interpret* this gradient as the LSTM increasingly relying on visual features over the integrated GPS-sensor signal as encoder spatial-feature variety grows; this interpretation is consistent with the data but is not directly tested by a causal intervention (the resolution scaling sweep in Appendix H would). All “LSTM gain” numbers are single-seed.

Provisional conclusion. Foveation under $\sigma_{\max} = 8$ Gaussian blur is *not a copy of uniform*: it converges on H1 but diverges on H2 / behaviour / dataset-shift (Table 2). The encoder feature-map probe further shows the encoder discards linear GPS regardless of condition, so *whatever foveation does differently from uniform, it does so inside the LSTM in subspaces invisible to a linear-GPS probe*. The four in-flight experiments (Appendix G) test *what* that “something different” is. F3 log-polar in particular has a falsifiable prediction: log-polar’s $\sim 2\times 2$ encoder spatial output should produce LSTM GPS $R^2 \geq 0.3$ (between matched’s $+0.78$ and uniform’s ≈ 0); if instead it matches uniform, the encoder-spatial-output mechanism would need reframing. The foveation-vs-uniform contrasts in Table 2 are also single-seed and await multi-seed replication.

4.5 Probe-readable vs. policy-used memory: a 2×2 dissociation

H1 (§4.2) measures what is *readable* from the recurrent state. The shortcut-discovery experiment measures what the policy actually *relies on*: in paired same-scene/different-goal episodes (20 scenes $\times$ 10 pairs), the second-episode SPL drop under persistent vs. reset memory indexes how tightly the policy couples actions to integrated recurrent memory (blind loses 52%, uniform 41%, foveated 21%, matched 18%, foveated-learned 15%). Plotting probe-readable GPS against this behavioural reliance shows the five conditions in a 2×2 pattern (Figure 4) with two off-diagonal points: matched-compute has a linear top-layer GPS code yet its policy weights it less than the H1 reading would predict, while uniform has no linear GPS but relies heavily on memory — plausibly via non-spatial scene-history features. We label these as *candidate* dissociations rather than established anomalies: the 5 points are single-seed, and confirming that “probe-readable” and “policy-relied-on” truly dissociate (rather than the off-diagonal points sitting within seed-to-seed noise) requires the multi-seed replication that is in flight.

A trajectory-level look at *how* persistent-memory failures manifest is consistent with the dissociation (Figure 5). Aggregating across all same-floor paired-episode failures (Figure 5, right panel): uniform




Figure 4: Probe-readable GPS (H1) vs. behavioural memory reliance (shortcut). The five conditions occupy four corners of a 2×2 : blind “has GPS, uses memory” (consistent with H1); foveated-fixed and foveated-learned “no linear GPS, low memory reliance” (also consistent with H1); **matched** and **uniform** are the two off-diagonal anomalies. Fov-learned’s $R^2 = -2.43$ is clipped at -1.5 .

is the only condition with a meaningful sample size whose persistent agent ends up closer to the previous-episode goal than the new one (margin $+1.83\text{m}$ on $n=46$); blind / matched / foveated all end nearer the new goal but never reach it. Foveated-learned shares uniform’s positive-margin direction at $+2.30\text{m}$ but $n=5$ is too small to interpret. *If* the uniform pattern survives multi-seed replication, it is consistent with the 2×2 : uniform’s memory would then plausibly act as a visual / scene-history anchor that locks the agent in place, whereas blind’s GPS code would interfere via a different channel (the recurrent state mis-reporting current position to the policy’s goal-direction integrator). The locking interpretation is single-seed and we do not claim it has been established; multi-seed replication is in flight.

4.6 Gaze location (H3, in progress)

H3 asks whether gaze *location* acts as a second representational-content axis within the rich-encoder regime. Our minimal learned-gaze module (deterministic sigmoid MLP, slow updates per 128-step segment) freezes at $(0.49, 0.62)$ with per-dimension std $\leq 2.5 \times 10^{-4}$ after 250M frames; anti-collapse regularisers restore variance only at task-cost (Appendix E). The collapse is not evidence about active gaze in general — the decoder is minimal by design — but it provides an empirical anchor for the gaze-location test: a foveated-shifted control with gaze hardcoded at $(0.49, 0.62)$ instead of $(0.5, 0.5)$, identical to foveated-fixed in every other respect, isolates static gaze location from the optimisation-path interaction that produced the collapsed gaze. Training is in progress at submission.

4.7 Boundaries

Three probes that do *not* discriminate define the boundary of our claims. Coarse occupancy decodes above chance everywhere; metric 20×20 occupancy fails everywhere (consistent with [Ramakrishnan et al., 2025] that high-resolution metric layout needs non-linear probes); the ego-frame goal vector is at chance everywhere because PointGoal supplies it as a per-step input. Population coding (Appendix D) sharpens H1 in a direction we did not expect: rich-encoder conditions have a few units with *higher* peak spatial information than blind, but those peaked units do not decode GPS — suggesting they encode features merely correlated with position (visual landmarks, trajectory phase). Blind’s broader, lower-peak distribution carries the actual linear position code.




Figure 5: *Persistent-memory failure modes (one paired-episode case per condition + aggregate)*. The first three panels show *Blind* (persistent agent attempts the new goal, loops, gives up at 443 steps), *Uniform* (persistent agent stays at the old-goal location for the full 2000-step cap), and *Foveated* (persistent agent loops chaotically, reaches neither goal). Right panel: per-condition margin = (avg distance to old goal) – (avg distance to new goal) over all same-floor failures (reset SPL > 0.5, persistent SPL < 0.2, persistent steps ≥ 30 , $|\Delta y_{\text{goal}}| < 0.5\text{m}$). Uniform shows a positive margin at meaningful $n=46$ (closer to the old goal); fov-learned shows the same direction at +2.30m but $n=5$ is too small to interpret. Single-seed; multi-seed replication is in flight.

5 Discussion

5.1 Two orthogonal axes: sensor structure and gaze location

Our findings unify under a candidate account we call the *encoder-memory race*: top-layer linear GPS encoding in the LSTM is *maintained* when the encoder hands the LSTM minimal spatial-feature variety per step (blind, matched-compute), and *is no longer linearly readable* in conditions where richer visual features are available (uniform, foveated, foveated-learned). The encoder feature-map probe (§4.4) shows that no sighted encoder linearly re-derives GPS, so the H1 phenomenon is not explained by encoder-level position retention; we *interpret* it as the LSTM trading off integrating its Layer-0 GPS-sensor signal across time against using the richer visual features the encoder supplies. H2 (§4.3) cuts orthogonally: *what* the LSTM encodes lives in distinct linear subspaces across conditions, and the difference matters for behaviour (cross-condition memory transplants drop SPL beyond transplant-mechanics noise; the 5×5 matrix is asymmetric, with 4 matched-recipient cells still pending). H3 (§4.6) asks whether, within the rich-encoder pass-through regime, gaze location is a second content axis; the foveated-shifted causal control is in training. We present the unifying account as a candidate, not a proven mechanism: a direct causal test (e.g. ablating the visual stream

mid-rollout in rich-encoder agents to see whether the top-layer GPS code re-emerges) is left for follow-up.

5.2 Biological precedent: sensor structure shapes hippocampal representation

The principle that sensor structure constrains spatial-memory format is not one we propose; biological evidence for it predates ours by decades. Our contribution is to isolate the principle in a controlled silicon model where the encoder, memory, policy, training distribution and reward are held fixed and only the visual sensor varies. Three threads of animal-navigation research are particularly close to the three findings.

H1 (sensor bottleneck $\rightarrow$ memory takes over). Congenitally blind humans show enhanced occipital-hippocampal coupling during spatial tasks [Kupers and Ptito, 2014], consistent with hippocampus carrying more navigational load when the visual stream is absent. Rodent grid-cell periodicity collapses under prolonged darkness while the animal still navigates [Chen et al., 2016], indicating spatial behaviour can be sustained when the visual landmark stream is removed. Both are biological analogs of our blind / matched-compute regime, where the LSTM — deprived of rich visual variety per step — retains a linear top-layer GPS code that is no longer linearly readable in the rich-encoder conditions.

H2 (different sensors $\rightarrow$ different spatial codes). The primate vs. rodent contrast in hippocampal cell types — view-cells dominant in primates, place-cells dominant in rodents — has been attributed in part to the foveated-with-saccades vs. near-panoramic visual sampling regime each species uses [Rolls, 2024]. Cross-modality remapping in echolocating bats, where the same neurons recode under vision vs. echolocation [Geva-Sagiv et al., 2016], demonstrates that sensor modality alters the linear subspace of hippocampal coding. Both parallel our H2 finding: the same task with different visual structure yields linearly separable LSTM subspaces ($\text{CKA} < 10^{-4}$, probe-transfer collapse, asymmetric memory transplant).

H3 (gaze location modulates memory encoding). In primates, hippocampal theta is gated by saccades, and the reliability of this saccade-gated signal predicts memory encoding success [Jutras et al., 2013, Tas et al., 2016]. Where the eye points is therefore not memory-neutral. Whether the analogous prediction holds for an LSTM gaze module is what §4.6 is testing (foveated-shifted causal control in training).

We treat these as convergent (not conclusive) evidence. Convergence across systems — and across silicon vs. neural — is suggestive of a sensor-memory coupling principle more general than any single architecture, but it does not show that the mechanisms are the same. Our experiments isolate the principle in a controlled, single-architecture setting; biological work establishes that the principle exists in animals at all. The two are complementary; neither is decisive alone.

5.3 Why this, not alternative accounts

Four alternative explanations are ruled out: skill difference (success bunched 93–99%), probe capacity (DtG decodes everywhere), sample-size or stochastic-sampling artefacts (Appendix A), and linear-probe artefact (memory transplant reproduces the ordering outside the probe framework; MLP probe shows the divergence is specific to *linear* top-layer decodability, which is what the linear DD-PPO action head reads). Full rebuttals in Appendix C.

5.4 Implications and scope

If the encoder-memory race is causal — the resolution scaling sweep (Appendix H) tests this — encoder capacity becomes a practical training-time lever for inducing cognitive-map-like representations. The relevant axis is not pixel count: matched-compute’s 48^2 input with a 1×1 feature map has a strong linear top-layer GPS code while uniform’s 256^2 does not; we attribute the pattern to encoder spatial-feature *variety* per step. Outside the recurrent setting we test, H3 suggests a prediction for transformer navigators: if learned attention selects observation content the way our gaze module does, strong constraints on attended tokens should produce content-level dissociations analogous to ours. Whether sensor-memory coupling extends to supervised visual learners, non-visual modalities, or multimodal systems is open.

5.5 Limitations

(i) *Single seed* for the H1 numbers; multi-seed replication is in progress and gates the headline claims. (ii) *Foveated-fixed checkpoint* is ckpt.36 ($\sim 174\text{M}$ frames, last clean before a silent NaN-gradient corruption; Appendix F); the other four conditions use the final converged checkpoint. (iii) *Learned-gaze module* is a minimal deterministic sigmoid MLP that collapsed under pure task supervision; the H3 test (foveated-shifted control) does not depend on this module working. Richer gaze mechanisms (stochastic gaze, intrinsic-reward gaze, attention-based selection) are out of scope. (iv) *Foveation model*: $\sigma_{\max} = 8$ Gaussian blur is a simplification; a log-polar control and an $\sigma_{\max} \in \{2, 4, 12, 20\}$ strength sweep are in training (Appendix G). (v) *Linear probes only*: non-linear probes might reveal structure Ridge misses (a 2-layer MLP partially recovers GPS in rich-encoder conditions; Appendix B).

6 Conclusion

A controlled five-condition ablation, with the visual pathway as the only varied component, suggests sensor structure as a representational-content axis in recurrent navigation agents: the encoder–memory race (H1), condition-specific representational format (H2), and a candidate probe-readable-vs.–policy-used dissociation at the $\text{H1} \times \text{shortcut}$ intersection. The H1 ordering reproduces on held-out MP3D, and the pattern parallels independent animal-navigation findings on hippocampal compensation under sensory deprivation and cross-modality remapping. The cross-condition observations are single-seed; multi-seed replication is in flight and gates the strength of every quantitative claim. Pending experiments that would tighten or falsify the account: a finer-grained encoder-resolution scaling sweep (Appendix H) for causal H1; the foveated-shifted control for H3; the four matched-recipient transplant cells; the foveation strength sweep and log-polar control. Out of scope here: whether the principle extends to transformer navigators, supervised visual learners, or non-navigation tasks.

References

- Andrei Atanov, Yicheng Fu, Gaurav Singh, Jianren Yu, Andrew Spielberg, and Amir Zamir. How far can a 1-pixel camera go? solving vision tasks using photoreceptors and computationally designed visual morphology. In *European Conference on Computer Vision (ECCV)*, 2024.
- Andrea Banino, Caswell Barry, Benigno Uria, Charles Blundell, Timothy Lillicrap, Piotr Mirowski, Alexander Pritzel, Martin J Chadwick, Thomas Degris, Joseph Modayil, et al. Vector-based navigation using grid-like representations in artificial agents. *Nature*, 557(7705):429–433, 2018.
- Yonatan Belinkov. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219, 2022.
- Guifen Chen, John A. King, Neil Burgess, and John O’Keefe. Absence of visual input results in the disruption of grid cell firing in the mouse. *Current Biology*, 26(17):2335–2342, 2016.
- Christopher J Cueva and Xue-Xin Wei. Emergence of grid-like representations by training recurrent neural networks to perform spatial localization. In *International Conference on Learning Representations (ICLR)*, 2018.
- Kshitij Dwivedi, Gemma Roig, Aniruddha Kembhavi, and Roozbeh Mottaghi. What do navigation agents learn about their environment? In *Computer Vision and Pattern Recognition (CVPR)*, 2022.
- Maya Geva-Sagiv, Sandro Romani, Liora Las, and Nachum Ulanovsky. Hippocampal global remapping for different sensory modalities in flying bats. *Nature Neuroscience*, 19(7):952–958, 2016.
- James Gornet and Matt Thomson. Automated construction of cognitive maps with visual predictive coding. *Nature Machine Intelligence*, 6:820–833, 2024.
- Jay A Hennig, Sandra A Romero Pinto, Takahiro Yamaguchi, Scott W Linderman, Naoshige Uchida, and Samuel J Gershman. Emergence of belief-like representations through reinforcement learning. *PLOS Computational Biology*, 19(9):e1011067, 2023.
- John Hewitt and Percy Liang. Designing and interpreting probes with control tasks. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

- Michael J. Jutras, Pascal Fries, and Elizabeth A. Buffalo. Oscillatory activity in the monkey hippocampus during visual exploration and memory formation. *Proceedings of the National Academy of Sciences*, 110(32):13144–13149, 2013.
- Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International Conference on Machine Learning (ICML)*, 2019.
- Ron Kupers and Maurice Ptito. Compensatory plasticity and cross-modal reorganization following early visual deprivation. *Neuroscience & Biobehavioral Reviews*, 41:36–52, 2014.
- Volodymyr Mnih, Nicolas Heess, Alex Graves, and Koray Kavukcuoglu. Recurrent models of visual attention. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2014.
- Motahareh Pourrahimi and Pouya Bashivan. Emergent brain-like representations in a goal-directed neural network model of visual search. *bioRxiv preprint*, 2025.
- Santhosh Kumar Ramakrishnan, Erik Wijmans, Philipp Krähenbühl, and Vladlen Koltun. Does spatial cognition emerge in frontier models? In *International Conference on Learning Representations (ICLR)*, 2025.
- Edmund T. Rolls. Why do primates have view cells instead of place cells? *Trends in Cognitive Sciences*, 28(9):862–874, 2024.
- Ruth Rosenholtz. Capabilities and limitations of peripheral vision. *Annual Review of Vision Science*, 2:437–457, 2016.
- Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, Dhruv Batra, and Devi Parikh. Habitat: A platform for embodied AI research. In *International Conference on Computer Vision (ICCV)*, 2019.
- Jinghuan Shang and Michael S. Ryoo. Active vision reinforcement learning under limited visual observability. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.
- Nathan Sprague and Dana H. Ballard. Eye movements for reward maximization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2003.
- Hans Strasburger, Ingo Rentschler, and Martin Jüttner. Peripheral vision and pattern recognition: A review. *Journal of Vision*, 11(5):13, 2011.
- Amanda C. Tas, Steven J. Luck, and Andrew Hollingworth. The role of attention in the encoding of visual working memory. *Journal of Experimental Psychology: Human Perception and Performance*, 42(8):1121–1138, 2016.
- Erik Wijmans, Abhishek Kadian, Ari Morcos, Stefan Lee, Irfan Essa, Devi Parikh, Dhruv Batra, and Manolis Savva. DD-PPO: Learning near-perfect pointgoal navigators from 2.5 billion frames. In *International Conference on Learning Representations (ICLR)*, 2020.
- Erik Wijmans, Manolis Savva, Irfan Essa, Stefan Lee, Ari Morcos, and Dhruv Batra. Emergence of maps in the memories of blind navigation agents. In *International Conference on Learning Representations (ICLR)*, 2023.
- Sylvia Wirth, Pierre Baraduc, Angélique Planté, Serge Pinede, and Jean-René Duhamel. Gaze-informed, task-situated representation of space in primate hippocampus during virtual navigation. *PLOS Biology*, 15(2):e2001045, 2017.
- Fei Xia, Amir R Zamir, Zhiyang He, Alexander Sax, Jitendra Malik, and Silvio Savarese. Gibson Env: Real-world perception for embodied agents. In *Computer Vision and Pattern Recognition (CVPR)*, 2018.

NeurIPS Paper Checklist

The checklist is designed to encourage best practices for responsible machine learning research, addressing issues of reproducibility, transparency, research ethics, and societal impact. Do not remove the checklist: **The papers not including the checklist will be desk rejected.** The checklist should follow the references and follow the (optional) supplemental material. The checklist does NOT count towards the page limit.

Please read the checklist guidelines carefully for information on how to answer these questions. For each question in the checklist:

- You should answer [Yes], [No], or [N/A].
- [N/A] means either that the question is Not Applicable for that particular paper or the relevant information is Not Available.
- Please provide a short (1–2 sentence) justification right after your answer (even for [N/A]).

The checklist answers are an integral part of your paper submission. They are visible to the reviewers, area chairs, senior area chairs, and ethics reviewers. You will also be asked to include it (after eventual revisions) with the final version of your paper, and its final version will be published with the paper.

The reviewers of your paper will be asked to use the checklist as one of the factors in their evaluation. While [Yes] is generally preferable to [No], it is perfectly acceptable to answer [No] provided a proper justification is given (e.g., error bars are not reported because it would be too computationally expensive” or “we were unable to find the license for the dataset we used”). In general, answering [No] or [N/A] is not grounds for rejection. While the questions are phrased in a binary way, we acknowledge that the true answer is often more nuanced, so please just use your best judgment and write a justification to elaborate. All supporting evidence can appear either in the main paper or the supplemental material, provided in appendix. If you answer [Yes] to a question, in the justification please point to the section(s) where related material for the question can be found.

IMPORTANT, please:

- **Delete this instruction block, but keep the section heading “NeurIPS Paper Checklist”.**
- **Keep the checklist subsection headings, questions/answers and guidelines below.**
- **Do not modify the questions and only use the provided macros for your answers.**

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer:
answerYes

Justification: The abstract and §1 state the three hypotheses H1/H2/H3 with explicit signatures (what pattern supports each), and preview the three findings with specific magnitudes (path-history $R^2=0.56$, CKA <0.004 , compass $R^2=0.94$ vs GPS $R^2=0.03$). These are expanded in §4 and §5 with no stronger claims than the data support.

Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer:

answerYes

Justification: §5.4 explicitly lists six limitations (i–vi) covering checkpoint staleness, single-seed H3, missing proposed analyses, foveation-model simplification, linear-probes-only, and LSTM-architecture scope.

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren’t acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer:

answerNA

Justification: The paper reports empirical results; it contains no theoretical claims or proofs.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer:
answerYes

Justification: §3.1 describes the architecture (3-layer LSTM, 512-d, Wijmans non-visual sensor stack, ResNet-18 encoder) and training setup (DD-PPO on Gibson-0+ $\cup$ MP3D-train, 250M-frame targets). §3.2–§3.6 describe all probing and cross-condition protocols. Appendix A details the gaze-diversity ablation. Code will be released upon publication.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer:
answerYes

Justification: §3.7 commits to open-source release of the training and probing code. Datasets (Gibson, Matterport3D) are standard public academic-research benchmarks; we describe our train/eval splits in §3.1.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).

- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer:

answerYes

Justification: §3.1 specifies training pool and eval set; §3.3 specifies probe hyperparameters (Ridge $\alpha = 10$, episode-level splits, Hewitt–Liang control). Appendix A gives the ablation’s loss formulation and coefficient.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer:

answerNo

Justification: We report single-seed numbers per condition. This is documented as Limitation (ii) in §5.4. Multi-seed replication for tighter confidence intervals is in the immediate follow-up.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).

- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer:

answerYes

Justification: §3.7 reports per-condition training budget (5–7 days on 2×V100 for 250M frames) and probing budget (<1h per condition on one V100).

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer:

answerYes

Justification: The research uses public academic-research benchmarks, publicly-released open-source RL frameworks, and involves no human subjects or deployment. We also report and remediate a numerical-stability bug upstream (Appendix B).

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer:

answerYes

Justification: §5.3 discusses implications — sensor design as a tunable axis for interpretable embodied agents. Negative societal impacts are minimal: the work is fundamental research on simulated indoor navigation with no direct deployment pathway.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.

- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer:

answerNA

Justification: We release neither a high-risk dataset nor a generative model. Our contribution is a small set of trained RL policies on simulated indoor scenes, which pose no identifiable misuse risk.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer:

answerYes

Justification: Gibson Database and Matterport3D are used under their released academic-research licenses; Habitat-Sim and habitat-lab are MIT-licensed. Our use complies with their terms; citations §3.1.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.

- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer:

answerYes

Justification: Code will be released with documentation upon publication. Figures are novel; they are released under the paper's license alongside the code. The gaze-diversity auxiliary loss and NaN-sanitisation patch are small standalone modules with docstrings.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer:

answerNA

Justification: The paper involves no crowdsourcing and no human-subjects data.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer:

answerNA

Justification: No human-subjects research; no IRB/equivalent review was required.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer:

answerNA

Justification: LLMs were used only for writing assistance on the manuscript. They are not part of the core research methodology; all empirical results come from standard RL training and linear probing.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.

A Probing protocol details

Sampling protocol An earlier draft used stochastic (policy-distribution) action selection at probe time. Conditions with higher action-entropy under their trained stochastic policies sampled the STOP action early with ~ 0.25 per-step probability, producing ~ 4 -step rollouts and target variance two orders of magnitude below the episodic range. The resulting probe R^2 values were trivially high across all conditions (any predictor fits a near-constant target). This confounded cross-condition comparisons; we switched to the deterministic (argmax) protocol used here and elsewhere in our pipeline. All paper results use the deterministic protocol.

Length-matching ablation. Under deterministic rollouts, episode lengths span ~ 100 – 400 mean steps depending on condition. We use 5-fold episode-level CV to keep splits balanced per scene rather than length-matching across conditions. **[TODO: A controlled length-matching ablation (truncate every condition to a common length) is left for follow-up; we expect it to leave the H1 ordering unchanged because the bottleneck conditions decode at high R^2 even at the smallest sub-sample, but have not verified.]**

Cross-heading probe. The proposal included a cross-heading generalisation probe (train on heading A , test on opposite heading). Our implementation returned “insufficient samples” sentinels at our probe sizes; not in our results.

B Probing details (Layer 0 sensor branch and MLP probe)

LSTM Layer 0 sensor branch. The non-visual sensor stack (goal-in-start-frame, GPS, compass, close-to-goal scalar, prev-action) projects each sensor to 32-d, concatenates them with the visual encoder’s flattened output, and feeds the result as the LSTM’s Layer 0 input. The GPS embedding therefore enters the LSTM via this concatenation; this explains why Figure 2c shows linearly-decodable GPS at Layer 0 even for conditions whose visual encoder discards GPS entirely.

MLP probe details. For each condition we fit a 2-layer MLP (hidden dim 256, ReLU, L_2 weight decay 10^{-4}) on the same top-layer hidden states + GPS labels as the linear Ridge probe, with the same 5-fold episode-level CV. Top-layer recovery: foveated $R^2 = 0.51$, foveated-learned 0.73, uniform 0.55 (vs. Ridge’s chance R^2). The MLP probe alone cannot disentangle “non-linear position code” from “MLP regressing through position-correlated features (wall distance, scene identifiers, episode-phase markers)”; the resolution scaling sweep (Appendix H) tests this more directly by varying input resolution at fixed encoder stack.

C Alternative-account rebuttals (full)

Task-competence differences. All conditions solve PointGoal at 93–99% success (Table 1); the encoded-content gap cannot be attributed to navigation skill.

Probe-capacity / probe-fitting artefacts. DtG decodes robustly across all five conditions ($R^2 \geq 0.81$), demonstrating Ridge has the capacity to fit high- R^2 scalars when the hidden state contains them. Hewitt–Liang label-permutation selectivity is high where GPS is high (blind, matched) and at chance where GPS is at chance — the latter follows from real and control probes facing the same near-zero target-information ceiling. The chance-level rich-encoder R^2 is therefore a hidden-state property, not a probe artefact.

Sample-size / trajectory-distribution artefacts. CV σ spans come from the same 500-episode pool with ~ 100 – 400 -step rollouts under identical deterministic evaluation; the protocol confound that haunted an earlier draft is documented and retired in Appendix A.

Linear-probe artefacts. Two complementary checks. (a) *Behavioural*: the memory-transplant intervention goes outside the probe framework and reproduces the bottleneck-vs-pass-through ordering; the 5×5 matrix’s asymmetry adds a structure no linear-similarity measure can read. (b) *Non-linear probe*: a 2-layer MLP recovers $R^2 \in [0.51, 0.73]$ from rich-encoder top-layer states (Appendix B). The bottleneck-vs-pass-through divergence is therefore not about whether *any* probe can recover position; it is specifically about whether a *linear* top-layer probe can. Since the DD-PPO action head is a linear projection from $\mathbf{h}_2$, the linear metric is what the policy itself can use, so H1 maps onto policy-accessible encoding regardless of how the MLP interpretation resolves.

D Supplementary visualisations




Figure 6: Supplementary visualisations referenced from the main text.




Figure 7: Unaligned linear CKA [Kornblith et al., 2019] between top-layer LSTM hidden states ($n=95,640$ steps per condition under deterministic-rollout probes); every off-diagonal is below 10^{-4} . Within-condition split-half CKA ≈ 1 confirms the near-zero off-diagonals are not estimator noise. Pairs that look identical here differ markedly under transplant and probe-transfer (Figure 3); CKA is the least informative of the three H2 measures because it cannot read the asymmetric structure that transplant and probe-transfer show.

E Gaze-Diversity Auxiliary Loss (H3 Ablation)

Motivation. In the first foveated-learned training run the gaze decoder collapsed (per-dimension std $\approx 5 \times 10^{-4}$). We attribute this to two mechanisms: (i) once the sigmoid output saturates, its derivative $\sigma'(x) \rightarrow 0$ attenuates gradient signal; (ii) consistent-gaze views yield more predictable visual features, so the reward-gradient path has no explicit incentive for variety.

Target-variance hinge. We add $\mathcal{L}_{\text{div}} = \lambda \cdot \text{relu}(\sigma_{\text{target}}^2 - \text{Var}_{\text{batch}}[g])$ where $g \in [0, 1]^2$, $\text{Var}_{\text{batch}}$ averaged over the two gaze dimensions, $\sigma_{\text{target}}^2 = 0.01$ (std ≈ 0.1), $\lambda = 0.01$. The hinge disappears once variance exceeds the target. We also evaluated an un-capped $-\lambda \cdot \text{Var}[g]$ variant as a negative control.




Figure 8: Memory-transplant midpoint sweep on three representative donor→recipient pairs (foveated→uniform, foveated→blind, foveated-learned→foveated) across midpoints $\{0, 15, 30, 60, 90\}$ time-steps ($n=100\text{--}150$ episodes/cell). The full 5×5 matrix in Figure 3 (right) is at midpoint $t=30$; this supplementary figure shows that the cross-self gap is roughly stable for $t \geq 15$ and that the $t=0$ self-/cross- baseline collapses to a protocol-noise floor (so the diagonal in Figure 3 is correctly read as “rollout-divergence noise” rather than “condition-mismatch noise”). Foveated-learned→foveated incurs -0.17 SPL on average across $t \geq 15$, foveated→uniform -0.10 , foveated→blind -0.02 , consistent with the asymmetry pattern in the full matrix.




Figure 9: Population coding analysis (referenced from §4.7). (a) Per-unit spatial-information distribution: each curve is one condition’s units sorted by spatial information (descending), x-axis log scale. Counter-intuitively, rich-encoder conditions (uniform / foveated / fov-learned) have a few more peaked spatially-tuned units (max ≈ 2 bits) than bottleneck conditions; blind has the flattest distribution (max ≈ 1 bit, no unit reaches the dashed 1-bit threshold). (b) Sparse-vs-distributed GPS decoding: probe R^2 when only the top- k spatial-info units are used as features. Blind reaches $R^2 \approx 1.0$ at $k = 512$; matched climbs to $R^2 \approx 0.5$; rich-encoder networks fail to decode GPS at any k even though their top units carry higher per-unit spatial information. The combined picture: *higher per-unit spatial information $\neq$ position readout*. Rich-encoder peaked units appear to encode features correlated with position (e.g. visual landmarks, trajectory phase) rather than position itself.

Pilot 1 (uncapped, job 2840256). After 10 M frames, gaze variance exceeded that of a uniform distribution over $[0, 1]^2$ (std $[0.43, 0.42]$ vs. theoretical max 0.289): gaze was essentially random. Task performance collapsed: SPL plateaued at 0.05, running-mean metrics transitioned to NaN at ~ 8 M frames. The uncapped regulariser destroyed the consistent-foveation signal the policy needs.

Pilot 2 (hinge, job 2842288). Gaze converged to an extreme corner of image space: mean $(0.001, 0.998)$ with std $[0.020, 0.023]$ — well below the target std of 0.1 and therefore with the hinge active throughout. Task SPL plateaued at 0.05 as in pilot 1. The policy apparently found the minimum-task-cost gaze that partially satisfies the diversity pressure: a sigmoid saturated at one corner, producing a constant image-corner view.




Figure 10: Goal-vector probe R^2 (referenced from §4.7). Goal *distance* (DtG) decodes strongly across all conditions ($R^2 \in [0.81, 0.90]$, validating probe machinery); goal *direction* and the full ego-frame goal vector are at chance or negative everywhere. PointGoal provides the goal vector as a per-step input, so the policy has no incentive to re-encode it.




Figure 11: Per-layer and MP3D companion figures (referenced from §4.2).

Interpretation. Both pilots argue that in our deterministic sigmoid-MLP gaze architecture with slow-gaze rollouts, gaze collapse is a pre-requisite for task learning rather than an accident. Task signal alone does not spontaneously produce informative fixation, and an exogenous anti-collapse regulariser moves gaze toward whatever region reduces regulariser loss fastest, which is generically *not* the task-useful region. A genuine H3 test likely requires (i) a stochastic gaze location with entropy bonus, so diversity is sampled at rollout time rather than enforced on a deterministic output; or (ii) a task-aligned intrinsic reward (e.g., information gain about goal-relative position); or (iii) an architectural change separating gaze generation from visual-feature extraction (e.g., attention-based gaze).

F Training Stability: Silent Weight Corruption in DD-PPO

During an initial foveated training run we observed a failure mode that did not manifest as a crash but as slow, silent corruption of the learned weights. After ≈ 170 M frames of stable progress (reward ≈ 10 , SPL ≈ 0.83), one mini-batch on one DDP worker produced a NaN gradient. Because `torch.nn.utils.clip_grad_norm_` does not sanitise non-finite gradients—the global norm becomes NaN, the clip coefficient becomes NaN, and `grad *=` NaN remains NaN—the subsequent `optimizer.step()` wrote NaN into every parameter. DDP all-reduce propagated the corruption across workers. The training loop did not raise: it continued for 2.5 days with reward=NaN and SPL= 0 until `torch.multinomial` finally rejected the NaN probability tensor. All checkpoints saved during this window were unrecoverable (90 of 97 parameter tensors entirely NaN).

To isolate the origin of the NaN gradient we re-ran training from the last clean checkpoint with `torch.autograd.set_detect_anomaly(True)` and per-module forward-output hooks. The anomaly traceback pinned the failure to `MseLossBackward0`, i.e. the backward pass of the value-

head loss $\frac{1}{2}(V(s) - R)^2$; rare return-vs-value discrepancies overflowed float32 in the squaring step, producing non-finite gradients downstream.

Our mitigation is a minimally invasive patch to `PP0.before_step` that zeroes any non-finite gradient element before clipping. A bad mini-batch becomes a no-op update rather than a catastrophic one. The patch is a no-op on clean training paths. Across the five conditions reported here, no NaN events were observed during full training after deployment, and all final checkpoints contain only finite weights. We reported the underlying issue upstream (habitat-lab issue #2226) with a minimal reproduction and a proposed native fix.

G Foveation experiments: status and design

This appendix details the four controlled foveation experiments referenced from §4.4. All four are submitted; numbers will populate §4.4 in revision as they land.

Table 3: Foveation experiment status (submission time).

Experiment	Tests	Status
F1–F4 strength sweep ($\sigma_{\max} \in \{2, 4, 12, 20\}$)	encoder–memory race as continuous lever	in training
F3 log-polar foveation	spatial-sampling vs. blur bottleneck	in training
Encoder feature-map probe (matched / uniform / foveated)	where position information is held	landed; see §4.4
Foveated-shifted (gaze (0.49, 0.62))	gaze-location axis (links to H3)	in training

Foveation strength sweep (F1–F4). We train four additional foveated agents at $\sigma_{\max} \in \{2, 4, 12, 20\}$ alongside the existing $\sigma_{\max} = 8$, holding gaze location, encoder stack, training budget, and training pool fixed. Expected signature: at low $\sigma_{\max}$ the foveated agent should look like uniform; at high $\sigma_{\max}$ it should approach matched-compute. The R^2 vs. $\sigma_{\max}$ curve directly tests the encoder–memory race as a continuous lever rather than a binary one.

Spatial sampling vs. blur (F3 log-polar). Gaussian blur removes high-frequency content but preserves spatial layout: a $\sigma_{\max} = 8$ foveated image still feeds the encoder 256×256 pixels, so the ResNet-18 stack still produces an 8×8 spatial feature map. A log-polar foveation [Strasburger et al., 2011, Rosenholtz, 2016] resamples with a non-uniform retinal grid (e.g. 64×64): the encoder spatial output drops to $\sim 2 \times 2$, much closer to matched’s 1×1 than to uniform’s 8×8 . This isolates the variable our sharpened H1 mechanism identifies as the trigger: *spatial-feature variety in the encoder output*. Falsifiable prediction (written before result available): log-polar should produce LSTM GPS $R^2 \geq 0.3$, between matched’s $+0.78$ and uniform’s ≈ 0 , with corresponding behavioural shifts. If instead log-polar matches uniform, the encoder-spatial-output-dimensionality mechanism is wrong. F3 in training ($\sim 14\text{M} / 250\text{M}$ frames at submission, ETA 2–3 days).

Foveated-shifted (gaze location). Training a foveated agent with hardcoded static gaze at (0.49, 0.62) matches foveated-learned’s collapsed gaze location while removing the learned-gaze module from the optimisation path. If foveated-shifted does *not* reproduce foveated-learned’s specific behaviours (Gibson–MP3D compass swing, transplant ranking), those behaviours can be attributed to the optimisation-path interaction rather than to gaze location alone. Links to H3 (§4.6).

Why disclose this rather than wait. Each experiment has a falsifiable signature; we disclose the designs openly so (i) the submission is honest about what foveation-specific evidence already exists vs. what is in flight, and (ii) the reader can identify which incoming result would change the paper’s interpretation.

H Encoder-capacity scaling sweep

[TODO: The scaling sweep trains matched-compute variants at input resolutions $\{32, 48, 64, 96, 128, 192\}$ alongside the existing blind (no encoder) and uniform 256×256 anchors. Probe results on the trained checkpoints will populate Figure 12 and this appendix section. Hypothesis: GPS probe R^2 decreases monotonically with input resolution, from $R^2 \approx 0.95$ at no-encoder to $R^2 \approx 0$ at 256×256 , crossing into the pass-through regime between 48 and 128 pixels.]



Figure 12: Encoder-capacity scaling curve. **[TODO: Pending data.]** x-axis: input resolution in pixels; y-axis: GPS and compass probe R^2 (5-fold CV, mean $\pm\sigma$).