IDB Information Technology Department

Header and footer for External Websites

DOCUMENT CLASSIFICATION	Bank Only
DOCUMENT CODE	IDB TTD/TDS
VERSION	1.0
INFORMATION OWNER	Raul Blanco

Revision History

Version	Date	Revision Author	Summary Of Changes
1.0	08/01/2025	Created by Maria Vega	Official version
1.1			

Approval

Version	Name	Department / Position	Initials	Date
1.0		ITO/ITE		

Content

Introduction 4
IDB Header and footer Configuration for Drupal 4
IDB Header and footer Configuration HTML 6

Introduction

This document is oriented to serve as guidance how to implement the header and footer for external websites

IDB Header and footer Configuration for Drupal

Open the file *.libraries.yml in your custom theme and add the following line in the CSS assets:

https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/css/idb-tailwind.css?v=0.0.1: { type: external }

In the same file, find the JS asset and add the following line:

https:// www.iadb.org /modules/custom/api_menu_items/V.0.0.5/js/main.js?v=0.0.1: { type: external }

Example:

```
global-styling:
  css:
    base:
      https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/css/idb-tailwind.css?v=0.0.1: { type: external }
      css/contrib/slick/slick.css: {}
      css/contrib/slick/slick-theme.css: {}
      css/contrib/font-awesome.min.css: {}
      css/idb_publications.css: {}
global-js:
  js:
    js/slick/slick.min.js: {}
    js/idb_publications.js: {}
    https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/js/main.js?v=0.0.1: { type: external }
  dependencies:
    - core/jquery
    - core/drupal
    - core/drupalSettings
    - core/jquery.once
    - core/drupal.ajax
```

Open the file *.theme in your custom theme and add the variables for the translation menu.

In the function hook_preprocess_html add the following code:

```
// Get language ID.
$variables['language'] = \Drupal::languageManager()->getCurrentLanguage()->getId();
// Current path.
$current_path = \Drupal::service('path.current')->getPath();
// Set English path.
$result = \Drupal::service('path_alias.manager')->getAliasByPath($current_path , 'en');
$variables['language_url_en'] =  $result;
// Set Spanish path.
$result = \Drupal::service('path_alias.manager')->getAliasByPath( $current_path, 'es');
$variables['language_url_es'] = strpos( $result , 'node/') !== false ? "no-link" : "/es" . $result;
// Set Portuguese path.
$result = \Drupal::service('path_alias.manager')->getAliasByPath( $current_path, 'pt');
$variables['language_url_pt'] = strpos( $result , 'node/') !== false ? "no-link" : "/pt" . $result;
// Set French path.
$result = \Drupal::service('path_alias.manager')->getAliasByPath( $current_path, 'fr');
$variables['language_url_fr'] = strpos( $result , 'node/') !== false ? "no-link" : "/fr" . $result;
```

Each language must be added to the variables if the site has one or two languages the variables for the others must be assigned with the string 'no-link'.

Example:

```
/**
 * Preprocess variables for html templates.
 * @param $variables
 */
function demandsolutions_preprocess_html(&$variables) {
  // Get language ID.
  $variables['language'] = \Drupal::languageManager()->getCurrentLanguage()->getId();
  // Current path.
  $current_path = \Drupal::service('path.current')->getPath();
  // Set English path.
  $result = \Drupal::service('path_alias.manager')->getAliasByPath($current_path , 'en');
  $variables['language_url_en'] =  $result;
  // Set Spanish path.
  $result = \Drupal::service('path_alias.manager')->getAliasByPath( $current_path, 'es');
  $variables['language_url_es'] = strpos( $result , 'node/') !== false ? "no-link" : "/es" . $result;
  // Set Portuguese path.
  $variables['language_url_pt'] = "no-link" ;
  // Set French path.
  $variables['language_url_fr'] = "no-link" ;
}
```

IDB Header and footer Configuration HTML

To embed the header and footer, you can use the ** HTML tags** as containers. Here's how to structure it

```
<div id="idb-header"></div>
<!-- contenido de la página -->
<div id="idb-footer"></div>
```

Add between the tags **<head></head> html tag** the following script to ensure the CSS are available on the web pages.

<!-- Estilos Tailwind personalizados del BID -->

<link rel="stylesheet" href="https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/css/idb-tailwind.css?v=0.0.1"/>

<!-- jQuery necesario para el script principal -->

<script src="https://code.jquery.com/jquery-3.6.0.min.js"> </script>

<!-- Script que inyecta el header y footer -->

<script src="https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/js/main.js?v=0.0.1" defer></script>

The **defer** attribute ensures the script runs after the HTML is parsed, which is useful for manipulating DOM elements like headers and. Example:

```html
<head>
  <!-- Tailwind styles customized for IDB's header/footer -->
  <link rel="stylesheet"
    href="https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/css/idb-tailwind.css?v=0.0.1" />

  <!-- jQuery: required by main.js -->
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>

  <!-- Main logic for injecting the header and footer -->
  <script src="https://www.iadb.org/modules/custom/api_menu_items/V.0.0.5/js/main.js?v=0.0.1" defer></script>
</head>
```

Resources	Description
idb-tailwind.css	Contiene los estilos visuales del header y footer (layout, colores, tipografía).
jquery.min.js	This library is mandatory to be used with main.js
main.js	Script that embeds the header and footer .

It is recommended to include the following inputs outside the main container of the app, preferably where the footer should be located.

- In the **value, language and the slug of url** should be included not only the language
- The first input adds the **pivot/default language if it is english** it should remain as is
- Use **"no-link"** when the selected language is not available.

Below you can see an example of the implementation:

```html
<input type="hidden" id="language_IADB" name="language_IADB" value="en">
<input type="hidden" id="en_path_IADB" name="en_path_IADB" value="/knowledge-resources">
<input type="hidden" id="es_path_IADB" name="es_path_IADB" value="/es/recursos-de-conocimiento">
<input type="hidden" id="pt_path_IADB" name="pt_path_IADB" value="/pt-br/recursos-de-conhecimento">
<input type="hidden" id="fr_path_IADB" name="fr_path_IADB" value="no-link">
```