

Package ‘CRMC’

May 20, 2025

Type Package

Title C-Optimality Based Two-Stage Continual Reassessment Method (CRM)

Version 0.1.0

Author Alvaro Cia-Mina

Maintainer Alvaro Cia-Mina <aciamina@unav.es>

Description Simulates a two-stage CRM design for dose-finding in clinical trials, including MTD estimation and plotting.

License MIT

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Imports lattice

Suggests testthat

Contents

export_simulation_table_manual	1
logistic_3_3	2
potential_3_3	3
run_simulation_logistic	4
run_simulation_potential	6
simulate_across_n_initial	7
two_stage_crm_logistic	8
two_stage_crm_potential	9

Index	11
--------------	-----------

export_simulation_table_manual

Export Simulation Summary to LaTeX

Description

Writes a LaTeX table with MTD and toxicity summaries using cat(), without external dependencies.

Usage

```
export_simulation_table_manual(
  df,
  file_path = "RESULTS/simulation_results.tex"
)
```

Arguments

df A data frame with simulation summaries for one model (e.g., `result_list$potential`) as returned by `simulate_across_n_initial()`.

file_path Path to the output .tex file.

Examples

```
result_list <- simulate_across_n_initial()
export_simulation_table_manual(result_list$potential, "table_potential.tex")
export_simulation_table_manual(result_list$logistic, "table_logistic.tex")
```

logistic_3_3

*3+3 Design Simulation for Logistic model with 2 parameters***Description**

Simulates a single trial using a 3+3 dose-escalation method for estimating the Maximum Tolerated Dose (MTD).

Usage

```
logistic_3_3(
  theta = c(-3, 2),
  theta_0 = c(-3.1, 1.8),
  n_initial = 3,
  p_tox_init = 0.05,
  delta_dosis = 0.092,
  seed = 1234,
  show_plot = FALSE
)
```

Arguments

theta True value of the vector of parameters for the dose-toxicity curve. Default is `c(-3,2)`.

theta_0 Nominal value for the vector of parameters. Default is `c(-3.1,1.8)`.

n_initial Number of patients per dose level. Default is 3.

p_tox_init Initial toxicity probability for computing starting dose. Default is 0.05.

delta_dosis Step size for dose escalation. Default is 0.05.

seed Random seed for reproducibility. Default is 1234.

show_plot Logical. If TRUE, plot dose level vs. patient index. Default is FALSE.

Value

A list with:

- n_toxicities** Total number of toxicities observed.
- mtd_estimated** Estimated MTD (last safe dose).
- n_patients** Total number of patients enrolled.
- x** Dose levels assigned.
- y** Observed toxicity outcomes (1 = toxic, 0 = non-toxic).

Examples

```
res <- logistic_3_3()
print(res$mtd_estimated)
```

potential_3_3

3+3 Design Simulation for Potential model

Description

Simulates one trial using a 3+3 dose-escalation method for estimating the Maximum Tolerated Dose (MTD).

Usage

```
potential_3_3(
  theta = 3,
  theta_0 = 2.7,
  n_initial = 3,
  p_tox_init = 0.02,
  delta_dosis = 0.05,
  seed = 1234,
  show_plot = FALSE
)
```

Arguments

- theta** True value for the dose-toxicity curve. Default is 3.
- theta_0** Nominal value for the dose-toxicity curve. Default is 2.7.
- n_initial** Number of patients per dose level. Default is 3.
- p_tox_init** Initial toxicity probability for computing starting dose. Default is 0.02.
- delta_dosis** Step size for dose escalation. Default is 0.05.
- seed** Random seed for reproducibility. Default is 1234.
- show_plot** Logical. If TRUE, plot dose level vs. patient index. Default is FALSE.

Value

A list with:

- n_toxicities** Total number of toxicities observed.
- mtd_estimated** Estimated MTD (last safe dose).
- n_patients** Total number of patients enrolled.
- x** Dose levels assigned.
- y** Observed toxicity outcomes (1 = toxic, 0 = non-toxic).

Examples

```
res <- potential_3_3()
print(res$mtd_estimated)
```

```
run_simulation_logistic
```

Simulation Comparison of 3+3 and Two-Stage CRM Designs for a Logistic Model with Two Parameters

Description

Simulates and compares MTD estimates and toxicity outcomes between the 3+3 design and a two-stage CRM design over multiple replications.

Usage

```
run_simulation_logistic(
  num_rep = 1000,
  seed = 1234,
  save_plot = FALSE,
  p0 = 0.4,
  theta = c(-3, 2),
  theta_0 = c(-3.1, 1.8),
  N = 24,
  n_initial = 1,
  q_0 = 0.05,
  q_2 = 0.4,
  q_1 = 0.9,
  lim_sup_prob = 0.7,
  p_tox_init_3_3 = 0.05,
  delta_dosis_3_3 = 0.092
)
```

Arguments

- num_rep** Number of replications to run. Default is 1000.
- seed** Base random seed for reproducibility. Default is 1234.
- save_plot** Logical. If TRUE, saves comparison plots as PDF. Default is FALSE.

p0	Target toxicity probability. Default is 0.4.
theta	True value of the vector of parameters for the dose-toxicity curve. Default is c(-3,2).
theta_0	Nominal value for the vector of parameters. Default is c(-3.1,1.8).
N	Total number of patients in the CRM design. Default is 24.
n_initial	Number of patients per dose level in the CRM design (not used in 3+3). Default is 1.
q_0	Initial toxicity probability for CRM design. Default is 0.05.
q_2	Fraction of patients in CRM stage 1. Default is 0.4.
q_1	Target probability of observing at least one toxicity in CRM stage 1. Default is 0.9.
lim_sup_prob	Maximum probability of toxicity the model allows. Default is 0.7.
p_tox_init_3_3	Initial toxicity probability for the 3+3 model. Default is 0.05.
delta_dosis_3_3	Step size for dose escalation in the 3+3 model. Default is 0.092.

Value

A data.frame with one row per method ("3+3" and "2stage") and the following columns:

method Design used ("3+3" or "2stage")
mean_pat Mean of patients
median_pat Median of patients
mean_mtd Mean of the estimated MTDs
var_mtd Variance of the estimated MTDs
median_mtd Median of the estimated MTDs
min_mtd Minimum of the estimated MTDs
q1_mtd First quartile (Q1) of the estimated MTDs
q3_mtd Third quartile (Q3) of the estimated MTDs
max_mtd Maximum of the estimated MTDs
iqr_mtd Interquartile range of the estimated MTDs
mean_tox Mean number of toxicities
median_tox Median number of toxicities
min_tox Minimum number of toxicities
q1_tox First quartile (Q1) of the number of toxicities
q3_tox Third quartile (Q3) of the number of toxicities
max_tox Maximum number of toxicities
iqr_tox Interquartile range of the number of toxicities

Examples

```
df <- run_simulation_logistic(num_rep = 100)
head(df)
```

run_simulation_potential

Run Simulation Comparison Between 3+3 and Two-Stage CRM for the potential model

Description

Compares the MTD estimation and toxicity count between the potential 3+3 method and the two-stage CRM using multiple replications.

Usage

```
run_simulation_potential(
  num_rep = 1000,
  seed = 1234,
  save_plot = FALSE,
  p0 = 0.4,
  theta_0 = 2.7,
  theta = 3,
  N = 24,
  n_initial = 1,
  q_0 = 0.05,
  q_2 = 0.5,
  q_1 = 0.9,
  p_tox_init_3_3 = 0.02,
  delta_dosis_3_3 = 0.055,
  fixed_optimal_dose = 0.2032
)
```

Arguments

num_rep	Number of replications to run. Default is 1000.
seed	Base random seed for reproducibility. Default is 1234.
save_plot	Logical. If TRUE, saves comparison plots as PDF. Default is FALSE.
p0	Target toxicity probability. Default is 0.4.
theta_0	Nominal value of theta used in CRM and 3+3 escalation models. Default is 2.7.
theta	True theta used for generating the MTD reference. Default is 3.
N	Total number of patients in the CRM design. Default is 24.
n_initial	Number of patients per dose level in the CRM design (not used in 3+3). Default is 1.
q_0	Initial toxicity probability for CRM design. Default is 0.05.
q_2	Fraction of patients in CRM stage 1. Default is 0.5.
q_1	Target probability of observing at least one toxicity in CRM stage 1. Default is 0.9.
p_tox_init_3_3	Initial toxicity probability for the 3+3 model. Default is 0.02.
delta_dosis_3_3	Step size for dose escalation in the 3+3 model. Default is 0.055.
fixed_optimal_dose	Reference dose for optimal CRM design. Default is 0.2032.

Value

A data.frame with one row per method ("3+3" and "2stage") and the following columns:

method Design used ("3+3" or "2stage")
mean_pat Mean of patients
median_pat Median of patients
mean_mtd Mean of the estimated MTDs
var_mtd Variance of the estimated MTDs
median_mtd Median of the estimated MTDs
min_mtd Minimum of the estimated MTDs
q1_mtd First quartile (Q1) of the estimated MTDs
q3_mtd Third quartile (Q3) of the estimated MTDs
max_mtd Maximum of the estimated MTDs
iqr_mtd Interquartile range of the estimated MTDs
mean_tox Mean number of toxicities
median_tox Median number of toxicities
min_tox Minimum number of toxicities
q1_tox First quartile (Q1) of the number of toxicities
q3_tox Third quartile (Q3) of the number of toxicities
max_tox Maximum number of toxicities
iqr_tox Interquartile range of the number of toxicities

Examples

```
df <- run_simulation_potential(num_rep = 100)
head(df)
```

```
simulate_across_n_initial
```

Simulation Study for Different n_initial Values (Potential and Logistic Models)

Description

Runs simulations using run_simulation_potential() and run_simulation_logistic() with varying n_initial values and summarizes key results.

Usage

```
simulate_across_n_initial(num_rep = 500, seed = 1234)
```

Arguments

num_rep Number of repetitions for each simulation. Default is 500.
seed Random seed. Default is 1234.

Value

A list of two data frames: \$potential and \$logistic, each containing results for CRM at $n_{\text{initial}} = 1:5$ and $3+3$.

Examples

```
result_list <- simulate_across_n_initial()
head(result_list$potential)
```

```
two_stage_crm_logistic
```

*C-optimal based two-stage Continual Reassessment Method (CRM)
Simulation for logistic model with 2 parameters*

Description

Performs one simulation run of a two-stage CRM design for estimating the Maximum Tolerated Dose (MTD) in phase I trials.

Usage

```
two_stage_crm_logistic(
  p0 = 0.4,
  theta = c(-3, 2),
  theta_0 = c(-3.1, 1.8),
  N = 24,
  n_initial = 3,
  q_0 = 0.05,
  q_2 = 0.4,
  q_1 = 0.9,
  lim_sup_prob = 0.7,
  show_plot = FALSE,
  seed = 1234
)
```

Arguments

p0	Target toxicity probability. Default is 0.4.
theta	True value for the vector of parameters for the dose-toxicity curve. Default is $c(-3, 2)$.
theta_0	Nominal value of the vector of parameters. Default is $c(-3.1, 1.8)$.
N	Total number of patients (including both stages). Default is 24.
n_initial	Number of patients per dose in stage 1. Default is 3.
q_0	Toxicity probability at first dose. Default is 0.02.
q_2	Fraction of patients in stage 1. Default is 0.5.
q_1	Target probability of observing at least one toxicity during stage 1. Default is 0.9.
show_plot	Logical. If TRUE, plots the dose levels for patients in the trial. Default is FALSE.
seed	Random seed for reproducibility. Default is 1234.

Value

A list with:

n_toxicities Total number of toxicities observed.

mtd_estimated Estimated Maximum Tolerated Dose (MTD). If no toxicity is observed in the first stage, the MTD is set to the largest dose level used.

mle_theta Vector of estimated parameters $\theta = (\alpha, \beta)$ for the logistic dose-toxicity model. Set to NA if no toxicity is detected in stage 1.

x Vector of dose levels administered.

y Vector of toxicity outcomes (1 = toxic, 0 = non-toxic).

Note

If no toxicity is observed during the first stage of the trial (i.e., $\text{sum}(y) == 0$), the simulation is terminated. A warning is issued, and the MTD is conservatively estimated as the highest dose level reached. The value of `mle_theta` is set to NA in this case.

Examples

```
result <- two_stage_crm_logistic(show_plot = TRUE)
print(result$mtd_estimated)
```

```
two_stage_crm_potential
```

*C-optimal based two-stage Continual Reassessment Method (CRM)
Simulation for potential model*

Description

Performs one simulation run of a two-stage CRM design for estimating the Maximum Tolerated Dose (MTD) in phase I trials.

Usage

```
two_stage_crm_potential(
  p0 = 0.4,
  theta = 3,
  theta_0 = 2.7,
  N = 24,
  n_initial = 3,
  q_0 = 0.02,
  q_2 = 0.5,
  q_1 = 0.9,
  fixed_optimal_dose = 0.2032,
  show_plot = FALSE,
  seed = 1234
)
```

Arguments

<code>p0</code>	Target toxicity probability. Default is 0.4.
<code>theta</code>	True value for the dose-toxicity curve. Default is 3.
<code>theta_0</code>	Nominal value of the dose-toxicity curve parameter (initial guess). Default is 2.7.
<code>N</code>	Total number of patients (including both stages). Default is 24.
<code>n_initial</code>	Number of patients per dose in stage 1. Default is 3.
<code>q_0</code>	Toxicity probability at first dose. Default is 0.02.
<code>q_2</code>	Fraction of patients in stage 1. Default is 0.5.
<code>q_1</code>	Target probability of observing at least one toxicity during stage 1. Default is 0.9.
<code>fixed_optimal_dose</code>	Reference dose for optimal design estimation. Default is 0.2032.
<code>show_plot</code>	Logical. If TRUE, plots the dose levels for patients in the trial. Default is FALSE.
<code>seed</code>	Random seed for reproducibility. Default is 1234.

Value

A list with:

- n_toxicities** Total number of toxicities observed.
- mtd_estimated** Estimated Maximum Tolerated Dose (MTD). If no toxicity is observed in the first stage, the MTD is set to the largest dose level used.
- mle_theta** Estimated value of the dose-toxicity parameter θ . Set to NA if no toxicity is detected in stage 1.
- x** Vector of dose levels administered.
- y** Vector of toxicity outcomes (1 = toxic, 0 = non-toxic).

Note

If no toxicity is observed during the first stage of the trial (i.e., `sum(y) == 0`), the simulation is terminated. A warning is issued, and the MTD is conservatively estimated as the highest dose level reached. The value of `mle_theta` is set to NA in this case.

Examples

```
result <- two_stage_crm_potential(show_plot = TRUE)
print(result$mtd_estimated)
```

Index

`export_simulation_table_manual`, [1](#)

`logistic_3_3`, [2](#)

`potential_3_3`, [3](#)

`run_simulation_logistic`, [4](#)

`run_simulation_potential`, [6](#)

`simulate_across_n_initial`, [7](#)

`two_stage_crm_logistic`, [8](#)

`two_stage_crm_potential`, [9](#)