DEALER LOCATOR (/DEALER-LOCATOR)



E804/E805 ADVENTURE TRAIL

Utilizing the latest in dual sport tire technology these adventure tires are ideal for situations where a rider spends 40% on-road and 60% off-road.

- Latest in Big-Block Technology
- Superior on-road handling and mileage
- · Stable sidewalls for soft surfaces
- DOT approved
- M+S = Mud and Snow Rated

SPEC CHART RELATED PRODUCTS

Part #	Size	Special Description	Speed Rating	Load Index	Permitted Rim Size	Outside Diameter	Width	Max Load @	Tube Type	List Price
87-4698	110/80R19	804 Front TIRE	S HPRODUCT	S) ₅₉ SUPPO	RT ABOUT (/AB	OUT) CONTACT	(/CONT	ACT) FITME	EN _{TUD} UELTME	EN \$ T } _{2.95}
• ⁹⁷ -4' '2	אר אר פ	30/ Fr it (/)	S	57	2.15~2.75	26.1 in.	3.9 in.	41 psi	Tube	\$127.95
87-4708	120/70R19	804 Front	Н	60		26.26 in.		42 psi	Tubeless	\$186.95
№ 87 - 4700	110/80-19	804 Front	ER LOCATOR	59	2.15~3.00	25.95 in.	4.29 in.	33 psi	Tubeless	\$132.95
\$ 87 - 4702	90/90-21	804 Front	Т	54	1.85~2.50	27.4 in.	3.50 in.	40 psi	Tubeless	\$117.95
Rear										
Part #	Size	Special Description	Speed Rating	Load Index	Permitted Rim Size	Outside Diameter	Width	Max Load @	Tube Type	List Price
87-4697	150/80B16		Н	77					Tubeless	\$162.95
87-4699	150/70R17		R	69					Tubeless	\$149.95
87-4709	170/60R17	805 Rear	Н	72		25.04 in.		42 psi	Tubeless	\$229.95
07.4704						23.04 111.		12 poi	100000	Ψ220.00
87-4704	130/80-17	805 Rear	Т	65	2.50~3.50	25.2 in.	5.1 in.	41 psi	Tubeless	\$159.95
87-4704 № 87-4706	130/80-17 140/80-17	805 Rear	T Q	65 65	2.50~3.50 2.75~3.75		5.1 in. 5.59 in.	·		
						25.2 in.		41 psi	Tubeless	\$159.95
≯ 87-4706	140/80-17	805 Rear	Q	65	2.75~3.75	25.2 in. 25.83 in.	5.59 in.	41 psi 41 psi	Tubeless Tube	\$159.95 \$149.95

MOTORCYCLE TIRES

HOME (/)

FAQ (/SUPPORT/QUESTIONS)

CONTACT US (/CONTACT)

LOCATE A DEALER (/DEALER-LOCATOR)

ABOUT US (/ABOUT)

TIRE REGISTRATION (/SUPPORT/TIRE-REGISTRATION)

601 E. Gowen Road Boise, Idaho 83716 United States of America

BE A SHINKO TIRE INSIDER!

Get the latest product information and tech tips!

Enter your e-mail here

