KEY FOB ASSIGNMENT

Refer to Table 14. The key fob on security system motorcycles must be set so it will operate the alarm system on the vehicle. This assignment **must** be completed with no pauses **greater than 10 seconds** between steps. Turn the ignition OFF after both key fobs have been assigned. The programming mode will also exit after 60 seconds has elapsed without detecting any key fob sign up messages or turn signal activity.

Two key fobs may be assigned to the security system. The first successful attempt to program a key fob will disable all previously assigned key fobs. If a second key fob is to be programmed, it must be done in the same programming sequence as the initial key fob.

To assign a key fob to a motorcycle, refer to Table 14.

BATTERY DISCONNECTS AND CONFIGURING

After reconnecting a battery, the security system will not enter the configuration mode on the first attempt. Therefore, after all battery reconnects, the configuration sequence must be modified as follows.

- Set run switch to OFF, cycle ignition key ON-OFF-ON-OFF-ON and press left turn signal switch twice.
 - Wait for one to three confirmation flashes of the turn signals and then set ignition key switch to **OFF**.
- Repeat step listed above.
- 3. Continue with configuration sequence listed.

Table 14. Key Fob Assignment

STEP NO.	ACTION	WAIT FOR CONFIRMATION	NOTES
1	Turn IGN key ON-OFF-ON-OFF-ON		
2	Press left turn switch 2 times and release	2 - 3 flashes turn signals & indicators depending on vehicle configuration (See BATTERY DISCONNECTS AND CONFIGURING section)	2 flashes - North American/ Domestic configuration Security System 3 flashes - European/HDI config- uration Security System
3	Press right turn switch 1 time and release	1 flash turn signals & indicators	
4	Press left turn switch 1 time and release	2 flashes turn signals & indicators	
5	Press and hold key fob button until confirmation is received	2 flashes turn signals & indicators	This may take 10 - 25 seconds
6	If you have two key fobs, press and hold button on second key fob until confirmation is received	2 flashes turn signals & indicators	Optional step
7	Turn IGN key OFF		