



## DAILY ASSESSMENT FORMAT

Date:	28/05/2020	Name:	Davis S. Patel
Course:	Logic Design	USN:	4AL16EC045
Topic:	Boolean equations for digital circuits. Combinational circuits: Conversion of MUX and Decoders to logic gates.	Semester & Section:	8 <sup>th</sup> - A
GitHub Repository:	Davis		

### FORENOON SESSION DETAILS

Image of session



## **Report –**

### **Boolean algebra:**

- In 1854, George Boole Developed an Algebraic System Called Boolean algebra.
- Boolean algebra is a System of Mathematical Logics.
- It is Defined With a set of Elements, a set of Operators and a Number of Postulates

### **Laws of Boolean algebra:**

#### ➤ **Commutative Law**

Commutative law states that changing the sequence of the variables does not have any effect on the output of a logic circuit.

$$X+Y=Y+X$$

$$A+B =B+A$$

$$X.Y=Y.X$$

$$A.B=B.A$$

#### ➤ **Associative Law**

If a logical operation of any two Boolean variables is performed first and then the same operation is performed with the remaining variable gives the same result, then that logical operation is said to be Associative.

$$X+(Y+Z)=(X+Y)+Z$$

$$A+(B+C)=(A+B)+C$$

$$X.(Y.Z)=(X.Y).Z$$

$$A.(B.C)=(A.B).C$$

➤ **Distributive Law**

If any logical operation can be distributed to all the terms present in the Boolean function, then that logical operation is said to be Distributive.

$$X(Y+Z)=XY+YZ$$

$$A(B+C)=AB+AC$$

➤ **Absorption Theorem**

This law enables a reduction in a complicated expression to a simpler one by absorbing like terms.

$$X+XY=X$$

$$A+AB=A$$


$$X+\sim XY=X+Y$$

**MUX to Logic Gates Conversion:**

1. NAND, NOR-Universal Gates
2. Universal Gates
3. MUX and Decoders are Called Universal Logic

Multiplexer is device which Selects one or Several Digital or Analog Inputs and It will forward it to the Output Line, Which is Single Output line.

**BCD to SEVEN Segment Decoder**





Binary Inputs	Decoder Outputs	7 Segment Display Outputs
D C B A	a b c d e f g	
0 0 0 0	1 1 1 1 1 1 0	0
0 0 0 1	0 1 1 0 0 0 0	1
0 0 1 0	1 1 0 1 1 0 1	2
0 0 1 1	1 1 1 1 0 0 1	3
0 1 0 0	0 1 1 0 0 1 1	4
0 1 0 1	1 0 1 1 0 1 1	5
0 1 1 0	1 0 1 1 1 1 1	6
0 1 1 1	1 1 1 0 0 0 0	7
1 0 0 0	1 1 1 1 1 1 1	8
1 0 0 1	1 1 1 1 0 1 1	9



## DAILY ASSESSMENT FORMAT

<b>Date:</b>	<b>28/05/2020</b>	<b>Name:</b>	<b>Davis S. Patel</b>
<b>Course:</b>	<b>Python Course</b>	<b>USN:</b>	<b>4AL16EC045</b>
<b>Topic:</b>	<b>Application 5 : Build a Desktop Database Application</b>	<b>Semester &amp; Section:</b>	<b>8<sup>th</sup> - A</b>
<b>GitHub Repository:</b>	<b>Davis</b>		

### AFTERNOON SESSION DETAILS

#### Image of Session





## **Report –**

### **Application 5: Build a Desktop Database Application**

Front-end Web Development refers to building web interfaces, specifically the parts of the website that the user will interact with. When you're browsing the web, everything you see, from images and headings to sliders and buttons is made using HTML, CSS and JavaScript, the main components to any website.

Back-end Development refers to the parts of the website that a user doesn't see or directly interact with. The back end handles application logic, algorithms, database interaction and the processing of user requests.

## **Frontend.py –**

Frontend.py

```
from tkinter import *
```

```
import backend
```

```
def get_selected_row(event):
```

```
    global selected_tuple
```

```
    index=list1.curselection()[0]
```

```
    selected_tuple=list1.get(index)
```

```
    e1.delete(0,END)
```

```
    e1.insert(END,selected_tuple[1])
```

```
    e2.delete(0,END)
```

```
    e2.insert(END,selected_tuple[2])
```

```
    e3.delete(0,END)
```

```
e3.insert(END,selected_tuple[3])
e4.delete(0,END)
e4.insert(END,selected_tuple[4])
```

```
def view_command():
```

```
    list1.delete(0,END)
    for row in backend.view():
        list1.insert(END,row)
```

```
def search_command():
```

```
    list1.delete(0,END)
    for row in backend.search(title_text.get(),author_text.get(),year_text.get(),isbn_text.get()):
        list1.insert(END,row)
```

```
def add_command():
```

```
    backend.insert(title_text.get(),author_text.get(),year_text.get(),isbn_text.get())
    list1.delete(0,END)
    list1.insert(END,(title_text.get(),author_text.get(),year_text.get(),isbn_text.get()))
```

```
def delete_command():
```

```
    backend.delete(selected_tuple[0])
```

```
def update_command():
```

```
    backend.update(selected_tuple[0],title_text.get(),author_text.get(),year_text.get(),isbn_text.get())
```

```
window=Tk()
```



```
window.wm_title("BookStore")
```

```
l1=Label(window,text="Title")
```

```
l1.grid(row=0,column=0)
```

```
l2=Label(window,text="Author")
```

```
l2.grid(row=0,column=2)
```

```
l3=Label(window,text="Year")
```

```
l3.grid(row=1,column=0)
```

```
l4=Label(window,text="ISBN")
```

```
l4.grid(row=1,column=2)
```

```
title_text=StringVar()
```

```
e1=Entry(window,textvariable=title_text)
```

```
e1.grid(row=0,column=1)
```

```
author_text=StringVar()
```

```
e2=Entry(window,textvariable=author_text)
```

```
e2.grid(row=0,column=3)
```

```
year_text=StringVar()
```

```
e3=Entry(window,textvariable=year_text)
```

```
e3.grid(row=1,column=1)
```

```
isbn_text=StringVar()
```

```
e4=Entry(window,textvariable=isbn_text)
```

```
e4.grid(row=1,column=3)
```

```
list1=Listbox(window, height=6,width=35)
```

```
list1.grid(row=2,column=0,rowspan=6,columnspan=2)
```

```
sb1=Scrollbar(window)
```

```
sb1.grid(row=2,column=2,rowspan=6)
```

```
list1.configure(yscrollcommand=sb1.set)
```

```
sb1.configure(command=list1.yview)
```

```
list1.bind('<<ListboxSelect>>',get_selected_row)
```

```
b1=Button(window,text="View all", width=12,command=view_command)
```

```
b1.grid(row=2,column=3)
```

```
b2=Button(window,text="Search entry", width=12,command=search_command)
```

```
b2.grid(row=3,column=3)
```

```
b3=Button(window,text="Add entry", width=12,command=add_command)
```

```
b3.grid(row=4,column=3)
```

```
b4=Button(window,text="Update selected", width=12,command=update_command)
```

```
b4.grid(row=5,column=3)
```

```
b5=Button(window,text="Delete selected", width=12,command=delete_command)
```

```
b5.grid(row=6,column=3)
```

```
b6=Button(window,text="Close", width=12,command=window.destroy)
b6.grid(row=7,column=3)
```

```
window.mainloop()
```

### **Backend.py -**

```
import sqlite3
```

```
def connect():
```

```
    conn=sqlite3.connect("books.db")
```

```
    cur=conn.cursor()
```

```
    cur.execute("CREATE TABLE IF NOT EXISTS book (id INTEGER PRIMARY KEY, title text, author text, year integer, isbn integer)")
```

```
    conn.commit()
```

```
    conn.close()
```

```
def insert(title,author,year,isbn):
```

```
    conn=sqlite3.connect("books.db")
```

```
    cur=conn.cursor()
```

```
    cur.execute("INSERT INTO book VALUES (NULL,?,?,?)",(title,author,year,isbn))
```

```
    conn.commit()
```

```
    conn.close()
```

```
    view()
```

```
def view():
```

```
    conn=sqlite3.connect("books.db")
```

```
cur=conn.cursor()
cur.execute("SELECT * FROM book")
rows=cur.fetchall()
conn.close()
return rows
```

```
def search(title="",author="",year="",isbn=""):
    conn=sqlite3.connect("books.db")
    cur=conn.cursor()
    cur.execute("SELECT * FROM book WHERE title=? OR author=? OR year=? OR isbn=?",
(title,author,year,isbn))
    rows=cur.fetchall()
    conn.close()
    return rows
```

```
def delete(id):
    conn=sqlite3.connect("books.db")
    cur=conn.cursor()
    cur.execute("DELETE FROM book WHERE id=?", (id,))
    conn.commit()
    conn.close()
```

```
def update(id,title,author,year,isbn):
    conn=sqlite3.connect("books.db")
    cur=conn.cursor()
    cur.execute("UPDATE book SET title=?, author=?, year=?, isbn=? WHERE
id=?", (title,author,year,isbn,id))
    conn.commit()
    conn.close()
```

```
connect()
insert("The Sun","John Smith",1918,913123132)
delete(3)
update(4,"The moon","John Smooth",1917,999999)
print(view())
print(search(author="John Smooth"))
```