JAVA CODING CHALLENGE: 29-05-2020

1. Write a Program in Java to check whether a number is an Armstrong Number or not.

SAMPLE OUTPUT:

Input an integer: **153**
Is Armstrong number? **True**

Solution:

```
import java.util.*;
public class solution {
	public static boolean is_Amstrong(int n)
	{
		int remainder, sum = 0, temp = 0;
		temp = n;
		while (n > 0)
		{
			remainder = n % 10;
			sum = sum + (remainder * remainder * remainder);
			n = n / 10;
		}return sum == temp;
	}
	public static void main(String[] args)
	{
		Scanner scanner = new Scanner(System.in);
		System.out.print("Input an integer: ");
		String input = scanner.nextLine();
		int number = Integer.parseInt(input);
		System.out.println("Is Armstrong number? "+is_Amstrong(number));
	}
}
```

****

2. Write a Java program to find the second most frequent character in a given string.

Sample Output:

The given string is: **successes**
The second most frequent char in the string is: c

Solution:

```
import java.util.*;

public class Main

{

	static final int NOOFCHARS = 256;

	static char get2ndMostFreq(String str1)

	{

		int[] ctr = new int[NOOFCHARS];

		int i;

		for (i = 0; i < str1.length(); i++)

		(ctr[str1.charAt(i)]) ++;

		 int ctr_first = 0, ctr_second = 0;

		 for (i = 0; i < NOOFCHARS; i++)

		{

			if (ctr[i] > ctr[ctr_first]) {

			ctr_second = ctr_first;

			ctr_first = i;

		}

		else if (ctr[i] > ctr[ctr_second] && ctr[i] != ctr[ctr_first])

		 ctr_second = i;

	}

	return (char) ctr_second;
```

```
    }
    public static void main(String args[])
    {
        String str1 = "successes";
        System.out.println("The given string is: " + str1);
        char res = get2ndMostFreq(str1);
        if (res != '\0')
        System.out.println("The second most frequent char in the string is: " + res);
        else
        System.out.println("No second most frequent character found in the string.");
    }
}
```

****

3. Write a Java program to find the length of the longest consecutive elements sequence from a given unsorted array of integers.

SAMPLE OUTPUT:

Sample array: [49, 1, 3, 200, 2, 4, 70, 5]
The longest consecutive elements sequence is [1, 2, 3, 4, 5], therefore the program will return its length 5

Solution:

```
import java.util.HashSet;
public class Example
{
    public static void main(String[] args)
    {
        int nums[] = {49, 1, 3, 200, 2, 4, 70, 5};
        System.out.println("Original array length: "+nums.length);
        System.out.print("Array elements are: ");
        for (int i = 0; i < nums.length; i++)
        {
```

```
                System.out.print(nums[i]+" ");
            }
            System.out.println("\nThe new length of the array is: "+longest_sequence(nums));
        }
        public static int longest_sequence(int[] nums)
        {
            final HashSet<Integer> h_set = new HashSet<Integer>();
            for (int i : nums) h_set.add(i);
            int longest_sequence_len = 0;
            for (int i : nums)
            {
                int length = 1;
                for (int j = i - 1; h_set.contains(j); --j)
                {
                    h_set.remove(j);
                    ++length;
                }
                for (int j = i + 1; h_set.contains(j); ++j)
                {
                    h_set.remove(j);
                    ++length;
                }
                longest_sequence_len = Math.max(longest_sequence_len, length);
            }
            return longest_sequence_len;
        }
}
```

****

4. Write a Java program to segregate all 0s on left side and all 1s on right side of a given array of 0s and 1s.

SAMPLE OUTPUT:

Sample array: [1,0,1,1,0,0,1,1]
So, the Output must be: [0,0,0,1,1,1,1,1]

Solution:

```
import java.util.Arrays;
public class Main
{
	public static void main(String[] args)
	{
		int arr[] = new int[]{ 0, 0, 1, 1, 0, 1, 1, 1,0 };
		int result[];
		System.out.println("Sample array :");
		System.out.println(Arrays.toString(arr));
		int n = arr.length;
		result = separate_0_1(arr, n);
		System.out.println("So, the Output must be:");
		System.out.println(Arrays.toString(result));
	} static int [] separate_0_1(int arr[], int n)
	{
		int count = 0;
		for (int i = 0; i < n; i++)
		{
			if (arr[i] == 0)
			count++;
		}
		for (int i = 0; i < count; i++)
		arr[i] = 0;
		 for (int i = count; i < n; i++)ss
		arr[i] = 1;
		return arr;
	 }
  }
```

****