


# DAILY ASSESSMENT FORMAT

<b>Date:</b>	<b>11 JUNE 2020</b>	<b>Name:</b>	<b>PAVITHRAN S</b>
<b>Course:</b>	<b>R PROGRAMMING</b>	<b>USN:</b>	<b>4AL17EC068</b>
<b>Topic:</b>	<b>R PROGRAM MANIPULATION</b>	<b>Semester &amp; Section:</b>	<b>6<sup>TH</sup> B</b>
<b>Github Repository:</b>	<b>Pavithran</b>		

## FORENOON SESSION DETAILS

### Image of session



**Report – Report can be typed or hand written for up to two pages.**

An operator is a symbol that tells the compiler to perform specific mathematical or logical manipulations. R language is rich in built-in operators and provides following types of operators.

## Types of Operators

We have the following types of operators in R programming –

- Arithmetic Operators
- Relational Operators
- Logical Operators
- Assignment Operators
- Miscellaneous Operators

# Arithmetic Operators

Following table shows the arithmetic operators supported by R language. The operators act on each element of the vector.

Operator	Description	Example
+	Adds two vectors	<a href="#">Live Demo</a>
		<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v+t)</pre>
		it produces the following result – [1] 10.0 8.5 10.0
–	Subtracts second vector from the first	<a href="#">Live Demo</a>
		<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v-t)</pre>
		it produces the following result – [1] -6.0 2.5 2.0
*	Multiplies both vectors	<a href="#">Live Demo</a>
		<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v*t)</pre>
		it produces the following result – [1] 16.0 16.5 24.0
/	Divide the first vector with the second	<a href="#">Live Demo</a>
		<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v/t)</pre>
		When we execute the above code, it produces the following result – [1] 0.250000 1.833333 1.500000
%%	Give the remainder of the first vector with the second	<a href="#">Live Demo</a>
		<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v%%t)</pre>
		it produces the following result –

		[1] 2.0 2.5 2.0	
%%	The result of division of first vector with second (quotient)	<div>Live Demo</div> <pre>v &lt;- c( 2, 5.5, 6) t &lt;- c(8, 3, 4) print(v%%t)</pre> <p>it produces the following result –</p> <pre>[1] 0 1 1</pre>	
^	The first vector raised to the exponent of second vector	<div>Live Demo</div> <pre>v &lt;- c( 2, 5.5, 6) t &lt;- c(8, 3, 4) print(v^t)</pre> <p>it produces the following result –</p> <pre>[1] 256.000 166.375 1296.000</pre>	

## Relational Operators

Following table shows the relational operators supported by R language. Each element of the first vector is compared with the corresponding element of the second vector. The result of comparison is a Boolean value.

Operator	Description	Example
>	Checks if each element of the first vector is greater than the corresponding element of the second vector.	<pre>v &lt;- c(2, 5.5, 6, 9) t &lt;- c(8, 2.5, 14, 9) print(v&gt;t)</pre> <p>it produces the following result –</p> <pre>[1] FALSE TRUE FALSE FALSE</pre>
<	Checks if each element of the first vector is less than the corresponding element of the second vector.	<pre>v &lt;- c(2, 5.5, 6, 9) t &lt;- c(8, 2.5, 14, 9) print(v &lt; t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE FALSE TRUE FALSE</pre>
==	Checks if each element of the first vector is equal to the corresponding element of the second vector.	<pre>v &lt;- c(2, 5.5, 6, 9) t &lt;- c(8, 2.5, 14, 9) print(v == t)</pre> <p>it produces the following result –</p>

		[1] FALSE FALSE FALSE TRUE
<=	Checks if each element of the first vector is less than or equal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v&lt;=t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE FALSE TRUE TRUE</pre>
>=	Checks if each element of the first vector is greater than or equal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v&gt;=t)</pre> <p>it produces the following result –</p> <pre>[1] FALSE TRUE FALSE TRUE</pre>
!=	Checks if each element of the first vector is unequal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v!=t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE TRUE TRUE FALSE</pre>

## Logical Operators

Following table shows the logical operators supported by R language. It is applicable only to vectors of type logical, numeric or complex. All numbers greater than 1 are considered as logical value TRUE.

Each element of the first vector is compared with the corresponding element of the second vector. The result of comparison is a Boolean value.

Operator	Description	Example
&	It is called Element-wise Logical AND operator. It combines each element of the first vector with the corresponding element of the second vector and gives a output TRUE if both the elements are TRUE.	<pre>v &lt;- c(3,1,TRUE,2+3i) t &lt;- c(4,1,FALSE,2+3i) print(v&amp;t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE TRUE FALSE TRUE</pre>

	It is called Element-wise Logical OR operator. It combines each element of the first vector with the corresponding element of the second vector and gives a output TRUE if one the elements is TRUE.	<pre>v &lt;- c(3,0,TRUE,2+2i) t &lt;- c(4,0,FALSE,2+3i) print(v t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE FALSE TRUE TRUE</pre>
!	It is called Logical NOT operator. Takes each element of the vector and gives the opposite logical value.	<pre>v &lt;- c(3,0,TRUE,2+2i) print(!v)</pre> <p>it produces the following result –</p> <pre>[1] FALSE TRUE FALSE FALSE</pre>

The logical operator && and || considers only the first element of the vectors and give a vector of single element as output.

Operator	Description	Example
&&	Called Logical AND operator. Takes first element of both the vectors and gives the TRUE only if both are TRUE.	<pre>v &lt;- c(3,0,TRUE,2+2i) t &lt;- c(1,3,TRUE,2+3i) print(v&amp;&amp; t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE</pre>
	Called Logical OR operator. Takes first element of both the vectors and gives the TRUE if one of them is TRUE.	<pre>v &lt;- c(0,0,TRUE,2+2i) t &lt;- c(0,3,TRUE,2+3i) print(v   t)</pre> <p>it produces the following result –</p> <pre>[1] FALSE</pre>

## Assignment Operators

These operators are used to assign values to vectors.

Operator	Description	Example
<- or =	Called Left Assignment	<pre>v1 &lt;- c(3,1,TRUE,2+3i) v2 &lt;&lt;- c(3,1,TRUE,2+3i) v3 = c(3,1,TRUE,2+3i) print(v1)</pre>

<p>= or &lt;&lt;-</p>		<div data-bbox="818 155 1419 235"><pre>print(v2) print(v3)</pre></div> <p>it produces the following result –</p> <pre>[1] 3+0i 1+0i 1+0i 2+3i [1] 3+0i 1+0i 1+0i 2+3i [1] 3+0i 1+0i 1+0i 2+3i</pre>
<p>-&gt; or -&gt;&gt;</p>	<p>Called Right Assignment</p>	<div data-bbox="818 443 1419 594"><pre>c(3,1,TRUE,2+3i) -&gt; v1 c(3,1,TRUE,2+3i) -&gt;&gt; v2 print(v1) print(v2)</pre></div> <p>it produces the following result –</p> <pre>[1] 3+0i 1+0i 1+0i 2+3i [1] 3+0i 1+0i 1+0i 2+3i</pre>