


Date: 06/06/2020  
Course: UdemY  
Topic: Python

Name: Soundarya NA  
USN: 4AL16EC077  
Semester & Section: 8<sup>th</sup> B

## AFTERNOON SESSION DETAILS




```
app_ver3.py — D:\Dropbox\pp\geocoder_service\geocoder_web_app_ver3\app — Atom
File Edit View Selection Find Packages Help

static
main.css
templates
download.html
index.html
uploads
virtual
app_ver1.py
app_ver2.py
app_ver3.py
app_ver4.py

1 from flask import Flask, render_template, request, send_file
2 from geopy.geocoders import Nominatim
3 import pandas
4
5 app=Flask(__name__)
6
7 @app.route("/")
8 def index():
9     return render_template("index.html")
10
11 @app.route('/success-table', methods=['POST'])
12 def success_table():
13     if request.method=="POST":
14         file=request.files['file']
15         try:
16             df=pandas.read_csv(file)
17             gc=Nominatim()
18             df["coordinates"]=df["Address"].apply(gc.geocode)
19             df['Latitude'] = df['coordinates'].apply(lambda x: x.latitude if x != None
20             df['Longitude'] = df['coordinates'].apply(lambda x: x.longitude if x != None
21             df=df.drop("coordinates",1)
22             df.to_csv("uploads/geocoded.csv",index=None)
23             return render_template("index.html", text=df.to_html(), btn="download.html")
24         except:
25             return render_template("index.html", text="Please make sure you have an ad
26
27 @app.route("/download-file/")
28 def download():
29     return send_file("uploads/geocoded.csv", attachment_filename='yourfile.csv', as_at
30
31 if __name__ == "__main__":
32     app.run(debug=True)
```

```
index.html
1 <!DOCTYPE html>
2 <html lang="en">
3 <title> Super Geocoder </title>
4 <head>
5 <link href="../static/main.css" rel="stylesheet">
6 </head>
7 <body>
8 <div class="container">
9 <h1>Super Geocoder</h1>
10 <h3>Please upload your CSV file. The values con
11 <form action="{{url_for('success_table')}}" m
12 <input type="file" accept=".csv" name="file"
13 <button type="submit"> Submit </button>
14 </form>
15 <div class="output">
16 {{text|safe}}
17 {% include btn ignore missing %}
18 </div>
19 </div>
20 </body>
21 </html>
22
```



Udemy | The Python Mega Course: Build 10 Real World Applications | ★ Leave a rating

send\_email.py — D:\Dropbox\pp\geocoder\_service\geocoder\_web\_app\_ver3\app — Atom

```
1 from email.mime.text import MIMEText
2
3 def send_email(email, height):
4     from_email="aristulce@gmail.com"
5     from_password="pythonlecture"
6     to_email=email
7
8     subject="Height data"
9     message="Hey there, your height"
10
11 msg=MIMEText(message, 'html')
12 msg['Subject']=subject
13 msg['To']=to_email
14 msg['From']=from_email
15
16 gmail=smtp3lib.SMTP('smtp.gmail.com', 587)
17 gmail.starttls()
18 gmail.login(from_email, from_password)
19 gmail.send_message(msg)
```

www.google.at/int/en/policies/privacy/

Google Privacy & Terms

Overview Privacy Policy Terms of Service Technologies and Principles FAQ My Account

Privacy Policy

Welcome to the Google Privacy Policy

When you use Google services, you trust us with your information. This Privacy Policy is meant to help you understand what data we collect, why we collect it, and what we do with it. This is important; we hope you will take time to read it carefully. And remember, you can find controls to manage your information and protect your privacy and security at [My Account](#).

Privacy Policy

10 people bookmarked this moment.

**Report:**

The GeocoderRequest object literal contains the following fields:

```
{  
  address: string,  
  location: LatLng,  
  placeId: string,  
  bounds: LatLngBounds,  
  componentRestrictions: GeocoderComponentRestrictions,  
  region: string  
}
```

Required parameters: You must supply one, and only one, of the following fields:

- address — The address which you want to geocode.

or

location — The LatLng (or LatLngLiteral) for which you wish to obtain the closest, human-readable address. The geocoder performs a reverse geocode. See Reverse Geocoding for more information.

or

placeId — The place ID of the place for which you wish to obtain the closest, human-readable address.

See more about retrieving an address for a place ID.

Optional parameters:

- bounds — The LatLngBounds within which to bias geocode results more prominently. The bounds parameter will only influence, not fully restrict, results from the geocoder. See more information about viewport biasing below.
- componentRestrictions — Used to restrict results to a specific area. See more information about component filtering below.
- region — The region code, specified as a IANA language region subtag. In most cases, these tags map directly to familiar ccTLD ("top-level domain") two-character values. The region parameter will only influence, not fully restrict, results from the geocoder. See more information about region code biasing below.

The GeocoderResult object represents a single geocoding result. A geocode request may return multiple result objects:

```
results[]: {
```

```

types[]: string,
formatted_address: string,
address_components[]: {
  short_name: string,
  long_name: string,
  postcode_localities[]: string,
  types[]: string
},
partial_match: boolean,
place_id: string,
postcode_localities[]: string,
geometry: {
  location: LatLng,
  location_type: GeocoderLocationType
  viewport: LatLngBounds,
  bounds: LatLngBounds
}
}

```

**Code:**

```

<html>
<head>
  <meta name="viewport" content="initial-scale=1.0, width=device-width" />
  <script src="https://js.api.here.com/v3/3.1/mapsjs-core.js" type="text/javascript" charset="utf-8"></script>
  <script src="https://js.api.here.com/v3/3.1/mapsjs-service.js" type="text/javascript" charset="utf-8"></script>
</head>
<body style='margin: 0'>
  <div style="width: 100vw; height: 100vh" id="mapContainer"></div>
  <script>

```

```

// Initialize the platform object:
var platform = new H.service.Platform({
  'apikey': '{{apikey}}'
});

    const lng = {{longitude}};
    const lat = {{latitude}};

// Obtain the default map types from the platform object
    var defaultLayers = platform.createDefaultLayers();

// Instantiate (and display) a map object:
var map = new H.Map(
  document.getElementById('mapContainer'),
  defaultLayers.vector.normal.map,
  {
    zoom: 10,
    center: { lat: lat, lng: lng }
  });

    const marker = new H.map.Marker({lat: lat, lng: lng});
    map.addObject(marker);
</script>
</body>
</html>

```