




## DAILY ASSESSMENT FORMAT

Date:	28-05-2020	Name:	YAMUNASHREE N
Course:	Logic Design	USN:	4AL17EC097
Topic:	Boolean equations for digital circuit. Combinational circuits: conversion of MUX and decoders to logic gates. Design 7 segment decoder with common anode display.	Semester & Section:	6 <sup>th</sup> B sec
Github Repository:	yamunashree-courses		

### FORENOON SESSION DETAILS

Image of session





SELECTION (S)	OUTPUT(Y)
0	A
1	B

$$2^n - 1$$

$$2^n = \text{inputs}$$

$n$  = selection lines


$$Y = A\bar{S} + BS$$



Shot on OnePlus  
Scanned with CamScanner

BCD to 7 segment decoder

BCD to 7-segment decoder



A	B	C	D	a	b	c	d	e	f	g
0	0	0	0	1	1	1	1	1	1	0
0	0	0	1	0	1	1	0	0	0	0
0	0	1	0	1	1	0	1	1	0	1
0	0	1	1	1	1	1	1	0	0	1
0	1	0	0	0	1	1	0	0	1	1
0	1	0	1	1	0	1	1	0	1	1
0	1	1	0	1	0	1	1	1	1	1
0	1	1	1	1	1	1	0	0	0	0
1	0	0	0	1	1	1	1	1	1	1
1	0	0	1	1	1	1	1	0	1	1



Shot on OnePlus  
Scanned with CamScanner

## Logic Design

### Boolean equations for digital circuits

- Cost of the circuit
- Simple realization of a circuit
- Boolean algebra is a system of mathematical
- It is defined with set of elements, a set of operators, and a number of axioms or postulates
- set of elements (0,1)
- binary operators - or, and
- unary " - NOT

### Axioms & Laws of Boolean Algebra:-

Difference between boolean algebra, ordinary algebra and binary number system

#### Boolean Algebra:-

$$A + A = A \quad A \cdot A = A$$

$$1 + 1 = 1 \quad 1 \cdot 1 = 1$$

#### Ordinary Algebra

$$A + A = 2A \quad A \cdot A = A^2$$

$$1 + 1 = 2 \quad 1 \cdot 1 = 1$$

#### Binary number system

$$1 + 1 = (10) \quad 1 \cdot 1 = 1$$

### Axioms and Postulates:-

$$\rightarrow (x')' = x$$

#### Identity Element:-

or operation

additive identity = 0

multiplicative = 1

AND operation

#### Laws of Boolean Algebra:-

$$1) \text{ Commutative Law:- } x + y = y + x \quad x \cdot y = y \cdot x$$

$$A + B = B + A \quad A \cdot B = B \cdot A$$

#### MUX to logic gates:-

NAND, NOR → Universal gates  
MUX and Decoders are called "Universal logic"

#### Switcher Design

$$Y = 1 \cdot \bar{A} + 0 \cdot A$$


$$Y = \bar{A}$$

#### AND gate


$$Y = 0 \cdot \bar{B} + A \cdot B$$

$$Y = AB$$

#### OR gate



#### Ex - NOR



#### Bcd to 7 segment decoder

dec	0	1	2	3	4	5	6	7	8	9
0	1	1	1	1	1	0	0	1	1	1
1	0	1	1	0	0	1	1	0	0	0
2	1	0	1	1	0	0	1	0	0	0
3	1	1	0	1	0	0	0	0	0	0
4	0	1	1	0	1	0	0	0	0	0
5	1	1	1	0	0	1	0	0	0	0
6	1	1	1	1	0	0	0	0	0	0
7	1	1	0	0	0	0	1	1	1	1
8	1	1	1	1	1	0	0	1	1	1
9	1	1	1	1	0	1	0	1	1	1

$$a = \bar{C} + A + B\bar{D} + BD$$

$$b = \bar{B} + CD + \bar{E}\bar{D}$$


$$c = B + \bar{E} + D$$

$$d = A + B\bar{D} + \bar{C}\bar{D} + \bar{B}C + B\bar{C}\bar{D}$$

$$e = \bar{B}\bar{D} + \bar{C}\bar{D}$$

$$f = A + \bar{E}\bar{D} + B\bar{D} + \bar{B}\bar{C}$$



$$g = A + B\bar{C} + \bar{B}C + \bar{C}\bar{D}$$



Date:	28-05-2020	Name:	YAMUNASHREE N
Course:	Python Programming	USN:	4AL17EC097
Topic:	Application 5: Build a desktop database application.	Semester & Section:	6 <sup>th</sup> sem B sec

#### AFTERNOON SESSION DETAILS

##### Image of session





## 184. Connecting the Frontend to the Backend, Part 1

## 184. Connecting the Frontend to the Backend, Part 1

## Fixing the Bug (Practice)

### Exercise

If you haven't already noticed, the program has a bug. When the listbox is empty and the user clicks the listbox, an *IndexError* is generated in the terminal:

```
ARGUMENTS=NONE; echo -e "\n\nquit\n\n" | ssh python frontend.py  
Execution in /tmp/ssh-XXXXXX:  
Traceback (most recent call last):  
File "/Library/Frameworks/Python.framework/Versions/3.6/lib/python3.6/tkinter.  
__init__.py", line 1899, in __call__  
return self.func(*args)  
File "/tmp/ssh-XXXXXX", line 4, in get_selected_row  
index=index.cursor.selection()[0]  
IndexError: tuple index out of range
```

## Application 5: Build a Desktop Database

Day 3

### Application:

A program that stores this book information:

Title: Author

Year: ISBN

User can:

view all records

search an entry

Add entry

update entry

Delete

Close

import sqlite3

def connect():

conn = sqlite3.connect("books.db")

cur = conn.cursor()

cur.execute("Create Table if Not exists book")

(id Integer Primary Key, title text, author text, year integer, isbn integer)")

conn.commit()

conn.close()

def insert(title, author, year, isbn):

conn = sqlite3.connect("books.db")

cur = conn.cursor()

cur.execute("Insert into book values (Null, ?, ?, ?, ?)")

(title, author, year, isbn)

conn.commit()

conn.close()

def view():

conn = sqlite3.connect("books.db")

cur = conn.cursor()

cur.execute("select \* from book")

rows = cur.fetchall()

conn.close()

return rows

### Solution:-

def get\_selected\_row(event):

try:

global selected\_tuple

index = list1.curselection()[0]

selected\_tuple = list1.get(index)

e1 = delete(0, END)

e1.insert(END, selected\_tuple[1])

e2 = delete(0, END)

e2.insert(END, selected\_tuple[2])

e3 = delete(0, END)

e3.insert(END, selected\_tuple[3])

e4 = delete(0, END)

e4.insert(END, selected\_tuple[4])

except IndexError:

pass