

## THE L-WAT MINIFIED MOBILE VERSION API

### Routes Prefix

http://127.0.0.1/api/

### User Roles

- Client
- Partner
- Associate

### User Roles that login

- Associate
- Partner

### Guest Uer role

- Client

### Login Creds for each

#### Associate

- [esther@gmail.com](mailto:esther@gmail.com)
- 123456789

#### Partner

- [fred@gmail.com](mailto:fred@gmail.com)
- 123456789

**Note: 1.** On the mobile app, the associate and the partner user roles perform the same roles i.e. do the same things as listed in the next section. So Associate == Partner

**Note: 2.** All succeeding accesses after login must have the **bearer token** in the headers and a header type of Accept, application/json

Note 3. The Content-Type header should be set to application/json

### Associate/Partner funcs

- When click on 'login' link at landing page, access login page

| Request Type | Endpoint               | Payload   | Response 200   |   |
|--------------|------------------------|---|--|---|
| POST         | /login                 | {<br>"email" : "",<br>"password" : ""<br>}  | {<br>"token" : "",<br>"error": false,<br>"defaultPassword: ""<br>}   | {<br>"error": true,<br>"message": ""<br>} |
| GET          | /user/cases            | NONE  | {<br>"error": false,<br>"cases": []<br>}   |   |
| POST         | /user/view/case        | {<br>"case_number": ""<br>}   | {<br>"error" : false,<br>"data" :<br>{<br>"case": "",<br>"client": "",<br>"meetings": "",<br>"tasks": "",<br>"notes": ""<br>}<br>} | {<br>"error": true,<br>"message": ""<br>} |
| POST         | /user/schedule/meeting | {<br>"date": "",<br>"time": "",<br>"agenda": "",<br>"venue": "",<br>"caseID": ""<br>} | {<br>"error": false,<br>"message": ""<br>}   | {<br>"error": true,<br>"message": ""<br>} |

|      |                            |  |  |   |
|------|----------------------------|--|--|---|
| POST | <i>/user/add/casetask</i>  | {<br>“task”: “”,<br>“caseID”: “”<br>}  | {<br>“error”: false,<br>“message”: “”<br>} | {<br>“error”: true,<br>“message”: “”<br>} |
| POST | <i>/user/add/casenote</i>  | {<br>“note”: “”,<br>“caseID”: “”<br>}  | {<br>“error”: false,<br>“message”: “”<br>} | {<br>“error”: true,<br>“message”: “”<br>} |
| GET  | <i>/guest/view/firms</i>   | NONE   | {<br>“error”: false,<br>“firms”: []<br>}   |   |
| POST | <i>/guest/view/firm</i>    | {<br>“firm_id” : “”<br>}   | {<br>“error”: false,<br>“firm”: []<br>}    |   |
| POST | <i>/guest/contact/firm</i> | {<br>“name”: “”,<br>“email”: “”,<br>“contactChoice”: “”,<br>“query”: “”,<br>“phone”: “”,<br>“firm_id”: “”<br>} | {<br>“error”: false,<br>“message”: “”<br>} |   |
| POST | <i>/guest/search/firm</i>  | {<br>“pattern”: “”<br>}  | {<br>“error”: false,<br>“firms”: []<br>}   |   |

|     |         |      |  |  |
|-----|---------|------|--|--|
|     |         |      | }  |  |
| GET | /logout | NONE | {<br>“error”: false,<br>“message”: “”<br>} |  |

## IMPORTANT NOTES

The contactChoice field in the */guest/contact/firm* route is an enumeration of value, either 1 or 2, and so you might need to represent it via dropdown, radio or checkbox.

***Developer***  
***Alvin Mukiibi***  
***mukikelly792@gmail.com***

***“All winners, make a fatal mistake, just before they win, and become losers ”, John Ransom 1856***