

Quest Rubric No: 2		4	
Objective criteria (0/1, 1=met)	Rating	Max	Comments
Converts raw ADC values into correct engineering units for sonar, lidar	1	1	
Generates real-time plot(s) on host machine from live sensor and localization	1	1	
Quantifies noise/error using double integration from accelerometer (using ground truth)	1	1	
Implements a basic sensor fusion strategy (only one additional sensor is sufficient) to improve localization estimate	1	1	Each sensor only measures a separate axis. There is a better way to fuse sensors, such as setting the weight $x = x_1w_1 + x_2w_2$. But your method still counts as sensor fusion as you combine them for the (x,y,z) coordinate.
Exploring the role of at least 2 filtering mechanisms (e.g., one temporal, one threshold based)	1	1	
Compare with a smartphone accelerometer-based positioning (offline, just report the quality with double integrating smartphone	1	1	
Investigative question response	1	1	
Bonus: Make positioning orientation invariant	1	1	
Total objective criteria	8	7	
Qualitative criteria	Rating	Max	Comments
Quality of solution	5	5	
Quality of report.md including use of graphics	3	3	
Quality of code reporting	3	3	
Quality of video presentation	3	3	
Total qualitative criteria	14	14	
Quant Weight (75)	85.7	75	
Qual Weight (25)	25	25	
Total Score	110.7	100	
Rank (1-5)		5	
Comments			
If you wish to do a regrade request on objectives, please contact the professor			