```sql
SET FOREIGN_KEY_CHECKS = 0;

DROP TABLE EventRequest;

SET FOREIGN_KEY_CHECKS = 1;


CREATE TABLE EventRequest (

 evntNo     CHAR(8)     NOT NULL,

 custNo     CHAR(8)     NOT NULL,

 facNo      CHAR(8)     NOT NULL,

 dateHeld   DATE        NOT NULL,

 dateReq    DATE        NOT NULL,

 dateAuth   DATE,

 status     CHAR(20)    NOT NULL,

 estCost    DECIMAL(8, 2) NOT NULL,

 estAudience INTEGER     NOT NULL,

 budNo      CHAR(30),

 CONSTRAINT EventRequestPK PRIMARY KEY (evntNo),

 CONSTRAINT FK_Facility FOREIGN KEY (facNo) REFERENCES Facility (facNo),

 CONSTRAINT FK_Customer FOREIGN KEY (custNo) REFERENCES Customer (custNo),

 CHECK (status IN('Pending','Denied','Approved') AND estaudience>0)

);
```

```
+--------+--------------+--------+
| resNo  | resName      | rate   |
+--------+--------------+--------+
| R100   | attendant    | 10.00  |
| R101   | police       | 15.00  |
| R102   | usher        | 10.00  |
| R103   | nurse        | 20.00  |
| R104   | janitor      | 15.00  |
| R105   | food service | 10.00  |
+--------+--------------+--------+
```