

URBAN INDUSTRIAL EMISSIONS CONTROL STANDARDS, 2026

(ILLUSTRATIVE)

Sample document generated for RAG test-dataset purposes — not an official publication

1. Applicability

1.1 These Standards apply to any manufacturing unit operating within 5 km of a declared residential zone. 1.2 Units classified as Red Category under the State Pollution Control Board's classification are subject to additional conditions under Section 4.

2. Emission Limits

2.1 Particulate matter emissions from any stack shall not exceed 150 mg per normal cubic metre. 2.2 Units emitting sulphur dioxide above 40 ppm at the stack outlet must install a flue gas desulphurisation system within 12 months of the limit being exceeded in two consecutive quarterly tests.

3. Monitoring Obligations

3.1 A unit with an annual production capacity above 10,000 tonnes must install a Continuous Emission Monitoring System connected to the Board's central server. 3.2 Monitoring data must be retained for a minimum of 5 years and made available to inspecting officers on demand.

4. Red Category Conditions

4.1 A Red Category unit must undergo a third-party environmental audit once every 2 years. 4.2 A Red Category unit found in violation of Section 2 twice within a 3-year period shall have its consent-to-operate suspended for a minimum of 30 days.

5. Penalties

5.1 Exceeding the particulate matter limit under Section 2.1 shall attract a fine of Rs. 25,000 per day of continued violation after the first inspection. 5.2 Tampering with or disconnecting a Continuous Emission Monitoring System shall attract a fine of up to Rs. 5,00,000 and may result in criminal referral.