
Contents

1	Introduction	3
1.1	Supervised learning	3
1.2	Unsupervised learning	3
1.3	Reinforcement learning	3
2	Statistical Learning	5
2.1	Finite hypothesis class	5
3	Probably Approximately Correct Learning	7
3.1	Generalized loss functions	8

Chapter 1

Introduction

Some kinds of learning include;

1.1 Supervised learning

Given a dataset of pair

$$\mathcal{D}_n = \{(x^{(1)}, y^{(1)}), \dots, (x^{(n)}, y^{(n)})\} \quad (1.1)$$

we wish to establish a relationship between $x^{(i)}$ and $y^{(i)}$. Typically, $x^{(i)} \in \mathbb{R}^d$ is a representation of input, called **feature representation**. Based on the format of the output we can have different types of supervised learning:

Classification when the set of possible values of $y^{(i)}$ is discrete (small finite set). If there two possible values then the classification problem is *binary* otherwise, it is called *multi-class*.

Regression when the set of possible values of $y^{(i)}$ is continuous (or a large finite set). That is, $y^{(i)} \in \mathbb{R}^k$.

1.2 Unsupervised learning

Given a dataset we wish to find some patterns or structures in it. There are several types of unsupervised learning:

Density estimation The data is i.i.d from some distribution $p_X(x)$. The goal is to predict the probability $p_X(x^{(n+1)})$.

Clustering the goal is to find a partitioning of the sample data that groups together samples that are similar. Clustering is sometimes used in density estimation.

Dimensionality reduction the goal is to re-represent the same data in \mathbb{R}^l where $l < d$.

1.3 Reinforcement learning

The goal is to learn a mapping from input values to output values without a direct supervision signal. There is no training set specified *a priori*. Instead, the learning problem is framed as an agent interacting with an environment. Looking at input as our states and output as a

transition between states, we can assign a reward value $r^{(i,j)}$ to each such transition. We aim to find a policy π that maximizes the long-term sum or average of rewards.

Chapter 2

Statistical Learning

A statistical learner needs to know the *domain set*, \mathcal{X} , *label set*, \mathcal{Y} , and a training data set (more like a sequence) $S \subset \mathcal{X} \times \mathcal{Y}$. Given these, learner outputs a *predictor* $h : \mathcal{X} \rightarrow \mathcal{Y}$ which is also called *hypothesis* or *classifier*. We can assume that $\mathcal{D} = \mathbb{P}_{\mathcal{X}}$ is the distribution on \mathcal{X} and there exists a correct function f that for each sampled x output the corresponding label $y = f(x)$. Then the *error* of h is defined as

$$L_{\mathcal{D},f}(h) = \mathbb{P}(h(x) \neq f(x))$$

Since we know neither f nor \mathcal{D} we can not find the exact error. To approximate this error, we can use the *empirical error*.

$$L_S(h) = \frac{|\{i \mid h(x_i) \neq y_i\}|}{|S|}$$

Since S is a representation of the real distribution it makes sense to minimize $L_S(h)$ and expect that $L_{\mathcal{D},f}(h)$ is minimized as well. This is called **empirical risk minimization** or ERM for short. *Overfitting* is one drawback of ERM which arises when S is not fully representative of \mathcal{D} . In that case, predictor though working well on the training data, fails to generalize and mislabels the new data.

One way to avoid overfitting is to restrict possible hypotheses to a class of hypothesis \mathcal{H} . Then

$$ERM_{\mathcal{H}}(S) \in \underset{h \in \mathcal{H}}{\operatorname{argmin}} L_S(h)$$

This way, we increase the bias toward \mathcal{H} and possibly increasing the true error.

2.1 Finite hypothesis class

Suppose \mathcal{D} is finite and assume that there exists a $h^* \in \mathcal{H}$ such that

$$L_{\mathcal{D},f}(h^*) = 0$$

This is called the *realizability assumption*. Furthermore, we can assume that training data are selected independent of each other.

We often assign a probability δ to getting a non-representative training data. $1 - \delta$ is called the *confidence parameter*. We then assign an *accuracy parameter* ϵ where $L_{\mathcal{D},f}(h_S) > \epsilon$ is a failure. We wish to find an upperbound for the probability of getting a training data that results in a failure.

$$\mathbb{P}(S \text{ s.t. } L_{\mathcal{D},f}(h_S) > \epsilon)$$

Let \mathcal{H}_B be the set of bad hypotheses

$$\mathcal{H}_B = \{h \mid L_{\mathcal{D},f}(h) > \epsilon\}$$

and M the set of misleading samples

$$M = \{S \mid \exists h \in \mathcal{H}_B, L_S(h) = 0\}$$

Chapter 3

Probably Approximately Correct Learning

Definition: A hypothesis class \mathcal{H} is PAC learnable if there exist a function $m_{\mathcal{H}} :]0, 1]^2 \rightarrow \mathbb{N}$ and a learning algorithm such that:

- For every $\epsilon, \delta \in]0, 1[$, distribution \mathcal{D} over \mathcal{X} , and labeling function $f : \mathcal{X} \rightarrow \{0, 1\}$
- If the realizable assumption hold with respect to $\mathcal{H}, \mathcal{D}, f$
- Then, when running the algorithm on $m \geq m_{\mathcal{H}}(\epsilon, \delta)$ of i.i.d. samples generated by \mathcal{D} and labeled by f , the algorithm returns a hypothesis h such that

$$\mathbb{P}(L_{\mathcal{D}, f}(h) \leq \epsilon) \geq 1 - \delta$$

Remark 1. The minimal function $m_{\mathcal{H}}$ determines the sample complexity of learning \mathcal{H} .

Corollary 3.1. *Every finite hypothesis class is PAC learnable with sample complexity*

$$m_{\mathcal{H}}(\epsilon, \delta) \leq \left\lceil \frac{\log(|\mathcal{H}|/\delta)}{\epsilon} \right\rceil$$

Let \mathcal{J} be the joint distribution over $\mathcal{X} \times \mathcal{Y}$. Note that, \mathcal{D} is the marginal distribution of \mathcal{J} . Then we can revise the definition for the true error

$$L_{\mathcal{J}}(h) = \mathbb{P}_{(x,y) \sim \mathcal{J}}(h(x) \neq y)$$

Then given \mathcal{J} the best label prediction function is

$$f_{\mathcal{J}}(x) = \begin{cases} 1 & \text{if } \mathbb{P}(y = 1 \mid x) \geq \frac{1}{2} \\ 0 & \text{otherwise} \end{cases}$$

that is, there is no other classifier g with $L_{\mathcal{J}}(g) < L_{\mathcal{J}}(f_{\mathcal{J}})$

Definition: A hypothesis \mathcal{H} is **agnostic PAC learnable** if there exist a function $m_{\mathcal{H}} :]0, 1]^2 \rightarrow \mathbb{N}$ and a learning algorithm such that:

- For every $\epsilon, \delta \in]0, 1[$, distribution \mathcal{J} over $\mathcal{X} \times \mathcal{Y}$
- Then, when running the algorithm on $m \geq m_{\mathcal{H}}(\epsilon, \delta)$ of i.i.d. samples generated by \mathcal{D} and labeled by f , the algorithm returns a hypothesis h such that

$$\mathbb{P}\left(L_{\mathcal{J}}(h) \leq \min_{h'} L_{\mathcal{J}}(h') + \epsilon\right) \geq 1 - \delta$$

3.1 Generalized loss functions

Given any set \mathcal{H} and some domain Z , let l be any function from $\mathcal{H} \times Z$ to \mathbb{R}_+ . We call such functions *loss functions*. We then define the risk function to be

$$L_{\mathcal{Z}}(h) = \mathbb{E}_{\mathcal{Z}}[l(h, z)]$$

where $h \in \mathcal{H}$, and \mathcal{Z} is the distribution on Z . Similarly, the empirical risk over a given sample $S \in Z^m$ is

$$L_S(h) = \frac{1}{m} \sum_{i=1}^m l(h, z_i)$$

Then revising the agnostic PAC learnability definition for general loss function gives

Definition: A hypothesis \mathcal{H} is **agnostic PAC learnable** with respect to Z and a loss function $l : \mathcal{H} \times Z \rightarrow \mathbb{R}_+$, if there exist a function $m_{\mathcal{H}} :]0, 1]^2 \rightarrow \mathbb{N}$ and a learning algorithm such that:

- For every $\epsilon, \delta \in]0, 1[$, distribution \mathcal{Z} over Z
- Then, when running the algorithm on $m \geq m_{\mathcal{H}}(\epsilon, \delta)$ of i.i.d. samples generated by \mathcal{Z} and labeled by f , the algorithm returns a hypothesis h such that

$$\mathbb{P}\left(L_{\mathcal{Z}}(h) \leq \min_{h'} L_{\mathcal{Z}}(h') + \epsilon\right) \geq 1 - \delta$$

Remark 2. In some situations, \mathcal{H} is a subset of a set \mathcal{H}' , and the loss function can be naturally extended to be a function from $\mathcal{H}' \times Z$. In this cases, we may allow the algorithm to return a hypothesis $h' \in \mathcal{H}'$ as long as it satisfies the requirement

$$\mathbb{P}\left(L_{\mathcal{Z}}(h') \leq \min_{h \in \mathcal{H}} L_{\mathcal{Z}}(h) + \epsilon\right) \geq 1 - \delta$$

This is called *representation independent learning*, or *improper learning*.