

**产品规格书****Specification of Product**

V1.0 Page 1/2

产品名称: 6V 18公斤数码舵机 Product Name: 6V 18kg-cm Digital Servo**产品型号** Model No.FT5519M**1.使用环境条件** Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30℃~80℃
1-2	运行温度 Operating Temperature Range	-15℃~70℃

2.测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25℃ ±5℃
2-2	湿度 Humidity range	65%±10%

3.机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 40.2mm B: 20.1mm C: 38.8mm D: 48.0mm E: 10mm
3-2	重量 Weight	56g ±0.2 (1.46oz)
3-3	齿轮类型 Gear type	Titanium Gear
3-6	机构极限角度 Limit angle	210° ±5°
3-7	轴承 Bearing	2 Ball bearings
3-8	出力轴 Horn gear spline	25T
3-9	摆臂 Horn type	Plastic,POM
3-10	外壳 Case	Engineering plastics & Aluminium
3-11	舵机线 Connector wire	300mm ±5 mm
3-12	马达 Motor	Coreless motor
3-13	防水性能 Splash water resistance	Yes

4.电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	4.8V	6V
4-1*	静态电流 Idle current(at stopped)	4.8mA	6.0mA
4-2*	空载速度 No load speed	0.18sec/60°	0.15 sec/60°
4-3*	空载电流 Runnig current(at no load)	125 mA	150 mA
4-4	堵转扭矩 Peak stall torque	15.7 kg.cm	18.5 kg.cm
		218.4 oz.in	257.4 oz.in
4-5	堵转电流 Stall current	1500 mA	2000 mA

Note: "*"definition is average value when the servo runing with no load



FEETECH RC Model Co.,Ltd.

产品规格书

Specification of Product

V1.0 Page 1/2


产品名称: 6V 18公斤数码舵机 Product Name: 6V 18kg-cm Digital Servo

产品型号 Model No.FT5519M

5.控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	Pulse width modification
5-2	放大器类型 Amplifier type	Digital Controller
5-3	脉冲宽度范围 Pulse width range	900~2100μsec
5-4	中立位置 Neutral position	1500 μsec
5-5	旋转角度 Running degree	120° (when 900~2100 μ sec)
5-6	死区宽度 Dead band width	2 μsec
5-7	旋转方向 Rotating direction	Counterclockwise (when 1000~2000 μsec)

6.外形图 The Drawings



A: 40.2mm B: 20.1mm C: 38.8mm D: 48.0mm E: 10mm