



DIESEL & GAS GENERATORS

GUANGDONG BINSHI POWER TECHNOLOGY CO., LTD.

Add: Shangtun Industrial District, Liaobu Town, Dongguan City, China.

Tel: 0086-769-88992216/+86-13971295780

Wuhan Binshi Taiyang New Energy Technology Co.,Ltd

Add: Room 3, 22nd Floor, Building C5, Rongke Zhigu Industrial Project
(PhaseIII), No.555 Culture Avenue, Hongshan District, Wuhan

Tel: 0086-27-59712856/+86-13971295780

Web: <https://www.bs-power.com>

[https:// www.binshipower.com](https://www.binshipower.com)

<https://bspower.en.alibaba.com>



GUANGDONG BINSHI POWER TECHNOLOGY CO.,LTD.

Company Profile

Company : Guangdong Binshi Power Technology Co.,Ltd

Established Year: 2002.

Registered Capital : USD20,000,000.00

Staffs:150.

Business Type: Manufacturer,agent,dealer,Wholesaler.

Business Scope: Diesel generator set, gas generator set, Heavy fuel diesel generator set.

Engine Brand: Cummins, Perkins, MTU, Googol, CAT, Volvo, Liebherr, Mitsubishi,MAN,Yuchai.etc.

Alternator brand: Stamford, Marathon,Leroy somer,Engga,Faraday,etc.

Branches: 15 branches over China.

Production base: Three.



One is the South China production base and after-sales service center which is located in Dongguan city, Guangdong Province which is the famous manufacturing city in the world.




another is located in Middle China, Xiaogan city, Hubei Province.

The Third production base located in the central of China, Ezhou City, Gedian Economic&Technological Development Zone, Which will officially start production in the year of 2023 .

The three production bases cover an area of 66,000 square meters, owns more than 150 employees, in which 58 percent is engineering technicians, and has numbers of senior engineers.

Cooperation relationship: MTU, MAN,Mitsubishi, Perkins, Doosan, Cummins, Marathon, Stamford, Faraday, Leroy somer, etc.

Certificates: OEM Certificates, ISO9001: 2000, ISO14001: 2004 National Testing Report,ect.





Portable Diesel Generator Set

	Single cylinder(Air-cooled)										Dual cylinder(Air-cooled)						Four cylinder (Water-cooled)	
Frequency Hz	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ	60HZ	50HZ
Cont.AC output kW	3.2KW	2.8KW	5KW	4.5KW	6KW	5.5KW	7.5KW	7KW	9KW	8KW	10KW	10KW	12KW	12KW	16KW	15KW	22kw	20KW
Max.AC output kW	3.5KW	3KW	6KW	5kw	7KW	6KW	8.5KW	8kw	10KW	9KW	11KW	11KW	13KW	13KW	17KW	16KW	24kw	22KW
Voltage(A.C) V	110/220、115/230、120/240、127/220、220/380、230/400、240/415																	
ATS is optional																		
Alternator (IP23)																		
Type	Self excitation、constant voltage、field rotating、2 pole generator																	
Stator size mm	φ 190-150							φ190-165	φ204-165	φ245-130			φ245-150		φ270-170			
Phase	Single phase/3-phase																	
Power factor cosφ	1.0/0.8																	
Insulation	F (Stator/rotor)																	
Engine																		
Model	BS178F		BS186F		BS192F		BS198F		BS1100F		BS2V88F		BS292F		BS2V95F		K4100D	
Bore×stroke mm	78X62		86X72		92X75		98X75		100X78		2V-88×72		2L-92×75		2V-95×88		100*115	
Displacements	0.296L		0.418L		0.499L		0.573L		0.655L		0.912L		0.997L		1.247L		3.6L	
Compression ratio	20:01										19.5:1		19.5:1		19:1		19:1	
Combustion system	Direct injection																	
Starting system	Electric starter																	
Lube oil capacity L	1.56										2.7		2.8		3.8		13	
Lubrication oil	CD grade or higher (CD grade or higher (Summer 40CD、15W/40CD , Winter30CD、10W/30CD))																	
Fuel oil	Summer : GB 252-2000 Premium or first grade 0, 10 light diesel oil, Winter: GB 252-2000 Premium or first grade light diesel 0, -10, -20, -35																	
Generator Set																		
Fuel tank capacity L	13										26						100	
Fuel consunmption L/h	≤2.3									≤2.6	≤3.9	≤4.5	≤4.1	≤4.7	≤5.5	≤6.2	≤251g/kw.h	
Noise level at 7m dB(A)	71 ~ 73										71 ~ 73		72 ~ 74		73 ~ 75		73 ~ 75	
Product dimensions L×W×H) mm	940X545X770								970X555X725		1250×650×760				1300×650×760		1980x890x1190	
Packing dimension L×W×H)	950X555X780								980X560X765		1300×700×880				1350×700×880		2000x900x1200	
N.W/G.W kg	170/175								180/190		280/300		300/320		320/340		840/850	



Dual Fuel Generator Set

Model	BS2-D	BS2.8-D	BS5-D	BS6-D	BS7.5-D	BS8.5-D	BS10-D	BS12-D	BS15-D	BS18-D	BS20-D	BS25-D	BS30-D	
	BS2.2-D	BS3-D	BS5.3-D	BS6.4-D	BS8-D	BS9-D	BS10.5-D	BS13.5-D	BS16-D	BS19-D	BS21-D	BS26-D	BS32-D	
Rated Voltage (V)	110-440													
Rated Frequency(HZ)	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	
Rated power(KW)	2/2.2	2.8/3	5/5.3	6/6.4	7.5/8	8.5/9	10/10.5	12/13.5	15/16	18/19	20/21	25/26	30/32	
Power factor	1/0.8													
Noise (dB)	75	75	75	75	75	≤90								
Weight(kg)	41	44	83	83	86	93	93	93	93	300	300	420	420	
Dimension(mm)	650x450/60x450		705x555x585				1010x630x700	1010x630x700	1050x610x700	1310x680x810		1240x780x980		
Engine technical data														
Type	single cylinder, four stroke, Overhead valve						dual cylinder , four stroke			four cylinder four stroke water cooled				
Displacement (mL)	196	212	389	420	450	624	725	725	999	861	861	1500	1500	
Compression ratio	8.5:1	8.5:1	8.0:1	8.0:1	8.0:1	8.0:1	8.0:1	8.0:1	8.0:1	9.5:1	9.5:1	11:01	11:01	
Bore × Stroke	68x54	70x55	88x64	90x66	92x68	77x67	83x67	83x67	90x78.5	63.5x73.5	63.5x73.5	77.4x79.5	77.4x79.5	
Lubrication capacity (L)	0.6	1.1	1.1	1.1	1.1	1.9	1.9	1.9	2.75	2.75	2.75	2.75	2.75	
Fuel	natural gas/LPG/LNG/Non-sulfur biogas or 92#/high level clear gasoline													
Method of ignition	Transistor magnet ignition (non-contact)													
Voltage Regulator	Automatic Voltage Regulation(AVR)													
Cooling method	air cooling									water cooling				
Alternator technical data														
Exciting Type	Brushless, self-exciting													
Insulation class	F													
Voltage regulation without loading	≥±5%													
Steady state voltage deviation	≤±2%													
gasoline Consumption:0.4L / 1KW.h, Natural gas : 1m³/ 3KW.h ,biogas :1m³/2.5KW.h														





Water Cooling Silent Diesel Generator Set

Model	BS6.5J	BS7.5J	BS8J	BS9.5J	BS10J	BS11J	BS11.5J	BS7J	BS8.5J	BS9J	BS10.5J	BS11J
Rated Voltage	110-440V											
Phase	Single/three phase											
Rated Frequency(HZ)	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	60Hz	60Hz	60Hz	60Hz	60Hz
Rated power(KW)	6.5kw	7.5kw	8kw	9.5kw	10kw	11kw	11.5kw	7kw	8.5kw	9kw	10.5kw	11kw
Max power(KW)	7kw	8.5kw	9kw	11kw	11kw	12kw	13kw	7.5kw	9.5kw	10kw	12kw	12kw
Power factor	1/0.8											
RPM	3000rpm							3600rpm				
Noise (dB)	66dB(A)/7m		67dB(A)/7m	75-78dB(A)/7m				66dB(A)/7m		75-78dB(A)/7m		
Weight(kg)	166	167	222	222	225	225	225	166	167	167	222	225
Dimension(mm)	920×550×850			1100×650×930				920×550×850			1100×650×930	
Engine technical data												
Type	single cylinder, four stroke, Overhead valve											
Starting system	electrical start											
Displacement (cc)	498	531	667	667	718	718	718	498	531	667	718	718
Bore × Stroke	68x54	70x55	88x64	92x68				77x67	83x67	83x67	90x78.5	63.5x73.5
Fuel grade	0#--10#											
Fuel tank capacity (L)	16	16	16	25	25	25	25	16	16	25	25	25
Fuel tank refill cosuming period @ 100% load	8 hours											
Water tank capacity(L)	26	26	26	30	30	30	30	26	26	30	30	30
water tank refill cosuming period @ 100% load (H)	9 hours											
Lubrication capacity	1.65	1.65	2.1	2.1	2.1	2.1	2.1	1.65	1.65	2.1	2.1	2.1
Voltage Regulator	Automatic Voltage Regulation(AVR)											
Cooling method	water cooling											
other												
Alternator	Brushless, self-exciting, 100% copper											
AC overload protection	Fuseless Circuit Breaker											
Dc protection	No fuse overcurrent protector + fuse breaker											
Low water level protection	Mechanical sensor											
Low oil pressure protection	Mechanical sensor											
Voltmeter	Electronic display											





Marine Use Diesel Generator Set

genset model number			BS5.5J/BS6.5J		BS8J/BS9J		BS12J/BS13J		BS15J/BS16J		BS20J/BS22J		BS28J/BS30J		
genset	rated frequency	HZ	50	60	50	60	50	60	50	60	50	60	50	60	
	prime power	KVA	5.5	6.5	8	9	12	13	15	16	20	24	28	30	
		KW	5.5	6.5	8	9	12	13	15	16	20	24	28	30	
	standby power	KVA	6	7	9	10	13	15	16	18	22	26	30	33	
		KW	6	7	9	10	13	15	16	18	22	26	30	33	
	rated voltage	V	115/230	120/240	115/230	120/240	115/230	120/240	115/230	120/240	115/230	120/240	115/230	120/240	
	rated current	A	47.8/23.9	56.5/28.3	74/37	87.6/43.8	104/52.2	125/62.5	130/65.2	141.7/70.8	173.9/87	200/100	243.5/121.7	300/150	
rated speed	r/min	3000	3600	1500	1800	1500	1800	1500	1800	1500	1800	1500	1800		
alternator	pole		4		4		4		4		4		4		
	phase		single		single		single		single		single		single		
	Excitation mode		Brush self-excited constant voltage (with AVR)		Brushless self-excited constant voltage (with AVR)		Brushless self-excited constant voltage (with AVR)		Brushless self-excited constant voltage (with AVR)		Brushless self-excited constant voltage (with AVR)		Brushless self-excited constant voltage (with AVR)		
	power factor	COSΦ	1		1		1		1		1		1		
	Insulation level		F		H		H		H		H		H		
engine	cylinder		Single cylinder in-line, four stroke, direct injection, water-cooled		3 cylinder in-line, four stroke, direct injection, water-cooled		4 cylinder in-line, four stroke, direct injection, water-cooled		4 cylinder in-line, four stroke, direct injection, water-cooled		4 cylinder in-line, four stroke, direct injection, water-cooled		4 cylinder in-line, four stroke, direct injection, water-cooled		
	Bore & stroke	mm	92×75		78×85		98×105		98×105		87×103		87×103		
	total displacement	L	0.499		1.218		3.17		3.17		3.349		3.349		
	Compression ratio		19.5 : 1		18.2 : 1		18.2 : 1		18.2 : 1		18.5 : 1		18.5 : 1		
	rated power	KW	7.6	8.6	12.3	13.2	20	22	20	22	27.45	32.85	36	48	
	coolant capacity(engine)	L	4		5		6		6		11		11		
	Lubrication method		combined force-feed and splash lubrication												
	lube oil level		Class CD or above, SAE 10W-30, 15W-40												
	lube oil capacity	L	1.65		6.9		8.5		8.5		9.5		9.5		
	starting method		12V electric start												
	starter motor capacity	V-KW	12V 1.2KW		12V 1.4KW		12V 1.4KW		12V 1.4KW		12V 2.8KW		12V 2.8KW		
	consumption rate	g/KW.h	298		240		215		215		215	220	215	220	
	fuel type		Diesel: 0# (summer)-10# (winter)-35# (severe cold)												
genset	control panel			Smartgen4010											
	output	socket	without		without		without		without		without		without		
		terminal	with		with		with		with		with		with		
	noise level(@7m)	dB(A)	58		62		62		62		64		64		
	genset size	mm	760*570*650		1080*650*740		1230*700*850		1230*700*850		1360*720*850		1460*720*850		
	net weight	kg	170		345		485		485		670		680		

