

66

Name Dhoruba Chowdhury.

Midterm Examination 2
CHE 230
Molecular Systems in Chemical Engineering

UIC Chemical Engineering Department

04/27/2026

Time: 70 minutes

Honor Code: As a commitment to the personal, academic, and professional standards upheld by the Honors College, as a student, I hereby pledge to respect, preserve, and promote the Honor Code of Conduct during my entire tenure at the Honors College. I agree to uphold high ethical principles in all personal, academic, and professional endeavors related to the Honors College and beyond, and to always be mindful of being a representative of the Honors College and the UIC community


Signature 

Date 04/27/26

Part A: Phases

1. A Lead-Tin (Pb-Sn) alloy with an overall composition of 40 wt% Sn is slowly cooled from the liquid state to just below the eutectic temperature of 183°C . At this temperature, the maximum solid solubility of Sn in the α phase is 18.3 wt% Sn, the maximum solid solubility of Pb in the β phase is 97.8 wt% Sn, and the eutectic composition is 61.9 wt% Sn.

- Determine the mass fractions of the primary α microconstituent and the eutectic microconstituent. (6 points)
- Determine the mass fraction of the total α phase in the alloy. (4 points)



$$a) w_{\alpha} = \frac{C_{\beta} - C_0}{C_{\beta} - C_{\alpha}}$$

$$= \frac{97.8 - 61.9}{97.8 - 18.3} = 0.452$$

$$C_{\alpha} = 18.3 \text{ wt.}\%$$

$$C_{\beta} = 97.8 \text{ wt.}\%$$

$$C_0 = 61.9 \text{ wt.}\%$$

$$C = 40$$

$$w_{\beta} = \frac{C_0 - C_{\alpha}}{C_{\beta} - C_{\alpha}} = \frac{61.9 - 18.3}{97.8 - 18.3} = 0.548$$

$$w_0 = \frac{C_0 - C}{C_0 - C_{\alpha}} = \frac{61.9 - 40}{61.9 - 18.3} = 0.502$$

$$b) \text{ mass fraction of total } \alpha = \frac{\alpha}{\alpha + L}$$

$$= \frac{18.3}{18.3 + 40} = 0.314$$

2. Derive the lever rule (8 points)

$$w_{\alpha} = \frac{C_L - C_0}{C_L - C_{\alpha}}$$

$$C_L w_{\alpha} - C_{\alpha} w_{\alpha} = 1$$

5

8

3. You are analyzing a binary Copper-Silver (Cu-Ag) alloy system at a constant atmospheric pressure of 1 atm.

a. Write down the condensed Gibbs Phase Rule equation. (3 points)

b. The alloy is currently exactly at its eutectic temperature and eutectic composition, and it is in the process of solidifying. Calculate the degrees of freedom (F) for the system at this exact moment. (7 Points)

$$a) F = C - P + 2$$

$$b) \text{ components} = 2$$

$$P_{\text{phase}} \rightarrow \text{in the process of solidifying} = 2$$

$$F = C - P + 1 \text{ [for binary]}$$

$$= 2 - 2 + 1$$

$$= 1$$

6

Part B: Thermal, Electrical, Magnetic, and Optical Properties

29

- Identify the terms defined in the table below from the following list: (8 points)

Word bank

heat capacity	temperature coefficient of resistance	ferrimagnetic
specific heat	permeability	ferromagnetic
thermal expansion	magnetic susceptibility	photon
thermal conductivity	magnetic induction	refractive index
electrical resistivity	magnetic moments	total internal reflectance
electrical conductivity	diamagnetic	opaque
dielectric strength	paramagnetic	transparent
thermoelectric effect		translucent

Terms	Definition
Heat capacity	The amount of heat required to raise the temperature of a material by one degree.
Thermal expansion	The tendency of a material to expand when heated due to increased atomic vibrations
ferromagnetic	Materials with opposing magnetic moments of unequal strength, leading to net magnetization
Permeability	A dimensionless quantity that describes how much a material will become magnetized in response to an external magnetic field
photon	A quantum of light or electromagnetic radiation, carrying energy that depends on its wavelength or frequency.
total internal reflectance	A measure of how much light slows down and bends when entering a material from another medium
opaque	A material that allows light to pass through but scatters it, preventing clear visibility of objects on the other side

5

dielectric strength

The maximum electric field a material can withstand without breaking down and becoming conductive.

2. A brass rod is to be used in an application requiring its ends to be held rigid. If the rod is stress-free at room temperature (20°C or 68°F), what is the maximum temperature to which the rod may be heated without exceeding a compressive stress of 172 MPa ($25,000\text{ psi}$)? (6 points)

Assume the following properties for brass:

Modulus of elasticity (E) = 100 GPa ($14.6 \times 10^6\text{ psi}$)

Linear coefficient of thermal expansion (α) = $20.0 \times 10^{-6}\text{ }^{\circ}\text{C}^{-1}$ ($11.1 \times 10^{-6}\text{ }^{\circ}\text{F}^{-1}$)

$$\sigma = E\alpha\Delta T$$

$$\Rightarrow 172 = 100 \times 10^3 \times 20.0 \times 10^{-6} (T_f - 20)$$

$$\Rightarrow T_f - 20 = \frac{172}{2}$$

$$\Rightarrow T_f = (86 + 20)^{\circ}\text{C} = 106^{\circ}\text{C}$$

$$\sigma = 172\text{ MPa}$$

$$E = 100 \times 10^3\text{ MPa}$$


$$\alpha = 20.0 \times 10^{-6}\text{ }^{\circ}\text{C}^{-1}$$

$$T_0 = 20^{\circ}\text{C}$$

$$T_f = ?$$

3. A photon emitted by a specific light source possesses an energy of $4.42 \times 10^{-19}\text{ J}$.
- Compute the frequency (f) and the wavelength (λ) of this photon in meters. (5 points)
 - Convert your calculated wavelength into nanometers (nm). Using a standard visible light color spectrum chart, determine what color this light appears to the human eye. (3 points)

(Constants: Speed of light, $c = 3 \times 10^8\text{ m/s}$; Planck's constant, $h = 6.63 \times 10^{-34}\text{ Js}$)



i)

$$E = h\nu$$

$$= \frac{hc}{\lambda}$$

$$\Rightarrow \lambda = \frac{hc}{E} = \frac{6.63 \times 10^{-34} \text{ J.s} \times 3 \times 10^8 \text{ ms}^{-1}}{4.42 \times 10^{-19} \text{ J}}$$

$$= \underline{4.5 \times 10^{-7} \text{ m}}$$

$$E = hf$$

$$\Rightarrow f = \frac{E}{h} = \underline{6.67 \times 10^{14} \text{ Hz}}$$

$$E = 4.42 \times 10^{-19} \text{ J}$$

$$h = 6.63 \times 10^{-34} \text{ J.s}$$

$$c = 3 \times 10^8 \text{ ms}^{-1}$$

$$\text{ii) } \lambda = (4.5 \times 10^{-7}) \times 10^9 \text{ nm}$$

$$= 450 \text{ nm} \quad [1 \text{ m} = 10^9 \text{ nm}]$$

Color is Blue

4. The magnetic flux density within a bar of some material is 0.435 tesla at an H field of 3.44 $\cdot 10^5$ A/m. Compute the following for this material: (a) the magnetic permeability, and (b) the magnetic susceptibility. (c) What type(s) of magnetism would you suggest is displayed by this material? Why? $\mu_0 = 4\pi \times 10^{-7} \text{ T.m/A}$ (10 points)

$$\text{a) } B = \mu H$$

$$\Rightarrow \mu = \frac{B}{H} = \frac{0.435}{3.44 \times 10^5} = 1.265 \times 10^{-6} \text{ T.m/A}$$

$$B = 0.435 \text{ tesla}$$

$$H = 3.44 \times 10^5 \text{ A/m}$$

$$\text{b) } \mu_r = \mu / \mu_0 = 1.265 \times 10^{-6} / 4\pi \times 10^{-7} = 1.007$$

$$\therefore \text{ susceptibility } \chi = \mu_r - 1 = +0.007$$

c) The susceptibility of the magnet is positive but very small value, According to magnetic explanations this falls into paramagnetic characteristics.

Part C: Polymers, Ceramics

10


Word Bank

Natural	Atactic
Thermoplastic	Isotactic
Branched	Semi-Synthetic
Synthetic	Crosslinked
Syndiotactic	Amorphous
Crystalline	Thermoset
Semi-Crystalline	Linear

1. Select the word that matches the definition listed below related to polymer classification (4 points).

Polymer Classification	Meaning
synthetic +	Polymers derived from nature but chemically modified
Branched +	Polymers that <u>undergo permanent deformation</u> after heating
semi synthetic +	A polymer <u>with</u> regular or irregular attachments of side chains to the main polymer's backbone chain
Amorphous. +	A polymer or polymer structure in which the repeating units have no regular <u>stereochemical configuration</u> .

2. Sketch a stress-strain curve to highlight the behavior of brittle polymers, plastics, and elastomers during tensile testing (8 points)



3. You are evaluating the mechanical stability of a brittle ceramic catalyst support for a packed-bed reactor. To determine its flexural strength (σ), you perform a center-point loading test with a support span of $L = 18 \text{ mm}$. The initial tests are performed on rectangular bar specimens with width $b = 6 \text{ mm}$ and height $d = 4 \text{ mm}$.

Batch A fractures at an applied force $F = 120 \text{ N}$.

Batch B fractures at an applied force $F = 145 \text{ N}$.

To optimize gas flow, the reactor design team wants to switch to cylindrical pellets with radius $R = 3.5 \text{ mm}$, tested over the same 18 mm span.

- Calculate the flexural strength (σ) of each batch from the rectangular specimen tests.
- Using the flexural strength from each batch, determine the maximum applied force (F) the cylindrical pellet can withstand before fracturing: (10 points)

$$a) \sigma_{f1} = \frac{3F_1L}{(2bd)^2} = \frac{3 \times 120 \text{ N} \times 18 \times 10^{-3} \text{ m}}{(2 \times 6 \times 10^{-3} \text{ m} \times 4 \times 10^{-3} \text{ m})^2} \quad \text{N/m}^2$$

$$= 135000 \text{ N/m}^2$$

$$\sigma_{f2} = \frac{3F_2L}{2bd^2} = 163125 \text{ N/m}^2$$

$$\sigma_{f2} > \sigma_{f1}$$

$$F_1 = 120 \text{ N}$$

$$F_2 = 145 \text{ N}$$

$$L = 18 \times 10^{-3} \text{ m}$$

$$b = 6 \times 10^{-3} \text{ m}$$

$$d = 4 \times 10^{-3} \text{ m}$$

$$R = 3.5 \times 10^{-3} \text{ m}$$

$$b) \sigma_{f1} = \frac{FL}{\pi R^3} = \frac{120 \times 18 \times 10^{-3}}{\pi \times (3.5 \times 10^{-3})^3}$$

$$= 16.04 \text{ MPa}$$

$$\sigma_{f2} = \frac{145 \times 18 \times 10^{-3}}{\pi (3.5 \times 10^{-3})^3}$$

$$= 19.377 \text{ MPa}$$

Part D: Introduction to Macromolecules and Nanoscale Systems

1. What is the difference between the top-down and bottom-up methods? (5 points)

2. You are developing a wearable biosensor to detect abnormal blood glucose levels in diabetic patients. The sensor's electrical circuit relies on an ultra-thin sheet of graphene (a single atomic layer of carbon). When glucose molecules bind to the graphene surface, they alter its electrical conductivity, triggering an alert.

a. Classify the single-atom-thick graphene sheet by its nanomaterial dimension (0D, 1D, 2D, or 3D). (3 points)

~~0D~~

~~1D: Nanowires, nanorods.~~

2D: ultra-thin graphene sheet.

~~3D~~

b. To manufacture this single-layer graphene sheet atom-by-atom to ensure perfect precision, would you choose a "top-down" or "bottom-up" synthesis technique? Why? (5 points)

bottom up ~~meth~~ technique, because it will deliver our expected dimension with more control and ~~precision~~ accuracy.

c. Glucose is a simple monosaccharide. When the human body has excess glucose, it stores it by linking the molecules together into a large polysaccharide called glycogen. What specific chemical reaction links these glucose molecules together, and what small molecule is released as a byproduct during this process? (5 points)

Extra Credit

1. How many known amino groups are there? (3 points)

9

2. In the special talk, what deposition method did Dr. Kim use for the MoS_2 ? (2 points)

~~laser~~

