

Name:

Lucia Hernandez

We are separating a mixture of ethane (C2), propane (C3), n-butane (C4), and n-pentane (C5) in a distillation column operating at 5.0 atm. The column has a total condenser and a partial reboiler. The feed flow rate is 1000 kmol/h. The feed is a saturated liquid. Feed is 10 mol% ethane, 30 mol% propane, 50 mol% n-butane, and 10 mol% n-pentane. K values are $K_{C2}=4.6$, $K_{C3}=1.37$, $K_{C4}=0.35$, and $K_{C5}=0.10$. A 99.5% recovery of propane is desired in the distillate. A 99.0% recovery of n-butane is desired in the bottoms.

- 1) (2pts) Identify each component such as LNK, LK, NK, HK, or HNK

ethane (C2) LNK
propane (C3) LK
n-butane (C4) HK
n-pentane (C5) HNK

- 2) (2pts) Write down fractional recovery (e.g., $FR_{i,D} = x_{i,D} \cdot D / F \cdot z_i$) of ethane, propane, n-butane, and n-pentane both in distillate and bottom

	Distillate	Bottom
Ethane	$D \cdot x_{C2,D} = F \cdot z_{C2} = 100$	$B \cdot x_{C2,B} = 0$
Propane	$D \cdot x_{C3,D} = 298.5$	$B \cdot x_{C3,B} = 1.5$
Butane	$D \cdot x_{C4,D} = 5$	$B \cdot x_{C4,B} = 495$
Pentane	$D \cdot x_{C5,D} = 0$	$B \cdot x_{C5,B} = 100$

- 3) (3pts) Calculate the distillate flow rate (D).

$$D = \sum (D \cdot x_{i,D}) = 100 + 298.5 + 5 + 0 = 403.5 \text{ kmol/h}$$

- 4) (3pts) Find N_{min} from the Fenske equation (hint: use the relationship between α and K value)

$$N_{min} = \frac{\ln \left[\frac{(FR_A)_{dist} (FR_B)_{bot}}{[1 - (FR_A)_{dist}] [1 - (FR_B)_{bot}]} \right]}{\ln \alpha_{AB}}$$

where, $(FR_A)_{dist}$ = fractional recovery of LK in distillate (i.e., A=LK)

$(FR_B)_{bot}$ = fractional recovery of HK in distillate or bottom (i.e., B=HK)

α_{AB} = the relative volatility

$$N_{min} = \frac{\ln \left[\frac{0.995 \cdot 0.99}{(1 - 0.995)(1 - 0.99)} \right]}{\ln 3.91} = \frac{9.888}{1.36} = 7.25$$

≈ 7 stages

$$\alpha_{AB} = \frac{K_A}{K_B}$$

$$\alpha_{LK-HK} = \frac{K_{LK}}{K_{HK}} = \frac{1.37}{0.35} = 3.91$$