

KMeans Clustering — Quiz

Topic: K-Means | Total Questions: 16

1) How many columns contain null data?

- a) 5
- b) 3
- c) 0
- d) 4

2) How many status ids are unique?

- a) 3984
- b) 6503
- c) 4509
- d) 6997

3) How many video posts have been made for live selling?

- a) 2334
- b) 2345
- c) 1827
- d) 2871

4) How many likes have been given to the photo posted on 4/19/2018 at 22:26?

- a) 293
- b) 379
- c) 359
- d) 493

5) How many total shares were made for the video post posted on 7/15/2017 at 10:52?

- a) 153
- b) 173
- c) 139
- d) 167

6) What does K-Means do?

- a) Finds relationships between dependent and independent data
- b) None of the above
- c) Group similar elements
- d) Finds probability of elements

7) What output will the below code give?

```
colour=['red','blue','green','yellow','cyan']  
for i in range(0,len(colour)):  
plt.scatter(X[df['Clusters(5)']==i], Y[df['Clusters(5)']==i], s=10, c=colour[i])  
plt.scatter(k.cluster_centers_[0], k.cluster_centers_[1], color='black')
```

- a) Gives 3 clusters
- b) Gives 5 clusters
- c) Gives 2 clusters
- d) Gives 5 clusters with midpoints

8) Which method is used to decide the optimal number of clusters in K-Means clustering?

- a) None
- b) Elbow method
- c) Append method
- d) Evaluation Method

9) In what cases is K-Means used?

- a) Clustering
- b) Regression
- c) Classification
- d) None of the above

10) For exploration, do we use Hierarchical Clustering?

- a) FALSE
- b) TRUE

11) Which is the function used for K-Means?

- a) heatmap
- b) None of the above
- c) KMeans
- d) Clusters

12) How to train the K-Means model?

- a) train_test_split()
- b) train()
- c) predict()
- d) fit()

13) What does random_state do?

- a) All of the above
- b) Shows states
- c) Checks and validates data when code is run multiple times
- d) Used to split data

14) How to check which data is placed under which Cluster?

- a) Cluster_
- b) Labels_
- c) None of the above
- d) Inertia_

15) Why do we perform Standard Scalar?

- a) Standardizing the data
- b) None of the above
- c) Removing standard values
- d) Adding standard values

16) Perform the following operations on the dataset:

- Drop Status id and status published column.
- Use a label encoder to encode the status type column.
- Standardize the data using min-max scalar.
- Create a K-Means model for 2 clusters.

From the above model, what is the inter-cluster variance of the model?
