

> My courses > Software Model Exam > 23 March - 29 March > Software mock exam II

Question 8

Not yet answered

Marked out of 1.00

Flag question

A hash table of length 10 uses open addressing with hash function $h(k)=k \bmod 10$, and linear probing. After inserting 6 values into an empty hash table, the table is as shown below. Which one of the following choices gives a possible order in which the key values could have been inserted in the table?

0	
1	
2	42
3	23
4	34
5	52
6	46
7	33
8	
9	

- ☐ a. 46, 42, 34, 52, 23, 33
- ☐ b. 42, 46, 33, 23, 34, 52
- ☐ c. 34, 42, 23, 52, 33, 46
- ☐ d. 46, 34, 42, 23, 52, 33

Quiz navigation

1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22
23	24	25	26	27	28	29	30	31	32	33
34	35	36	37	38	39	40	41	42	43	44
45	46	47	48	49	50	51	52	53	54	55
56	57	58	59	60	61	62	63	64	65	66
67	68	69	70	71	72	73	74	75	76	77
78	79	80	81	82	83	84	85	86	87	88
89	90	91	92	93	94	95	96	97	98	99
100										

Finish attempt ...

Previous page

Next page