



WOLLO University

Department of software engineering

Exit multiple choice questions for

Fundamental networking

Prepared by:

@Neyatibeb

KOMBOLCHA, Ethiopia

2015 E.C

- ☐ A. 32 bits
- ☐ B. 128 bytes
- ☐ C. 64 bits
- ☐ D. 128 bits

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

An IPv6 address is 128 bits long.

2.

What flavor of Network Address Translation can be used to have one IP address allow many users to connect to the global Internet?

- ☐ A. NAT
- ☐ B. Static
- ☐ C. Dynamic
- ☐ D. PAT

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

Port Address Translation (PAT) allows a one-to-many approach to network address translation.

3.

What are the two main types of access control lists (ACLs)?

1. Standard
2. IEEE
3. Extended
4. Specialized



A. 1 and 3



B. 2 and 4



C. 3 and 4



D. 1 and 2

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

Standard and extended access control lists (ACLs) are used to configure security on a router.

4.

What command is used to create a backup configuration?

Department of software engineering

- A. ☐ *copy running backup*
- B. ☒ *copy running-config startup-config*
- C. ☐ *config mem*
- D. ☐ *wr mem*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

The command to back up the configuration on a router is *copy running-config startup-config*.

5.

You have 10 users plugged into a hub running 10Mbps half-duplex. There is a server connected to the switch running 10Mbps half-duplex as well. How much bandwidth does each host have to the server?

- ☐
- A. ☐ 100 kbps
- ☐
- B. ☐ 1 Mbps
- ☐
- C. ☐ 2 Mbps
- ☒
- D. ☐ 10 Mbps

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

Each device has 10 Mbps to the server.

6.

Which WLAN IEEE specification allows up to 54Mbps at 2.4GHz?

- ☐ A. A
- ☐ B. B
- ☐ C. G
- ☐ D. N

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

IEEE 802.11B is 2.4GHz, but with a maximum of only 11Mbps. IEEE 802.11G is in the 2.4GHz range, with a top speed of 54Mbps.

7.

Which of the following is the valid host range for the subnet on which the IP address 192.168.168.188 resides?

- ☐ A. 192.168.168.129-190
- ☐ B. 192.168.168.129-191
- ☐ C. 192.168.168.128-190



D. 192.168.168.128-192

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

$256 - 192 = 64$. $64 + 64 = 128$. $128 + 64 = 192$.

The subnet is 128, the broadcast address is 191, and the valid host range is the numbers in between, or 129-190.

8.

To back up an IOS, what command will you use?

- A. ☐ *backup IOS disk*
- B. ☐ *copy ios tftp*
- C. ☐ *copy tftp flash*
- D. ☐ *copy flash tftp*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

The command *copy flash tftp* will prompt you to back up an existing IOS in flash to a TFTP host.

9.

What protocol does PPP use to identify the Network layer protocol?

- A. ☐ NCP
- B. ☐ ISDN

- ☐ C. HDLC

- ☐ D. LCP

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

Network Control Protocol is used to help identify the Network layer protocol used in the packet.

10.

Which of the following commands will allow you to set your Telnet password on a Cisco router?

- ☐ A. `line telnet 0 4`
- ☐ B. `line aux 0 4`
- ☐ C. `line vty 0 4`
- ☐ D. `line con 0`

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

The command `line vty 0 4` places you in a prompt that will allow you to set or change your Telnet password.

- ☐ A. IP
- ☐ B. TCP
- ☐ C. UDP



D. ARP

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

User Datagram Protocol is a connection network service at the Transport layer, and DHCP uses this connectionless service.

12.

Which command is used to determine if an IP access list is enabled on a particular interface?

- A. ☐ *show access-lists*
- B. ☐ *show interface*
- C. ☐ *show ip interface*
- D. ☐ *show interface access-lists*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

The *show ip interface* command will show you if any outbound or inbound interfaces have an access list set.

13.

Where is a hub specified in the OSI model?

- A. ☐ Session layer
- B. ☐ Physical layer



C. Data Link layer



D. Application layer

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

Hubs regenerate electrical signals, which are specified at the Physical layer.

14.

What does the *passive* command provide to dynamic routing protocols?



A. Stops an interface from sending or receiving periodic dynamic updates.



B. Stops an interface from sending periodic dynamic updates but not from receiving updates.



C. Stops the router from receiving any dynamic updates.



D. Stops the router from sending any dynamic updates.

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

The *passive* command, short for passive-interface, stops regular updates from being sent out an interface. However, the interface can still receive updates.

15.

Which protocol is used to send a destination network unknown message back to originating hosts?

- ☐ A. TCP
- ☐ B. ARP
- ☐ C. ICMP
- ☐ D. BootP

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

ICMP is the protocol at the Network layer that is used to send messages back to an originating router.

16.

How often are BPDUs sent from a layer 2 device?

- ☐ A. Never
- ☐ B. Every 2 seconds
- ☐ C. Every 10 minutes
- ☐ D. Every 30 seconds

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

Every 2 seconds, BPDUs are sent out from all active bridge ports by default.

17.

How many broadcast domains are created when you segment a network with a 12-port switch?

- ☐ A. 1
- ☐ B. 2
- ☐ C. 5
- ☐ D. 12

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

By default, switches break up collision domains but are one large broadcast domain.

18.

What does the command *routerA (config) #line cons 0* allow you to perform next?

- ☐ A. Set the Telnet password.

Department of software engineering

- ☐ A. Shut down the router.
- ☐ B. Shut down the router.
- ☐ C. Set your console password.
- ☐ D. Disable console connections.

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

The command *line console 0* places you at a prompt where you can then set your console user-mode password.

19.

Which router command allows you to view the entire contents of all access lists?

- ☐ A. *show all access-lists*
- ☐ B. *show access-lists*
- ☐ C. *show ip interface*
- ☐ D. *show interface*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

To see the contents of all access lists, use the *show access-lists* command.

20.

Which class of IP address has the most host addresses available by default?



A. A



B. B



C. C



D. A and B

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

Class A addressing provides 24 bits for host addressing



A. 1



B. 2



C. 5



D. 12

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

You should have only one root bridge per network.

22.

What PPP protocol provides dynamic addressing, authentication, and multilink?

- ☐ A. NCP
- ☐ B. HDLC
- ☐ C. LCP
- ☐ D. X.25

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

Link Control Protocol in the PPP stack provides dynamic addressing, authentication, and multilink.

23.

What is a stub network?

- ☐ A. A network with more than one exit point.
- ☐ B. A network with more than one exit and entry point.
- ☐ C. A network with only one entry and no exit point.



- D. A network that has only one entry and exit point.

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

Stub networks have only one connection to an internetwork. Only default routes can be set on a stub network or network loops may occur.

24.

If your router is facilitating a CSU/DSU, which of the following commands do you need to use to provide the router with a 64000bps serial link?

- A. ☐ *RouterA (config) #bandwidth 64*
B. ☐ *RouterA (config-if) #bandwidth 64000*
C. ☐ *RouterA (config-if) #clock rate 64*
D. ☐ *RouterA (config-if) #clock rate 64000*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

The *clock rate* command is two words, and the speed of the line is in bps.

25.

Which one of the following is true regarding VLANs?



- A. Two VLANs are configured by default on all Cisco switches.

- ☐
- B. VLANs only work if you have a complete Cisco switched internetwork. No off-brand switches are allowed.
- ☐
- C. You should not have more than 10 switches in the same VTP domain.
- ☐
- D. VTP is used to send VLAN information to switches in a configured VTP domain.

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

Switches do not propagate VLAN information by default; you must configure the VTP domain. VLAN Trunking Protocol (VTP) is used to propagate VLAN information across a trunk link.

26.

What does a VLAN do?

- ☐
- A. Acts as the fastest port to all servers.
- ☐
- B. Provides multiple collision domains on one switch port.
- ☐
- C. Breaks up broadcast domains in a layer 2 switch internetwork.
- ☐
- D. Provides multiple broadcast domains within a single collision domain.

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

VLANs break up broadcast domains at layer 2.

27.

What is the main reason the OSI model was created?

- ☐
- A. To create a layered model larger than the DoD model.
- ☐
- B. So application developers can change only one layer's protocols at a time.
- ☐
- C. So different networks could communicate.
- ☐
- D. So Cisco could use the model.

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

The primary reason the OSI model was created was so that different networks could inter-operate.

28.

How many collision domains are created when you segment a network with a 12-port switch?

- ☐
- A. 1
- ☐
- B. 2



C. 5



D. 12

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

Layer 2 switching creates individual collision domains.

29.

What command will display the line, protocol, DLCI, and LMI information of an interface?



A. *sh pvc*



B. *show interface*



C. *show frame-relay pvc*



D. *show run*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

The *show interface* command shows the line, protocol, DLCI, and LMI information of an interface.

30.

Which protocol does Ping use?



A. TCP

- ☐ A. ARP
- ☐ B. ARP
- ☐ C. ICMP
- ☐ D. BootP

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option C

Solution:

ICMP is the protocol at the Network layer that is used to send echo requests and replies.

1.

Which command is used to upgrade an IOS on a Cisco router?

- ☐ A. `copy tftp run`
- ☐ B. `copy tftp start`
- ☐ C. `config net`
- ☐ D. `copy tftp flash`

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

The `copy tftp flash` command places a new file in flash memory, which is the default location for the Cisco IOS in Cisco routers.

32.

If you wanted to delete the configuration stored in NVRAM, what would you type?

- A. ☐ *erase startup*
- B. ☐ *erase nvram*
- C. ☐ *delete nvram*
- D. ☐ *erase running*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option A

Solution:

The command *erase startup-config* deletes the configuration stored in NVRAM.

33.

What protocols are used to configure trunking on a switch?

1. VLAN Trunking Protocol

2. VLAN

3. 802.1Q

4. ISL

- ☐
- A. ☐ 1 and 2
- ☐
- B. ☐ 3 and 4
- ☐
- C. ☐ 1 only
- ☐
- D. ☐ 2 only

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option B

Solution:

VTP is not right because it has nothing to do with trunking except that it sends VLAN information across a trunk link. 802.1Q and ISL are used to configure trunking on a port.

34.

Which command is used to upgrade an IOS on a Cisco router?

- A. ☐ *copy tftp run*
- B. ☐ *copy tftp start*
- C. ☐ *config net*
- D. ☐ *copy tftp flash*

[Answer & Solution](#) [Discuss in Board](#) [Save for Later](#)

Answer & Solution

Answer: Option D

Solution:

The *copy tftp flash* command places a new file in flash memory, which is the default location for the Cisco IOS in Cisco routers.

Q.1. Which of the following are the network services?

- A. File service
- B. Database service
- C. Print service
- D. All of the above

D. All of the above

Q.2.FDDI stands for-----

- A. Fiber Data Distributed Interface
- B. Fiber Distributed Data Interface
- C. Fiber Dual Distributed Interface
- D. Fiber Distributed Data Interface

B. Fiber Distributed Data Interface

Q.3. A group of computers and other devices connected together is called a network, and the concept of connected computers sharing resources is called -----.

- A. Inter-Network
- B. Networking
- C. Inter-Connection
- D. Computer Group

B. Networking

Q.4. When collection of various computers seems a single coherent system to its client, then it is called-----

- A. distributed system
- B. computer network
- C. both (A) and (B)
- D. None of the above

A. distributed system

Q.5. Two devices are in network if -----.

- A. a process is running on both devices.
- B. PIDs of the processes running of different devices are same.
- C. a process in one device is able to exchange information with a process in another device.
- D. None of the above.

C. a process in one device is able to exchange information with a process in another device.

Q.6. Communication channel is shared by all the machines on the network in-----

- A. unicast network
- B. broadcast network
- C. multicast network
- D. None of the above

B. broadcast network

Q.7. A device that connects to a network with our the use of cables is said to be-----

- A. Open source
- B. Wireless
- C. Cabled
- D. Distributed

B. Wireless

Q.8. Which of the following is the fastest communication channel?

- A. Optical fiber
- B. Radio wave
- C. Micro wave
- D. None of the above

C. Micro wave

Department of software engineering

Q.9. The first network that has planted the seeds of internet was-----.

- | | |
|------------|------------|
| A. ARPANET | B. NSF net |
| C. ARRNET | D. APNET |

A. ARPANET

Q.10. A combination of hardware and software that allows communication and electronic transfer of information between computer is a-----.

- | | |
|------------|---------------|
| A. Server | B. Peripheral |
| C. Network | D. internet |

C. Network

Q.11. -----is the transmission of data between two or more computer over communication links.

- | | |
|--------------------|-----------------------|
| A. Data networking | B. Data communication |
| C. Communication | D. Networking |

B. Data communication

Q.12. Communication channel having-----types.

- | | |
|------|------|
| A. 1 | B. 2 |
| C. 3 | D. 4 |

C. 3

Q.13. Broadcasting technology is used in broadcast network in which special code in the address field for addressing is used.

- | | |
|---------|----------|
| A. True | B. False |
|---------|----------|

A. True

Q.14. Broadcast Network have-----communication channels.

- | | |
|-----------|-------------|
| A. Single | B. Two |
| C. Three | D. Multiple |

A. Single

Department of software engineering

Q.15. Transmission to a subset of the machines in broadcast system is called as-----

- A. Multi Broadband
- B. Multi Casting
- C. Multi Network
- D. None of the above

B. Multi Casting

1. A proxy server is used as the computer?

- A. acting as a backup
- B. performing file handling
- C. with external access
- D. accessing user permissions

Answer: with external access

2. The term HTTP stands for?

- A. Hypertext transfer program
- B. Hypertext tracing protocol
- C. Hyper terminal tracing program
- D. Hypertext transfer protocol

Answer: Hypertext transfer protocol

3. The location of a resource on the internet is given by its?

- A. Protocol
- B. uniform resource locator (URL)
- C. ICQ
- D. E-mail address

Answer: uniform resource locator (URL)

4. Which one of the following would breach the integrity of a system?

- A. Looking the room to prevent theft
- B. Full access rights for all users
- C. Protecting the device against
- D. Fitting the system with an anti-theft device

Department of software engineering

Answer: **Full access rights for all users**

5. *Which type of topology is best suited for large businesses which must carefully control and coordinate the operation of distributed branch outlets?*

- A. Star
- B. Local area
- C. Hierarchical
- D. Ring

Answer: **Star**

6. *Which software prevents the external access to a system?*

- A. firewall
- B. Virus checker
- C. Gateway
- D. Router

Answer: **firewall**

7. *Which of the following transmission directions listed is not a legitimate channel?*

- A. Half Duplex
- B. Double Duplex
- C. Simplex
- D. Full Duplex

Answer: **Double Duplex**

8. *Which of these is a standard interface for serial data transmission?*

- A. ASCII
- B. 2
- C. RS232C
- D. Centronics

Answer: **RS232C**

9. *"Parity bits" are used for which of the following purposes?*

- A. To identify the user
- B. Encryption of data

C. error detection

D. To transmit faster

Answer: error detection

10. A collection of hyperlinked documents on the internet forms is ?

A. World Wide Web

B. E-mail system

C. Mailing list

D. Hypertext markup language

Answer: World Wide Web (WWW).

11. What kind of transmission medium is most appropriate to carry data in a computer network that is exposed to electrical interferences?

A. Unshielded twisted pair

B. Coaxial cable

C. Microwave

D. Optical fiber

Answer: Optical fiber

12. When the mail server sends mail to other mail servers it becomes ____ ?

A. Master

B. Peer

C. SMTP server

D. SMTP client

Answer: SMTP client

13. The length of an IPv6 address is?

A. 64 bits

B. 32 bits

C. 128 bits

D. 256 bits

Answer: 128 bits

14. Which of the following is correct IPv4 address?

A. 01.200.128.123

B. 300.142.210.64

C. 128.64.0.0

D. 124.201.3.1.52

Answer: 128.64.0.0

15. How many versions available of IP?

A. 2 version

B. 6 version

C. 4 version

D. 1 version

Answer: 2 version

16. The private key in asymmetric key cryptography is kept by?

A. Transmission

B. Receiver

C. Sender

D. Sender and Receiver

Answer: Receiver

17. Which layer of the TCP / IP stack corresponds to the OSI model transport layer?

A. Application

B. Host to Host

C. Network Access

D. Internet

Answer: Host to Host

18. The term IPv4 stands for?

A. International Programming Version 4

B. Internet Programming Version 4

Department of software engineering

C. Internet Protocol Version 4

D. None

Answer: Internet Protocol Version 4

19. How many digits of the Data Network Identification Code (DNIC) identify the country?

A. first four

B. first five

C. first three

D. first six

Answer: first three

20. Which of the through is share the data of two computer?

A. Integrated system

B. Library

C. Network

D. Grouping

Answer: Network

21. The term IANA stands for?

A. Internal Assigned Numbers Authority

B. Internet Associative Numbers Authoritative

C. Internet Assigned Numbers Authority

D. Internal Associative Numbers Authority

Answer: Internet Assigned Numbers Authority

22. The term WAN stands for?

A. Wide Area Net

B. Wide Area Network

C. Wide Access Network

D. Wide Access Net

Answer: Wide Area Network

Department of software engineering

23. *Software programs that allow you to legally copy files and give them away at no cost are called which of the following?*

- A. Probe ware
- B. Shareware
- C. Timeshare
- D. Public domain

Answer: Public domain

24. *Which of the following statements could be valid with respect to the ICMP (Internet Control Message Protocol)?*

- A. It reports all errors which occur during transmission.
- B. It informs routers when an incorrect path has been taken.
- C. A redirect message is used when a router notices that a packet seems to have been routed wrongly
- D. The “destination unreachable” type message is used when a router cannot locate the destination.

Answer: A redirect message is used when a router notices that a packet seems to have been routed wrongly

25. *The IP network 192.168.50.0 is to be divided into 10 equal sized subnets. Which of the following subnet masks can be used for the above requirement?*

- A. 255.255.255.0
- B. 255.243.240
- C. 255.255.255
- D. 255.255.0

Answer: 255.255.255.0

26. *The term FTP stands for?*

- A. File transfer protocol
- B. File transfer program
- C. File transfer protection
- D. File transmission protocol

Answer: File transfer protocol

27. *Which one of the following is not a network topology?*

- A. Star

B. Ring

C. Bus

D. Peer to Peer

Answer: Peer to Peer

28. The maximum length (in bytes) of an IPv4 datagram is?

A. 32

B. 65535

C. 1024

D. 516

Answer: 65535

29. Which one of the following is the most common internet protocol?

A. HTML

B. TCP/IP

C. IPX/SPX

D. NetBEUI

Answer: TCP/IP

30. Which of the following best describes uploading information?

A. Receiving information from a host computer

B. Sorting data on a disk drive

C. Sending information to a host computer

D. Sorting data on a hard drive

Answer: Sending information to a host computer

Question: In networking terminology, UTP means

- (a) Unshielded Twisted pair
- (b) Ubiquitous Teflon port
- (c) Uniformly Terminating port
- (d) Unshielded T-connector port

Hide Answer

Ans. (a)

Question: End – to – end connectivity is provided from host – to – host in the

- (a) network layer
- (b) transport layer
- (c) session layer
- (d) none of these

Hide Answer

Ans. (b)

Question: For a 1-Gbps network operating over 4000 km, the delay is the limiting factor, not the bandwidth. Consider a MAN with the average source and destination 20 km apart. At what data rate does the round-trip delay due to the speed of light equal the transmission delay for a 1-KB packet ?

- (a) 24 Mbps
- (b) 36 Mbps
- (c) 40 Mbps
- (d) 48 Mbps

Hide Answer

Ans. (c)

Question: Which of the following is the correct order of the four major functions of a computer?

- (a) Process, an Output, an Input, a Storage
- (b) Input a Output a Process a Storage
- (c) Process a Storage, an Input an Output
- (d) Input a Process, an Output a Storage

Hide Answer

Ans. (d)

Question: Whether LAN uses

- (a) Polar encoding
- (b) differential Manchester encoding
- (c) Manchester encoding
- (d) NRZ

Hide Answer

Ans. (c)

Related: [Adobe Photoshop test questions](#)

Question: A desirable property of a module is

- (a) independency
- (b) low cohesiveness
- (c) high coupling
- (d) multifunctional

Hide Answer

Ans. (a)

Question: Gateways can function all the way upto

- (a) transport layer
- (b) session layer
- (c) presentation layer
- (d) application layer

Hide Answer

Ans. (d)

Question: Which of the following is not relevant to networking ?

- (a) Low-end stand-alone hubs
- (b) Stackable hubs
- (c) Mesh network
- (d) Bus hubs

Hide Answer

Ans. (d)

Department of software engineering

Question: GET method, HEAD method, the post methods are the methods of

- (a) HTTP methods
- (b) HPTP method
- (c) Current standard
- (d) None

Hide Answer

Ans. (a)

Question: If a network designer wants to connect 5 routers as point-to-point a simplex line, then the total number of lines required would be

- (a) 5
- (b) 10
- (c) 20
- (d) 32

Hide Answer

Ans. (b)

Related: [Excel multiple choice questions](#)

Question: Which company develops the TCP/IP protocol for networking ?

- (a) IBM
- (b) DEC
- (c) NOVELL
- (d) DARPA

Hide Answer

Ans. (d)

Question: The IP was originally designed for

- (a) Data net working
- (b) Data processing
- (c) Data Execution
- (d) none

Hide Answer

Ans. (a)

Question: Which one of the following is not a class of LAN ?

- (a) Broadband
- (b) CSMA/CD
- (c) Token bus
- (d) Token ring

Hide Answer

Ans. (a)

Question: A local area network

- (a) that connects thirty personnel computers can provide more computing power than a minicomputer
- (b) controls error detection and correction
- (c) constructs packets of data and sends them across the network
- (d) none of these

Hide Answer

Ans. (a)

Related: [List of Commonly Used Abbreviations](#)

Question: Different computers are connected to a LAN by a cable and

- (a) modem
- (b) interface card
- (c) special wires
- (d) telephone lines

Hide Answer

Ans. (b)

Question: What is a FTP program used for?

- (a) Transfer files to and from an Internet Server
- (b) Designing a website
- (c) Connecting to the internet
- (d) None of the above

Hide Answer

Answer. (a)

Question: Bit stuffing refers to

- (a) inserting a '0' in the user stream to differentiate it with a flag
- (b) inserting a '0' in the flag stream to avoid ambiguity
- (c) appending a nibble to the flag sequence
- (d) appending a nibble to the used data stream

Hide Answer

Ans. (a)

Related: [MS Word test questions and answers](#)

Question: A network that contains multiple hubs is most likely configured in which topology ?

- (a) Mesh
- (b) Tree
- (c) Bus
- (d) Star

Hide Answer

Ans. (b)

Question: In Ethernet CSMA/CA, the special bit sequence transmitted by media access management collision handling is called

- (a) preamble
- (b) postamble
- (c) jam
- (d) none of these

Hide Answer

Ans. (c)

Question: A field in the Ethernet message packet is

- (a) Type
- (b) Data
- (c) Address
- (d) All of these

Hide Answer

Ans. (d)

Related: [Operating system quiz questions with answers](#)

Question: A 3000 Hz bandwidth noisy channel transmits bits with a signal to thermal noise ratio of 30 dB.

What is the maximum data rate of the channel ?

- (a) 30 kbps
- (b) 90 kbps
- (c) 60 kbps
- (d) none of these

Hide Answer

Ans. (a)

Question: Which of the following is a valid IP address?

- (a) 984.12.787.76
- (b) 192.168.321.10
- (c) 1.888.234.3456
- (d) 192.168.56.115

Hide Answer

Answer. (d)

Department of software engineering

Question: A high speed communication equipment typically would not be needed for

- (a) E-mail
- (b) transferring a large volume of data
- (c) supporting communication between nodes on a LAN
- (d) All of these

Hide Answer

Ans. (a)

Question: In the context of OSI or TCP/IP computer network models, which of the following is FALSE ?

- (a) Besides the span of geographical area, the other major difference between LAN and WAN is that the latter uses switching element
- (b) A repeater is used just to forward bits from one network to another one.
- (c) The IP layer is a connected oriented layer in TCP/IP
- (d) A gateway is used to connect incompatible networks

Hide Answer

Ans. (c)

1. A _____ is a system in which multiple computers are connected to each other to share information and resources.

- A. Hardware
- B. Software
- C. Number system
- D. Computer network

View Answer

Ans : D

Explanation: A computer network is a system in which multiple computers are connected to each other to share information and resources

2. Which cables are used to connect computers.

- A. Twisted Pair
- B. Network
- C. Coaxial
- D. Fiber

View Answer

Ans : B

Explanation: Network cables are used to connect computers. The most commonly used cable is Category 5 cable RJ-45.

3. NIC stands for?

- A. Network Internal Card
- B. Network Interconnect Card
- C. Network Interface Card
- D. Network Interface Component

View Answer

Ans : C

Explanation: Network card is a necessary component of a computer without which a computer cannot be connected over a network. It is also known as the network adapter or Network Interface Card (NIC).

4. External network cards are of _____ types.

- A. 2
- B. 3
- C. 4
- D. 5

[View Answer](#)

Ans : A

Explanation: External network cards are of two types: Wireless and USB based

5. A router is a type of device which acts as the central point among computers and other devices that are a part of the network.

- A. TRUE
- B. FALSE
- C. Can be true or false
- D. Can not say

[View Answer](#)

Ans : A

Explanation: True, A router is a type of device which acts as the central point among computers and other devices that are a part of the network.

6. Configuration where many independent computer systems are connected.

- A. Complex
- B. Cloud
- C. Incremental
- D. Distributed

[View Answer](#)

Ans : D

Explanation: Distributed configuration has many systems connected, and messages, programs, etc are transmitted between cooperating computer systems

7. A term that refers to the way in which the nodes of a network are linked together.

- A. network
- B. topology
- C. connection
- D. interconnectivity

[View Answer](#)

Ans : B

Explanation: Topology is a term that refers to the way in which the nodes are connected. There are 4 major topology networks.

8. A topology that involves Tokens.

- A. Star
- B. Bus
- C. Ring
- D. Daisy Chaining

[View Answer](#)

Ans : C

Explanation: Ring topology involves sending and receiving of data with the help of tokens. Ring started out as a simple peer-to-peer LAN topology.

9. WANs that need to interconnect a very large number of sites

- A. bus
- B. two-tiered
- C. ring
- D. three-tiered

[View Answer](#)

Ans : D

Explanation: Wide Area Networks that need to interconnect a very large number of sites, or are built using smaller routers that can support only a few serial connections, may find the two-tiered architecture insufficiently scalable

10. Motherboard has a slot for internal network card

- A. Yes
- B. No
- C. Can be yes or false
- D. Can not say

[View Answer](#)

Ans : A

Explanation: Yes, Motherboard has a slot for internal network card where it is to be inserted.