



WOLLO University

Department of software engineering

Exit multiple choice questions for

Computer programming

Prepared by:

@Neyatibeb

KOMBOLCHA, Ethiopia

2015 E.C

Department of software engineering

1: select one of the true statement for the compiler?

- a. the input of the compiler is source program
- b.it translates the source code into object code as a whole
- c. the output of the compiler is object code
- d.all of above

Answer - Click Here:

D

2: the pseudocode is...

- a. algorithm
- b. flowchart
- c. object code
- d.coding

Answer - Click Here:

A

3: the language processor translates the program into object code as a whole...

- a.linker
- b.debugger
- c.compiler
- d.interpreter

Answer - Click Here:

C

4: finding and solving errors in the source code is...

- a. desk checking
- b. debugging
- c. decoding
- d. testing

Answer - Click Here:

B

5. translates the source code into machine language...

- a. operating system
- b. programming language
- c. language processor
- d. all of these

Answer - Click Here:

C

6: The step by step procedure for solving a problem...

- a. programming
- b. algorithm
- c. planing
- d. flowchart

Answer - Click Here:

B

7.language is not an object oriented pogramming language...

- a. visual basic
- b. c
- c. c++
- d. java

Answer - Click Here:

C

8. communication between user and the computer is...

- a. programming language
- b. software
- c. syntax
- d. english language

Answer - Click Here:

A

1.In flowchart rectangle symbol indicates:

- a.Input/Output
- b.Connector

- c.Process
- d.Decision

Answer - Click Here:

C

2.C++ is a(n):

- a.Object-oriented programming language.
- b.Event-driven programming language.
- c.Structured programming language.
- d.None of these.

Answer - Click Here:

A

3.The arithmetic operators are:

- a.Ternary operators
- b.Unary operators
- c.Binary operators
- d.None of these

Answer - Click Here:

C

4.The escape sequence for carriage return is:

- a./t
- b./f
- c./n
- d./r

Answer - Click Here:

D

5.In switch structure, each case label may be an integer constant or:

- a.Real constant
- b.Character constant
- c.String constant
- d.None of these

Answer - Click Here:

B

6.What will be the value of 'x' after executing for(x=1;x<=15;x++);?

- a.15

- b.1
- c.14
- d.16

Answer - Click Here:

C

7.The pointers are used for implementing the concept of:

- a.Polymorphism
- b.Array
- c.Structure
- d.Inheritance

Answer - Click Here:

A

8.The function `strlen("ABC")`;will return value:

- a.4
- b.ABC
- c.3
- d.None of these

Answer - Click Here:

C

9.The data item of a structured are called:

- a.Fields
- b.Elements
- c.Members
- d.ALI of these

Answer - Click Here:

D

10.In C++,the functions of a class are called:

- a.Attributes
- b.Methods
- c.Member function
- d.Both a and b

Answer - Click Here:

C

11.The derived class is also called:

- a.parent class

- b.sub class
- c.child class
- d.both b and c

Answer - Click Here:

D

12.Which of the following type of inheritance is commonly used:

- a.private
- b.public
- c.protected
- d.none of these

Answer - Click Here:

B

13.Polymorphism is achieved through:

- a.destructor
- b.constructor
- c.virtual function
- d.overloading operator

Answer - Click Here:

C

14.Which of the following stream class is used to perform both input and output file operation:

- a ofstream
- b ifstream
- c fstream
- d iostream

Answer - Click Here:

C

15.How many operations can be performed on stack:

- a.4
- b.5
- c.3
- d.2

Answer - Click Here:

D

16.Which of the following is used in recursion operation:

- a.stack
- b.deque
- c.queue
- d.tree

Answer - Click Here:

A

17.In order traversal:

- a.Right sub-tree is visited first in inorder
- b.Root is visited first
- c.Left sub-tree is visited in inorder
- d.None of the above

Answer - Click Here:

C

18.In binary I/O,the integer value 16324 will take:

- a.5 bytes
- b.6 bytes
- c.4 bytes
- d.2 bytes

Answer - Click Here:

D

19.A class that has at least one pure virtual function is called:

- a.Abstract class
- b.Super class
- c.Concrete class
- d.Derived class

Answer - Click Here:

A

20.Inheritance is the process of creating new classes called:

- a.Super classes
- b.Parent classes
- c.Base classes
- d.Derived classes

Answer - Click Here:

D

21. Which of the following function is a non-member function of a class?

- a. Overridden function
- b. Friend function
- c. Constructor
- d. Destructor

Answer - Click Here:

D

22. When accessing a structure member, the identifier to the left of the dot operator is the name of:

- a. a structure tag
- b. a structure variable
- c. the keyword struct
- d. a structure member

Answer - Click Here:

B

23. The null character is denoted by:

- a. '\e'
- b. '\n'
- c. '\0'
- d. 0

Answer - Click Here:

C

24. Each element of array of character occupies:

- a. one byte
- b. four bytes
- c. two bytes
- d. None of the above

Answer - Click Here:

A

25. How many arithmetic operations can be performed on a pointer?

- a. 6
- b. 4
- c. 2
- d. 3

Answer - Click Here:

C

26.The only integer that can be assigned directly to a pointer is:

- a.2
- b.0
- c.1
- d.3

Answer - Click Here:

B

27.Which of the following loop structure has test condition after the body of loop?

- a.do-while
- b.while
- c.for
- d.None

Answer - Click Here:

A

28.Which of the following is a counter loop statement?

- a.do-while
- b.for
- c.while
- d.none

Answer - Click Here:

D

29.How many relational operators in C++?

- a.2
- b.4
- c.6
- d.3

Answer - Click Here:

C

30.Which of the following is a logical operator?

- a.=
- b.!=
- c.==
- d.!

Answer - Click Here:

D

31.A stream refers to:

- a.flow of data
- b.output statement
- c.input statement
- d.flow of program control

Answer - Click Here:

A

32.A person that can write a computer program is called:

- a.coder
- b.programmer
- c.analyst
- d.coordinator
- e.both c and d

Answer - Click Here:

B

33.The term mnemonic is used in:

- a.C-language
- b.Ada language
- c.Assembly language
- d.Machine language
- e.none of these

Answer - Click Here:

C

34.In which year BCPL was developed:

- a.1980
- b.1970
- c.1967
- d.1972
- e.None of these

Answer - Click Here:

C

35.Which of the following is the part of C++ compiler?

- a. obj
- b. .exe
- c. .cpp
- d. .h
- e. none of these

Answer - Click Here:

D

36.The extension of C++ source program is:

- a.ccp
- b.cpp
- c.exe
- d.obj
- e.none of these

Answer - Click Here:

B

36.Which operator is unary operator?

- a.\$\$
- b.>==
- c.//
- d.++
- e.all of these

Answer - Click Here:

D

37.a++ statement, is equivalent to:

- a.a=a+a
- b.a=a+1
- c=.a=++a+1
- d.both b and c
- e. none of these

Answer - Click Here:

B

38. The cerr is a(n):

- a.output stream object
- b.built-in error function
- c.keyword
- d.input stream object
- e.all of these

Answer - Click Here:

A

39.The escape sequence for carriage return is:

- a./f

- b./r
- c./n
- d./t
- e.both c and d

Answer - Click Here:

b

40.A relational operator :

- a. Compares two operands.
- b.assign one operand to another
- c.logically combines two operands
- d.adds two operands.
- e.none of these

Answer - Click Here:

A

41.Which of the following statement is a loop statement?

- a.while
- b.switch
- c.if
- d.if-else
- e.both a and b

Answer - Click Here:

A

42.Which logical operator is unary operator?

- a.//
- b.!
- c.&&
- d.both a and b
- e.none of the above

Answer - Click Here:

B

43.A pointer may be initialized to:

- a.NULL
- b.Address of a variable
- c.0
- d.All of these

Answer - Click Here:

D

44.How many loop structure in C++?

a.4

b.2

c.1

d.3

e.none

Answer - Click Here:

D

45.Which of the following is an address operator?

a.!

b.*

c.&

d.&&

e. all of these

Answer - Click Here:

C

46.A pointer is a(n):

a.Data type

b.Variable

c.Operator

d.Keyword

e.both c and d

Answer - Click Here:

B

47.Which of the following is relational operator?

a.%

b.=

c.&&

d.==

e.all of these

Answer - Click Here:

C

48.In following statement which statement are correct?

a.char *X3="ABC";

b.char X1[]="ABC";

Department of software engineering

- c.char X2[5]="ABC";
- d.both b and c
- e.None of these

Answer - Click Here:

E

[Pay AssignmentCore for doing programming assignn](#)

49.The keyword 'friend' is used to define a:

- a.Friend class
- b.Friend constructor
- c.Friend function
- d.Both a and b

Answer - Click Here:

D

1. Choose one of the best options. An element Referring outside array bounds is a ____?

- A. Logical error
- B. Syntax error
- C. Execution time error
- D. Both A and C

Answer - Click Here:

D

2. Every element in an array is searched against some searching key, special for

- A. Linear search
- B. Bubble sort
- C. All of them
- D. Binary search

Answer - Click Here:

A

3. A one-dimensional array contains one-dimensional arrays is called

- A. Two-dimensional array
- B. Multi-casting array
- C. Multi-dimensional array
- D. Three-dimensional array

Answer - Click Here:

A

4. Objects in a sequence that have the same type, is called

- A. Arrays
- B. Operators
- C. Functions
- D. Stacks

Answer - Click Here:

A

5. A binary search algorithm is an algorithm that is used for

- A. Divide and conquer method
- B. Linear way to search values
- C. Bubble sorting technique
- D. None of them

Answer - Click Here:

A

6. With the help of which character array can be initialized using

- A. A string literal
- B. Integer values
- C. Floats value
- D. None of them

Answer - Click Here:

A

7. In an array starting from the beginning and inspecting each element one after other for finding an object, until the object is found is called as

- A. Linear search algorithm
- B. Searching
- C. Inspecting
- D. All of them

Answer - Click Here:

A

8. Consecutive group of memory locations contains all same name and same type, is called as

Department of software engineering

- A. Structures
- B. Arrays
- C. Classes
- D. Functions

Answer - Click Here:

B

9. For finding value in an array which of the following technique is used?

- A. Binary search algorithm
- B. Bubble sort
- C. Linear search algorithm
- D. All of them

Answer - Click Here:

D

10. Programmer's uses _____ for defining their own types.?

- A. Algorithms
- B. Operators
- C. Enumerations
- D. None of them

Answer - Click Here:

C

11. Choose one of the best option from the following Position number contained within a square brackets e.g. my_array [5], is referred as ____?

- A. Sub-scripts
- B. Post-scripts
- C. Elements of an array
- D. None of them

Answer - Click Here:

A

12. A one dimensional array is always considered as ____?

- A. Complex
- B. Sequential
- C. Linear
- D. Both C and B

Answer - Click Here:

D

13. when _____ array that are declared static are initialized

- A. The first element is zero
- B. Program is about to end

- C. Program is loaded into the memory
- D. None of them

Answer - Click Here:

C

14. One-dimensional array having two-dimensional arrays is called

- A. Two-dimensional array
- B. Multi-dimensional array
- C. One-dimensional array
- D. Three-dimensional array

Answer - Click Here:

C

15. To identify a particular element tables or arrays that require two subscripts are called

- A. Multiple subscripted array
- B. Double subscripted array
- C. Two way array
- D. None of them

Answer - Click Here:

B

16. Objects in an array is called as

- A. Functions of an array
- B. Elements of an array
- C. Indexes of an array
- D. All of them

Answer - Click Here:

B

17. An array having arrays is called

- A. Uni-casting array
- B. Multi-dimensional array
- C. One-dimensional array
- D. Multi-casting array

Answer - Click Here:

B

18. An array can contain how many kinds of elements ?

- A. Only int type
- B. Only char type
- C. Char and int type
- D. All of them have same type

Answer - Click Here:

D

19. Example of___ is Float a [3] = {10.2, 33.4, 44.4}

- A. Initializing array
- B. Initializing variables
- C. Initializing functions
- D. None of them

Answer - Click Here:

A

20. Array containing elements are numbered as 0,1,2,3? these numbers are called

- A. Subscripts of the array
- B. Index values
- C. Members of an array
- D. Both A and B

Answer - Click Here:

D

21. _____ is correctly declares an array?

- A. int array;
- B. int array[10];
- C. array{10};
- D. array array[10];

Answer - Click Here:

B

22. Index number of the last element of an array having 9 elements is _____

- A. 9
- B. Programmer-defined
- C. 0
- D. 8

Answer - Click Here:

D

23. Array is defined as

- A. An array is a series of element
- B. An array is a series of elements of the same type in contiguous memory locations
- C. An array is a series of elements of the same type placed in non-contiguous memory locations
- D. None of the mentioned

Answer - Click Here:

B

24. How we access the seventh element stored in array?

- A. array[6];
- B. array(7);
- C. array[7];
- D. array;

Answer - Click Here:

A

25. The memory address of the first element in array is _____

- A. array[0];
- B. array(2);
- C. array[1];
- D. array;

Answer - Click Here:

D

26. Output of the this program will be _____

```
#include
using namespace std;
int main ()
{
int array[] = {0, 2, 4, 6, 7, 5, 3};
int n, result = 0;
for (n = 0 ;n < 8 ;n++) {
result += array[n];
}
cout << result;
return 0;
}
```

- A. 25
- B. 27
- C. 26
- D. None of the mentioned

Answer - Click Here:

B

27. Output of this program will be _____?

```
#include
using namespace std;
int main()
{
int a = 5, b = 10, c = 15;
int arr[3] = {&a, &b, &c};
cout << *arr[*arr[1] - 8];
return 0;
}
```

- }
- A. 18
 - B. 15
 - C. garbage value
 - D. compile time error

Answer - Click Here:

D

28. Output of this program will be _____?

```
#include
using namespace std;
int main()
{
char str[5] = "ABC";
cout << str[3];
cout << str;
return 0;
}
```

- A. ABCD
- B. AB
- C. ABC
- D. None of the mentioned

Answer - Click Here:

C

29. Output of this program will be _____?

```
#include
using namespace std;
int main()
{
int array[] = {10, 20, 30};
cout << -2[array];
return 0;
}
```

- A. -30
- B. -15
- C. garbage value
- D. compile time error

Answer - Click Here:

A

Department of software engineering

1. Choose one of the best options. An element Referring outside array bounds is a ____?

- A. Logical error
- B. Syntax error
- C. Execution time error
- D. Both A and C

Answer - Click Here:

D

2. Every element in an array is searched against some searching key, special for

- A. Linear search
- B. Bubble sort
- C. All of them
- D. Binary search

Answer - Click Here:

A

3. A one-dimensional array contains one-dimensional arrays is called

- A. Two-dimensional array
- B. Multi-casting array
- C. Multi-dimensional array
- D. Three-dimensional array

Answer - Click Here:

A

4. Objects in a sequence that have the same type, is called

- A. Arrays
- B. Operators
- C. Functions
- D. Stacks

Answer - Click Here:

A

5. A binary search algorithm is an algorithm that is used for

- A. Divide and conquer method
- B. Linear way to search values
- C. Bubble sorting technique
- D. None of them

Answer - Click Here:

A

6. With the help of which character array can be initialized using

- A. A string literal
- B. Integer values
- C. Floats value
- D. None of them

Answer - Click Here:

A

7. In an array starting from the beginning and inspecting each element one after other for finding an object, until the object is found is called as

- A. Linear search algorithm
- B. Searching
- C. Inspecting
- D. All of them

Answer - Click Here:

A

8. Consecutive group of memory locations contains all same name and same type, is called as

- A. Structures
- B. Arrays
- C. Classes
- D. Functions

Answer - Click Here:

B

9. For finding value in an array which of the following technique is used?

- A. Binary search algorithm
- B. Bubble sort
- C. Linear search algorithm
- D. All of them

Answer - Click Here:

D

10. Programmer's uses _____ for defining their own types.?

- A. Algorithms
- B. Operators
- C. Enumerations
- D. None of them

Answer - Click Here:

C

11. Choose one of the best option from the following Position number contained within a square brackets e.g. my_array [5], is referred as ____?

- A. Sub-scripts
- B. Post-scripts
- C. Elements of an array
- D. None of them

Answer - Click Here:

A

12. A one dimensional array is always considered as_____?

- A. Complex
- B. Sequential
- C. Linear
- D. Both C and B

Answer - Click Here:

D

13. when _____ array that are declared static are initialized

- A. The first element is zero
- B. Program is about to end
- C. Program is loaded into the memory
- D. None of them

Answer - Click Here:

C

14. One-dimensional array having two-dimensional arrays is called

- A. Two-dimensional array
- B. Multi-dimensional array
- C. One-dimensional array
- D. Three-dimensional array

Answer - Click Here:

C

15. To identify a particular element tables or arrays that require two subscripts are called

- A. Multiple subscripted array
- B. Double subscripted array
- C. Two way array
- D. None of them

Answer - Click Here:

B

16. Objects in an array is called as

- A. Functions of an array
- B. Elements of an array

- C. Indexes of an array
- D. All of them

Answer - Click Here:

B

17. An array having arrays is called

- A. Uni-casting array
- B. Multi-dimensional array
- C. One-dimensional array
- D. Multi-casting array

Answer - Click Here:

B

18. An array can contain how many kinds of elements ?

- A. Only int type
- B. Only char type
- C. Char and int type
- D. All of them have same type

Answer - Click Here:

D

19. Example of___ is Float a [3] = {10.2, 33.4, 44.4}

- A. Initializing array
- B. Initializing variables
- C. Initializing functions
- D. None of them

Answer - Click Here:

A

20. Array containing elements are numbered as 0,1,2,3? these numbers are called

- A. Subscripts of the array
- B. Index values
- C. Members of an array
- D. Both A and B

Answer - Click Here:

D

21. _____ is correctly declares an array?

- A. int array;
- B. int array[10];
- C. array{10};
- D. array array[10];

Answer - Click Here:

B

22. Index number of the last element of an array having 9 elements is _____

- A. 9
- B. Programmer-defined
- C. 0
- D. 8

Answer - Click Here:

D

23. Array is defined as

- A. An array is a series of element
- B. An array is a series of elements of the same type in contiguous memory locations
- C. An array is a series of elements of the same type placed in non-contiguous memory locations
- D. None of the mentioned

Answer - Click Here:

B

24. How we access the seventh element stored in array?

- A. array[6];
- B. array(7);
- C. array[7];
- D. array;

Answer - Click Here:

A

25. The memory address of the first element in array is _____

- A. array[0];
- B. array(2);
- C. array[1];
- D. array;

Answer - Click Here:

D

26. Output of the this program will be _____

```
#include
using namespace std;
int main ()
{
int array[] = {0, 2, 4, 6, 7, 5, 3};
int n, result = 0;
for (n = 0 ;n < 8 ;n++) {
```

```
result += array[n];  
}  
cout << result;  
return 0;  
}
```

- A. 25
- B. 27
- C. 26
- D. None of the mentioned

Answer - Click Here:

B

27. Output of this program will be _____?

```
#include  
using namespace std;  
int main()  
{  
int a = 5, b = 10, c = 15;  
int arr[3] = {&a, &b, &c};  
cout << *arr[*arr[1] - 8];  
return 0;  
}
```

- A. 18
- B. 15
- C. garbage value
- D. compile time error

Answer - Click Here:

D

28. Output of this program will be _____?

```
#include  
using namespace std;  
int main()  
{  
char str[5] = "ABC";  
cout << str[3];  
cout << str;  
return 0;  
}
```

- A. ABCD
- B. AB
- C. ABC
- D. None of the mentioned

Answer - Click Here:

C

29. Output of this program will be _____?

```
#include  
using namespace std;  
int main()  
{  
int array[] = {10, 20, 30};  
cout << -2[array];  
return 0;  
}
```

- A. -30
- B. -15
- C. garbage value
- D. compile time error

Answer - Click Here:

A

1. we can manipulate data stored in other variables _____ with pointer variables.

- a. All of these
- b. never
- c. seldom
- d. indirectly
- e. none of these
- f. both a and b

Answer d

2. following statement has the same meaning as

```
int *ptr;
```

- a. int* ptr;
- b. int ptr;
- c. *int ptr;
- d. int ptr*;
- e. none of these
- f. both a and b

Answer a

3. which of the following options can be used as pointers.

- a. All of these
- b. Array names
- c. Numeric constants
- d. Punctuation marks
- e. None of these
- e. none of these

f. both c and b

Answer b

4. which of the following operators are used to increment or decrement a pointer variable.

a. modulus, division

b. addition, subtraction

c. ++, —

d. +-, -+

e. None of these

e. none of these

d. both c and d

Answer c

5. _____ is used to initialize a pointer.

a. all of these

b. the address of an existing object

c. the value of an integer variable

d. the value of a floating-point variable

e. none of these

f. both a and b

Answer b

6. What is the function of the following statement?

`double *num2;`

a. Declares a pointer variable named num2.

b. Declares a double variable named num2.

c. Declares and initializes a pointer variable named num2.

d. Initializes a variable named *num2.

e. none of these

f. both a and b

Answer a

7. the delete operator can be used on the pointers:

a. dereferenced inappropriately

b. never used

c. not correctly initialized

d. created with the new operator

e. none of these

f. both a and b

Answer d

8. Which of the following are invalid statements?

a. `float num1 = &ptr2;`

b. `int ptr = &num1;`

c. `int ptr = int *num1;`

d. All of these are invalid

e. All of these are valid

f. both a and b

Answer d

9. what is stored in a pointer variable?

a. an integer

b. a memory address.

c. only floating-point values.

d. any C++ value.

e. none of these

d. both a and b

Answer b

10. pointer variables may be changed with mathematical statements that perform_____.

a. special operations

b. all mathematical operations

c. multiplication and division

d. addition and subtraction

e. none of these

f. both a and b

Answer d

11. Reference is not the same as a pointer because

A. a reference can never be null

B. a reference once established cannot be changed.

C. reference doesn't need an explicit dereferencing mechanism.

D. All of above

e. none of these

d. both a and b

Answer c

12. size of generic pointer is _____.

A. 0

B. 1

C. 2

D. 3

e. none of these

d. both a and b

Answer c

13. Referencing a value through a pointer is called

a. All of them

b. Direct calling

c. Indirection

d. Pointer referencing

e. none of these

d. both a and b

Answer c

14. Generic pointers can be declared with_____ .

- A. void
- B. asm
- C. auto
- D. all of the above
- e. none of these
- d. both a and c

Answer a