

Object Oriented Programming in Java

Total points 62/100

Please try, find your gap and read more.

Since

the purpose is to support you don't try to use a search engines or compilers since you will not have an access of them at your exam room

✓ What is a correct syntax to output "Hello World" in Java? *

1/1

- ☐ print ("Hello World");
- ☐ echo("Hello World");
- ☐ Console.WriteLine("Hello World");
- ☒ System.out.println("Hello World");



✓ How do you insert COMMENTS in Java code? *

1/1

- ☐ /* This is a comment
- ☒ // This is a comment
- ☐ # This is a comment
- ☐ & This is a comment



✓ Which data type is used to create a variable that should store text? * 1/1

- ☐ myString
- ☐ Txt
- ☒ String
- ☐ string



✓ How do you create a variable with the numeric value 5? * 1/1

- ☐ float x = 5;
- ☐ x = 5;
- ☐ num x = 5
- ☒ int x = 5;



✓ How do you create a variable with the floating number 2.8? * 1/1

- ☒ float x = 2.8f;
- ☐ x = 2.8f;
- ☐ byte x = 2.8f
- ☐ int x = 2.8f;



✓ Which method can be used to find the length of a string? *

1/1

- ☐ getLength()
- ☐ len()
- ☒ length()
- ☐ getSize()



✗ Which operator is used to add together two values? *

0/1

- ☒ The + sign
- ☐ The * sign
- ☐ The & sign
- ☐ The () sign



Correct answer

- ☒ The & sign



✗ Which operator is used to add together two values? *

0/1

- ☒ The + sign
- ☐ The * sign
- ☐ The & sign
- ☐ The () sign

✗

Correct answer

- ☒ The & sign

✗ Which of the following is true *

0/1

- ☒ The value of a string variable can be surrounded by single quotes.
- ☐ Java is short for "JavaScript".
- ☐ Array indexes start with 1
- ☐ In Java, it is possible to inherit attributes and methods from one class to another.

✗

Correct answer

- ☒ In Java, it is possible to inherit attributes and methods from one class to another.



✓ Which method can be used to return a string in upper case letters? * 1/1

- ☐ tuc()
- ☐ upperCase()
- ☒ toUpperCase()
- ☐ touppercase()



✓ Which operator can be used to compare two values? * 1/1

- ☐ =
- ☐ < >
- ☒ ==
- ☐ > <



✓ To declare an array in Java, define the variable type with: * 1/1

- ☐ ()
- ☐ {}
- ☒ []
- ☐ > <



✓ To declare an array in Java, define the variable type with: *

1/1

- ☐ ()
- ☐ {}
- ☒ []
- ☐ > <



✓ How do you create a method in Java? *

1/1

- ☐ methodName[]
- ☐ (methodName)
- ☒ methodName()
- ☐ methodName.



✓ How do you call a method in Java? *

1/1

- ☐ (methodName);
- ☒ methodName();
- ☐ methodName;
- ☐ methodName[];



✓ Which keyword is used to create a class in Java? *

1/1

- ☒ class
- ☐ class()
- ☐ className
- ☐ MyClass



✓ What is the correct way to create an object called myObj of MyClass? *

1/1

- ☐ class MyClass = new myObj();
- ☐ new myObj = MyClass();
- ☐ class myObj = new MyClass();
- ☒ MyClass myObj = new MyClass();



✓ What is the correct way to create an object called myObj of MyClass? *

1/1

- ☐ class MyClass = new myObj();
- ☐ new myObj = MyClass();
- ☐ class myObj = new MyClass();
- ☒ MyClass myObj = new MyClass();



✓ Which method can be used to find the highest value of x and y? * 1/1

- ☐ Math.largest(x,y)
- ☐ Math.maxNum(x,y)
- ☐ Math.maximum(x,y)
- ☒ Math.max(x,y)



✓ Which operator is used to multiply numbers? * 1/1

- ☒ *
- ☐ %
- ☐ x
- ☐ #



✓ Which keyword is used to import a package from the Java API library? * 1/1

- ☐ getlib
- ☒ import
- ☐ lib
- ☐ package



✓ How do you start writing an if statement in Java? *

1/1

- ☐ if x > y then:
- ☒ if (x > y)
- ☐ if x > y:
- ☐ if x > < y:



✓ How do you start writing an if statement in Java? *

1/1

- ☒ while (x > y)
- ☐ while x > y {
- ☐ while x > y:
- ☐ x > y while {



✓ Which keyword is used to return a value inside a method? *

1/1

- ☐ get
- ☐ break
- ☐ void
- ☒ return



✓ What is the output of the script below *

1/1

```
import java.io.File;
import java.io.IOException;

public class CreateFile {
    public static void main(String[] args) {
        try {
            File myObj = new File("filename.txt");
            if (myObj.createNewFile()) {
                System.out.println("File created: " + myObj.getName());
            } else {
                System.out.println("File already exists.");
            }
        } catch (IOException e) {
            System.out.println("An error occurred.");
            e.printStackTrace();
        }
    }
}
```

- ☒ File created: filename.txt
- ☐ File already exists.
- ☐ An error occurred.
- ☐ Script Error: No output



✓ What is the output of the script below *

1/1

```
import java.io.FileWriter;
import java.io.IOException;

public class WriteToFile {
    public static void main(String[] args) {
        try {
            FileWriter myWriter = new FileWriter("filename.txt");
            myWriter.write("Files in Java might be tricky, but it is fun
enough!");
            myWriter.close();
            System.out.println("Successfully wrote to the file.");
        } catch (IOException e) {
            System.out.println("An error occurred.");
            e.printStackTrace();
        }
    }
}
```

- ☒ Successfully wrote to the file.
- ☐ Files in Java might be tricky, but it is fun enough!
- ☐ Successfully wrote to the file?
- ☐ An error occurred.



✗ public class Main extends Thread {
 public static int amount = 0;

*0/1

```
    public static void main(String[] args) {  
        Main thread = new Main();  
        thread.start();  
        System.out.println(amount);  
        amount++;  
        System.out.println(amount);  
    }
```

```
    public void run() {  
        amount++;  
    }  
}
```

What are the output to the above script (More than one answer is possible)

- ☒ 0
- ☐ 2
- ☐ 3
- ☐ 4
- ☐ 1
- ☐ 5
- ☐ Error



Correct answer

- ☒ 0
- ☒ 2

Feedback

0





*0/1

```
import java.util.regex.Matcher;
import java.util.regex.Pattern;

public class Main {
    public static void main(String[] args) {
        Pattern pattern = Pattern.compile("w3schools",
        Pattern.CASE_INSENSITIVE);
        Matcher matcher = pattern.matcher("Visit W3Schools!");
        boolean matchFound = matcher.find();
        if(matchFound) {
            System.out.println("Match found");
        } else {
            System.out.println("Match not found");
        }
    }
}
```

What is the output of the script above?

- ☐ Match found
- ☐ Match not found
- ☐ "Match found"
- ☒ "Match not found"



Correct answer

- ☒ Match found





*0/1

```
import java.util.regex.Matcher;
import java.util.regex.Pattern;

public class Main {
    public static void main(String[] args) {
        Pattern pattern = Pattern.compile("w3schools",
        Pattern.CASE_INSENSITIVE);
        Matcher matcher = pattern.matcher("Visit W3Schools!");
        boolean matchFound = matcher.find();
        if(matchFound) {
            System.out.println("Match found");
        } else {
            System.out.println("Match not found");
        }
    }
}
```

What is the output of the script above?

- ☐ Match found
- ☐ Match not found
- ☐ "Match found"
- ☒ "Match not found"



Correct answer

- ☒ Match found



✗ import java.util.ArrayList;
import java.util.Iterator;

*

0/1

```
public class Main {  
    public static void main(String[] args) {  
  
        // Make a collection  
        ArrayList<String> cars = new ArrayList<String>();  
        cars.add("Volvo");  
        cars.add("BMW");  
        cars.add("Ford");  
        cars.add("Mazda");  
  
        // Get the iterator  
        Iterator<String> it = cars.iterator();  
  
        // Print the first item  
        System.out.println(it.next());  
    }  
}
```

What will be the output of the above java script?

☐ Volvo

☒ BMW

✗

☐ Ford

☐ Mazda

Correct answer

☒ Volvo





```
enum Level {  
    LOW,  
    MEDIUM,  
    HIGH  
}
```

*

1/1

```
public class Main {  
    public static void main(String[] args) {  
        Level myVar = Level.MEDIUM;  
        System.out.println(myVar);  
    }  
}
```

What is the output of the above script?

- ☒ MEDIUM
- ☐ LOW
- ☐ HIGH
- ☐ All





```
class OuterClass {  
    int x = 10;
```

```
    class InnerClass {  
        int y = 5;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        OuterClass myOuter = new OuterClass();  
        OuterClass.InnerClass myInner = myOuter.new InnerClass();  
        System.out.println(myInner.y + myOuter.x);  
    }  
}
```

What is the output of the above script?

- ☒ 15
- ☐ 5
- ☐ 10
- ☐ Error

1/1





```
class OuterClass {  
    int x = 10;
```

*

1/1

```
    static class InnerClass {  
        int y = 5;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        OuterClass.InnerClass myInner = new OuterClass.InnerClass();  
        System.out.println(myInner.y);  
    }  
}
```

What is the output of the above script?

- ☐ 15
- ☒ 5
- ☐ 10
- ☐ Error



✗ If a class that inherits a method from a super class, you have opportunity *0/1 to

- ☐ overload method
- ☐ override method
- ☐ clone method
- ☒ All of the above

✗

Correct answer

- ☒ override method

✗ If a class inherits class then it must implement the methods in subclass *0/1 unless the class is also

- ☐ inner class
- ☐ inter Face
- ☐ abstract
- ☒ All of the above

✗

Correct answer

- ☒ abstract



✓ `class TIH {` *
 `TIH () {}`
}

1/1

- ☐ method
- ☒ constructor
- ☐ Both
- ☐ None

✓

✗ Which of the following is Wrong *

0/1

- ☐ class can be nested
- ☒ Interface can be nested
- ☐ Both
- ☐ None

✗

Correct answer

- ☒ None



✗ Which of the following can have both abstract and non- abstract method? * 0/1

- ☒ interface
- ☐ abstract class
- ☐ inner class
- ☐ All

✗

Correct answer

- ☒ abstract class

✗ Interface can have only _____ variables. *

0/1

- ☐ Static
- ☐ final
- ☒ non-static & final
- ☐ Static & final

✗

Correct answer

- ☒ Static & final



✗ Interface can have only _____ variables. *

0/1

- ☒ Static
- ☐ final
- ☐ non-static & final
- ☐ Static & final

✗

Correct answer

- ☒ Static & final

✓ Members of java interface are by default *

1/1

- ☒ public
- ☐ private
- ☐ protected
- ☐ default

✓

✓ Grouping of similar type of classes, interfaces, sub-packages are known as *1/1

- ☐ JAR
- ☐ WAR
- ☐ EAR
- ☒ Package

✓



✗ Which of the following is not correct? *

0/1

- ☐ Java package removes namespace collision
- ☐ Polymorphism is implemented using either overloading or overriding
- ☐ Java is a pure OOP Language
- ☒ Interface can extend interface

✗

Correct answer

- ☒ Java is a pure OOP Language

✓ Which of the following is correct? *

1/1

- ☐ Java program can be written without class as well
- ☐ Both this() and super() can be used together in a constructor
- ☐ We can create only one instance from one class
- ☒ static keyword can be applied to variables, methods, blocks and nested class

✓

✓ Which member variables/functions cannot be accessed by subclasses? * 1/1

- ☒ private
- ☐ public
- ☐ protected
- ☐ default

✓



✗ Which of the following statement is correct? *

0/1

- ☐ final variables value can be modified in java.
- ☒ final method can be override in java
- ☐ final class cannot be sub-classed
- ☐ final cannot be used with class or methods.

✗

Correct answer

- ☒ final class cannot be sub-classed

✓ Can we declare a Final constructor? *

1/1

- ☐ Yes
- ☒ No
- ☐ Depends on the situation
- ☐ None of the above

✓



✗ Parent class of all the java class is *

0/1

- ☐ Collections
- ☐ Object
- ☒ Super
- ☐ Collection

✗

Correct answer

- ☒ Object

Feedback

Object class is the super class of all the classes in java.

✓ Java is portable and platform independent because of _____ and _____ . *1/1

- ☐ bytecode and interpretor
- ☐ bytecode and code
- ☐ JVM and interpretor
- ☒ JVM and bytecode

✓

Feedback

JVM and bytecode is the reason behind the java platform independence and portable nature.



✗ Which of the following is true about instance variable? *

0/1

- ☐ It should be static
- ☐ It should be declared inside method.
- ☐ It holds unique value for each instance
- ☒ None of the above

✗

Correct answer

- ☒ It holds unique value for each instance

✗ String in java is a *

0/1

- ☐ primitive data type
- ☐ Class
- ☐ Mutable
- ☒ None of the above

✗

Correct answer

- ☒ Class



✗ Wrapping up of data and function into a single unit called class is known as *0/1

- ☒ binding
- ☐ overriding
- ☐ serialization
- ☐ encapsulation

✗

Correct answer

- ☒ encapsulation

✗ Using which collection class ensures insertion order of the element is maintained *0/1

- ☒ HashSet
- ☐ LinkedHashSet
- ☐ TreeSet
- ☐ Vector

✗

Correct answer

- ☒ LinkedHashSet



✓ Which method is called before garbage is collected in java? *

1/1

- ☐ collect()
- ☐ synchronized()
- ☒ finalize()
- ☐ no method is called



✗ How many instance of abstract class can be created? *

0/1

- ☒ Multiple
- ☐ 1
- ☐ 2
- ☐ 0



Correct answer

- ☒ 0

Feedback

Abstract class cannot be instantiated. So it will have 0 instances.



✗ An Interface can _____ an interface *

0/1

- ☐ implements
- ☐ extends
- ☐ override
- ☒ overload

✗

Correct answer

- ☒ extends

✗ Can we have multiple public class in java? *

0/1

- ☒ Yes
- ☐ No
- ☐ Depends on Editor
- ☐ None

✗

Correct answer

- ☒ No

Feedback

We cannot have more than one public class in single java source file.



✗ Default value of instance variable is: *

0/1

- ☒ null
- ☐ 0
- ☐ Depends on Variable Type
- ☐ 1

✗

Correct answer

- ☒ Depends on Variable Type

Feedback

Instance variable default value depends on type of variable. For example int will have 0 and object will have null default value.

✗ The place where compiled .class file is searched is known as: *

0/1

- ☐ path
- ☐ classpath
- ☐ directory
- ☒ package

✗

Correct answer

- ☒ classpath



✓ Parent class variable can be referred using *

1/1

- ☐ this
- ☒ super
- ☐ transient
- ☐ final



Feedback

super keyword is used to refer to parent class method, variable and constructors.

✓ main() method in java can be? *

1/1

- ☐ overridden
- ☐ extended
- ☒ overloaded
- ☐ none of the above



Feedback

Main method in java can be overloaded.



✗ Which of the following has more restrictive power? *

0/1

- ☐ public
- ☐ private
- ☒ protected
- ☐ default

✗

Correct answer

- ☒ private

Feedback

Private is most restrictive of all.

✗ Can a java class be inherited by more than one class? *

0/1

- ☒ yes
- ☐ no
- ☐ sometimes possible
- ☐ depends on JVM

✗

Correct answer

- ☒ no

Feedback

Multiple inheritance is not allowed in java.



✓ Which method of the Runnable interface that must be implemented by all threads? *1/1

- ☐ start()
- ☐ sleep()
- ☐ wait()
- ☒ run()



✓ Suppose there are going to be lots and lots of elements in a List. You need to perform large number of insert and delete operations on this list. Which list class would be most preferable. *1/1

- ☐ ArrayList
- ☐ Vector
- ☒ LinkedList
- ☐ None



Feedback

LinkedList is most suitable for insertion and deletion operation as minimum nodes are to be affected during add and delete.



✓ Which of the following is not OOP concept? *

1/1

- ☐ Inheritance
- ☐ Polymorphism
- ☒ Serialization
- ☐ Encapsulation



Feedback

OOP: Inheritance, Polymorphism, Encapsulation, Abstraction.

✓ Choose the correct option about break statement in java *

1/1

- ☐ Break forces the control out of the loop and starts the execution of next iteration.
- ☒ Break halts the execution and forces the control out of the loop
- ☐ Break stops the execution of entire program
- ☐ All are wrong



Feedback

Break halts the execution and forces the control out of the loop



✓ Which of the following is used with Switch case? *

1/1

- ☐ do
- ☐ continue
- ☐ exit
- ☒ break



Feedback

Break is used in switch case to let the control move out of switch case

✓ Which is not a decision making statement? *

1/1

- ☐ if
- ☐ if-else-if
- ☒ do-while
- ☐ switch-case



Feedback

do-while is a loop control statement in java



✓ Which loop will execute atleast once even when testing condition is false?

*1/1

- ☒ do-while loop
- ☐ for loop
- ☐ while loop
- ☐ for each loop



Feedback

do-while will execute atleast once even if testing condition is false.

✗ Which is invalid identifier with main method? *

0/1

- ☐ public
- ☒ static
- ☐ private
- ☐ final



Correct answer

- ☒ private

Feedback

main() cannot be private as it needs to be invoked by JVM. Making private will make it invisible.



✓ Correct extension of compiled java files is *

1/1

- ☐ .java
- ☐ .javac
- ☒ .class
- ☐ .txt



Feedback

java files when compiled are converted to portable .class files.

✗ Partial abstraction in java is provided by *

0/1

- ☒ interface
- ☐ overloading
- ☐ abstract class
- ☐ overriding



Correct answer

- ☒ abstract class

Feedback

Abstract class provides partial abstraction in java.



✓ Which of the following keyword helps in creating object in java? *

1/1

- ☒ new
- ☐ this
- ☐ malloc
- ☐ calloc



Feedback

new keyword helps in creating object in java

✓ Which of the following is valid declaration of object in java? *

1/1

- ☐ Boy obj = new Boy;
- ☒ Boy obj = new Boy();
- ☐ obj = new Boy();
- ☐ new Boy obj;



✗ Which of the following statement is incorrect? *

0/1

- ☐ main() method is public
- ☐ We can have more than one class in a single java source file.
- ☐ Every java class must contain main() method
- ☒ super is used to call parent class method or constructor

✗

Correct answer

- ☒ Every java class must contain main() method

Feedback

Not mandatory for every java class to have main() method.

✓ What is a suitable return type of a method that does not return any value? * 1/1

- ☐ int
- ☐ float
- ☐ double
- ☒ void

✓

Feedback

void means method will return nothing



✓ Which of the following entity has same name as that of the class? * 1/1

- ☐ method
- ☐ sub-class
- ☐ clone-able object
- ☒ constructor



Feedback

constructor has same name as that of class.

✓ Which can be declared only once in a program? * 1/1

- ☒ main() method
- ☐ static method
- ☐ private method
- ☐ final method



Feedback

main() method can be defined only once in a java program



✓ Which keyword is used to refer to the current object that invoked it? * 1/1

- ☐ super
- ☐ static
- ☐ transient
- ☒ this



Feedback

this keyword is used inside any method to refer to the current object

✗ Which operator is in Java to free the garbage memory? * 0/1

- ☐ free
- ☒ new
- ☐ dealloc
- ☐ None of them



Correct answer

- ☒ None of them

Feedback

Java free's memory automatically. We do not need to explicitly delete an element.

Automatic garbage collection mechanism is provided by java.



✓ Which method is called by garbage collector before it claims the garbage?

*1/1

- ☐ final () method
- ☒ finalize() method
- ☐ deserialize() method
- ☐ None of them



Feedback

finalize is called before garbage is collected.

✗ What would be behavior if constructor has a return type? *

0/1

- ☐ runtime error
- ☐ normal flow
- ☐ compilation error
- ☒ None of them



Correct answer

- ☒ compilation error



✗ What is true about constructor? *

0/1

- ☐ Constructors cannot be synchronized in Java
- ☐ Java does not provide default copy constructor
- ☐ Constructor can be overloaded
- ☒ "this" and "super" can be used in a constructor

✗

Correct answer

- ☒ Constructor can be overloaded

Feedback

We can overload constructors just like methods in java.

✗ Which exception is thrown when java is out of memory? *

0/1

- ☐ FullMemoryException
- ☒ MemoryOutOfBoundsException
- ☐ Error
- ☐ OutOfMemoryError

✗

Correct answer

- ☒ OutOfMemoryError

Feedback

java.lang.OutOfMemoryError is thrown



✓ The process of defining two or more methods within same class that have same name but different parameters declaration. *1/1

- ☐ method overriding
- ☒ method overloadig
- ☐ method hiding
- ☐ method cloning



Feedback

Two or more methods can have same name as long as their parameters declaration is different, the methods are said to be overloaded and process is called method overloading

✓ What can be overloaded in java? * 1/1

- ☐ method
- ☐ constructor
- ☒ both of the above
- ☐ none of the above



Feedback

Both method and constructors can be overloaded in java.



✓ What is the process of defining a method in terms of itself, that is a method that calls itself? *1/1

- ☐ polymorphism
- ☐ abstraction
- ☒ recursion
- ☐ inheritance

✓

Feedback

Recursion- method calling itself repeatedly

✓ Which of these access specifiers must be used for main() method? * 1/1

- ☒ public
- ☐ private
- ☐ protected
- ☐ prevented

✓



✓ Which of these is used to access member of class before object of that class is created? *1/1

- ☐ public
- ☒ static
- ☐ transient
- ☐ non-static



✓ Which one of the following is not an access modifier? * 1/1

- ☐ public
- ☐ private
- ☐ protected
- ☒ void



Feedback

Public, private, protected and default are the access modifiers.



✓ Which one of the following modifier means a particular variable cannot be accessed within the package owing is not an access modifier? *1/1

- ☐ public
- ☒ private
- ☐ protected
- ☐ default



Feedback

Private variables are accessible only within the same class.

✗ Modifier accessible within same package and outside package by online child class *0/1

- ☐ public
- ☐ private
- ☐ protected
- ☒ default



Correct answer

- ☒ protected



✓ All the variables of interface should be: *

1/1

- ☐ public and final
- ☒ public, static and final
- ☐ public and static
- ☐ protected, static, final



✗ Which one of the following statement is wrong? *

0/1

- ☒ Parsing in java refers to converting String to date format
- ☐ Marker interface in java is an empty interface. It has no variables or methods declared inside
- ☐ finally in java is useful in case there is some clean up activity like closing open connection, etc to be performed. and it should be placed only after the last catch block, if catch block is used.
- ☐ throwable is the base class of all the Exception and Error in java
- ☐ None



Correct answer

- ☒ None



✓ Which of the following is method of Object class? *

1/1

- ☐ equal()
- ☐ hashCode()
- ☐ finalize()
- ☒ All of them
- ☐ None of them



Feedback

All the methods given below is provided by Object class

clone() - Creates and returns a copy of this object.

equals() - Indicates whether some other object is "equal to" this one.

finalize() - Called by the garbage collector on an object when garbage collection determines that there are no more references to the object.

getClass() - Returns the runtime class of an object.

hashCode() - Returns a hash code value for the object.

notify() - Wakes up a single thread that is waiting on this object's monitor.

notifyAll() - Wakes up all threads that are waiting on this object's monitor.

toString() - Returns a string representation of the object.

wait() - Causes current thread to wait until another thread invokes the *notify()* method or the *notifyAll()* method for this object.



✗ Which of the following converts human readable file into platform independent code file in Java?

*0/1

- ☒ JVM
- ☐ JRE
- ☐ Applet
- ☐ Comiler

✗

Correct answer

- ☒ Comiler

✓ Choose the option below which can show polymorphism. *

1/1

- ☐ Overloading ||
- ☒ Overloading <<
- ☐ Overloading &&
- ☐ Overlaoding +=

✓

Feedback

Overloading << can show polymorphism.





Which of this keyword must be used to inherit a class? *

1/1

- ☐ this
- ☐ super
- ☐ extent
- ☒ extends



Which inheritance in java programming is not supported *

0/1

- ☐ Single inheritance
- ☒ Multilevel inheritance
- ☐ Multiple inheritance using classes
- ☐ Multiple inheritance using interfaces



Correct answer

- ☒ Multiple inheritance using classes

This content is neither created nor endorsed by Google. - [Terms of Service](#) - [Privacy Policy](#).

Google Forms



