

Fibonacci series Program

```
import java.util.Scanner;
class Fibonacci
{
public void series(int n)
{
int a=0,b=1,sum,i;
for(i=1;i<=n;i++)
{
System.out.println(a +" ");
sum=a+b;
a=b;
b=sum;
}
}
}
```

- class UseFibonacci
- {
- public static void main(String [] args)
- {
- Scanner kb=new Scanner(System.in);
- System.out.println("Enter the Nth term of Fibonacci Series:");
- int n=kb.nextInt();
- Fibonacci obj=new Fibonacci();
- obj.series(n);
- }
- }

Perfect Number Program

- `import java.util.Scanner;`
- `class PerfectNumber`
- `{`
- `public static void main(String[] args)`
- `{`
- `int n, sum = 0;`
- `Scanner s = new Scanner(System.in);`
- `System.out.println("Enter the number you want to`
`check:");`
- `n = s.nextInt();`

- for(int i = 1; i < n; i++)
- {
- if(n % i == 0)
- {
- sum = sum + i;
- }
- }
- if(sum == n)
- {
- System.out.println("Given number is Perfect");
- }

- else
- {
- System.out.println("Given number is
not Perfect");
- }
- }
-
- }

Factorial Program

- `import java.util.Scanner;`
- `class Fact`
- `{`
- `public static void main(String [] args)`
- `{`
- `Scanner kb=new Scanner(System.in);`
- `int n,fact=1;`
- `System.out.println("Enter a number");`
- `n=kb.nextInt();`

- while(n>1)
- {
- fact=fact*n;
- n--;
- }
- System.out.println("factorial is "+fact);
- }
- }

Palindrome Program

- import java.util.Scanner;
- class Palindrome
- {
- public static void main(String [] args)
- {
- Scanner kb=new Scanner(System.in);
- int rem,sum=0,temp;
- System.out.println("Enter the number");
- int n=kb.nextInt();//It is the number variable to
be checked for palindrome
- }

- temp=n;
- while(n>0)
- {
- rem=n%10; //getting remainder
- sum=(sum*10)+rem;
- n=n/10;
- }
- if(temp==sum)
- System.out.println("palindrome number ");
- else
- System.out.println("not palindrome");
- }
- }

Reverse String Program

- `import java.util.Scanner;`
- `class ReverseString`
- `{`
- `public static void main(String[] args)`
- `{`
- `System.out.println("Enter string to reverse:");`
-
- `Scanner kb = new Scanner(System.in);`
- `String str = kb.nextLine();`
- `String reverse = "";`

- `for(int i = str.length() - 1; i >= 0; i--)`
- `{`
- `reverse = reverse + str.charAt(i);`
- `}`
-
- `System.out.println("Reversed string is:");`
- `System.out.println(reverse);`
- `}`
- `}`

GCD Program

- import java.util.Scanner;
- class GCD
- {
- public int gcd(int a,int b)
- {
- if (b==0)
- {
- return a;
- }
- else
- {
- return gcd(b,a%b);
- }
- }
- }

- class UseGCD
- {
- public static void main(String[] args)
- {
- Scanner kb=new Scanner(System.in);
- System.out.println("Enter 2 numbers:");
- int a=kb.nextInt();
- int b=kb.nextInt();
- GCD obj=new GCD();
- int g= obj.gcd(a,b);
- System.out.println("GCD is :"+g);
- }
- }
-

Prime Number Program

- class Prime
- {
- public int IsPrime(int n)
- {
-
- if(n==1 || n==0)
- {
- return 1;
- }
- for (int i=2;i<n;i++)
- {
- if(n%i==0)
- {
- return 1;
- }
- }
- return 0;
- }
- }

- class UsePrime
- {
- public static void main(String [] args)
- {
- Scanner kb=new Scanner(System.in);
- System.out.println("Enter a number to check whether it is prime or not?");
- int n=kb.nextInt();
- Prime obj=new Prime();
- int g=obj.IsPrime(n);

- if (g==0)
- {
- System.out.println("Prime number");
- }
- else
- {
- System.out.println("Non Prime Number");
- }
- }
- }

Sort Array Program

- `import java.util.Scanner;`
- `class SortedArray`
- `{`
- `public static void main(String [] args)`
- `{`
- `Scanner kb=new Scanner(System.in);`
- `System.out.println("Enter the size of array");`
- `int n=kb.nextInt();`
- `int c;`
- `int [] arr=new int[n];`
- `System.out.println("Enter "+n+ " Numbers");`

- for (int i=0;i<arr.length;i++)
- {
- arr[i]=kb.nextInt();
- }
- for (int i=0;i<arr.length;i++)
- {
- for(int j=i+1;j<arr.length;j++)
- {
- if (arr[i]>arr[j])
- {
- c=arr[i];
- arr[i]=arr[j];
- arr[j]=c;
- }
- }
- }
- }

- `System.out.println("Sorted array is ");`
- `for (int i=0;i<arr.length;i++)`
- `{`
- `System.out.println(arr[i]);`
- `}`
- `}`
- `}`