ENTERPRISE ERP · DEVELOPER DOCUMENTATION

Enterprise ERP — API Reference

REST API ka mukammal hawala: authentication, tenancy, permissions aur har endpoint ki tafseel — Hinglish mein.

Version	1.0.0 (OpenAPI 3.1.0)
Date	2026-10-15
Base URL (local)	`http://localhost:8000/api/v1`
Base URL (production example)	`https://api.example.com/api/v1`
Coverage	314 paths · 533 operations · 148 schemas

Source: `docs/api/openapi.yaml` (generated from code by `backend/tools/openapi/gen.php`) · Proprietary

Fehrist (Table of contents)

1 · Shuruaat

1. Ta'aruf (Introduction)
2. Authentication flow
3. Tenancy: X-Company-Id
4. Permissions model
5. Request/response envelope & errors
6. Pagination, search, sort, filter
7. Money, numbers & dates
8. Rate limits
9. File uploads & downloads
10. Versioning

2 · Endpoint reference

Module	Operations	GET	POST	PUT/PATCH	DELETE
Health	**2**	2	0	0	0
Auth	**17**	3	12	2	0
Company	**19**	8	3	5	3
Access	**16**	7	3	4	2
Notifications	**7**	3	1	2	1
HR	**82**	33	23	17	9
Payroll	**38**	18	10	6	4
Finance – Ledger	**42**	20	10	8	4
Finance – Receivables	**38**	14	15	6	3
Sales	**67**	22	22	15	8
Procurement	**56**	17	21	12	6
Inventory	**60**	24	14	14	8
Projects	**47**	17	8	15	7
Documents	**17**	7	4	4	2
Dashboard	**1**	1	0	0	0
Approvals	**2**	2	0	0	0
Reports	**6**	5	1	0	0
Search	**1**	1	0	0	0
Platform	**15**	7	3	4	1
Total	**533**	**211**	**150**	**114**	**58**

3 · Appendices

A. Schemas
B. Enums
C. Permission slugs → endpoints

SHURUAAT

Ta'aruf (Introduction)

Ye document Enterprise ERP ke REST API ka mukammal reference hai. Backend Laravel 13 par bana hai aur authentication Laravel Sanctum ke **SPA (stateful cookie)** mode se hoti hai. Ye reference seedha code se generate hone wali OpenAPI 3.1 spec (`docs/api/openapi.yaml`, version `1.0.0`) se banaya gaya hai: **314 paths** par **533 operations**, aur **148 schemas**.

Base URL (local)	`http://localhost:8000/api/v1`
Base URL (production example)	`https://api.example.com/api/v1`
CSRF cookie route	`GET /sanctum/csrf-cookie` — ye `/api/v1` se bahar web route hai (local: `http://localhost:8000/sanctum/csrf-cookie`)
Format	JSON (`Accept: application/json`); uploads `multipart/form-data`
Auth	Session cookie `enterprise-erp-session` + `X-XSRF-TOKEN` header (mutating requests par)
Tenant	`X-Company-Id` header (module routes par zaroori)

Is document ko kaise parhein

- **Shuruaat** chapters mein woh sab conventions hain jo har endpoint par lagu hote hain (auth, tenancy, permissions, envelope, errors, pagination, money/dates, rate limits, files, versioning). Ye cheezein har endpoint par dobara nahi likhi gayin.
- **Endpoint reference** har module (tag) ke liye ek naye page se shuru hota hai: pehle module ka ta'aruf aur overview table, phir har operation ka card.
- Har card mein: method badge, poora path, summary, Hinglish wazahat, auth/permission/throttle, parameters, request body fields (nested arrays `lines[].field` ki shakal mein), create endpoints ke liye example JSON, aur responses.
- **Appendix A** mein saare object schemas, **Appendix B** mein enums, aur **Appendix C** mein permission slug → endpoints index hai. Blue links clickable hain.
- Kuch responses par shape inferred from code likha hai: ye ad-hoc JSON (reports, dashboards, summaries) hai jiski shape controller code se infer ki gayi hai, is liye kam precise ho sakti hai.

Method colours: GET read · POST create/action · PUT PATCH update · DELETE delete.

SHURUAAT

Authentication flow

API **Sanctum SPA cookie authentication** use karti hai — koi bearer token ya API key nahi hoti, aur kuch bhi secret `localStorage` mein nahi rakha jata. Browser ko `HttpOnly`, `SameSite=Lax` (production mein `Secure`) session cookie milti hai. Cookie ka naam `enterprise-erp-session` hai (`SESSION_COOKIE` se set hota hai; Laravel ka default `laravel_session` hota). CORS sirf configured frontend origin (`FRONTEND_URL`) ke liye credentials allow karta hai, aur `SANCTUM_STATEFUL_DOMAINS` / `SESSION_DOMAIN` frontend host se match hone chahiye.

Step 1 — CSRF cookie lein

`GET /sanctum/csrf-cookie` call karein (ye `/api/v1` ke bahar hai). Server `XSRF-TOKEN` cookie set karta hai. Is cookie ki **URL-decoded** value har mutating request (POST/PUT/PATCH/DELETE) mein `X-XSRF-TOKEN` header ke taur par bhejni hoti hai. Axios ye kaam khud karta hai; curl mein haath se karna padta hai.

```
# cookie jar file: cookies.txt   (Origin/Referer frontend ka hona chahiye — SANCTUM_STATEFUL_DOMAINS)
curl -s -c cookies.txt -b cookies.txt \
  -H "Accept: application/json" -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" \
  http://localhost:8000/sanctum/csrf-cookie

# XSRF-TOKEN cookie ki value nikaal kar URL-decode karein (%3D → =)
XSRF=$(awk '$6=="XSRF-TOKEN"{print $7}' cookies.txt | sed 's/%3D/=/g')
```

Step 2 — Login

`POST /auth/login` par `email`, `password` (aur optional `remember`) bhejein, `X-XSRF-TOKEN` header ke saath. Is route par alag `login` rate limit hai: 5/minute per email+IP aur 30/minute per IP. Galat email aur galat password dono par ek jaisa message milta hai (account ka wujood zahir nahi hota).

```
curl -s -c cookies.txt -b cookies.txt \
  -H "Accept: application/json" -H "Content-Type: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" \
  -H "X-XSRF-TOKEN: $XSRF" \
  -d '{"email":"ali.raza@example.com","password":"S3cure-Passw0rd","remember":false}' \
  http://localhost:8000/api/v1/auth/login
```

Response do mein se ek shape ka hota hai:

- `{"two_factor": false, "session": {...}}` — login mukammal; session cookie jar mein aa gayi.
- `{"two_factor": true}` — user ka 2FA on hai. User **abhi authenticated nahi**; session mein ek short-lived challenge rakha gaya hai. Step 3 par jayein.

Tip: har response naya `XSRF-TOKEN` cookie bhi bhej sakta hai — curl script mein mutating request se pehle `$XSRF` ko cookie jar se dobara parh lena mehfooz hai.

Step 3 — 2FA challenge (sirf agar `two_factor: true`)

`POST /auth/2fa/challenge` par authenticator app ka 6-digit TOTP `code` **ya** ek `recovery_code` bhejein (dono mein se ek zaroori). Recovery codes hashed aur single-use hain. Rate limit: `two-factor` 5/minute per pending 2FA session.

```
curl -s -c cookies.txt -b cookies.txt -H "Accept: application/json" -H "Content-Type: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" -H "X-XSRF-TOKEN: $XSRF" \
  -d '{"code":"123456"}' http://localhost:8000/api/v1/auth/2fa/challenge
```

Step 4 — Session bootstrap

`GET /auth/session` logged-in user, uski company memberships (`companies`), `current_company`, active company ke liye `permissions` (slugs) aur branches deta hai. Frontend isi se menu aur buttons decide karta hai — lekin asal

enforcement hamesha server par hota hai.

```
curl -s -c cookies.txt -b cookies.txt -H "Accept: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" \
  http://localhost:8000/api/v1/auth/session
```

Step 5 — Aage ki requests

- Har request session cookie bhejti hai (browser mein `withCredentials: true`).
- Har **mutating** request (POST/PUT/PATCH/DELETE) `X-XSRF-TOKEN` bhi bhejti hai. Token missing/stale ho to **419** `auth.csrf`.
- Module routes par `X-Company-Id` header (agla chapter).

```
curl -s -c cookies.txt -b cookies.txt -H "Accept: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" \
  -H "X-Company-Id: 1" "http://localhost:8000/api/v1/invoices?page=1&per_page=25&sort=-invoice_date"
```

Step 6 — Logout

`POST /auth/logout` session khatam karta hai aur `204` deta hai. Password change (`POST /auth/password`) ya reset (`POST /auth/reset-password`) par user ke **baqi saare sessions** bhi invalidate ho jate hain. Inactive (deactivated) user agli request par khud logout ho jata hai.

```
curl -s -c cookies.txt -b cookies.txt -X POST -H "Accept: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" -H "X-XSRF-TOKEN: $XSRF" \
  http://localhost:8000/api/v1/auth/logout
```

Password confirmation (re-authentication)

Kuch sensitive operations `password.confirm` middleware ke peeche hain (jaise 2FA recovery codes). In ke liye pichhle **15 minute** mein `POST /auth/confirm-password` (`{"password": "..."}`) kiya hona chahiye — response mein `confirmed_until` aata hai. Warna **423** `http.423` milta hai.

2FA on/off karna

`POST /auth/2fa/enable` ek pending secret generate karta hai; 2FA tabhi active hota hai jab `POST /auth/2fa/confirm` se TOTP code confirm ho jaye. `POST /auth/2fa/disable` se band hota hai, aur `GET /auth/2fa/recovery-codes` naye recovery codes banata hai (purane invalid ho jate hain).

SHURUAAT

Tenancy: `X-Company-Id`

System multi-company hai — `companies` tenant root hai aur har tenant-owned table mein `company_id` hota hai. `/health*`, `/auth/*` aur `/platform/*` ke ilawa **saare module routes** ek company context mein chalte hain. Active company ka id `X-Company-Id` header mein bhejein.

1. Server header parhta hai (file downloads jo naye tab mein khulte hain, unke liye `company_id` query parameter bhi chalta hai).
2. Verify karta hai ke logged-in user ki us company mein **active membership** hai.
3. Agar nahi, to **403** `tenant.forbidden`.

- **Doosri company ka record id** (URL mein) hamesha **404** deta hai — record ka wujood zahir nahi kiya jata.
- **Request body mein** doosri company ka id (jaise `customer_id`, `warehouse_id`) dena **422** `tenant.mismatch` deta hai.
- `company_id` client se kabhi trust nahi hota — create par server khud context se set karta hai.
- Branch restriction wale users (`branch_ids` membership par) sirf apni branches ke records dekhte hain.

Company switch karna

`POST /auth/switch-company` body `{"company_id": 2}` ke saath. Server membership verify karta hai aur switch audit log mein jata hai; response mein naya `Session` aata hai. Is ke baad client har request par naya `X-Company-Id` bhejta hai.

```
curl -s -c cookies.txt -b cookies.txt -H "Accept: application/json" -H "Content-Type: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" -H "X-XSRF-TOKEN: $XSRF" \
  -d '{"company_id":2}' http://localhost:8000/api/v1/auth/switch-company
```

SHURUAAT

Permissions model

Authorization do layers mein hota hai:

- **Route middleware** `permission:<slug>` — coarse RBAC. Agar route par kai slugs listed hain to **koi ek** kaafi hai.
- **Policies** — fine-grained check (har controller action `authorize()` call karta hai). Kuch abilities record ke owner / self-service ko bhi allow karti hain.

Permission slugs `module.action` format mein hain (jaise `invoices.approve`), roles ke zariye users ko milte hain, aur **active company** ke hisaab se resolve hote hain. Current user ke slugs `GET /auth/session` → `permissions` mein hain.

`x-permissions` ka matlab

Har operation par spec ka `x-permissions` route middleware aur policy abilities dono ke slugs list karta hai. Is reference mein card par ye alag dikhaye gaye hain: **Route:** (middleware slugs, "ya" = koi ek) aur **Policy:** (policy jo slugs check karti hai), saath mein policy ability (jaise `viewAny on Invoice`). Agar koi slug nahi, to sirf authentication (ya ownership) kaafi hai. Poora index Appendix C mein hai.

403 vs 404

Surat-e-haal	Response
Permission nahi / policy ne deny kiya	**403** `auth.forbidden`
`X-Company-Id` missing ya membership nahi	**403** `tenant.forbidden`
Record doosri company ka hai (URL id)	**404** `not_found` (existence disclose nahi hoti)
Body mein doosri company ka id	**422** `tenant.mismatch`
Non-platform user platform route par	**404** `not_found`

Platform roles (`platform.owner`, `platform.admin`) ki `company_id` NULL hoti hai aur sirf yehi `/api/v1/platform/*` tak pahunchte hain. Sensitive actions (payroll processing, invoice approval, user management, report export, inventory adjustment, journal posting) audit log mein darj hote hain. UI mein button chhupana kabhi akela check nahi hota.

SHURUAAT

Request/response envelope & errors

Success

- Single resource: `{ "data": { ... } }`
- List: `{ "data": [ ... ], "meta": { "pagination": { "page", "per_page", "total", "last_page" } } }`
- Create **201** deta hai (naya record `data` mein), delete **204** khaali body ke saath.

```
{
  "data": [ { "id": 41, "number": "INV-000041", "total": "1250.0000", "status": "approved" } ],
  "meta": { "pagination": { "page": 1, "per_page": 25, "total": 1, "last_page": 1 } }
}
```

Kuch endpoints jo raw paginated collection lautate hain unme Laravel paginator ki `links` /extra meta keys bhi aa sakti hain; clients ko sirf `meta.pagination` par bharosa karna chahiye.

Errors

Har error ek hi envelope use karta hai: `{ "message": string, "code": string, "errors"?: {field: [messages]}, "details"?: object }`. `message` user ko dikhane ke liye safe hai; `code` stable machine code hai — client logic isi par banayein. Validation errors ke field paths dot notation mein hote hain (jaise `lines.0.quantity`). `debug` sirf `APP_DEBUG=true` par 500 responses mein aata hai, production mein kabhi nahi.

```
HTTP/1.1 422 Unprocessable Content
{ "message": "Please correct the highlighted fields.", "code": "validation.failed",
  "errors": { "name": ["The name field is required."] } }
```

Status codes & error codes

HTTP	code	Meaning (spec)	Matlab
401	`auth.unauthenticated`	No/expired session.	Session nahi hai ya expire ho gaya — dobara login karein.
403	`auth.forbidden`	Missing permission or policy denied.	Permission nahi hai ya policy ne mana kar diya.
403	`tenant.forbidden`	No `X-Company-Id` or no active membership in that company.	`X-Company-Id` missing hai ya us company mein active membership nahi.
404	`not_found`	Unknown route/record, other company's record, or platform route for non-platform users.	Route/record nahi mila — doosri company ka record bhi 404 deta hai; platform routes non-platform users ke liye bhi 404.
409	`conflict`	Business-state conflict (e.g. approving a non-pending record).	Record ki maujooda state is action ki ijazat nahi deti (jaise non-pending record approve karna).
409	`finance.period_closed`, `finance.no_period`, `finance.immutable`	Ledger refusals.	Ledger refusal — period closed, period maujood nahi, ya posted entry immutable hai.
409	`inventory.insufficient_stock`	Outbound movement exceeds stock (`details` has the figures).	Outbound movement stock se zyada; `details` mein figures.
410	`http.410`	Expired export file.	Export file expire ho chuki — report dobara chalayein.
419	`auth.csrf`	CSRF token missing or session expired.	CSRF token missing/galat ya session expire.
422	`validation.failed`	Validation errors in `errors`.	Validation errors `errors` object mein (field → messages).
422	`tenant.mismatch`	A referenced id belongs to another company.	Body mein diya gaya koi id doosri company ka hai.
422	`finance.unbalanced`	Journal entry debits ≠ credits.	Journal entry ke debits aur credits barabar nahi.

HTTP	code	Meaning (spec)	Matlab
423	`http.423`	Password confirmation required.	Password confirmation zaroori (`POST /auth/confirm-password`).
429	`throttled`	Rate limit hit (`Retry-After` header).	Rate limit hit — `Retry-After` header dekhein.
500	`server.error`	Unexpected error (no stack traces unless APP_DEBUG).	Ghair-mutawaqqa error (APP_DEBUG ke baghair stack trace nahi).

Shared response components

Spec ke `components.responses` — endpoint cards par error list inhi ki taraf ishara karti hai:

Component	Description	Example body
`Unauthenticated`	Not authenticated.	`{"message":"Unauthenticated.","code":"auth.unauthenticated"}`
`Forbidden`	Missing permission, policy denial, or no access to the company in `X-Company-Id`.	`{"message":"You don't have permission to perform this action.","code":"auth.forbidden"}`
`NotFound`	Record not found (including records of other companies).	`{"message":"The requested record was not found.","code":"not_found"}`
`Conflict`	The record is not in a state that allows this action.	`{"message":"Only pending leave requests can be approved.","code":"conflict"}`
`Gone`	The resource has expired.	`{"message":"This export has expired. Please run it again.","code":"http.410"}`
`CsrfMismatch`	CSRF token missing/invalid or session expired.	`{"message":"Your session has expired. Please refresh and try again.","code":"auth.csrf"}`
`PasswordConfirmationRequired`	Recent password confirmation required.	`{"message":"Password confirmation required.","code":"http.423"}`
`Validation`	Validation failed.	`{"message":"Please correct the highlighted fields.","code":"validation.failed","errors":{"name":["The name field is required."]}}`
`Throttled`	Too many requests. Headers: `Retry-After`, `X-RateLimit-Limit`, `X-RateLimit-Remaining`	`{"message":"Too many attempts. Please wait a moment and try again.","code":"throttled"}`

SHURUAAT

Pagination, search, sort, filter

List endpoints (jin ke card par "List params" likha hai) ye standard query parameters lete hain. Ye parameters har card par dobara document nahi kiye gaye — sirf naam diye gaye hain.

Parameter	Type	Tafseel
`page`	integer ≥ 1	1-based page number (default 1).
`per_page`	integer 1–100	Page size, 1–100 mein clamp hota hai; default **25** (`config/erp.php` → `pagination.default`).
`search`	string ≤ 200	Case-insensitive substring match; har endpoint ke allow-listed columns card ke note mein ("`search` matches …") diye gaye hain.
`sort`	string	Endpoint ki allow-list se ek column; `-` prefix = descending (jaise `sort=-created_at`). Unknown column default par wapas chala jata hai; primary key tie-breaker ke taur par hamesha lagti hai.
`filter[<column>]`	string	Exact match. Kai values: `filter[status]=draft,approved` ya `filter[status][]=draft&filter[status][]=approved` (koi bhi match). Booleans `true`/`false`.
`from` / `to`	date `YYYY-MM-DD`	List ke main date column par inclusive range (UTC day start/end). Kaunsa column — card par likha hai.
`branch_id`	integer	Jahan supported ho, branch ke hisaab se filter.

```
GET http://localhost:8000/api/v1/invoices?page=2&per_page=50&search=INV-00&sort=-
due_date&filter[status]=approved,partially_paid&from=2026-01-01&to=2026-06-30
X-Company-Id: 1
```

Selectors ke liye kai modules mein lightweight, bina pagination wale endpoints bhi hain (jaise `/branches/all`, `/customers/all`, `/suppliers/all`, `/warehouses/all`).

SHURUAAT

Money, numbers & dates

- **Money** hamesha `DECIMAL(18,4)` **string** hai (schema `Money`, jaise `"1250.5000"`) — kabhi float nahi. Currency document ya company ke ISO-4217 `currency` code se pata chalti hai.
- Quantities, rates aur hours bhi exact decimal strings hain (schema `Decimal`). Request mein decimals **string** ke taur par bhejein (jaise `"quantity": "2.5000"`) taake float rounding na ho.
- **Timestamps** ISO-8601 UTC mein: `2026-10-15T09:30:00.000000Z`. **Plain dates**: `YYYY-MM-DD`.
- Company ka `timezone` sirf display ke liye hai; API hamesha UTC deti/leti hai.

SHURUAAT

Rate limits

Limiter	Limit	Kahan lagta hai
`api`	240 / minute per user (anonymous: per IP)	Har route
`login`	5 / minute per email+IP, 30 / minute per IP	`POST /auth/login`
`auth`	10 / minute per IP	Forgot/reset password, confirm-password, e-mail verification
`two-factor`	5 / minute per pending 2FA session	`/auth/2fa/challenge`, `/auth/2fa/confirm`
`exports`	10 / minute per user	Report/data exports
`search` (`60,1`)	60 / minute	`GET /search`

Limit hit hone par **429** `throttled` milta hai, `Retry-After` header ke saath (aur `X-RateLimit-Limit` / `X-RateLimit-Remaining`). Har endpoint card par uske limiters "Throttle" row mein likhe hain (spec ka `x-throttle`).

SHURUAAT

File uploads & downloads

Uploads (multipart)

File wale endpoints `multipart/form-data` lete hain (company logo, employee photo/documents, employment contract, leave attachment, product image, documents aur versions, expense receipt). Server MIME type, extension aur size validate karta hai; allowed types aur max size har card ke body table mein likhe hain (jaise documents: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt — max 10240 KB). Sensitive files private disk par rehti hain. Multipart par bhi `X-XSRF-TOKEN` aur `X-Company-Id` zaroori hain.

```
curl -s -c cookies.txt -b cookies.txt -H "Accept: application/json" \
  -H "Origin: http://localhost:3000" -H "Referer: http://localhost:3000/" \
  -H "X-XSRF-TOKEN: $XSRF" -H "X-Company-Id: 1" \
  -F "file=@contract.pdf" -F "title=Signed contract" -F "category=contract" \
  http://localhost:8000/api/v1/employees/7/documents
```

Note: example ki `category` value `HRDocumentCategory` enum (Appendix B) se honi chahiye.

Downloads

Download endpoints file stream karte hain (`Content-Disposition: attachment`) — policy check ke baad, aur kai audited hain. Agar file naye browser tab mein kholni ho (jahan custom header nahi bhej sakte), to `X-Company-Id` ki jagah `company_id` query parameter use karein:

```
GET http://localhost:8000/api/v1/invoices/41/pdf?company_id=1
```

Report exports

`POST /reports/{key}/export` body `{"format": "csv" | "xlsx" | "pdf", "params": ...}` . Chhota export seedha file (`200`) deta hai; bada export `202` ke saath `ExportJob` deta hai — `GET /report-exports/{exportJob}` se status dekhein aur `/download` se file lein. Expired export **410** `http.410` deta hai.

SHURUAAT

Versioning

Saare endpoints `/api/v1` prefix ke neeche hain (resource-oriented, plural nouns; actions sub-POST ki shakal mein, jaise `/invoices/{id}/approve`). Is reference mein paths `/api/v1` ke baad wale hisse ke saath likhe gaye hain; card header mein poora path dikhaya gaya hai. Breaking changes ek naye version prefix ke saath aayenge; `v1` ke andar fields add ho sakte hain, is liye clients ko unknown fields ignore karne chahiye.

Spec code se generate hoti hai (`backend/tools/openapi/gen.php`): routes, FormRequests, API Resources, Enums aur migrations se. `PUT|PATCH` ke liye register shuda routes do operations ki shakal mein document hue hain jo ek hi handler share karte hain.

MODULE

Health

> Ye public endpoints server ki liveness aur database readiness check karte hain. Load balancer ya monitoring tools inhe bina login aur bina `X-Company-Id` ke call kar sakte hain.

Spec: Liveness / readiness probes (public). — 2 operations.

Method	Path	Summary	Permission
GET	/health	Health	—
GET	/health/db	Db – health	—

Endpoints

GET /api/v1/health

Health `health`

Application ki liveness check — `status`, `app`, `environment` aur `time` deta hai.

Auth	Public (login nahi chahiye)
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api`

RESPONSES

200 — Object: shape inferred from code

`status` string `app` string `environment` string `time` string(date-time)

Errors: `429` throttled

GET /api/v1/health/db

Db – health `healthDb`

Database connectivity (readiness) check karta hai.

Auth	Public (login nahi chahiye)
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api`

RESPONSES

200 — Object: shape inferred from code

`status` string `driver` string `version` string `tls` boolean `latency_ms` number `migrations_table` boolean

Errors: `429` throttled · `503` OK

MODULE

Auth

> Login, 2FA, password management, session bootstrap aur profile/preferences yahan hain. Poora login flow (CSRF cookie → login → 2FA → session) "Shuruaat" chapter mein step-by-step samjhaya gaya hai. In routes ko tenant header ki zaroorat nahi hoti; company badalne ke liye `POST /auth/switch-company` use karein.

Spec: Login, 2FA, password management, session bootstrap and profile/preferences. — 17 operations.

Method	Path	Summary	Permission
POST	/auth/login	Login – auth	—
POST	/auth/2fa/challenge	Step 2 of login: verify TOTP or a recovery code for the pending challenge.	—
POST	/auth/forgot-password	Always responds 200 so account existence is not disclosed.	—
POST	/auth/reset-password	Reset – password	—
GET	/auth/email/verify/{id}/{hash}	Signed URL target (`verification.verify`) — hit from the email link.	—
POST	/auth/logout	Logout – auth	—
GET	/auth/session	Current user + memberships + permissions for the active company.	—
POST	/auth/switch-company	Switch company – auth	—
POST	/auth/password	Authenticated password change.	—
POST	/auth/confirm-password	Re-authentication gate for sensitive actions (`password.confirm` middleware).	—
PATCH	/auth/preferences	Preferences – auth	—
PATCH	/auth/profile	Profile – auth	—
POST	/auth/email/verification-notification	Send – verification	—
POST	/auth/2fa/enable	Generate a pending secret; 2FA only becomes active after `confirm`.	—
POST	/auth/2fa/confirm	Confirm – 2fa	—
POST	/auth/2fa/disable	Disable – 2fa	—
GET	/auth/2fa/recovery-codes	Regenerates codes; existing ones become invalid. Requires recent password confirmation.	—

Endpoints

POST `/api/v1/auth/login`

Login – auth `authLogin`

Email/password se login karta hai (login flow ka step 1). 2FA on ho to `two_factor: true` aata hai aur `POST /auth/2fa/challenge` zaroori hai.

Step 1 of login. With 2FA enabled the user is NOT authenticated yet; a short-lived challenge is stored in the session instead.

Auth: Public (login nahi chahiye) + `X-XSRF-TOKEN`
Permission: Koi permission slug nahi (sirf authentication/ownership)
Throttle: `api` `login`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`email`	string(email)	yes	maxLength 150
`password`	string	yes	maxLength 200
`remember`	boolean	no	

RESPONSES

200 — Response in shapes mein se ek: { `two_factor` } ya { `two_factor` , `session` } shape inferred from code

Errors: `419` auth.csrf · `422` validation.failed · `429` throttled

POST `/api/v1/auth/2fa/challenge`

Step 2 of login: verify TOTP or a recovery code for the pending challenge. `auth2faChallenge`

Login ka step 2: pending challenge ke liye TOTP `code` ya `recovery_code` verify karta hai.

Auth: Public (login nahi chahiye) + `X-XSRF-TOKEN`
Permission: Koi permission slug nahi (sirf authentication/ownership)
Throttle: `api` `two-factor`

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`code`	string | null	no	pattern `^\d{6}$` · `required_without:recovery_code`.
`recovery_code`	string | null	no	maxLength 30 · `required_without:code`.

RESPONSES

200 — Object: shape inferred from code

`two_factor` boolean `session` Session

Errors: `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/auth/forgot-password

Always responds 200 so account existence is not disclosed. `authPasswordEmail`

Password reset link email karta hai; account ho ya na ho, hamesha `200` deta hai.

Auth	Public (login nahi chahiye) + `X-XSRF-TOKEN`
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api` `auth`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`email`	string(email)	yes	maxLength 150

RESPONSES

200 — Object:

- `message` string

Errors: `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/auth/reset-password

Reset – password `authPasswordReset`

Email wale reset token se naya password set karta hai; user ke baqi sessions invalidate ho jate hain.

Auth	Public (login nahi chahiye) + `X-XSRF-TOKEN`
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api` `auth`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`email`	string(email)	yes	
`password`	string	yes	minLength 10 · Requires matching `password_confirmation`.
`password_confirmation`	string	yes	minLength 10
`token`	string	yes	

RESPONSES

200 — Object:

- `message` string

Errors: `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/auth/email/verify/{id}/{hash}

Signed URL target (verification.verify) — hit from the email link. authVerificationVerify

Email verification ka signed URL — user email ke link se yahan aata hai.

> Must be called through the signed URL that was e-mailed/generated (valid signature and expires query params); invalid signatures return **403**.

Auth	Public (login nahi chahiye)
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	api auth

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
id	path	string	yes	
hash	path	string	yes	

RESPONSES

200 — Object:

- message string

Errors: 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/auth/logout

Logout – auth authLogout

Current session khatam karta hai (204).

Auth	Session cookie + X-XSRF-TOKEN
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	api

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 419 auth.csrf · 429 throttled

GET /api/v1/auth/session

Current user + memberships + permissions for the active company. authSession

Current user, company memberships, active company aur uske permission slugs deta hai — SPA isi se bootstrap hota hai.

Auth	Session cookie · X-Company-Id optional
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	api

RESPONSES

200 — data : Session shape inferred from code

- user object companies object[] current_company object | null permissions any[] branches object[]

Errors: 401 auth.unauthenticated · 429 throttled

POST /api/v1/auth/switch-company

Switch company – auth `authSwitchCompany`

Active company badalta hai; membership server par verify hoti hai aur switch audit hota hai.

> Switch the active company. The membership is verified server-side and the switch is audited; the SPA then sends X-Company-Id on every request.

Auth Session cookie + `X-XSRF-TOKEN`
Permission Koi permission slug nahi (sirf authentication/ownership)
Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`company_id`	integer	yes	

RESPONSES

200 — `data` : Session shape inferred from code

`user` object `companies` object[] `current_company` object | null `permissions` any[] `branches` object[]

Errors: `401` auth.unauthenticated · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/auth/password

Authenticated password change. `authPasswordUpdate`

Logged-in user ka password badalta hai; baqi sessions invalidate ho jate hain.

Auth Session cookie + `X-XSRF-TOKEN`
Permission Koi permission slug nahi (sirf authentication/ownership)
Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`current_password`	any	yes	Must equal the user's current password.
`password`	string	yes	minLength 10 · Requires matching `password_confirmation`. `different:current_password`.
`password_confirmation`	string	yes	minLength 10

RESPONSES

200 — Object:

`message` string

Errors: `401` auth.unauthenticated · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/auth/confirm-password

Re-authentication gate for sensitive actions (password.confirm middleware). authPasswordConfirm

Password dobara confirm karta hai taake password.confirm wale sensitive actions agle 15 minute tak chal sakein.

Auth Session cookie + X-XSRF-TOKEN
Permission Koi permission slug nahi (sirf authentication/ownership)
Throttle api auth

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
password	string	yes	

RESPONSES

200 — Object: shape inferred from code

confirmed_until string(date-time)

Errors: 401 auth.unauthenticated · 419 auth.csrf · 422 validation.failed · 429 throttled

PATCH /api/v1/auth/preferences

Preferences – auth authPreferences

Logged-in user ki preferences update karta hai.

Auth Session cookie + X-XSRF-TOKEN
Permission Koi permission slug nahi (sirf authentication/ownership)
Throttle api

REQUEST BODY application/json **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
high_contrast	boolean	no	
locale	string	no	maxLength 10
theme	string	no	values: light, dark, system

RESPONSES

200 — data : object shape inferred from code

id integer name string email string preferences object

Errors: 401 auth.unauthenticated · 419 auth.csrf · 422 validation.failed · 429 throttled

PATCH /api/v1/auth/profile

Profile – auth `authProfile`

Logged-in user ka profile update karta hai.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
name	string	yes	maxLength 150
phone	string | null	no	maxLength 40

RESPONSES

200 — `data` : object shape inferred from code

`id` integer `name` string `phone` string | null

Errors: `401` auth.unauthenticated · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/auth/email/verification-notification

Send – verification `authVerificationSend`

Email verification link dobara bhejta hai.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api` `auth`

RESPONSES

200 — Object:

`message` string

Errors: `401` auth.unauthenticated · `419` auth.csrf · `429` throttled

POST /api/v1/auth/2fa/enable

Generate a pending secret; 2FA only becomes active after `confirm`. `auth2faEnable`

Naya pending 2FA secret generate karta hai; 2FA `/auth/2fa/confirm` ke baad hi active hota hai.

Requires a recent password confirmation (`POST /auth/confirm-password`); otherwise **423**.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

Sensitive action: pichhle 15 minute mein `POST /auth/confirm-password` zaroori hai, warna `423` .

RESPONSES

200 — Response in shapes mein se ek: { `message` } ya { `secret` , `qr_svg` }

Errors: `401` auth.unauthenticated · `409` conflict · `419` auth.csrf · `423` http.423 · `429` throttled

POST /api/v1/auth/2fa/confirm

Confirm – 2fa `auth2faConfirm`

TOTP code se pending 2FA setup confirm karta hai.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api` `two-factor`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
code	string	yes	pattern `^\d{6}$`

RESPONSES

200 — Object: shape inferred from code

`recovery_codes` any[]

Errors: `401` auth.unauthenticated · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/auth/2fa/disable

Disable – 2fa `auth2faDisable`

User ka 2FA band karta hai.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
password	any	yes	Must equal the user's current password.

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/auth/2fa/recovery-codes

Regenerates codes; existing ones become invalid. Requires recent password confirmation. `auth2faRecoveryCodes`

Naye recovery codes banata hai; purane invalid ho jate hain. Recent password confirmation zaroori hai.

Requires a recent password confirmation (`POST /auth/confirm-password`); otherwise **423**.

Auth Session cookie

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

Sensitive action: pichhle 15 minute mein `POST /auth/confirm-password` zaroori hai, warna `423` .

RESPONSES

200 — Response in shapes mein se ek: { `message` } ya { `recovery_codes` }

Errors: `401` auth.unauthenticated · `409` conflict · `423` http.423 · `429` throttled

MODULE

Company

> Active company ka profile aur logo, branches, departments (tree ke saath) aur company members. Ye sab requests `X-Company-Id` wali active company ke context mein chalti hain.

Spec: Current company profile, branches, departments and members. — 19 operations.

Method	Path	Summary	Permission
GET	/company	Get company	—
PUT	/company	Update company	company.settings.manage
POST	/company/logo	Create logo	company.settings.manage
DELETE	/company/logo	Delete logo	company.settings.manage
GET	/branches/all	Lightweight list for selectors & the map (all active branches, no pagination).	branches.view
GET	/branches	List branches	branches.view
POST	/branches	Create branch	branches.manage
GET	/branches/{branch}	Get branch	branches.view
PUT	/branches/{branch}	Update branch	branches.manage
PATCH	/branches/{branch}	Update branch	branches.manage
DELETE	/branches/{branch}	Delete branch	branches.manage
GET	/departments/tree	Full tree for org charts and selectors.	departments.view
GET	/departments	List departments	departments.view
POST	/departments	Create department	departments.manage
GET	/departments/{department}	Get department	departments.view
PUT	/departments/{department}	Update department	departments.manage
PATCH	/departments/{department}	Update department	departments.manage
DELETE	/departments/{department}	Delete department	departments.manage
GET	/members	List members	—

Endpoints

GET /api/v1/company

Get company companyShow

Ek company ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id required

Permission Koi permission slug nahi (sirf authentication/ownership) (view)

Throttle api

RESPONSES

200 — data : Company

id integer name string legal_name string | null slug string code string email string | null phone string | null website string | null tax_number string | null registration_number string | null address object currency string timezone string locale string date_format string fiscal_year_start_month integer logo_url string(uri) | null primary_color string | null is_active boolean is_demo boolean settings object branches_count integer users_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

PUT /api/v1/company

Update company companyUpdate

Maujooda company ko update karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id required

Permission Policy: company.settings.manage (update on Company)

Throttle api

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200
address_line2	string | null	no	maxLength 200
city	string | null	no	maxLength 100
country	string | null	no	minLength 2 · maxLength 2
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$ · Required when present (sometimes|required).
date_format	string	no	values: Y-m-d, d/m/Y, m/d/Y, d.m.Y, d M Y · Required when present (sometimes|required).
email	string(email) | null	no	maxLength 150
fiscal_year_start_month	integer	no	min 1 · max 12 · Required when present (sometimes|required).
legal_name	string | null	no	maxLength 200
locale	string	no	maxLength 10 · Required when present (sometimes|required).
name	string	no	maxLength 150 · Required when present (sometimes|required).
phone	string | null	no	maxLength 40
postal_code	string | null	no	maxLength 20
primary_color	any	no	pattern ^#[0-9a-fA-F]{6}$
registration_number	string | null	no	maxLength 60
settings	any[] | null	no	
state	string | null	no	maxLength 100
tax_number	string | null	no	maxLength 60

Field	Type	Req.	Constraints / notes
`timezone`	string	no	IANA timezone identifier. Required when present (`sometimes|required`).
`website`	string(uri) | null	no	maxLength 200

RESPONSES

200 — `data` : Company

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

POST `/api/v1/company/logo`

Create logo `companyLogoStore`

Naya logo banata hai.

Auth — Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission — Policy: `company.settings.manage` (update on Company)

Throttle — `api`

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`logo`	string(binary)	**yes**	Image file. Allowed types: png, jpg, jpeg, webp, svg. Max size … KB.

RESPONSES

200 — `data` : Company

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

DELETE `/api/v1/company/logo`

Delete logo `companyLogoDestroy`

Logo delete karta hai — kamyabi par `204` (khaali body).

Auth — Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission — Policy: `company.settings.manage` (update on Company)

Throttle — `api`

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `429` throttled

GET /api/v1/branches/all

Lightweight list for selectors & the map (all active branches, no pagination). branchesAll

Saari active branches ki halki list deta hai (selectors aur map ke liye, bina pagination).

Auth Session cookie · X-Company-Id **required**

Permission Policy: branches.view (viewAny on Branch)

Throttle api

RESPONSES

200 — data : array of Branch

id integer company_id integer name string code string is_head_office boolean email string | null phone string | null address object latitude Decimal (string) | null longitude Decimal (string) | null timezone string | null is_active boolean departments_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/branches

List branches branchesIndex

Branches ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , code , city .

Auth Session cookie · X-Company-Id **required**

Permission Policy: branches.view (viewAny on Branch)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[country]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, city, -city, created_at, -created_at · default name

RESPONSES

200 — data : array of Branch + meta.pagination

id integer company_id integer name string code string is_head_office boolean email string | null phone string | null address object latitude Decimal (string) | null longitude Decimal (string) | null timezone string | null is_active boolean departments_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/branches

Create branch branchesStore

Naya branch banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: branches.manage (create on Branch)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`address_line1`	string | null	no	maxLength 200
`address_line2`	string | null	no	maxLength 200
`city`	string | null	no	maxLength 100
`code`	string	**yes**	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `branches` (per company).
`country`	string | null	no	minLength 2 · maxLength 2
`email`	string(email) | null	no	maxLength 150
`is_active`	boolean	no	
`is_head_office`	boolean	no	
`latitude`	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`longitude`	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`name`	string	**yes**	maxLength 150
`phone`	string | null	no	maxLength 40
`postal_code`	string | null	no	maxLength 20
`state`	string | null	no	maxLength 100
`timezone`	string | null	no	IANA timezone identifier.

EXAMPLE REQUEST

```
{
  "code": "CODE-001",
  "name": "Sample name",
  "address_line1": "Shahrah-e-Faisal, Karachi",
  "address_line2": "Shahrah-e-Faisal, Karachi",
  "city": "Karachi",
  "country": "PK",
  "email": "ali.raza@example.com",
  "is_active": true
}
```

RESPONSES

201 — `data`: Branch

`id` integer `company_id` integer `name` string `code` string `is_head_office` boolean `email` string | null `phone` string | null `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `timezone` string | null `is_active` boolean `departments_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/branches/{branch}`

Get branch `branchesShow`

Ek branch ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `branches.view` (view on Branch)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
branch	path	integer	yes	ID of the Branch. · min 1

RESPONSES

200 — `data` : Branch

`id` integer `company_id` integer `name` string `code` string `is_head_office` boolean `email` string | null `phone` string | null `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `timezone` string | null `is_active` boolean `departments_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/branches/{branch}

Update branch branchesUpdate

Maujooda branch ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `branches.manage` (update on Branch)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
branch	path	integer	yes	ID of the Branch. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200
address_line2	string | null	no	maxLength 200
city	string | null	no	maxLength 100
code	string	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within branches (per company).
country	string | null	no	minLength 2 · maxLength 2
email	string(email) | null	no	maxLength 150
is_active	boolean	no	
is_head_office	boolean	no	
latitude	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
longitude	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	no	maxLength 150
phone	string | null	no	maxLength 40
postal_code	string | null	no	maxLength 20
state	string | null	no	maxLength 100
timezone	string | null	no	IANA timezone identifier.

RESPONSES

200 — `data` : Branch

`id` integer `company_id` integer `name` string `code` string `is_head_office` boolean `email` string | null `phone` string | null `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `timezone` string | null `is_active` boolean `departments_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/branches/{branch}

Update branch branchesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /branches/{branch}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `branches.manage`

DELETE /api/v1/branches/{branch}

Delete branch branchesDestroy

Branch delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `branches.manage` (delete on Branch)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
branch	path	integer	**yes**	ID of the Branch. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/departments/tree

Full tree for org charts and selectors. departmentsTree

Departments ka poora tree deta hai (org chart aur selectors ke liye).

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `departments.view` (viewAny on Department)

Throttle `api`

RESPONSES

200 — `data` : array of object shape inferred from code

`id` integer `name` string `code` string `branch_id` integer | null `manager_employee_id` integer | null `children` any[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET `/api/v1/departments`

List departments `departmentsIndex`

Departments ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` , `code` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `departments.view` (viewAny on Department)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[parent_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`name`). The primary key is always appended as a tie-breaker. · values: `name`, `-name`, `code`, `-code`, `created_at`, `-created_at` · default `name`

RESPONSES

200 — `data` : array of Department + `meta.pagination`

`id` integer `company_id` integer `branch_id` integer | null `branch` object `parent_id` integer | null `parent` object | null `manager_employee_id` integer | null `name` string `code` string `description` string | null `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/departments

Create department departmentsStore

Naya department banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `departments.manage` (create on Department)
Throttle	`api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `TenantExists`.
`code`	string	**yes**	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `departments` (per company).
`description`	string | null	no	maxLength 500
`is_active`	boolean	no	
`name`	string	**yes**	maxLength 150
`parent_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.

EXAMPLE REQUEST

```
{
  "branch_id": 1,
  "code": "CODE-001",
  "description": "Sample text",
  "is_active": true,
  "name": "Sample name",
  "parent_id": 1
}
```

RESPONSES

201 — `data` : Department

`id` integer `company_id` integer `branch_id` integer | null `branch` object `parent_id` integer | null `parent` object | null `manager_employee_id` integer | null `name` string `code` string `description` string | null `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/departments/{department}

Get department departmentsShow

Ek department ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `departments.view` (view on Department)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`department`	path	integer	**yes**	ID of the Department. · min 1

RESPONSES

200 — `data` : Department

`id` integer `company_id` integer `branch_id` integer | null `branch` object `parent_id` integer | null `parent` object | null `manager_employee_id` integer | null `name` string `code` string `description` string | null `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/departments/{department}

Update department departmentsUpdate

Maujooda department ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `departments.manage` (update on Department)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`department`	path	integer	**yes**	ID of the Department. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `TenantExists`.
`code`	string	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `departments` (per company).
`description`	string | null	no	maxLength 500
`is_active`	boolean	no	
`name`	string	no	maxLength 150
`parent_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.

RESPONSES

200 — `data` : Department

`id` integer `company_id` integer `branch_id` integer | null `branch` object `parent_id` integer | null `parent` object | null `manager_employee_id` integer | null `name` string `code` string `description` string | null `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/departments/{department}

Update department departmentsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /departments/{department}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `departments.manage`

DELETE /api/v1/departments/{department}

Delete department departmentsDestroy

Department delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `departments.manage` (delete on Department)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
department	path	integer	yes	ID of the Department. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/members

List members membersIndex

Members ki list deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
permission	query	string | null	no	maxLength 100 · pattern `^[a-z0-9_.-]+$`
search	query	string | null	no	maxLength 100

RESPONSES

200 — `data` : array of object shape inferred from code

`id` integer `name` string `email` string `avatar_url` string(uri) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Access

> Company users, roles, permission catalogue aur audit trail. Roles ke zariye permission slugs users ko milte hain; audit logs append-only hain aur sirf parhe ja sakte hain.

Spec: Company users, roles, permission catalogue and audit trail. — 16 operations.

Method	Path	Summary	Permission
GET	/users	List users	users.view
POST	/users	Create user	users.manage
GET	/users/{user}	Get user	users.view
PUT	/users/{user}	Update user	users.manage
PATCH	/users/{user}	Update user	users.manage
DELETE	/users/{user}	Delete user	users.manage
POST	/users/{user}/resend-invite	Re-sends the password-reset link so an invited user can (re)set their password.	users.manage
GET	/permissions	List permissions	roles.view
GET	/roles	List roles	roles.view
POST	/roles	Create role	roles.manage
GET	/roles/{role}	Get role	roles.view
PUT	/roles/{role}	Update role	roles.manage
PATCH	/roles/{role}	Update role	roles.manage
DELETE	/roles/{role}	Delete role	roles.manage
GET	/audit-logs	List audit logs	audit.view
GET	/audit-logs/{auditLog}	Get audit log	audit.view

Endpoints

GET /api/v1/users

List users `usersIndex`

Users ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `users.name` , `users.email` .

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `users.view` · Policy: `users.view` (viewAny on CompanyUser)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[is_default]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`

RESPONSES

200 — `data` : array of CompanyUser + `meta.pagination`

`id` integer `membership_id` integer `company_id` integer `name` string `email` string `phone` string | null

`avatar_url` string(uri) | null `user_is_active` boolean `email_verified_at` string(date-time) | null

`last_login_at` string(date-time) | null `is_active` boolean `is_default` boolean `branch_ids` any[] | null `roles` any[]

`joined_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/users

Create user usersStore

Naya user banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: users.manage · Policy: users.manage (create on CompanyUser)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
branch_ids	integer[] | null	no	
email	string(email)	**yes**	maxLength 150
name	string	**yes**	maxLength 150
role_ids	integer[]	**yes**	minItems 1

EXAMPLE REQUEST

```
{"branch_ids":[1],"email":"ali.raza@example.com","name":"Sample name","role_ids":[1]}
```

RESPONSES

201 — data : CompanyUser

id integer · membership_id integer · company_id integer · name string · email string · phone string | null
avatar_url string(uri) | null · user_is_active boolean · email_verified_at string(date-time) | null
last_login_at string(date-time) | null · is_active boolean · is_default boolean · branch_ids any[] | null · roles any[]
joined_at string(date-time) | null · created_at string(date-time) | null · updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/users/{user}

Get user usersShow

Ek user ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Route: users.view (view)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
user	path	integer	**yes**	min 1

RESPONSES

200 — data : CompanyUser

id integer · membership_id integer · company_id integer · name string · email string · phone string | null
avatar_url string(uri) | null · user_is_active boolean · email_verified_at string(date-time) | null
last_login_at string(date-time) | null · is_active boolean · is_default boolean · branch_ids any[] | null · roles any[]
joined_at string(date-time) | null · created_at string(date-time) | null · updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

PUT `/api/v1/users/{user}`

Update user `usersUpdate`

Maujooda user ko update karta hai.

> Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `users.manage` (update)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`user`	path	integer	**yes**	min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`branch_ids`	integer[] | null	no	
`is_active`	boolean	no	
`role_ids`	integer[]	no	minItems 1

RESPONSES

200 — `data`: CompanyUser

`id` integer `membership_id` integer `company_id` integer `name` string `email` string `phone` string | null
`avatar_url` string(uri) | null `user_is_active` boolean `email_verified_at` string(date-time) | null
`last_login_at` string(date-time) | null `is_active` boolean `is_default` boolean `branch_ids` any[] | null `roles` any[]
`joined_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH `/api/v1/users/{user}`

Update user `usersUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /users/{user}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `users.manage`

DELETE `/api/v1/users/{user}`

Delete user `usersDestroy`

User delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `users.manage` (delete)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`user`	path	integer	**yes**	min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

POST /api/v1/users/{user}/resend-invite

Re-sends the password-reset link so an invited user can (re)set their password. `usersResendInvite`

Invited user ko password-reset link dobara bhejta hai taake woh apna password set kar sake.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `users.manage` (update)

Throttle `api` `auth`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`user`	path	integer	**yes**	min 1

RESPONSES

200 — Object:

`message` string

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/permissions

List permissions `permissionsIndex`

Permissions ki list deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `roles.view` · Policy: `roles.view` (viewAny on Role)

Throttle `api`

RESPONSES

200 — `data` : array of objects shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/roles

List roles `rolesIndex`

Roles ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` , `slug` , `description` .

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `roles.view` · Policy: `roles.view` (viewAny on Role)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[is_system]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (`name`). The primary key is always appended as a tie-breaker. · values: `name`, `-name`, `slug`, `-slug`, `created_at`, `-created_at` · default `name`

RESPONSES

200 — `data` : array of Role + `meta.pagination`

`id` integer `company_id` integer | null `slug` string `name` string `description` string | null `is_system` boolean `is_locked` boolean `users_count` integer `permissions_count` integer `permissions` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/roles

Create role `rolesStore`

Naya role banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `roles.manage` · Policy: `roles.manage` (create on Role)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`description`	string | null	no	maxLength 300
`name`	string	**yes**	maxLength 100 · Must be unique within `roles` (per company).
`permission_ids`	integer[]	**yes**	

EXAMPLE REQUEST

```
{"description":"Sample text","name":"Sample name","permission_ids":[1]}
```

RESPONSES

201 — `data` : Role

`id` integer `company_id` integer | null `slug` string `name` string `description` string | null `is_system` boolean `is_locked` boolean `users_count` integer `permissions_count` integer `permissions` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/roles/{role}

Get role `rolesShow`

Ek role ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `roles.view` (view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`role`	path	integer	**yes**	min 1

RESPONSES

200 — `data` : Role

`id` integer `company_id` integer | null `slug` string `name` string `description` string | null `is_system` boolean `is_locked` boolean `users_count` integer `permissions_count` integer `permissions` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/roles/{role}

Update role `rolesUpdate`

Maujooda role ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `roles.manage` (update)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`role`	path	integer	**yes**	min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`description`	string | null	no	maxLength 300
`name`	string	no	maxLength 100 · Must be unique within `roles` (per company).
`permission_ids`	integer[]	no	

RESPONSES

200 — `data` : Role

`id` integer `company_id` integer | null `slug` string `name` string `description` string | null `is_system` boolean `is_locked` boolean `users_count` integer `permissions_count` integer `permissions` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/roles/{role}

Update role rolesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /roles/{role}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `roles.manage`

DELETE /api/v1/roles/{role}

Delete role rolesDestroy

Role delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `roles.manage` (delete)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`role`	path	integer	**yes**	min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/audit-logs`

List audit logs `auditLogsIndex`

Audit logs ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `entity_label` , `action` , `actor_name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `audit.view` · Policy: `audit.view` (viewAny on AuditLog)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[entity_type]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[actor_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[entity_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `created_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `created_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-created_at`). The primary key is always appended as a tie-breaker. · values: `created_at`, `-created_at`, `action`, `-action`, `entity_type`, `-entity_type` · default `-created_at`

RESPONSES

200 — `data` : array of AuditLog + `meta.pagination`

`id` integer `company_id` integer | null `company` object | null `actor` object `actor_name` string | null `action` string `entity_type` string | null `entity_id` integer | null `entity_label` string | null `old_values` any[] | null `new_values` any[] | null `context` object | null `ip_address` string | null `user_agent` string | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/audit-logs/{auditLog}

Get audit log auditLogsShow

Ek audit log ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `audit.view` · Policy: `audit.view` (view on AuditLog)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
auditLog	path	integer	yes	min 1

RESPONSES

200 — `data` : AuditLog

`id` integer `company_id` integer | null `company` object | null `actor` object `actor_name` string | null `action` string `entity_type` string | null `entity_id` integer | null `entity_label` string | null `old_values` any[] | null `new_values` any[] | null `context` object | null `ip_address` string | null `user_agent` string | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

MODULE

Notifications

> In-app notifications aur har user ki notification preferences. User apni notifications list kar sakta hai, unread count le sakta hai, read mark ya delete kar sakta hai.

Spec: In-app notifications and per-user notification preferences. — 7 operations.

Method	Path	Summary	Permission
GET	/notifications	List notifications	—
GET	/notifications/unread-count	Unread count – notification	—
GET	/notifications/preferences	Get preference	—
PUT	/notifications/preferences	Update preference	—
POST	/notifications/read-all	Read all – notification	—
PATCH	/notifications/{id}/read	Read – notification	—
DELETE	/notifications/{id}	Delete notification	—

Endpoints

GET /api/v1/notifications

List notifications `notificationsIndex`

Notifications ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth	Session cookie · `X-Company-Id` **required**
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api`
List params	`page` , `per_page` (standard — §Pagination dekhein)

RESPONSES

200 — `data` : array of Notification + `meta.pagination`

`id` string(uuid) `type` string `title` string `body` null | null `url` string(uri) | null `company_id` integer `meta` object `is_read` boolean `read_at` string(date-time) | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/notifications/unread-count

Unread count – notification `notificationsUnreadCount`

Logged-in user ki unread notifications ki ginti deta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api`

RESPONSES

200 — `data` : object shape inferred from code

`unread` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/notifications/preferences

Get preference notificationsPreferencesShow

Ek preference ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

RESPONSES

200 — `data` : object shape inferred from code

`defaults` object `known_types` any[] `preferences` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

PUT /api/v1/notifications/preferences

Update preference notificationsPreferencesUpdate

Maujooda preference ko update karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`preferences`	object[]	**yes**	maxItems 200
`preferences[].email`	boolean	no	
`preferences[].in_app`	boolean	no	

RESPONSES

200 — `data` : object shape inferred from code

`defaults` object `known_types` any[] `preferences` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/notifications/read-all

Read all – notification notificationsReadAll

User ki saari notifications ko read mark karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

RESPONSES

200 — `data` : object shape inferred from code

`marked` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `429` throttled

PATCH /api/v1/notifications/{id}/read

Read – notification notificationsRead

Ek notification ko read mark karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`id`	path	string(uuid)	**yes**	

RESPONSES

200 — `data` : Notification

`id` string(uuid) `type` string `title` string `body` null | null `url` string(uri) | null `company_id` integer `meta` object `is_read` boolean `read_at` string(date-time) | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

DELETE /api/v1/notifications/{id}

Delete notification notificationsDestroy

Notification delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`id`	path	string(uuid)	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

MODULE

HR

Employees, designations, attendance (check-in/out, bulk), shifts, leave types/balances/requests, holidays, employment contracts, employee documents aur performance reviews. Self-service endpoints (jaise `/employees/me`, `/leave-balances/mine`) logged-in employee ka apna data dete hain.

Spec: Employees, attendance, shifts, leave, holidays, contracts, documents, performance reviews. — 82 operations.

Method	Path	Summary	Permission
GET	/designations	List designations	employees.view
POST	/designations	Create designation	employees.update
GET	/designations/{designation}	Get designation	employees.view
PUT	/designations/{designation}	Update designation	employees.update
PATCH	/designations/{designation}	Update designation	employees.update
DELETE	/designations/{designation}	Delete designation	employees.update
GET	/employees/me	Me – employee	—
GET	/employees/directory	Lightweight list of everyone on the books (selectors, org chart).	employees.view
GET	/employees/org-chart	Reporting-line tree (roots are employees without a manager).	employees.view
POST	/employees/{employee}/terminate	Terminate – employee	employees.update
POST	/employees/{employee}/reactivate	Reactivate – employee	employees.update
POST	/employees/{employee}/photo	Photo – employee	employees.update
GET	/employees/{employee}/shifts	Shift history for one employee.	shifts.manage attendance.view employees.view
POST	/employees/{employee}/shifts	Assign a shift; the previous open-ended assignment is closed the day before.	shifts.manage employees.update
GET	/employees/{employee}/documents	List documents	employees.documents.view
POST	/employees/{employee}/documents	Create document	employees.update
GET	/employees	List employees	employees.view
POST	/employees	Create employee	employees.create
GET	/employees/{employee}	Get employee	employees.view employees.update
PUT	/employees/{employee}	Update employee	employees.update
PATCH	/employees/{employee}	Update employee	employees.update
DELETE	/employees/{employee}	Delete employee	employees.delete
GET	/employee-documents/{employee_document}/download	Download – employee document	employees.documents.view
DELETE	/employee-documents/{employee_document}	Delete employee document	employees.update

Method	Path	Summary	Permission
GET	/employment-contracts/{employment_contract}/document	Document – employment contract	employees.view employees.documents.view
GET	/employment-contracts	List employment contracts	employees.view
POST	/employment-contracts	Create employment contract	employees.update
GET	/employment-contracts/{employment_contract}	Get employment contract	employees.view
PUT	/employment-contracts/{employment_contract}	Update employment contract	employees.update
PATCH	/employment-contracts/{employment_contract}	Update employment contract	employees.update
DELETE	/employment-contracts/{employment_contract}	Delete employment contract	employees.update
GET	/shifts	List shifts	shifts.manage attendance.view employees.view
POST	/shifts	Create shift	shifts.manage
GET	/shifts/{shift}	Get shift	shifts.manage attendance.view employees.view
PUT	/shifts/{shift}	Update shift	shifts.manage
PATCH	/shifts/{shift}	Update shift	shifts.manage
DELETE	/shifts/{shift}	Delete shift	shifts.manage
GET	/holidays	List holidays	shifts.manage attendance.view employees.view leave.request leave.view
POST	/holidays	Create holiday	shifts.manage
GET	/holidays/{holiday}	Get holiday	shifts.manage attendance.view employees.view leave.request leave.view
PUT	/holidays/{holiday}	Update holiday	shifts.manage
PATCH	/holidays/{holiday}	Update holiday	shifts.manage
DELETE	/holidays/{holiday}	Delete holiday	shifts.manage
POST	/attendance/bulk	Bulk – attendance	attendance.manage
POST	/attendance/check-in	Check in – attendance	—
POST	/attendance/check-out	Check out – attendance	—
GET	/attendance/today	Today – attendance	—
GET	/attendance/summary	Per-employee totals for a period: ?from&to&department_id.	attendance.view
GET	/attendance	List attendance	attendance.view
POST	/attendance	Create attendance	attendance.manage
GET	/attendance/{attendance}	Get attendance	attendance.view
PUT	/attendance/{attendance}	Update attendance	attendance.manage
PATCH	/attendance/{attendance}	Update attendance	attendance.manage

Method	Path	Summary	Permission
DELETE	/attendance/{attendance}	Delete attendance	attendance.manage
GET	/leave-types	List leave types	leave.view leave.request leave.approve leave.manage
POST	/leave-types	Create leave type	leave.manage
GET	/leave-types/{leave_type}	Get leave type	leave.view leave.request leave.approve leave.manage
PUT	/leave-types/{leave_type}	Update leave type	leave.manage
PATCH	/leave-types/{leave_type}	Update leave type	leave.manage
DELETE	/leave-types/{leave_type}	Delete leave type	leave.manage
GET	/leave-balances/mine	The acting user's own balances (defaults to the current year).	—
POST	/leave-balances/generate	Generate – leave balance	leave.manage
GET	/leave-balances	List leave balances	leave.view leave.manage leave.approve
PUT	/leave-balances/{leave_balance}	Manual correction: { adjusted, entitled?, carried_forward? }.	leave.manage
POST	/leave-requests/{leave_request}/approve	Approve – leave request	leave.approve
POST	/leave-requests/{leave_request}/reject	Reject – leave request	leave.approve
POST	/leave-requests/{leave_request}/cancel	Cancel – leave request	leave.manage
GET	/leave-requests/{leave_request}/attachment	Attachment – leave request	leave.view leave.approve leave.manage
GET	/leave-requests	Holders of leave.view/approve/manage see everything; others only their own requests.	leave.view leave.request leave.approve leave.manage
POST	/leave-requests	Create leave request	leave.request
GET	/leave-requests/{leave_request}	Get leave request	leave.view leave.approve leave.manage
POST	/performance-reviews/{performance_review}/submit	Submit – performance review	performance.manage
POST	/performance-reviews/{performance_review}/acknowledge	The reviewed employee confirms they have read the review.	—
GET	/performance-reviews	List performance reviews	performance.view performance.manage
POST	/performance-reviews	Create performance review	performance.manage
GET	/performance-reviews/{performance_review}	Get performance review	performance.view performance.manage
PUT	/performance-reviews/{performance_review}	Update performance review	performance.manage
PATCH	/performance-reviews/{performance_review}	Update performance review	performance.manage
DELETE	/performance-reviews/{performance_review}	Delete performance review	performance.manage

Method	Path	Summary	Permission
GET	/hr/reports/headcount	Headcount – report	employees.view
GET	/hr/reports/attendance	Attendance – report	employees.view
GET	/hr/reports/leave	Leave – report	employees.view

Endpoints

GET /api/v1/**designations**

List designations `hrDesignationsIndex`

Designations ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `title` , `code` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `employees.view` (viewAny on Designation)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[level]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (level). The primary key is always appended as a tie-breaker. · values: title, -title, code, -code, level, -level, created_at, -created_at · default level

RESPONSES

200 — `data` : array of Designation + `meta.pagination`

`id` integer `company_id` integer `title` string `code` string `level` integer `is_active` boolean `employees_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/designations

Create designation hrDesignationsStore

Naya designation banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: employees.update (create on Designation)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
code	string	yes	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within designations (per company).
is_active	boolean	no	
level	integer	no	min 1 · max 99
title	string	yes	maxLength 150

EXAMPLE REQUEST

```
{"code":"CODE-001","is_active":true,"level":1,"title":"Sample title"}
```

RESPONSES

201 — data : Designation

id integer company_id integer title string code string level integer is_active boolean employees_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/designations/{designation}

Get designation hrDesignationsShow

Ek designation ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: employees.view (view on Designation)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
designation	path	integer	yes	ID of the Designation. · min 1

RESPONSES

200 — data : Designation

id integer company_id integer title string code string level integer is_active boolean employees_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

PUT /api/v1/designations/{designation}

Update designation hrDesignationsUpdate

Maujooda designation ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `employees.update` (update on Designation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`designation`	path	integer	yes	ID of the Designation. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`code`	string	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `designations` (per company).
`is_active`	boolean	no	
`level`	integer	no	min 1 · max 99
`title`	string	no	maxLength 150

RESPONSES

200 — `data`: Designation

`id` integer `company_id` integer `title` string `code` string `level` integer `is_active` boolean `employees_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/designations/{designation}

Update designation hrDesignationsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /designations/{designation}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `employees.update`

DELETE /api/v1/designations/{designation}

Delete designation hrDesignationsDestroy

Designation delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `employees.update` (delete on Designation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`designation`	path	integer	yes	ID of the Designation. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/employees/me

Me – employee `hrEmployeesMe`

Logged-in user ka apna employee record deta hai (self-service).

GET /employees/me — the current user's own employee record in this company. Any active member may call it (no employees.view needed); the masked sensitive block and internal HR notes are never included.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Koi permission slug nahi (sirf authentication/ownership)
Throttle	`api`

RESPONSES

200 — `data` : any shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/employees/directory

Lightweight list of everyone on the books (selectors, org chart). `hrEmployeesDirectory`

Saare employees ki halki list deta hai (selectors, org chart).

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `employees.view` (viewAny on Employee)
Throttle	`api`

RESPONSES

200 — `data` : array of object shape inferred from code

`id` integer `employee_code` string `name` string `email` string `status` enum EmployeeStatus | null `department_id` integer | null `department` string `branch_id` integer | null `designation_id` integer | null `designation` string `manager_id` integer | null `photo_url` string(uri) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/employees/org-chart

Reporting-line tree (roots are employees without a manager). `hrEmployeesOrgChart`

Reporting-line tree deta hai; roots woh employees hain jin ka koi manager nahi.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `employees.view` (viewAny on Employee)
Throttle	`api`

RESPONSES

200 — `data` : array of number shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/employees/{employee}/terminate`

Terminate – employee `hrEmployeesTerminate`

Employee ko terminate karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `employees.update` · Policy: `employees.update` (terminate on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee`	path	integer	yes	ID of the Employee. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`reason`	string	yes	maxLength 500
`terminated_at`	string(date)	yes	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.

RESPONSES

200 — `data` : Employee

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null …

aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST `/api/v1/employees/{employee}/reactivate`

Reactivate – employee `hrEmployeesReactivate`

Employee ko dobara active karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `employees.update` · Policy: `employees.update` (reactivate on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee`	path	integer	yes	ID of the Employee. · min 1

RESPONSES

200 — `data` : Employee

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null …

aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`POST` `/api/v1/employees/{employee}/photo`

Photo – employee `hrEmployeesPhoto`

Employee ki photo upload karta hai (multipart).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `employees.update` · Policy: `employees.update` (uploadPhoto on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee`	path	integer	yes	ID of the Employee. · min 1

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`photo`	string(binary)	yes	Image file. Allowed types: png, jpg, jpeg, webp. Max size … KB.

RESPONSES

200 — `data` : Employee

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null … aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/employees/{employee}/shifts`

Shift history for one employee. `hrEmployeesShiftsIndex`

Shifts ki list deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `shifts.manage` / `attendance.view` / `employees.view` (viewAny on Shift; view on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee`	path	integer	yes	ID of the Employee. · min 1

RESPONSES

200 — `data` : array of EmployeeShift

`id` integer `employee_id` integer `shift_id` integer `shift` object `effective_from` string(date) | null `effective_to` string(date) | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/employees/{employee}/shifts

Assign a shift; the previous open-ended assignment is closed the day before. hrEmployeesShiftsStore

Naya shift banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: shifts.manage · Policy: shifts.manage / employees.update (assign on Shift; update on Employee)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employee	path	integer	yes	ID of the Employee. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
effective_from	string(date)	yes	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
effective_to	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:effective_from.
shift_id	integer	yes	Validated by TenantExists.

EXAMPLE REQUEST

```
{"effective_from":"2026-10-15","effective_to":"2026-11-14","shift_id":1}
```

RESPONSES

201 — data : EmployeeShift

id integer employee_id integer shift_id integer shift object effective_from string(date) | null effective_to string(date) | null created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/employees/{employee}/documents

List documents hrEmployeesDocumentsIndex

Documents ki list deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: employees.documents.view (viewAny; viewAll on EmployeeDocument)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employee	path	integer	yes	ID of the Employee. · min 1

RESPONSES

200 — data : array of EmployeeDocument

id integer company_id integer employee_id integer title string category enum HRDocumentCategory | null mime string size_bytes integer expires_at string(date) | null is_expired boolean is_confidential boolean uploaded_by integer | null uploader object | null download_url string created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

`POST` `/api/v1/employees/{employee}/documents`

Create document `hrEmployeesDocumentsStore`

Naya document banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `employees.update` (create)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee`	path	integer	**yes**	ID of the Employee. · min 1

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`category`	enum HRDocumentCategory	**yes**	values: `contract`, `id`, `certificate`, `visa`, `other`
`expires_at`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`file`	string(binary)	**yes**	Allowed types: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt. Max size 10240 KB.
`is_confidential`	boolean	no	
`title`	string	**yes**	maxLength 150

RESPONSES

201 — `data` : EmployeeDocument

`id` integer `company_id` integer `employee_id` integer `title` string `category` enum HRDocumentCategory | null `mime` string `size_bytes` integer `expires_at` string(date) | null `is_expired` boolean `is_confidential` boolean `uploaded_by` integer | null `uploader` object | null `download_url` string `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/employees`

List employees `hrEmployeesIndex`

Employees ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `first_name` , `last_name` , `email` , `employee_code` , `phone` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `employees.view` (viewAny on Employee)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum EmployeeStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `probation`, `active`, `on_leave`, `suspended`, `terminated`
`filter[department_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[designation_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[employment_type]`	query	enum EmploymentType	no	Exact-match filter (comma-separated = koi bhi value). · values: `full_time`, `part_time`, `contract`, `intern`
`filter[manager_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `hired_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `hired_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`last_name`). The primary key is always appended as a tie-breaker. · values: `first_name`, `last_name`, `employee_code`, `email`, `hired_at`, `status`, `created_at` (prefix `-` = descending) · default `last_name`

RESPONSES

200 — `data` : array of Employee + `meta.pagination`

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null …

aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/employees`

Create employee `hrEmployeesStore`

Naya employee banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `employees.create` (create on Employee)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`address_line1`	string | null	no	maxLength 200
`address_line2`	string | null	no	maxLength 200
`bank_account_number`	string | null	no	maxLength 60
`bank_iban`	string | null	no	maxLength 60
`bank_name`	string | null	no	maxLength 150
`base_salary`	string | number | null	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`city`	string | null	no	maxLength 100
`country`	string | null	no	minLength 2 · maxLength 2
`currency`	string | null	no	minLength 3 · maxLength 3
`date_of_birth`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `before:today`.
`department_id`	integer | null	no	Validated by `TenantExists`.
`designation_id`	integer | null	no	Validated by `TenantExists`.
`email`	string(email)	**yes**	maxLength 150 · Must be unique within `employees` (per company).
`emergency_contact_name`	string | null	no	maxLength 150
`emergency_contact_phone`	string | null	no	maxLength 40
`emergency_contact_relationship`	string | null	no	maxLength 60
`employment_type`	enum EmploymentType	**yes**	values: `full_time`, `part_time`, `contract`, `intern`
`first_name`	string	**yes**	maxLength 100
`gender`	enum Gender | null	no	
`hired_at`	string(date)	**yes**	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`last_name`	string	**yes**	maxLength 100
`manager_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`marital_status`	enum MaritalStatus | null	no	
`national_id`	string | null	no	maxLength 60
`notes`	string | null	no	maxLength 5000
`phone`	string | null	no	maxLength 40
`postal_code`	string | null	no	maxLength 20
`probation_ends_at`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:hired_at`.

Field	Type	Req.	Constraints / notes
`state`	string | null	no	maxLength 100
`status`	string	no	values: `probation`, `active`
`tax_identifier`	string | null	no	maxLength 60
`user_id`	integer | null	no	Must reference an existing `company_user` record in the current company. Must be unique within `employees` (per company).

EXAMPLE REQUEST

```
{
  "email": "ali.raza@example.com",
  "employment_type": "full_time",
  "first_name": "Ali",
  "hired_at": "2026-10-15",
  "last_name": "Raza",
  "address_line1": "Shahrah-e-Faisal, Karachi",
  "address_line2": "Shahrah-e-Faisal, Karachi",
  "bank_account_number": "string"
}
```

RESPONSES

201 — `data` : Employee

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null ... aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/employees/{employee}`

Get employee `hrEmployeesShow`

Ek employee ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `employees.view` / `employees.update` (view on Employee; viewSensitive on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee`	path	integer	**yes**	ID of the Employee. · min 1

RESPONSES

200 — `data` : Employee

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null ... aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/employees/{employee}

Update employee hrEmployeesUpdate

Maujooda employee ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `employees.update` (update on Employee; viewSensitive on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employee	path	integer	yes	ID of the Employee. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200
address_line2	string | null	no	maxLength 200
bank_account_number	string | null	no	maxLength 60
bank_iban	string | null	no	maxLength 60
bank_name	string | null	no	maxLength 150
base_salary	string | number | null	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
branch_id	integer | null	no	Validated by AccessibleBranch.
city	string | null	no	maxLength 100
country	string | null	no	minLength 2 · maxLength 2
currency	string | null	no	minLength 3 · maxLength 3
date_of_birth	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. before:today.
department_id	integer | null	no	Validated by TenantExists.
designation_id	integer | null	no	Validated by TenantExists.
email	string(email)	no	maxLength 150 · Must be unique within employees (per company).
emergency_contact_name	string | null	no	maxLength 150
emergency_contact_phone	string | null	no	maxLength 40
emergency_contact_relationship	string | null	no	maxLength 60
employment_type	enum EmploymentType	no	values: full_time, part_time, contract, intern
first_name	string	no	maxLength 100
gender	enum Gender | null	no	
hired_at	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
last_name	string	no	maxLength 100
manager_id	integer | null	no	Validated by TenantExists. Custom validation applies.
marital_status	enum MaritalStatus | null	no	
national_id	string | null	no	maxLength 60

Field	Type	Req.	Constraints / notes
notes	string | null	no	maxLength 5000
phone	string | null	no	maxLength 40
postal_code	string | null	no	maxLength 20
probation_ends_at	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:hired_at.
state	string | null	no	maxLength 100
status	string	no	values: probation, active, on_leave, suspended
tax_identifier	string | null	no	maxLength 60
user_id	integer | null	no	Must reference an existing company_user record in the current company. Must be unique within employees (per company).

RESPONSES

200 — `data` : Employee

`id` integer `company_id` integer `employee_code` string `user_id` integer | null `user` object | null `first_name` string `last_name` string `name` string `email` string `phone` string | null `date_of_birth` string(date) | null `gender` enum Gender | null `marital_status` enum MaritalStatus | null `address` object `emergency_contact` object `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `designation_id` integer | null `designation` object | null `manager_id` integer | null `manager` object | null `employment_type` enum EmploymentType | null `status` enum EmployeeStatus | null … aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`PATCH` /api/v1/**employees/{employee}**

Update employee `hrEmployeesUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /employees/{employee}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `employees.update`

`DELETE` /api/v1/**employees/{employee}**

Delete employee `hrEmployeesDestroy`

Employee delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `employees.delete` (delete on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employee	path	integer	**yes**	ID of the Employee. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/employee-documents/{employee_document}/download

Download – employee document `hrEmployeeDocumentsDownload`

Employee document ki file download karta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `employees.documents.view` (download on EmployeeDocument)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee_document`	path	string	**yes**	

RESPONSES

200 — File (`application/octet-stream`). File download (`Content-Disposition: attachment`). The actual `Content-Type` is the stored file's MIME type.

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

DELETE /api/v1/employee-documents/{employee_document}

Delete employee document `hrEmployeeDocumentsDestroy`

Employee document delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `employees.update` · Policy: `employees.update` (delete on EmployeeDocument)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employee_document`	path	string	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/employment-contracts/{employment_contract}/document

Document – employment contract `hrEmploymentContractsDocument`

Employment contract ke saath attached document ki file download karta hai.

GET /employment-contracts/{id}/document — employees.view + employees.documents.view; private disk, audited.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `employees.view` / `employees.documents.view` (downloadDocument on EmploymentContract)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employment_contract`	path	string	**yes**	

RESPONSES

200 — File (`application/octet-stream`). File download (`Content-Disposition: attachment`). The actual `Content-Type` is the stored file's MIME type.

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET `/api/v1/employment-contracts`

List employment contracts `hrEmploymentContractsIndex`

Employment contracts ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `employees.view` (viewAny on EmploymentContract)
Throttle	`api`
List params	`page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[employee_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[status]`	query	enum ContractStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `active`, `expired`, `terminated`
`filter[contract_type]`	query	enum EmploymentType	no	Exact-match filter (comma-separated = koi bhi value). · values: `full_time`, `part_time`, `contract`, `intern`
`from`	query	string(date)	no	Inclusive lower bound on `start_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `start_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-start_date`). The primary key is always appended as a tie-breaker. · values: `start_date`, `-start_date`, `end_date`, `-end_date`, `salary`, `-salary`, `status`, `-status`, `created_at`, `-created_at` · default `-start_date`

RESPONSES

200 — `data` : array of EmploymentContract + `meta.pagination`

`id` integer `company_id` integer `employee_id` integer `employee` object `contract_type` enum EmploymentType | null
`start_date` string(date) | null `end_date` string(date) | null `salary` Money (string) `currency` string
`working_hours_per_week` Decimal (string) `has_document` boolean `status` enum ContractStatus | null `notes` string | null
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

`POST` `/api/v1/employment-contracts`

Create employment contract `hrEmploymentContractsStore`

Naya employment contract banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `employees.update` (create on EmploymentContract)
Throttle	`api`

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`contract_type`	enum EmploymentType	**yes**	values: `full_time`, `part_time`, `contract`, `intern`
`currency`	string	**yes**	minLength 3 · maxLength 3
`document`	string(binary) | null	no	Allowed types: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt. Max size 10240 KB.
`employee_id`	integer	**yes**	Validated by `TenantExists`.
`end_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:start_date`.
`notes`	string | null	no	maxLength 5000
`salary`	string | number	**yes**	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`start_date`	string(date)	**yes**	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`status`	enum ContractStatus	no	values: `active`, `expired`, `terminated`
`working_hours_per_week`	string | number	no	min 0 · max 168 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.

RESPONSES

201 — `data`: EmploymentContract

`id` integer `company_id` integer `employee_id` integer `employee` object `contract_type` enum EmploymentType | null
`start_date` string(date) | null `end_date` string(date) | null `salary` Money (string) `currency` string
`working_hours_per_week` Decimal (string) `has_document` boolean `status` enum ContractStatus | null `notes` string | null
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/employment-contracts/{employment_contract}`

Get employment contract `hrEmploymentContractsShow`

Ek employment contract ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `employees.view` (view on EmploymentContract)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`employment_contract`	path	string	**yes**	

RESPONSES

200 — `data` : EmploymentContract

`id` integer `company_id` integer `employee_id` integer `employee` object `contract_type` enum EmploymentType | null
`start_date` string(date) | null `end_date` string(date) | null `salary` Money (string) `currency` string
`working_hours_per_week` Decimal (string) `has_document` boolean `status` enum ContractStatus | null `notes` string | null
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/employment-contracts/{employment_contract}

Update employment contract hrEmploymentContractsUpdate

Maujooda employment contract ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `employees.update` (update on EmploymentContract)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employment_contract	path	string	yes	

REQUEST BODY multipart/form-data (OPTIONAL)

Field	Type	Req.	Constraints / notes
contract_type	enum EmploymentType	no	values: full_time, part_time, contract, intern
currency	string	no	minLength 3 · maxLength 3
document	string(binary) | null	no	Allowed types: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt. Max size 10240 KB.
employee_id	integer	no	Prohibited. Validated by TenantExists.
end_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:start_date.
notes	string | null	no	maxLength 5000
salary	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
start_date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
status	enum ContractStatus	no	values: active, expired, terminated
working_hours_per_week	string | number	no	min 0 · max 168 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.

RESPONSES

200 — `data` : EmploymentContract

`id` integer `company_id` integer `employee_id` integer `employee` object `contract_type` enum EmploymentType | null
`start_date` string(date) | null `end_date` string(date) | null `salary` Money (string) `currency` string
`working_hours_per_week` Decimal (string) `has_document` boolean `status` enum ContractStatus | null `notes` string | null
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/employment-contracts/{employment_contract}

Update employment contract hrEmploymentContractsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /employment-contracts/{employment_contract} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission employees.update

DELETE /api/v1/employment-contracts/{employment_contract}

Delete employment contract hrEmploymentContractsDestroy

Employment contract delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: employees.update (delete on EmploymentContract)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employment_contract	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

GET /api/v1/shifts

List shifts hrShiftsIndex

Shifts ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name .

Auth Session cookie · X-Company-Id **required**

Permission Policy: shifts.manage / attendance.view / employees.view (viewAny on Shift)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_default]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, start_time, -start_time, created_at, -created_at · default name

RESPONSES

200 — data : array of Shift + meta.pagination

id integer company_id integer name string start_time string end_time string break_minutes integer days_of_week any[]
is_default boolean assignments_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/shifts

Create shift hrShiftsStore

Naya shift banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: shifts.manage (create on Shift)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
break_minutes	integer	no	min 0 · max 480
days_of_week	integer[]	**yes**	minItems 1 · maxItems 7
end_time	string(time)	**yes**	Format: H:i.
is_default	boolean	no	
name	string	**yes**	maxLength 100
start_time	string(time)	**yes**	Format: H:i.

EXAMPLE REQUEST

```
{
  "break_minutes": 1,
  "days_of_week": [1],
  "end_time": "17:00",
  "is_default": true,
  "name": "Sample name",
  "start_time": "09:00"
}
```

RESPONSES

201 — data : Shift

id integer company_id integer name string start_time string end_time string break_minutes integer days_of_week any[]
is_default boolean assignments_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/shifts/{shift}

Get shift hrShiftsShow

Ek shift ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: shifts.manage / attendance.view / employees.view (view on Shift)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
shift	path	integer	**yes**	ID of the Shift. · min 1

RESPONSES

200 — data : Shift

id integer company_id integer name string start_time string end_time string break_minutes integer days_of_week any[]
is_default boolean assignments_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

PUT /api/v1/shifts/{shift}

Update shift hrShiftsUpdate

Maujooda shift ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `shifts.manage` (update on Shift)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`shift`	path	integer	**yes**	ID of the Shift. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`break_minutes`	integer	no	min 0 · max 480
`days_of_week`	integer[]	no	minItems 1 · maxItems 7
`end_time`	string(time)	no	Format: `H:i`.
`is_default`	boolean	no	
`name`	string	no	maxLength 100
`start_time`	string(time)	no	Format: `H:i`.

RESPONSES

200 — `data`: Shift

`id` integer `company_id` integer `name` string `start_time` string `end_time` string `break_minutes` integer `days_of_week` any[]
`is_default` boolean `assignments_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/shifts/{shift}

Update shift hrShiftsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /shifts/{shift}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `shifts.manage`

DELETE /api/v1/shifts/{shift}

Delete shift hrShiftsDestroy

Shift delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `shifts.manage` (delete on Shift)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`shift`	path	integer	**yes**	ID of the Shift. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/holidays

List holidays `hrHolidaysIndex`

Holidays ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `shifts.manage` / `attendance.view` / `employees.view` / `leave.request` / `leave.view` (viewAny on Holiday)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[is_recurring]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`from`	query	string(date)	no	Inclusive lower bound on `date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`date`). The primary key is always appended as a tie-breaker. · values: `date`, `-date`, `name`, `-name`, `created_at`, `-created_at` · default `date`

RESPONSES

200 — `data` : array of Holiday + `meta.pagination`

`id` integer `company_id` integer `branch_id` integer | null `branch` object | null `name` string `date` string(date) | null `is_recurring` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/holidays

Create holiday hrHolidaysStore

Naya holiday banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: shifts.manage (create on Holiday)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
branch_id	integer | null	no	Validated by AccessibleBranch.
date	string(date)	yes	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
is_recurring	boolean	no	
name	string	yes	maxLength 150

EXAMPLE REQUEST

```
{"branch_id":1,"date":"2026-10-15","is_recurring":true,"name":"Sample name"}
```

RESPONSES

201 — data : Holiday

id integer company_id integer branch_id integer | null branch object | null name string date string(date) | null is_recurring boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/holidays/{holiday}

Get holiday hrHolidaysShow

Ek holiday ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: shifts.manage / attendance.view / employees.view / leave.request / leave.view (view on Holiday)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
holiday	path	integer	yes	ID of the Holiday. · min 1

RESPONSES

200 — data : Holiday

id integer company_id integer branch_id integer | null branch object | null name string date string(date) | null is_recurring boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

PUT /api/v1/holidays/{holiday}

Update holiday hrHolidaysUpdate

Maujooda holiday ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `shifts.manage` (update on Holiday)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
holiday	path	integer	yes	ID of the Holiday. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
branch_id	integer | null	no	Validated by AccessibleBranch.
date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
is_recurring	boolean	no	
name	string	no	maxLength 150

RESPONSES

200 — `data` : Holiday

`id` integer `company_id` integer `branch_id` integer | null `branch` object | null `name` string `date` string(date) | null `is_recurring` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/holidays/{holiday}

Update holiday hrHolidaysUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /holidays/{holiday}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `shifts.manage`

DELETE /api/v1/holidays/{holiday}

Delete holiday hrHolidaysDestroy

Holiday delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `shifts.manage` (delete on Holiday)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
holiday	path	integer	yes	ID of the Holiday. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

POST /api/v1/attendance/bulk

Bulk – attendance hrAttendanceBulk

Ek saath kai attendance records darj karta hai (bulk).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `attendance.manage` · Policy: `attendance.manage` (create on AttendanceRecord)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`date`	string(date)	yes	
`records`	object[]	yes	minItems 1 · maxItems 500
`records[].check_in`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`records[].check_out`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`records[].employee_id`	integer	no	Values must be distinct. Validated by `TenantExists`.
`records[].notes`	string | null	no	maxLength 500
`records[].status`	enum AttendanceStatus	no	values: `present`, `absent`, `late`, `half_day`, `on_leave`, `holiday`, `weekend`
`source`	string	no	values: `manual`, `import`, `biometric`

RESPONSES

200 — `data` : object shape inferred from code

`written` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/attendance/check-in

Check in – attendance hrAttendanceCheckIn

Logged-in user ka attendance check-in record karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

RESPONSES

201 — `data` : AttendanceRecord

`id` integer `company_id` integer `employee_id` integer `employee` object `date` string(date) | null `check_in` string(date-time) | null `check_out` string(date-time) | null `status` enum AttendanceStatus | null `worked_minutes` integer `late_minutes` integer `source` enum AttendanceSource | null `notes` string | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/attendance/check-out

Check out – attendance `hrAttendanceCheckOut`

Logged-in user ka attendance check-out record karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

RESPONSES

200 — `data` : AttendanceRecord

`id` integer `company_id` integer `employee_id` integer `employee` object `date` string(date) | null `check_in` string(date-time) | null `check_out` string(date-time) | null `status` enum AttendanceStatus | null `worked_minutes` integer `late_minutes` integer `source` enum AttendanceSource | null `notes` string | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/attendance/today

Today – attendance `hrAttendanceToday`

Aaj ki attendance ka data deta hai.

GET /attendance/today — the caller's own attendance record for today (company timezone) or null, plus the shift that applies today. Any member may call it; members without an employee record get 404.

Auth Session cookie · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api`

RESPONSES

200 — `data` : object shape inferred from code

`date` string(date) `timezone` string `employee_id` integer `record` AttendanceRecord | null `shift` object | null `can_check_in` boolean `can_check_out` boolean

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/attendance/summary

Per-employee totals for a period: `?from&to&department_id` . `hrAttendanceSummary`

Ek period ke liye har employee ke attendance totals deta hai (`from` , `to` , `department_id`).

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `attendance.view` · Policy: `attendance.view` (viewAny on AttendanceRecord)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`department_id`	query	integer | null	no	
`from`	query	string(date)	**yes**	
`to`	query	string(date)	**yes**	`after_or_equal:from.`

RESPONSES

200 — `data` : array of object + `meta` { `from` , `to` } shape inferred from code

`employee_id` integer `employee_code` string `name` string `department_id` integer | null `present_days` integer `late_days` integer `absent_days` integer `half_days` integer `leave_days` integer `worked_minutes` integer `worked_hours` number `late_minutes` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/attendance

List attendance hrAttendanceIndex

Attendance ki list deta hai — results paginated hote hain (page , per_page).

Auth Session cookie · X-Company-Id required

Permission Policy: attendance.view (viewAny on AttendanceRecord)

Throttle api

List params page , per_page (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[employee_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[status]	query	enum AttendanceStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: present, absent, late, half_day, on_leave, holiday, weekend
filter[source]	query	enum AttendanceSource	no	Exact-match filter (comma-separated = koi bhi value). · values: manual, import, biometric, self
from	query	string(date)	no	Inclusive lower bound on date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-date). The primary key is always appended as a tie-breaker. · values: date, -date, status, -status, worked_minutes, -worked_minutes, late_minutes, -late_minutes, created_at, -created_at · default -date
department_id	query	integer	no	

RESPONSES

200 — data : array of AttendanceRecord + meta.pagination

id integer company_id integer employee_id integer employee object date string(date) | null check_in string(date-time) | null check_out string(date-time) | null status enum AttendanceStatus | null worked_minutes integer late_minutes integer source enum AttendanceSource | null notes string | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/attendance

Create attendance hrAttendanceStore

Naya attendance banata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `attendance.manage` (create on AttendanceRecord)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
check_in	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
check_out	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after:check_in.
date	string(date)	yes	
employee_id	integer	yes	Validated by TenantExists.
notes	string | null	no	maxLength 500
source	string	no	values: manual, import, biometric
status	enum AttendanceStatus	yes	values: present, absent, late, half_day, on_leave, holiday, weekend

EXAMPLE REQUEST

```
{
  "check_in": "2026-10-15",
  "check_out": "2026-10-15",
  "date": "2026-10-15",
  "employee_id": 1,
  "notes": "Sample text",
  "source": "manual",
  "status": "present"
}
```

RESPONSES

200 — `data` : AttendanceRecord

`id` integer `company_id` integer `employee_id` integer `employee` object `date` string(date) | null `check_in` string(date-time) | null `check_out` string(date-time) | null `status` enum AttendanceStatus | null `worked_minutes` integer `late_minutes` integer `source` enum AttendanceSource | null `notes` string | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/attendance/{attendance}

Get attendance hrAttendanceShow

Ek attendance ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `attendance.view` (view on AttendanceRecord)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
attendance	path	integer	yes	ID of the Attendance Record. · min 1

RESPONSES

200 — `data` : AttendanceRecord

`id` integer `company_id` integer `employee_id` integer `employee` object `date` string(date) | null `check_in` string(date-time) | null `check_out` string(date-time) | null `status` enum AttendanceStatus | null `worked_minutes` integer `late_minutes` integer `source` enum AttendanceSource | null `notes` string | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/attendance/{attendance}

Update attendance hrAttendanceUpdate

Maujooda attendance ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `attendance.manage` (update on AttendanceRecord)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
attendance	path	integer	yes	ID of the Attendance Record. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
check_in	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
check_out	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after:check_in.
date	string(date)	no	Prohibited.
employee_id	integer	no	Prohibited. Validated by TenantExists.
notes	string | null	no	maxLength 500
source	string	no	values: manual, import, biometric
status	enum AttendanceStatus	no	values: present, absent, late, half_day, on_leave, holiday, weekend

RESPONSES

200 — `data` : AttendanceRecord

`id` integer `company_id` integer `employee_id` integer `employee` object `date` string(date) | null `check_in` string(date-time) | null `check_out` string(date-time) | null `status` enum AttendanceStatus | null `worked_minutes` integer `late_minutes` integer `source` enum AttendanceSource | null `notes` string | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/attendance/{attendance}

Update attendance hrAttendanceUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /attendance/{attendance} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission attendance.manage

DELETE /api/v1/attendance/{attendance}

Delete attendance hrAttendanceDestroy

Attendance delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: attendance.manage (delete on AttendanceRecord)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
attendance	path	integer	**yes**	ID of the Attendance Record. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

GET /api/v1/leave-types

List leave types hrLeaveTypesIndex

Leave types ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , code .

Auth Session cookie · X-Company-Id **required**

Permission Policy: leave.view / leave.request / leave.approve / leave.manage (viewAny on LeaveType)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[is_paid]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, days_per_year, -days_per_year, created_at, -created_at · default name

RESPONSES

200 — data : array of LeaveType + meta.pagination

id integer company_id integer name string code string days_per_year Decimal (string) is_paid boolean requires_approval boolean carry_forward boolean max_carry_forward_days Decimal (string) | null color string | null is_active boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

`POST` `/api/v1/leave-types`

Create leave type `hrLeaveTypesStore`

Naya leave type banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `leave.manage` (create on LeaveType)
Throttle	`api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`carry_forward`	boolean	no	
`code`	string	**yes**	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `leave_types` (per company).
`color`	string | null	no	maxLength 9 · pattern `^#[0-9a-fA-F]{6}([0-9a-fA-F]{2})?$`
`days_per_year`	string | number	**yes**	min 0 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`is_active`	boolean	no	
`is_paid`	boolean	no	
`max_carry_forward_days`	string | number | null	no	min 0 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`name`	string	**yes**	maxLength 100
`requires_approval`	boolean	no	

EXAMPLE REQUEST

```
{
  "carry_forward": false,
  "code": "CODE-001",
  "color": "#4f46e5",
  "days_per_year": "1250.0000",
  "is_active": true,
  "is_paid": true,
  "max_carry_forward_days": "1250.0000",
  "name": "Sample name",
  "requires_approval": false
}
```

RESPONSES

201 — `data` : LeaveType

`id` integer · `company_id` integer · `name` string · `code` string · `days_per_year` Decimal (string) · `is_paid` boolean · `requires_approval` boolean · `carry_forward` boolean · `max_carry_forward_days` Decimal (string) | null · `color` string | null · `is_active` boolean · `created_at` string(date-time) | null · `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/leave-types/{leave_type}

Get leave type `hrLeaveTypesShow`

Ek leave type ki poori tafseel deta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `leave.view` / `leave.request` / `leave.approve` / `leave.manage` (view on LeaveType)
Throttle	`api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`leave_type`	path	string	**yes**	

RESPONSES

200 — `data`: LeaveType

`id` integer `company_id` integer `name` string `code` string `days_per_year` Decimal (string) `is_paid` boolean `requires_approval` boolean `carry_forward` boolean `max_carry_forward_days` Decimal (string) | null `color` string | null `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/leave-types/{leave_type}

Update leave type hrLeaveTypesUpdate

Maujooda leave type ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leave.manage` (update on LeaveType)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_type	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
carry_forward	boolean	no	
code	string	no	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within leave_types (per company).
color	string | null	no	maxLength 9 · pattern ^#[0-9a-fA-F]{6}([0-9a-fA-F]{2})?$
days_per_year	string | number	no	min 0 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
is_active	boolean	no	
is_paid	boolean	no	
max_carry_forward_days	string | number | null	no	min 0 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	no	maxLength 100
requires_approval	boolean	no	

RESPONSES

200 — `data`: LeaveType

`id` integer `company_id` integer `name` string `code` string `days_per_year` Decimal (string) `is_paid` boolean `requires_approval` boolean `carry_forward` boolean `max_carry_forward_days` Decimal (string) | null `color` string | null `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/leave-types/{leave_type}

Update leave type hrLeaveTypesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /leave-types/{leave_type} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission leave.manage

DELETE /api/v1/leave-types/{leave_type}

Delete leave type hrLeaveTypesDestroy

Leave type delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: leave.manage (delete on LeaveType)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_type	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/leave-balances/mine

The acting user's own balances (defaults to the current year). hrLeaveBalancesMine

Logged-in user ke apne leave balances deta hai (default: current year).

Auth Session cookie · X-Company-Id **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
year	query	integer	no	

RESPONSES

200 — data : array of LeaveBalance

id integer company_id integer employee_id integer employee object leave_type_id integer leave_type object year integer entitled Decimal (string) used Decimal (string) carried_forward Decimal (string) adjusted Decimal (string) remaining string updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

POST /api/v1/leave-balances/generate

Generate – leave balance `hrLeaveBalancesGenerate`

Leave balances generate karta hai (optional `year` ke liye).

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Route: `leave.manage` · Policy: `leave.manage` (generate on LeaveBalance)

Throttle: `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
year	integer	yes	min 2000 · max 2100

RESPONSES

200 — `data` : object shape inferred from code

`year` integer `created` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/leave-balances

List leave balances `hrLeaveBalancesIndex`

Leave balances ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth: Session cookie · `X-Company-Id` **required**

Permission: Policy: `leave.view` / `leave.manage` / `leave.approve` (viewAny on LeaveBalance)

Throttle: `api`

List params: `page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[employee_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[leave_type_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[year]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-year). The primary key is always appended as a tie-breaker. · values: year, -year, entitled, -entitled, used, -used, updated_at, -updated_at · default -year

RESPONSES

200 — `data` : array of LeaveBalance + `meta.pagination`

`id` integer `company_id` integer `employee_id` integer `employee` object `leave_type_id` integer `leave_type` object `year` integer `entitled` Decimal (string) `used` Decimal (string) `carried_forward` Decimal (string) `adjusted` Decimal (string) `remaining` string `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

PUT /api/v1/leave-balances/{leave_balance}

Manual correction: { adjusted, entitled?, carried_forward? }. hrLeaveBalancesAdjust

Leave balance ki manual correction karta hai (adjusted , optional entitled , carried_forward).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: leave.manage · Policy: leave.manage (adjust on LeaveBalance)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_balance	path	string	yes	

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
adjusted	string | number	yes	min -999.9 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
carried_forward	string | number	no	min 0 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
entitled	string | number	no	min 0 · max 999.9 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
note	string | null	no	maxLength 500

RESPONSES

200 — data : LeaveBalance

id integer company_id integer employee_id integer employee object leave_type_id integer leave_type object year integer entitled Decimal (string) used Decimal (string) carried_forward Decimal (string) adjusted Decimal (string) remaining string updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

POST /api/v1/leave-requests/{leave_request}/approve

Approve – leave request hrLeaveRequestsApprove

Leave request ko approve karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: leave.approve · Policy: leave.approve (approve on LeaveRequest)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_request	path	string	yes	

RESPONSES

200 — data : LeaveRequest

id integer company_id integer employee_id integer employee object leave_type_id integer leave_type object start_date string(date) | null end_date string(date) | null days Decimal (string) reason string | null status enum LeaveRequestStatus | null approver_id integer | null approver object | null approved_at string(date-time) | null rejection_reason string | null has_attachment boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

POST /api/v1/leave-requests/{leave_request}/reject

Reject – leave request hrLeaveRequestsReject

Leave request ko reject karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `leave.approve` · Policy: `leave.approve` (reject on LeaveRequest)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_request	path	string	yes	

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
reason	string	yes	maxLength 500

RESPONSES

200 — `data` : LeaveRequest

`id` integer `company_id` integer `employee_id` integer `employee` object `leave_type_id` integer `leave_type` object
`start_date` string(date) | null `end_date` string(date) | null `days` Decimal (string) `reason` string | null
`status` enum LeaveRequestStatus | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null
`rejection_reason` string | null `has_attachment` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/leave-requests/{leave_request}/cancel

Cancel – leave request hrLeaveRequestsCancel

Leave request ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leave.manage` (cancel on LeaveRequest)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_request	path	string	yes	

RESPONSES

200 — `data` : LeaveRequest

`id` integer `company_id` integer `employee_id` integer `employee` object `leave_type_id` integer `leave_type` object
`start_date` string(date) | null `end_date` string(date) | null `days` Decimal (string) `reason` string | null
`status` enum LeaveRequestStatus | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null
`rejection_reason` string | null `has_attachment` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/leave-requests/{leave_request}/attachment

Attachment – leave request `hrLeaveRequestsAttachment`

Leave request ke saath attached file download karta hai.

GET /leave-requests/{id}/attachment — owner or leave viewers/approvers; streamed from the private disk and audited.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leave.view` / `leave.approve` / `leave.manage` (downloadAttachment on LeaveRequest)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`leave_request`	path	string	**yes**	

RESPONSES

200 — File (`application/octet-stream`). File download (`Content-Disposition: attachment`). The actual `Content-Type` is the stored file's MIME type.

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET `/api/v1/leave-requests`

Holders of leave.view/approve/manage see everything; others only their own requests. `hrLeaveRequestsIndex`

Leave requests ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `leave.view` / `leave.request` / `leave.approve` / `leave.manage` (viewAny on LeaveRequest; viewAll on LeaveRequest)
Throttle	`api`
List params	`page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum LeaveRequestStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `pending`, `approved`, `rejected`, `cancelled`
`filter[leave_type_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[employee_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `start_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `start_date` (UTC day end).
`department_id`	query	integer	no	
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-created_at`). The primary key is always appended as a tie-breaker. · values: `start_date`, `-start_date`, `end_date`, `-end_date`, `days`, `-days`, `status`, `-status`, `created_at`, `-created_at` · default `-created_at`

RESPONSES

200 — `data` : array of LeaveRequest + `meta.pagination`

`id` integer `company_id` integer `employee_id` integer `employee` object `leave_type_id` integer `leave_type` object `start_date` string(date) | null `end_date` string(date) | null `days` Decimal (string) `reason` string | null `status` enum LeaveRequestStatus | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `has_attachment` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/leave-requests

Create leave request hrLeaveRequestsStore

Naya leave request banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: leave.request (create on LeaveRequest)

Throttle api

REQUEST BODY multipart/form-data

Field	Type	Req.	Constraints / notes
attachment	string(binary) | null	no	Allowed types: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt. Max size 10240 KB.
end_date	string(date)	yes	after_or_equal:start_date.
leave_type_id	integer	yes	Validated by TenantExists.
reason	string | null	no	maxLength 1000
start_date	string(date)	yes	

RESPONSES

201 — data : LeaveRequest

id integer company_id integer employee_id integer employee object leave_type_id integer leave_type object start_date string(date) | null end_date string(date) | null days Decimal (string) reason string | null status enum LeaveRequestStatus | null approver_id integer | null approver object | null approved_at string(date-time) | null rejection_reason string | null has_attachment boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/leave-requests/{leave_request}

Get leave request hrLeaveRequestsShow

Ek leave request ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: leave.view / leave.approve / leave.manage (view on LeaveRequest)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
leave_request	path	string	yes	

RESPONSES

200 — data : LeaveRequest

id integer company_id integer employee_id integer employee object leave_type_id integer leave_type object start_date string(date) | null end_date string(date) | null days Decimal (string) reason string | null status enum LeaveRequestStatus | null approver_id integer | null approver object | null approved_at string(date-time) | null rejection_reason string | null has_attachment boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/performance-reviews/{performance_review}/submit

Submit – performance review `hrPerformanceReviewsSubmit`

Performance review ko approval ke liye submit karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `performance.manage` (submit on PerformanceReview)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
performance_review	path	string	yes	

RESPONSES

200 — `data` : PerformanceReview

`id` integer `company_id` integer `employee_id` integer `employee` object `reviewer_id` integer | null `reviewer` object | null `cycle` string `period_start` string(date) | null `period_end` string(date) | null `status` enum ReviewStatus | null `overall_rating` Decimal (string) | null `ratings` any[] `strengths` string | null `improvements` string | null `goals` string | null `submitted_at` string(date-time) | null `acknowledged_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/performance-reviews/{performance_review}/acknowledge

The reviewed employee confirms they have read the review. `hrPerformanceReviewsAcknowledge`

Jis employee ka review hua, woh confirm karta hai ke usne review parh liya.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership) (acknowledge on PerformanceReview)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
performance_review	path	string	yes	

RESPONSES

200 — `data` : PerformanceReview

`id` integer `company_id` integer `employee_id` integer `employee` object `reviewer_id` integer | null `reviewer` object | null `cycle` string `period_start` string(date) | null `period_end` string(date) | null `status` enum ReviewStatus | null `overall_rating` Decimal (string) | null `ratings` any[] `strengths` string | null `improvements` string | null `goals` string | null `submitted_at` string(date-time) | null `acknowledged_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/performance-reviews

List performance reviews `hrPerformanceReviewsIndex`

Performance reviews ki list deta hai — results paginated hote hain (`page` , `per_page`).

> Without performance.view the list is limited to reviews the user is subject of or reviewer for.
> `search` matches (case-insensitive, substring): `cycle` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `performance.view` / `performance.manage` (viewAny on PerformanceReview; viewAll on PerformanceReview)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum ReviewStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `submitted`, `acknowledged`
`filter[employee_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[reviewer_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[cycle]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `period_end` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `period_end` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-period_end`). The primary key is always appended as a tie-breaker. · values: `cycle`, `-cycle`, `period_end`, `-period_end`, `status`, `-status`, `overall_rating`, `-overall_rating`, `created_at`, `-created_at` · default `-period_end`

RESPONSES

200 — `data` : array of PerformanceReview + `meta.pagination`

`id` integer `company_id` integer `employee_id` integer `employee` object `reviewer_id` integer | null `reviewer` object | null `cycle` string `period_start` string(date) | null `period_end` string(date) | null `status` enum ReviewStatus | null `overall_rating` Decimal (string) | null `ratings` any[] `strengths` string | null `improvements` string | null `goals` string | null `submitted_at` string(date-time) | null `acknowledged_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/performance-reviews

Create performance review `hrPerformanceReviewsStore`

Naya performance review banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `performance.manage` (create on PerformanceReview)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`cycle`	string	yes	maxLength 20
`employee_id`	integer	yes	Validated by `TenantExists`.
`goals`	string | null	no	maxLength 5000
`improvements`	string | null	no	maxLength 5000
`overall_rating`	string | number | null	no	min 0 · max 10 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`period_end`	string(date)	yes	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:period_start`.
`period_start`	string(date)	yes	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`ratings`	object[] | null	no	maxItems 50
`ratings[].comment`	string | null	no	maxLength 1000
`ratings[].criterion`	string	no	maxLength 150
`ratings[].rating`	string | number	no	min 0 · max 10 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`reviewer_id`	integer	yes	Must reference an existing `company_user` record in the current company.
`strengths`	string | null	no	maxLength 5000

EXAMPLE REQUEST

```
{
  "cycle": "string",
  "employee_id": 1,
  "goals": "string",
  "improvements": "string",
  "overall_rating": "1250.0000",
  "period_end": "2026-11-14",
  "period_start": "2026-10-15",
  "ratings": [{"comment":"Sample text","criterion":"string","rating":"1250.0000"}],
  "reviewer_id": 1,
  "strengths": "string"
}
```

RESPONSES

201 — `data` : PerformanceReview

`id` integer `company_id` integer `employee_id` integer `employee` object `reviewer_id` integer | null `reviewer` object | null `cycle` string `period_start` string(date) | null `period_end` string(date) | null `status` enum ReviewStatus | null `overall_rating` Decimal (string) | null `ratings` any[] `strengths` string | null `improvements` string | null `goals` string | null `submitted_at` string(date-time) | null `acknowledged_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/performance-reviews/{performance_review}

Get performance review hrPerformanceReviewsShow

Ek performance review ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `performance.view` / `performance.manage` (view on PerformanceReview)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
performance_review	path	string	yes	

RESPONSES

200 — `data` : PerformanceReview

`id` integer `company_id` integer `employee_id` integer `employee` object `reviewer_id` integer | null `reviewer` object | null `cycle` string `period_start` string(date) | null `period_end` string(date) | null `status` enum ReviewStatus | null `overall_rating` Decimal (string) | null `ratings` any[] `strengths` string | null `improvements` string | null `goals` string | null `submitted_at` string(date-time) | null `acknowledged_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/performance-reviews/{performance_review}

Update performance review hrPerformanceReviewsUpdate

Maujooda performance review ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `performance.manage` (update on PerformanceReview)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
performance_review	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
cycle	string	no	maxLength 20
employee_id	integer	no	Prohibited. Validated by TenantExists.
goals	string | null	no	maxLength 5000
improvements	string | null	no	maxLength 5000
overall_rating	string | number | null	no	min 0 · max 10 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
period_end	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:period_start.
period_start	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
ratings	object[] | null	no	maxItems 50
ratings[].comment	string | null	no	maxLength 1000
ratings[].criterion	string	no	maxLength 150
ratings[].rating	string | number	no	min 0 · max 10 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
reviewer_id	integer	no	Must reference an existing company_user record in the current company.
strengths	string | null	no	maxLength 5000

RESPONSES

200 — `data` : PerformanceReview

`id` integer `company_id` integer `employee_id` integer `employee` object `reviewer_id` integer | null `reviewer` object | null `cycle` string `period_start` string(date) | null `period_end` string(date) | null `status` enum ReviewStatus | null `overall_rating` Decimal (string) | null `ratings` any[] `strengths` string | null `improvements` string | null `goals` string | null `submitted_at` string(date-time) | null `acknowledged_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/performance-reviews/{performance_review}

Update performance review hrPerformanceReviewsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /performance-reviews/{performance_review} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission performance.manage

DELETE /api/v1/performance-reviews/{performance_review}

Delete performance review hrPerformanceReviewsDestroy

Performance review delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: performance.manage (delete on PerformanceReview)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
performance_review	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/hr/reports/headcount

Headcount – report hrReportsHeadcount

Headcount report ka data JSON mein deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Route: employees.view · Policy: employees.view (viewAny on Employee)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
from	query	string(date) | null	no	required_with:to.
to	query	string(date) | null	no	required_with:from. after_or_equal:from.

RESPONSES

200 — data : object shape inferred from code

total integer by_department object[] by_branch object[] by_employment_type object[] by_status object[] joiners null | null leavers null | null from string(date) to string(date)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

GET /api/v1/hr/reports/attendance

Attendance – report `hrReportsAttendance`

Attendance report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `employees.view` · Policy: `employees.view` (viewAny on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`from`	query	string(date) | null	no	`required_with:to.`
`to`	query	string(date) | null	no	`required_with:from. after_or_equal:from.`

RESPONSES

200 — `data` : object shape inferred from code

`from` string(date) `to` string(date) `totals` object `by_department` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/hr/reports/leave

Leave – report `hrReportsLeave`

Leave report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `employees.view` · Policy: `employees.view` (viewAny on Employee)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`from`	query	string(date) | null	no	`required_with:to.`
`to`	query	string(date) | null	no	`required_with:from. after_or_equal:from.`

RESPONSES

200 — `data` : object shape inferred from code

`from` string(date) `to` string(date) `approved_by_type` object[] `by_status` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Payroll

Pay components, tax tables, salary structures, employee salaries, payroll runs aur payslips. Payroll run ka status `draft → calculated → approved → finalized → paid` (ya `cancelled`) chalta hai, aur har qadam ke liye alag action endpoint hai. Employees apni payslips `/my-payslips` se dekhte hain.

Spec: Pay components, salary structures, tax tables, payroll runs and payslips. — 38 operations.

Method	Path	Summary	Permission
GET	/pay-components	List pay components	payroll.view payroll.manage
POST	/pay-components	Create pay component	payroll.manage
GET	/pay-components/{pay_component}	Get pay component	payroll.view payroll.manage
PUT	/pay-components/{pay_component}	Update pay component	payroll.manage
PATCH	/pay-components/{pay_component}	Update pay component	payroll.manage
DELETE	/pay-components/{pay_component}	Delete pay component	payroll.manage
GET	/tax-tables	List tax tables	payroll.view payroll.manage
POST	/tax-tables	Create tax table	payroll.manage
GET	/tax-tables/{tax_table}	Get tax table	payroll.view payroll.manage
PUT	/tax-tables/{tax_table}	Update tax table	payroll.manage
PATCH	/tax-tables/{tax_table}	Update tax table	payroll.manage
DELETE	/tax-tables/{tax_table}	Delete tax table	payroll.manage
GET	/salary-structures	List salary structures	payroll.view payroll.manage
POST	/salary-structures	Create salary structure	payroll.manage
GET	/salary-structures/{salary_structure}	Get salary structure	payroll.view payroll.manage
PUT	/salary-structures/{salary_structure}	Update salary structure	payroll.manage
PATCH	/salary-structures/{salary_structure}	Update salary structure	payroll.manage
DELETE	/salary-structures/{salary_structure}	Delete salary structure	payroll.manage
GET	/employees/{employee}/salaries	List salaries	payroll.view payroll.manage
POST	/employees/{employee}/salaries	Create salary	payroll.manage
GET	/payroll-runs	List payroll runs	payroll.view
POST	/payroll-runs	Create payroll run	payroll.process
GET	/payroll-runs/{payroll_run}	Get payroll run	payroll.view
DELETE	/payroll-runs/{payroll_run}	Only Draft runs may be deleted; later states are cancelled instead.	payroll.process
POST	/payroll-runs/{payroll_run}/calculate	Calculate – payroll run	payroll.process
POST	/payroll-runs/{payroll_run}/approve	Approve – payroll run	payroll.process

Method	Path	Summary	Permission
POST	/payroll-runs/{payroll_run}/finalize	Finalize – payroll run	payroll.process
POST	/payroll-runs/{payroll_run}/pay	Pay – payroll run	payroll.process
POST	/payroll-runs/{payroll_run}/cancel	Cancel – payroll run	payroll.process
GET	/payroll-runs/{payroll_run}/payslips	Payslips – payroll run	payroll.view
GET	/payroll-runs/{payroll_run}/export	Export – payroll run	payroll.view
GET	/payroll/reports/summary	Summary – report	payroll.view
GET	/payroll/reports/components	Components – report	payroll.view
GET	/payslips/{payslip}	Get payslip	payroll.view payslips.view.own
GET	/payslips/{payslip}/pdf	Pdf – payslip	payroll.view payslips.view.own
GET	/my-payslips	List my payslips	payslips.view.own
GET	/my-payslips/{payslip}	Get my payslip	payslips.view.own
GET	/my-payslips/{payslip}/pdf	Pdf – my payslip	payslips.view.own

Endpoints

GET `/api/v1/pay-components`

List pay components `payrollPayComponentsIndex`

Pay components ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `code` , `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payroll.manage` (viewAny on PayComponent)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[kind]`	query	enum PayComponentKind	no	Exact-match filter (comma-separated = koi bhi value). · values: `earning`, `deduction`, `employer_contribution`
`filter[calculation]`	query	enum CalculationMethod	no	Exact-match filter (comma-separated = koi bhi value). · values: `fixed`, `percent_of_base`, `percent_of_gross`
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[is_taxable]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`sort_order`). The primary key is always appended as a tie-breaker. · values: `code`, `-code`, `name`, `-name`, `kind`, `-kind`, `sort_order`, `-sort_order`, `created_at`, `-created_at` · default `sort_order`

RESPONSES

200 — `data` : array of PayComponent + `meta.pagination`

`id` integer `code` string `name` string `description` string | null `kind` enum PayComponentKind `calculation` enum CalculationMethod `default_amount` Money (string) `default_rate` Decimal (string) `is_taxable` boolean `reduces_taxable` boolean `affects_gross` boolean `gl_account_code` string | null `effective_gl_account_code` string `sort_order` integer `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/pay-components`

Create pay component `payrollPayComponentsStore`

Naya pay component banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `payroll.manage` (create on PayComponent)
Throttle	`api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`affects_gross`	boolean	no	
`calculation`	enum CalculationMethod	**yes**	values: `fixed`, `percent_of_base`, `percent_of_gross`
`code`	string	**yes**	maxLength 30 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `pay_components` (per company).
`default_amount`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`default_rate`	string | number	no	min 0 · max 1000 · pattern `^\d{1,4}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`description`	string | null	no	maxLength 500
`gl_account_code`	string | null	no	maxLength 20 · Validated by `TenantExists`.
`is_active`	boolean	no	
`is_taxable`	boolean	no	
`kind`	enum PayComponentKind	**yes**	values: `earning`, `deduction`, `employer_contribution`
`name`	string	**yes**	maxLength 100
`reduces_taxable`	boolean	no	
`sort_order`	integer	no	min 0 · max 65535

EXAMPLE REQUEST

```
{
  "calculation": "fixed",
  "code": "CODE-001",
  "kind": "earning",
  "name": "Sample name",
  "affects_gross": false,
  "default_amount": "1250.0000",
  "default_rate": "17.0000",
  "description": "Sample text"
}
```

RESPONSES

201 — `data` : PayComponent

`id` integer `code` string `name` string `description` string | null `kind` enum PayComponentKind
`calculation` enum CalculationMethod `default_amount` Money (string) `default_rate` Decimal (string) `is_taxable` boolean
`reduces_taxable` boolean `affects_gross` boolean `gl_account_code` string | null `effective_gl_account_code` string
`sort_order` integer `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/pay-components/{pay_component}`

Get pay component `payrollPayComponentsShow`

Ek pay component ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payroll.manage` (view on PayComponent)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
pay_component	path	string	yes	

RESPONSES

200 — `data` : PayComponent

`id` integer `code` string `name` string `description` string | null `kind` enum PayComponentKind
`calculation` enum CalculationMethod `default_amount` Money (string) `default_rate` Decimal (string) `is_taxable` boolean
`reduces_taxable` boolean `affects_gross` boolean `gl_account_code` string | null `effective_gl_account_code` string
`sort_order` integer `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/pay-components/{pay_component}

Update pay component payrollPayComponentsUpdate

Maujooda pay component ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `payroll.manage` (update on PayComponent)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
pay_component	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
affects_gross	boolean	no	
calculation	enum CalculationMethod	no	values: fixed, percent_of_base, percent_of_gross
code	string	no	maxLength 30 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within pay_components (per company).
default_amount	string | number	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
default_rate	string | number	no	min 0 · max 1000 · pattern ^\d{1,4}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
description	string | null	no	maxLength 500
gl_account_code	string | null	no	maxLength 20 · Validated by TenantExists.
is_active	boolean	no	
is_taxable	boolean	no	
kind	enum PayComponentKind	no	values: earning, deduction, employer_contribution
name	string	no	maxLength 100
reduces_taxable	boolean	no	
sort_order	integer	no	min 0 · max 65535

RESPONSES

200 — `data` : PayComponent

`id` integer `code` string `name` string `description` string | null `kind` enum PayComponentKind
`calculation` enum CalculationMethod `default_amount` Money (string) `default_rate` Decimal (string) `is_taxable` boolean
`reduces_taxable` boolean `affects_gross` boolean `gl_account_code` string | null `effective_gl_account_code` string
`sort_order` integer `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/pay-components/{pay_component}

Update pay component payrollPayComponentsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /pay-components/{pay_component}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `payroll.manage`

DELETE /api/v1/pay-components/{pay_component}

Delete pay component payrollPayComponentsDestroy

Pay component delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `payroll.manage` (delete on PayComponent)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
pay_component	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/tax-tables

List tax tables payrollTaxTablesIndex

Tax tables ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payroll.manage` (viewAny on TaxTable)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[period]	query	enum TaxTablePeriod	no	Exact-match filter (comma-separated = koi bhi value). · values: monthly, annual
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-effective_from). The primary key is always appended as a tie-breaker. · values: name, -name, effective_from, -effective_from, created_at, -created_at · default -effective_from

RESPONSES

200 — `data` : array of TaxTable + `meta.pagination`

`id` integer `name` string `effective_from` string(date) | null `period` enum TaxTablePeriod `is_active` boolean `notes` string | null `brackets` object[] `brackets_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/**tax-tables**

Create tax table `payrollTaxTablesStore`

Naya tax table banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `payroll.manage` (create on TaxTable)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`brackets`	object[]	**yes**	minItems 1 · maxItems 50
`brackets[].fixed_amount`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`brackets[].from_amount`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`brackets[].rate`	string | number	no	min 0 · max 100 · pattern `^\d{1,4}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`brackets[].to_amount`	string | number | null	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`effective_from`	string(date)	**yes**	
`is_active`	boolean	no	
`name`	string	**yes**	maxLength 100
`notes`	string | null	no	maxLength 1000
`period`	enum TaxTablePeriod	**yes**	values: `monthly`, `annual`

EXAMPLE REQUEST

```
{
  "brackets": [
    {
      "fixed_amount": "1250.0000",
      "from_amount": "1250.0000",
      "rate": "17.0000",
      "to_amount": "1250.0000"
    }
  ],
  "effective_from": "2026-10-15",
  "is_active": true,
  "name": "Sample name",
  "notes": "Sample text",
  "period": "monthly"
}
```

RESPONSES

201 — `data`: TaxTable

`id` integer `name` string `effective_from` string(date) | null `period` enum TaxTablePeriod `is_active` boolean `notes` string | null `brackets` object[] `brackets_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/tax-tables/{tax_table}

Get tax table `payrollTaxTablesShow`

Ek tax table ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payroll.manage` (view on TaxTable)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`tax_table`	path	string	**yes**	

RESPONSES

200 — `data` : TaxTable

`id` integer `name` string `effective_from` string(date) | null `period` enum TaxTablePeriod `is_active` boolean `notes` string | null `brackets` object[] `brackets_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/tax-tables/{tax_table}

Update tax table payrollTaxTablesUpdate

Maujooda tax table ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `payroll.manage` (update on TaxTable)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
tax_table	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
brackets	object[]	no	minItems 1 · maxItems 50
brackets[].fixed_amount	string | number	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
brackets[].from_amount	string | number	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
brackets[].rate	string | number	no	min 0 · max 100 · pattern ^\d{1,4}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
brackets[].to_amount	string | number | null	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
effective_from	string(date)	no	
is_active	boolean	no	
name	string	no	maxLength 100
notes	string | null	no	maxLength 1000
period	enum TaxTablePeriod	no	values: monthly, annual

RESPONSES

200 — `data`: TaxTable

`id` integer `name` string `effective_from` string(date) | null `period` enum TaxTablePeriod `is_active` boolean `notes` string | null `brackets` object[] `brackets_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/tax-tables/{tax_table}

Update tax table payrollTaxTablesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /tax-tables/{tax_table}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `payroll.manage`

DELETE /api/v1/tax-tables/{tax_table}

Delete tax table payrollTaxTablesDestroy

Tax table delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `payroll.manage` (delete on TaxTable)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`tax_table`	path	string	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/salary-structures

List salary structures payrollSalaryStructuresIndex

Salary structures ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payroll.manage` (viewAny on SalaryStructure)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[currency]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`name`). The primary key is always appended as a tie-breaker. · values: `name`, `-name`, `created_at`, `-created_at` · default `name`

RESPONSES

200 — `data` : array of SalaryStructure + `meta.pagination`

`id` integer `name` string `description` string | null `currency` string `is_active` boolean `components` object[]
`components_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/salary-structures

Create salary structure `payrollSalaryStructuresStore`

Naya salary structure banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `payroll.manage` (create on SalaryStructure)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`components`	object[]	no	maxItems 100
`components[].amount`	string | number | null	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`components[].pay_component_id`	integer	no	Values must be distinct. Validated by `TenantExists`.
`components[].rate`	string | number | null	no	min 0 · max 1000 · pattern `^\d{1,4}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`currency`	string	**yes**	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`description`	string | null	no	maxLength 500
`is_active`	boolean	no	
`name`	string	**yes**	maxLength 100 · Must be unique within `salary_structures` (per company).

EXAMPLE REQUEST

```
{
  "components": [{"amount":"1250.0000","pay_component_id":1,"rate":"17.0000"}],
  "currency": "PKR",
  "description": "Sample text",
  "is_active": true,
  "name": "Sample name"
}
```

RESPONSES

201 — `data` : SalaryStructure

`id` integer `name` string `description` string | null `currency` string `is_active` boolean `components` object[]
`components_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/salary-structures/{salary_structure}

Get salary structure `payrollSalaryStructuresShow`

Ek salary structure ki poori tafseel deta hai.

Auth: Session cookie · `X-Company-Id` **required**

Permission: Policy: `payroll.view` / `payroll.manage` (view on SalaryStructure)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`salary_structure`	path	string	**yes**	

RESPONSES

200 — `data` : SalaryStructure

`id` integer `name` string `description` string | null `currency` string `is_active` boolean `components` object[]
`components_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/salary-structures/{salary_structure}

Update salary structure `payrollSalaryStructuresUpdate`

Maujooda salary structure ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Policy: `payroll.manage` (update on SalaryStructure)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`salary_structure`	path	string	**yes**	

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`components`	object[]	no	maxItems 100
`components[].amount`	string | number | null	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`components[].pay_component_id`	integer	no	Values must be distinct. Validated by `TenantExists`.
`components[].rate`	string | number | null	no	min 0 · max 1000 · pattern `^\d{1,4}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`description`	string | null	no	maxLength 500
`is_active`	boolean	no	
`name`	string	no	maxLength 100 · Must be unique within `salary_structures` (per company).

RESPONSES

200 — `data` : SalaryStructure

`id` integer `name` string `description` string | null `currency` string `is_active` boolean `components` object[]
`components_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/salary-structures/{salary_structure}

Update salary structure payrollSalaryStructuresUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /salary-structures/{salary_structure} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission payroll.manage

DELETE /api/v1/salary-structures/{salary_structure}

Delete salary structure payrollSalaryStructuresDestroy

Salary structure delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: payroll.manage (delete on SalaryStructure)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
salary_structure	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/employees/{employee}/salaries

List salaries payrollEmployeesSalariesIndex

Salaries ki list deta hai — results paginated hote hain (page , per_page).

Auth Session cookie · X-Company-Id **required**

Permission Policy: payroll.view / payroll.manage (viewAny on EmployeeSalary)

Throttle api

List params page , per_page (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employee	path	integer	yes	ID of the Employee. · min 1

RESPONSES

200 — data : array of EmployeeSalary + meta.pagination

id integer employee_id integer salary_structure_id integer | null salary_structure object | null base_salary Money (string) currency string effective_from string(date) | null effective_to string(date) | null pay_frequency enum PayFrequency notes string | null components object[] created_by object | null created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/employees/{employee}/salaries

Create salary payrollEmployeesSalariesStore

Naya salary banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: payroll.manage · Policy: payroll.manage (create on EmployeeSalary)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
employee	path	integer	yes	ID of the Employee. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
base_salary	string | number	yes	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
components	object[]	no	maxItems 100
components[].amount	string | number | null	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
components[].pay_component_id	integer	no	Values must be distinct. Validated by TenantExists.
components[].rate	string | number | null	no	min 0 · max 1000 · pattern ^\d{1,4}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
currency	string	yes	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
effective_from	string(date)	yes	Must be unique within employee_salaries (per company).
effective_to	string(date) | null	no	after_or_equal:effective_from.
notes	string | null	no	maxLength 1000
pay_frequency	enum PayFrequency	no	values: monthly
salary_structure_id	integer | null	no	Validated by TenantExists.

EXAMPLE REQUEST

```
{
  "base_salary": "1250.0000",
  "components": [{"amount":"1250.0000","pay_component_id":1,"rate":"17.0000"}],
  "currency": "PKR",
  "effective_from": "2026-10-15",
  "effective_to": "2026-11-14",
  "notes": "Sample text",
  "pay_frequency": "monthly",
  "salary_structure_id": 1
}
```

RESPONSES

201 — data : EmployeeSalary

id integer · employee_id integer · salary_structure_id integer | null · salary_structure object | null · base_salary Money (string) · currency string · effective_from string(date) | null · effective_to string(date) | null · pay_frequency enum PayFrequency · notes string | null · components object[] · created_by object | null · created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/payroll-runs

List payroll runs `payrollPayrollRunsIndex`

Payroll runs ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payroll.view` · Policy: `payroll.view` (viewAny on PayrollRun)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum PayrollRunStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `calculated`, `approved`, `finalized`, `paid`, `cancelled`
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[department_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `period_end` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `period_end` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-period_end`). The primary key is always appended as a tie-breaker. · values: `period_end`, `-period_end`, `payment_date`, `-payment_date`, `number`, `-number`, `status`, `-status`, `created_at`, `-created_at` · default `-period_end`

RESPONSES

200 — `data` : array of PayrollRun + `meta.pagination`

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null

...aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/payroll-runs

Create payroll run `payrollPayrollRunsStore`

Naya payroll run banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Route: `payroll.process` · Policy: `payroll.process` (create on PayrollRun)
Throttle	`api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	`required_if:(condition)`. Validated by `AccessibleBranch`.
`department_id`	integer | null	no	Validated by `TenantExists`.
`name`	string	**yes**	maxLength 150
`notes`	string | null	no	maxLength 1000
`payment_date`	string(date)	**yes**	`after_or_equal:period_start`.
`period_end`	string(date)	**yes**	`after_or_equal:period_start`.
`period_start`	string(date)	**yes**	

EXAMPLE REQUEST

```
{
  "branch_id": 1,
  "department_id": 1,
  "name": "Sample name",
  "notes": "Sample text",
  "payment_date": "2026-10-15",
  "period_end": "2026-11-14",
  "period_start": "2026-10-15"
}
```

RESPONSES

201 — `data` : PayrollRun + `meta` { `skipped` }

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null

…aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/payroll-runs/{payroll_run}

Get payroll run `payrollPayrollRunsShow`

Ek payroll run ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payroll.view` · Policy: `payroll.view` (view on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

RESPONSES

200 — `data` : PayrollRun

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

DELETE /api/v1/payroll-runs/{payroll_run}

Only Draft runs may be deleted; later states are cancelled instead. `payrollPayrollRunsDestroy`

Payroll run delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `payroll.process` · Policy: `payroll.process` (delete on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST `/api/v1/payroll-runs/{payroll_run}/calculate`

Calculate – payroll run `payrollPayrollRunsCalculate`

Payroll run ka calculation chalata hai.

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Route: `payroll.process` · Policy: `payroll.process` (process on PayrollRun)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

RESPONSES

200 — `data`: PayrollRun + `meta` { `skipped` }

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST `/api/v1/payroll-runs/{payroll_run}/approve`

Approve – payroll run `payrollPayrollRunsApprove`

Payroll run ko approve karta hai.

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Route: `payroll.process` · Policy: `payroll.process` (process on PayrollRun)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

RESPONSES

200 — `data`: PayrollRun

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST `/api/v1/payroll-runs/{payroll_run}/finalize`

Finalize – payroll run `payrollPayrollRunsFinalize`

Payroll run ko finalize karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `payroll.process` · Policy: `payroll.process` (process on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

RESPONSES

200 — `data` : PayrollRun

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST `/api/v1/payroll-runs/{payroll_run}/pay`

Pay – payroll run `payrollPayrollRunsPay`

Payroll run ko paid mark karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `payroll.process` · Policy: `payroll.process` (process on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
bank_account_id	integer	yes	Validated by `TenantExists`.
paid_at	string(date)	yes	

RESPONSES

200 — `data` : PayrollRun

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/payroll-runs/{payroll_run}/cancel

Cancel – payroll run `payrollPayrollRunsCancel`

Payroll run ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `payroll.process` · Policy: `payroll.process` (process on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payroll_run	path	string	yes	

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
reason	string | null	no	maxLength 500

RESPONSES

200 — `data`: PayrollRun

`id` integer `number` string `name` string `period_start` string(date) | null `period_end` string(date) | null `payment_date` string(date) | null `currency` string `status` enum PayrollRunStatus `branch_id` integer | null `branch` object | null `department_id` integer | null `department` object | null `totals` object `calculated_at` string(date-time) | null `created_by` object | null `approved_by` object | null `approved_at` string(date-time) | null `finalized_by` object | null `finalized_at` string(date-time) | null `paid_at` string(date-time) | null `bank_account_id` integer | null `cancelled_at` string(date-time) | null `journal_entry_id` integer | null `payment_journal_entry_id` integer | null `notes` string | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/payroll-runs/{payroll_run}/payslips

Payslips – payroll run `payrollPayrollRunsPayslips`

Payroll run ki saari payslips deta hai.

`search` matches (case-insensitive, substring): `employee_code`, `employee_name`, `number`.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payroll.view` · Policy: `payroll.view` (view on PayrollRun)

Throttle `api`

List params `page`, `per_page`, `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`payroll_run`	path	string	**yes**	
`filter[department_id]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (`employee_code`). The primary key is always appended as a tie-breaker. · values: `employee_code`, `-employee_code`, `employee_name`, `-employee_name`, `net`, `-net`, `gross`, `-gross` · default `employee_code`

RESPONSES

200 — `data`: array of Payslip + `meta.pagination`

`id` integer `number` string | null `status` enum PayrollRunStatus `payroll_run_id` integer `run` object `employee` object `currency` string `base_salary` Money (string) `working_days` Decimal (string) `unpaid_days` Decimal (string) `paid_days` Decimal (string) `earned_base` Money (string) `gross` Money (string) `taxable` Money (string) `tax` Money (string) `total_deductions` Money (string) `employer_contributions` Money (string) `net` Money (string) `warnings` any[] `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/payroll-runs/{payroll_run}/export

Export – payroll run `payrollPayrollRunsExport`

Payroll run ko file (CSV/XLSX) ki shakal mein export/download karta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payroll.view` · Policy: `payroll.view` (export on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`payroll_run`	path	string	**yes**	
`format`	query	string	no	values: `csv`, `xlsx`

RESPONSES

200 — File (`text/csv`, `application/vnd.openxmlformats-officedocument.spreadsheetml.sheet`). File download (`Content-Disposition: attachment`).

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `422` validation.failed · `429` throttled

GET /api/v1/payroll/reports/summary

Summary – report `payrollReportsSummary`

Summary report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payroll.view` · Policy: `payroll.view` (viewAny on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`from`	query	string(date)	**yes**	
`to`	query	string(date)	**yes**	`after_or_equal:from`.

RESPONSES

200 — `data` : object shape inferred from code

`from` string(date) `to` string(date) `runs` object[] `departments` object[] `totals` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/payroll/reports/components

Components – report `payrollReportsComponents`

Components report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payroll.view` · Policy: `payroll.view` (viewAny on PayrollRun; view on PayrollRun)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`run_id`	query	integer	**yes**	Validated by `TenantExists`.

RESPONSES

200 — `data` : object shape inferred from code

`run` object `components` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/payslips/{payslip}

Get payslip payrollPayslipsShow

Ek payslip ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payslips.view.own` (view on Payslip)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payslip	path	integer	yes	ID of the Payslip. · min 1

RESPONSES

200 — `data` : Payslip

`id` integer `number` string | null `status` enum PayrollRunStatus `payroll_run_id` integer `run` object `employee` object `currency` string `base_salary` Money (string) `working_days` Decimal (string) `unpaid_days` Decimal (string) `paid_days` Decimal (string) `earned_base` Money (string) `gross` Money (string) `taxable` Money (string) `tax` Money (string) `total_deductions` Money (string) `employer_contributions` Money (string) `net` Money (string) `warnings` any[] `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/payslips/{payslip}/pdf

Pdf – payslip payrollPayslipsPdf

Payslip ki PDF download karta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payroll.view` / `payslips.view.own` (view on Payslip)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payslip	path	integer	yes	ID of the Payslip. · min 1

RESPONSES

200 — File (`application/pdf`). File download (`Content-Disposition: attachment`).

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/my-payslips

List my payslips `payrollMyPayslipsIndex`

My payslips ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payslips.view.own` · Policy: `payslips.view.own` (viewMine on Payslip)

Throttle `api`

List params `page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`sort`	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (`-id`). The primary key is always appended as a tie-breaker. · values: `created_at`, `-created_at`, `id`, `-id` · default `-id`

RESPONSES

200 — `data` : array of Payslip + `meta.pagination`

`id` integer `number` string | null `status` enum PayrollRunStatus `payroll_run_id` integer `run` object `employee` object `currency` string `base_salary` Money (string) `working_days` Decimal (string) `unpaid_days` Decimal (string) `paid_days` Decimal (string) `earned_base` Money (string) `gross` Money (string) `taxable` Money (string) `tax` Money (string) `total_deductions` Money (string) `employer_contributions` Money (string) `net` Money (string) `warnings` any[] `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/my-payslips/{payslip}

Get my payslip `payrollMyPayslipsShow`

Ek my payslip ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payslips.view.own` · Policy: `payslips.view.own` (viewMine on Payslip)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`payslip`	path	integer	**yes**	min 1

RESPONSES

200 — `data` : Payslip

`id` integer `number` string | null `status` enum PayrollRunStatus `payroll_run_id` integer `run` object `employee` object `currency` string `base_salary` Money (string) `working_days` Decimal (string) `unpaid_days` Decimal (string) `paid_days` Decimal (string) `earned_base` Money (string) `gross` Money (string) `taxable` Money (string) `tax` Money (string) `total_deductions` Money (string) `employer_contributions` Money (string) `net` Money (string) `warnings` any[] `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/my-payslips/{payslip}/pdf

Pdf – my payslip `payrollMyPayslipsPdf`

Logged-in employee ki apni payslip ki PDF download karta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `payslips.view.own` · Policy: `payslips.view.own` (viewMine on Payslip)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`payslip`	path	integer	**yes**	min 1

RESPONSES

200 — File (`application/pdf`). File download (`Content-Disposition: attachment`).

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

MODULE

Finance – Ledger

Chart of accounts, financial years/periods, journal entries, tax rates, bank accounts aur ledger reports (trial balance, P&L, balance sheet, cash flow, general ledger). Debits ≠ credits par `422 finance.unbalanced`, aur closed period ya posted entry badalne par `409 finance.period_closed / finance.immutable` milta hai.

Spec: Chart of accounts, financial years/periods, journal entries, tax rates, bank accounts, ledger reports. — 42 operations.

Method	Path	Summary	Permission
GET	/accounts/tree	Full hierarchy for the chart-of-accounts view and account pickers.	accounts.view
POST	/accounts/seed-defaults	Seeds the standard chart, current financial year and tax rates (idempotent).	accounts.manage
GET	/accounts/{account}/ledger	General ledger for one account: opening balance, lines with running balance.	accounts.view
GET	/accounts	List accounts	accounts.view
POST	/accounts	Create account	accounts.manage
GET	/accounts/{account}	Get account	accounts.view
PUT	/accounts/{account}	Update account	accounts.manage
PATCH	/accounts/{account}	Update account	accounts.manage
DELETE	/accounts/{account}	Delete account	accounts.manage
GET	/financial-years	List financial years	accounts.view journals.view periods.manage
POST	/financial-years	Creates a 12-month year with its monthly periods.	periods.manage
GET	/financial-years/{financial_year}	Get financial year	accounts.view journals.view periods.manage
POST	/financial-periods/{financialPeriod}/close	Close – financial period	periods.manage
POST	/financial-periods/{financialPeriod}/reopen	Reopen – financial period	periods.manage
GET	/financial-periods	List financial periods	accounts.view journals.view periods.manage
GET	/financial-periods/{financial_period}	Get financial period	accounts.view journals.view periods.manage
GET	/tax-rates	List tax rates	accounts.view tax.manage
POST	/tax-rates	Create tax rate	tax.manage
GET	/tax-rates/{tax_rate}	Get tax rate	accounts.view tax.manage
PUT	/tax-rates/{tax_rate}	Update tax rate	tax.manage
PATCH	/tax-rates/{tax_rate}	Update tax rate	tax.manage

Method	Path	Summary	Permission
DELETE	/tax-rates/{tax_rate}	Delete tax rate	tax.manage
GET	/bank-accounts	List bank accounts	accounts.view bank.manage
POST	/bank-accounts	Create bank account	bank.manage
GET	/bank-accounts/{bank_account}	Get bank account	accounts.view bank.manage
PUT	/bank-accounts/{bank_account}	Update bank account	bank.manage
PATCH	/bank-accounts/{bank_account}	Update bank account	bank.manage
DELETE	/bank-accounts/{bank_account}	Delete bank account	bank.manage
POST	/journal-entries/{journalEntry}/post	Post – journal entry	journals.post
POST	/journal-entries/{journalEntry}/reverse	Reverse – journal entry	journals.post
GET	/journal-entries	List journal entries	journals.view
POST	/journal-entries	Create journal entry	journals.create
GET	/journal-entries/{journal_entry}	Get journal entry	journals.view
PUT	/journal-entries/{journal_entry}	Update journal entry	journals.create
PATCH	/journal-entries/{journal_entry}	Update journal entry	journals.create
DELETE	/journal-entries/{journal_entry}	Delete journal entry	journals.create
GET	/finance/reports/trial-balance	Trial balance – report	reports.financial.view
GET	/finance/reports/profit-and-loss	Profit and loss – report	reports.financial.view
GET	/finance/reports/balance-sheet	Balance sheet – report	reports.financial.view
GET	/finance/reports/cash-flow	Cash flow – report	reports.financial.view
GET	/finance/reports/general-ledger	General ledger – report	reports.financial.view
GET	/finance/reports/account-balances	Account balances – report	reports.financial.view

Endpoints

GET /api/v1/**accounts/tree**

Full hierarchy for the chart-of-accounts view and account pickers. `accountsTree`

Chart of accounts ki poori hierarchy deta hai (tree view aur account pickers ke liye).

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` (viewAny on Account)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
include_inactive	query	boolean	no	

RESPONSES

200 — `data` : array of object shape inferred from code

`id` integer `code` string `name` string `type` enum AccountType `subtype` string | null `is_bank` boolean `is_cash` boolean `is_system` boolean `is_active` boolean `children` any[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/accounts/seed-defaults`

Seeds the standard chart, current financial year and tax rates (idempotent). `accountsSeedDefaults`

Standard chart of accounts, current financial year aur tax rates seed karta hai (idempotent — dobara chalane se duplicate nahi bante).

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Route: `accounts.manage` · Policy: `accounts.manage` (create on Account)
Throttle	`api`

RESPONSES

200 — `data` : object shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `429` throttled

GET `/api/v1/accounts/{account}/ledger`

General ledger for one account: opening balance, lines with running balance. `accountsLedger`

Ek account ka general ledger deta hai: opening balance aur running balance ke saath lines.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `accounts.view` (view on Account)
Throttle	`api`
List params	`page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`account`	path	integer	**yes**	ID of the Account. · min 1
`account_id`	query	integer | null	no	Validated by `TenantExists`.
`as_of`	query	string(date) | null	no	
`branch_id`	query	integer | null	no	Validated by `AccessibleBranch`.
`compare`	query	string | null	no	values: `true`, `false`, `1`, `0`,
`from`	query	string(date) | null	no	
`include_zero`	query	string | null	no	values: `true`, `false`, `1`, `0`,
`to`	query	string(date) | null	no	Validated by `ConditionalRules`.

RESPONSES

200 — `data` : object + `meta` { `pagination` } shape inferred from code

`account` object `from` string(date) `to` string(date) `opening_balance` Decimal (string) `closing_balance` Decimal (string) `lines` any[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `422` validation.failed · `429` throttled

GET `/api/v1/accounts`

List accounts `accountsIndex`

Accounts ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `code` , `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` (viewAny on Account)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[type]`	query	enum AccountType	no	Exact-match filter (comma-separated = koi bhi value). · values: `asset`, `liability`, `equity`, `revenue`, `expense`
`filter[subtype]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[is_bank]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[is_cash]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[is_system]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[parent_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`code`). The primary key is always appended as a tie-breaker. · values: `code`, `-code`, `name`, `-name`, `type`, `-type`, `created_at`, `-created_at` · default `code`

RESPONSES

200 — `data` : array of Account + `meta.pagination`

`id` integer `company_id` integer `parent_id` integer | null `code` string `name` string `type` enum AccountType `subtype` string | null `normal_balance` string `is_bank` boolean `is_cash` boolean `is_system` boolean `is_active` boolean `currency` string `description` string | null `opening_balance` Money (string) `opening_balance_date` string(date) | null `parent` object `lines_count` integer `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/accounts

Create account accountsStore

Naya account banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `accounts.manage` (create on Account)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
code	string	yes	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within accounts (per company).
currency	string | null	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
description	string | null	no	maxLength 500
is_active	boolean	no	
is_bank	boolean	no	
is_cash	boolean	no	
name	string	yes	maxLength 150
opening_balance	string | number | null	no	pattern ^-?\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
opening_balance_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
parent_id	integer | null	no	Validated by TenantExists.
subtype	string | null	no	values: cash, bank, receivable, inventory, prepaid, current_asset, fixed_asset, accumulated_depreciation, intangible, investment, payable, tax, accrued_payroll, accrued_liability, current_liability, loan, long_term_liability, share_capital, retained_earnings, owner_drawings, other_equity, sales_revenue, service_revenue, other_income, cost_of_sales, operating_expense, payroll_expense, depreciation, finance_cost, tax_expense, other_expense,
type	enum AccountType	yes	values: asset, liability, equity, revenue, expense

EXAMPLE REQUEST

```
{
  "code": "CODE-001",
  "name": "Sample name",
  "type": "asset",
  "currency": "PKR",
  "description": "Sample text",
  "is_active": true,
  "is_bank": true,
  "is_cash": true
}
```

RESPONSES

201 — `data` : Account

`id` integer `company_id` integer `parent_id` integer | null `code` string `name` string `type` enum AccountType `subtype` string | null `normal_balance` string `is_bank` boolean `is_cash` boolean `is_system` boolean `is_active` boolean `currency` string `description` string | null `opening_balance` Money (string) `opening_balance_date` string(date) | null `parent` object `lines_count` integer `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/accounts/{account}`

Get account `accountsShow`

Ek account ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` (view on Account)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`account`	path	integer	**yes**	ID of the Account. · min 1

RESPONSES

200 — `data` : Account

`id` integer `company_id` integer `parent_id` integer | null `code` string `name` string `type` enum AccountType
`subtype` string | null `normal_balance` string `is_bank` boolean `is_cash` boolean `is_system` boolean `is_active` boolean
`currency` string `description` string | null `opening_balance` Money (string) `opening_balance_date` string(date) | null
`parent` object `lines_count` integer `children_count` integer `created_at` string(date-time) | null
`updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/accounts/{account}

Update account accountsUpdate

Maujooda account ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `accounts.manage` (update on Account)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account	path	integer	yes	ID of the Account. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
code	string	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within accounts (per company).
currency	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
description	string | null	no	maxLength 500
is_active	boolean	no	
is_bank	boolean	no	
is_cash	boolean	no	
name	string	no	maxLength 150
opening_balance	string | number | null	no	pattern `^-?\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
opening_balance_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
parent_id	integer | null	no	Validated by TenantExists.
subtype	string | null	no	values: cash, bank, receivable, inventory, prepaid, current_asset, fixed_asset, accumulated_depreciation, intangible, investment, payable, tax, accrued_payroll, accrued_liability, current_liability, loan, long_term_liability, share_capital, retained_earnings, owner_drawings, other_equity, sales_revenue, service_revenue, other_income, cost_of_sales, operating_expense, payroll_expense, depreciation, finance_cost, tax_expense, other_expense,
type	enum AccountType	no	values: asset, liability, equity, revenue, expense

RESPONSES

200 — `data` : Account

`id` integer `company_id` integer `parent_id` integer | null `code` string `name` string `type` enum AccountType `subtype` string | null `normal_balance` string `is_bank` boolean `is_cash` boolean `is_system` boolean `is_active` boolean `currency` string `description` string | null `opening_balance` Money (string) `opening_balance_date` string(date) | null `parent` object `lines_count` integer `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/accounts/{account}

Update account accountsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /accounts/{account}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `accounts.manage`

DELETE /api/v1/accounts/{account}

Delete account accountsDestroy

Account delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `accounts.manage` (delete on Account)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account	path	integer	yes	ID of the Account. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/financial-years

List financial years financialYearsIndex

Financial years ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` / `journals.view` / `periods.manage` (viewAny on FinancialYear)

Throttle `api`

List params `page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum PeriodStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: open, closed
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-start_date). The primary key is always appended as a tie-breaker. · values: start_date, -start_date, name, -name, created_at, -created_at · default -start_date

RESPONSES

200 — `data` : array of FinancialYear + `meta.pagination`

`id` integer `company_id` integer `name` string `start_date` string(date) `end_date` string(date) `status` enum PeriodStatus

`periods` FinancialPeriod[] `periods_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/financial-years

Creates a 12-month year with its monthly periods. financialYearsStore

Naya financial year banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: periods.manage (create on FinancialYear)

Throttle api

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
name	string | null	no	maxLength 40
start_date	string(date) | null	no	

EXAMPLE REQUEST

```
{"name":"Sample name","start_date":"2026-10-15"}
```

RESPONSES

201 — data : FinancialYear

id integer company_id integer name string start_date string(date) end_date string(date) status enum PeriodStatus
periods FinancialPeriod[] periods_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/financial-years/{financial_year}

Get financial year financialYearsShow

Ek financial year ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: accounts.view / journals.view / periods.manage (view on FinancialYear)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
financial_year	path	string	**yes**	

RESPONSES

200 — data : FinancialYear

id integer company_id integer name string start_date string(date) end_date string(date) status enum PeriodStatus
periods FinancialPeriod[] periods_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/financial-periods/{financialPeriod}/close

Close – financial period financialPeriodsClose

Financial period ko close karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: periods.manage · Policy: periods.manage (close on FinancialPeriod)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
financialPeriod	path	integer	yes	ID of the Financial Period. · min 1

RESPONSES

200 — data : FinancialPeriod

id integer company_id integer financial_year_id integer name string start_date string(date) end_date string(date) status enum PeriodStatus closed_by object | null closed_at string(date-time) | null financial_year object created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/financial-periods/{financialPeriod}/reopen

Reopen – financial period financialPeriodsReopen

Financial period ko dobara open karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: periods.manage · Policy: periods.manage (reopen on FinancialPeriod)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
financialPeriod	path	integer	yes	ID of the Financial Period. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
reason	string | null	no	maxLength 255

RESPONSES

200 — data : FinancialPeriod

id integer company_id integer financial_year_id integer name string start_date string(date) end_date string(date) status enum PeriodStatus closed_by object | null closed_at string(date-time) | null financial_year object created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/financial-periods

List financial periods financialPeriodsIndex

Financial periods ki list deta hai — results paginated hote hain (page , per_page).

Auth Session cookie · X-Company-Id required

Permission Policy: accounts.view / journals.view / periods.manage (viewAny on FinancialPeriod)

Throttle api

List params page , per_page (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum PeriodStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: open, closed
filter[financial_year_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on start_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on start_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (start_date). The primary key is always appended as a tie-breaker. · values: start_date, -start_date, name, -name, status, -status · default start_date

RESPONSES

200 — data : array of FinancialPeriod + meta.pagination

id integer company_id integer financial_year_id integer name string start_date string(date) end_date string(date)
status enum PeriodStatus closed_by object | null closed_at string(date-time) | null financial_year object
created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/financial-periods/{financial_period}

Get financial period financialPeriodsShow

Ek financial period ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id required

Permission Policy: accounts.view / journals.view / periods.manage (view on FinancialPeriod)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
financial_period	path	string	yes	

RESPONSES

200 — data : FinancialPeriod

id integer company_id integer financial_year_id integer name string start_date string(date) end_date string(date)
status enum PeriodStatus closed_by object | null closed_at string(date-time) | null financial_year object
created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

`GET` `/api/v1/tax-rates`

List tax rates `taxRatesIndex`

Tax rates ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` , `code` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` / `tax.manage` (viewAny on TaxRate)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[type]`	query	enum TaxRateType	no	Exact-match filter (comma-separated = koi bhi value). · values: `sales`, `purchase`, `both`
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`sort`	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (`code`). The primary key is always appended as a tie-breaker. · values: `code`, `-code`, `name`, `-name`, `rate`, `-rate`, `created_at`, `-created_at` · default `code`

RESPONSES

200 — `data` : array of TaxRate + `meta.pagination`

`id` integer `company_id` integer `name` string `code` string `rate` Decimal (string) `type` enum TaxRateType `account_id` integer | null `account` object | null `is_compound` boolean `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/tax-rates`

Create tax rate `taxRatesStore`

Naya tax rate banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `tax.manage` (create on TaxRate)
Throttle	`api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`account_id`	integer | null	no	Validated by `TenantExists`.
`code`	string	**yes**	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `tax_rates` (per company).
`is_active`	boolean	no	
`is_compound`	boolean	no	
`name`	string	**yes**	maxLength 100
`rate`	string | number	**yes**	min 0 · max 1000 · pattern `^\d{1,4}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`type`	enum TaxRateType	**yes**	values: `sales`, `purchase`, `both`

EXAMPLE REQUEST

```
{
  "account_id": 1,
  "code": "CODE-001",
  "is_active": true,
  "is_compound": true,
  "name": "Sample name",
  "rate": "17.0000",
  "type": "sales"
}
```

RESPONSES

201 — `data`: TaxRate

`id` integer `company_id` integer `name` string `code` string `rate` Decimal (string) `type` enum TaxRateType
`account_id` integer | null `account` object | null `is_compound` boolean `is_active` boolean `created_at` string(date-time) | null
`updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/tax-rates/{tax_rate}

Get tax rate taxRatesShow

Ek tax rate ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: accounts.view / tax.manage (view on TaxRate)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
tax_rate	path	string	yes	

RESPONSES

200 — data : TaxRate

id integer company_id integer name string code string rate Decimal (string) type enum TaxRateType
account_id integer | null account object | null is_compound boolean is_active boolean created_at string(date-time) | null
updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

PUT /api/v1/tax-rates/{tax_rate}

Update tax rate taxRatesUpdate

Maujooda tax rate ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use sometimes).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: tax.manage (update on TaxRate)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
tax_rate	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
account_id	integer | null	no	Validated by TenantExists.
code	string	no	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within tax_rates (per company).
is_active	boolean	no	
is_compound	boolean	no	
name	string	no	maxLength 100
rate	string | number	no	min 0 · max 1000 · pattern ^\d{1,4}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
type	enum TaxRateType	no	values: sales, purchase, both

RESPONSES

200 — data : TaxRate

id integer company_id integer name string code string rate Decimal (string) type enum TaxRateType
account_id integer | null account object | null is_compound boolean is_active boolean created_at string(date-time) | null
updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

PATCH /api/v1/tax-rates/{tax_rate}

Update tax rate `taxRatesUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /tax-rates/{tax_rate}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `tax.manage`

DELETE /api/v1/tax-rates/{tax_rate}

Delete tax rate `taxRatesDestroy`

Tax rate delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `tax.manage` (delete on TaxRate)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
tax_rate	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/bank-accounts`

List bank accounts `bankAccountsIndex`

Bank accounts ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` , `bank_name` , `account_number_last4` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` / `bank.manage` (viewAny on BankAccount)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[currency]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[account_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`name`). The primary key is always appended as a tie-breaker. · values: `name`, `-name`, `bank_name`, `-bank_name`, `created_at`, `-created_at` · default `name`

RESPONSES

200 — `data` : array of BankAccount + `meta.pagination`

`id` integer `company_id` integer `account_id` integer `account` object `name` string `bank_name` string | null `account_number_masked` string | null `account_number_last4` string | null `iban_masked` string | null `swift` string | null `currency` string `opening_balance` Money (string) `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/bank-accounts

Create bank account bankAccountsStore

Naya bank account banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `bank.manage` (create on BankAccount)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
account_id	integer	yes	Custom validation applies.
account_number	string | null	no	maxLength 64
bank_name	string | null	no	maxLength 150
currency	string | null	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
iban	string | null	no	maxLength 34 · pattern ^[A-Za-z0-9]+$
is_active	boolean	no	
name	string	yes	maxLength 150
opening_balance	string | number | null	no	pattern ^-?\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
swift	string | null	no	maxLength 20 · pattern ^[A-Za-z0-9]+$

EXAMPLE REQUEST

```
{
  "account_id": 1,
  "account_number": "string",
  "bank_name": "Sample name",
  "currency": "PKR",
  "iban": "string",
  "is_active": true,
  "name": "Sample name",
  "opening_balance": "1250.0000",
  "swift": "string"
}
```

RESPONSES

201 — `data` : BankAccount

`id` integer `company_id` integer `account_id` integer `account` object `name` string `bank_name` string | null `account_number_masked` string | null `account_number_last4` string | null `iban_masked` string | null `swift` string | null `currency` string `opening_balance` Money (string) `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/bank-accounts/{bank_account}`

Get bank account `bankAccountsShow`

Ek bank account ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `accounts.view` / `bank.manage` (view on BankAccount)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
bank_account	path	string	yes	

RESPONSES

200 — `data` : BankAccount

`id` integer `company_id` integer `account_id` integer `account` object `name` string `bank_name` string | null `account_number_masked` string | null `account_number_last4` string | null `iban_masked` string | null `swift` string | null `currency` string `opening_balance` Money (string) `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/bank-accounts/{bank_account}

Update bank account bankAccountsUpdate

Maujooda bank account ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `bank.manage` (update on BankAccount)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
bank_account	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
account_id	integer	no	Custom validation applies.
account_number	string | null	no	maxLength 64
bank_name	string | null	no	maxLength 150
currency	string | null	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
iban	string | null	no	maxLength 34 · pattern ^[A-Za-z0-9]+$
is_active	boolean	no	
name	string	no	maxLength 150
opening_balance	string | number | null	no	pattern ^-?\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
swift	string | null	no	maxLength 20 · pattern ^[A-Za-z0-9]+$

RESPONSES

200 — `data`: BankAccount

`id` integer `company_id` integer `account_id` integer `account` object `name` string `bank_name` string | null `account_number_masked` string | null `account_number_last4` string | null `iban_masked` string | null `swift` string | null `currency` string `opening_balance` Money (string) `is_active` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/bank-accounts/{bank_account}

Update bank account bankAccountsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /bank-accounts/{bank_account} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission bank.manage

DELETE /api/v1/bank-accounts/{bank_account}

Delete bank account bankAccountsDestroy

Bank account delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: bank.manage (delete on BankAccount)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
bank_account	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

POST /api/v1/journal-entries/{journalEntry}/post

Post – journal entry journalEntriesPost

Journal entry ko post karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: journals.post · Policy: journals.post (post on JournalEntry)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
journalEntry	path	integer	yes	ID of the Journal Entry. · min 1

RESPONSES

200 — data : JournalEntry

id integer · company_id integer · number string · entry_date string(date) · financial_period_id integer | null · period object | null · reference string | null · memo string | null · status enum JournalEntryStatus · source_type string | null · source_id integer | null · branch_id integer | null · branch object | null · total_debit Money (string) · total_credit Money (string) · is_balanced boolean · created_by integer | null · creator object | null · posted_by integer | null · poster object | null · posted_at string(date-time) | null · reverses_entry_id integer | null · reversed_by_entry_id integer | null · lines JournalLine[] · lines_count integer …aur 2 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/journal-entries/{journalEntry}/reverse

Reverse – journal entry `journalEntriesReverse`

Journal entry ko reverse karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `journals.post` · Policy: `journals.post` (reverse on JournalEntry)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`journalEntry`	path	integer	yes	ID of the Journal Entry. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`entry_date`	string(date) | null	no	
`memo`	string | null	no	maxLength 500

EXAMPLE REQUEST

```
{"entry_date":"2026-10-15","memo":"string"}
```

RESPONSES

201 — `data` : JournalEntry

`id` integer `company_id` integer `number` string `entry_date` string(date) `financial_period_id` integer | null `period` object | null `reference` string | null `memo` string | null `status` enum JournalEntryStatus `source_type` string | null `source_id` integer | null `branch_id` integer | null `branch` object | null `total_debit` Money (string) `total_credit` Money (string) `is_balanced` boolean `created_by` integer | null `creator` object | null `posted_by` integer | null `poster` object | null `posted_at` string(date-time) | null `reverses_entry_id` integer | null `reversed_by_entry_id` integer | null `lines` JournalLine[] `lines_count` integer …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/journal-entries

List journal entries journalEntriesIndex

Journal entries ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): number , reference , memo .

Auth Session cookie · X-Company-Id **required**

Permission Policy: journals.view (viewAny on JournalEntry)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum JournalEntryStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: draft, posted, reversed
filter[source_type]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[source_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[branch_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[financial_period_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on entry_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on entry_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-entry_date). The primary key is always appended as a tie-breaker. · values: entry_date, -entry_date, number, -number, status, -status, total_debit, -total_debit, created_at, -created_at · default -entry_date
account_id	query	integer	no	

RESPONSES

200 — data : array of JournalEntry + meta.pagination

id integer company_id integer number string entry_date string(date) financial_period_id integer | null period object | null reference string | null memo string | null status enum JournalEntryStatus source_type string | null source_id integer | null branch_id integer | null branch object | null total_debit Money (string) total_credit Money (string) is_balanced boolean created_by integer | null creator object | null posted_by integer | null poster object | null posted_at string(date-time) | null reverses_entry_id integer | null reversed_by_entry_id integer | null lines JournalLine[] lines_count integer ...aur 2 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/journal-entries

Create journal entry journalEntriesStore

Naya journal entry banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: journals.create (create on JournalEntry)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`entry_date`	string(date)	**yes**	
`lines`	object[]	**yes**	minItems 2 · maxItems 200
`lines[].account_id`	integer	no	Validated by `TenantExists`.
`lines[].branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`lines[].credit`	string | number | null	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].debit`	string | number | null	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].description`	string | null	no	maxLength 255
`lines[].partner_id`	integer | null	no	`required_with:lines.*.partner_type`.
`lines[].partner_type`	string | null	no	maxLength 30 · pattern `^[A-Za-z0-9_-]+$`
`lines[].tax_rate_id`	integer | null	no	Validated by `TenantExists`.
`memo`	string | null	no	maxLength 500
`reference`	string | null	no	maxLength 100

EXAMPLE REQUEST

```
{
  "branch_id": 1,
  "entry_date": "2026-10-15",
  "lines": [
    {
      "account_id": 1,
      "branch_id": 1,
      "credit": "1250.0000",
      "debit": "1250.0000",
      "description": "Sample text",
      "partner_id": 1,
      "partner_type": "string",
      "tax_rate_id": 1
    }
  ],
  "memo": "string",
  "reference": "string"
}
```

RESPONSES

201 — `data` : JournalEntry

`id` integer `company_id` integer `number` string `entry_date` string(date) `financial_period_id` integer | null `period` object | null `reference` string | null `memo` string | null `status` enum JournalEntryStatus `source_type` string | null `source_id` integer | null `branch_id` integer | null `branch` object | null `total_debit` Money (string) `total_credit` Money (string) `is_balanced` boolean `created_by` integer | null `creator` object | null `posted_by` integer | null `poster` object | null `posted_at` string(date-time) | null `reverses_entry_id` integer | null `reversed_by_entry_id` integer | null `lines` JournalLine[] `lines_count` integer …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/journal-entries/{journal_entry}

Get journal entry journalEntriesShow

Ek journal entry ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `journals.view` (view on JournalEntry)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
journal_entry	path	string	yes	

RESPONSES

200 — `data` : JournalEntry

`id` integer `company_id` integer `number` string `entry_date` string(date) `financial_period_id` integer | null `period` object | null `reference` string | null `memo` string | null `status` enum JournalEntryStatus `source_type` string | null `source_id` integer | null `branch_id` integer | null `branch` object | null `total_debit` Money (string) `total_credit` Money (string) `is_balanced` boolean `created_by` integer | null `creator` object | null `posted_by` integer | null `poster` object | null `posted_at` string(date-time) | null `reverses_entry_id` integer | null `reversed_by_entry_id` integer | null `lines` JournalLine[] `lines_count` integer …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/journal-entries/{journal_entry}

Update journal entry journalEntriesUpdate

Maujooda journal entry ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `journals.create` (update on JournalEntry)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
journal_entry	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
branch_id	integer | null	no	Validated by AccessibleBranch.
entry_date	string(date)	no	
lines	object[]	no	minItems 2 · maxItems 200
lines[].account_id	integer	no	Validated by TenantExists.
lines[].branch_id	integer | null	no	Validated by AccessibleBranch.
lines[].credit	string | number | null	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].debit	string | number | null	no	min 0 · pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].description	string | null	no	maxLength 255
lines[].partner_id	integer | null	no	required_with:lines.*.partner_type.
lines[].partner_type	string | null	no	maxLength 30 · pattern ^[A-Za-z0-9_-]+$
lines[].tax_rate_id	integer | null	no	Validated by TenantExists.
memo	string | null	no	maxLength 500
reference	string | null	no	maxLength 100

RESPONSES

200 — `data` : JournalEntry

`id` integer `company_id` integer `number` string `entry_date` string(date) `financial_period_id` integer | null `period` object | null `reference` string | null `memo` string | null `status` enum JournalEntryStatus `source_type` string | null `source_id` integer | null `branch_id` integer | null `branch` object | null `total_debit` Money (string) `total_credit` Money (string) `is_balanced` boolean `created_by` integer | null `creator` object | null `posted_by` integer | null `poster` object | null `posted_at` string(date-time) | null `reverses_entry_id` integer | null `reversed_by_entry_id` integer | null `lines` JournalLine[] `lines_count` integer ...aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/journal-entries/{journal_entry}

Update journal entry journalEntriesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /journal-entries/{journal_entry} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission journals.create

DELETE /api/v1/journal-entries/{journal_entry}

Delete journal entry journalEntriesDestroy

Journal entry delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: journals.create (delete on JournalEntry)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
journal_entry	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/finance/reports/trial-balance

Trial balance – report financeReportsTrialBalance

Trial balance report ka data JSON mein deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Route: reports.financial.view (finance.reports.view)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account_id	query	integer | null	no	Validated by TenantExists.
as_of	query	string(date) | null	no	
branch_id	query	integer | null	no	Validated by AccessibleBranch.
compare	query	string | null	no	values: true, false, 1, 0,
from	query	string(date) | null	no	
include_zero	query	string | null	no	values: true, false, 1, 0,
to	query	string(date) | null	no	Validated by ConditionalRules.

RESPONSES

200 — data : any shape inferred from code

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

GET /api/v1/finance/reports/profit-and-loss

Profit and loss – report `financeReportsProfitAndLoss`

Profit and loss report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account_id	query	integer | null	no	Validated by TenantExists.
as_of	query	string(date) | null	no	
branch_id	query	integer | null	no	Validated by AccessibleBranch.
compare	query	string | null	no	values: true, false, 1, 0,
from	query	string(date) | null	no	
include_zero	query	string | null	no	values: true, false, 1, 0,
to	query	string(date) | null	no	Validated by ConditionalRules.

RESPONSES

200 — `data` : object shape inferred from code

`from` string(date) `to` string(date) `branch_id` integer `revenue` object `cost_of_sales` object `gross_profit` Decimal (string) `expenses` object `total_expenses` Decimal (string) `net_profit` Decimal (string)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/finance/reports/balance-sheet

Balance sheet – report `financeReportsBalanceSheet`

Balance sheet report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account_id	query	integer | null	no	Validated by TenantExists.
as_of	query	string(date) | null	no	
branch_id	query	integer | null	no	Validated by AccessibleBranch.
compare	query	string | null	no	values: true, false, 1, 0,
from	query	string(date) | null	no	
include_zero	query	string | null	no	values: true, false, 1, 0,
to	query	string(date) | null	no	Validated by ConditionalRules.

RESPONSES

200 — `data` : object shape inferred from code

`as_of` string(date) `branch_id` integer `fiscal_year_start` string(date) `assets` object `liabilities` object `equity` number `total_liabilities_and_equity` Decimal (string) `check` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/finance/reports/cash-flow

Cash flow – report `financeReportsCashFlow`

Cash flow report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account_id	query	integer | null	no	Validated by TenantExists.
as_of	query	string(date) | null	no	
branch_id	query	integer | null	no	Validated by AccessibleBranch.
compare	query	string | null	no	values: true, false, 1, 0,
from	query	string(date) | null	no	
include_zero	query	string | null	no	values: true, false, 1, 0,
to	query	string(date) | null	no	Validated by ConditionalRules.

RESPONSES

200 — `data` : object shape inferred from code

`from` string(date) `to` string(date) `branch_id` integer `opening_cash` Decimal (string) `net_change` Decimal (string) `closing_cash` Decimal (string) `reconciles` boolean

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/finance/reports/general-ledger

General ledger – report `financeReportsGeneralLedger`

General ledger report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

List params `page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
account_id	query	integer | null	no	Validated by TenantExists.
as_of	query	string(date) | null	no	
branch_id	query	integer | null	no	Validated by AccessibleBranch.
compare	query	string | null	no	values: true, false, 1, 0,
from	query	string(date) | null	no	
include_zero	query	string | null	no	values: true, false, 1, 0,
to	query	string(date) | null	no	Validated by ConditionalRules.

RESPONSES

200 — `data` : object + `meta` { `pagination` } shape inferred from code

`account` object `from` string(date) `to` string(date) `opening_balance` Decimal (string) `closing_balance` Decimal (string) `lines` any[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET `/api/v1/finance/reports/account-balances`

Account balances – report `financeReportsAccountBalances`

Account balances report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`account_id`	query	integer | null	no	Validated by `TenantExists`.
`as_of`	query	string(date) | null	no	
`branch_id`	query	integer | null	no	Validated by `AccessibleBranch`.
`compare`	query	string | null	no	values: `true`, `false`, `1`, `0`,
`from`	query	string(date) | null	no	
`include_zero`	query	string | null	no	values: `true`, `false`, `1`, `0`,
`to`	query	string(date) | null	no	Validated by `ConditionalRules`.

RESPONSES

200 — `data` : object shape inferred from code

`as_of` string(date) `accounts` object[] `totals` any[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Finance – Receivables

> Invoices, bills, payments, expense claims aur AR/AP reports (aging, receivables summary, customer statement). Documents draft → submit → approve flow follow karte hain, aur radd karne ke liye `void` action hai. Invoice PDF bhi yahan se download hoti hai.

Spec: Invoices, bills, payments, expense claims and AR/AP reports. — 38 operations.

Method	Path	Summary	Permission
POST	/invoices/{invoice}/submit	Submit – invoice	invoices.create invoices.update
POST	/invoices/{invoice}/approve	Approve – invoice	invoices.approve
POST	/invoices/{invoice}/void	Void – invoice	invoices.approve
GET	/invoices/{invoice}/pdf	Pdf – invoice	invoices.view
GET	/invoices	List invoices	invoices.view
POST	/invoices	Create invoice	invoices.create
GET	/invoices/{invoice}	Get invoice	invoices.view
PUT	/invoices/{invoice}	Update invoice	invoices.update
PATCH	/invoices/{invoice}	Update invoice	invoices.update
DELETE	/invoices/{invoice}	Delete invoice	invoices.delete
POST	/bills/{bill}/submit	Submit – bill	bills.create
POST	/bills/{bill}/approve	Approve – bill	bills.approve
POST	/bills/{bill}/void	Void – bill	bills.approve
GET	/bills	List bills	bills.view
POST	/bills	Create bill	bills.create
GET	/bills/{bill}	Get bill	bills.view
PUT	/bills/{bill}	Update bill	bills.create
PATCH	/bills/{bill}	Update bill	bills.create
DELETE	/bills/{bill}	Delete bill	bills.create
POST	/payments/{payment}/void	Void – payment	payments.create
GET	/payments	List payments	payments.view
POST	/payments	Create payment	payments.create
GET	/payments/{payment}	Get payment	payments.view
POST	/expense-claims/{expenseClaim}/submit	Submit – expense claim	expenses.submit
POST	/expense-claims/{expenseClaim}/approve	Approve – expense claim	expenses.approve
POST	/expense-claims/{expenseClaim}/reject	Reject – expense claim	expenses.approve
GET	/expense-claims/{expenseClaim}/lines/{line}/receipt	Get receipt	expenses.submit expenses.view expenses.approve
POST	/expense-claims/{expenseClaim}/lines/{line}/receipt	Create receipt	expenses.submit

Method	Path	Summary	Permission
GET	/expense-claims	List expense claims	expenses.view expenses.approve expenses.submit
POST	/expense-claims	Create expense claim	expenses.submit
GET	/expense-claims/{expenseClaim}	Get expense claim	expenses.submit expenses.view expenses.approve
PUT	/expense-claims/{expenseClaim}	Update expense claim	expenses.submit
PATCH	/expense-claims/{expenseClaim}	Update expense claim	expenses.submit
DELETE	/expense-claims/{expenseClaim}	Delete expense claim	expenses.submit
GET	/finance/reports/ar-aging	Ar aging – report	reports.financial.view
GET	/finance/reports/ap-aging	Ap aging – report	reports.financial.view
GET	/finance/reports/receivables-summary	Receivables summary – report	reports.financial.view
GET	/finance/customer-statements/{customer}	Get customer statement	—

Endpoints

POST /api/v1/**invoices/{invoice}/submit**

Submit – invoice `invoicesSubmit`

Invoice ko approval ke liye submit karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `invoices.create` / `invoices.update` (submit on Invoice)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
invoice	path	integer	yes	ID of the Invoice. · min 1

RESPONSES

200 — `data` : Invoice

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null … aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/invoices/{invoice}/approve

Approve – invoice `invoicesApprove`

Invoice ko approve karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `invoices.approve` · Policy: `invoices.approve` (approve on Invoice)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`invoice`	path	integer	**yes**	ID of the Invoice. · min 1

RESPONSES

200 — `data` : Invoice

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null … aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/invoices/{invoice}/void

Void – invoice `invoicesVoid`

Invoice ko void (radd) karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `invoices.approve` · Policy: `invoices.approve` (void on Invoice)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`invoice`	path	integer	**yes**	ID of the Invoice. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`reason`	string	**yes**	minLength 3 · maxLength 500

RESPONSES

200 — `data` : Invoice

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null … aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/invoices/{invoice}/pdf

Pdf – invoice `invoicesPdf`

Invoice ki PDF download karta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `invoices.view` (view on Invoice)
Throttle	`api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`invoice`	path	integer	**yes**	ID of the Invoice. · min 1

RESPONSES

200 — File (`application/pdf`). File download (`Content-Disposition: attachment`).

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/invoices

List invoices `invoicesIndex`

Invoices ki list deta hai — results paginated hote hain (`page` , `per_page`).

Filters: filter[status] (overdue = derived), filter[customer_id], filter[branch_id], overdue=true, from/to on invoice_date, search on number.
`search` matches (case-insensitive, substring): `number` .

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `invoices.view` (viewAny on Invoice)
Throttle	`api`
List params	`page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`overdue`	query	boolean	no	
`filter[status]`	query	enum InvoiceStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `pending_approval`, `approved`, `partially_paid`, `paid`, `overdue`, `void`
`filter[customer_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[sales_order_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[currency]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `invoice_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `invoice_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-invoice_date`). The primary key is always appended as a tie-breaker. · values: `invoice_date`, `due_date`, `number`, `total`, `balance_due`, `status`, `created_at` (prefix `-` = descending) · default `-invoice_date`

RESPONSES

200 — `data` : array of Invoice + `meta.pagination`

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null ... aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/**invoices**

Create invoice `invoicesStore`

Naya invoice banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `invoices.create` (create on Invoice)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`customer_id`	integer	**yes**	Validated by `TenantReferenceExists`.
`due_date`	string(date) | null	no	`after_or_equal:invoice_date`.
`invoice_date`	string(date)	**yes**	
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].account_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`lines[].description`	string	no	maxLength 255
`lines[].discount_percent`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].tax_rate_id`	integer | null	no	Validated by `TenantExists`.
`lines[].unit_price`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`notes`	string | null	no	maxLength 5000
`sales_order_id`	integer | null	no	Validated by `TenantReferenceExists`.
`terms`	string | null	no	maxLength 5000

EXAMPLE REQUEST

```
{
  "branch_id": 1,
  "currency": "PKR",
  "customer_id": 1,
  "due_date": "2026-11-14",
  "invoice_date": "2026-10-15",
  "lines": [
    {
      "account_id": 1,
      "description": "Sample text",
      "discount_percent": "10.0000",
      "product_id": 1,
      "quantity": "2.0000",
      "tax_rate_id": 1,
      "unit_price": "1250.0000"
    }
  ],
  "notes": "Sample text",
  "sales_order_id": 1,
  "terms": "Sample text"
}
```

RESPONSES

201 — `data` : Invoice

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null … aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/invoices/{invoice}`

Get invoice `invoicesShow`

Ek invoice ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `invoices.view` (view on Invoice)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`invoice`	path	integer	**yes**	ID of the Invoice. · min 1

RESPONSES

200 — `data` : Invoice

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null … aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/invoices/{invoice}

Update invoice invoicesUpdate

Maujooda invoice ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `invoices.update` (update on Invoice)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`invoice`	path	integer	**yes**	ID of the Invoice. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`customer_id`	integer	no	Validated by `TenantReferenceExists`.
`due_date`	string(date) | null	no	`after_or_equal:invoice_date`.
`invoice_date`	string(date)	no	
`lines`	object[]	no	minItems 1 · maxItems 200
`lines[].account_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`lines[].description`	string	no	maxLength 255
`lines[].discount_percent`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].tax_rate_id`	integer | null	no	Validated by `TenantExists`.
`lines[].unit_price`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`notes`	string | null	no	maxLength 5000
`sales_order_id`	integer | null	no	Validated by `TenantReferenceExists`.
`terms`	string | null	no	maxLength 5000

RESPONSES

200 — `data` : Invoice

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object | null `sales_order_id` integer | null `invoice_date` string(date) `due_date` string(date) `currency` string `status` enum InvoiceStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `terms` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `creator` object | null `approved_by` integer | null … aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/invoices/{invoice}

Update invoice invoicesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /invoices/{invoice} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission invoices.update

DELETE /api/v1/invoices/{invoice}

Delete invoice invoicesDestroy

Invoice delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: invoices.delete (delete on Invoice)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
invoice	path	integer	**yes**	ID of the Invoice. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/bills/{bill}/submit

Submit – bill billsSubmit

Bill ko approval ke liye submit karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: bills.create (submit on Bill)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
bill	path	integer	**yes**	ID of the Bill. · min 1

RESPONSES

200 — data : Bill

id integer · company_id integer · number string · supplier_id integer · supplier object | null · purchase_order_id integer | null · supplier_reference string · bill_date string(date) · due_date string(date) · currency string · status enum BillStatus · is_overdue boolean · subtotal Money (string) · discount_total Money (string) · tax_total Money (string) · total Money (string) · amount_paid Money (string) · balance_due Money (string) · notes string | null · branch_id integer | null · branch object | null · journal_entry_id integer | null · created_by integer | null · approved_by integer | null · approver object | null · ...aur 8 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/bills/{bill}/approve

Approve – bill billsApprove

Bill ko approve karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `bills.approve` · Policy: `bills.approve` (approve on Bill)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`bill`	path	integer	**yes**	ID of the Bill. · min 1

RESPONSES

200 — `data` : Bill

`id` integer `company_id` integer `number` string `supplier_id` integer `supplier` object | null `purchase_order_id` integer | null `supplier_reference` string `bill_date` string(date) `due_date` string(date) `currency` string `status` enum BillStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `approved_by` integer | null `approver` object | null …aur 8 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/bills/{bill}/void

Void – bill billsVoid

Bill ko void (radd) karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `bills.approve` · Policy: `bills.approve` (void on Bill)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`bill`	path	integer	**yes**	ID of the Bill. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`reason`	string	**yes**	minLength 3 · maxLength 500

RESPONSES

200 — `data` : Bill

`id` integer `company_id` integer `number` string `supplier_id` integer `supplier` object | null `purchase_order_id` integer | null `supplier_reference` string `bill_date` string(date) `due_date` string(date) `currency` string `status` enum BillStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `approved_by` integer | null `approver` object | null …aur 8 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/bills

List bills billsIndex

Bills ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): number , supplier_reference .

Auth Session cookie · X-Company-Id **required**

Permission Policy: bills.view (viewAny on Bill)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
overdue	query	boolean	no	
filter[status]	query	enum BillStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: draft, pending_approval, approved, partially_paid, paid, overdue, void
filter[supplier_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[branch_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[purchase_order_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[currency]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on bill_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on bill_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-bill_date). The primary key is always appended as a tie-breaker. · values: bill_date, due_date, number, total, balance_due, status, created_at (prefix - = descending) · default -bill_date

RESPONSES

200 — data : array of Bill + meta.pagination

id integer company_id integer number string supplier_id integer supplier object | null purchase_order_id integer | null supplier_reference string bill_date string(date) due_date string(date) currency string status enum BillStatus is_overdue boolean subtotal Money (string) discount_total Money (string) tax_total Money (string) total Money (string) amount_paid Money (string) balance_due Money (string) notes string | null branch_id integer | null branch object | null journal_entry_id integer | null created_by integer | null approved_by integer | null approver object | null …aur 8 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/bills

Create bill billsStore

Naya bill banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: bills.create (create on Bill)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`bill_date`	string(date)	**yes**	
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`due_date`	string(date) | null	no	`after_or_equal:bill_date`.
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].account_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`lines[].description`	string	no	maxLength 255
`lines[].discount_percent`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].tax_rate_id`	integer | null	no	Validated by `TenantExists`.
`lines[].unit_price`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`notes`	string | null	no	maxLength 5000
`purchase_order_id`	integer | null	no	Validated by `TenantReferenceExists`.
`supplier_id`	integer	**yes**	Validated by `TenantReferenceExists`.
`supplier_reference`	string	**yes**	maxLength 60 · Must be unique within `bills` (per company).

EXAMPLE REQUEST

```
{
  "bill_date": "2026-10-15",
  "branch_id": 1,
  "currency": "PKR",
  "due_date": "2026-11-14",
  "lines": [
    {
      "account_id": 1,
      "description": "Sample text",
      "discount_percent": "10.0000",
      "product_id": 1,
      "quantity": "2.0000",
      "tax_rate_id": 1,
      "unit_price": "1250.0000"
    }
  ],
  "notes": "Sample text",
  "purchase_order_id": 1,
  "supplier_id": 1,
  "supplier_reference": "string"
}
```

RESPONSES

201 — `data` : Bill

`id` integer `company_id` integer `number` string `supplier_id` integer `supplier` object | null `purchase_order_id` integer | null `supplier_reference` string `bill_date` string(date) `due_date` string(date) `currency` string `status` enum BillStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `approved_by` integer | null `approver` object | null …aur 8 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/bills/{bill}`

Get bill `billsShow`

Ek bill ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `bills.view` (view on Bill)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`bill`	path	integer	**yes**	ID of the Bill. · min 1

RESPONSES

200 — `data` : Bill

`id` integer `company_id` integer `number` string `supplier_id` integer `supplier` object | null `purchase_order_id` integer | null `supplier_reference` string `bill_date` string(date) `due_date` string(date) `currency` string `status` enum BillStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `approved_by` integer | null `approver` object | null …aur 8 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/bills/{bill}

Update bill billsUpdate

Maujooda bill ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `bills.create` (update on Bill)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`bill`	path	integer	yes	ID of the Bill. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`bill_date`	string(date)	no	
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`due_date`	string(date) | null	no	`after_or_equal:bill_date`.
`lines`	object[]	no	minItems 1 · maxItems 200
`lines[].account_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`lines[].description`	string	no	maxLength 255
`lines[].discount_percent`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].tax_rate_id`	integer | null	no	Validated by `TenantExists`.
`lines[].unit_price`	string | number	no	min 0 · pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`notes`	string | null	no	maxLength 5000
`purchase_order_id`	integer | null	no	Validated by `TenantReferenceExists`.
`supplier_id`	integer	no	Validated by `TenantReferenceExists`.
`supplier_reference`	string	no	maxLength 60 · Must be unique within `bills` (per company).

RESPONSES

200 — `data` : Bill

`id` integer `company_id` integer `number` string `supplier_id` integer `supplier` object | null `purchase_order_id` integer | null `supplier_reference` string `bill_date` string(date) `due_date` string(date) `currency` string `status` enum BillStatus `is_overdue` boolean `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `branch` object | null `journal_entry_id` integer | null `created_by` integer | null `approved_by` integer | null `approver` object | null …aur 8 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/bills/{bill}

Update bill billsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /bills/{bill}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `bills.create`

DELETE /api/v1/bills/{bill}

Delete bill billsDestroy

Bill delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `bills.create` (delete on Bill)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`bill`	path	integer	**yes**	ID of the Bill. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/payments/{payment}/void

Void – payment paymentsVoid

Payment ko void (radd) karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `payments.create` · Policy: `payments.create` (void on Payment)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`payment`	path	integer	**yes**	ID of the Payment. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`reason`	string	**yes**	minLength 3 · maxLength 500

RESPONSES

200 — `data` : Payment

`id` integer `company_id` integer `number` string `type` enum PaymentType `partner_type` enum PaymentPartnerType `partner_id` integer `partner` object | null `payment_date` string(date) `method` enum PaymentMethod `bank_account_id` integer `bank_account` object | null `amount` Money (string) `currency` string `reference` string | null `notes` string | null `status` enum PaymentStatus `branch_id` integer | null `journal_entry_id` integer | null `created_by` integer | null `voided_at` string(date-time) | null `void_reason` string | null `allocations` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/payments`

List payments `paymentsIndex`

Payments ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `reference` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `payments.view` (viewAny on Payment)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[type]`	query	enum PaymentType	no	Exact-match filter (comma-separated = koi bhi value). · values: `receipt`, `payment`
`filter[partner_type]`	query	enum PaymentPartnerType	no	Exact-match filter (comma-separated = koi bhi value). · values: `customer`, `supplier`, `employee`
`filter[partner_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[method]`	query	enum PaymentMethod	no	Exact-match filter (comma-separated = koi bhi value). · values: `cash`, `bank_transfer`, `cheque`, `card`, `other`
`filter[status]`	query	enum PaymentStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `posted`, `void`
`filter[bank_account_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `payment_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `payment_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-payment_date`). The primary key is always appended as a tie-breaker. · values: `payment_date`, `-payment_date`, `number`, `-number`, `amount`, `-amount`, `created_at`, `-created_at` · default `-payment_date`

RESPONSES

200 — `data` : array of Payment + `meta.pagination`

`id` integer `company_id` integer `number` string `type` enum PaymentType `partner_type` enum PaymentPartnerType `partner_id` integer `partner` object | null `payment_date` string(date) `method` enum PaymentMethod `bank_account_id` integer `bank_account` object | null `amount` Money (string) `currency` string `reference` string | null `notes` string | null `status` enum PaymentStatus `branch_id` integer | null `journal_entry_id` integer | null `created_by` integer | null `voided_at` string(date-time) | null `void_reason` string | null `allocations` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/payments`

Create payment `paymentsStore`

Naya payment banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `payments.create` (create on Payment)
Throttle	`api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`allocations`	object[]	**yes**	minItems 1 · maxItems 100
`allocations[].amount`	string | number	no	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`allocations[].id`	integer	no	Values must be distinct.
`allocations[].type`	string	no	values: `invoice`, `bill`, `expense_claim`
`amount`	string | number	**yes**	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`bank_account_id`	integer	**yes**	Validated by `TenantExists`.
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`method`	enum PaymentMethod	**yes**	values: `cash`, `bank_transfer`, `cheque`, `card`, `other`
`notes`	string | null	no	maxLength 1000
`partner_id`	integer	**yes**	
`partner_type`	enum PaymentPartnerType	**yes**	values: `customer`, `supplier`, `employee`
`payment_date`	string(date)	**yes**	
`reference`	string | null	no	maxLength 100
`type`	string | null	no	values: `receipt`, `payment`,

EXAMPLE REQUEST

```
{
  "allocations": [{"amount":"1250.0000","id":1,"type":"invoice"}],
  "amount": "1250.0000",
  "bank_account_id": 1,
  "method": "cash",
  "partner_id": 1,
  "partner_type": "customer",
  "payment_date": "2026-10-15",
  "branch_id": 1
}
```

RESPONSES

201 — `data` : Payment

`id` integer · `company_id` integer · `number` string · `type` enum PaymentType · `partner_type` enum PaymentPartnerType · `partner_id` integer · `partner` object | null · `payment_date` string(date) · `method` enum PaymentMethod · `bank_account_id` integer · `bank_account` object | null · `amount` Money (string) · `currency` string · `reference` string | null · `notes` string | null · `status` enum PaymentStatus · `branch_id` integer | null · `journal_entry_id` integer | null · `created_by` integer | null · `voided_at` string(date-time) | null · `void_reason` string | null · `allocations` object[] · `created_at` string(date-time) | null · `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/payments/{payment}

Get payment paymentsShow

Ek payment ki poori tafseel deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: payments.view (view on Payment)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
payment	path	integer	yes	ID of the Payment. · min 1

RESPONSES

200 — data : Payment

id integer company_id integer number string type enum PaymentType partner_type enum PaymentPartnerType partner_id integer partner object | null payment_date string(date) method enum PaymentMethod bank_account_id integer bank_account object | null amount Money (string) currency string reference string | null notes string | null status enum PaymentStatus branch_id integer | null journal_entry_id integer | null created_by integer | null voided_at string(date-time) | null void_reason string | null allocations object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/expense-claims/{expenseClaim}/submit

Submit – expense claim expenseClaimsSubmit

Expense claim ko approval ke liye submit karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: expenses.submit (submit on ExpenseClaim)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
expenseClaim	path	integer	yes	ID of the Expense Claim. · min 1

RESPONSES

200 — data : ExpenseClaim

id integer company_id integer number string employee_id integer | null user_id integer user object | null claim_date string(date) currency string status enum ExpenseClaimStatus subtotal Money (string) tax_total Money (string) total Money (string) amount_paid Money (string) balance_due Money (string) notes string | null branch_id integer | null submitted_at string(date-time) | null approver_id integer | null approver object | null approved_at string(date-time) | null rejection_reason string | null journal_entry_id integer | null lines object[] lines_count integer created_at string(date-time) | null ...aur 1 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/expense-claims/{expenseClaim}/approve

Approve – expense claim `expenseClaimsApprove`

Expense claim ko approve karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `expenses.approve` · Policy: `expenses.approve` (approve on ExpenseClaim)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`expenseClaim`	path	integer	yes	ID of the Expense Claim. · min 1

RESPONSES

200 — `data` : ExpenseClaim

`id` integer `company_id` integer `number` string `employee_id` integer | null `user_id` integer `user` object | null `claim_date` string(date) `currency` string `status` enum ExpenseClaimStatus `subtotal` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `journal_entry_id` integer | null `lines` object[] `lines_count` integer `created_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/expense-claims/{expenseClaim}/reject

Reject – expense claim `expenseClaimsReject`

Expense claim ko reject karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `expenses.approve` · Policy: `expenses.approve` (reject on ExpenseClaim)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`expenseClaim`	path	integer	yes	ID of the Expense Claim. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`reason`	string	yes	minLength 3 · maxLength 500

RESPONSES

200 — `data` : ExpenseClaim

`id` integer `company_id` integer `number` string `employee_id` integer | null `user_id` integer `user` object | null `claim_date` string(date) `currency` string `status` enum ExpenseClaimStatus `subtotal` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `journal_entry_id` integer | null `lines` object[] `lines_count` integer `created_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/expense-claims/{expenseClaim}/lines/{line}/receipt

Get receipt `expenseClaimsLinesReceiptShow`

Expense claim line ki receipt file download karta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `expenses.submit` / `expenses.view` / `expenses.approve` (view on ExpenseClaim)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`expenseClaim`	path	integer	**yes**	ID of the Expense Claim. · min 1
`line`	path	integer	**yes**	ID of the Expense Claim Line. · min 1

RESPONSES

200 — File (`application/octet-stream`). File download (`Content-Disposition: attachment`). The actual `Content-Type` is the stored file's MIME type.

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/expense-claims/{expenseClaim}/lines/{line}/receipt

Create receipt `expenseClaimsLinesReceiptStore`

Expense claim line ke liye receipt file upload karta hai (multipart).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `expenses.submit` (update on ExpenseClaim)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`expenseClaim`	path	integer	**yes**	ID of the Expense Claim. · min 1
`line`	path	integer	**yes**	ID of the Expense Claim Line. · min 1

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`receipt`	string(binary)	**yes**	Allowed types: pdf, jpg, jpeg, png, webp. Max size 5120 KB.

RESPONSES

200 — `data` : ExpenseClaim

`id` integer `company_id` integer `number` string `employee_id` integer | null `user_id` integer `user` object | null `claim_date` string(date) `currency` string `status` enum ExpenseClaimStatus `subtotal` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `journal_entry_id` integer | null `lines` object[] `lines_count` integer `created_at` string(date-time) | null …aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/expense-claims

List expense claims expenseClaimsIndex

Expense claims ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): number , notes .

Auth Session cookie · X-Company-Id required

Permission Policy: expenses.view / expenses.approve / expenses.submit (viewAny on ExpenseClaim; viewAll on ExpenseClaim)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum ExpenseClaimStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: draft, submitted, approved, rejected, paid
filter[user_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[employee_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[branch_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on claim_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on claim_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-claim_date). The primary key is always appended as a tie-breaker. · values: claim_date, -claim_date, number, -number, total, -total, status, -status, created_at, -created_at · default - claim_date

RESPONSES

200 — data : array of ExpenseClaim + meta.pagination

id integer company_id integer number string employee_id integer | null user_id integer user object | null claim_date string(date) currency string status enum ExpenseClaimStatus subtotal Money (string) tax_total Money (string) total Money (string) amount_paid Money (string) balance_due Money (string) notes string | null branch_id integer | null submitted_at string(date-time) | null approver_id integer | null approver object | null approved_at string(date-time) | null rejection_reason string | null journal_entry_id integer | null lines object[] lines_count integer created_at string(date-time) | null ...aur 1 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/expense-claims

Create expense claim expenseClaimsStore

Naya expense claim banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id required

Permission Policy: expenses.submit (create on ExpenseClaim)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`claim_date`	string(date)	**yes**	
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`employee_id`	integer | null	no	Validated by `TenantReferenceExists`.
`lines`	object[]	**yes**	minItems 1 · maxItems 100
`lines[].account_id`	integer	no	Validated by `TenantExists`.
`lines[].amount`	string | number	no	pattern `^\d{1,14}(\.\d{1,4})?$` · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].category`	string	no	maxLength 60
`lines[].description`	string | null	no	maxLength 255
`lines[].expense_date`	string(date)	no	
`lines[].id`	integer | null	no	Values must be distinct.
`lines[].tax_rate_id`	integer | null	no	Validated by `TenantExists`.
`notes`	string | null	no	maxLength 5000

EXAMPLE REQUEST

```
{
  "branch_id": 1,
  "claim_date": "2026-10-15",
  "currency": "PKR",
  "employee_id": 1,
  "lines": [
    {
      "account_id": 1,
      "amount": "1250.0000",
      "category": "string",
      "description": "Sample text",
      "expense_date": "2026-10-15",
      "id": 1,
      "tax_rate_id": 1
    }
  ],
  "notes": "Sample text"
}
```

RESPONSES

201 — `data` : ExpenseClaim

`id` integer `company_id` integer `number` string `employee_id` integer | null `user_id` integer `user` object | null `claim_date` string(date) `currency` string `status` enum ExpenseClaimStatus `subtotal` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `journal_entry_id` integer | null `lines` object[] `lines_count` integer `created_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/expense-claims/{expenseClaim}

Get expense claim expenseClaimsShow

Ek expense claim ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `expenses.submit` / `expenses.view` / `expenses.approve` (view on ExpenseClaim)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
expenseClaim	path	integer	yes	ID of the Expense Claim. · min 1

RESPONSES

200 — `data` : ExpenseClaim

`id` integer `company_id` integer `number` string `employee_id` integer | null `user_id` integer `user` object | null `claim_date` string(date) `currency` string `status` enum ExpenseClaimStatus `subtotal` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `journal_entry_id` integer | null `lines` object[] `lines_count` integer `created_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/expense-claims/{expenseClaim}

Update expense claim expenseClaimsUpdate

Maujooda expense claim ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `expenses.submit` (update on ExpenseClaim)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
expenseClaim	path	integer	yes	ID of the Expense Claim. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
branch_id	integer | null	no	Validated by AccessibleBranch.
claim_date	string(date)	no	
currency	string | null	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
employee_id	integer | null	no	Validated by TenantReferenceExists.
lines	object[]	no	minItems 1 · maxItems 100
lines[].account_id	integer	no	Validated by TenantExists.
lines[].amount	string | number	no	pattern ^\d{1,14}(\.\d{1,4})?$ · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].category	string	no	maxLength 60
lines[].description	string | null	no	maxLength 255
lines[].expense_date	string(date)	no	
lines[].id	integer | null	no	Values must be distinct.
lines[].tax_rate_id	integer | null	no	Validated by TenantExists.
notes	string | null	no	maxLength 5000

RESPONSES

200 — `data` : ExpenseClaim

`id` integer `company_id` integer `number` string `employee_id` integer | null `user_id` integer `user` object | null `claim_date` string(date) `currency` string `status` enum ExpenseClaimStatus `subtotal` Money (string) `tax_total` Money (string) `total` Money (string) `amount_paid` Money (string) `balance_due` Money (string) `notes` string | null `branch_id` integer | null `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejection_reason` string | null `journal_entry_id` integer | null `lines` object[] `lines_count` integer `created_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/expense-claims/{expenseClaim}

Update expense claim expenseClaimsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /expense-claims/{expenseClaim} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission expenses.submit

DELETE /api/v1/expense-claims/{expenseClaim}

Delete expense claim expenseClaimsDestroy

Expense claim delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: expenses.submit (delete on ExpenseClaim)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
expenseClaim	path	integer	**yes**	ID of the Expense Claim. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/finance/reports/ar-aging

Ar aging – report financeReportsArAging

Ar aging report ka data JSON mein deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Route: reports.financial.view (finance.reports.view)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
as_of	query	string(date) | null	no	

RESPONSES

200 — data : object shape inferred from code

as_of string(date) rows object[] totals number

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

GET /api/v1/finance/reports/ap-aging

Ap aging – report `financeReportsApAging`

Ap aging report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
as_of	query	string(date) | null	no	

RESPONSES

200 — `data` : object shape inferred from code

`as_of` string(date) `rows` object[] `totals` number

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/finance/reports/receivables-summary

Receivables summary – report `financeReportsReceivablesSummary`

Receivables summary report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.financial.view` (finance.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
as_of	query	string(date) | null	no	

RESPONSES

200 — `data` : object shape inferred from code

`as_of` string(date) `receivables` object `payables` object `expense_claims_payable` object

`average_days_to_pay` Decimal (string) | null `dso_days` Decimal (string) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET `/api/v1/finance/customer-statements/{customer}`

Get customer statement `financeCustomerStatementsShow`

Ek customer statement ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership) (receivables.statements.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	**yes**	min 1
`from`	query	string(date) | null	no	
`to`	query	string(date) | null	no	`after_or_equal:from`.

RESPONSES

200 — `data` : object shape inferred from code

`customer` object `from` string(date) `to` string(date) `opening_balance` Decimal (string) `entries` number[]
`total_debits` Decimal (string) `total_credits` Decimal (string) `closing_balance` Decimal (string)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `422` validation.failed · `429` throttled

MODULE

Sales

Customers (contacts, communications, map), CRM (leads, opportunities, pipeline stages, Kanban board), quotations, sales orders aur deliveries. Quotation ko `convert` kar ke sales order banaya ja sakta hai aur sales order se deliveries banti hain.

Spec: Customers, CRM (leads, opportunities, pipeline), quotations, sales orders, deliveries. — 67 operations.

Method	Path	Summary	Permission
GET	/customers/all	Lightweight {id, name, code, currency, payment_terms_days} list for selectors.	customers.view
GET	/customers/map	Active customers that have coordinates, for the map view.	customers.view
GET	/customers	List customers	customers.view
POST	/customers	Create customer	customers.manage
GET	/customers/{customer}	Get customer	customers.view
PUT	/customers/{customer}	Update customer	customers.manage
PATCH	/customers/{customer}	Update customer	customers.manage
DELETE	/customers/{customer}	Delete customer	customers.manage
GET	/customers/{customer}/summary	Summary – customer	customers.view
POST	/customers/{customer}/contacts	Create contact	customers.manage
PUT	/customers/{customer}/contacts/{contact}	Update contact	customers.manage
DELETE	/customers/{customer}/contacts/{contact}	Delete contact	customers.manage
GET	/customers/{customer}/communications	List communications	customers.view
POST	/customers/{customer}/communications	Create communication	customers.manage
PUT	/customers/{customer}/communications/{communication}	Update communication	customers.manage
DELETE	/customers/{customer}/communications/{communication}	Delete communication	customers.manage
POST	/pipeline-stages/reorder	Persist a new order: { ids: [stageId, ...] } → positions 1..n.	leads.manage
GET	/pipeline-stages	List pipeline stages	leads.view
POST	/pipeline-stages	Create pipeline stage	leads.manage
GET	/pipeline-stages/{pipelineStage}	Get pipeline stage	leads.view
PUT	/pipeline-stages/{pipelineStage}	Update pipeline stage	leads.manage
PATCH	/pipeline-stages/{pipelineStage}	Update pipeline stage	leads.manage
DELETE	/pipeline-stages/{pipelineStage}	Delete pipeline stage	leads.manage
GET	/leads	List leads	leads.view
POST	/leads	Create lead	leads.manage
GET	/leads/{lead}	Get lead	leads.view
PUT	/leads/{lead}	Update lead	leads.manage
PATCH	/leads/{lead}	Update lead	leads.manage

Method	Path	Summary	Permission
DELETE	/leads/{lead}	Delete lead	leads.manage
POST	/leads/{lead}/convert	Convert – lead	leads.manage
POST	/leads/{lead}/assign	Assign – lead	leads.manage
GET	/opportunities/board	Kanban payload: every stage (ordered) with its opportunities and totals.	leads.view
GET	/opportunities	List opportunities	leads.view
POST	/opportunities	Create opportunity	leads.manage
GET	/opportunities/{opportunity}	Get opportunity	leads.view
PUT	/opportunities/{opportunity}	Update opportunity	leads.manage
PATCH	/opportunities/{opportunity}	Update opportunity	leads.manage
DELETE	/opportunities/{opportunity}	Delete opportunity	leads.manage
PATCH	/opportunities/{opportunity}/stage	Move to another stage (won/lost stages close the opportunity).	leads.manage
GET	/sales/pipeline-summary	Pipeline summary – sale	—
GET	/quotations	List quotations	quotations.view
POST	/quotations	Create quotation	quotations.manage
GET	/quotations/{quotation}	Get quotation	quotations.view
PUT	/quotations/{quotation}	Update quotation	quotations.manage
PATCH	/quotations/{quotation}	Update quotation	quotations.manage
DELETE	/quotations/{quotation}	Delete quotation	quotations.manage
POST	/quotations/{quotation}/send	Send – quotation	quotations.manage
POST	/quotations/{quotation}/accept	Accept – quotation	quotations.manage
POST	/quotations/{quotation}/reject	Reject – quotation	quotations.manage
POST	/quotations/{quotation}/convert	Convert – quotation	quotations.manage sales_orders.manage
GET	/sales-orders	List sales orders	sales_orders.view
POST	/sales-orders	Create sales order	sales_orders.manage
GET	/sales-orders/{salesOrder}	Get sales order	sales_orders.view
PUT	/sales-orders/{salesOrder}	Update sales order	sales_orders.manage
PATCH	/sales-orders/{salesOrder}	Update sales order	sales_orders.manage
DELETE	/sales-orders/{salesOrder}	Delete sales order	sales_orders.manage
POST	/sales-orders/{salesOrder}/confirm	Draft → Confirmed; announces the order to Inventory/AR via SalesOrderConfirmed.	sales_orders.manage
POST	/sales-orders/{salesOrder}/approve	Confirmed → Approved (sales_orders.approve).	sales_orders.approve
POST	/sales-orders/{salesOrder}/cancel	Cancel unless anything has already been delivered. Open deliveries are cancelled too.	sales_orders.manage
POST	/sales-orders/{salesOrder}/deliveries	Create delivery (from sales order)	sales_orders.manage
GET	/deliveries	List deliveries	sales_orders.view

Method	Path	Summary	Permission
GET	/deliveries/{delivery}	Get delivery	sales_orders.view
POST	/deliveries/{delivery}/ship	Ship – delivery	sales_orders.manage
POST	/deliveries/{delivery}/deliver	Deliver – delivery	sales_orders.manage
POST	/deliveries/{delivery}/cancel	Cancel – delivery	sales_orders.manage
GET	/sales/reports/performance	performance	reports.view
GET	/sales/reports/pipeline	pipeline	reports.view

Endpoints

GET /api/v1/customers/all

Lightweight `{id, name, code, currency, payment_terms_days}` list for selectors. `customersAll`

Selectors ke liye customers ki halki list deta hai (`id`, `name`, `code`, `currency`, `payment_terms_days`).

Auth: Session cookie · `X-Company-Id` **required**

Permission: Policy: `customers.view` (viewAny on Customer)

Throttle: `api`

RESPONSES

200 — `data`: array of object shape inferred from code

`id` integer `name` string `code` string `currency` string `payment_terms_days` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/customers/map

Active customers that have coordinates, for the map view. `customersMap`

Woh active customers deta hai jin ke coordinates hain (map view ke liye).

Auth: Session cookie · `X-Company-Id` **required**

Permission: Policy: `customers.view` (viewAny on Customer)

Throttle: `api`

RESPONSES

200 — `data`: array of object shape inferred from code

`id` integer `name` string `code` string `latitude` Decimal (string) | null `longitude` Decimal (string) | null `city` string | null `country` string | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/customers

List customers customersIndex

Customers ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , code , email , phone , billing_city .

Auth Session cookie · X-Company-Id required

Permission Policy: customers.view (viewAny on Customer)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[type]	query	enum CustomerType	no	Exact-match filter (comma-separated = koi bhi value). · values: individual, company
filter[sales_rep_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[source]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[billing_country]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[currency]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, created_at, -created_at, payment_terms_days, -payment_terms_days, credit_limit, -credit_limit · default name

RESPONSES

200 — data : array of Customer + meta.pagination

id integer company_id integer code string name string type enum CustomerType | null email string | null phone string | null website string | null tax_number string | null currency string payment_terms_days integer credit_limit Money (string) | null billing_address object shipping_address object latitude Decimal (string) | null longitude Decimal (string) | null sales_rep_id integer | null sales_rep UserRef | null source string | null tags any[] notes string | null is_active boolean contacts CustomerContact[] contacts_count integer created_at string(date-time) | null ...aur 1 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/customers

Create customer customersStore

Naya customer banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id required

Permission Policy: customers.manage (create on Customer)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
billing_address_line1	string | null	no	maxLength 200

Field	Type	Req.	Constraints / notes
billing_address_line2	string | null	no	maxLength 200
billing_city	string | null	no	maxLength 100
billing_country	string | null	no	minLength 2 · maxLength 2
billing_postal_code	string | null	no	maxLength 20
billing_state	string | null	no	maxLength 100
code	string | null	no	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within customers (per company).
credit_limit	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
email	string(email) | null	no	maxLength 150
is_active	boolean	no	
latitude	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
longitude	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	**yes**	maxLength 150
notes	string | null	no	maxLength 5000
payment_terms_days	integer	no	min 0 · max 365
phone	string | null	no	maxLength 40
sales_rep_id	integer | null	no	Validated by CompanyMember.
shipping_address_line1	string | null	no	maxLength 200
shipping_address_line2	string | null	no	maxLength 200
shipping_city	string | null	no	maxLength 100
shipping_country	string | null	no	minLength 2 · maxLength 2
shipping_postal_code	string | null	no	maxLength 20
shipping_state	string | null	no	maxLength 100
source	string | null	no	maxLength 40
tags	string[] | null	no	maxItems 20
tax_number	string | null	no	maxLength 60
type	enum CustomerType	no	values: individual, company
website	string | null	no	maxLength 200

EXAMPLE REQUEST

```
{
  "name": "Sample name",
  "billing_address_line1": "Shahrah-e-Faisal, Karachi",
  "billing_address_line2": "Shahrah-e-Faisal, Karachi",
  "billing_city": "Karachi",
  "billing_country": "PK",
  "billing_postal_code": "CODE-001",
  "billing_state": "string",
  "code": "CODE-001"
}
```

RESPONSES

201 — `data` : Customer

`id` integer `company_id` integer `code` string `name` string `type` enum CustomerType | null `email` string | null `phone` string | null `website` string | null `tax_number` string | null `currency` string `payment_terms_days` integer `credit_limit` Money (string) | null `billing_address` object `shipping_address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `sales_rep_id` integer | null `sales_rep` UserRef | null `source` string | null `tags` any[] `notes` string | null `is_active` boolean `contacts` CustomerContact[] `contacts_count` integer `created_at` string(date-time) | null …aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/customers/{customer}`

Get customer `customersShow`

Ek customer ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `customers.view` (view on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	**yes**	ID of the Customer. · min 1

RESPONSES

200 — `data` : Customer

`id` integer `company_id` integer `code` string `name` string `type` enum CustomerType | null `email` string | null `phone` string | null `website` string | null `tax_number` string | null `currency` string `payment_terms_days` integer `credit_limit` Money (string) | null `billing_address` object `shipping_address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `sales_rep_id` integer | null `sales_rep` UserRef | null `source` string | null `tags` any[] `notes` string | null `is_active` boolean `contacts` CustomerContact[] `contacts_count` integer `created_at` string(date-time) | null …aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

---

`PUT` `/api/v1/customers/{customer}`

Update customer `customersUpdate`

Maujooda customer ko update karta hai.

> Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	**yes**	ID of the Customer. · min 1

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`billing_address_line1`	string | null	no	maxLength 200
`billing_address_line2`	string | null	no	maxLength 200
`billing_city`	string | null	no	maxLength 100
`billing_country`	string | null	no	minLength 2 · maxLength 2
`billing_postal_code`	string | null	no	maxLength 20
`billing_state`	string | null	no	maxLength 100

Field	Type	Req.	Constraints / notes
`code`	string | null	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `customers` (per company).
`credit_limit`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`email`	string(email) | null	no	maxLength 150
`is_active`	boolean	no	
`latitude`	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`longitude`	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`name`	string	no	maxLength 150
`notes`	string | null	no	maxLength 5000
`payment_terms_days`	integer	no	min 0 · max 365
`phone`	string | null	no	maxLength 40
`sales_rep_id`	integer | null	no	Validated by `CompanyMember`.
`shipping_address_line1`	string | null	no	maxLength 200
`shipping_address_line2`	string | null	no	maxLength 200
`shipping_city`	string | null	no	maxLength 100
`shipping_country`	string | null	no	minLength 2 · maxLength 2
`shipping_postal_code`	string | null	no	maxLength 20
`shipping_state`	string | null	no	maxLength 100
`source`	string | null	no	maxLength 40
`tags`	string[] | null	no	maxItems 20
`tax_number`	string | null	no	maxLength 60
`type`	enum CustomerType	no	values: `individual`, `company`
`website`	string | null	no	maxLength 200

RESPONSES

200 — `data` : Customer

`id` integer `company_id` integer `code` string `name` string `type` enum CustomerType | null `email` string | null `phone` string | null `website` string | null `tax_number` string | null `currency` string `payment_terms_days` integer `credit_limit` Money (string) | null `billing_address` object `shipping_address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `sales_rep_id` integer | null `sales_rep` UserRef | null `source` string | null `tags` any[] `notes` string | null `is_active` boolean `contacts` CustomerContact[] `contacts_count` integer `created_at` string(date-time) | null …aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/customers/{customer}

Update customer customersUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /customers/{customer}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `customers.manage`

DELETE /api/v1/customers/{customer}

Delete customer customersDestroy

Customer delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (delete on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
customer	path	integer	yes	ID of the Customer. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/customers/{customer}/summary

Summary – customer customersSummary

Ek customer ka summary (aggregate data) deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `customers.view` (view on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
customer	path	integer	yes	ID of the Customer. · min 1

RESPONSES

200 — `data` : object shape inferred from code

`customer_id` integer `quotations` object `sales_orders` object `opportunities` object `last_order_date` number `outstanding_balance` Decimal (string) `overdue_balance` Decimal (string) `open_invoices_count` integer `overdue_invoices_count` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/customers/{customer}/contacts

Create contact customersContactsStore

Naya contact banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
customer	path	integer	yes	ID of the Customer. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
email	string(email) | null	no	maxLength 150
is_primary	boolean	no	
name	string	yes	maxLength 150
phone	string | null	no	maxLength 40
title	string | null	no	maxLength 100

EXAMPLE REQUEST

```
{
  "email": "ali.raza@example.com",
  "is_primary": true,
  "name": "Sample name",
  "phone": "+92 300 1234567",
  "title": "Sample title"
}
```

RESPONSES

201 — `data` : CustomerContact

`id` integer `customer_id` integer `name` string `title` string | null `email` string | null `phone` string | null `is_primary` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PUT /api/v1/customers/{customer}/contacts/{contact}

Update contact customersContactsUpdate

Maujooda contact ko update karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
customer	path	integer	yes	ID of the Customer. · min 1
contact	path	integer	yes	ID of the Customer Contact. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
email	string(email) | null	no	maxLength 150
is_primary	boolean	no	
name	string	no	maxLength 150
phone	string | null	no	maxLength 40
title	string | null	no	maxLength 100

RESPONSES

200 — `data` : CustomerContact

`id` integer `customer_id` integer `name` string `title` string | null `email` string | null `phone` string | null `is_primary` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

DELETE /api/v1/customers/{customer}/contacts/{contact}

Delete contact customersContactsDestroy

Contact delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
customer	path	integer	yes	ID of the Customer. · min 1
contact	path	integer	yes	ID of the Customer Contact. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

`GET` `/api/v1/customers/{customer}/communications`

List communications `customersCommunicationsIndex`

Communications ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `subject` , `body` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `customers.view` (view on Customer)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	**yes**	ID of the Customer. · min 1
`filter[type]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[user_id]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `happened_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `happened_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-happened_at`). The primary key is always appended as a tie-breaker. · values: `happened_at`, `-happened_at`, `follow_up_at`, `-follow_up_at`, `created_at`, `-created_at` · default `-happened_at`

RESPONSES

200 — `data` : array of CustomerCommunication + `meta.pagination`

`id` integer `customer_id` integer `user_id` integer | null `user` UserRef | null `type` enum CommunicationType | null `subject` string `body` string | null `happened_at` string(date-time) | null `follow_up_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/customers/{customer}/communications

Create communication `customersCommunicationsStore`

Naya communication banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	**yes**	ID of the Customer. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`body`	string | null	no	maxLength 10000
`follow_up_at`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`happened_at`	string(date)	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`subject`	string	**yes**	maxLength 200
`type`	enum CommunicationType	**yes**	values: `call`, `email`, `meeting`, `note`

EXAMPLE REQUEST

```
{
  "body": "Sample text",
  "follow_up_at": "2026-10-15",
  "happened_at": "2026-10-15",
  "subject": "Sample title",
  "type": "call"
}
```

RESPONSES

201 — `data` : CustomerCommunication

`id` integer `customer_id` integer `user_id` integer | null `user` UserRef | null `type` enum CommunicationType | null `subject` string `body` string | null `happened_at` string(date-time) | null `follow_up_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PUT /api/v1/customers/{customer}/communications/{communication}

Update communication customersCommunicationsUpdate

Maujooda communication ko update karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	yes	ID of the Customer. · min 1
`communication`	path	integer	yes	ID of the Customer Communication. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`body`	string | null	no	maxLength 10000
`follow_up_at`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`happened_at`	string(date)	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`subject`	string	no	maxLength 200
`type`	enum CommunicationType	no	values: `call`, `email`, `meeting`, `note`

RESPONSES

200 — `data` : CustomerCommunication

`id` integer `customer_id` integer `user_id` integer | null `user` UserRef | null `type` enum CommunicationType | null `subject` string `body` string | null `happened_at` string(date-time) | null `follow_up_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

DELETE /api/v1/customers/{customer}/communications/{communication}

Delete communication customersCommunicationsDestroy

Communication delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `customers.manage` (update on Customer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`customer`	path	integer	yes	ID of the Customer. · min 1
`communication`	path	integer	yes	ID of the Customer Communication. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

POST /api/v1/pipeline-stages/reorder

Persist a new order: `{ ids: [stageId, ...] }` → positions 1..n. `pipelineStagesReorder`

Pipeline stages ki nayi tarteeb save karta hai: `{ ids: [...] }` → positions 1..n.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (create on PipelineStage)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`ids`	integer[]	**yes**	minItems 1

RESPONSES

200 — `data` : array of PipelineStage

`id` integer `name` string `probability` integer `position` integer `is_won` boolean `is_lost` boolean `color` string | null `opportunities_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/pipeline-stages

List pipeline stages `pipelineStagesIndex`

Pipeline stages ki list deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leads.view` (viewAny on PipelineStage)

Throttle `api`

RESPONSES

200 — `data` : array of PipelineStage

`id` integer `name` string `probability` integer `position` integer `is_won` boolean `is_lost` boolean `color` string | null `opportunities_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

`POST` /api/v1/**pipeline-stages**

Create pipeline stage `pipelineStagesStore`

Naya pipeline stage banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (create on PipelineStage)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`color`	string | null	no	maxLength 9 · pattern `^#[0-9A-Fa-f]{6}([0-9A-Fa-f]{2})?$`
`is_lost`	boolean	no	
`is_won`	boolean	no	
`name`	string	**yes**	maxLength 80
`position`	integer	no	min 0
`probability`	integer	no	min 0 · max 100

EXAMPLE REQUEST

```
{
  "color": "#4f46e5",
  "is_lost": true,
  "is_won": true,
  "name": "Sample name",
  "position": 1,
  "probability": 1
}
```

RESPONSES

201 — `data` : PipelineStage

`id` integer `name` string `probability` integer `position` integer `is_won` boolean `is_lost` boolean `color` string | null
`opportunities_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` /api/v1/**pipeline-stages/{pipelineStage}**

Get pipeline stage `pipelineStagesShow`

Ek pipeline stage ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leads.view` (view on PipelineStage)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`pipelineStage`	path	integer	**yes**	ID of the Pipeline Stage. · min 1

RESPONSES

200 — `data` : PipelineStage

`id` integer `name` string `probability` integer `position` integer `is_won` boolean `is_lost` boolean `color` string | null
`opportunities_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/pipeline-stages/{pipelineStage}

Update pipeline stage `pipelineStagesUpdate`

Maujooda pipeline stage ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (update on PipelineStage)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`pipelineStage`	path	integer	**yes**	ID of the Pipeline Stage. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`color`	string | null	no	maxLength 9 · pattern `^#[0-9A-Fa-f]{6}([0-9A-Fa-f]{2})?$`
`is_lost`	boolean	no	
`is_won`	boolean	no	
`name`	string	no	maxLength 80
`position`	integer	no	min 0
`probability`	integer	no	min 0 · max 100

RESPONSES

200 — `data`: PipelineStage

`id` integer `name` string `probability` integer `position` integer `is_won` boolean `is_lost` boolean `color` string | null `opportunities_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/pipeline-stages/{pipelineStage}

Update pipeline stage `pipelineStagesUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /pipeline-stages/{pipelineStage}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `leads.manage`

DELETE /api/v1/pipeline-stages/{pipelineStage}

Delete pipeline stage `pipelineStagesDestroy`

Pipeline stage delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (delete on PipelineStage)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`pipelineStage`	path	integer	**yes**	ID of the Pipeline Stage. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/leads`

List leads `leadsIndex`

Leads ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `name` , `company_name` , `email` , `phone` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leads.view` (viewAny on Lead)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum LeadStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `new`, `contacted`, `qualified`, `unqualified`, `converted`
`filter[source]`	query	enum LeadSource	no	Exact-match filter (comma-separated = koi bhi value). · values: `website`, `referral`, `campaign`, `cold_call`, `event`, `other`
`filter[assigned_to]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `created_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `created_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-id`). The primary key is always appended as a tie-breaker. · values: `name`, `-name`, `company_name`, `-company_name`, `status`, `-status`, `estimated_value`, `-estimated_value`, `created_at`, `-created_at` · default `-id`

RESPONSES

200 — `data` : array of Lead + `meta.pagination`

`id` integer `company_id` integer `name` string `company_name` string | null `email` string | null `phone` string | null `source` enum LeadSource | null `status` enum LeadStatus | null `estimated_value` Money (string) | null `assigned_to` integer | null `assignee` UserRef | null `notes` string | null `converted_customer_id` integer | null `converted_customer` object | null `converted_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/leads

Create lead `leadsStore`

Naya lead banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (create on Lead)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`assigned_to`	integer | null	no	Validated by `CompanyMember`.
`company_name`	string | null	no	maxLength 150
`email`	string(email) | null	no	maxLength 150
`estimated_value`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`name`	string	**yes**	maxLength 150
`notes`	string | null	no	maxLength 5000
`phone`	string | null	no	maxLength 40
`source`	enum LeadSource	no	values: `website`, `referral`, `campaign`, `cold_call`, `event`, `other`
`status`	enum LeadStatus	no	values: `new`, `contacted`, `qualified`, `unqualified`, `converted`

EXAMPLE REQUEST

```
{
  "assigned_to": 1,
  "company_name": "Sample name",
  "email": "ali.raza@example.com",
  "estimated_value": "1250.0000",
  "name": "Sample name",
  "notes": "Sample text",
  "phone": "+92 300 1234567",
  "source": "website",
  "status": "new"
}
```

RESPONSES

201 — `data` : Lead

`id` integer `company_id` integer `name` string `company_name` string | null `email` string | null `phone` string | null `source` enum LeadSource | null `status` enum LeadStatus | null `estimated_value` Money (string) | null `assigned_to` integer | null `assignee` UserRef | null `notes` string | null `converted_customer_id` integer | null `converted_customer` object | null `converted_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/leads/{lead}`

Get lead `leadsShow`

Ek lead ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leads.view` (view on Lead)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`lead`	path	integer	**yes**	ID of the Lead. · min 1

RESPONSES

200 — `data` : Lead

`id` integer `company_id` integer `name` string `company_name` string | null `email` string | null `phone` string | null `source` enum LeadSource | null `status` enum LeadStatus | null `estimated_value` Money (string) | null `assigned_to` integer | null `assignee` UserRef | null `notes` string | null `converted_customer_id` integer | null `converted_customer` object | null `converted_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/leads/{lead}

Update lead `leadsUpdate`

Maujooda lead ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (update on Lead)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`lead`	path	integer	**yes**	ID of the Lead. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`assigned_to`	integer | null	no	Validated by `CompanyMember`.
`company_name`	string | null	no	maxLength 150
`email`	string(email) | null	no	maxLength 150
`estimated_value`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`name`	string	no	maxLength 150
`notes`	string | null	no	maxLength 5000
`phone`	string | null	no	maxLength 40
`source`	enum LeadSource	no	values: `website`, `referral`, `campaign`, `cold_call`, `event`, `other`
`status`	enum LeadStatus	no	values: `new`, `contacted`, `qualified`, `unqualified`, `converted`

RESPONSES

200 — `data` : Lead

`id` integer `company_id` integer `name` string `company_name` string | null `email` string | null `phone` string | null `source` enum LeadSource | null `status` enum LeadStatus | null `estimated_value` Money (string) | null `assigned_to` integer | null `assignee` UserRef | null `notes` string | null `converted_customer_id` integer | null `converted_customer` object | null `converted_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/leads/{lead}

Update lead leadsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /leads/{lead} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission leads.manage

DELETE /api/v1/leads/{lead}

Delete lead leadsDestroy

Lead delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: leads.manage (delete on Lead)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
lead	path	integer	**yes**	ID of the Lead. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

POST /api/v1/leads/{lead}/convert

Convert – lead leadsConvert

Lead ko convert karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: leads.manage (update on Lead)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
lead	path	integer	**yes**	ID of the Lead. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
create_opportunity	boolean	no	
stage_id	integer | null	no	Validated by TenantExists.

RESPONSES

200 — data : object shape inferred from code

lead Lead customer Customer customer_created boolean opportunity Opportunity | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

POST /api/v1/leads/{lead}/assign

Assign – lead `leadsAssign`

Lead ko kisi user ko assign karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (update on Lead)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`lead`	path	integer	**yes**	ID of the Lead. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`user_id`	integer	**yes**	Validated by `CompanyMember`.

RESPONSES

200 — `data` : Lead

`id` integer `company_id` integer `name` string `company_name` string | null `email` string | null `phone` string | null `source` enum LeadSource | null `status` enum LeadStatus | null `estimated_value` Money (string) | null `assigned_to` integer | null `assignee` UserRef | null `notes` string | null `converted_customer_id` integer | null `converted_customer` object | null `converted_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/opportunities/board

Kanban payload: every stage (ordered) with its opportunities and totals. `opportunitiesBoard`

Kanban payload deta hai: har stage (tarteeb se) apni opportunities aur totals ke saath.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leads.view` (viewAny on Opportunity)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`owner_id`	query	integer	no	
`status`	query	enum OpportunityStatus	no	values: `open`, `won`, `lost`

RESPONSES

200 — `data` : array of object shape inferred from code

`stage` object `count` integer `total_value` Decimal (string) `items` Opportunity[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/opportunities

List opportunities opportunitiesIndex

Opportunities ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): title .

Auth Session cookie · X-Company-Id **required**

Permission Policy: leads.view (viewAny on Opportunity)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum OpportunityStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: open, won, lost
filter[stage_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[owner_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[customer_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[lead_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on expected_close_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on expected_close_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-id). The primary key is always appended as a tie-breaker. · values: title, -title, value, -value, probability, -probability, expected_close_date, -expected_close_date, status, -status, created_at, -created_at · default -id

RESPONSES

200 — data : array of Opportunity + meta.pagination

id integer company_id integer title string customer_id integer | null customer object | null lead_id integer | null stage_id integer stage object value Money (string) currency string probability integer expected_close_date string(date) | null status enum OpportunityStatus | null lost_reason string | null owner_id integer | null owner UserRef | null closed_at string(date-time) | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/opportunities

Create opportunity opportunitiesStore

Naya opportunity banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (create on Opportunity)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
customer_id	integer | null	no	Validated by TenantExists.
expected_close_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lead_id	integer | null	no	Validated by TenantExists.
lost_reason	string | null	no	maxLength 500
owner_id	integer | null	no	Validated by CompanyMember.
probability	integer | null	no	min 0 · max 100
stage_id	integer	**yes**	Validated by TenantExists.
title	string	**yes**	maxLength 200
value	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.

EXAMPLE REQUEST

```
{
  "currency": "PKR",
  "customer_id": 1,
  "expected_close_date": "2026-10-15",
  "lead_id": 1,
  "lost_reason": "Sample text",
  "owner_id": 1,
  "probability": 1,
  "stage_id": 1,
  "title": "Sample title",
  "value": "1250.0000"
}
```

RESPONSES

201 — `data` : Opportunity

`id` integer `company_id` integer `title` string `customer_id` integer | null `customer` object | null `lead_id` integer | null `stage_id` integer `stage` object `value` Money (string) `currency` string `probability` integer `expected_close_date` string(date) | null `status` enum OpportunityStatus | null `lost_reason` string | null `owner_id` integer | null `owner` UserRef | null `closed_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/opportunities/{opportunity}`

Get opportunity `opportunitiesShow`

Ek opportunity ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `leads.view` (view on Opportunity)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`opportunity`	path	integer	**yes**	ID of the Opportunity. · min 1

RESPONSES

200 — `data` : Opportunity

`id` integer `company_id` integer `title` string `customer_id` integer | null `customer` object | null `lead_id` integer | null `stage_id` integer `stage` object `value` Money (string) `currency` string `probability` integer `expected_close_date` string(date) | null `status` enum OpportunityStatus | null `lost_reason` string | null `owner_id` integer | null `owner` UserRef | null `closed_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/opportunities/{opportunity}

Update opportunity `opportunitiesUpdate`

Maujooda opportunity ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `leads.manage` (update on Opportunity)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`opportunity`	path	integer	**yes**	ID of the Opportunity. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`customer_id`	integer | null	no	Validated by `TenantExists`.
`expected_close_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`lead_id`	integer | null	no	Validated by `TenantExists`.
`lost_reason`	string | null	no	maxLength 500
`owner_id`	integer | null	no	Validated by `CompanyMember`.
`probability`	integer | null	no	min 0 · max 100
`stage_id`	integer	no	Validated by `TenantExists`.
`title`	string	no	maxLength 200
`value`	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.

RESPONSES

200 — `data` : Opportunity

`id` integer `company_id` integer `title` string `customer_id` integer | null `customer` object | null `lead_id` integer | null `stage_id` integer `stage` object `value` Money (string) `currency` string `probability` integer `expected_close_date` string(date) | null `status` enum OpportunityStatus | null `lost_reason` string | null `owner_id` integer | null `owner` UserRef | null `closed_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/opportunities/{opportunity}

Update opportunity opportunitiesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /opportunities/{opportunity} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission leads.manage

DELETE /api/v1/opportunities/{opportunity}

Delete opportunity opportunitiesDestroy

Opportunity delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: leads.manage (delete on Opportunity)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
opportunity	path	integer	**yes**	ID of the Opportunity. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

PATCH /api/v1/opportunities/{opportunity}/stage

Move to another stage (won/lost stages close the opportunity). opportunitiesStage

Opportunity ko doosri stage mein move karta hai; won/lost stages opportunity ko close kar deti hain.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: leads.manage (update on Opportunity)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
opportunity	path	integer	**yes**	ID of the Opportunity. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
lost_reason	string | null	no	maxLength 500
stage_id	integer	**yes**	Validated by TenantExists.

RESPONSES

200 — data : Opportunity

id integer · company_id integer · title string · customer_id integer | null · customer object | null · lead_id integer | null · stage_id integer · stage object · value Money (string) · currency string · probability integer · expected_close_date string(date) | null · status enum OpportunityStatus | null · lost_reason string | null · owner_id integer | null · owner UserRef | null · closed_at string(date-time) | null · created_at string(date-time) | null · updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

GET `/api/v1/sales/pipeline-summary`

Pipeline summary – sale `salesPipelineSummary`

Sales pipeline ka summary (aggregate) deta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Koi permission slug nahi (sirf authentication/ownership) (sales.pipeline.view)
Throttle	`api`

RESPONSES

200 — `data` : object shape inferred from code

`stages` object[] `open` object `win_rate_90d` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/quotations

List quotations quotationsIndex

Quotations ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): number , notes .

Auth Session cookie · X-Company-Id **required**

Permission Policy: quotations.view (viewAny on Quotation)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum QuotationStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: draft, sent, accepted, rejected, expired, converted
filter[customer_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[sales_rep_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[currency]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-id). The primary key is always appended as a tie-breaker. · values: number, -number, date, -date, valid_until, -valid_until, status, -status, total, -total, created_at, -created_at · default -id

RESPONSES

200 — data : array of Quotation + meta.pagination

id integer company_id integer number string customer_id integer customer object date string(date) | null valid_until string(date) | null status enum QuotationStatus | null currency string subtotal Money (string) discount_total Money (string) tax_total Money (string) total Money (string) notes string | null terms string | null rejection_reason string | null sales_rep_id integer | null sales_rep UserRef | null created_by integer | null converted_sales_order_id integer | null lines SalesDocumentLine[] lines_count integer sent_at string(date-time) | null accepted_at string(date-time) | null rejected_at string(date-time) | null …aur 2 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/quotations

Create quotation quotationsStore

Naya quotation banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: quotations.manage (create on Quotation)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`customer_id`	integer	**yes**	Validated by `TenantExists`.
`date`	string(date)	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].description`	string	no	maxLength 500
`lines[].discount_percent`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].tax_rate`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].unit_price`	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].uom`	string | null	no	maxLength 10
`notes`	string | null	no	maxLength 5000
`sales_rep_id`	integer | null	no	Validated by `CompanyMember`.
`terms`	string | null	no	maxLength 5000
`valid_until`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:date`.

EXAMPLE REQUEST

```
{
  "currency": "PKR",
  "customer_id": 1,
  "date": "2026-10-15",
  "lines": [
    {
      "description": "Sample text",
      "discount_percent": "10.0000",
      "product_id": 1,
      "quantity": "2.0000",
      "tax_rate": "17.0000",
      "unit_price": "1250.0000",
      "uom": "string"
    }
  ],
  "notes": "Sample text",
  "sales_rep_id": 1,
  "terms": "Sample text",
  "valid_until": "2026-10-15"
}
```

RESPONSES

201 — `data` : Quotation

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `date` string(date) | null `valid_until` string(date) | null `status` enum QuotationStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `notes` string | null `terms` string | null `rejection_reason` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null

`converted_sales_order_id` integer | null `lines` SalesDocumentLine[] `lines_count` integer `sent_at` string(date-time) | null
`accepted_at` string(date-time) | null `rejected_at` string(date-time) | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/quotations/{quotation}`

Get quotation `quotationsShow`

Ek quotation ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**
Permission Policy: `quotations.view` (view on Quotation)
Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`quotation`	path	integer	**yes**	ID of the Quotation. · min 1

RESPONSES

200 — `data` : Quotation

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `date` string(date) | null
`valid_until` string(date) | null `status` enum QuotationStatus | null `currency` string `subtotal` Money (string)
`discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `notes` string | null `terms` string | null
`rejection_reason` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null
`converted_sales_order_id` integer | null `lines` SalesDocumentLine[] `lines_count` integer `sent_at` string(date-time) | null
`accepted_at` string(date-time) | null `rejected_at` string(date-time) | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/quotations/{quotation}

Update quotation quotationsUpdate

Maujooda quotation ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `quotations.manage` (update on Quotation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
quotation	path	integer	yes	ID of the Quotation. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
customer_id	integer	no	Validated by TenantExists.
date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lines	object[]	no	minItems 1 · maxItems 200
lines[].description	string	no	maxLength 500
lines[].discount_percent	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].product_id	integer | null	no	Validated by TenantExists.
lines[].quantity	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].tax_rate	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].unit_price	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].uom	string | null	no	maxLength 10
notes	string | null	no	maxLength 5000
sales_rep_id	integer | null	no	Validated by CompanyMember.
terms	string | null	no	maxLength 5000
valid_until	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:date.

RESPONSES

200 — `data` : Quotation

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `date` string(date) | null `valid_until` string(date) | null `status` enum QuotationStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `notes` string | null `terms` string | null `rejection_reason` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `converted_sales_order_id` integer | null `lines` SalesDocumentLine[] `lines_count` integer `sent_at` string(date-time) | null `accepted_at` string(date-time) | null `rejected_at` string(date-time) | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/quotations/{quotation}

Update quotation quotationsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /quotations/{quotation} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission quotations.manage

DELETE /api/v1/quotations/{quotation}

Delete quotation quotationsDestroy

Quotation delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: quotations.manage (delete on Quotation)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
quotation	path	integer	**yes**	ID of the Quotation. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/quotations/{quotation}/send

Send – quotation quotationsSend

Quotation ko sent mark karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: quotations.manage (update on Quotation)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
quotation	path	integer	**yes**	ID of the Quotation. · min 1

RESPONSES

200 — data : Quotation

id integer · company_id integer · number string · customer_id integer · customer object · date string(date) | null · valid_until string(date) | null · status enum QuotationStatus | null · currency string · subtotal Money (string) · discount_total Money (string) · tax_total Money (string) · total Money (string) · notes string | null · terms string | null · rejection_reason string | null · sales_rep_id integer | null · sales_rep UserRef | null · created_by integer | null · converted_sales_order_id integer | null · lines SalesDocumentLine[] · lines_count integer · sent_at string(date-time) | null · accepted_at string(date-time) | null · rejected_at string(date-time) | null · …aur 2 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST `/api/v1/quotations/{quotation}/accept`

Accept – quotation `quotationsAccept`

Quotation ko accept karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `quotations.manage` (update on Quotation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`quotation`	path	integer	**yes**	ID of the Quotation. · min 1

RESPONSES

200 — `data` : Quotation

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `date` string(date) | null `valid_until` string(date) | null `status` enum QuotationStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `notes` string | null `terms` string | null `rejection_reason` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `converted_sales_order_id` integer | null `lines` SalesDocumentLine[] `lines_count` integer `sent_at` string(date-time) | null `accepted_at` string(date-time) | null `rejected_at` string(date-time) | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST `/api/v1/quotations/{quotation}/reject`

Reject – quotation `quotationsReject`

Quotation ko reject karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `quotations.manage` (update on Quotation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`quotation`	path	integer	**yes**	ID of the Quotation. · min 1

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`reason`	string | null	no	maxLength 500

RESPONSES

200 — `data` : Quotation

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `date` string(date) | null `valid_until` string(date) | null `status` enum QuotationStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `notes` string | null `terms` string | null `rejection_reason` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `converted_sales_order_id` integer | null `lines` SalesDocumentLine[] `lines_count` integer `sent_at` string(date-time) | null `accepted_at` string(date-time) | null `rejected_at` string(date-time) | null …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/quotations/{quotation}/convert

Convert – quotation quotationsConvert

Quotation ko convert karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `quotations.manage` / `sales_orders.manage` (update on Quotation; create on SalesOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
quotation	path	integer	yes	ID of the Quotation. · min 1

RESPONSES

201 — `data` : SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/sales-orders`

List sales orders `salesOrdersIndex`

Sales orders ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `shipping_name` , `notes` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `sales_orders.view` (viewAny on SalesOrder)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum SalesOrderStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `confirmed`, `approved`, `partially_delivered`, `delivered`, `cancelled`
`filter[customer_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[sales_rep_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[quotation_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[currency]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `order_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `order_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-id`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `order_date`, `-order_date`, `expected_delivery_date`, `-expected_delivery_date`, `status`, `-status`, `total`, `-total`, `created_at`, `-created_at` · default `-id`

RESPONSES

200 — `data` : array of SalesOrder + `meta.pagination`

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/sales-orders

Create sales order salesOrdersStore

Naya sales order banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (create on SalesOrder)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
customer_id	integer	yes	Validated by TenantExists.
expected_delivery_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lines	object[]	yes	minItems 1 · maxItems 200
lines[].description	string	no	maxLength 500
lines[].discount_percent	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].product_id	integer | null	no	Validated by TenantExists.
lines[].quantity	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].tax_rate	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].unit_price	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].uom	string | null	no	maxLength 10
notes	string | null	no	maxLength 5000
order_date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
sales_rep_id	integer | null	no	Validated by CompanyMember.
shipping_address_line1	string | null	no	maxLength 200
shipping_address_line2	string | null	no	maxLength 200
shipping_city	string | null	no	maxLength 100
shipping_country	string | null	no	minLength 2 · maxLength 2
shipping_name	string | null	no	maxLength 150
shipping_postal_code	string | null	no	maxLength 20
shipping_state	string | null	no	maxLength 100
terms	string | null	no	maxLength 5000
warehouse_id	integer | null	no	Validated by TenantExists.

EXAMPLE REQUEST

```
{
  "customer_id": 1,
  "lines": [
    {
      "description": "Sample text",
      "discount_percent": "10.0000",
      "product_id": 1,
      "quantity": "2.0000",
      "tax_rate": "17.0000",
      "unit_price": "1250.0000",
      "uom": "string"
    }
  ],
  "currency": "PKR",
  "expected_delivery_date": "2026-10-15",
  "notes": "Sample text",
  "order_date": "2026-10-15",
  "sales_rep_id": 1,
  "shipping_address_line1": "Shahrah-e-Faisal, Karachi"
}
```

RESPONSES

201 — `data` : SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/sales-orders/{salesOrder}`

Get sales order `salesOrdersShow`

Ek sales order ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `sales_orders.view` (view on SalesOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`salesOrder`	path	integer	**yes**	ID of the Sales Order. · min 1

RESPONSES

200 — `data` : SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/sales-orders/{salesOrder}

Update sales order salesOrdersUpdate

Maujooda sales order ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (update on SalesOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
salesOrder	path	integer	yes	ID of the Sales Order. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
customer_id	integer	no	Validated by TenantExists.
expected_delivery_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lines	object[]	no	minItems 1 · maxItems 200
lines[].description	string	no	maxLength 500
lines[].discount_percent	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].product_id	integer | null	no	Validated by TenantExists.
lines[].quantity	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].tax_rate	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].unit_price	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].uom	string | null	no	maxLength 10
notes	string | null	no	maxLength 5000
order_date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
sales_rep_id	integer | null	no	Validated by CompanyMember.
shipping_address_line1	string | null	no	maxLength 200
shipping_address_line2	string | null	no	maxLength 200
shipping_city	string | null	no	maxLength 100
shipping_country	string | null	no	minLength 2 · maxLength 2
shipping_name	string | null	no	maxLength 150
shipping_postal_code	string | null	no	maxLength 20
shipping_state	string | null	no	maxLength 100
terms	string | null	no	maxLength 5000
warehouse_id	integer | null	no	Validated by TenantExists.

RESPONSES

200 — `data`: SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null
`order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string
`subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string)
`shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null
`sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null
`approved_by` integer | null `approver` UserRef | null ...aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/**sales-orders/{salesOrder}**

Update sales order `salesOrdersUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /sales-orders/{salesOrder}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `sales_orders.manage`

DELETE /api/v1/**sales-orders/{salesOrder}**

Delete sales order `salesOrdersDestroy`

Sales order delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission Policy: `sales_orders.manage` (delete on SalesOrder)
Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`salesOrder`	path	integer	**yes**	ID of the Sales Order. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/sales-orders/{salesOrder}/confirm

Draft → Confirmed; announces the order to Inventory/AR via SalesOrderConfirmed. salesOrdersConfirm

Sales order ko Draft → Confirmed karta hai; Inventory/AR ko `SalesOrderConfirmed` ke zariye khabar jati hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (update on SalesOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
salesOrder	path	integer	yes	ID of the Sales Order. · min 1

RESPONSES

200 — `data` : SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/sales-orders/{salesOrder}/approve

Confirmed → Approved (sales_orders.approve). salesOrdersApprove

Sales order ko Confirmed → Approved karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `sales_orders.approve` · Policy: `sales_orders.approve` (approve on SalesOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
salesOrder	path	integer	yes	ID of the Sales Order. · min 1

RESPONSES

200 — `data` : SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/sales-orders/{salesOrder}/cancel

Cancel unless anything has already been delivered. Open deliveries are cancelled too. `salesOrdersCancel`

Sales order cancel karta hai, basharte kuch deliver na hua ho; open deliveries bhi cancel ho jati hain.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (update on SalesOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`salesOrder`	path	integer	**yes**	ID of the Sales Order. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`reason`	string	**yes**	maxLength 500

RESPONSES

200 — `data` : SalesOrder

`id` integer `company_id` integer `number` string `customer_id` integer `customer` object `quotation_id` integer | null `order_date` string(date) | null `expected_delivery_date` string(date) | null `status` enum SalesOrderStatus | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `total` Money (string) `shipping_address` object `warehouse_id` integer | null `warehouse` object | null `notes` string | null `terms` string | null `sales_rep_id` integer | null `sales_rep` UserRef | null `created_by` integer | null `confirmed_at` string(date-time) | null `approved_by` integer | null `approver` UserRef | null …aur 9 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST `/api/v1/sales-orders/{salesOrder}/deliveries`

Create delivery (from sales order) `salesOrdersDeliveriesStore`

Naya delivery (from sales order) banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Policy: `sales_orders.manage` (update on SalesOrder)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`salesOrder`	path	integer	**yes**	ID of the Sales Order. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`carrier`	string | null	no	maxLength 100
`delivery_date`	string(date)	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].quantity`	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].sales_order_line_id`	integer	no	Values must be distinct.
`notes`	string | null	no	maxLength 5000
`tracking_number`	string | null	no	maxLength 100

EXAMPLE REQUEST

```
{
  "carrier": "string",
  "delivery_date": "2026-10-15",
  "lines": [{"quantity":"2.0000","sales_order_line_id":1}],
  "notes": "Sample text",
  "tracking_number": "string"
}
```

RESPONSES

201 — `data` : Delivery

`id` integer `company_id` integer `number` string `sales_order_id` integer `sales_order` object `customer` object | null `delivery_date` string(date) | null `status` enum DeliveryStatus | null `tracking_mode` string `carrier` string | null `tracking_number` string | null `shipped_at` string(date-time) | null `delivered_at` string(date-time) | null `cancelled_at` string(date-time) | null `notes` string | null `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/deliveries

List deliveries deliveriesIndex

Deliveries ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): number , carrier , tracking_number .

Auth Session cookie · X-Company-Id **required**

Permission Policy: sales_orders.view (viewAny on Delivery)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum DeliveryStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: pending, in_transit, delivered, cancelled
filter[sales_order_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[carrier]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on delivery_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on delivery_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-id). The primary key is always appended as a tie-breaker. · values: number, -number, delivery_date, -delivery_date, status, -status, shipped_at, -shipped_at, delivered_at, -delivered_at, created_at, -created_at · default -id

RESPONSES

200 — data : array of Delivery + meta.pagination

id integer company_id integer number string sales_order_id integer sales_order object customer object | null
delivery_date string(date) | null status enum DeliveryStatus | null tracking_mode string carrier string | null
tracking_number string | null shipped_at string(date-time) | null delivered_at string(date-time) | null
cancelled_at string(date-time) | null notes string | null lines object[] created_at string(date-time) | null
updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

`GET` /api/v1/deliveries/{delivery}

Get delivery `deliveriesShow`

Ek delivery ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `sales_orders.view` (view on Delivery)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`delivery`	path	integer	**yes**	ID of the Delivery. · min 1

RESPONSES

200 — `data` : Delivery

`id` integer `company_id` integer `number` string `sales_order_id` integer `sales_order` object `customer` object | null `delivery_date` string(date) | null `status` enum DeliveryStatus | null `tracking_mode` string `carrier` string | null `tracking_number` string | null `shipped_at` string(date-time) | null `delivered_at` string(date-time) | null `cancelled_at` string(date-time) | null `notes` string | null `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

`POST` /api/v1/deliveries/{delivery}/ship

Ship – delivery `deliveriesShip`

Delivery ko shipped mark karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (update on Delivery)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`delivery`	path	integer	**yes**	ID of the Delivery. · min 1

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`carrier`	string | null	no	maxLength 100
`tracking_number`	string | null	no	maxLength 100

RESPONSES

200 — `data` : Delivery

`id` integer `company_id` integer `number` string `sales_order_id` integer `sales_order` object `customer` object | null `delivery_date` string(date) | null `status` enum DeliveryStatus | null `tracking_mode` string `carrier` string | null `tracking_number` string | null `shipped_at` string(date-time) | null `delivered_at` string(date-time) | null `cancelled_at` string(date-time) | null `notes` string | null `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/deliveries/{delivery}/deliver

Deliver – delivery `deliveriesDeliver`

Delivery ko delivered mark karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (update on Delivery)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`delivery`	path	integer	**yes**	ID of the Delivery. · min 1

RESPONSES

200 — `data` : Delivery

`id` integer `company_id` integer `number` string `sales_order_id` integer `sales_order` object `customer` object | null `delivery_date` string(date) | null `status` enum DeliveryStatus | null `tracking_mode` string `carrier` string | null `tracking_number` string | null `shipped_at` string(date-time) | null `delivered_at` string(date-time) | null `cancelled_at` string(date-time) | null `notes` string | null `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/deliveries/{delivery}/cancel

Cancel – delivery `deliveriesCancel`

Delivery ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `sales_orders.manage` (update on Delivery)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`delivery`	path	integer	**yes**	ID of the Delivery. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`reason`	string | null	no	maxLength 500

RESPONSES

200 — `data` : Delivery

`id` integer `company_id` integer `number` string `sales_order_id` integer `sales_order` object `customer` object | null `delivery_date` string(date) | null `status` enum DeliveryStatus | null `tracking_mode` string `carrier` string | null `tracking_number` string | null `shipped_at` string(date-time) | null `delivered_at` string(date-time) | null `cancelled_at` string(date-time) | null `notes` string | null `lines` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/sales/reports/performance

performance `salesReportsPerformance`

Performance report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.view` (sales.reports.view)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`from`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`group_by`	query	string	no	values: `rep`, `customer`, `month`
`to`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:from`.

RESPONSES

200 — `data` : object shape inferred from code

`from` string(date) `to` string(date) `group_by` string `rows` object[] `totals` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/sales/reports/pipeline

pipeline `salesReportsPipeline`

Pipeline report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.view` (sales.reports.view)

Throttle `api`

RESPONSES

200 — `data` : object shape inferred from code

`stages` object[] `open` object `win_rate_90d` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

MODULE

Procurement

Suppliers (contacts, approval, summary), purchase requisitions, purchase orders, goods receipts aur purchase returns, saath mein spend aur supplier-performance reports. Approved requisition se `create-purchase-order` ke zariye PO banta hai.

Spec: Suppliers, purchase requisitions, purchase orders, goods receipts, purchase returns. — 56 operations.

Method	Path	Summary	Permission
GET	/suppliers/all	Lightweight list for selectors (active suppliers, no pagination).	suppliers.view
GET	/suppliers/map	Geo-coded active suppliers for the map view.	suppliers.view
GET	/suppliers/{supplier}/summary	Summary – supplier	suppliers.view
POST	/suppliers/{supplier}/approve	Vendor approval: marks the supplier as approved for purchasing (audited).	suppliers.manage
GET	/suppliers	List suppliers	suppliers.view
POST	/suppliers	Create supplier	suppliers.manage
GET	/suppliers/{supplier}	Get supplier	suppliers.view
PUT	/suppliers/{supplier}	Update supplier	suppliers.manage
PATCH	/suppliers/{supplier}	Update supplier	suppliers.manage
DELETE	/suppliers/{supplier}	Delete supplier	suppliers.manage
GET	/suppliers/{supplier}/contacts	List contacts	suppliers.view
POST	/suppliers/{supplier}/contacts	Create contact	suppliers.manage
PUT	/suppliers/{supplier}/contacts/{contact}	Update contact	suppliers.manage
PATCH	/suppliers/{supplier}/contacts/{contact}	Update contact	suppliers.manage
DELETE	/suppliers/{supplier}/contacts/{contact}	Delete contact	suppliers.manage
POST	/requisitions/{requisition}/submit	Submit – requisition	requisitions.create
POST	/requisitions/{requisition}/approve	Approve – requisition	requisitions.approve
POST	/requisitions/{requisition}/reject	Reject – requisition	requisitions.approve
POST	/requisitions/{requisition}/cancel	Requester withdraws a draft or submitted requisition.	requisitions.create
POST	/requisitions/{requisition}/create-purchase-order	Create purchase order – requisition	purchase_orders.manage
GET	/requisitions	List requisitions	requisitions.view requisitions.create requisitions.approve
POST	/requisitions	Create requisition	requisitions.create
GET	/requisitions/{requisition}	Get requisition	requisitions.view requisitions.approve requisitions.create

Method	Path	Summary	Permission
PUT	/requisitions/{requisition}	Update requisition	requisitions.create
PATCH	/requisitions/{requisition}	Update requisition	requisitions.create
DELETE	/requisitions/{requisition}	Delete requisition	requisitions.create
POST	/purchase-orders/{purchase_order}/submit	Submit – purchase order	purchase_orders.manage
POST	/purchase-orders/{purchase_order}/approve	Approve – purchase order	purchase_orders.approve
POST	/purchase-orders/{purchase_order}/cancel	Cancel – purchase order	purchase_orders.manage
POST	/purchase-orders/{purchase_order}/close	Manual close: fully received, or nothing more is expected from the supplier.	purchase_orders.manage
POST	/purchase-orders/{purchase_order}/send	Marks the approved order as sent to the supplier (status unchanged).	purchase_orders.manage
POST	/purchase-orders/{purchase_order}/goods-receipts	Create goods receipt (from purchase order)	goods_receipts.manage
GET	/purchase-orders	List purchase orders	purchase_orders.view
POST	/purchase-orders	Create purchase order	purchase_orders.manage
GET	/purchase-orders/{purchase_order}	Get purchase order	purchase_orders.view
PUT	/purchase-orders/{purchase_order}	Update purchase order	purchase_orders.manage
PATCH	/purchase-orders/{purchase_order}	Update purchase order	purchase_orders.manage
DELETE	/purchase-orders/{purchase_order}	Delete purchase order	purchase_orders.manage
POST	/goods-receipts/{goods_receipt}/confirm	Confirm – goods receipt	goods_receipts.manage
POST	/goods-receipts/{goods_receipt}/cancel	Cancel – goods receipt	goods_receipts.manage
GET	/goods-receipts	List goods receipts	purchase_orders.view goods_receipts.manage
GET	/goods-receipts/{goods_receipt}	Get goods receipt	purchase_orders.view goods_receipts.manage
PUT	/goods-receipts/{goods_receipt}	Update goods receipt	goods_receipts.manage
PATCH	/goods-receipts/{goods_receipt}	Update goods receipt	goods_receipts.manage
DELETE	/goods-receipts/{goods_receipt}	Delete goods receipt	goods_receipts.manage
POST	/purchase-returns/{purchase_return}/confirm	Confirm – purchase return	goods_receipts.manage
POST	/purchase-returns/{purchase_return}/cancel	Cancel – purchase return	goods_receipts.manage
GET	/purchase-returns	List purchase returns	purchase_orders.view goods_receipts.manage
POST	/purchase-returns	Create purchase return	goods_receipts.manage
GET	/purchase-returns/{purchase_return}	Get purchase return	purchase_orders.view goods_receipts.manage
PUT	/purchase-returns/{purchase_return}	Update purchase return	goods_receipts.manage
PATCH	/purchase-returns/{purchase_return}	Update purchase return	goods_receipts.manage
DELETE	/purchase-returns/{purchase_return}	Delete purchase return	goods_receipts.manage
GET	/procurement/reports/spend	Spend – report	reports.view
GET	/procurement/reports/status-summary	Status summary – report	reports.view

Method	Path	Summary	Permission
GET	/procurement/reports/supplier-performance	Supplier performance – report	reports.view

Endpoints

GET /api/v1/suppliers/all

Lightweight list for selectors (active suppliers, no pagination). suppliersAll

Selectors ke liye active suppliers ki halki list deta hai (bina pagination).

Auth: Session cookie · X-Company-Id **required**

Permission: Policy: suppliers.view (viewAny on Supplier)

Throttle: api

RESPONSES

200 — data : array of Supplier

id integer · company_id integer · code string · name string · type enum SupplierType | null · email string | null · phone string | null · website string | null · tax_number string | null · currency string · payment_terms_days integer · credit_limit Money (string) | null · address object · latitude Decimal (string) | null · longitude Decimal (string) | null · bank_name string | null · bank_account_last4 string | null · rating integer | null · lead_time_days integer | null · categories any[] · notes string | null · is_active boolean · is_approved boolean · approved_at string(date-time) | null · approver object | null …aur 5 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/suppliers/map

Geo-coded active suppliers for the map view. suppliersMap

Geo-coded active suppliers deta hai (map view ke liye).

Auth: Session cookie · X-Company-Id **required**

Permission: Policy: suppliers.view (viewAny on Supplier)

Throttle: api

RESPONSES

200 — data : array of object shape inferred from code

id integer · code string · name string · type enum SupplierType | null · city string | null · country string | null · latitude Decimal (string) | null · longitude Decimal (string) | null · rating integer | null · is_approved boolean

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/suppliers/{supplier}/summary

Summary – supplier `suppliersSummary`

Ek supplier ka summary deta hai (aggregate data).

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `suppliers.view` (view on Supplier)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`supplier`	path	integer	**yes**	ID of the Supplier. · min 1

RESPONSES

200 — `data` : object shape inferred from code

`supplier_id` integer `currency` string `purchase_orders` object `goods_receipts_count` integer
`avg_lead_time_days` number | null `promised_lead_time_days` integer | null `last_order_date` number
`last_received_date` string(date) `outstanding_payable` Decimal (string) `overdue_payable` Decimal (string)
`open_bills_count` integer `overdue_bills_count` integer

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/suppliers/{supplier}/approve

Vendor approval: marks the supplier as approved for purchasing (audited). `suppliersApprove`

Vendor approval: supplier ko purchasing ke liye approved mark karta hai (audited).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `suppliers.manage` · Policy: `suppliers.manage` (approve on Supplier)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`supplier`	path	integer	**yes**	ID of the Supplier. · min 1

RESPONSES

200 — `data` : Supplier

`id` integer `company_id` integer `code` string `name` string `type` enum SupplierType | null `email` string | null `phone` string | null
`website` string | null `tax_number` string | null `currency` string `payment_terms_days` integer `credit_limit` Money (string) | null
`address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `bank_name` string | null
`bank_account_last4` string | null `rating` integer | null `lead_time_days` integer | null `categories` any[] `notes` string | null
`is_active` boolean `is_approved` boolean `approved_at` string(date-time) | null `approver` object | null …aur 5 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/suppliers

List suppliers suppliersIndex

Suppliers ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , code , email , city , tax_number .

Auth Session cookie · X-Company-Id **required**

Permission Policy: suppliers.view (viewAny on Supplier)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[is_approved]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[type]	query	enum SupplierType	no	Exact-match filter (comma-separated = koi bhi value). · values: individual, company
filter[country]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[currency]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[rating]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, rating, -rating, city, -city, created_at, -created_at · default name

RESPONSES

200 — data : array of Supplier + meta.pagination

id integer company_id integer code string name string type enum SupplierType | null email string | null phone string | null website string | null tax_number string | null currency string payment_terms_days integer credit_limit Money (string) | null address object latitude Decimal (string) | null longitude Decimal (string) | null bank_name string | null bank_account_last4 string | null rating integer | null lead_time_days integer | null categories any[] notes string | null is_active boolean is_approved boolean approved_at string(date-time) | null approver object | null …aur 5 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/suppliers

Create supplier suppliersStore

Naya supplier banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: suppliers.manage (create on Supplier)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200

Field	Type	Req.	Constraints / notes
address_line2	string | null	no	maxLength 200
bank_account_number	string | null	no	maxLength 64
bank_name	string | null	no	maxLength 150
categories	string[] | null	no	maxItems 20
city	string | null	no	maxLength 100
code	string | null	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `suppliers` (per company).
country	string | null	no	minLength 2 · maxLength 2
credit_limit	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
currency	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
email	string(email) | null	no	maxLength 150
is_active	boolean	no	
latitude	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lead_time_days	integer | null	no	min 0 · max 365
longitude	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	**yes**	maxLength 150
notes	string | null	no	maxLength 2000
payment_terms_days	integer	no	min 0 · max 365
phone	string | null	no	maxLength 40
postal_code	string | null	no	maxLength 20
rating	integer | null	no	min 1 · max 5
state	string | null	no	maxLength 100
tax_number	string | null	no	maxLength 60
type	enum SupplierType	no	values: `individual`, `company`
website	string(uri) | null	no	maxLength 200

EXAMPLE REQUEST

```
{
  "name": "Sample name",
  "address_line1": "Shahrah-e-Faisal, Karachi",
  "address_line2": "Shahrah-e-Faisal, Karachi",
  "bank_account_number": "string",
  "bank_name": "Sample name",
  "categories": ["string"],
  "city": "Karachi",
  "code": "CODE-001"
}
```

RESPONSES

201 — `data` : Supplier

`id` integer `company_id` integer `code` string `name` string `type` enum SupplierType | null `email` string | null `phone` string | null `website` string | null `tax_number` string | null `currency` string `payment_terms_days` integer `credit_limit` Money (string) | null `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `bank_name` string | null `bank_account_last4` string | null `rating` integer | null `lead_time_days` integer | null `categories` any[] `notes` string | null `is_active` boolean `is_approved` boolean `approved_at` string(date-time) | null `approver` object | null …aur 5 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/suppliers/{supplier}`

Get supplier `suppliersShow`

Ek supplier ki poori tafseel deta hai.

Auth — Session cookie · `X-Company-Id` **required**

Permission — Policy: `suppliers.view` (view on Supplier)

Throttle — `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`supplier`	path	integer	**yes**	ID of the Supplier. · min 1

RESPONSES

200 — `data` : Supplier

`id` integer `company_id` integer `code` string `name` string `type` enum SupplierType | null `email` string | null `phone` string | null `website` string | null `tax_number` string | null `currency` string `payment_terms_days` integer `credit_limit` Money (string) | null `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `bank_name` string | null `bank_account_last4` string | null `rating` integer | null `lead_time_days` integer | null `categories` any[] `notes` string | null `is_active` boolean `is_approved` boolean `approved_at` string(date-time) | null `approver` object | null …aur 5 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

---

`PUT` `/api/v1/suppliers/{supplier}`

Update supplier `suppliersUpdate`

Maujooda supplier ko update karta hai.

> Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth — Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission — Policy: `suppliers.manage` (update on Supplier)

Throttle — `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`supplier`	path	integer	**yes**	ID of the Supplier. · min 1

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`address_line1`	string | null	no	maxLength 200
`address_line2`	string | null	no	maxLength 200
`bank_account_number`	string | null	no	maxLength 64
`bank_name`	string | null	no	maxLength 150
`categories`	string[] | null	no	maxItems 20
`city`	string | null	no	maxLength 100
`code`	string | null	no	maxLength 20 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `suppliers` (per company).
`country`	string | null	no	minLength 2 · maxLength 2
`credit_limit`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`

Field	Type	Req.	Constraints / notes
email	string(email) | null	no	maxLength 150
is_active	boolean	no	
latitude	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lead_time_days	integer | null	no	min 0 · max 365
longitude	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	no	maxLength 150
notes	string | null	no	maxLength 2000
payment_terms_days	integer	no	min 0 · max 365
phone	string | null	no	maxLength 40
postal_code	string | null	no	maxLength 20
rating	integer | null	no	min 1 · max 5
state	string | null	no	maxLength 100
tax_number	string | null	no	maxLength 60
type	enum SupplierType	no	values: individual, company
website	string(uri) | null	no	maxLength 200

RESPONSES

200 — data : Supplier

id integer company_id integer code string name string type enum SupplierType | null email string | null phone string | null website string | null tax_number string | null currency string payment_terms_days integer credit_limit Money (string) | null address object latitude Decimal (string) | null longitude Decimal (string) | null bank_name string | null bank_account_last4 string | null rating integer | null lead_time_days integer | null categories any[] notes string | null is_active boolean is_approved boolean approved_at string(date-time) | null approver object | null …aur 5 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

PATCH /api/v1/suppliers/{supplier}

Update supplier suppliersUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /suppliers/{supplier} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission suppliers.manage

DELETE /api/v1/suppliers/{supplier}

Delete supplier suppliersDestroy

Supplier delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: suppliers.manage (delete on Supplier)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
supplier	path	integer	**yes**	ID of the Supplier. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

GET /api/v1/suppliers/{supplier}/contacts

List contacts suppliersContactsIndex

Contacts ki list deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: suppliers.view (view on Supplier)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
supplier	path	integer	**yes**	ID of the Supplier. · min 1

RESPONSES

200 — data : array of SupplierContact

id integer supplier_id integer name string title string | null email string | null phone string | null is_primary boolean created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/suppliers/{supplier}/contacts

Create contact suppliersContactsStore

Naya contact banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `suppliers.manage` (update on Supplier)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
supplier	path	integer	yes	ID of the Supplier. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
email	string(email) | null	no	maxLength 150
is_primary	boolean	no	
name	string	yes	maxLength 150
phone	string | null	no	maxLength 40
title	string | null	no	maxLength 100

EXAMPLE REQUEST

```
{
  "email": "ali.raza@example.com",
  "is_primary": true,
  "name": "Sample name",
  "phone": "+92 300 1234567",
  "title": "Sample title"
}
```

RESPONSES

201 — `data` : SupplierContact

`id` integer `supplier_id` integer `name` string `title` string | null `email` string | null `phone` string | null `is_primary` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PUT /api/v1/suppliers/{supplier}/contacts/{contact}

Update contact suppliersContactsUpdate

Maujooda contact ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `suppliers.manage` (update on Supplier)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`supplier`	path	integer	**yes**	ID of the Supplier. · min 1
`contact`	path	integer	**yes**	ID of the Supplier Contact. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`email`	string(email) | null	no	maxLength 150
`is_primary`	boolean	no	
`name`	string	no	maxLength 150
`phone`	string | null	no	maxLength 40
`title`	string | null	no	maxLength 100

RESPONSES

200 — `data`: SupplierContact

`id` integer `supplier_id` integer `name` string `title` string | null `email` string | null `phone` string | null `is_primary` boolean `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/suppliers/{supplier}/contacts/{contact}

Update contact suppliersContactsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /suppliers/{supplier}/contacts/{contact} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission suppliers.manage

DELETE /api/v1/suppliers/{supplier}/contacts/{contact}

Delete contact suppliersContactsDestroy

Contact delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: suppliers.manage (update on Supplier)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
supplier	path	integer	yes	ID of the Supplier. · min 1
contact	path	integer	yes	ID of the Supplier Contact. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

POST /api/v1/requisitions/{requisition}/submit

Submit – requisition requisitionsSubmit

Requisition ko approval ke liye submit karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: requisitions.create (submit on PurchaseRequisition)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
requisition	path	integer	yes	ID of the Purchase Requisition. · min 1

RESPONSES

200 — data : PurchaseRequisition

id integer company_id integer number string status enum RequisitionStatus | null priority enum RequisitionPriority | null requester_id integer requester object | null department_id integer | null department object | null branch_id integer | null branch object | null needed_by string(date) | null justification string | null estimated_total Money (string) submitted_at string(date-time) | null approver_id integer | null approver object | null approved_at string(date-time) | null rejected_at string(date-time) | null rejection_reason string | null lines PurchaseRequisitionLine[] lines_count integer purchase_orders object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/requisitions/{requisition}/approve

Approve – requisition requisitionsApprove

Requisition ko approve karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: requisitions.approve · Policy: requisitions.approve (approve on PurchaseRequisition)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
requisition	path	integer	yes	ID of the Purchase Requisition. · min 1

RESPONSES

200 — data : PurchaseRequisition

id integer company_id integer number string status enum RequisitionStatus | null priority enum RequisitionPriority | null requester_id integer requester object | null department_id integer | null department object | null branch_id integer | null branch object | null needed_by string(date) | null justification string | null estimated_total Money (string) submitted_at string(date-time) | null approver_id integer | null approver object | null approved_at string(date-time) | null rejected_at string(date-time) | null rejection_reason string | null lines PurchaseRequisitionLine[] lines_count integer purchase_orders object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/requisitions/{requisition}/reject

Reject – requisition requisitionsReject

Requisition ko reject karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: requisitions.approve · Policy: requisitions.approve (reject on PurchaseRequisition)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
requisition	path	integer	yes	ID of the Purchase Requisition. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
reason	string	yes	maxLength 500

RESPONSES

200 — data : PurchaseRequisition

id integer company_id integer number string status enum RequisitionStatus | null priority enum RequisitionPriority | null requester_id integer requester object | null department_id integer | null department object | null branch_id integer | null branch object | null needed_by string(date) | null justification string | null estimated_total Money (string) submitted_at string(date-time) | null approver_id integer | null approver object | null approved_at string(date-time) | null rejected_at string(date-time) | null rejection_reason string | null lines PurchaseRequisitionLine[] lines_count integer purchase_orders object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

POST /api/v1/requisitions/{requisition}/cancel

Requester withdraws a draft or submitted requisition. requisitionsCancel

Requester apni draft ya submitted requisition wapas le leta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: requisitions.create (cancel on PurchaseRequisition)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
requisition	path	integer	yes	ID of the Purchase Requisition. · min 1

RESPONSES

200 — data : PurchaseRequisition

id integer company_id integer number string status enum RequisitionStatus | null priority enum RequisitionPriority | null requester_id integer requester object | null department_id integer | null department object | null branch_id integer | null branch object | null needed_by string(date) | null justification string | null estimated_total Money (string) submitted_at string(date-time) | null approver_id integer | null approver object | null approved_at string(date-time) | null rejected_at string(date-time) | null rejection_reason string | null lines PurchaseRequisitionLine[] lines_count integer purchase_orders object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/requisitions/{requisition}/create-purchase-order

Create purchase order – requisition `requisitionsCreatePurchaseOrder`

Naya purchase order – requisition banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `purchase_orders.manage` · Policy: `purchase_orders.manage` (createPurchaseOrder on PurchaseRequisition)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`requisition`	path	integer	**yes**	ID of the Purchase Requisition. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`delivery_address`	string | null	no	maxLength 500
`expected_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`notes`	string | null	no	maxLength 2000
`supplier_id`	integer	**yes**	Validated by `TenantExists`.
`warehouse_id`	integer | null	no	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "delivery_address": "Shahrah-e-Faisal, Karachi",
  "expected_date": "2026-10-15",
  "notes": "Sample text",
  "supplier_id": 1,
  "warehouse_id": 1
}
```

RESPONSES

201 — `data` : PurchaseOrder

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string) `warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer `notes` string | null `terms` string | null `created_by` integer | null `creator` object | null …aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/requisitions`

List requisitions `requisitionsIndex`

Requisitions ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `justification` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `requisitions.view` / `requisitions.create` / `requisitions.approve` (viewAny on PurchaseRequisition)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`mine`	query	boolean	no	
`filter[status]`	query	enum RequisitionStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `submitted`, `approved`, `rejected`, `ordered`, `cancelled`
`filter[priority]`	query	enum RequisitionPriority	no	Exact-match filter (comma-separated = koi bhi value). · values: `low`, `normal`, `high`, `urgent`
`filter[department_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[requester_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `created_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `created_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-created_at`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `status`, `-status`, `priority`, `-priority`, `needed_by`, `-needed_by`, `estimated_total`, `-estimated_total`, `created_at`, `-created_at` · default `-created_at`

RESPONSES

200 — `data` : array of PurchaseRequisition + `meta.pagination`

`id` integer `company_id` integer `number` string `status` enum RequisitionStatus | null `priority` enum RequisitionPriority | null `requester_id` integer `requester` object | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `needed_by` string(date) | null `justification` string | null `estimated_total` Money (string) `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejected_at` string(date-time) | null `rejection_reason` string | null `lines` PurchaseRequisitionLine[] `lines_count` integer `purchase_orders` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/**requisitions**

Create requisition `requisitionsStore`

Naya requisition banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `requisitions.create` (create on PurchaseRequisition)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`department_id`	integer | null	no	Validated by `TenantExists`.
`justification`	string | null	no	maxLength 2000
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].description`	string	no	maxLength 255
`lines[].estimated_unit_price`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].uom`	string | null	no	maxLength 20
`needed_by`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`priority`	enum RequisitionPriority	no	values: `low`, `normal`, `high`, `urgent`

EXAMPLE REQUEST

```
{
  "branch_id": 1,
  "department_id": 1,
  "justification": "string",
  "lines": [
    {
      "description": "Sample text",
      "estimated_unit_price": "1250.0000",
      "product_id": 1,
      "quantity": "2.0000",
      "uom": "string"
    }
  ],
  "needed_by": "2026-10-15",
  "priority": "low"
}
```

RESPONSES

201 — `data` : PurchaseRequisition

`id` integer `company_id` integer `number` string `status` enum RequisitionStatus | null `priority` enum RequisitionPriority | null `requester_id` integer `requester` object | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `needed_by` string(date) | null `justification` string | null `estimated_total` Money (string) `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejected_at` string(date-time) | null `rejection_reason` string | null `lines` PurchaseRequisitionLine[] `lines_count` integer `purchase_orders` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/requisitions/{requisition}

Get requisition `requisitionsShow`

Ek requisition ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `requisitions.view` / `requisitions.approve` / `requisitions.create` (view on PurchaseRequisition)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`requisition`	path	integer	**yes**	ID of the Purchase Requisition. · min 1

RESPONSES

200 — `data` : PurchaseRequisition

`id` integer `company_id` integer `number` string `status` enum RequisitionStatus | null `priority` enum RequisitionPriority | null `requester_id` integer `requester` object | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `needed_by` string(date) | null `justification` string | null `estimated_total` Money (string) `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejected_at` string(date-time) | null `rejection_reason` string | null `lines` PurchaseRequisitionLine[] `lines_count` integer `purchase_orders` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/requisitions/{requisition}

Update requisition requisitionsUpdate

Maujooda requisition ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `requisitions.create` (update on PurchaseRequisition)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`requisition`	path	integer	**yes**	ID of the Purchase Requisition. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`department_id`	integer | null	no	Validated by `TenantExists`.
`justification`	string | null	no	maxLength 2000
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].description`	string	no	maxLength 255
`lines[].estimated_unit_price`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].uom`	string | null	no	maxLength 20
`needed_by`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`priority`	enum RequisitionPriority	no	values: `low`, `normal`, `high`, `urgent`

RESPONSES

200 — `data` : PurchaseRequisition

`id` integer `company_id` integer `number` string `status` enum RequisitionStatus | null `priority` enum RequisitionPriority | null `requester_id` integer `requester` object | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `needed_by` string(date) | null `justification` string | null `estimated_total` Money (string) `submitted_at` string(date-time) | null `approver_id` integer | null `approver` object | null `approved_at` string(date-time) | null `rejected_at` string(date-time) | null `rejection_reason` string | null `lines` PurchaseRequisitionLine[] `lines_count` integer `purchase_orders` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/requisitions/{requisition}

Update requisition requisitionsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /requisitions/{requisition} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission requisitions.create

DELETE /api/v1/requisitions/{requisition}

Delete requisition requisitionsDestroy

Requisition delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: requisitions.create (delete on PurchaseRequisition)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
requisition	path	integer	**yes**	ID of the Purchase Requisition. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/purchase-orders/{purchase_order}/submit

Submit – purchase order purchaseOrdersSubmit

Purchase order ko approval ke liye submit karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: purchase_orders.manage (submit on PurchaseOrder)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_order	path	string	**yes**	

RESPONSES

200 — data : PurchaseOrder

id integer · company_id integer · number string · status enum PurchaseOrderStatus | null · supplier_id integer · supplier object | null · requisition_id integer | null · requisition object | null · branch_id integer | null · order_date string(date) | null · expected_date string(date) | null · currency string · subtotal Money (string) · discount_total Money (string) · tax_total Money (string) · shipping_cost Money (string) · total Money (string) · warehouse_id integer | null · warehouse object | null · delivery_address string | null · payment_terms_days integer · notes string | null · terms string | null · created_by integer | null · creator object | null · …aur 13 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/purchase-orders/{purchase_order}/approve

Approve – purchase order purchaseOrdersApprove

Purchase order ko approve karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `purchase_orders.approve` · Policy: `purchase_orders.approve` (approve on PurchaseOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_order	path	string	yes	

RESPONSES

200 — `data` : PurchaseOrder

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string) `warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer `notes` string | null `terms` string | null `created_by` integer | null `creator` object | null …aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/purchase-orders/{purchase_order}/cancel

Cancel – purchase order purchaseOrdersCancel

Purchase order ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `purchase_orders.manage` (cancel on PurchaseOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_order	path	string	yes	

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
reason	string	yes	maxLength 500

RESPONSES

200 — `data` : PurchaseOrder

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string) `warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer `notes` string | null `terms` string | null `created_by` integer | null `creator` object | null …aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST `/api/v1/purchase-orders/{purchase_order}/close`

Manual close: fully received, or nothing more is expected from the supplier. `purchaseOrdersClose`

Purchase order ko manually close karta hai — jab poora receive ho chuka ho ya supplier se mazeed kuch expected na ho.

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Policy: `purchase_orders.manage` (close on PurchaseOrder)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`purchase_order`	path	string	**yes**	

RESPONSES

200 — `data` : PurchaseOrder

`id` integer · `company_id` integer · `number` string · `status` enum PurchaseOrderStatus | null · `supplier_id` integer · `supplier` object | null · `requisition_id` integer | null · `requisition` object | null · `branch_id` integer | null · `order_date` string(date) | null · `expected_date` string(date) | null · `currency` string · `subtotal` Money (string) · `discount_total` Money (string) · `tax_total` Money (string) · `shipping_cost` Money (string) · `total` Money (string) · `warehouse_id` integer | null · `warehouse` object | null · `delivery_address` string | null · `payment_terms_days` integer · `notes` string | null · `terms` string | null · `created_by` integer | null · `creator` object | null · …aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST `/api/v1/purchase-orders/{purchase_order}/send`

Marks the approved order as sent to the supplier (status unchanged). `purchaseOrdersSend`

Approved order ko supplier ko "sent" mark karta hai (status nahi badalta).

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Policy: `purchase_orders.manage` (send on PurchaseOrder)

Throttle: `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`purchase_order`	path	string	**yes**	

RESPONSES

200 — `data` : PurchaseOrder

`id` integer · `company_id` integer · `number` string · `status` enum PurchaseOrderStatus | null · `supplier_id` integer · `supplier` object | null · `requisition_id` integer | null · `requisition` object | null · `branch_id` integer | null · `order_date` string(date) | null · `expected_date` string(date) | null · `currency` string · `subtotal` Money (string) · `discount_total` Money (string) · `tax_total` Money (string) · `shipping_cost` Money (string) · `total` Money (string) · `warehouse_id` integer | null · `warehouse` object | null · `delivery_address` string | null · `payment_terms_days` integer · `notes` string | null · `terms` string | null · `created_by` integer | null · `creator` object | null · …aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST `/api/v1/purchase-orders/{purchase_order}/goods-receipts`

Create goods receipt (from purchase order) `purchaseOrdersGoodsReceiptsStore`

Naya goods receipt (from purchase order) banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Route: `goods_receipts.manage` · Policy: `goods_receipts.manage` (create on GoodsReceipt; receive on PurchaseOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`purchase_order`	path	string	**yes**	

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].batch_number`	string | null	no	maxLength 60
`lines[].expires_at`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`lines[].purchase_order_line_id`	integer	no	min 1
`lines[].quantity_received`	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].quantity_rejected`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].rejection_reason`	string | null	no	maxLength 255
`notes`	string | null	no	maxLength 2000
`received_date`	string(date)	**yes**	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`supplier_delivery_note`	string | null	no	maxLength 100
`warehouse_id`	integer | null	no	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "lines": [
    {
      "batch_number": "string",
      "expires_at": "2026-11-14",
      "purchase_order_line_id": 1,
      "quantity_received": "2.0000",
      "quantity_rejected": "2.0000",
      "rejection_reason": "Sample text"
    }
  ],
  "notes": "Sample text",
  "received_date": "2026-10-15",
  "supplier_delivery_note": "Sample text",
  "warehouse_id": 1
}
```

RESPONSES

201 — `data` : GoodsReceipt

`id` integer `company_id` integer `number` string `status` enum GoodsReceiptStatus | null `purchase_order_id` integer `purchase_order` object | null `received_date` string(date) | null `warehouse_id` integer | null `warehouse` object | null `received_by` integer | null `receiver` object | null `supplier_delivery_note` string | null `notes` string | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` GoodsReceiptLine[] `lines_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/purchase-orders`

List purchase orders `purchaseOrdersIndex`

Purchase orders ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `notes` , `delivery_address` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `purchase_orders.view` (viewAny on PurchaseOrder)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum PurchaseOrderStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `submitted`, `approved`, `partially_received`, `received`, `closed`, `cancelled`
`filter[supplier_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[requisition_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[branch_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[currency]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `order_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `order_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-order_date`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `order_date`, `-order_date`, `expected_date`, `-expected_date`, `status`, `-status`, `total`, `-total`, `created_at`, `-created_at` · default `-order_date`

RESPONSES

200 — `data` : array of PurchaseOrder + `meta.pagination`

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string) `warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer `notes` string | null `terms` string | null `created_by` integer | null `creator` object | null …aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/purchase-orders`

Create purchase order `purchaseOrdersStore`

Naya purchase order banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth: Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission: Policy: `purchase_orders.manage` (create on PurchaseOrder)

Throttle: `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`currency`	string | null	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`delivery_address`	string | null	no	maxLength 500
`expected_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:order_date`.
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].description`	string	no	maxLength 255
`lines[].discount_percent`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer | null	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].tax_rate`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].unit_price`	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].uom`	string | null	no	maxLength 20
`notes`	string | null	no	maxLength 2000
`order_date`	string(date)	**yes**	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`payment_terms_days`	integer | null	no	min 0 · max 365
`requisition_id`	integer | null	no	Validated by `TenantExists`.
`shipping_cost`	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`supplier_id`	integer	**yes**	Validated by `TenantExists`.
`terms`	string | null	no	maxLength 5000
`warehouse_id`	integer | null	no	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "lines": [
    {
      "description": "Sample text",
      "discount_percent": "10.0000",
      "product_id": 1,
      "quantity": "2.0000",
      "tax_rate": "17.0000",
      "unit_price": "1250.0000",
      "uom": "string"
    }
  ],
  "order_date": "2026-10-15",
  "supplier_id": 1,
  "branch_id": 1,
  "currency": "PKR",
  "delivery_address": "Shahrah-e-Faisal, Karachi",
  "expected_date": "2026-10-15",
  "notes": "Sample text"
}
```

RESPONSES

201 — `data` : PurchaseOrder

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string) `warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer `notes` string | null `terms` string | null `created_by` integer | null `creator` object | null ...aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/purchase-orders/{purchase_order}`

Get purchase order `purchaseOrdersShow`

Ek purchase order ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `purchase_orders.view` (view on PurchaseOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_order	path	string	yes	

RESPONSES

200 — `data` : PurchaseOrder

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string) `warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer `notes` string | null `terms` string | null `created_by` integer | null `creator` object | null ...aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/purchase-orders/{purchase_order}

Update purchase order purchaseOrdersUpdate

Maujooda purchase order ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `purchase_orders.manage` (update on PurchaseOrder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_order	path	string	yes	

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
branch_id	integer | null	no	Validated by AccessibleBranch.
currency	string | null	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$
delivery_address	string | null	no	maxLength 500
expected_date	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:order_date.
lines	object[]	yes	minItems 1 · maxItems 200
lines[].description	string	no	maxLength 255
lines[].discount_percent	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].product_id	integer | null	no	Validated by TenantExists.
lines[].quantity	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].tax_rate	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].unit_price	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].uom	string | null	no	maxLength 20
notes	string | null	no	maxLength 2000
order_date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
payment_terms_days	integer | null	no	min 0 · max 365
requisition_id	integer | null	no	Validated by TenantExists.
shipping_cost	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
supplier_id	integer	no	Validated by TenantExists.
terms	string | null	no	maxLength 5000
warehouse_id	integer | null	no	Validated by TenantExists.

RESPONSES

200 — `data` : PurchaseOrder

`id` integer `company_id` integer `number` string `status` enum PurchaseOrderStatus | null `supplier_id` integer `supplier` object | null `requisition_id` integer | null `requisition` object | null `branch_id` integer | null `order_date` string(date) | null `expected_date` string(date) | null `currency` string `subtotal` Money (string) `discount_total` Money (string) `tax_total` Money (string) `shipping_cost` Money (string) `total` Money (string)

`warehouse_id` integer | null `warehouse` object | null `delivery_address` string | null `payment_terms_days` integer
`notes` string | null `terms` string | null `created_by` integer | null `creator` object | null ...aur 13 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

---

PATCH `/api/v1/purchase-orders/{purchase_order}`

Update purchase order `purchaseOrdersUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /purchase-orders/{purchase_order}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `purchase_orders.manage`

DELETE `/api/v1/purchase-orders/{purchase_order}`

Delete purchase order `purchaseOrdersDestroy`

Purchase order delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission Policy: `purchase_orders.manage` (delete on PurchaseOrder)
Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_order	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

---

POST `/api/v1/goods-receipts/{goods_receipt}/confirm`

Confirm – goods receipt `goodsReceiptsConfirm`

Goods receipt ko confirm karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission Route: `goods_receipts.manage` · Policy: `goods_receipts.manage` (confirm on GoodsReceipt)
Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
goods_receipt	path	string	yes	

RESPONSES

200 — `data` : GoodsReceipt

`id` integer `company_id` integer `number` string `status` enum GoodsReceiptStatus | null `purchase_order_id` integer
`purchase_order` object | null `received_date` string(date) | null `warehouse_id` integer | null `warehouse` object | null
`received_by` integer | null `receiver` object | null `supplier_delivery_note` string | null `notes` string | null
`confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` GoodsReceiptLine[] `lines_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/goods-receipts/{goods_receipt}/cancel

Cancel – goods receipt goodsReceiptsCancel

Goods receipt ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `goods_receipts.manage` (cancel on GoodsReceipt)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
goods_receipt	path	string	yes	

RESPONSES

200 — `data` : GoodsReceipt

`id` integer `company_id` integer `number` string `status` enum GoodsReceiptStatus | null `purchase_order_id` integer `purchase_order` object | null `received_date` string(date) | null `warehouse_id` integer | null `warehouse` object | null `received_by` integer | null `receiver` object | null `supplier_delivery_note` string | null `notes` string | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` GoodsReceiptLine[] `lines_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/goods-receipts`

List goods receipts `goodsReceiptsIndex`

Goods receipts ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `supplier_delivery_note` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `purchase_orders.view` / `goods_receipts.manage` (viewAny on GoodsReceipt)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum GoodsReceiptStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `confirmed`, `cancelled`
`filter[purchase_order_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[received_by]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `received_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `received_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-received_date`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `received_date`, `-received_date`, `status`, `-status`, `created_at`, `-created_at` · default `-received_date`

RESPONSES

200 — `data` : array of GoodsReceipt + `meta.pagination`

`id` integer `company_id` integer `number` string `status` enum GoodsReceiptStatus | null `purchase_order_id` integer `purchase_order` object | null `received_date` string(date) | null `warehouse_id` integer | null `warehouse` object | null `received_by` integer | null `receiver` object | null `supplier_delivery_note` string | null `notes` string | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` GoodsReceiptLine[] `lines_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/goods-receipts/{goods_receipt}

Get goods receipt goodsReceiptsShow

Ek goods receipt ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `purchase_orders.view` / `goods_receipts.manage` (view on GoodsReceipt)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
goods_receipt	path	string	yes	

RESPONSES

200 — `data` : GoodsReceipt

`id` integer `company_id` integer `number` string `status` enum GoodsReceiptStatus | null `purchase_order_id` integer `purchase_order` object | null `received_date` string(date) | null `warehouse_id` integer | null `warehouse` object | null `received_by` integer | null `receiver` object | null `supplier_delivery_note` string | null `notes` string | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` GoodsReceiptLine[] `lines_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/goods-receipts/{goods_receipt}

Update goods receipt goodsReceiptsUpdate

Maujooda goods receipt ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `goods_receipts.manage` (update on GoodsReceipt)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
goods_receipt	path	string	yes	

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
lines	object[]	yes	minItems 1 · maxItems 200
lines[].batch_number	string | null	no	maxLength 60
lines[].expires_at	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lines[].purchase_order_line_id	integer	no	min 1
lines[].quantity_received	string | number	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].quantity_rejected	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].rejection_reason	string | null	no	maxLength 255
notes	string | null	no	maxLength 2000
received_date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
supplier_delivery_note	string | null	no	maxLength 100
warehouse_id	integer | null	no	Validated by TenantExists.

RESPONSES

200 — `data` : GoodsReceipt

`id` integer `company_id` integer `number` string `status` enum GoodsReceiptStatus | null `purchase_order_id` integer `purchase_order` object | null `received_date` string(date) | null `warehouse_id` integer | null `warehouse` object | null `received_by` integer | null `receiver` object | null `supplier_delivery_note` string | null `notes` string | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` GoodsReceiptLine[] `lines_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/goods-receipts/{goods_receipt}

Update goods receipt goodsReceiptsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /goods-receipts/{goods_receipt} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission goods_receipts.manage

DELETE /api/v1/goods-receipts/{goods_receipt}

Delete goods receipt goodsReceiptsDestroy

Goods receipt delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: goods_receipts.manage (delete on GoodsReceipt)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
goods_receipt	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/purchase-returns/{purchase_return}/confirm

Confirm – purchase return purchaseReturnsConfirm

Purchase return ko confirm karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: goods_receipts.manage · Policy: goods_receipts.manage (confirm on PurchaseReturn)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_return	path	string	yes	

RESPONSES

200 — data : PurchaseReturn

id integer company_id integer number string status enum PurchaseReturnStatus | null reason enum PurchaseReturnReason | null purchase_order_id integer purchase_order object | null goods_receipt_id integer | null goods_receipt object | null return_date string(date) | null notes string | null total Money (string) created_by integer | null confirmed_at string(date-time) | null cancelled_at string(date-time) | null lines PurchaseReturnLine[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

POST /api/v1/purchase-returns/{purchase_return}/cancel

Cancel – purchase return purchaseReturnsCancel

Purchase return ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `goods_receipts.manage` (cancel on PurchaseReturn)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_return	path	string	yes	

RESPONSES

200 — `data` : PurchaseReturn

`id` integer `company_id` integer `number` string `status` enum PurchaseReturnStatus | null `reason` enum PurchaseReturnReason | null `purchase_order_id` integer `purchase_order` object | null `goods_receipt_id` integer | null `goods_receipt` object | null `return_date` string(date) | null `notes` string | null `total` Money (string) `created_by` integer | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` PurchaseReturnLine[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/purchase-returns`

List purchase returns `purchaseReturnsIndex`

Purchase returns ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `notes` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `purchase_orders.view` / `goods_receipts.manage` (viewAny on PurchaseReturn)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum PurchaseReturnStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `confirmed`, `cancelled`
`filter[reason]`	query	enum PurchaseReturnReason	no	Exact-match filter (comma-separated = koi bhi value). · values: `damaged`, `wrong_item`, `quality`, `excess`, `other`
`filter[purchase_order_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[goods_receipt_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `return_date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `return_date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-return_date`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `return_date`, `-return_date`, `status`, `-status`, `total`, `-total`, `created_at`, `-created_at` · default `-return_date`

RESPONSES

200 — `data` : array of PurchaseReturn + `meta.pagination`

`id` integer `company_id` integer `number` string `status` enum PurchaseReturnStatus | null `reason` enum PurchaseReturnReason | null `purchase_order_id` integer `purchase_order` object | null `goods_receipt_id` integer | null `goods_receipt` object | null `return_date` string(date) | null `notes` string | null `total` Money (string) `created_by` integer | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` PurchaseReturnLine[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/purchase-returns

Create purchase return purchaseReturnsStore

Naya purchase return banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `goods_receipts.manage` (create on PurchaseReturn)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
goods_receipt_id	integer | null	no	Validated by TenantExists.
lines	object[]	yes	minItems 1 · maxItems 200
lines[].purchase_order_line_id	integer	no	min 1
lines[].quantity	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].unit_cost	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
notes	string | null	no	maxLength 2000
purchase_order_id	integer	yes	Validated by TenantExists.
reason	enum PurchaseReturnReason	yes	values: damaged, wrong_item, quality, excess, other
return_date	string(date)	yes	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.

EXAMPLE REQUEST

```
{
  "goods_receipt_id": 1,
  "lines": [{"purchase_order_line_id":1,"quantity":"2.0000","unit_cost":"1250.0000"}],
  "notes": "Sample text",
  "purchase_order_id": 1,
  "reason": "damaged",
  "return_date": "2026-10-15"
}
```

RESPONSES

201 — `data` : PurchaseReturn

`id` integer `company_id` integer `number` string `status` enum PurchaseReturnStatus | null `reason` enum PurchaseReturnReason | null `purchase_order_id` integer `purchase_order` object | null `goods_receipt_id` integer | null `goods_receipt` object | null `return_date` string(date) | null `notes` string | null `total` Money (string) `created_by` integer | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` PurchaseReturnLine[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/purchase-returns/{purchase_return}`

Get purchase return `purchaseReturnsShow`

Ek purchase return ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `purchase_orders.view` / `goods_receipts.manage` (view on PurchaseReturn)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_return	path	string	yes	

RESPONSES

200 — `data` : PurchaseReturn

`id` integer `company_id` integer `number` string `status` enum PurchaseReturnStatus | null `reason` enum PurchaseReturnReason | null `purchase_order_id` integer `purchase_order` object | null `goods_receipt_id` integer | null `goods_receipt` object | null `return_date` string(date) | null `notes` string | null `total` Money (string) `created_by` integer | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` PurchaseReturnLine[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/purchase-returns/{purchase_return}

Update purchase return purchaseReturnsUpdate

Maujooda purchase return ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `goods_receipts.manage` (update on PurchaseReturn)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_return	path	string	yes	

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
goods_receipt_id	integer | null	no	Validated by TenantExists.
lines	object[]	yes	minItems 1 · maxItems 200
lines[].purchase_order_line_id	integer	no	min 1
lines[].quantity	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].unit_cost	string | number | null	no	min 0 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
notes	string | null	no	maxLength 2000
purchase_order_id	integer	no	Prohibited. Validated by TenantExists.
reason	enum PurchaseReturnReason	no	values: damaged, wrong_item, quality, excess, other
return_date	string(date)	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.

RESPONSES

200 — `data` : PurchaseReturn

`id` integer `company_id` integer `number` string `status` enum PurchaseReturnStatus | null `reason` enum PurchaseReturnReason | null `purchase_order_id` integer `purchase_order` object | null `goods_receipt_id` integer | null `goods_receipt` object | null `return_date` string(date) | null `notes` string | null `total` Money (string) `created_by` integer | null `confirmed_at` string(date-time) | null `cancelled_at` string(date-time) | null `lines` PurchaseReturnLine[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/purchase-returns/{purchase_return}

Update purchase return purchaseReturnsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /purchase-returns/{purchase_return} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission goods_receipts.manage

DELETE /api/v1/purchase-returns/{purchase_return}

Delete purchase return purchaseReturnsDestroy

Purchase return delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: goods_receipts.manage (delete on PurchaseReturn)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
purchase_return	path	string	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/procurement/reports/spend

Spend – report procurementReportsSpend

Spend report ka data JSON mein deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Route: reports.view

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
from	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
group_by	query	string | null	no	values: supplier, month, department,
supplier_id	query	integer | null	no	min 1
to	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:from.

RESPONSES

200 — data : object + meta { from , to , group_by , currency } shape inferred from code

group_by string rows object[] total Decimal (string) order_count number

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

GET /api/v1/procurement/reports/status-summary

Status summary – report `procurementReportsStatusSummary`

Status summary report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.view`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`from`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`group_by`	query	string | null	no	values: `supplier`, `month`, `department`,
`supplier_id`	query	integer | null	no	min 1
`to`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:from`.

RESPONSES

200 — `data` : object + `meta` { `from` , `to` , `currency` } shape inferred from code

`purchase_orders` object[] `requisitions` object[] `avg_requisition_approval_hours` number | null `on_time_receipt` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/procurement/reports/supplier-performance

Supplier performance – report `procurementReportsSupplierPerformance`

Supplier performance report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Route: `reports.view`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`from`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`group_by`	query	string | null	no	values: `supplier`, `month`, `department`,
`supplier_id`	query	integer | null	no	min 1
`to`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:from`.

RESPONSES

200 — `data` : array of objects + `meta` { `from` , `to` , `currency` } shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Inventory

Products, categories, units of measure, warehouses, storage locations, stock levels/movements, stock receive/issue, adjustments aur transfers. Agar outbound movement available stock se zyada ho to `409 inventory.insufficient_stock` milta hai (`details` mein figures hote hain).

Spec: Products, categories, units, warehouses, locations, stock levels/movements, adjustments, transfers. — 60 operations.

Method	Path	Summary	Permission
GET	/units-of-measure	List units of measure	products.view
POST	/units-of-measure	Create units of measure	products.manage
GET	/units-of-measure/{unit_of_measure}	Get units of measure	products.view
PUT	/units-of-measure/{unit_of_measure}	Update units of measure	products.manage
PATCH	/units-of-measure/{unit_of_measure}	Update units of measure	products.manage
DELETE	/units-of-measure/{unit_of_measure}	Delete units of measure	products.manage
GET	/product-categories/tree	Category tree; active categories only unless include_inactive=1.	products.view
GET	/product-categories	List product categories	products.view
POST	/product-categories	Create product category	products.manage
GET	/product-categories/{product_category}	Get product category	products.view
PUT	/product-categories/{product_category}	Update product category	products.manage
PATCH	/product-categories/{product_category}	Update product category	products.manage
DELETE	/product-categories/{product_category}	Delete product category	products.manage
GET	/products/low-stock	Low stock – product	products.view
GET	/products	List products	products.view
POST	/products	Create product	products.manage
GET	/products/{product}	Get product	products.view
PUT	/products/{product}	Update product	products.manage
PATCH	/products/{product}	Update product	products.manage
DELETE	/products/{product}	Delete product	products.manage
POST	/products/{product}/image	Create image	products.manage
DELETE	/products/{product}/image	removes the stored image file and clears the path.	products.manage
GET	/products/{product}/batches	Batches – product	inventory.view products.view
GET	/products/{product}/stock	Stock per warehouse / location for one product.	inventory.view products.view
GET	/products/{product}/movements	Paginated movement history for one product.	inventory.view products.view
GET	/warehouses/all	All – warehouse	warehouses.view
GET	/warehouses	List warehouses	warehouses.view
POST	/warehouses	Create warehouse	warehouses.manage

Method	Path	Summary	Permission
GET	/warehouses/{warehouse}	Get warehouse	warehouses.view
PUT	/warehouses/{warehouse}	Update warehouse	warehouses.manage
PATCH	/warehouses/{warehouse}	Update warehouse	warehouses.manage
DELETE	/warehouses/{warehouse}	Delete warehouse	warehouses.manage
GET	/warehouses/{warehouse}/locations	List locations	warehouses.view
POST	/warehouses/{warehouse}/locations	Create location	warehouses.manage
GET	/locations/{location}	Get location	warehouses.view
PUT	/locations/{location}	Update location	warehouses.manage
PATCH	/locations/{location}	Update location	warehouses.manage
DELETE	/locations/{location}	Delete location	warehouses.manage
POST	/stock/receive	Receive – stock	inventory.receive
POST	/stock/issue	Issue – stock	inventory.issue
GET	/stock/levels	Stock per product × warehouse (× location).	inventory.view
GET	/stock/movements	Company-wide movement history.	inventory.view
GET	/stock-transfers	List stock transfers	inventory.view inventory.transfer
POST	/stock-transfers	Create stock transfer	inventory.transfer
GET	/stock-transfers/{stock_transfer}	Get stock transfer	inventory.view inventory.transfer
PUT	/stock-transfers/{stock_transfer}	Update stock transfer	inventory.transfer
PATCH	/stock-transfers/{stock_transfer}	Update stock transfer	inventory.transfer
DELETE	/stock-transfers/{stock_transfer}	Delete stock transfer	inventory.transfer
POST	/stock-transfers/{stock_transfer}/ship	Ship – stock transfer	inventory.transfer
POST	/stock-transfers/{stock_transfer}/receive	Receive – stock transfer	inventory.transfer
POST	/stock-transfers/{stock_transfer}/cancel	Cancel – stock transfer	inventory.transfer
GET	/stock-adjustments	List stock adjustments	inventory.view inventory.adjust
POST	/stock-adjustments	Create stock adjustment	inventory.adjust
GET	/stock-adjustments/{stock_adjustment}	Get stock adjustment	inventory.view inventory.adjust
PUT	/stock-adjustments/{stock_adjustment}	Update stock adjustment	inventory.adjust
PATCH	/stock-adjustments/{stock_adjustment}	Update stock adjustment	inventory.adjust
DELETE	/stock-adjustments/{stock_adjustment}	Delete stock adjustment	inventory.adjust
POST	/stock-adjustments/{stock_adjustment}/post	Post – stock adjustment	inventory.adjust
GET	/inventory/reports/valuation	Valuation – report	inventory.view
GET	/inventory/reports/movement-summary	Movement summary – report	inventory.view

Endpoints

GET /api/v1/units-of-measure

List units of measure unitsOfMeasureIndex

Units of measure ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , symbol .

Auth Session cookie · X-Company-Id **required**

Permission Policy: products.view (viewAny on UnitOfMeasure)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, symbol, -symbol, created_at, -created_at · default name

RESPONSES

200 — data : array of UnitOfMeasure + meta.pagination

id integer company_id integer name string symbol string precision integer is_active boolean products_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/units-of-measure

Create units of measure unitsOfMeasureStore

Naya units of measure banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: products.manage (create on UnitOfMeasure)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
is_active	boolean	no	
name	string	**yes**	maxLength 60
precision	integer	no	min 0 · max 4
symbol	string	**yes**	maxLength 12 · Must be unique within units_of_measure (per company).

EXAMPLE REQUEST

```
{"is_active":true,"name":"Sample name","precision":1,"symbol":"string"}
```

RESPONSES

201 — data : UnitOfMeasure

id integer company_id integer name string symbol string precision integer is_active boolean products_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/units-of-measure/{unit_of_measure}

Get units of measure `unitsOfMeasureShow`

Ek units of measure ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `products.view` (view on UnitOfMeasure)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`unit_of_measure`	path	string	yes	

RESPONSES

200 — `data` : UnitOfMeasure

`id` integer `company_id` integer `name` string `symbol` string `precision` integer `is_active` boolean `products_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/units-of-measure/{unit_of_measure}

Update units of measure `unitsOfMeasureUpdate`

Maujooda units of measure ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `products.manage` (update on UnitOfMeasure)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`unit_of_measure`	path	string	yes	

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`is_active`	boolean	no	
`name`	string	no	maxLength 60
`precision`	integer	no	min 0 · max 4
`symbol`	string	no	maxLength 12 · Must be unique within `units_of_measure` (per company).

RESPONSES

200 — `data` : UnitOfMeasure

`id` integer `company_id` integer `name` string `symbol` string `precision` integer `is_active` boolean `products_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/units-of-measure/{unit_of_measure}

Update units of measure unitsOfMeasureUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /units-of-measure/{unit_of_measure} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission products.manage

DELETE /api/v1/units-of-measure/{unit_of_measure}

Delete units of measure unitsOfMeasureDestroy

Units of measure delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: products.manage (delete on UnitOfMeasure)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
unit_of_measure	path	string	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/product-categories/tree

Category tree; active categories only unless include_inactive=1. productCategoriesTree

Product categories ka tree deta hai; sirf active categories, jab tak include_inactive=1 na ho.

Auth Session cookie · X-Company-Id **required**

Permission Policy: products.view (viewAny on ProductCategory)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
include_inactive	query	boolean	no	

RESPONSES

200 — data: array of object shape inferred from code

id integer name string code string is_active boolean products_count integer children any[]

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/product-categories

List product categories productCategoriesIndex

Product categories ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , code .

Auth Session cookie · X-Company-Id **required**

Permission Policy: products.view (viewAny on ProductCategory)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[parent_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, created_at, -created_at · default name

RESPONSES

200 — data : array of ProductCategory + meta.pagination

id integer company_id integer parent_id integer | null parent object | null name string code string is_active boolean children_count integer products_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/product-categories

Create product category productCategoriesStore

Naya product category banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: products.manage (create on ProductCategory)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
code	string	**yes**	maxLength 30 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within product_categories (per company).
is_active	boolean	no	
name	string	**yes**	maxLength 120
parent_id	integer | null	no	Validated by TenantExists.

EXAMPLE REQUEST

```
{"code":"CODE-001","is_active":true,"name":"Sample name","parent_id":1}
```

RESPONSES

201 — data : ProductCategory

id integer company_id integer parent_id integer | null parent object | null name string code string is_active boolean children_count integer products_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/product-categories/{product_category}

Get product category `productCategoriesShow`

Ek product category ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `products.view` (view on ProductCategory)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`product_category`	path	string	yes	

RESPONSES

200 — `data` : ProductCategory

`id` integer `company_id` integer `parent_id` integer | null `parent` object | null `name` string `code` string `is_active` boolean `children_count` integer `products_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/product-categories/{product_category}

Update product category `productCategoriesUpdate`

Maujooda product category ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `products.manage` (update on ProductCategory)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`product_category`	path	string	yes	

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`code`	string	no	maxLength 30 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `product_categories` (per company).
`is_active`	boolean	no	
`name`	string	no	maxLength 120
`parent_id`	integer	null	no	Validated by `TenantExists`.

RESPONSES

200 — `data` : ProductCategory

`id` integer `company_id` integer `parent_id` integer | null `parent` object | null `name` string `code` string `is_active` boolean `children_count` integer `products_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/product-categories/{product_category}

Update product category productCategoriesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /product-categories/{product_category}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `products.manage`

DELETE /api/v1/product-categories/{product_category}

Delete product category productCategoriesDestroy

Product category delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `products.manage` (delete on ProductCategory)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
product_category	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET `/api/v1/products/low-stock`

Low stock – product `productsLowStock`

Woh products deta hai jin ka stock low hai.

Products whose total on-hand is at or below their (non-zero) reorder level. Defaults to active goods; `filter[type]` / `filter[is_active]` override those defaults.
`search` matches (case-insensitive, substring): `sku`, `name`.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `products.view` (viewAny on Product)
Throttle	`api`
List params	`page`, `per_page`, `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[category_id]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[type]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (`name`). The primary key is always appended as a tie-breaker. · values: `sku`, `-sku`, `name`, `-name`, `reorder_level`, `-reorder_level` · default `name`

RESPONSES

200 — `data` : array of Product + `meta.pagination`

`id` integer `company_id` integer `sku` string `barcode` string | null `name` string `description` string | null `type` enum ProductType `category_id` integer | null `category` object | null `uom_id` integer | null `uom` object | null `cost_price` Money (string) `sale_price` Money (string) `currency` string `tax_rate` Decimal (string) | null `reorder_level` Decimal (string) `reorder_quantity` Decimal (string) `track_batches` boolean `track_serials` boolean `is_active` boolean `image_url` string(uri) | null `attributes` object `quantity_on_hand` Decimal (string) `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/products

List products productsIndex

Products ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): sku , name , barcode .

Auth Session cookie · X-Company-Id **required**

Permission Policy: products.view (viewAny on Product)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[type]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[category_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[uom_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[track_batches]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[track_serials]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: sku, -sku, name, -name, sale_price, -sale_price, cost_price, -cost_price, created_at, -created_at · default name

RESPONSES

200 — data : array of Product + meta.pagination

id integer company_id integer sku string barcode string | null name string description string | null type enum ProductType category_id integer | null category object | null uom_id integer | null uom object | null cost_price Money (string) sale_price Money (string) currency string tax_rate Decimal (string) | null reorder_level Decimal (string) reorder_quantity Decimal (string) track_batches boolean track_serials boolean is_active boolean image_url string(uri) | null attributes object quantity_on_hand Decimal (string) created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/products

Create product productsStore

Naya product banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: products.manage (create on Product)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
attributes	any[] | null	no	maxItems 50
barcode	string | null	no	maxLength 64
category_id	integer | null	no	Validated by TenantExists.
cost_price	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
currency	string	no	minLength 3 · maxLength 3

Field	Type	Req.	Constraints / notes
`description`	string | null	no	maxLength 1000
`is_active`	boolean	no	
`name`	string	**yes**	maxLength 200
`reorder_level`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`reorder_quantity`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`sale_price`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`sku`	string	**yes**	maxLength 60 · Must be unique within `products` (per company).
`tax_rate`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`track_batches`	boolean	no	
`track_serials`	boolean	no	
`type`	enum ProductType	no	values: `goods`, `service`
`uom_id`	integer | null	no	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "name": "Sample name",
  "sku": "CODE-001",
  "attributes": ["string"],
  "barcode": "string",
  "category_id": 1,
  "cost_price": "1250.0000",
  "currency": "PKR",
  "description": "Sample text"
}
```

RESPONSES

201 — `data` : Product

`id` integer `company_id` integer `sku` string `barcode` string | null `name` string `description` string | null `type` enum ProductType `category_id` integer | null `category` object | null `uom_id` integer | null `uom` object | null `cost_price` Money (string) `sale_price` Money (string) `currency` string `tax_rate` Decimal (string) | null `reorder_level` Decimal (string) `reorder_quantity` Decimal (string) `track_batches` boolean `track_serials` boolean `is_active` boolean `image_url` string(uri) | null `attributes` object `quantity_on_hand` Decimal (string) `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/products/{product}`

Get product `productsShow`

Ek product ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `products.view` (view on Product)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`product`	path	integer	**yes**	ID of the Product. · min 1

RESPONSES

200 — `data` : Product

`id` integer `company_id` integer `sku` string `barcode` string | null `name` string `description` string | null `type` enum ProductType `category_id` integer | null `category` object | null `uom_id` integer | null `uom` object | null `cost_price` Money (string) `sale_price` Money (string) `currency` string `tax_rate` Decimal (string) | null `reorder_level` Decimal (string) `reorder_quantity` Decimal (string) `track_batches` boolean `track_serials` boolean `is_active` boolean `image_url` string(uri) | null `attributes` object `quantity_on_hand` Decimal (string) `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/products/{product}

Update product productsUpdate

Maujooda product ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `products.manage` (update on Product)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`product`	path	integer	**yes**	ID of the Product. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`attributes`	any[] | null	no	maxItems 50
`barcode`	string | null	no	maxLength 64
`category_id`	integer | null	no	Validated by `TenantExists`.
`cost_price`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`currency`	string	no	minLength 3 · maxLength 3
`description`	string | null	no	maxLength 1000
`is_active`	boolean	no	
`name`	string	no	maxLength 200
`reorder_level`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`reorder_quantity`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`sale_price`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`sku`	string	no	maxLength 60 · Must be unique within `products` (per company).
`tax_rate`	string | number | null	no	min 0 · max 100 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`track_batches`	boolean	no	
`track_serials`	boolean	no	
`type`	enum ProductType	no	values: `goods`, `service`
`uom_id`	integer | null	no	Validated by `TenantExists`.

RESPONSES

200 — `data`: Product

`id` integer `company_id` integer `sku` string `barcode` string | null `name` string `description` string | null `type` enum ProductType `category_id` integer | null `category` object | null `uom_id` integer | null `uom` object | null `cost_price` Money (string) `sale_price` Money (string) `currency` string `tax_rate` Decimal (string) | null `reorder_level` Decimal (string) `reorder_quantity` Decimal (string) `track_batches` boolean `track_serials` boolean `is_active` boolean `image_url` string(uri) | null `attributes` object `quantity_on_hand` Decimal (string) `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/products/{product}

Update product productsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /products/{product} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission products.manage

DELETE /api/v1/products/{product}

Delete product productsDestroy

Product delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: products.manage (delete on Product)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
product	path	integer	yes	ID of the Product. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/products/{product}/image

Create image productsImageStore

Naya image banata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: products.manage (update on Product)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
product	path	integer	yes	ID of the Product. · min 1

REQUEST BODY multipart/form-data

Field	Type	Req.	Constraints / notes
image	string(binary)	yes	Image file. Allowed types: png, jpg, jpeg, webp. Max size … KB.

RESPONSES

200 — data : Product

id integer company_id integer sku string barcode string | null name string description string | null type enum ProductType
category_id integer | null category object | null uom_id integer | null uom object | null cost_price Money (string)
sale_price Money (string) currency string tax_rate Decimal (string) | null reorder_level Decimal (string)
reorder_quantity Decimal (string) track_batches boolean track_serials boolean is_active boolean
image_url string(uri) | null attributes object quantity_on_hand Decimal (string) created_at string(date-time) | null
updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

DELETE /api/v1/products/{product}/image

removes the stored image file and clears the path. productsImageDestroy

Image delete karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `products.manage` · Policy: `products.manage` (update on Product)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
product	path	integer	yes	ID of the Product. · min 1

RESPONSES

200 — `data` : Product

`id` integer `company_id` integer `sku` string `barcode` string | null `name` string `description` string | null `type` enum ProductType `category_id` integer | null `category` object | null `uom_id` integer | null `uom` object | null `cost_price` Money (string) `sale_price` Money (string) `currency` string `tax_rate` Decimal (string) | null `reorder_level` Decimal (string) `reorder_quantity` Decimal (string) `track_batches` boolean `track_serials` boolean `is_active` boolean `image_url` string(uri) | null `attributes` object `quantity_on_hand` Decimal (string) `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/products/{product}/batches

Batches – product productsBatches

Ek product ke batches deta hai.

> Batches of one product with expiry and on-hand per warehouse. On-hand is derived from the batch-tagged stock movements (receipts / issues that named the batch); issues that did not name a batch are not attributed to any batch.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` / `products.view` (viewStock on Product)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
product	path	integer	yes	ID of the Product. · min 1

RESPONSES

200 — `data` : array of object shape inferred from code

`id` integer `batch_number` string `manufactured_at` string(date) | null `expires_at` string(date) | null `is_expired` boolean `on_hand` Decimal (string) `warehouses` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET `/api/v1/products/{product}/stock`

Stock per warehouse / location for one product. `productsStock`

Ek product ka stock har warehouse / location ke hisaab se deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` / `products.view` (viewStock on Product)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`product`	path	integer	**yes**	ID of the Product. · min 1

RESPONSES

200 — `data`: array of StockLevel

`id` integer `product_id` integer `product` object `warehouse_id` integer `warehouse` object `location_id` integer | null `location` object | null `quantity_on_hand` Decimal (string) `quantity_reserved` Decimal (string) `quantity_available` Decimal (string) `average_cost` Money (string) `stock_value` Decimal (string) `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/products/{product}/movements

Paginated movement history for one product. productsMovements

Ek product ki stock movement history deta hai (paginated).

Auth Session cookie · X-Company-Id required

Permission Policy: inventory.view / products.view (viewStock on Product)

Throttle api

List params page, per_page (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
product	path	integer	yes	ID of the Product. · min 1
filter[warehouse_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[type]	query	enum StockMovementType	no	Exact-match filter (comma-separated = koi bhi value). · 11 values (Appendix B)
from	query	string(date)	no	Inclusive lower bound on moved_at (UTC day start).
to	query	string(date)	no	Inclusive upper bound on moved_at (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-moved_at). The primary key is always appended as a tie-breaker. · values: moved_at, -moved_at, id, -id · default -moved_at

RESPONSES

200 — data : array of StockMovement + meta.pagination

id integer company_id integer product_id integer product object warehouse_id integer warehouse object location_id integer | null batch_id integer | null batch object | null type enum StockMovementType quantity Decimal (string) unit_cost Money (string) total_cost Money (string) balance_after Money (string) reference_type string | null reference_id integer | null reason string | null moved_at string(date-time) | null created_by integer | null creator object | null created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

GET /api/v1/warehouses/all

All – warehouse warehousesAll

Saare warehouses ki list deta hai (selectors ke liye, bina pagination).

GET /warehouses/all — unpaginated picker list of active warehouses the user's branch restriction allows (id, name, code, is_default).

Auth Session cookie · X-Company-Id required

Permission Policy: warehouses.view (viewAny on Warehouse)

Throttle api

RESPONSES

200 — data : array of object shape inferred from code

id integer name string code string is_default boolean

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/warehouses

List warehouses warehousesIndex

Warehouses ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , code , city .

Auth Session cookie · X-Company-Id **required**

Permission Policy: warehouses.view (viewAny on Warehouse)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[is_default]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[branch_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[country]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, city, -city, created_at, -created_at · default name

RESPONSES

200 — data : array of Warehouse + meta.pagination

id integer company_id integer branch_id integer | null branch object | null name string code string address object latitude Decimal (string) | null longitude Decimal (string) | null is_active boolean is_default boolean locations_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/warehouses

Create warehouse warehousesStore

Naya warehouse banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `warehouses.manage` (create on Warehouse)

Throttle `api`

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200
address_line2	string | null	no	maxLength 200
branch_id	integer | null	no	Validated by AccessibleBranch.
city	string | null	no	maxLength 100
code	string	yes	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within warehouses (per company).
country	string | null	no	minLength 2 · maxLength 2
is_active	boolean	no	
is_default	boolean	no	
latitude	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
longitude	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	yes	maxLength 150
postal_code	string | null	no	maxLength 20
state	string | null	no	maxLength 100

EXAMPLE REQUEST

```
{
  "code": "CODE-001",
  "name": "Sample name",
  "address_line1": "Shahrah-e-Faisal, Karachi",
  "address_line2": "Shahrah-e-Faisal, Karachi",
  "branch_id": 1,
  "city": "Karachi",
  "country": "PK",
  "is_active": true
}
```

RESPONSES

201 — `data` : Warehouse

`id` integer `company_id` integer `branch_id` integer | null `branch` object | null `name` string `code` string `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `is_active` boolean `is_default` boolean `locations_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/warehouses/{warehouse}

Get warehouse `warehousesShow`

Ek warehouse ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `warehouses.view` (view on Warehouse)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
warehouse	path	integer	yes	ID of the Warehouse. · min 1

RESPONSES

200 — `data` : Warehouse

`id` integer `company_id` integer `branch_id` integer | null `branch` object | null `name` string `code` string `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `is_active` boolean `is_default` boolean `locations_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/warehouses/{warehouse}

Update warehouse warehousesUpdate

Maujooda warehouse ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `warehouses.manage` (update on Warehouse)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
warehouse	path	integer	yes	ID of the Warehouse. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200
address_line2	string | null	no	maxLength 200
branch_id	integer | null	no	Validated by AccessibleBranch.
city	string | null	no	maxLength 100
code	string	no	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within warehouses (per company).
country	string | null	no	minLength 2 · maxLength 2
is_active	boolean	no	
is_default	boolean	no	
latitude	string | number | null	no	min -90 · max 90 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
longitude	string | number | null	no	min -180 · max 180 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
name	string	no	maxLength 150
postal_code	string | null	no	maxLength 20
state	string | null	no	maxLength 100

RESPONSES

200 — `data`: Warehouse

`id` integer `company_id` integer `branch_id` integer | null `branch` object | null `name` string `code` string `address` object `latitude` Decimal (string) | null `longitude` Decimal (string) | null `is_active` boolean `is_default` boolean `locations_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/warehouses/{warehouse}

Update warehouse warehousesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /warehouses/{warehouse} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission warehouses.manage

DELETE /api/v1/warehouses/{warehouse}

Delete warehouse warehousesDestroy

Warehouse delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: warehouses.manage (delete on Warehouse)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
warehouse	path	integer	**yes**	ID of the Warehouse. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

`GET` `/api/v1/warehouses/{warehouse}/locations`

List locations `warehousesLocationsIndex`

Locations ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `code` , `name` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `warehouses.view` (view on Warehouse; viewAny on StorageLocation)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`warehouse`	path	integer	**yes**	ID of the Warehouse. · min 1
`filter[type]`	query	enum StorageLocationType	no	Exact-match filter (comma-separated = koi bhi value). · values: `zone`, `aisle`, `rack`, `bin`
`filter[is_active]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`filter[parent_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`code`). The primary key is always appended as a tie-breaker. · values: `code`, `-code`, `name`, `-name`, `type`, `-type`, `created_at`, `-created_at` · default `code`

RESPONSES

200 — `data` : array of StorageLocation + `meta.pagination`

`id` integer `company_id` integer `warehouse_id` integer `parent_id` integer | null `parent` object | null `code` string `name` string `type` enum StorageLocationType `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/warehouses/{warehouse}/locations

Create location `warehousesLocationsStore`

Naya location banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `warehouses.manage` (update on Warehouse; create on StorageLocation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
warehouse	path	integer	yes	ID of the Warehouse. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
code	string	yes	maxLength 30 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `storage_locations` (per company).
is_active	boolean	no	
name	string	yes	maxLength 120
parent_id	integer | null	no	Validated by `TenantExists`.
type	enum StorageLocationType	no	values: `zone`, `aisle`, `rack`, `bin`

EXAMPLE REQUEST

```
{"code":"CODE-001","is_active":true,"name":"Sample name","parent_id":1,"type":"zone"}
```

RESPONSES

201 — `data` : StorageLocation

`id` integer `company_id` integer `warehouse_id` integer `parent_id` integer | null `parent` object | null `code` string `name` string `type` enum StorageLocationType `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/locations/{location}

Get location `locationsShow`

Ek location ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `warehouses.view` (view on StorageLocation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
location	path	integer	yes	ID of the Storage Location. · min 1

RESPONSES

200 — `data` : StorageLocation

`id` integer `company_id` integer `warehouse_id` integer `parent_id` integer | null `parent` object | null `code` string `name` string `type` enum StorageLocationType `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/locations/{location}

Update location locationsUpdate

Maujooda location ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `warehouses.manage` (update on StorageLocation)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`location`	path	integer	**yes**	ID of the Storage Location. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`code`	string	no	maxLength 30 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `storage_locations` (per company).
`is_active`	boolean	no	
`name`	string	no	maxLength 120
`parent_id`	integer | null	no	Validated by `TenantExists`.
`type`	enum StorageLocationType	no	values: `zone`, `aisle`, `rack`, `bin`

RESPONSES

200 — `data` : StorageLocation

`id` integer `company_id` integer `warehouse_id` integer `parent_id` integer | null `parent` object | null `code` string `name` string `type` enum StorageLocationType `is_active` boolean `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/locations/{location}

Update location locationsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /locations/{location} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission warehouses.manage

DELETE /api/v1/locations/{location}

Delete location locationsDestroy

Location delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: warehouses.manage (delete on StorageLocation)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
location	path	integer	yes	ID of the Storage Location. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/stock/receive

Receive – stock stockReceive

Warehouse mein stock receive (inbound movement) darj karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: inventory.receive · Policy: inventory.receive (receive on StockMovement)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
lines	object[]	yes	minItems 1 · maxItems 200
lines[].batch_number	string | null	no	maxLength 60
lines[].expires_at	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lines[].manufactured_at	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
lines[].product_id	integer	no	Validated by TenantExists.
lines[].quantity	string | number	no	max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
lines[].serials	string[] | null	no	maxItems 1000
lines[].unit_cost	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
location_id	integer | null	no	Validated by TenantExists.
moved_at	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
reason	string | null	no	maxLength 200
warehouse_id	integer	yes	Validated by TenantExists.

EXAMPLE REQUEST

```
{
  "lines": [
    {
      "batch_number": "string",
      "expires_at": "2026-11-14",
      "manufactured_at": "2026-10-15",
      "product_id": 1,
      "quantity": "2.0000",
      "serials": ["string"],
      "unit_cost": "1250.0000"
    }
  ],
  "location_id": 1,
  "moved_at": "2026-10-15",
  "reason": "Sample text",
  "warehouse_id": 1
}
```

RESPONSES

201 — `data` : array of StockMovement

`id` integer `company_id` integer `product_id` integer `product` object `warehouse_id` integer `warehouse` object `location_id` integer | null `batch_id` integer | null `batch` object | null `type` enum StockMovementType `quantity` Decimal (string) `unit_cost` Money (string) `total_cost` Money (string) `balance_after` Money (string) `reference_type` string | null `reference_id` integer | null `reason` string | null `moved_at` string(date-time) | null `created_by` integer | null `creator` object | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

POST /api/v1/stock/issue

Issue – stock `stockIssue`

Warehouse se stock issue (outbound movement) karta hai; stock kam ho to `409` `inventory.insufficient_stock`.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `inventory.issue` · Policy: `inventory.issue` (issue on StockMovement)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`lines`	object[]	**yes**	minItems 1 · maxItems 200
`lines[].batch_id`	integer | null	no	Validated by `TenantExists`.
`lines[].product_id`	integer	no	Validated by `TenantExists`.
`lines[].quantity`	string | number	no	max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`.
`lines[].serials`	string[] | null	no	maxItems 1000
`location_id`	integer | null	no	Validated by `TenantExists`.
`moved_at`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`reason`	string | null	no	maxLength 200
`warehouse_id`	integer	**yes**	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "lines": [{"batch_id":1,"product_id":1,"quantity":"2.0000","serials":["string"]}],
  "location_id": 1,
  "moved_at": "2026-10-15",
  "reason": "Sample text",
  "warehouse_id": 1
}
```

RESPONSES

201 — `data` : array of StockMovement

`id` integer `company_id` integer `product_id` integer `product` object `warehouse_id` integer `warehouse` object `location_id` integer | null `batch_id` integer | null `batch` object | null `type` enum StockMovementType `quantity` Decimal (string) `unit_cost` Money (string) `total_cost` Money (string) `balance_after` Money (string) `reference_type` string | null `reference_id` integer | null `reason` string | null `moved_at` string(date-time) | null `created_by` integer | null `creator` object | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/stock/levels`

Stock per product × warehouse (× location). `stockLevels`

Stock levels deta hai: product × warehouse (× location).

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` (viewAny on StockLevel)

Throttle `api`

List params `page`, `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[product_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[location_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`category_id`	query	integer	no	
`below_reorder`	query	boolean	no	
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`product_id`). The primary key is always appended as a tie-breaker. · values: `quantity_on_hand`, `-quantity_on_hand`, `average_cost`, `-average_cost`, `updated_at`, `-updated_at`, `product_id`, `-product_id`, `warehouse_id`, `-warehouse_id` · default `product_id`

RESPONSES

200 — `data` : array of StockLevel + `meta.pagination`

`id` integer `product_id` integer `product` object `warehouse_id` integer `warehouse` object `location_id` integer | null `location` object | null `quantity_on_hand` Decimal (string) `quantity_reserved` Decimal (string) `quantity_available` Decimal (string) `average_cost` Money (string) `stock_value` Decimal (string) `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET `/api/v1/stock/movements`

Company-wide movement history. `stockMovements`

Poori company ki stock movement history deta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Policy: `inventory.view` (viewAny on StockMovement)
Throttle	`api`
List params	`page`, `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[product_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[location_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[type]`	query	enum StockMovementType	no	Exact-match filter (comma-separated = koi bhi value). · 11 values (Appendix B)
`filter[reference_type]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[reference_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[created_by]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `moved_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `moved_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-moved_at`). The primary key is always appended as a tie-breaker. · values: `moved_at`, `-moved_at`, `quantity`, `-quantity`, `id`, `-id` · default `-moved_at`

RESPONSES

200 — `data`: array of StockMovement + `meta.pagination`

`id` integer `company_id` integer `product_id` integer `product` object `warehouse_id` integer `warehouse` object `location_id` integer | null `batch_id` integer | null `batch` object | null `type` enum StockMovementType `quantity` Decimal (string) `unit_cost` Money (string) `total_cost` Money (string) `balance_after` Money (string) `reference_type` string | null `reference_id` integer | null `reason` string | null `moved_at` string(date-time) | null `created_by` integer | null `creator` object | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

`GET` `/api/v1/stock-transfers`

List stock transfers `stockTransfersIndex`

Stock transfers ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `notes` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` / `inventory.transfer` (viewAny on StockTransfer)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum StockTransferStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `in_transit`, `received`, `cancelled`
`filter[from_warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[to_warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `created_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `created_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-created_at`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `status`, `-status`, `created_at`, `-created_at`, `shipped_at`, `-shipped_at`, `received_at`, `-received_at` · default `-created_at`

RESPONSES

200 — `data` : array of StockTransfer + `meta.pagination`

`id` integer `company_id` integer `number` string `status` enum StockTransferStatus `from_warehouse_id` integer `from_warehouse` object `to_warehouse_id` integer `to_warehouse` object `notes` string | null `lines` object[] `lines_count` integer `shipped_at` string(date-time) | null `received_at` string(date-time) | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/stock-transfers

Create stock transfer stockTransfersStore

Naya stock transfer banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: inventory.transfer (create on StockTransfer)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
from_warehouse_id	integer	yes	Validated by TenantExists.
lines	object[]	yes	minItems 1 · maxItems 200
lines[].product_id	integer	no	Values must be distinct. Validated by TenantExists.
lines[].quantity	string | number	no	max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
notes	string | null	no	maxLength 1000
to_warehouse_id	integer	yes	different:from_warehouse_id. Validated by TenantExists.

EXAMPLE REQUEST

```
{
  "from_warehouse_id": 1,
  "lines": [{"product_id":1,"quantity":"2.0000"}],
  "notes": "Sample text",
  "to_warehouse_id": 2
}
```

RESPONSES

201 — data : StockTransfer

id integer company_id integer number string status enum StockTransferStatus from_warehouse_id integer from_warehouse object to_warehouse_id integer to_warehouse object notes string | null lines object[] lines_count integer shipped_at string(date-time) | null received_at string(date-time) | null created_by integer | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/stock-transfers/{stock_transfer}

Get stock transfer stockTransfersShow

Ek stock transfer ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` / `inventory.transfer` (view on StockTransfer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_transfer	path	string	yes	

RESPONSES

200 — `data` : StockTransfer

`id` integer `company_id` integer `number` string `status` enum StockTransferStatus `from_warehouse_id` integer `from_warehouse` object `to_warehouse_id` integer `to_warehouse` object `notes` string | null `lines` object[] `lines_count` integer `shipped_at` string(date-time) | null `received_at` string(date-time) | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/stock-transfers/{stock_transfer}

Update stock transfer stockTransfersUpdate

Maujooda stock transfer ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `inventory.transfer` (update on StockTransfer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_transfer	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
from_warehouse_id	integer	no	Validated by TenantExists.
lines	object[]	no	minItems 1 · maxItems 200
lines[].product_id	integer	no	Values must be distinct. Validated by TenantExists.
lines[].quantity	string | number	no	max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. gt:0.
notes	string | null	no	maxLength 1000
to_warehouse_id	integer	no	different:from_warehouse_id. Validated by TenantExists.

RESPONSES

200 — `data` : StockTransfer

`id` integer `company_id` integer `number` string `status` enum StockTransferStatus `from_warehouse_id` integer `from_warehouse` object `to_warehouse_id` integer `to_warehouse` object `notes` string | null `lines` object[] `lines_count` integer `shipped_at` string(date-time) | null `received_at` string(date-time) | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/stock-transfers/{stock_transfer}

Update stock transfer stockTransfersUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /stock-transfers/{stock_transfer} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission inventory.transfer

DELETE /api/v1/stock-transfers/{stock_transfer}

Delete stock transfer stockTransfersDestroy

Stock transfer delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: inventory.transfer (delete on StockTransfer)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_transfer	path	string	yes	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/stock-transfers/{stock_transfer}/ship

Ship – stock transfer stockTransfersShip

Stock transfer ko shipped mark karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: inventory.transfer · Policy: inventory.transfer (ship on StockTransfer)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_transfer	path	string	yes	

RESPONSES

200 — data : StockTransfer

id integer company_id integer number string status enum StockTransferStatus from_warehouse_id integer from_warehouse object to_warehouse_id integer to_warehouse object notes string | null lines object[] lines_count integer shipped_at string(date-time) | null received_at string(date-time) | null created_by integer | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/stock-transfers/{stock_transfer}/receive

Receive – stock transfer stockTransfersReceive

Stock transfer ki receiving record karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `inventory.transfer` · Policy: `inventory.transfer` (receive on StockTransfer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_transfer	path	string	yes	

RESPONSES

200 — `data` : StockTransfer

`id` integer `company_id` integer `number` string `status` enum StockTransferStatus `from_warehouse_id` integer `from_warehouse` object `to_warehouse_id` integer `to_warehouse` object `notes` string | null `lines` object[] `lines_count` integer `shipped_at` string(date-time) | null `received_at` string(date-time) | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/stock-transfers/{stock_transfer}/cancel

Cancel – stock transfer stockTransfersCancel

Stock transfer ko cancel karta hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `inventory.transfer` · Policy: `inventory.transfer` (cancel on StockTransfer)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_transfer	path	string	yes	

RESPONSES

200 — `data` : StockTransfer

`id` integer `company_id` integer `number` string `status` enum StockTransferStatus `from_warehouse_id` integer `from_warehouse` object `to_warehouse_id` integer `to_warehouse` object `notes` string | null `lines` object[] `lines_count` integer `shipped_at` string(date-time) | null `received_at` string(date-time) | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

`GET` `/api/v1/stock-adjustments`

List stock adjustments `stockAdjustmentsIndex`

Stock adjustments ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `number` , `notes` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` / `inventory.adjust` (viewAny on StockAdjustment)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[status]`	query	enum StockAdjustmentStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: `draft`, `posted`
`filter[reason]`	query	enum StockAdjustmentReason	no	Exact-match filter (comma-separated = koi bhi value). · values: `count`, `damage`, `loss`, `correction`, `expiry`
`filter[warehouse_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `created_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `created_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-created_at`). The primary key is always appended as a tie-breaker. · values: `number`, `-number`, `status`, `-status`, `reason`, `-reason`, `created_at`, `-created_at`, `posted_at`, `-posted_at` · default `-created_at`

RESPONSES

200 — `data` : array of StockAdjustment + `meta.pagination`

`id` integer `company_id` integer `number` string `status` enum StockAdjustmentStatus `reason` enum StockAdjustmentReason `warehouse_id` integer `warehouse` object `notes` string | null `lines` object[] `lines_count` integer `posted_at` string(date-time) | null `created_by` integer | null `posted_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST /api/v1/**stock-adjustments**

Create stock adjustment `stockAdjustmentsStore`

Naya stock adjustment banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `inventory.adjust` (create on StockAdjustment)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`lines`	object[]	**yes**	minItems 1 · maxItems 500
`lines[].counted_quantity`	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`lines[].product_id`	integer	no	Values must be distinct. Validated by `TenantExists`.
`lines[].unit_cost`	string | number | null	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
`notes`	string | null	no	maxLength 1000
`reason`	enum StockAdjustmentReason	**yes**	values: `count`, `damage`, `loss`, `correction`, `expiry`
`warehouse_id`	integer	**yes**	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "lines": [{"counted_quantity":"2.0000","product_id":1,"unit_cost":"1250.0000"}],
  "notes": "Sample text",
  "reason": "count",
  "warehouse_id": 1
}
```

RESPONSES

201 — `data` : StockAdjustment

`id` integer `company_id` integer `number` string `status` enum StockAdjustmentStatus `reason` enum StockAdjustmentReason `warehouse_id` integer `warehouse` object `notes` string | null `lines` object[] `lines_count` integer `posted_at` string(date-time) | null `created_by` integer | null `posted_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/stock-adjustments/{stock_adjustment}`

Get stock adjustment `stockAdjustmentsShow`

Ek stock adjustment ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` / `inventory.adjust` (view on StockAdjustment)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`stock_adjustment`	path	string	**yes**	

RESPONSES

200 — `data` : StockAdjustment

`id` integer `company_id` integer `number` string `status` enum StockAdjustmentStatus `reason` enum StockAdjustmentReason `warehouse_id` integer `warehouse` object `notes` string | null `lines` object[] `lines_count` integer `posted_at` string(date-time) | null `created_by` integer | null `posted_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/stock-adjustments/{stock_adjustment}

Update stock adjustment stockAdjustmentsUpdate

Maujooda stock adjustment ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `inventory.adjust` (update on StockAdjustment)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_adjustment	path	string	yes	

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
lines	object[]	no	minItems 1 · maxItems 500
lines[].counted_quantity	string | number	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
lines[].product_id	integer	no	Values must be distinct. Validated by TenantExists.
lines[].unit_cost	string | number | null	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding.
notes	string | null	no	maxLength 1000
reason	enum StockAdjustmentReason	no	values: count, damage, loss, correction, expiry
warehouse_id	integer	no	Validated by TenantExists.

RESPONSES

200 — `data`: StockAdjustment

`id` integer `company_id` integer `number` string `status` enum StockAdjustmentStatus `reason` enum StockAdjustmentReason `warehouse_id` integer `warehouse` object `notes` string | null `lines` object[] `lines_count` integer `posted_at` string(date-time) | null `created_by` integer | null `posted_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/stock-adjustments/{stock_adjustment}

Update stock adjustment stockAdjustmentsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /stock-adjustments/{stock_adjustment} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission inventory.adjust

DELETE /api/v1/stock-adjustments/{stock_adjustment}

Delete stock adjustment stockAdjustmentsDestroy

Stock adjustment delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: inventory.adjust (delete on StockAdjustment)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_adjustment	path	string	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

POST /api/v1/stock-adjustments/{stock_adjustment}/post

Post – stock adjustment stockAdjustmentsPost

Stock adjustment ko post karta hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: inventory.adjust · Policy: inventory.adjust (post on StockAdjustment)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
stock_adjustment	path	string	**yes**	

RESPONSES

200 — data : StockAdjustment

id integer company_id integer number string status enum StockAdjustmentStatus reason enum StockAdjustmentReason warehouse_id integer warehouse object notes string | null lines object[] lines_count integer posted_at string(date-time) | null created_by integer | null posted_by integer | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/inventory/reports/valuation

Valuation – report `inventoryReportsValuation`

Valuation report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` (viewAny on StockLevel)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
group_by	query	string | null	no	values: category,
warehouse_id	query	integer | null	no	

RESPONSES

200 — `data` : object shape inferred from code

`currency` string `as_of` string(date-time) `warehouses` object[] `total` object `categories` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

GET /api/v1/inventory/reports/movement-summary

Movement summary – report `inventoryReportsMovementSummary`

Movement summary report ka data JSON mein deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `inventory.view` (viewAny on StockMovement)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
from	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended.
group	query	string | null	no	values: day, month,
product_id	query	integer | null	no	
to	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (YYYY-MM-DD) recommended. after_or_equal:from.
warehouse_id	query	integer | null	no	

RESPONSES

200 — `data` : object shape inferred from code

`group` string `from` string(date-time) `to` string(date-time) `currency` string `rows` object[] `totals` object

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Projects

Projects, members, milestones, tasks (Kanban board, subtasks, move, comments), time entries aur project expenses. Overview aur summary endpoints dashboards ke liye aggregate data dete hain.

Spec: Projects, members, milestones, tasks, comments, time entries, expenses. — 47 operations.

Method	Path	Summary	Permission
GET	/projects/overview	Portfolio stats for the projects index page.	projects.view projects.manage tasks.view
GET	/projects/{project}/summary	Progress dashboard for one project.	projects.view projects.manage tasks.view
GET	/projects/{project}/time-summary	Time summary – project	projects.view projects.manage tasks.view
GET	/projects/{project}/board	Kanban board: columns per status with ordered top-level tasks.	projects.view projects.manage tasks.view
GET	/projects	List projects	projects.view projects.manage tasks.view
POST	/projects	Create project	projects.manage
GET	/projects/{project}	Get project	projects.view projects.manage tasks.view
PUT	/projects/{project}	Update project	projects.manage
PATCH	/projects/{project}	Update project	projects.manage
DELETE	/projects/{project}	Delete project	projects.manage
GET	/projects/{project}/members	List members	projects.view projects.manage tasks.view
POST	/projects/{project}/members	Create member	projects.manage
PUT	/projects/{project}/members/{member}	Update member	projects.manage
PATCH	/projects/{project}/members/{member}	Update member	projects.manage
DELETE	/projects/{project}/members/{member}	Delete member	projects.manage
GET	/projects/{project}/milestones	List milestones	projects.view projects.manage tasks.view
POST	/projects/{project}/milestones	Create milestone	projects.manage
GET	/milestones/{milestone}	Get milestone	projects.view projects.manage tasks.view
PUT	/milestones/{milestone}	Update milestone	projects.manage
PATCH	/milestones/{milestone}	Update milestone	projects.manage
DELETE	/milestones/{milestone}	Tasks keep existing; their milestone link is cleared (FK nullOnDelete).	projects.manage
GET	/my-tasks	Mine – task	tasks.view projects.view projects.manage

Method	Path	Summary	Permission
GET	/projects/{project}/tasks	List tasks	projects.view projects.manage tasks.view
POST	/projects/{project}/tasks	Create task	projects.manage tasks.manage
POST	/tasks/{task}/subtasks	Create subtask	projects.manage tasks.manage
PATCH	/tasks/{task}/move	Move – task	projects.manage tasks.manage
GET	/tasks/{task}	Get task	projects.view projects.manage tasks.view
PUT	/tasks/{task}	Update task	projects.manage tasks.manage
PATCH	/tasks/{task}	Update task	projects.manage tasks.manage
DELETE	/tasks/{task}	Delete task	projects.manage tasks.manage
GET	/tasks/{task}/comments	List comments	projects.view projects.manage tasks.view
POST	/tasks/{task}/comments	Create comment	projects.view projects.manage tasks.view
PUT	/tasks/{task}/comments/{comment}	Update comment	—
PATCH	/tasks/{task}/comments/{comment}	Update comment	—
DELETE	/tasks/{task}/comments/{comment}	Delete comment	projects.manage
GET	/time-entries	List time entries	time_entries.manage projects.view projects.manage
POST	/time-entries	Create time entry	time_entries.manage projects.manage
GET	/time-entries/{time_entry}	Get time entry	projects.view projects.manage time_entries.manage
PUT	/time-entries/{time_entry}	Update time entry	projects.manage time_entries.manage
PATCH	/time-entries/{time_entry}	Update time entry	projects.manage time_entries.manage
DELETE	/time-entries/{time_entry}	Delete time entry	projects.manage time_entries.manage
GET	/projects/{project}/expenses	List expenses	projects.view projects.manage
POST	/projects/{project}/expenses	Create expense	projects.manage
GET	/projects/{project}/expenses/{expense}	Get expense	projects.view projects.manage
PUT	/projects/{project}/expenses/{expense}	Update expense	projects.manage
PATCH	/projects/{project}/expenses/{expense}	Update expense	projects.manage

Method	Path	Summary	Permission
DELETE	/projects/{project}/expenses/{expense}	Delete expense	projects.manage

Endpoints

GET /api/v1/projects/overview

Portfolio stats for the projects index page. projectsOverview

Projects index page ke liye portfolio stats deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (viewAny on Project)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
status	query	enum ProjectStatus | null	no	

RESPONSES

200 — data : object shape inferred from code

totals object projects object[]

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

GET /api/v1/projects/{project}/summary

Progress dashboard for one project. projectsSummary

Ek project ka progress dashboard deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (view on Project)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	**yes**	ID of the Project. · min 1

RESPONSES

200 — data : object shape inferred from code

project object tasks object hours object budget object milestones object

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

GET /api/v1/projects/{project}/time-summary

Time summary – project `projectsTimeSummary`

Ek project ki time entries ka summary deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `tasks.view` (view on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1
`from`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`to`	query	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:from`.

RESPONSES

200 — `data` : object shape inferred from code

`project_id` integer `from` string(date) | null `to` string(date) | null `totals` object `by_user` object[] `by_task` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `422` validation.failed · `429` throttled

GET /api/v1/projects/{project}/board

Kanban board: columns per status with ordered top-level tasks. `projectsBoard`

Kanban board deta hai: har status ka column, tarteeb wale top-level tasks ke saath.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `tasks.view` (view on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1
`assignee_id`	query	integer | null	no	
`milestone_id`	query	integer | null	no	

RESPONSES

200 — `data` : object shape inferred from code

`project` object `columns` object[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `422` validation.failed · `429` throttled

GET /api/v1/projects

List projects projectsIndex

Projects ki list deta hai — results paginated hote hain (page , per_page).

search matches (case-insensitive, substring): name , number , code .

Auth Session cookie · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (viewAny on Project)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[status]	query	enum ProjectStatus	no	Exact-match filter (comma-separated = koi bhi value). · values: planning, active, on_hold, completed, cancelled
filter[priority]	query	enum Priority	no	Exact-match filter (comma-separated = koi bhi value). · values: low, medium, high, critical
filter[department_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[branch_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[manager_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[customer_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[is_billable]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-created_at). The primary key is always appended as a tie-breaker. · values: name, number, status, priority, start_date, due_date, created_at (prefix - = descending) · default -created_at

RESPONSES

200 — data : array of Project + meta.pagination

id integer number string name string code string | null description string | null customer_id integer | null department_id integer | null department object | null branch_id integer | null branch object | null manager_id integer | null manager UserSummary | null status enum ProjectStatus | null priority enum Priority | null start_date string(date) | null due_date string(date) | null completed_at string(date-time) | null budget Money (string) | null currency string color string | null is_billable boolean members ProjectMember[] members_count integer tasks_count integer done_tasks_count integer …aur 2 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/projects

Create project projectsStore

Naya project banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.manage (create on Project)

Throttle `api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`budget`	string | number | null	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 4 decimal places.
`code`	string | null	no	maxLength 30 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `projects` (per company).
`color`	string | null	no	pattern `^#[0-9A-Fa-f]{6}([0-9A-Fa-f]{2})?$`
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`customer_id`	integer | null	no	Custom validation applies.
`department_id`	integer | null	no	Validated by `TenantExists`.
`description`	string | null	no	maxLength 10000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:start_date`.
`is_billable`	boolean	no	
`manager_id`	integer | null	no	Validated by `CompanyMember`.
`name`	string	**yes**	maxLength 150
`priority`	enum Priority	no	values: `low`, `medium`, `high`, `critical`
`start_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`status`	enum ProjectStatus	no	values: `planning`, `active`, `on_hold`, `completed`, `cancelled`

EXAMPLE REQUEST

```
{
  "name": "Sample name",
  "branch_id": 1,
  "budget": "1250.0000",
  "code": "CODE-001",
  "color": "#4f46e5",
  "currency": "PKR",
  "customer_id": 1,
  "department_id": 1
}
```

RESPONSES

201 — `data` : Project

`id` integer `number` string `name` string `code` string | null `description` string | null `customer_id` integer | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `manager_id` integer | null `manager` UserSummary | null `status` enum ProjectStatus | null `priority` enum Priority | null `start_date` string(date) | null `due_date` string(date) | null `completed_at` string(date-time) | null `budget` Money (string) | null `currency` string `color` string | null `is_billable` boolean `members` ProjectMember[] `members_count` integer `tasks_count` integer `done_tasks_count` integer ...aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/projects/{project}

Get project projectsShow

Ek project ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `tasks.view` (view on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	yes	ID of the Project. · min 1

RESPONSES

200 — `data` : Project

`id` integer `number` string `name` string `code` string | null `description` string | null `customer_id` integer | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `manager_id` integer | null `manager` UserSummary | null `status` enum ProjectStatus | null `priority` enum Priority | null `start_date` string(date) | null `due_date` string(date) | null `completed_at` string(date-time) | null `budget` Money (string) | null `currency` string `color` string | null `is_billable` boolean `members` ProjectMember[] `members_count` integer `tasks_count` integer `done_tasks_count` integer …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/projects/{project}

Update project projectsUpdate

Maujooda project ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (update on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	yes	ID of the Project. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`branch_id`	integer | null	no	Validated by `AccessibleBranch`.
`budget`	string | number | null	no	min 0 · max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 4 decimal places.
`code`	string | null	no	maxLength 30 · pattern `^[A-Za-z0-9_-]+$` · Must be unique within `projects` (per company).
`color`	string | null	no	pattern `^#[0-9A-Fa-f]{6}([0-9A-Fa-f]{2})?$`
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`customer_id`	integer | null	no	Custom validation applies.
`department_id`	integer | null	no	Validated by `TenantExists`.
`description`	string | null	no	maxLength 10000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:start_date`.
`is_billable`	boolean	no	
`manager_id`	integer | null	no	Validated by `CompanyMember`.
`name`	string	no	maxLength 150
`priority`	enum Priority	no	values: `low`, `medium`, `high`, `critical`
`start_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`status`	enum ProjectStatus	no	values: `planning`, `active`, `on_hold`, `completed`, `cancelled`

RESPONSES

200 — `data` : Project

`id` integer `number` string `name` string `code` string | null `description` string | null `customer_id` integer | null `department_id` integer | null `department` object | null `branch_id` integer | null `branch` object | null `manager_id` integer | null `manager` UserSummary | null `status` enum ProjectStatus | null `priority` enum Priority | null `start_date` string(date) | null `due_date` string(date) | null `completed_at` string(date-time) | null `budget` Money (string) | null `currency` string `color` string | null `is_billable` boolean `members` ProjectMember[] `members_count` integer `tasks_count` integer `done_tasks_count` integer …aur 2 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/projects/{project}

Update project projectsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /projects/{project}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `projects.manage`

DELETE /api/v1/projects/{project}

Delete project projectsDestroy

Project delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (delete on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/projects/{project}/members

List members projectsMembersIndex

Members ki list deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `tasks.view` (view on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1

RESPONSES

200 — `data` : array of ProjectMember

`id` integer `project_id` integer `user_id` integer `user` UserSummary | null `role` string `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/projects/{project}/members

Create member projectsMembersStore

Naya member banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.manage (manageMembers on Project)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	yes	ID of the Project. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
role	enum ProjectMemberRole	no	values: manager, member, viewer
user_id	integer	yes	Validated by CompanyMember. Must be unique within project_members (per company).

EXAMPLE REQUEST

```
{"role":"manager","user_id":1}
```

RESPONSES

201 — data : ProjectMember

id integer project_id integer user_id integer user UserSummary | null role string created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

PUT /api/v1/projects/{project}/members/{member}

Update member projectsMembersUpdate

Maujooda member ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use sometimes).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.manage (manageMembers on Project)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	yes	ID of the Project. · min 1
member	path	integer	yes	ID of the Project Member. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
role	enum ProjectMemberRole	yes	values: manager, member, viewer

RESPONSES

200 — data : ProjectMember

id integer project_id integer user_id integer user UserSummary | null role string created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 422 validation.failed · 429 throttled

PATCH /api/v1/projects/{project}/members/{member}

Update member projectsMembersUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /projects/{project}/members/{member} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission projects.manage

DELETE /api/v1/projects/{project}/members/{member}

Delete member projectsMembersDestroy

Member delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.manage (manageMembers on Project)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	**yes**	ID of the Project. · min 1
member	path	integer	**yes**	ID of the Project Member. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 409 conflict · 419 auth.csrf · 429 throttled

GET /api/v1/projects/{project}/milestones

List milestones projectsMilestonesIndex

Milestones ki list deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (view on Project)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	**yes**	ID of the Project. · min 1

RESPONSES

200 — data: array of Milestone

id integer project_id integer name string description string | null due_date string(date) | null
status enum MilestoneStatus | null completed_at string(date-time) | null position integer tasks_count integer
created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/projects/{project}/milestones

Create milestone `projectsMilestonesStore`

Naya milestone banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (update on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`description`	string | null	no	maxLength 1000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`name`	string	**yes**	maxLength 150
`position`	integer	no	min 0 · max 100000
`status`	enum MilestoneStatus	no	values: `pending`, `completed`

EXAMPLE REQUEST

```
{
  "description": "Sample text",
  "due_date": "2026-11-14",
  "name": "Sample name",
  "position": 1,
  "status": "pending"
}
```

RESPONSES

201 — `data` : Milestone

`id` integer `project_id` integer `name` string `description` string | null `due_date` string(date) | null
`status` enum MilestoneStatus | null `completed_at` string(date-time) | null `position` integer `tasks_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/milestones/{milestone}

Get milestone milestonesShow

Ek milestone ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `tasks.view` (view on Milestone)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`milestone`	path	integer	yes	ID of the Milestone. · min 1

RESPONSES

200 — `data` : Milestone

`id` integer `project_id` integer `name` string `description` string | null `due_date` string(date) | null
`status` enum MilestoneStatus | null `completed_at` string(date-time) | null `position` integer `tasks_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/milestones/{milestone}

Update milestone milestonesUpdate

Maujooda milestone ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (update on Milestone)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`milestone`	path	integer	yes	ID of the Milestone. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`description`	string | null	no	maxLength 1000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`name`	string	no	maxLength 150
`position`	integer	no	min 0 · max 100000
`status`	enum MilestoneStatus	no	values: `pending`, `completed`

RESPONSES

200 — `data` : Milestone

`id` integer `project_id` integer `name` string `description` string | null `due_date` string(date) | null
`status` enum MilestoneStatus | null `completed_at` string(date-time) | null `position` integer `tasks_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/milestones/{milestone}

Update milestone `milestonesUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /milestones/{milestone}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `projects.manage`

DELETE /api/v1/milestones/{milestone}

Tasks keep existing; their milestone link is cleared (FK nullOnDelete). `milestonesDestroy`

Milestone delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (delete on Milestone)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`milestone`	path	integer	**yes**	ID of the Milestone. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/my-tasks

Mine – task tasksMine

Logged-in user ko assign shuda tasks deta hai (saare projects se).

Tasks assigned to the current user across all projects (open ones unless include_done=1).
search matches (case-insensitive, substring): title.

Auth Session cookie · X-Company-Id **required**

Permission Policy: tasks.view / projects.view / projects.manage (viewAny on Task)

Throttle api

List params page, per_page, search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
include_done	query	boolean	no	
filter[project_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[status]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[priority]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[assignee_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[milestone_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[parent_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
due	query	string	no	
from	query	string(date)	no	Inclusive lower bound on due_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on due_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-id). The primary key is always appended as a tie-breaker. · values: · default -id

RESPONSES

200 — data : array of Task + meta.pagination

id integer project_id integer project object | null parent_id integer | null milestone_id integer | null milestone object | null title string description string | null status enum TaskStatus | null priority enum Priority | null assignee_id integer | null assignee UserSummary | null reporter_id integer | null reporter UserSummary | null start_date string(date) | null due_date string(date) | null estimate_hours Decimal (string) | null position integer completed_at string(date-time) | null labels any[] subtasks Task[] subtasks_count integer comments_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

GET /api/v1/projects/{project}/tasks

List tasks projectsTasksIndex

Tasks ki list deta hai — results paginated hote hain (page , per_page).

Tasks of one project. Filters: filter[status|priority|assignee_id|milestone_id|parent_id], due=overdue|today|week|none, from/to (due date), top_level=1.
search matches (case-insensitive, substring): title .

Auth Session cookie · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (view on Project)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	yes	ID of the Project. · min 1
top_level	query	boolean	no	
filter[status]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[priority]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[assignee_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[milestone_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[parent_id]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
due	query	string	no	
from	query	string(date)	no	Inclusive lower bound on due_date (UTC day start).
to	query	string(date)	no	Inclusive upper bound on due_date (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-id). The primary key is always appended as a tie-breaker. · values: · default -id

RESPONSES

200 — data : array of Task + meta.pagination

id integer project_id integer project object | null parent_id integer | null milestone_id integer | null
milestone object | null title string description string | null status enum TaskStatus | null priority enum Priority | null
assignee_id integer | null assignee UserSummary | null reporter_id integer | null reporter UserSummary | null
start_date string(date) | null due_date string(date) | null estimate_hours Decimal (string) | null position integer
completed_at string(date-time) | null labels any[] subtasks Task[] subtasks_count integer comments_count integer
created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

`POST` `/api/v1/projects/{project}/tasks`

Create task `projectsTasksStore`

Naya task banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` / `tasks.manage` (createTask on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`assignee_id`	integer | null	no	Validated by `CompanyMember`.
`description`	string | null	no	maxLength 20000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:start_date`.
`estimate_hours`	string | number | null	no	min 0 · max 999999.99 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 2 decimal places.
`labels`	string[] | null	no	maxItems 20
`milestone_id`	integer | null	no	Validated by `TenantExists`.
`priority`	enum Priority	no	values: `low`, `medium`, `high`, `critical`
`start_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`status`	enum TaskStatus	no	values: `todo`, `in_progress`, `in_review`, `done`, `blocked`
`title`	string	**yes**	maxLength 200

EXAMPLE REQUEST

```
{
  "assignee_id": 1,
  "description": "Sample text",
  "due_date": "2026-11-14",
  "estimate_hours": "7.5000",
  "labels": ["string"],
  "milestone_id": 1,
  "priority": "low",
  "start_date": "2026-10-15",
  "status": "todo",
  "title": "Sample title"
}
```

RESPONSES

201 — `data` : Task

`id` integer `project_id` integer `project` object | null `parent_id` integer | null `milestone_id` integer | null `milestone` object | null `title` string `description` string | null `status` enum TaskStatus | null `priority` enum Priority | null `assignee_id` integer | null `assignee` UserSummary | null `reporter_id` integer | null `reporter` UserSummary | null `start_date` string(date) | null `due_date` string(date) | null `estimate_hours` Decimal (string) | null `position` integer `completed_at` string(date-time) | null `labels` any[] `subtasks` Task[] `subtasks_count` integer `comments_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

`POST` `/api/v1/tasks/{task}/subtasks`

Create subtask `tasksSubtasksStore`

Naya subtask banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` / `tasks.manage` (update on Task)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`task`	path	integer	**yes**	ID of the Task. · min 1

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`assignee_id`	integer | null	no	Validated by `CompanyMember`.
`description`	string | null	no	maxLength 20000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:start_date`.
`estimate_hours`	string | number | null	no	min 0 · max 999999.99 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 2 decimal places.
`labels`	string[] | null	no	maxItems 20
`milestone_id`	integer | null	no	Validated by `TenantExists`.
`priority`	enum Priority	no	values: `low`, `medium`, `high`, `critical`
`start_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`status`	enum TaskStatus	no	values: `todo`, `in_progress`, `in_review`, `done`, `blocked`
`title`	string	**yes**	maxLength 200

EXAMPLE REQUEST

```
{
  "assignee_id": 1,
  "description": "Sample text",
  "due_date": "2026-11-14",
  "estimate_hours": "7.5000",
  "labels": ["string"],
  "milestone_id": 1,
  "priority": "low",
  "start_date": "2026-10-15",
  "status": "todo",
  "title": "Sample title"
}
```

RESPONSES

201 — `data` : Task

`id` integer `project_id` integer `project` object | null `parent_id` integer | null `milestone_id` integer | null `milestone` object | null `title` string `description` string | null `status` enum TaskStatus | null `priority` enum Priority | null `assignee_id` integer | null `assignee` UserSummary | null `reporter_id` integer | null `reporter` UserSummary | null `start_date` string(date) | null `due_date` string(date) | null `estimate_hours` Decimal (string) | null `position` integer `completed_at` string(date-time) | null `labels` any[] `subtasks` Task[] `subtasks_count` integer `comments_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/tasks/{task}/move

Move – task tasksMove

Task ko naye `status` / `position` par move karta hai (Kanban).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` / `tasks.manage` (update on Task)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
task	path	integer	yes	ID of the Task. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
position	integer	yes	min 0 · max 100000
status	enum TaskStatus	yes	values: `todo`, `in_progress`, `in_review`, `done`, `blocked`

RESPONSES

200 — `data` : Task

`id` integer `project_id` integer `project` object | null `parent_id` integer | null `milestone_id` integer | null
`milestone` object | null `title` string `description` string | null `status` enum TaskStatus | null `priority` enum Priority | null
`assignee_id` integer | null `assignee` UserSummary | null `reporter_id` integer | null `reporter` UserSummary | null
`start_date` string(date) | null `due_date` string(date) | null `estimate_hours` Decimal (string) | null `position` integer
`completed_at` string(date-time) | null `labels` any[] `subtasks` Task[] `subtasks_count` integer `comments_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/tasks/{task}

Get task tasksShow

Ek task ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `tasks.view` (view on Task)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
task	path	integer	yes	ID of the Task. · min 1

RESPONSES

200 — `data` : Task

`id` integer `project_id` integer `project` object | null `parent_id` integer | null `milestone_id` integer | null
`milestone` object | null `title` string `description` string | null `status` enum TaskStatus | null `priority` enum Priority | null
`assignee_id` integer | null `assignee` UserSummary | null `reporter_id` integer | null `reporter` UserSummary | null
`start_date` string(date) | null `due_date` string(date) | null `estimate_hours` Decimal (string) | null `position` integer
`completed_at` string(date-time) | null `labels` any[] `subtasks` Task[] `subtasks_count` integer `comments_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/tasks/{task}

Update task tasksUpdate

Maujooda task ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` / `tasks.manage` (update on Task)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`task`	path	integer	**yes**	ID of the Task. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`assignee_id`	integer | null	no	Validated by `CompanyMember`.
`description`	string | null	no	maxLength 20000
`due_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `after_or_equal:start_date`.
`estimate_hours`	string | number | null	no	min 0 · max 999999.99 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 2 decimal places.
`labels`	string[] | null	no	maxItems 20
`milestone_id`	integer | null	no	Validated by `TenantExists`.
`priority`	enum Priority	no	values: `low`, `medium`, `high`, `critical`
`start_date`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`status`	enum TaskStatus	no	values: `todo`, `in_progress`, `in_review`, `done`, `blocked`
`title`	string	no	maxLength 200

RESPONSES

200 — `data` : Task

`id` integer `project_id` integer `project` object | null `parent_id` integer | null `milestone_id` integer | null
`milestone` object | null `title` string `description` string | null `status` enum TaskStatus | null `priority` enum Priority | null
`assignee_id` integer | null `assignee` UserSummary | null `reporter_id` integer | null `reporter` UserSummary | null
`start_date` string(date) | null `due_date` string(date) | null `estimate_hours` Decimal (string) | null `position` integer
`completed_at` string(date-time) | null `labels` any[] `subtasks` Task[] `subtasks_count` integer `comments_count` integer
`created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/tasks/{task}

Update task tasksUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /tasks/{task} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission projects.manage tasks.manage

DELETE /api/v1/tasks/{task}

Delete task tasksDestroy

Task delete karta hai — kamyabi par 204 (khaali body).

Deletes the task with its subtasks and comments; time entries keep their hours (task link cleared).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.manage / tasks.manage (delete on Task)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
task	path	integer	**yes**	ID of the Task. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

GET /api/v1/tasks/{task}/comments

List comments tasksCommentsIndex

Comments ki list deta hai — results paginated hote hain (page , per_page).

Auth Session cookie · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (view on Task)

Throttle api

List params page , per_page (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
task	path	integer	**yes**	ID of the Task. · min 1

RESPONSES

200 — data : array of TaskComment + meta.pagination

id integer task_id integer user_id integer | null user UserSummary | null body string edited_at string(date-time) | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/tasks/{task}/comments

Create comment tasksCommentsStore

Naya comment banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.view / projects.manage / tasks.view (comment on Task)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
task	path	integer	yes	ID of the Task. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
body	string	yes	maxLength 5000

EXAMPLE REQUEST

```
{"body":"Sample text"}
```

RESPONSES

201 — data : TaskComment

id integer task_id integer user_id integer | null user UserSummary | null body string edited_at string(date-time) | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

PUT /api/v1/tasks/{task}/comments/{comment}

Update comment tasksCommentsUpdate

Maujooda comment ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use sometimes).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Koi permission slug nahi (sirf authentication/ownership) (update on TaskComment)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
task	path	integer	yes	ID of the Task. · min 1
comment	path	integer	yes	ID of the Task Comment. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
body	string	yes	maxLength 5000

RESPONSES

200 — data : TaskComment

id integer task_id integer user_id integer | null user UserSummary | null body string edited_at string(date-time) | null created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

PATCH /api/v1/tasks/{task}/comments/{comment}

Update comment tasksCommentsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /tasks/{task}/comments/{comment}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission —

DELETE /api/v1/tasks/{task}/comments/{comment}

Delete comment tasksCommentsDestroy

Comment delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (delete on TaskComment)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`task`	path	integer	**yes**	ID of the Task. · min 1
`comment`	path	integer	**yes**	ID of the Task Comment. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET `/api/v1/time-entries`

List time entries `timeEntriesIndex`

Time entries ki list deta hai — results paginated hote hain (`page` , `per_page`).

Filters: filter[project_id|user_id|task_id|is_billable], from/to (date). Without projects.view/manage only the caller's own entries are listed.
`search` matches (case-insensitive, substring): `description` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `time_entries.manage` / `projects.view` / `projects.manage` (viewAny on TimeEntry; viewAll on TimeEntry)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[project_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[user_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[task_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`filter[is_billable]`	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: `true`, `false`
`from`	query	string(date)	no	Inclusive lower bound on `date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-date`). The primary key is always appended as a tie-breaker. · values: `date`, `-date`, `hours`, `-hours`, `created_at`, `-created_at` · default `-date`

RESPONSES

200 — `data` : array of TimeEntry + `meta.pagination`

`id` integer `project_id` integer `project` object | null `task_id` integer | null `task` object | null `user_id` integer `user` UserSummary | null `date` string(date) | null `hours` Decimal (string) `description` string | null `is_billable` boolean `hourly_rate` Money (string) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

POST `/api/v1/time-entries`

Create time entry `timeEntriesStore`

Naya time entry banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth	Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**
Permission	Policy: `time_entries.manage` / `projects.manage` (create on TimeEntry)
Throttle	`api`

REQUEST BODY `application/json`

Field	Type	Req.	Constraints / notes
`date`	string(date)	**yes**	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `before_or_equal:2027-10-15`.
`description`	string | null	no	maxLength 500
`hourly_rate`	string | number | null	no	min 0 · max 99999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 4 decimal places.
`hours`	string | number	**yes**	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`. `lte:24`. Up to 2 decimal places.
`is_billable`	boolean	no	
`project_id`	integer	**yes**	Validated by `TenantExists`. Custom validation applies.
`task_id`	integer | null	no	Validated by `TenantExists`.
`user_id`	integer	no	Validated by `CompanyMember`. Custom validation applies.

EXAMPLE REQUEST

```
{
  "date": "2026-10-15",
  "description": "Sample text",
  "hourly_rate": "17.0000",
  "hours": "7.5000",
  "is_billable": true,
  "project_id": 1,
  "task_id": 1,
  "user_id": 1
}
```

RESPONSES

201 — `data` : TimeEntry

`id` integer `project_id` integer `project` object | null `task_id` integer | null `task` object | null `user_id` integer `user` UserSummary | null `date` string(date) | null `hours` Decimal (string) `description` string | null `is_billable` boolean `hourly_rate` Money (string) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/time-entries/{time_entry}

Get time entry `timeEntriesShow`

Ek time entry ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` / `time_entries.manage` (view on TimeEntry)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`time_entry`	path	string	**yes**	

RESPONSES

200 — `data` : TimeEntry

`id` integer `project_id` integer `project` object | null `task_id` integer | null `task` object | null `user_id` integer `user` UserSummary | null `date` string(date) | null `hours` Decimal (string) `description` string | null `is_billable` boolean `hourly_rate` Money (string) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/time-entries/{time_entry}

Update time entry `timeEntriesUpdate`

Maujooda time entry ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` / `time_entries.manage` (update on TimeEntry)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`time_entry`	path	string	**yes**	

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`date`	string(date)	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended. `before_or_equal:2027-10-15`.
`description`	string | null	no	maxLength 500
`hourly_rate`	string | number | null	no	min 0 · max 99999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. Up to 4 decimal places.
`hours`	string | number	no	Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`. `lte:24`. Up to 2 decimal places.
`is_billable`	boolean	no	
`project_id`	integer	no	Validated by `TenantExists`. Custom validation applies.
`task_id`	integer | null	no	Validated by `TenantExists`.
`user_id`	integer	no	Validated by `CompanyMember`. Custom validation applies.

RESPONSES

200 — `data` : TimeEntry

`id` integer `project_id` integer `project` object | null `task_id` integer | null `task` object | null `user_id` integer `user` UserSummary | null `date` string(date) | null `hours` Decimal (string) `description` string | null `is_billable` boolean `hourly_rate` Money (string) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/time-entries/{time_entry}

Update time entry `timeEntriesUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /time-entries/{time_entry}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `projects.manage` `time_entries.manage`

DELETE /api/v1/time-entries/{time_entry}

Delete time entry `timeEntriesDestroy`

Time entry delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` / `time_entries.manage` (delete on TimeEntry)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`time_entry`	path	string	**yes**	

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

`GET` `/api/v1/projects/{project}/expenses`

List expenses `projectsExpensesIndex`

Expenses ki list deta hai — results paginated hote hain (`page` , `per_page`).

`search` matches (case-insensitive, substring): `category` , `description` .

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` (viewFinancials on Project)

Throttle `api`

List params `page` , `per_page` , `search` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1
`filter[category]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`filter[currency]`	query	string	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `date` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `date` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-date`). The primary key is always appended as a tie-breaker. · values: `date`, `-date`, `amount`, `-amount`, `category`, `-category`, `created_at`, `-created_at` · default `-date`

RESPONSES

200 — `data` : array of ProjectExpense + `meta.pagination`

`id` integer `project_id` integer `date` string(date) | null `category` string `description` string | null `amount` Money (string) `currency` string `receipt_document_id` integer | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

POST /api/v1/projects/{project}/expenses

Create expense projectsExpensesStore

Naya expense banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (update on Project)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	yes	ID of the Project. · min 1

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
`amount`	string | number	yes	max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`. Up to 4 decimal places.
`category`	string	yes	maxLength 60
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`date`	string(date)	yes	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`description`	string | null	no	maxLength 500
`receipt_document_id`	integer | null	no	Validated by `TenantExists`.

EXAMPLE REQUEST

```
{
  "amount": "1250.0000",
  "category": "string",
  "currency": "PKR",
  "date": "2026-10-15",
  "description": "Sample text",
  "receipt_document_id": 1
}
```

RESPONSES

201 — `data` : ProjectExpense

`id` integer `project_id` integer `date` string(date) | null `category` string `description` string | null `amount` Money (string) `currency` string `receipt_document_id` integer | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

GET /api/v1/projects/{project}/expenses/{expense}

Get expense `projectsExpensesShow`

Ek expense ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `projects.view` / `projects.manage` (view on ProjectExpense)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	yes	ID of the Project. · min 1
`expense`	path	integer	yes	ID of the Project Expense. · min 1

RESPONSES

200 — `data` : ProjectExpense

`id` integer `project_id` integer `date` string(date) | null `category` string `description` string | null `amount` Money (string) `currency` string `receipt_document_id` integer | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/projects/{project}/expenses/{expense}

Update expense projectsExpensesUpdate

Maujooda expense ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `projects.manage` (update on ProjectExpense)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`project`	path	integer	**yes**	ID of the Project. · min 1
`expense`	path	integer	**yes**	ID of the Project Expense. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`amount`	string | number	no	max 99999999999999 · Decimal value; send as a string (e.g. "1250.5000") to avoid float rounding. `gt:0`. Up to 4 decimal places.
`category`	string	no	maxLength 60
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$`
`date`	string(date)	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`description`	string | null	no	maxLength 500
`receipt_document_id`	integer | null	no	Validated by `TenantExists`.

RESPONSES

200 — `data` : ProjectExpense

`id` integer `project_id` integer `date` string(date) | null `category` string `description` string | null `amount` Money (string) `currency` string `receipt_document_id` integer | null `created_by` integer | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/projects/{project}/expenses/{expense}

Update expense projectsExpensesUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul PUT /projects/{project}/expenses/{expense} jaise hain (route PUT|PATCH ek hi handler share karta hai).

Permission projects.manage

DELETE /api/v1/projects/{project}/expenses/{expense}

Delete expense projectsExpensesDestroy

Expense delete karta hai — kamyabi par 204 (khaali body).

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: projects.manage (delete on ProjectExpense)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
project	path	integer	**yes**	ID of the Project. · min 1
expense	path	integer	**yes**	ID of the Project Expense. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 429 throttled

MODULE

Documents

> Document library: folders, uploads (multipart), versions, share links aur downloads. Files private disk par rehti hain aur download sirf policy check ke baad stream hota hai.

Spec: Document library: folders, uploads, versions, sharing and downloads. — 17 operations.

Method	Path	Summary	Permission
GET	/document-folders	List document folders	documents.view
POST	/document-folders	Create document folder	documents.manage
GET	/document-folders/{folder}	Get document folder	documents.view
PUT	/document-folders/{folder}	Update document folder	documents.manage
PATCH	/document-folders/{folder}	Update document folder	documents.manage
DELETE	/document-folders/{folder}	Delete document folder	documents.manage
GET	/documents/{document}/download	Stream a version (default: current) from the private disk. Audited.	documents.view
GET	/documents/{document}/shared-download	Shared download – document	documents.view
POST	/documents/{document}/share-link	Share link – document	documents.view
GET	/documents/{document}/versions	List versions	documents.view
POST	/documents/{document}/versions	Create version	documents.manage
GET	/documents	List documents	documents.view
POST	/documents	Create document	documents.manage
GET	/documents/{document}	Get document	documents.view
PUT	/documents/{document}	Update document	documents.manage
PATCH	/documents/{document}	Update document	documents.manage
DELETE	/documents/{document}	Soft delete (audited by Auditable as documents.archived); files are kept for recovery.	documents.manage

Endpoints

GET /api/v1/document-folders

List document folders documentFoldersIndex

Document folders ki list deta hai — results paginated hote hain (page , per_page).

All visible folders (flat; build the tree client-side from parent_id). filter[parent_id] narrows. search matches (case-insensitive, substring): name .

Auth Session cookie · X-Company-Id **required**

Permission Policy: documents.view (viewAny on DocumentFolder)

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[parent_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[is_private]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, created_at, -created_at · default name

RESPONSES

200 — data : array of DocumentFolder + meta.pagination

id integer parent_id integer | null name string is_private boolean owner_id integer | null documents_count integer children_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 429 throttled

POST /api/v1/document-folders

Create document folder documentFoldersStore

Naya document folder banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Policy: documents.manage (create on DocumentFolder)

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
is_private	boolean	no	
name	string	**yes**	maxLength 150
parent_id	integer | null	no	Validated by TenantExists. Custom validation applies.

EXAMPLE REQUEST

```
{"is_private":true,"name":"Sample name","parent_id":1}
```

RESPONSES

201 — data : DocumentFolder

id integer parent_id integer | null name string is_private boolean owner_id integer | null documents_count integer children_count integer created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/document-folders/{folder}

Get document folder documentFoldersShow

Ek document folder ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `documents.view` (view on DocumentFolder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`folder`	path	integer	yes	ID of the Document Folder. · min 1

RESPONSES

200 — `data` : DocumentFolder

`id` integer `parent_id` integer | null `name` string `is_private` boolean `owner_id` integer | null `documents_count` integer `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/document-folders/{folder}

Update document folder documentFoldersUpdate

Maujooda document folder ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `documents.manage` (update on DocumentFolder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`folder`	path	integer	yes	ID of the Document Folder. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`is_private`	boolean	no	
`name`	string	no	maxLength 150
`parent_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.

RESPONSES

200 — `data` : DocumentFolder

`id` integer `parent_id` integer | null `name` string `is_private` boolean `owner_id` integer | null `documents_count` integer `children_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/document-folders/{folder}

Update document folder documentFoldersUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /document-folders/{folder}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `documents.manage`

DELETE /api/v1/document-folders/{folder}

Delete document folder documentFoldersDestroy

Document folder delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `documents.manage` (delete on DocumentFolder)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`folder`	path	integer	**yes**	ID of the Document Folder. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

GET /api/v1/documents/{document}/download

Stream a version (default: current) from the private disk. Audited. documentsDownload

Document ka version (default: current) private disk se stream karta hai; download audit hota hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `documents.view` (download on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	**yes**	ID of the Document. · min 1
`version`	query	string	no	

RESPONSES

200 — File (`application/octet-stream`). File download (`Content-Disposition: attachment`). The actual `Content-Type` is the stored file's MIME type.

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

`GET` `/api/v1/documents/{document}/shared-download`

Shared download – document `documentsSharedDownload`

Share link ke zariye document download karta hai.

Same as download, reached through a temporary signed URL. The route is still inside the auth + tenant group: the link is a short-lived convenience for opening in a new tab, never a public/anonymous link.
Must be called through the signed URL that was e-mailed/generated (valid `signature` and `expires` query params); invalid signatures return **403**.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `documents.view` (download on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	**yes**	ID of the Document. · min 1
`version`	query	string	no	

RESPONSES

200 — File (`application/octet-stream`). File download (`Content-Disposition: attachment`). The actual `Content-Type` is the stored file's MIME type.

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

`POST` `/api/v1/documents/{document}/share-link`

Share link – document `documentsShareLink`

Document ke liye share link banata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `documents.view` (share on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	**yes**	ID of the Document. · min 1

REQUEST BODY `application/json` **(OPTIONAL)**

Field	Type	Req.	Constraints / notes
`minutes`	integer	no	min 1 · max 60
`version`	integer	no	min 1

RESPONSES

200 — `data` : object shape inferred from code

`url` string(uri) `expires_at` string(date-time) `requires_authentication` boolean

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

`GET` `/api/v1/documents/{document}/versions`

List versions `documentsVersionsIndex`

Versions ki list deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `documents.view` (view on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	yes	ID of the Document. · min 1

RESPONSES

200 — `data`: array of DocumentVersion

`id` integer `document_id` integer `version` integer `original_name` string `mime` string | null `size_bytes` integer `checksum_sha256` string `uploaded_by` integer | null `uploader` object | null `note` string | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

`POST` `/api/v1/documents/{document}/versions`

Create version `documentsVersionsStore`

Naya version banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Route: `documents.manage` · Policy: `documents.manage` (addVersion on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	yes	ID of the Document. · min 1

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`file`	string(binary)	yes	Allowed types: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt. Max size 10240 KB.
`note`	string | null	no	maxLength 500

RESPONSES

201 — `data`: DocumentVersion

`id` integer `document_id` integer `version` integer `original_name` string `mime` string | null `size_bytes` integer `checksum_sha256` string `uploaded_by` integer | null `uploader` object | null `note` string | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/documents`

List documents `documentsIndex`

Documents ki list deta hai — results paginated hote hain (`page` , `per_page`).

Search & filter: search (title, description, tags), filter[category|visibility|owner_id], folder_id, documentable_type + documentable_id, archived=0|1|all (default 0), from/to (created).

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `documents.view` (viewAny on Document)

Throttle `api`

List params `page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`filter[category]`	query	enum DocumentsDocumentCategory	no	Exact-match filter (comma-separated = koi bhi value). · 9 values (Appendix B)
`filter[visibility]`	query	enum DocumentVisibility	no	Exact-match filter (comma-separated = koi bhi value). · values: `company`, `restricted`, `private`
`filter[owner_id]`	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
`from`	query	string(date)	no	Inclusive lower bound on `created_at` (UTC day start).
`to`	query	string(date)	no	Inclusive upper bound on `created_at` (UTC day end).
`sort`	query	string	no	Sort column; prefix with `-` for descending. Unknown columns fall back to the default (`-created_at`). The primary key is always appended as a tie-breaker. · values: `title`, `-title`, `category`, `-category`, `created_at`, `-created_at`, `updated_at`, `-updated_at`, `retention_until`, `-retention_until` · default `-created_at`
`archived`	query	string | null	no	values: `0`, `1`, `all`, `true`, `false`,
`documentable_id`	query	integer | null	no	
`documentable_type`	query	enum DocumentableType | null	no	
`folder_id`	query	integer | null	no	

RESPONSES

200 — `data` : array of Document + `meta.pagination`

`id` integer `title` string `description` string | null `category` enum DocumentsDocumentCategory | null `tags` any[] `folder_id` integer | null `folder` object | null `documentable_type` string | null `documentable_id` integer | null `visibility` enum DocumentVisibility | null `allowed_role_ids` any[] `owner_id` integer | null `owner` object | null `current_version` DocumentVersion | null `versions` DocumentVersion[] `versions_count` integer `download_url` string `retention_until` string(date) | null `is_archived` boolean `archived_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

`POST` `/api/v1/documents`

Create document `documentsStore`

Naya document banata hai; kamyabi par `201` aur naya record `data` mein wapas aata hai.

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `documents.manage` (create on Document)

Throttle `api`

REQUEST BODY `multipart/form-data`

Field	Type	Req.	Constraints / notes
`allowed_role_ids`	integer[] | null	no	maxItems 50 · `required_if:visibility,restricted`.
`category`	enum DocumentsDocumentCategory	no	9 values (Appendix B)
`description`	string | null	no	maxLength 5000
`documentable_id`	integer | null	no	`required_with:documentable_type`. Custom validation applies.
`documentable_type`	enum DocumentableType | null	no	`required_with:documentable_id`.
`file`	string(binary)	**yes**	Allowed types: pdf, png, jpg, jpeg, webp, doc, docx, xls, xlsx, csv, txt. Max size 10240 KB.
`folder_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`note`	string | null	no	maxLength 500
`retention_until`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`tags`	string[] | null	no	maxItems 20
`title`	string	no	maxLength 200
`visibility`	enum DocumentVisibility	no	values: `company`, `restricted`, `private`

RESPONSES

201 — `data` : Document

`id` integer `title` string `description` string | null `category` enum DocumentsDocumentCategory | null `tags` any[]
`folder_id` integer | null `folder` object | null `documentable_type` string | null `documentable_id` integer | null
`visibility` enum DocumentVisibility | null `allowed_role_ids` any[] `owner_id` integer | null `owner` object | null
`current_version` DocumentVersion | null `versions` DocumentVersion[] `versions_count` integer `download_url` string
`retention_until` string(date) | null `is_archived` boolean `archived_at` string(date-time) | null `created_at` string(date-time) | null
`updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `419` auth.csrf · `422` validation.failed · `429` throttled

GET `/api/v1/documents/{document}`

Get document `documentsShow`

Ek document ki poori tafseel deta hai.

Auth Session cookie · `X-Company-Id` **required**

Permission Policy: `documents.view` (view on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	**yes**	ID of the Document. · min 1

RESPONSES

200 — `data` : Document

`id` integer `title` string `description` string | null `category` enum DocumentsDocumentCategory | null `tags` any[]
`folder_id` integer | null `folder` object | null `documentable_type` string | null `documentable_id` integer | null
`visibility` enum DocumentVisibility | null `allowed_role_ids` any[] `owner_id` integer | null `owner` object | null
`current_version` DocumentVersion | null `versions` DocumentVersion[] `versions_count` integer `download_url` string
`retention_until` string(date) | null `is_archived` boolean `archived_at` string(date-time) | null `created_at` string(date-time) | null
`updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

PUT /api/v1/documents/{document}

Update document documentsUpdate

Maujooda document ko update karta hai.

Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `documents.manage` (update on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	**yes**	ID of the Document. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`allowed_role_ids`	integer[] | null	no	maxItems 50 · `required_if:visibility,restricted`.
`category`	enum DocumentsDocumentCategory	no	9 values (Appendix B)
`description`	string | null	no	maxLength 5000
`documentable_id`	integer | null	no	`required_with:documentable_type`. Custom validation applies.
`documentable_type`	enum DocumentableType | null	no	`required_with:documentable_id`.
`folder_id`	integer | null	no	Validated by `TenantExists`. Custom validation applies.
`is_archived`	boolean	no	
`retention_until`	string(date) | null	no	Any date parseable by PHP; ISO-8601 (`YYYY-MM-DD`) recommended.
`tags`	string[] | null	no	maxItems 20
`title`	string	no	maxLength 200
`visibility`	enum DocumentVisibility	no	values: `company`, `restricted`, `private`

RESPONSES

200 — `data`: Document

`id` integer `title` string `description` string | null `category` enum DocumentsDocumentCategory | null `tags` any[] `folder_id` integer | null `folder` object | null `documentable_type` string | null `documentable_id` integer | null `visibility` enum DocumentVisibility | null `allowed_role_ids` any[] `owner_id` integer | null `owner` object | null `current_version` DocumentVersion | null `versions` DocumentVersion[] `versions_count` integer `download_url` string `retention_until` string(date) | null `is_archived` boolean `archived_at` string(date-time) | null `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/documents/{document}

Update document documentsUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /documents/{document}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `documents.manage`

DELETE /api/v1/documents/{document}

Soft delete (audited by Auditable as documents.archived); files are kept for recovery. documentsDestroy

Document delete karta hai — kamyabi par `204` (khaali body).

Auth Session cookie + `X-XSRF-TOKEN` · `X-Company-Id` **required**

Permission Policy: `documents.manage` (delete on Document)

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`document`	path	integer	**yes**	ID of the Document. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

MODULE

Dashboard

> Role-aware dashboard widgets — response user ki permissions ke mutabiq banta hai.

Spec: Role-aware dashboard widgets. — 1 operations.

Method	Path	Summary	Permission
GET	/dashboard	Dashboard	dashboard.view

Endpoints

GET /api/v1/**dashboard**

Dashboard dashboard

User ke role/permissions ke mutabiq dashboard widgets ka data deta hai.

Auth Session cookie · X-Company-Id **required**

Permission Route: dashboard.view

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
branch_id	query	integer | null	no	Validated by AccessibleBranch.
from	query	string(date) | null	no	
to	query	string(date) | null	no	

RESPONSES

200 — data : object shape inferred from code

period object currency string modules any[] metrics any[] trend any[] by_branch object[] by_department object[] low_stock_items object[] sales_by_month any[] recent_invoices object[] pending_approvals object[] recent_activity object[]

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 422 validation.failed · 429 throttled

MODULE

Approvals

Unified approval inbox — mukhtalif modules ki pending approvals ek jagah, aur unke counts.

Spec: Unified approval inbox. — 2 operations.

Method	Path	Summary	Permission
GET	/approvals/counts	Counts – approval	approvals.view
GET	/approvals	List approvals	approvals.view

Endpoints

GET /api/v1/approvals/counts

Counts – approval `approvalsCounts`

Pending approvals ki counts deta hai.

Auth: Session cookie · `X-Company-Id` **required**

Permission: Route: `approvals.view`

Throttle: `api`

RESPONSES

200 — `data` : object shape inferred from code

`total` number `by_type` any[]

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/approvals

List approvals `approvalsIndex`

Approval inbox — pending approvals ki list deta hai.

Auth: Session cookie · `X-Company-Id` **required**

Permission: Route: `approvals.view`

Throttle: `api`

List params: `page` , `per_page` (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter	query	object | null	no	

RESPONSES

200 — `data` : array of objects + `meta` { `pagination` } shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Reports

Report catalogue, JSON preview (pehli 500 rows tak) aur exports. Chhota export seedha file stream karta hai; bada export `202` ke saath ek export job deta hai jise `/report-exports` se track aur download kiya jata hai. Expire ho chuki file `410` deti hai.

Spec: Report catalogue, JSON preview, exports (sync file or async export job). — 6 operations.

Method	Path	Summary	Permission
GET	/reports	reports this user may run.	reports.view
GET	/reports/{key}	paginated JSON preview (first 500 rows).	reports.view
POST	/reports/{key}/export	streamed file (small) or 202 + export job (large).	reports.export
GET	/report-exports	List report exports	reports.export
GET	/report-exports/{exportJob}	Get report export	reports.export
GET	/report-exports/{exportJob}/download	Download – report export	reports.export

Endpoints

GET /api/v1/**reports**

reports this user may run. `reportsIndex`

Woh reports list karta hai jo current user chala sakta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Route: `reports.view`
Throttle	`api`

RESPONSES

200 — `data` : array of objects shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/reports/{key}

paginated JSON preview (first 500 rows). reportsShow

Report ka paginated JSON preview deta hai (pehli 500 rows tak).

Auth Session cookie · X-Company-Id **required**

Permission Route: reports.view (runReport on ReportDefinition)

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
key	path	string	yes	Report key from GET /reports (e.g. finance.ar_aging). · pattern ^[a-z_]+\.[a-z_]+$
page	query	integer | null	no	min 1
per_page	query	integer | null	no	min 1 · max 500

RESPONSES

200 — data : object + meta { pagination , total_rows , truncated } shape inferred from code

report object params object currency string columns object rows any[] totals object

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 422 validation.failed · 429 throttled

POST /api/v1/reports/{key}/export

streamed file (small) or 202 + export job (large). reportsExport

Report export karta hai: chhota export seedha file (200), bada export 202 + export job.

Auth Session cookie + X-XSRF-TOKEN · X-Company-Id **required**

Permission Route: reports.export (runReport on ReportDefinition)

Throttle api exports

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
key	path	string	yes	Report key from GET /reports (e.g. finance.ar_aging). · pattern ^[a-z_]+\.[a-z_]+$

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
format	string	yes	values: csv, xlsx, pdf
params	any[] | null	no	

RESPONSES

200 — File (text/csv , application/vnd.openxmlformats-officedocument.spreadsheetml.sheet , application/pdf). File download (Content-Disposition: attachment).

202 — data : ExportJob

id string(uuid) report_key string report_name string format string params object status enum ExportJobStatus

row_count integer | null error string | null is_expired boolean download_url string | null created_at string(date-time) | null

started_at string(date-time) | null finished_at string(date-time) | null expires_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 419 auth.csrf · 422 validation.failed · 429 throttled

GET /api/v1/report-exports

List report exports `reportExportsIndex`

Report exports ki list deta hai — results paginated hote hain (`page` , `per_page`).

Auth	Session cookie · `X-Company-Id` **required**
Permission	Route: `reports.export` · Policy: `reports.export` (viewAny on ExportJob)
Throttle	`api`
List params	`page` , `per_page` (standard — §Pagination dekhein)

RESPONSES

200 — `data` : array of ExportJob + `meta.pagination`

`id` string(uuid) `report_key` string `report_name` string `format` string `params` object `status` enum ExportJobStatus `row_count` integer | null `error` string | null `is_expired` boolean `download_url` string | null `created_at` string(date-time) | null `started_at` string(date-time) | null `finished_at` string(date-time) | null `expires_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `429` throttled

GET /api/v1/report-exports/{exportJob}

Get report export `reportExportsShow`

Ek report export ki poori tafseel deta hai.

Auth	Session cookie · `X-Company-Id` **required**
Permission	Route: `reports.export` (view)
Throttle	`api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
exportJob	path	string(uuid)	yes	

RESPONSES

200 — `data` : ExportJob

`id` string(uuid) `report_key` string `report_name` string `format` string `params` object `status` enum ExportJobStatus `row_count` integer | null `error` string | null `is_expired` boolean `download_url` string | null `created_at` string(date-time) | null `started_at` string(date-time) | null `finished_at` string(date-time) | null `expires_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/report-exports/{exportJob}/download

Download – report export `reportExportsDownload`

Mukammal export job ki file download karta hai; expired ho to `410` .

Auth	Session cookie · `X-Company-Id` **required**
Permission	Route: `reports.export` (download)
Throttle	`api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
exportJob	path	string(uuid)	yes	

RESPONSES

200 — File (`text/csv` , `application/vnd.openxmlformats-officedocument.spreadsheetml.sheet` , `application/pdf`). File download (`Content-Disposition: attachment`).

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `410` http.410 · `429` throttled

MODULE

Search

Global search — query parameter `q` (2–100 characters) se active company ke modules mein dhoondta hai. Is par alag rate limit (60 requests/minute) lagta hai.

Spec: Global search across modules. — 1 operations.

Method	Path	Summary	Permission
GET	/search	Search	—

Endpoints

GET /api/v1/search

Search search

Active company ke modules mein global search karta hai (`q` zaroori).

Auth Session cookie · `X-Company-Id` **required**

Permission Koi permission slug nahi (sirf authentication/ownership)

Throttle `api` `60,1`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
q	query	string	yes	minLength 2 · maxLength 100
types	query	string | null	no	maxLength 300

RESPONSES

200 — `data` : array of objects + `meta` { `query` , `types` } shape inferred from code

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `422` validation.failed · `429` throttled

MODULE

Platform

Platform administration: companies, users, system info aur platform audit logs. Ye sirf platform staff ke liye hai — baqi sab ko `404` milta hai — aur in routes par koi tenant context (`X-Company-Id`) nahi hota.

Spec: Platform administration (platform staff only; 404 for everyone else). No tenant context. — 15 operations.

Method	Path	Summary	Permission
GET	/platform/companies	List companies (platform)	platform.companies.manage
POST	/platform/companies	Create company (platform)	platform.companies.manage
GET	/platform/companies/{company}	Get company (platform)	platform.companies.manage
PUT	/platform/companies/{company}	Update company (platform)	platform.companies.manage
PATCH	/platform/companies/{company}	Update company (platform)	platform.companies.manage
DELETE	/platform/companies/{company}	Soft-delete. Only inactive companies may be deleted (409 otherwise).	platform.companies.manage
POST	/platform/companies/{company}/activate	Activate – company (platform)	platform.companies.manage
POST	/platform/companies/{company}/deactivate	Deactivate – company (platform)	platform.companies.manage
GET	/platform/users	List users (platform)	platform.users.manage
GET	/platform/users/{user}	Get user (platform)	platform.users.manage
PUT	/platform/users/{user}	Update user (platform)	platform.users.manage
PATCH	/platform/users/{user}	Update user (platform)	platform.users.manage
GET	/platform/system	System – platform (platform)	platform.system.view
GET	/platform/audit-logs	List audit logs (platform)	platform.system.view
GET	/platform/audit-logs/{auditLog}	Get audit log (platform)	platform.system.view

Endpoints

GET /api/v1/platform/companies

List companies (platform) platformCcompaniesIndex

Companies ki list deta hai — results paginated hote hain (page , per_page).

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No X-Company-Id is needed. search matches (case-insensitive, substring): name , legal_name , code , slug , email .

Auth Session cookie

Permission Route: platform.companies.manage

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[is_demo]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
filter[country]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[currency]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, code, -code, created_at, -created_at, is_active, -is_active · default name

RESPONSES

200 — data : array of PlatformCompany + meta.pagination

id integer name string legal_name string | null slug string code string email string | null phone string | null website string | null tax_number string | null registration_number string | null address object currency string timezone string locale string date_format string fiscal_year_start_month integer logo_url string(uri) | null primary_color string | null is_active boolean is_demo boolean settings object branches_count integer users_count integer created_at string(date-time) | null updated_at string(date-time) | null ...aur 1 fields

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

POST /api/v1/platform/companies

Create company (platform) platformCompaniesStore

Naya company banata hai; kamyabi par 201 aur naya record data mein wapas aata hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No X-Company-Id is needed.

Auth Session cookie + X-XSRF-TOKEN

Permission Route: platform.companies.manage

Throttle api

REQUEST BODY application/json

Field	Type	Req.	Constraints / notes
address_line1	string | null	no	maxLength 200
address_line2	string | null	no	maxLength 200
city	string | null	no	maxLength 100

Field	Type	Req.	Constraints / notes
code	string | null	no	maxLength 20 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within companies (per company).
country	string | null	no	minLength 2 · maxLength 2
currency	string	no	minLength 3 · maxLength 3 · pattern ^[A-Za-z]+$ · Required when present (sometimes|required).
date_format	string	no	values: Y-m-d, d/m/Y, m/d/Y, d.m.Y, d M Y · Required when present (sometimes|required).
email	string(email) | null	no	maxLength 150
fiscal_year_start_month	integer	no	min 1 · max 12 · Required when present (sometimes|required).
is_demo	boolean	no	
legal_name	string | null	no	maxLength 200
locale	string	no	maxLength 10 · Required when present (sometimes|required).
name	string	**yes**	maxLength 150
owner	object	**yes**	
owner.email	string(email)	no	maxLength 150
owner.name	string	no	maxLength 150
phone	string | null	no	maxLength 40
postal_code	string | null	no	maxLength 20
primary_color	any	no	pattern ^#[0-9a-fA-F]{6}$
registration_number	string | null	no	maxLength 60
settings	any[] | null	no	
slug	string | null	no	maxLength 80 · pattern ^[A-Za-z0-9_-]+$ · Must be unique within companies (per company).
state	string | null	no	maxLength 100
tax_number	string | null	no	maxLength 60
timezone	string	no	IANA timezone identifier. Required when present (sometimes|required).
website	string(uri) | null	no	maxLength 200

EXAMPLE REQUEST

```
{
  "name": "Sample name",
  "owner": {"email":"ali.raza@example.com","name":"Sample name"},
  "address_line1": "Shahrah-e-Faisal, Karachi",
  "address_line2": "Shahrah-e-Faisal, Karachi",
  "city": "Karachi",
  "code": "CODE-001",
  "country": "PK",
  "currency": "PKR"
}
```

RESPONSES

201 — `data` : PlatformCompany

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`GET` `/api/v1/platform/companies/{company}`

Get company (platform) `platformCompaniesShow`

Ek company ki poori tafseel deta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed.

Auth Session cookie

Permission Route: `platform.companies.manage`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`company`	path	integer	yes	ID of the Company.. · min 1

RESPONSES

200 — `data` : PlatformCompany

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

---

`PUT` `/api/v1/platform/companies/{company}`

Update company (platform) `platformCompaniesUpdate`

Maujooda company ko update karta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed. Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN`

Permission Route: `platform.companies.manage`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`company`	path	integer	yes	ID of the Company.. · min 1

REQUEST BODY `application/json` (OPTIONAL)

Field	Type	Req.	Constraints / notes
`address_line1`	string | null	no	maxLength 200
`address_line2`	string | null	no	maxLength 200
`city`	string | null	no	maxLength 100
`country`	string | null	no	minLength 2 · maxLength 2
`currency`	string	no	minLength 3 · maxLength 3 · pattern `^[A-Za-z]+$` · Required when present (`sometimes|required`).
`date_format`	string	no	values: `Y-m-d`, `d/m/Y`, `m/d/Y`, `d.m.Y`, `d M Y` · Required when present (`sometimes|required`).
`email`	string(email) | null	no	maxLength 150
`fiscal_year_start_month`	integer	no	min 1 · max 12 · Required when present (`sometimes|required`).

Field	Type	Req.	Constraints / notes
`is_demo`	boolean	no	
`legal_name`	string | null	no	maxLength 200
`locale`	string	no	maxLength 10 · Required when present (`sometimes|required`).
`name`	string	no	maxLength 150 · Required when present (`sometimes|required`).
`phone`	string | null	no	maxLength 40
`postal_code`	string | null	no	maxLength 20
`primary_color`	any	no	pattern `^#[0-9a-fA-F]{6}$`
`registration_number`	string | null	no	maxLength 60
`settings`	any[] | null	no	
`state`	string | null	no	maxLength 100
`tax_number`	string | null	no	maxLength 60
`timezone`	string	no	IANA timezone identifier. Required when present (`sometimes|required`).
`website`	string(uri) | null	no	maxLength 200

RESPONSES

200 — `data` : PlatformCompany

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

---

`PATCH` `/api/v1/platform/companies/{company}`

Update company (platform) `platformCompaniesUpdatePatch`

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /platform/companies/{company}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `platform.companies.manage`

`DELETE` `/api/v1/platform/companies/{company}`

Soft-delete. Only inactive companies may be deleted (409 otherwise). `platformCompaniesDestroy`

Company delete karta hai — kamyabi par `204` (khaali body).

> Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Route: `platform.companies.manage`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`company`	path	integer	**yes**	ID of the Company.. · min 1

RESPONSES

204 — No content. (khaali body)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `409` conflict · `419` auth.csrf · `429` throttled

POST /api/v1/platform/companies/{company}/activate

Activate – company (platform) platformCompaniesActivate

Company ko activate karta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Route: `platform.companies.manage`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
company	path	integer	yes	ID of the Company.. · min 1

RESPONSES

200 — `data` : PlatformCompany

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

POST /api/v1/platform/companies/{company}/deactivate

Deactivate – company (platform) platformCompaniesDeactivate

Company ko deactivate karta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed.

Auth Session cookie + `X-XSRF-TOKEN`

Permission Route: `platform.companies.manage`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
company	path	integer	yes	ID of the Company.. · min 1

RESPONSES

200 — `data` : PlatformCompany

`id` integer `name` string `legal_name` string | null `slug` string `code` string `email` string | null `phone` string | null `website` string | null `tax_number` string | null `registration_number` string | null `address` object `currency` string `timezone` string `locale` string `date_format` string `fiscal_year_start_month` integer `logo_url` string(uri) | null `primary_color` string | null `is_active` boolean `is_demo` boolean `settings` object `branches_count` integer `users_count` integer `created_at` string(date-time) | null `updated_at` string(date-time) | null ...aur 1 fields

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `429` throttled

GET /api/v1/platform/users

List users (platform) platformUsersIndex

Users ki list deta hai — results paginated hote hain (page , per_page).

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No X-Company-Id is needed. search matches (case-insensitive, substring): name , email .

Auth Session cookie

Permission Route: platform.users.manage

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[is_active]	query	string	no	Exact-match filter (comma-separated = koi bhi value). · values: true, false
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (name). The primary key is always appended as a tie-breaker. · values: name, -name, email, -email, created_at, -created_at, last_login_at, -last_login_at, is_active, -is_active · default name

RESPONSES

200 — data : array of PlatformUser + meta.pagination

id integer name string email string phone string | null avatar_url string(uri) | null is_active boolean platform_role string | null is_platform_admin boolean email_verified_at string(date-time) | null two_factor_enabled boolean last_login_at string(date-time) | null deactivated_at string(date-time) | null memberships_count integer memberships object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

GET /api/v1/platform/users/{user}

Get user (platform) platformUsersShow

Ek user ki poori tafseel deta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No X-Company-Id is needed.

Auth Session cookie

Permission Route: platform.users.manage

Throttle api

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
user	path	integer	yes	ID of the User.. · min 1

RESPONSES

200 — data : PlatformUser

id integer name string email string phone string | null avatar_url string(uri) | null is_active boolean platform_role string | null is_platform_admin boolean email_verified_at string(date-time) | null two_factor_enabled boolean last_login_at string(date-time) | null deactivated_at string(date-time) | null memberships_count integer memberships object[] created_at string(date-time) | null updated_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

PUT /api/v1/platform/users/{user}

Update user (platform) platformUsersUpdate

Maujooda user ko update karta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed. Registered for both PUT and PATCH (same handler; partial updates are accepted — fields use `sometimes`).

Auth Session cookie + `X-XSRF-TOKEN`

Permission Route: `platform.users.manage`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
`user`	path	integer	yes	ID of the User.. · min 1

REQUEST BODY application/json (OPTIONAL)

Field	Type	Req.	Constraints / notes
`is_active`	boolean	no	
`platform_role`	string | null	no	values: `platform.owner`, `platform.admin`,

RESPONSES

200 — `data` : PlatformUser

`id` integer `name` string `email` string `phone` string | null `avatar_url` string(uri) | null `is_active` boolean `platform_role` string | null `is_platform_admin` boolean `email_verified_at` string(date-time) | null `two_factor_enabled` boolean `last_login_at` string(date-time) | null `deactivated_at` string(date-time) | null `memberships_count` integer `memberships` object[] `created_at` string(date-time) | null `updated_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `419` auth.csrf · `422` validation.failed · `429` throttled

PATCH /api/v1/platform/users/{user}

Update user (platform) platformUsersUpdatePatch

Ye PUT wale update ka PATCH variant hai. Parameters, request body, permissions aur responses bilkul `PUT /platform/users/{user}` jaise hain (route `PUT|PATCH` ek hi handler share karta hai).

Permission `platform.users.manage`

GET /api/v1/platform/system

System – platform (platform) platformSystem

Platform/system ki maloomat deta hai (sirf platform staff).

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed.

Auth Session cookie

Permission Route: `platform.system.view`

Throttle `api`

RESPONSES

200 — `data` : object shape inferred from code

`app` object `php` object `database` object `services` object `counts` object `storage` object `tables` any[] `generated_at` string(date-time)

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

GET /api/v1/platform/audit-logs

List audit logs (platform) platformAuditLogsIndex

Audit logs ki list deta hai — results paginated hote hain (page , per_page).

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No X-Company-Id is needed. search matches (case-insensitive, substring): entity_label , action , actor_name .

Auth Session cookie

Permission Route: platform.system.view

Throttle api

List params page , per_page , search (standard — §Pagination dekhein)

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
filter[entity_type]	query	string	no	Exact-match filter (comma-separated = koi bhi value).
filter[actor_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
filter[entity_id]	query	integer	no	Exact-match filter (comma-separated = koi bhi value).
from	query	string(date)	no	Inclusive lower bound on created_at (UTC day start).
to	query	string(date)	no	Inclusive upper bound on created_at (UTC day end).
sort	query	string	no	Sort column; prefix with - for descending. Unknown columns fall back to the default (-created_at). The primary key is always appended as a tie-breaker. · values: created_at, -created_at, action, -action, entity_type, -entity_type, company_id, -company_id · default -created_at

RESPONSES

200 — data : array of AuditLog + meta.pagination

id integer company_id integer | null company object | null actor object actor_name string | null action string entity_type string | null entity_id integer | null entity_label string | null old_values any[] | null new_values any[] | null context object | null ip_address string | null user_agent string | null created_at string(date-time) | null

Errors: 401 auth.unauthenticated · 403 auth.forbidden · 404 not_found · 429 throttled

GET /api/v1/platform/audit-logs/{auditLog}

Get audit log (platform) platformAuditLogsShow

Ek audit log ki poori tafseel deta hai.

Platform administrators only — other users receive **404** so the panel's existence is not disclosed. No `X-Company-Id` is needed.

Auth Session cookie

Permission Route: `platform.system.view`

Throttle `api`

PARAMETERS

Parameter	In	Type	Req.	Description / constraints
auditLog	path	integer	yes	min 1

RESPONSES

200 — `data` : AuditLog

`id` integer `company_id` integer | null `company` object | null `actor` object `actor_name` string | null `action` string `entity_type` string | null `entity_id` integer | null `entity_label` string | null `old_values` any[] | null `new_values` any[] | null `context` object | null `ip_address` string | null `user_agent` string | null `created_at` string(date-time) | null

Errors: `401` auth.unauthenticated · `403` auth.forbidden · `404` not_found · `429` throttled

APPENDIX A

Schemas

Spec ke `components.schemas` ke saare object (aur primitive) schemas. Enum-only schemas Appendix B mein hain. Nested objects ek level tak `parent.field` ki shakal mein dikhaye gaye hain.

Account

Source: `App\Http\Resources\Finance\AccountResource`

Field	Type	Notes
`id`	integer	
`company_id`	integer	
`parent_id`	integer | null	
`code`	string	
`name`	string	
`type`	enum AccountType	values: `asset`, `liability`, `equity`, `revenue`, `expense`
`subtype`	string | null	
`normal_balance`	string	
`is_bank`	boolean	
`is_cash`	boolean	
`is_system`	boolean	
`is_active`	boolean	
`currency`	string	
`description`	string | null	
`opening_balance`	Money (string)	
`opening_balance_date`	string(date) | null	
`parent`	object	
`parent.id`	integer	
`parent.code`	string	
`parent.name`	string	
`lines_count`	integer	
`children_count`	integer	
`created_at`	string(date-time) | null	
`updated_at`	string(date-time) | null	

AttendanceRecord

Source: `App\Http\Resources\HR\AttendanceRecordResource`

Field	Type
`id`	integer
`company_id`	integer
`employee_id`	integer
`employee`	object
`employee.id`	integer
`employee.name`	string
`employee.employee_code`	string
`employee.department_id`	integer | null
`date`	string(date) | null
`check_in`	string(date-time) | null
`check_out`	string(date-time) | null
`status`	enum AttendanceStatus | null
`worked_minutes`	integer
`late_minutes`	integer
`source`	enum AttendanceSource | null
`notes`	string | null
`created_at`	string(date-time) | null
`updated_at`	string(date-time) | null

AuditLog

Source: `App\Http\Resources\Access\AuditLogResource`

Field	Type
id	integer
company_id	integer | null
company	object | null
company.id	integer
company.name	string
actor	object
actor.id	integer
actor.name	string
actor_name	string | null
action	string
entity_type	string | null
entity_id	integer | null
entity_label	string | null
old_values	any[] | null
new_values	any[] | null
context	object | null
ip_address	string | null
user_agent	string | null
created_at	string(date-time) | null

BankAccount

Source: `App\Http\Resources\Finance\BankAccountResource`

Field	Type
id	integer
company_id	integer
account_id	integer
account	object
account.id	integer
account.code	string
account.name	string
name	string
bank_name	string | null
account_number_masked	string | null
account_number_last4	string | null
iban_masked	string | null
swift	string | null
currency	string
opening_balance	Money (string)
is_active	boolean
created_at	string(date-time) | null
updated_at	string(date-time) | null

Bill

Source: `App\Http\Resources\Finance\Receivables\BillResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
supplier_id	integer	
supplier	object | null	
purchase_order_id	integer | null	
supplier_reference	string	
bill_date	string(date)	
due_date	string(date)	
currency	string	
status	enum BillStatus	values: `draft`, `pending_approval`, `approved`, `partially_paid`, `paid`, `overdue`, `void`
is_overdue	boolean	
subtotal	Money (string)	
discount_total	Money (string)	
tax_total	Money (string)	
total	Money (string)	
amount_paid	Money (string)	
balance_due	Money (string)	
notes	string | null	
branch_id	integer | null	
branch	object | null	
branch.id	integer	
branch.name	string	
journal_entry_id	integer | null	
created_by	integer | null	
approved_by	integer | null	
approver	object | null	
approver.id	integer	
approver.name	string	
approved_at	string(date-time) | null	
voided_at	string(date-time) | null	
void_reason	string | null	
lines	FinanceDocumentLine[]	
lines_count	integer	
payments	object[]	
payments[].allocation_id	integer	
payments[].payment_id	integer	

Field	Type	Notes
payments[].payment_number	string	
payments[].payment_date	string(date) | null	
payments[].method	enum PaymentMethod | null	
payments[].amount	Money (string)	
payments[].status	enum PaymentStatus | null	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

Branch

Source: `App\Http\Resources\Company\BranchResource`

Field	Type
id	integer
company_id	integer
name	string
code	string
is_head_office	boolean
email	string | null
phone	string | null
address	object
address.line1	string | null
address.line2	string | null
address.city	string | null
address.state	string | null
address.postal_code	string | null
address.country	string | null
latitude	Decimal (string) | null
longitude	Decimal (string) | null
timezone	string | null
is_active	boolean
departments_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

Company

Source: `App\Http\Resources\Company\CompanyResource`

Field	Type
id	integer
name	string
legal_name	string | null
slug	string
code	string
email	string | null
phone	string | null
website	string | null
tax_number	string | null
registration_number	string | null
address	object
address.line1	string | null
address.line2	string | null
address.city	string | null
address.state	string | null
address.postal_code	string | null
address.country	string | null
currency	string
timezone	string
locale	string
date_format	string
fiscal_year_start_month	integer
logo_url	string(uri) | null
primary_color	string | null
is_active	boolean
is_demo	boolean
settings	object
branches_count	integer
users_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

CompanyUser

Source: `App\Http\Resources\Access\CompanyUserResource`

Field	Type
id	integer
membership_id	integer
company_id	integer
name	string
email	string
phone	string | null
avatar_url	string(uri) | null
user_is_active	boolean
email_verified_at	string(date-time) | null
last_login_at	string(date-time) | null
is_active	boolean
is_default	boolean
branch_ids	any[] | null
roles	any[]
joined_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

Customer

Source: `App\Http\Resources\Sales\CustomerResource`

Field	Type
id	integer
company_id	integer
code	string
name	string
type	enum CustomerType | null
email	string | null
phone	string | null
website	string | null
tax_number	string | null
currency	string
payment_terms_days	integer
credit_limit	Money (string) | null
billing_address	object
billing_address.line1	string | null
billing_address.line2	string | null
billing_address.city	string | null
billing_address.state	string | null
billing_address.postal_code	string | null
billing_address.country	string | null
shipping_address	object
shipping_address.line1	string | null
shipping_address.line2	string | null
shipping_address.city	string | null
shipping_address.state	string | null
shipping_address.postal_code	string | null
shipping_address.country	string | null
latitude	Decimal (string) | null
longitude	Decimal (string) | null
sales_rep_id	integer | null
sales_rep	UserRef | null
source	string | null
tags	any[]
notes	string | null
is_active	boolean
contacts	CustomerContact[]
contacts_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

CustomerCommunication

Source: `App\Http\Resources\Sales\CustomerCommunicationResource`

Field	Type
id	integer
customer_id	integer
user_id	integer | null
user	UserRef | null
type	enum CommunicationType | null
subject	string
body	string | null
happened_at	string(date-time) | null
follow_up_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

CustomerContact

Source: `App\Http\Resources\Sales\CustomerContactResource`

Field	Type
id	integer
customer_id	integer
name	string
title	string | null
email	string | null
phone	string | null
is_primary	boolean
created_at	string(date-time) | null
updated_at	string(date-time) | null

Decimal

Exact decimal as a string (quantities, rates, hours, coordinates, aggregates). Never a float.

Type: string pattern `^-?\d+(\.\d+)?$`

Delivery

Source: `App\Http\Resources\Sales\DeliveryResource`

Field	Type
id	integer
company_id	integer
number	string
sales_order_id	integer
sales_order	object
sales_order.id	integer
sales_order.number	string
sales_order.status	enum SalesOrderStatus | null
sales_order.customer_id	integer
customer	object | null
customer.id	integer
customer.name	string
delivery_date	string(date) | null
status	enum DeliveryStatus | null
tracking_mode	string
carrier	string | null
tracking_number	string | null
shipped_at	string(date-time) | null
delivered_at	string(date-time) | null
cancelled_at	string(date-time) | null
notes	string | null
lines	object[]
lines[].id	integer
lines[].sales_order_line_id	integer
lines[].quantity	Decimal (string)
lines[].description	string | null
lines[].product_id	integer | null
lines[].uom	string | null
lines[].product	object | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

Department

Source: `App\Http\Resources\Company\DepartmentResource`

Field	Type
id	integer
company_id	integer
branch_id	integer | null
branch	object
branch.id	integer
branch.name	string
parent_id	integer | null
parent	object | null
parent.id	integer
parent.name	string
manager_employee_id	integer | null
name	string
code	string
description	string | null
is_active	boolean
children_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

Designation

Source: `App\Http\Resources\HR\DesignationResource`

Field	Type
id	integer
company_id	integer
title	string
code	string
level	integer
is_active	boolean
employees_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

Document

Source: `App\Http\Resources\Documents\DocumentResource`

Field	Type
id	integer
title	string
description	string | null
category	enum DocumentsDocumentCategory | null
tags	any[]
folder_id	integer | null
folder	object | null
folder.id	integer
folder.name	string
documentable_type	string | null
documentable_id	integer | null
visibility	enum DocumentVisibility | null
allowed_role_ids	any[]
owner_id	integer | null
owner	object | null
owner.id	integer
owner.name	string
current_version	DocumentVersion | null
versions	DocumentVersion[]
versions_count	integer
download_url	string
retention_until	string(date) | null
is_archived	boolean
archived_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

DocumentFolder

Source: `App\Http\Resources\Documents\DocumentFolderResource`

Field	Type
id	integer
parent_id	integer | null
name	string
is_private	boolean
owner_id	integer | null
documents_count	integer
children_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

DocumentVersion

Source: `App\Http\Resources\Documents\DocumentVersionResource`

Field	Type
id	integer
document_id	integer
version	integer
original_name	string
mime	string | null
size_bytes	integer
checksum_sha256	string
uploaded_by	integer | null
uploader	object | null
uploader.id	integer
uploader.name	string
note	string | null
created_at	string(date-time) | null

Employee

Source: `App\Http\Resources\HR\EmployeeResource`

Field	Type
id	integer
company_id	integer
employee_code	string
user_id	integer | null
user	object | null
user.id	integer
user.email	string
first_name	string
last_name	string
name	string
email	string
phone	string | null
date_of_birth	string(date) | null
gender	enum Gender | null
marital_status	enum MaritalStatus | null
address	object
address.line1	string | null
address.line2	string | null
address.city	string | null
address.state	string | null
address.postal_code	string | null
address.country	string | null
emergency_contact	object
emergency_contact.name	string | null
emergency_contact.phone	string | null
emergency_contact.relationship	string | null
branch_id	integer | null
branch	object | null
branch.id	integer
branch.name	string
department_id	integer | null
department	object | null
department.id	integer
department.name	string
designation_id	integer | null
designation	object | null
designation.id	integer
designation.title	string
manager_id	integer | null
manager	object | null
manager.id	integer
manager.name	string

Field	Type
manager.employee_code	string
employment_type	enum EmploymentType | null
status	enum EmployeeStatus | null
hired_at	string(date) | null
probation_ends_at	string(date) | null
terminated_at	string(date) | null
termination_reason	string | null
photo_url	string(uri) | null
base_salary	Money (string) | null
currency	string | null
bank_name	string | null
notes	string | null
reports_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null
sensitive	object
sensitive.national_id	string | null
sensitive.bank_account_number	string | null
sensitive.bank_iban	string | null
sensitive.tax_identifier	string | null

EmployeeDocument

Source: `App\Http\Resources\HR\EmployeeDocumentResource`

Field	Type
id	integer
company_id	integer
employee_id	integer
title	string
category	enum HRDocumentCategory | null
mime	string
size_bytes	integer
expires_at	string(date) | null
is_expired	boolean
is_confidential	boolean
uploaded_by	integer | null
uploader	object | null
uploader.id	integer
uploader.name	string
download_url	string
created_at	string(date-time) | null

EmployeeSalary

Source: `App\Http\Resources\Payroll\EmployeeSalaryResource`

Field	Type	Notes
id	integer	
employee_id	integer	
salary_structure_id	integer | null	
salary_structure	object | null	
salary_structure.id	integer	
salary_structure.name	string	
base_salary	Money (string)	
currency	string	
effective_from	string(date) | null	
effective_to	string(date) | null	
pay_frequency	enum PayFrequency	values: `monthly`
notes	string | null	
components	object[]	
components[].pay_component_id	integer	
components[].code	string	
components[].name	string	
components[].amount	Money (string) | null	
components[].rate	Decimal (string) | null	
created_by	object | null	
created_by.id	integer	
created_by.name	string	
created_at	string(date-time) | null	

EmployeeShift

Source: `App\Http\Resources\HR\EmployeeShiftResource`

Field	Type
id	integer
employee_id	integer
shift_id	integer
shift	object
shift.id	integer
shift.name	string
effective_from	string(date) | null
effective_to	string(date) | null
created_at	string(date-time) | null

EmploymentContract

Source: `App\Http\Resources\HR\EmploymentContractResource`

Field	Type
id	integer
company_id	integer
employee_id	integer
employee	object
employee.id	integer
employee.name	string
employee.employee_code	string
contract_type	enum EmploymentType | null
start_date	string(date) | null
end_date	string(date) | null
salary	Money (string)
currency	string
working_hours_per_week	Decimal (string)
has_document	boolean
status	enum ContractStatus | null
notes	string | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

Error

Field	Type	Notes
message	string	**required** · Human-readable, safe to display.
code	string	**required** · Stable machine code (see the error code table in the API description).
details	object	Optional structured context (e.g. `inventory.insufficient_stock` includes product_id, sku, warehouse_id, location_id, available, requested).
debug	object	Only when APP_DEBUG=true on 500 responses. Never present in production.

ExpenseClaim

Source: `App\Http\Resources\Finance\Receivables\ExpenseClaimResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
employee_id	integer | null	
user_id	integer	
user	object | null	
user.id	integer	
user.name	string	
claim_date	string(date)	
currency	string	
status	enum ExpenseClaimStatus	values: `draft`, `submitted`, `approved`, `rejected`, `paid`
subtotal	Money (string)	
tax_total	Money (string)	
total	Money (string)	
amount_paid	Money (string)	
balance_due	Money (string)	
notes	string | null	
branch_id	integer | null	
submitted_at	string(date-time) | null	
approver_id	integer | null	
approver	object | null	
approver.id	integer	
approver.name	string	
approved_at	string(date-time) | null	
rejection_reason	string | null	
journal_entry_id	integer | null	
lines	object[]	
lines[].id	integer	
lines[].line_no	integer	
lines[].expense_date	string(date)	
lines[].category	string	
lines[].account_id	integer	
lines[].description	string | null	
lines[].amount	Money (string)	
lines[].tax_rate_id	integer | null	
lines[].tax_rate	Decimal (string)	
lines[].tax_amount	Money (string)	
lines[].line_total	Money (string)	
lines[].has_receipt	boolean	

Field	Type	Notes
lines[].receipt_name	string | null	
lines_count	integer	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

ExportJob

Source: App\Http\Resources\Reports\ExportJobResource

Field	Type	Notes
id	string(uuid)	
report_key	string	
report_name	string	
format	string	
params	object	
status	enum ExportJobStatus	values: queued, running, completed, failed
row_count	integer | null	
error	string | null	
is_expired	boolean	
download_url	string | null	
created_at	string(date-time) | null	
started_at	string(date-time) | null	
finished_at	string(date-time) | null	
expires_at	string(date-time) | null	

FinanceDocumentLine

Source: App\Http\Resources\Finance\Receivables\DocumentLineResource

Field	Type
id	integer
line_no	integer
product_id	integer | null
product	object | null
product.id	integer
product.sku	string
product.name	string
description	string
quantity	Decimal (string)
unit_price	Money (string)
discount_percent	Decimal (string)
tax_rate_id	integer | null
tax_rate	Decimal (string)
account_id	integer
account	object | null
account.id	integer
account.code	string
account.name	string
line_subtotal	Money (string)
discount_amount	Money (string)
tax_amount	Money (string)
line_total	Money (string)

FinancialPeriod

Source: `App\Http\Resources\Finance\FinancialPeriodResource`

Field	Type	Notes
id	integer	
company_id	integer	
financial_year_id	integer	
name	string	
start_date	string(date)	
end_date	string(date)	
status	enum PeriodStatus	values: open, closed
closed_by	object | null	
closed_by.id	integer	
closed_by.name	string	
closed_at	string(date-time) | null	
financial_year	object	
financial_year.id	integer	
financial_year.name	string	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

FinancialYear

Source: `App\Http\Resources\Finance\FinancialYearResource`

Field	Type	Notes
id	integer	
company_id	integer	
name	string	
start_date	string(date)	
end_date	string(date)	
status	enum PeriodStatus	values: open, closed
periods	FinancialPeriod[]	
periods_count	integer	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

GoodsReceipt

Source: `App\Http\Resources\Procurement\GoodsReceiptResource`

Field	Type
id	integer
company_id	integer
number	string
status	enum GoodsReceiptStatus | null
purchase_order_id	integer
purchase_order	object | null
purchase_order.id	integer
purchase_order.number	string
purchase_order.status	enum PurchaseOrderStatus | null
purchase_order.supplier_id	integer
received_date	string(date) | null
warehouse_id	integer | null
warehouse	object | null
warehouse.id	integer
warehouse.name	string
received_by	integer | null
receiver	object | null
receiver.id	integer
receiver.name	string
supplier_delivery_note	string | null
notes	string | null
confirmed_at	string(date-time) | null
cancelled_at	string(date-time) | null
lines	GoodsReceiptLine[]
lines_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

GoodsReceiptLine

Source: `App\Http\Resources\Procurement\GoodsReceiptLineResource`

Field	Type
id	integer
purchase_order_line_id	integer
product_id	integer | null
product	object | null
product.id	integer
product.sku	string
product.name	string
description	string
quantity_ordered	Decimal (string)
quantity_received	Decimal (string)
quantity_rejected	Decimal (string)
rejection_reason	string | null
unit_cost	Money (string)
batch_number	string | null
expires_at	string(date) | null

Holiday

Source: `App\Http\Resources\HR\HolidayResource`

Field	Type
id	integer
company_id	integer
branch_id	integer | null
branch	object | null
branch.id	integer
branch.name	string
name	string
date	string(date) | null
is_recurring	boolean
created_at	string(date-time) | null
updated_at	string(date-time) | null

Invoice

Source: `App\Http\Resources\Finance\Receivables\InvoiceResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
customer_id	integer	
customer	object | null	
sales_order_id	integer | null	
invoice_date	string(date)	
due_date	string(date)	
currency	string	
status	enum InvoiceStatus	values: `draft`, `pending_approval`, `approved`, `partially_paid`, `paid`, `overdue`, `void`
is_overdue	boolean	
subtotal	Money (string)	
discount_total	Money (string)	
tax_total	Money (string)	
total	Money (string)	
amount_paid	Money (string)	
balance_due	Money (string)	
notes	string | null	
terms	string | null	
branch_id	integer | null	
branch	object | null	
branch.id	integer	
branch.name	string	
journal_entry_id	integer | null	
created_by	integer | null	
creator	object | null	
creator.id	integer	
creator.name	string	
approved_by	integer | null	
approver	object | null	
approver.id	integer	
approver.name	string	
approved_at	string(date-time) | null	
voided_at	string(date-time) | null	
void_reason	string | null	
lines	FinanceDocumentLine[]	
lines_count	integer	
payments	object[]	

Field	Type	Notes
payments[].allocation_id	integer	
payments[].payment_id	integer	
payments[].payment_number	string	
payments[].payment_date	string(date) | null	
payments[].method	enum PaymentMethod | null	
payments[].amount	Money (string)	
payments[].status	enum PaymentStatus | null	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

JournalEntry

Source: `App\Http\Resources\Finance\JournalEntryResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
entry_date	string(date)	
financial_period_id	integer | null	
period	object | null	
period.id	integer	
period.name	string	
period.status	enum PeriodStatus	values: `open`, `closed`
reference	string | null	
memo	string | null	
status	enum JournalEntryStatus	values: `draft`, `posted`, `reversed`
source_type	string | null	
source_id	integer | null	
branch_id	integer | null	
branch	object | null	
branch.id	integer	
branch.name	string	
total_debit	Money (string)	
total_credit	Money (string)	
is_balanced	boolean	
created_by	integer | null	
creator	object | null	
creator.id	integer	
creator.name	string	
posted_by	integer | null	
poster	object | null	
poster.id	integer	
poster.name	string	
posted_at	string(date-time) | null	
reverses_entry_id	integer | null	
reversed_by_entry_id	integer | null	
lines	JournalLine[]	
lines_count	integer	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

JournalLine

Source: `App\Http\Resources\Finance\JournalLineResource`

Field	Type
id	integer
line_no	integer
account_id	integer
account	object
account.id	integer
account.code	string
account.name	string
description	string | null
debit	Money (string)
credit	Money (string)
branch_id	integer | null
partner_type	string | null
partner_id	integer | null
tax_rate_id	integer | null

Lead

Source: `App\Http\Resources\Sales\LeadResource`

Field	Type
id	integer
company_id	integer
name	string
company_name	string | null
email	string | null
phone	string | null
source	enum LeadSource | null
status	enum LeadStatus | null
estimated_value	Money (string) | null
assigned_to	integer | null
assignee	UserRef | null
notes	string | null
converted_customer_id	integer | null
converted_customer	object | null
converted_customer.id	integer
converted_customer.name	string
converted_customer.code	string
converted_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

LeaveBalance

Source: `App\Http\Resources\HR\LeaveBalanceResource`

Field	Type
id	integer
company_id	integer
employee_id	integer
employee	object
employee.id	integer
employee.name	string
employee.employee_code	string
leave_type_id	integer
leave_type	object
leave_type.id	integer
leave_type.name	string
leave_type.code	string
leave_type.color	string | null
year	integer
entitled	Decimal (string)
used	Decimal (string)
carried_forward	Decimal (string)
adjusted	Decimal (string)
remaining	string
updated_at	string(date-time) | null

LeaveRequest

Source: `App\Http\Resources\HR\LeaveRequestResource`

Field	Type
`id`	integer
`company_id`	integer
`employee_id`	integer
`employee`	object
`employee.id`	integer
`employee.name`	string
`employee.employee_code`	string
`employee.department_id`	integer | null
`leave_type_id`	integer
`leave_type`	object
`leave_type.id`	integer
`leave_type.name`	string
`leave_type.code`	string
`leave_type.is_paid`	boolean
`leave_type.color`	string | null
`start_date`	string(date) | null
`end_date`	string(date) | null
`days`	Decimal (string)
`reason`	string | null
`status`	enum LeaveRequestStatus | null
`approver_id`	integer | null
`approver`	object | null
`approver.id`	integer
`approver.name`	string
`approved_at`	string(date-time) | null
`rejection_reason`	string | null
`has_attachment`	boolean
`created_at`	string(date-time) | null
`updated_at`	string(date-time) | null

LeaveType

Source: `App\Http\Resources\HR\LeaveTypeResource`

Field	Type
`id`	integer
`company_id`	integer
`name`	string
`code`	string
`days_per_year`	Decimal (string)
`is_paid`	boolean
`requires_approval`	boolean
`carry_forward`	boolean
`max_carry_forward_days`	Decimal (string) | null
`color`	string | null
`is_active`	boolean
`created_at`	string(date-time) | null
`updated_at`	string(date-time) | null

Message

Field	Type	Notes
`message`	string	**required**

Milestone

Source: `App\Http\Resources\Projects\MilestoneResource`

Field	Type
`id`	integer
`project_id`	integer
`name`	string
`description`	string | null
`due_date`	string(date) | null
`status`	enum MilestoneStatus | null
`completed_at`	string(date-time) | null
`position`	integer
`tasks_count`	integer
`created_at`	string(date-time) | null
`updated_at`	string(date-time) | null

Money

Monetary amount as a DECIMAL(18,4) string, e.g. `"1250.5000"`. Never a float. The currency is given by the owning document/company (`currency`).

Type: string pattern `^-?\d+\.\d{4}$`

Notification

Source: `App\Http\Resources\Notifications\NotificationResource`

Field	Type
id	string(uuid)
type	string
title	string
body	null | null
url	string(uri) | null
company_id	integer
meta	object
is_read	boolean
read_at	string(date-time) | null
created_at	string(date-time) | null

Opportunity

Source: `App\Http\Resources\Sales\OpportunityResource`

Field	Type
id	integer
company_id	integer
title	string
customer_id	integer | null
customer	object | null
customer.id	integer
customer.name	string
customer.code	string
lead_id	integer | null
stage_id	integer
stage	object
stage.id	integer
stage.name	string
stage.color	string | null
stage.probability	integer
value	Money (string)
currency	string
probability	integer
expected_close_date	string(date) | null
status	enum OpportunityStatus | null
lost_reason	string | null
owner_id	integer | null
owner	UserRef | null
closed_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

Pagination

Field	Type	Notes
page	integer	**required** · min 1
per_page	integer	**required** · min 1 · max 100
total	integer	**required** · min 0
last_page	integer	**required** · min 1

PaginationMeta

List metadata. (Laravel paginator `links` /extra meta keys may also be present on a few endpoints that return a raw paginated collection; clients should rely on `meta.pagination`.)

Field	Type	Notes
pagination	Pagination	**required**

PayComponent

Source: `App\Http\Resources\Payroll\PayComponentResource`

Field	Type	Notes
id	integer	
code	string	
name	string	
description	string | null	
kind	enum PayComponentKind	values: `earning`, `deduction`, `employer_contribution`
calculation	enum CalculationMethod	values: `fixed`, `percent_of_base`, `percent_of_gross`
default_amount	Money (string)	
default_rate	Decimal (string)	
is_taxable	boolean	
reduces_taxable	boolean	
affects_gross	boolean	
gl_account_code	string | null	
effective_gl_account_code	string	
sort_order	integer	
is_active	boolean	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

Payment

Source: `App\Http\Resources\Finance\Receivables\PaymentResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
type	enum PaymentType	values: receipt, payment
partner_type	enum PaymentPartnerType	values: customer, supplier, employee
partner_id	integer	
partner	object | null	
payment_date	string(date)	
method	enum PaymentMethod	values: cash, bank_transfer, cheque, card, other
bank_account_id	integer	
bank_account	object | null	
bank_account.id	integer	
bank_account.name	string	
bank_account.account_number	string | null	
amount	Money (string)	
currency	string	
reference	string | null	
notes	string | null	
status	enum PaymentStatus	values: posted, void
branch_id	integer | null	
journal_entry_id	integer | null	
created_by	integer | null	
voided_at	string(date-time) | null	
void_reason	string | null	
allocations	object[]	
allocations[].id	integer	
allocations[].type	string	
allocations[].document_id	integer	
allocations[].document_number	string	
allocations[].amount	Money (string)	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

PayrollRun

Source: `App\Http\Resources\Payroll\PayrollRunResource`

Field	Type	Notes
id	integer	
number	string	
name	string	
period_start	string(date) | null	
period_end	string(date) | null	
payment_date	string(date) | null	
currency	string	
status	enum PayrollRunStatus	values: draft, calculated, approved, finalized, paid, cancelled
branch_id	integer | null	
branch	object | null	
branch.id	integer	
branch.name	string	
department_id	integer | null	
department	object | null	
department.id	integer	
department.name	string	
totals	object	
totals.gross	Money (string)	
totals.tax	Money (string)	
totals.deductions	Money (string)	
totals.employer_contributions	Money (string)	
totals.net	Money (string)	
totals.employee_count	integer	
calculated_at	string(date-time) | null	
created_by	object | null	
created_by.id	integer	
created_by.name	string	
approved_by	object | null	
approved_by.id	integer	
approved_by.name	string	
approved_at	string(date-time) | null	
finalized_by	object | null	
finalized_by.id	integer	
finalized_by.name	string	
finalized_at	string(date-time) | null	
paid_at	string(date-time) | null	
bank_account_id	integer | null	

Field	Type	Notes
cancelled_at	string(date-time) | null	
journal_entry_id	integer | null	
payment_journal_entry_id	integer | null	
notes	string | null	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

Payslip

Source: `App\Http\Resources\Payroll\PayslipResource`

Field	Type	Notes
id	integer	
number	string | null	
status	enum PayrollRunStatus	values: draft, calculated, approved, finalized, paid, cancelled
payroll_run_id	integer	
run	object	
run.id	integer	
run.number	string	
run.name	string	
run.period_start	string(date)	
run.period_end	string(date)	
run.payment_date	string(date)	
employee	object	
employee.id	integer	
employee.code	string	
employee.name	string	
employee.department	string | null	
employee.designation	string | null	
employee.bank_name	string | null	
employee.bank_account	string | null	
currency	string	
base_salary	Money (string)	
working_days	Decimal (string)	
unpaid_days	Decimal (string)	
paid_days	Decimal (string)	
earned_base	Money (string)	
gross	Money (string)	
taxable	Money (string)	
tax	Money (string)	
total_deductions	Money (string)	
employer_contributions	Money (string)	
net	Money (string)	
warnings	any[]	
lines	object[]	
lines[].code	string	
lines[].name	string	
lines[].kind	enum PayComponentKind	values: earning, deduction, employer_contribution
lines[].calculation	string | null	

Field	Type	Notes
lines[].rate	Decimal (string) | null	
lines[].amount	Money (string)	
lines[].is_taxable	boolean	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

PerformanceReview

Source: `App\Http\Resources\HR\PerformanceReviewResource`

Field	Type
id	integer
company_id	integer
employee_id	integer
employee	object
employee.id	integer
employee.name	string
employee.employee_code	string
reviewer_id	integer | null
reviewer	object | null
reviewer.id	integer
reviewer.name	string
cycle	string
period_start	string(date) | null
period_end	string(date) | null
status	enum ReviewStatus | null
overall_rating	Decimal (string) | null
ratings	any[]
strengths	string | null
improvements	string | null
goals	string | null
submitted_at	string(date-time) | null
acknowledged_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

PipelineStage

Source: `App\Http\Resources\Sales\PipelineStageResource`

Field	Type
id	integer
name	string
probability	integer
position	integer
is_won	boolean
is_lost	boolean
color	string | null
opportunities_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

PlatformCompany

Source: `App\Http\Resources\Platform\PlatformCompanyResource`

Field	Type
id	integer
name	string
legal_name	string | null
slug	string
code	string
email	string | null
phone	string | null
website	string | null
tax_number	string | null
registration_number	string | null
address	object
address.line1	string | null
address.line2	string | null
address.city	string | null
address.state	string | null
address.postal_code	string | null
address.country	string | null
currency	string
timezone	string
locale	string
date_format	string
fiscal_year_start_month	integer
logo_url	string(uri) | null
primary_color	string | null
is_active	boolean
is_demo	boolean
settings	object
branches_count	integer
users_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null
deleted_at	string(date-time) | null

PlatformUser

Source: `App\Http\Resources\Platform\PlatformUserResource`

Field	Type
id	integer
name	string
email	string
phone	string | null
avatar_url	string(uri) | null
is_active	boolean
platform_role	string | null
is_platform_admin	boolean
email_verified_at	string(date-time) | null
two_factor_enabled	boolean
last_login_at	string(date-time) | null
deactivated_at	string(date-time) | null
memberships_count	integer
memberships	object[]
memberships[].company_id	integer
memberships[].company_name	string | null
memberships[].is_active	boolean
memberships[].is_default	boolean
memberships[].joined_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

Product

Source: `App\Http\Resources\Inventory\ProductResource`

Field	Type	Notes
id	integer	
company_id	integer	
sku	string	
barcode	string | null	
name	string	
description	string | null	
type	enum ProductType	values: goods, service
category_id	integer | null	
category	object | null	
category.id	integer	
category.name	string	
uom_id	integer | null	
uom	object | null	
uom.id	integer	
uom.name	string	
uom.symbol	string	
cost_price	Money (string)	
sale_price	Money (string)	
currency	string	
tax_rate	Decimal (string) | null	
reorder_level	Decimal (string)	
reorder_quantity	Decimal (string)	
track_batches	boolean	
track_serials	boolean	
is_active	boolean	
image_url	string(uri) | null	
attributes	object	
quantity_on_hand	Decimal (string)	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

ProductCategory

Source: `App\Http\Resources\Inventory\ProductCategoryResource`

Field	Type
id	integer
company_id	integer
parent_id	integer | null
parent	object | null
parent.id	integer
parent.name	string
name	string
code	string
is_active	boolean
children_count	integer
products_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

Project

Source: `App\Http\Resources\Projects\ProjectResource`

Field	Type
id	integer
number	string
name	string
code	string | null
description	string | null
customer_id	integer | null
department_id	integer | null
department	object | null
department.id	integer
department.name	string
branch_id	integer | null
branch	object | null
branch.id	integer
branch.name	string
manager_id	integer | null
manager	UserSummary | null
status	enum ProjectStatus | null
priority	enum Priority | null
start_date	string(date) | null
due_date	string(date) | null
completed_at	string(date-time) | null
budget	Money (string) | null
currency	string
color	string | null
is_billable	boolean
members	ProjectMember[]
members_count	integer
tasks_count	integer
done_tasks_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

ProjectExpense

Source: `App\Http\Resources\Projects\ProjectExpenseResource`

Field	Type
id	integer
project_id	integer
date	string(date) | null
category	string
description	string | null
amount	Money (string)
currency	string
receipt_document_id	integer | null
created_by	integer | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

ProjectMember

Source: `App\Http\Resources\Projects\ProjectMemberResource`

Field	Type
id	integer
project_id	integer
user_id	integer
user	UserSummary | null
role	string
created_at	string(date-time) | null

PurchaseOrder

Source: `App\Http\Resources\Procurement\PurchaseOrderResource`

Field	Type
id	integer
company_id	integer
number	string
status	enum PurchaseOrderStatus | null
supplier_id	integer
supplier	object | null
supplier.id	integer
supplier.code	string
supplier.name	string
requisition_id	integer | null
requisition	object | null
requisition.id	integer
requisition.number	string
branch_id	integer | null
order_date	string(date) | null
expected_date	string(date) | null
currency	string
subtotal	Money (string)
discount_total	Money (string)
tax_total	Money (string)
shipping_cost	Money (string)
total	Money (string)
warehouse_id	integer | null
warehouse	object | null
warehouse.id	integer
warehouse.name	string
delivery_address	string | null
payment_terms_days	integer
notes	string | null
terms	string | null
created_by	integer | null
creator	object | null
creator.id	integer
creator.name	string
submitted_at	string(date-time) | null
approved_by	integer | null
approver	object | null
approver.id	integer
approver.name	string
approved_at	string(date-time) | null
sent_at	string(date-time) | null
closed_at	string(date-time) | null
cancelled_at	string(date-time) | null
cancelled_reason	string | null
lines	PurchaseOrderLine[]
lines_count	integer
goods_receipts_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

PurchaseOrderLine

Source: `App\Http\Resources\Procurement\PurchaseOrderLineResource`

Field	Type
id	integer
line_no	integer
product_id	integer | null
product	object | null
product.id	integer
product.sku	string
product.name	string
description	string
quantity	Decimal (string)
uom	string | null
unit_price	Money (string)
discount_percent	Decimal (string)
tax_rate	Decimal (string)
line_subtotal	Money (string)
tax_amount	Money (string)
line_total	Money (string)
quantity_received	Decimal (string)
quantity_returned	Decimal (string)
quantity_remaining	string

PurchaseRequisition

Source: `App\Http\Resources\Procurement\PurchaseRequisitionResource`

Field	Type
id	integer
company_id	integer
number	string
status	enum RequisitionStatus | null
priority	enum RequisitionPriority | null
requester_id	integer
requester	object | null
requester.id	integer
requester.name	string
department_id	integer | null
department	object | null
department.id	integer
department.name	string
branch_id	integer | null
branch	object | null
branch.id	integer
branch.name	string
needed_by	string(date) | null
justification	string | null
estimated_total	Money (string)
submitted_at	string(date-time) | null
approver_id	integer | null
approver	object | null
approver.id	integer
approver.name	string
approved_at	string(date-time) | null
rejected_at	string(date-time) | null
rejection_reason	string | null
lines	PurchaseRequisitionLine[]
lines_count	integer
purchase_orders	object[]
purchase_orders[].id	integer
purchase_orders[].number	string
purchase_orders[].status	enum PurchaseOrderStatus | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

PurchaseRequisitionLine

Source: `App\Http\Resources\Procurement\PurchaseRequisitionLineResource`

Field	Type
id	integer
line_no	integer
product_id	integer | null
product	object | null
product.id	integer
product.sku	string
product.name	string
description	string
quantity	Decimal (string)
uom	string | null
estimated_unit_price	Money (string)
line_total	Money (string)

PurchaseReturn

Source:
`App\Http\Resources\Procurement\PurchaseReturnResource`

Field	Type
id	integer
company_id	integer
number	string
status	enum PurchaseReturnStatus | null
reason	enum PurchaseReturnReason | null
purchase_order_id	integer
purchase_order	object | null
purchase_order.id	integer
purchase_order.number	string
purchase_order.status	enum PurchaseOrderStatus | null
purchase_order.supplier_id	integer
goods_receipt_id	integer | null
goods_receipt	object | null
goods_receipt.id	integer
goods_receipt.number	string
return_date	string(date) | null
notes	string | null
total	Money (string)
created_by	integer | null
confirmed_at	string(date-time) | null
cancelled_at	string(date-time) | null
lines	PurchaseReturnLine[]
created_at	string(date-time) | null
updated_at	string(date-time) | null

PurchaseReturnLine

Source:
`App\Http\Resources\Procurement\PurchaseReturnLineResource`

Field	Type
id	integer
purchase_order_line_id	integer
product_id	integer | null
product	object | null
product.id	integer
product.sku	string
product.name	string
description	string
quantity	Decimal (string)
unit_cost	Money (string)
line_total	Money (string)

Quotation

Source: `App\Http\Resources\Sales\QuotationResource`

Field	Type
id	integer
company_id	integer
number	string
customer_id	integer
customer	object
customer.id	integer
customer.name	string
customer.code	string
date	string(date) | null
valid_until	string(date) | null
status	enum QuotationStatus | null
currency	string
subtotal	Money (string)
discount_total	Money (string)
tax_total	Money (string)
total	Money (string)
notes	string | null
terms	string | null
rejection_reason	string | null
sales_rep_id	integer | null
sales_rep	UserRef | null
created_by	integer | null
converted_sales_order_id	integer | null
lines	SalesDocumentLine[]
lines_count	integer
sent_at	string(date-time) | null
accepted_at	string(date-time) | null
rejected_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

Role

Source: `App\Http\Resources\Access\RoleResource`

Field	Type
id	integer
company_id	integer | null
slug	string
name	string
description	string | null
is_system	boolean
is_locked	boolean
users_count	integer
permissions_count	integer
permissions	object[]
permissions[].id	integer
permissions[].slug	string
permissions[].module	string
permissions[].description	string
created_at	string(date-time) | null
updated_at	string(date-time) | null

SalaryStructure

Source: `App\Http\Resources\Payroll\SalaryStructureResource`

Field	Type	Notes
id	integer	
name	string	
description	string | null	
currency	string	
is_active	boolean	
components	object[]	
components[].pay_component_id	integer	
components[].code	string	
components[].name	string	
components[].kind	enum PayComponentKind	values: earning, deduction, employer_contribution
components[].calculation	enum CalculationMethod	values: fixed, percent_of_base, percent_of_gross
components[].amount	Money (string) | null	
components[].rate	Decimal (string) | null	
components_count	integer	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

SalesDocumentLine

Source: `App\Http\Resources\Sales\DocumentLineResource`

Field	Type
id	integer
line_no	integer
product_id	integer | null
product	object | null
product.id	integer
product.sku	string
product.name	string
description	string
quantity	Decimal (string)
quantity_delivered	Decimal (string)
uom	string | null
unit_price	Money (string)
discount_percent	Decimal (string)
tax_rate	Decimal (string)
line_subtotal	Money (string)
tax_amount	Money (string)
line_total	Money (string)

SalesOrder

Source: `App\Http\Resources\Sales\SalesOrderResource`

Field	Type
id	integer
company_id	integer
number	string
customer_id	integer
customer	object
customer.id	integer
customer.name	string
customer.code	string
quotation_id	integer | null
order_date	string(date) | null
expected_delivery_date	string(date) | null
status	enum SalesOrderStatus | null
currency	string
subtotal	Money (string)
discount_total	Money (string)
tax_total	Money (string)
total	Money (string)
shipping_address	object
shipping_address.name	string | null
shipping_address.line1	string | null
shipping_address.line2	string | null
shipping_address.city	string | null
shipping_address.state	string | null
shipping_address.postal_code	string | null
shipping_address.country	string | null
warehouse_id	integer | null
warehouse	object | null
warehouse.id	integer
warehouse.name	string
notes	string | null
terms	string | null
sales_rep_id	integer | null
sales_rep	UserRef | null
created_by	integer | null
confirmed_at	string(date-time) | null
approved_by	integer | null
approver	UserRef | null
approved_at	string(date-time) | null
cancelled_reason	string | null
cancelled_at	string(date-time) | null
lines	SalesDocumentLine[]
lines_count	integer

Field	Type
deliveries	Delivery[]
deliveries_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

Session

Source: App\Http\Resources\Auth\SessionResource

Field	Type
user	object
user.id	integer
user.name	string
user.email	string
user.avatar_url	string(uri) | null
user.is_platform_admin	boolean
user.platform_role	string | null
user.two_factor_enabled	boolean
user.email_verified_at	string(date-time) | null
user.last_login_at	string(date-time) | null
user.preferences	any[]
companies	object[]
companies[].id	integer
companies[].name	string
companies[].slug	string
companies[].logo_url	string(uri) | null
companies[].currency	string
companies[].timezone	string
companies[].role	string | null
companies[].branch_ids	any[] | null
companies[].is_default	boolean
current_company	object | null
current_company.id	integer
current_company.name	string
current_company.slug	string
current_company.logo_url	string(uri) | null
current_company.currency	string
current_company.timezone	string
current_company.role	string | null
current_company.branch_ids	any[] | null
current_company.is_default	boolean
permissions	any[]
branches	object[]
branches[].id	integer
branches[].company_id	integer
branches[].name	string
branches[].code	string
branches[].is_head_office	boolean

Shift

Source: `App\Http\Resources\HR\ShiftResource`

Field	Type
id	integer
company_id	integer
name	string
start_time	string
end_time	string
break_minutes	integer
days_of_week	any[]
is_default	boolean
assignments_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

StockAdjustment

Source: `App\Http\Resources\Inventory\StockAdjustmentResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
status	enum StockAdjustmentStatus	values: draft, posted
reason	enum StockAdjustmentReason	values: count, damage, loss, correction, expiry
warehouse_id	integer	
warehouse	object	
warehouse.id	integer	
warehouse.name	string	
warehouse.code	string	
notes	string | null	
lines	object[]	
lines[].id	integer	
lines[].product_id	integer	
lines[].product	object | null	
lines[].counted_quantity	Decimal (string)	
lines[].system_quantity	Decimal (string)	
lines[].difference	Decimal (string)	
lines[].unit_cost	Money (string)	
lines_count	integer	
posted_at	string(date-time) | null	
created_by	integer | null	
posted_by	integer | null	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

StockLevel

Source: `App\Http\Resources\Inventory\StockLevelResource`

Field	Type
`id`	integer
`product_id`	integer
`product`	object
`product.id`	integer
`product.sku`	string
`product.name`	string
`product.reorder_level`	Decimal (string)
`product.uom`	object | null
`warehouse_id`	integer
`warehouse`	object
`warehouse.id`	integer
`warehouse.name`	string
`warehouse.code`	string
`location_id`	integer | null
`location`	object | null
`location.id`	integer
`location.code`	string
`location.name`	string
`quantity_on_hand`	Decimal (string)
`quantity_reserved`	Decimal (string)
`quantity_available`	Decimal (string)
`average_cost`	Money (string)
`stock_value`	Decimal (string)
`updated_at`	string(date-time) | null

StockMovement

Source: `App\Http\Resources\Inventory\StockMovementResource`

Field	Type	Notes
`id`	integer	
`company_id`	integer	
`product_id`	integer	
`product`	object	
`product.id`	integer	
`product.sku`	string	
`product.name`	string	
`warehouse_id`	integer	
`warehouse`	object	
`warehouse.id`	integer	
`warehouse.name`	string	
`warehouse.code`	string	
`location_id`	integer | null	
`batch_id`	integer | null	
`batch`	object | null	
`batch.id`	integer	
`batch.batch_number`	string	
`batch.expires_at`	string(date) | null	
`type`	enum StockMovementType	11 values (Appendix B)
`quantity`	Decimal (string)	
`unit_cost`	Money (string)	
`total_cost`	Money (string)	
`balance_after`	Money (string)	
`reference_type`	string | null	
`reference_id`	integer | null	
`reason`	string | null	
`moved_at`	string(date-time) | null	
`created_by`	integer | null	
`creator`	object | null	
`creator.id`	integer	
`creator.name`	string	
`created_at`	string(date-time) | null	

StockTransfer

Source: `App\Http\Resources\Inventory\StockTransferResource`

Field	Type	Notes
id	integer	
company_id	integer	
number	string	
status	enum StockTransferStatus	values: draft, in_transit, received, cancelled
from_warehouse_id	integer	
from_warehouse	object	
from_warehouse.id	integer	
from_warehouse.name	string	
from_warehouse.code	string	
to_warehouse_id	integer	
to_warehouse	object	
to_warehouse.id	integer	
to_warehouse.name	string	
to_warehouse.code	string	
notes	string | null	
lines	object[]	
lines[].id	integer	
lines[].product_id	integer	
lines[].product	object | null	
lines[].quantity	Decimal (string)	
lines[].unit_cost	Money (string)	
lines_count	integer	
shipped_at	string(date-time) | null	
received_at	string(date-time) | null	
created_by	integer | null	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

StorageLocation

Source: `App\Http\Resources\Inventory\StorageLocationResource`

Field	Type	Notes
id	integer	
company_id	integer	
warehouse_id	integer	
parent_id	integer | null	
parent	object | null	
parent.id	integer	
parent.code	string	
parent.name	string	
code	string	
name	string	
type	enum StorageLocationType	values: zone, aisle, rack, bin
is_active	boolean	
children_count	integer	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

Supplier

Source: `App\Http\Resources\Procurement\SupplierResource`

Field	Type
id	integer
company_id	integer
code	string
name	string
type	enum SupplierType | null
email	string | null
phone	string | null
website	string | null
tax_number	string | null
currency	string
payment_terms_days	integer
credit_limit	Money (string) | null
address	object
address.line1	string | null
address.line2	string | null
address.city	string | null
address.state	string | null
address.postal_code	string | null
address.country	string | null
latitude	Decimal (string) | null
longitude	Decimal (string) | null
bank_name	string | null
bank_account_last4	string | null
rating	integer | null
lead_time_days	integer | null
categories	any[]
notes	string | null
is_active	boolean
is_approved	boolean
approved_at	string(date-time) | null
approver	object | null
approver.id	integer
approver.name	string
contacts	SupplierContact[]
contacts_count	integer
purchase_orders_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

SupplierContact

Source: `App\Http\Resources\Procurement\SupplierContactResource`

Field	Type
id	integer
supplier_id	integer
name	string
title	string | null
email	string | null
phone	string | null
is_primary	boolean
created_at	string(date-time) | null
updated_at	string(date-time) | null

Task

Source: `App\Http\Resources\Projects\TaskResource`

Field	Type
id	integer
project_id	integer
project	object | null
project.id	integer
project.number	string
project.name	string
parent_id	integer | null
milestone_id	integer | null
milestone	object | null
milestone.id	integer
milestone.name	string
title	string
description	string | null
status	enum TaskStatus | null
priority	enum Priority | null
assignee_id	integer | null
assignee	UserSummary | null
reporter_id	integer | null
reporter	UserSummary | null
start_date	string(date) | null
due_date	string(date) | null
estimate_hours	Decimal (string) | null
position	integer
completed_at	string(date-time) | null
labels	any[]
subtasks	Task[]
subtasks_count	integer
comments_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

TaskComment

Source: `App\Http\Resources\Projects\TaskCommentResource`

Field	Type
id	integer
task_id	integer
user_id	integer | null
user	UserSummary | null
body	string
edited_at	string(date-time) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

TaxRate

Source: `App\Http\Resources\Finance\TaxRateResource`

Field	Type	Notes
id	integer	
company_id	integer	
name	string	
code	string	
rate	Decimal (string)	
type	enum TaxRateType	values: sales, purchase, both
account_id	integer | null	
account	object | null	
account.id	integer	
account.code	string	
account.name	string	
is_compound	boolean	
is_active	boolean	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

TaxTable

Source: `App\Http\Resources\Payroll\TaxTableResource`

Field	Type	Notes
id	integer	
name	string	
effective_from	string(date) | null	
period	enum TaxTablePeriod	values: monthly, annual
is_active	boolean	
notes	string | null	
brackets	object[]	
brackets[].id	integer	
brackets[].from_amount	Money (string)	
brackets[].to_amount	Money (string) | null	
brackets[].rate	Decimal (string)	
brackets[].fixed_amount	Money (string)	
brackets_count	integer	
created_at	string(date-time) | null	
updated_at	string(date-time) | null	

TimeEntry

Source: `App\Http\Resources\Projects\TimeEntryResource`

Field	Type
id	integer
project_id	integer
project	object | null
project.id	integer
project.number	string
project.name	string
task_id	integer | null
task	object | null
task.id	integer
task.title	string
user_id	integer
user	UserSummary | null
date	string(date) | null
hours	Decimal (string)
description	string | null
is_billable	boolean
hourly_rate	Money (string) | null
created_at	string(date-time) | null
updated_at	string(date-time) | null

UnitOfMeasure

Source: `App\Http\Resources\Inventory\UnitOfMeasureResource`

Field	Type
id	integer
company_id	integer
name	string
symbol	string
precision	integer
is_active	boolean
products_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

UserRef

Minimal user reference.

Field	Type	Notes
id	integer	**required**
name	string	**required**

UserSummary

Field	Type	Notes
id	integer	**required**
name	string	**required**
avatar_url	string(uri) | null	

ValidationError

Field	Type	Notes
message	string	**required** · Human-readable, safe to display.
code	string	**required** · values: `validation.failed`, `tenant.mismatch`, `finance.unbalanced`
details	object	Optional structured context (e.g. `inventory.insufficient_stock` includes product_id, sku, warehouse_id, location_id, available, requested).
debug	object	Only when APP_DEBUG=true on 500 responses. Never present in production.
errors	object	**required** · Field path (dot notation, e.g. `lines.0.quantity`) → list of messages. Absent for `tenant.mismatch`/`finance.unbalanced`.

Warehouse

Source: `App\Http\Resources\Inventory\WarehouseResource`

Field	Type
id	integer
company_id	integer
branch_id	integer | null
branch	object | null
branch.id	integer
branch.name	string
name	string
code	string
address	object
address.line1	string | null
address.line2	string | null
address.city	string | null
address.state	string | null
address.postal_code	string | null
address.country	string | null
latitude	Decimal (string) | null
longitude	Decimal (string) | null
is_active	boolean
is_default	boolean
locations_count	integer
created_at	string(date-time) | null
updated_at	string(date-time) | null

APPENDIX B

Enums

Allowed values (`app/Enums/**` se). Request mein inhi exact strings ko bhejein.

Enum	Allowed values
`AccountSubtype` App\Enums\Finance\AccountSubtype	`cash` `bank` `receivable` `inventory` `prepaid` `current_asset` `fixed_asset` `accumulated_depreciation` `intangible` `investment` `payable` `tax` `accrued_payroll` `accrued_liability` `current_liability` `loan` `long_term_liability` `share_capital` `retained_earnings` `owner_drawings` `other_equity` `sales_revenue` `service_revenue` `other_income` `cost_of_sales` `operating_expense` `payroll_expense` `depreciation` `finance_cost` `tax_expense` `other_expense`
`AccountType` App\Enums\Finance\AccountType	`asset` `liability` `equity` `revenue` `expense`
`AttendanceSource` App\Enums\HR\AttendanceSource	`manual` `import` `biometric` `self`
`AttendanceStatus` App\Enums\HR\AttendanceStatus	`present` `absent` `late` `half_day` `on_leave` `holiday` `weekend`
`BillStatus` App\Enums\Finance\BillStatus	`draft` `pending_approval` `approved` `partially_paid` `paid` `overdue` `void`
`CalculationMethod` App\Enums\Payroll\CalculationMethod	`fixed` `percent_of_base` `percent_of_gross`
`CommunicationType` App\Enums\Sales\CommunicationType	`call` `email` `meeting` `note`
`ContractStatus` App\Enums\HR\ContractStatus	`active` `expired` `terminated`
`CustomerType` App\Enums\Sales\CustomerType	`individual` `company`
`DeliveryStatus` App\Enums\Sales\DeliveryStatus	`pending` `in_transit` `delivered` `cancelled`
`DocumentableType` App\Enums\Documents\DocumentableType	`project` `task` `employee` `invoice` `bill` `purchase_order` `customer` `supplier`
`DocumentsDocumentCategory` App\Enums\Documents\DocumentCategory	`contract` `policy` `invoice` `purchase` `employee` `legal` `certificate` `report` `other`
`DocumentVisibility` App\Enums\Documents\DocumentVisibility	`company` `restricted` `private`
`EmployeeStatus` App\Enums\HR\EmployeeStatus	`probation` `active` `on_leave` `suspended` `terminated`
`EmploymentType` App\Enums\HR\EmploymentType	`full_time` `part_time` `contract` `intern`
`ExpenseClaimStatus` App\Enums\Finance\ExpenseClaimStatus	`draft` `submitted` `approved` `rejected` `paid`
`ExportJobStatus` App\Models\Reports\ExportJobStatus	`queued` `running` `completed` `failed`
`Gender` App\Enums\HR\Gender	`male` `female` `other` `prefer_not_to_say`
`GoodsReceiptStatus` App\Enums\Procurement\GoodsReceiptStatus	`draft` `confirmed` `cancelled`
`HRDocumentCategory` App\Enums\HR\DocumentCategory	`contract` `id` `certificate` `visa` `other`
`InvoiceStatus` App\Enums\Finance\InvoiceStatus	`draft` `pending_approval` `approved` `partially_paid` `paid` `overdue` `void`

Enum	Allowed values
`JournalEntryStatus` App\Enums\Finance\JournalEntryStatus	`draft` `posted` `reversed`
`JournalSourceType` App\Enums\Finance\JournalSourceType	`manual` `invoice` `bill` `payment` `expense_claim` `payroll_run` `stock_adjustment` `opening_balance`
`LeadSource` App\Enums\Sales\LeadSource	`website` `referral` `campaign` `cold_call` `event` `other`
`LeadStatus` App\Enums\Sales\LeadStatus	`new` `contacted` `qualified` `unqualified` `converted`
`LeaveRequestStatus` App\Enums\HR\LeaveRequestStatus	`pending` `approved` `rejected` `cancelled`
`MaritalStatus` App\Enums\HR\MaritalStatus	`single` `married` `divorced` `widowed`
`MilestoneStatus` App\Enums\Projects\MilestoneStatus	`pending` `completed`
`OpportunityStatus` App\Enums\Sales\OpportunityStatus	`open` `won` `lost`
`PayComponentKind` App\Enums\Payroll\PayComponentKind	`earning` `deduction` `employer_contribution`
`PayFrequency` App\Enums\Payroll\PayFrequency	`monthly`
`PaymentMethod` App\Enums\Finance\PaymentMethod	`cash` `bank_transfer` `cheque` `card` `other`
`PaymentPartnerType` App\Enums\Finance\PaymentPartnerType	`customer` `supplier` `employee`
`PaymentStatus` App\Enums\Finance\PaymentStatus	`posted` `void`
`PaymentType` App\Enums\Finance\PaymentType	`receipt` `payment`
`PayrollRunStatus` App\Enums\Payroll\PayrollRunStatus	`draft` `calculated` `approved` `finalized` `paid` `cancelled`
`PeriodStatus` App\Enums\Finance\PeriodStatus	`open` `closed`
`Priority` App\Enums\Projects\Priority	`low` `medium` `high` `critical`
`ProductType` App\Enums\Inventory\ProductType	`goods` `service`
`ProjectMemberRole` App\Enums\Projects\ProjectMemberRole	`manager` `member` `viewer`
`ProjectStatus` App\Enums\Projects\ProjectStatus	`planning` `active` `on_hold` `completed` `cancelled`
`PurchaseOrderStatus` App\Enums\Procurement\PurchaseOrderStatus	`draft` `submitted` `approved` `partially_received` `received` `closed` `cancelled`
`PurchaseReturnReason` App\Enums\Procurement\PurchaseReturnReason	`damaged` `wrong_item` `quality` `excess` `other`
`PurchaseReturnStatus` App\Enums\Procurement\PurchaseReturnStatus	`draft` `confirmed` `cancelled`
`QuotationStatus` App\Enums\Sales\QuotationStatus	`draft` `sent` `accepted` `rejected` `expired` `converted`
`RequisitionPriority` App\Enums\Procurement\RequisitionPriority	`low` `normal` `high` `urgent`
`RequisitionStatus` App\Enums\Procurement\RequisitionStatus	`draft` `submitted` `approved` `rejected` `ordered` `cancelled`

Enum	Allowed values
`ReviewStatus` App\Enums\HR\ReviewStatus	`draft` `submitted` `acknowledged`
`SalesOrderStatus` App\Enums\Sales\SalesOrderStatus	`draft` `confirmed` `approved` `partially_delivered` `delivered` `cancelled`
`SerialStatus` App\Enums\Inventory\SerialStatus	`in_stock` `issued` `returned` `scrapped`
`StockAdjustmentReason` App\Enums\Inventory\StockAdjustmentReason	`count` `damage` `loss` `correction` `expiry`
`StockAdjustmentStatus` App\Enums\Inventory\StockAdjustmentStatus	`draft` `posted`
`StockMovementType` App\Enums\Inventory\StockMovementType	`receipt` `issue` `transfer_in` `transfer_out` `adjustment_in` `adjustment_out` `sale` `purchase` `return_in` `return_out` `opening`
`StockTransferStatus` App\Enums\Inventory\StockTransferStatus	`draft` `in_transit` `received` `cancelled`
`StorageLocationType` App\Enums\Inventory\StorageLocationType	`zone` `aisle` `rack` `bin`
`SupplierType` App\Enums\Procurement\SupplierType	`individual` `company`
`TaskStatus` App\Enums\Projects\TaskStatus	`todo` `in_progress` `in_review` `done` `blocked`
`TaxRateType` App\Enums\Finance\TaxRateType	`sales` `purchase` `both`
`TaxTablePeriod` App\Enums\Payroll\TaxTablePeriod	`monthly` `annual`

APPENDIX C

Permission slugs → endpoints

91 permission slugs. Har slug ke saath woh endpoints jin ke `x-permissions` mein ye slug hai (route middleware ya policy). Route par kai slugs hon to koi ek kaafi hai. Path par click karke endpoint card khulta hai.

accounts.manage 5 endpoints

- POST /accounts/seed-defaults
- POST /accounts
- PUT /accounts/{account}
- PATCH /accounts/{account}
- DELETE /accounts/{account}

accounts.view 12 endpoints

- GET /accounts/tree
- GET /accounts/{account}/ledger
- GET /accounts
- GET /accounts/{account}
- GET /financial-years
- GET /financial-years/{financial_year}
- GET /financial-periods
- GET /financial-periods/{financial_period}
- GET /tax-rates
- GET /tax-rates/{tax_rate}
- GET /bank-accounts
- GET /bank-accounts/{bank_account}

approvals.view 2 endpoints

- GET /approvals/counts
- GET /approvals

attendance.manage 5 endpoints

- POST /attendance/bulk
- POST /attendance
- PUT /attendance/{attendance}
- PATCH /attendance/{attendance}
- DELETE /attendance/{attendance}

attendance.view 8 endpoints

- GET /employees/{employee}/shifts
- GET /shifts
- GET /shifts/{shift}
- GET /holidays
- GET /holidays/{holiday}
- GET /attendance/summary
- GET /attendance
- GET /attendance/{attendance}

audit.view 2 endpoints

- GET /audit-logs
- GET /audit-logs/{auditLog}

bank.manage 6 endpoints

- GET /bank-accounts
- POST /bank-accounts
- GET /bank-accounts/{bank_account}
- PUT /bank-accounts/{bank_account}
- PATCH /bank-accounts/{bank_account}
- DELETE /bank-accounts/{bank_account}

bills.approve 2 endpoints

- POST /bills/{bill}/approve
- POST /bills/{bill}/void

bills.create 5 endpoints

- POST /bills/{bill}/submit
- POST /bills
- PUT /bills/{bill}
- PATCH /bills/{bill}
- DELETE /bills/{bill}

bills.view 2 endpoints

- GET /bills
- GET /bills/{bill}

branches.manage 4 endpoints

- POST /branches
- PUT /branches/{branch}
- PATCH /branches/{branch}
- DELETE /branches/{branch}

branches.view 3 endpoints

- GET /branches/all
- GET /branches
- GET /branches/{branch}

company.settings.manage 3 endpoints

- PUT /company
- POST /company/logo
- DELETE /company/logo

customers.manage 10 endpoints

- POST /customers
- PUT /customers/{customer}
- PATCH /customers/{customer}
- DELETE /customers/{customer}
- POST /customers/{customer}/contacts
- PUT /customers/{customer}/contacts/{contact}
- DELETE /customers/{customer}/contacts/{contact}
- POST /customers/{customer}/communications
- PUT /customers/{customer}/communications/{communication}
- DELETE /customers/{customer}/communications/{communication}

customers.view 6 endpoints

- GET /customers/all
- GET /customers/map
- GET /customers
- GET /customers/{customer}
- GET /customers/{customer}/summary
- GET /customers/{customer}/communications

dashboard.view 1 endpoint

- GET /dashboard

departments.manage 4 endpoints

- POST /departments
- PUT /departments/{department}
- PATCH /departments/{department}
- DELETE /departments/{department}

departments.view 3 endpoints

- GET /departments/tree
- GET /departments
- GET /departments/{department}

documents.manage 9 endpoints

- POST /document-folders
- PUT /document-folders/{folder}
- PATCH /document-folders/{folder}
- DELETE /document-folders/{folder}
- POST /documents/{document}/versions
- POST /documents
- PUT /documents/{document}
- PATCH /documents/{document}
- DELETE /documents/{document}

documents.view 8 endpoints

- GET /document-folders
- GET /document-folders/{folder}
- GET /documents/{document}/download
- GET /documents/{document}/shared-download
- POST /documents/{document}/share-link
- GET /documents/{document}/versions
- GET /documents
- GET /documents/{document}

employees.create 1 endpoint

- POST /employees

employees.delete 1 endpoint

- DELETE /employees/{employee}

employees.documents.view 3 endpoints

- GET /employees/{employee}/documents
- GET /employee-documents/{employee_document}/download
- GET /employment-contracts/{employment_contract}/document

employees.update 17 endpoints

- POST /designations
- PUT /designations/{designation}
- PATCH /designations/{designation}
- DELETE /designations/{designation}
- POST /employees/{employee}/terminate
- POST /employees/{employee}/reactivate
- POST /employees/{employee}/photo
- POST /employees/{employee}/shifts
- POST /employees/{employee}/documents
- GET /employees/{employee}
- PUT /employees/{employee}
- PATCH /employees/{employee}
- DELETE /employee-documents/{employee_document}
- POST /employment-contracts
- PUT /employment-contracts/{employment_contract}
- PATCH /employment-contracts/{employment_contract}
- DELETE /employment-contracts/{employment_contract}

employees.view 17 endpoints

- GET /designations
- GET /designations/{designation}
- GET /employees/directory
- GET /employees/org-chart
- GET /employees/{employee}/shifts
- GET /employees
- GET /employees/{employee}
- GET /employment-contracts/{employment_contract}/document
- GET /employment-contracts
- GET /employment-contracts/{employment_contract}
- GET /shifts
- GET /shifts/{shift}
- GET /holidays
- GET /holidays/{holiday}
- GET /hr/reports/headcount
- GET /hr/reports/attendance
- GET /hr/reports/leave

expenses.approve 5 endpoints

- POST /expense-claims/{expenseClaim}/approve
- POST /expense-claims/{expenseClaim}/reject
- GET /expense-claims/{expenseClaim}/lines/{line}/receipt
- GET /expense-claims
- GET /expense-claims/{expenseClaim}

expenses.submit 9 endpoints

- POST /expense-claims/{expenseClaim}/submit
- GET /expense-claims/{expenseClaim}/lines/{line}/receipt
- POST /expense-claims/{expenseClaim}/lines/{line}/receipt
- GET /expense-claims
- POST /expense-claims
- GET /expense-claims/{expenseClaim}
- PUT /expense-claims/{expenseClaim}
- PATCH /expense-claims/{expenseClaim}
- DELETE /expense-claims/{expenseClaim}

expenses.view 3 endpoints

- GET /expense-claims/{expenseClaim}/lines/{line}/receipt
- GET /expense-claims
- GET /expense-claims/{expenseClaim}

goods_receipts.manage 16 endpoints

- POST /purchase-orders/{purchase_order}/goods-receipts
- POST /goods-receipts/{goods_receipt}/confirm
- POST /goods-receipts/{goods_receipt}/cancel
- GET /goods-receipts
- GET /goods-receipts/{goods_receipt}
- PUT /goods-receipts/{goods_receipt}
- PATCH /goods-receipts/{goods_receipt}
- DELETE /goods-receipts/{goods_receipt}
- POST /purchase-returns/{purchase_return}/confirm
- POST /purchase-returns/{purchase_return}/cancel
- GET /purchase-returns
- POST /purchase-returns
- GET /purchase-returns/{purchase_return}
- PUT /purchase-returns/{purchase_return}
- PATCH /purchase-returns/{purchase_return}
- DELETE /purchase-returns/{purchase_return}

inventory.adjust 7 endpoints

- GET /stock-adjustments
- POST /stock-adjustments
- GET /stock-adjustments/{stock_adjustment}
- PUT /stock-adjustments/{stock_adjustment}
- PATCH /stock-adjustments/{stock_adjustment}
- DELETE /stock-adjustments/{stock_adjustment}
- POST /stock-adjustments/{stock_adjustment}/post

inventory.issue 1 endpoint

- POST /stock/issue

inventory.receive 1 endpoint

- POST /stock/receive

inventory.transfer 9 endpoints

- GET /stock-transfers
- POST /stock-transfers
- GET /stock-transfers/{stock_transfer}
- PUT /stock-transfers/{stock_transfer}
- PATCH /stock-transfers/{stock_transfer}
- DELETE /stock-transfers/{stock_transfer}
- POST /stock-transfers/{stock_transfer}/ship
- POST /stock-transfers/{stock_transfer}/receive
- POST /stock-transfers/{stock_transfer}/cancel

inventory.view 11 endpoints

- GET /products/{product}/batches
- GET /products/{product}/stock
- GET /products/{product}/movements
- GET /stock/levels
- GET /stock/movements
- GET /stock-transfers
- GET /stock-transfers/{stock_transfer}
- GET /stock-adjustments
- GET /stock-adjustments/{stock_adjustment}
- GET /inventory/reports/valuation
- GET /inventory/reports/movement-summary

invoices.approve 2 endpoints

- POST /invoices/{invoice}/approve
- POST /invoices/{invoice}/void

invoices.create 2 endpoints

- POST /invoices/{invoice}/submit
- POST /invoices

invoices.delete 1 endpoint

- DELETE /invoices/{invoice}

invoices.update 3 endpoints

- POST /invoices/{invoice}/submit
- PUT /invoices/{invoice}
- PATCH /invoices/{invoice}

invoices.view 3 endpoints

- GET /invoices/{invoice}/pdf
- GET /invoices
- GET /invoices/{invoice}

journals.create 4 endpoints

- POST /journal-entries
- PUT /journal-entries/{journal_entry}
- PATCH /journal-entries/{journal_entry}
- DELETE /journal-entries/{journal_entry}

journals.post 2 endpoints

- POST /journal-entries/{journalEntry}/post
- POST /journal-entries/{journalEntry}/reverse

journals.view 6 endpoints

- GET /financial-years
- GET /financial-years/{financial_year}
- GET /financial-periods
- GET /financial-periods/{financial_period}
- GET /journal-entries
- GET /journal-entries/{journal_entry}

leads.manage 16 endpoints

- POST /pipeline-stages/reorder
- POST /pipeline-stages
- PUT /pipeline-stages/{pipelineStage}
- PATCH /pipeline-stages/{pipelineStage}
- DELETE /pipeline-stages/{pipelineStage}
- POST /leads
- PUT /leads/{lead}
- PATCH /leads/{lead}
- DELETE /leads/{lead}
- POST /leads/{lead}/convert
- POST /leads/{lead}/assign
- POST /opportunities
- PUT /opportunities/{opportunity}
- PATCH /opportunities/{opportunity}
- DELETE /opportunities/{opportunity}
- PATCH /opportunities/{opportunity}/stage

leads.view 7 endpoints

- GET /pipeline-stages
- GET /pipeline-stages/{pipelineStage}
- GET /leads
- GET /leads/{lead}
- GET /opportunities/board
- GET /opportunities
- GET /opportunities/{opportunity}

leave.approve 8 endpoints

- GET /leave-types
- GET /leave-types/{leave_type}
- GET /leave-balances
- POST /leave-requests/{leave_request}/approve
- POST /leave-requests/{leave_request}/reject
- GET /leave-requests/{leave_request}/attachment
- GET /leave-requests
- GET /leave-requests/{leave_request}

leave.manage 13 endpoints

- GET /leave-types
- POST /leave-types
- GET /leave-types/{leave_type}
- PUT /leave-types/{leave_type}
- PATCH /leave-types/{leave_type}
- DELETE /leave-types/{leave_type}
- POST /leave-balances/generate
- GET /leave-balances
- PUT /leave-balances/{leave_balance}
- POST /leave-requests/{leave_request}/cancel
- GET /leave-requests/{leave_request}/attachment
- GET /leave-requests
- GET /leave-requests/{leave_request}

leave.request 6 endpoints

- GET /holidays
- GET /holidays/{holiday}
- GET /leave-types
- GET /leave-types/{leave_type}
- GET /leave-requests
- POST /leave-requests

leave.view 8 endpoints

- GET /holidays
- GET /holidays/{holiday}
- GET /leave-types
- GET /leave-types/{leave_type}
- GET /leave-balances
- GET /leave-requests/{leave_request}/attachment
- GET /leave-requests
- GET /leave-requests/{leave_request}

payments.create 2 endpoints

- POST /payments/{payment}/void
- POST /payments

payments.view 2 endpoints

- GET /payments
- GET /payments/{payment}

payroll.manage 20 endpoints

- GET /pay-components
- POST /pay-components
- GET /pay-components/{pay_component}
- PUT /pay-components/{pay_component}
- PATCH /pay-components/{pay_component}
- DELETE /pay-components/{pay_component}
- GET /tax-tables
- POST /tax-tables
- GET /tax-tables/{tax_table}
- PUT /tax-tables/{tax_table}
- PATCH /tax-tables/{tax_table}
- DELETE /tax-tables/{tax_table}
- GET /salary-structures
- POST /salary-structures
- GET /salary-structures/{salary_structure}
- PUT /salary-structures/{salary_structure}
- PATCH /salary-structures/{salary_structure}
- DELETE /salary-structures/{salary_structure}
- GET /employees/{employee}/salaries
- POST /employees/{employee}/salaries

payroll.process 7 endpoints

- POST /payroll-runs
- DELETE /payroll-runs/{payroll_run}
- POST /payroll-runs/{payroll_run}/calculate
- POST /payroll-runs/{payroll_run}/approve
- POST /payroll-runs/{payroll_run}/finalize
- POST /payroll-runs/{payroll_run}/pay
- POST /payroll-runs/{payroll_run}/cancel

payroll.view 15 endpoints

- GET /pay-components
- GET /pay-components/{pay_component}
- GET /tax-tables
- GET /tax-tables/{tax_table}
- GET /salary-structures
- GET /salary-structures/{salary_structure}
- GET /employees/{employee}/salaries
- GET /payroll-runs
- GET /payroll-runs/{payroll_run}
- GET /payroll-runs/{payroll_run}/payslips
- GET /payroll-runs/{payroll_run}/export
- GET /payroll/reports/summary
- GET /payroll/reports/components
- GET /payslips/{payslip}
- GET /payslips/{payslip}/pdf

payslips.view.own 5 endpoints

- GET /payslips/{payslip}
- GET /payslips/{payslip}/pdf
- GET /my-payslips
- GET /my-payslips/{payslip}
- GET /my-payslips/{payslip}/pdf

performance.manage 7 endpoints

- POST /performance-reviews/{performance_review}/submit
- GET /performance-reviews
- POST /performance-reviews
- GET /performance-reviews/{performance_review}
- PUT /performance-reviews/{performance_review}
- PATCH /performance-reviews/{performance_review}
- DELETE /performance-reviews/{performance_review}

performance.view 2 endpoints

- GET /performance-reviews
- GET /performance-reviews/{performance_review}

periods.manage 7 endpoints

- GET /financial-years
- POST /financial-years
- GET /financial-years/{financial_year}
- POST /financial-periods/{financialPeriod}/close
- POST /financial-periods/{financialPeriod}/reopen
- GET /financial-periods
- GET /financial-periods/{financial_period}

platform.companies.manage 8 endpoints

- GET /platform/companies
- POST /platform/companies
- GET /platform/companies/{company}
- PUT /platform/companies/{company}
- PATCH /platform/companies/{company}
- DELETE /platform/companies/{company}
- POST /platform/companies/{company}/activate
- POST /platform/companies/{company}/deactivate

platform.system.view 3 endpoints

- GET /platform/system
- GET /platform/audit-logs
- GET /platform/audit-logs/{auditLog}

platform.users.manage 4 endpoints

- GET /platform/users
- GET /platform/users/{user}
- PUT /platform/users/{user}
- PATCH /platform/users/{user}

products.manage 14 endpoints

- POST /units-of-measure
- PUT /units-of-measure/{unit_of_measure}
- PATCH /units-of-measure/{unit_of_measure}
- DELETE /units-of-measure/{unit_of_measure}
- POST /product-categories
- PUT /product-categories/{product_category}
- PATCH /product-categories/{product_category}
- DELETE /product-categories/{product_category}
- POST /products
- PUT /products/{product}
- PATCH /products/{product}
- DELETE /products/{product}
- POST /products/{product}/image
- DELETE /products/{product}/image

products.view 11 endpoints

- GET /units-of-measure
- GET /units-of-measure/{unit_of_measure}
- GET /product-categories/tree
- GET /product-categories
- GET /product-categories/{product_category}
- GET /products/low-stock
- GET /products
- GET /products/{product}
- GET /products/{product}/batches
- GET /products/{product}/stock
- GET /products/{product}/movements

projects.manage 45 endpoints

- GET /projects/overview
- GET /projects/{project}/summary
- GET /projects/{project}/time-summary
- GET /projects/{project}/board
- GET /projects
- POST /projects
- GET /projects/{project}
- PUT /projects/{project}
- PATCH /projects/{project}
- DELETE /projects/{project}
- GET /projects/{project}/members
- POST /projects/{project}/members
- PUT /projects/{project}/members/{member}
- PATCH /projects/{project}/members/{member}
- DELETE /projects/{project}/members/{member}
- GET /projects/{project}/milestones
- POST /projects/{project}/milestones
- GET /milestones/{milestone}
- PUT /milestones/{milestone}
- PATCH /milestones/{milestone}
- DELETE /milestones/{milestone}
- GET /my-tasks
- GET /projects/{project}/tasks
- POST /projects/{project}/tasks
- POST /tasks/{task}/subtasks
- PATCH /tasks/{task}/move
- GET /tasks/{task}
- PUT /tasks/{task}
- PATCH /tasks/{task}
- DELETE /tasks/{task}
- GET /tasks/{task}/comments
- POST /tasks/{task}/comments
- DELETE /tasks/{task}/comments/{comment}
- GET /time-entries
- POST /time-entries
- GET /time-entries/{time_entry}
- PUT /time-entries/{time_entry}
- PATCH /time-entries/{time_entry}
- DELETE /time-entries/{time_entry}
- GET /projects/{project}/expenses
- POST /projects/{project}/expenses
- GET /projects/{project}/expenses/{expense}
- PUT /projects/{project}/expenses/{expense}
- PATCH /projects/{project}/expenses/{expense}
- DELETE /projects/{project}/expenses/{expense}

projects.view 18 endpoints

- GET /projects/overview
- GET /projects/{project}/summary
- GET /projects/{project}/time-summary
- GET /projects/{project}/board
- GET /projects
- GET /projects/{project}
- GET /projects/{project}/members
- GET /projects/{project}/milestones
- GET /milestones/{milestone}
- GET /my-tasks
- GET /projects/{project}/tasks
- GET /tasks/{task}
- GET /tasks/{task}/comments
- POST /tasks/{task}/comments
- GET /time-entries
- GET /time-entries/{time_entry}
- GET /projects/{project}/expenses
- GET /projects/{project}/expenses/{expense}

purchase_orders.approve 1 endpoint

- POST /purchase-orders/{purchase_order}/approve

purchase_orders.manage 9 endpoints

- POST /requisitions/{requisition}/create-purchase-order
- POST /purchase-orders/{purchase_order}/submit
- POST /purchase-orders/{purchase_order}/cancel
- POST /purchase-orders/{purchase_order}/close
- POST /purchase-orders/{purchase_order}/send
- POST /purchase-orders
- PUT /purchase-orders/{purchase_order}
- PATCH /purchase-orders/{purchase_order}
- DELETE /purchase-orders/{purchase_order}

purchase_orders.view 6 endpoints

- GET /purchase-orders
- GET /purchase-orders/{purchase_order}
- GET /goods-receipts
- GET /goods-receipts/{goods_receipt}
- GET /purchase-returns
- GET /purchase-returns/{purchase_return}

quotations.manage 8 endpoints

- POST /quotations
- PUT /quotations/{quotation}
- PATCH /quotations/{quotation}
- DELETE /quotations/{quotation}
- POST /quotations/{quotation}/send
- POST /quotations/{quotation}/accept
- POST /quotations/{quotation}/reject
- POST /quotations/{quotation}/convert

quotations.view 2 endpoints

- GET /quotations
- GET /quotations/{quotation}

reports.export 4 endpoints

- POST /reports/{key}/export
- GET /report-exports
- GET /report-exports/{exportJob}
- GET /report-exports/{exportJob}/download

reports.financial.view 9 endpoints

- GET /finance/reports/trial-balance
- GET /finance/reports/profit-and-loss
- GET /finance/reports/balance-sheet
- GET /finance/reports/cash-flow
- GET /finance/reports/general-ledger
- GET /finance/reports/account-balances
- GET /finance/reports/ar-aging
- GET /finance/reports/ap-aging
- GET /finance/reports/receivables-summary

reports.view 7 endpoints

- GET /procurement/reports/spend
- GET /procurement/reports/status-summary
- GET /procurement/reports/supplier-performance
- GET /reports
- GET /reports/{key}
- GET /sales/reports/performance
- GET /sales/reports/pipeline

requisitions.approve 4 endpoints

- POST /requisitions/{requisition}/approve
- POST /requisitions/{requisition}/reject
- GET /requisitions
- GET /requisitions/{requisition}

requisitions.create 8 endpoints

- POST /requisitions/{requisition}/submit
- POST /requisitions/{requisition}/cancel
- GET /requisitions
- POST /requisitions
- GET /requisitions/{requisition}
- PUT /requisitions/{requisition}
- PATCH /requisitions/{requisition}
- DELETE /requisitions/{requisition}

requisitions.view 2 endpoints

- GET /requisitions
- GET /requisitions/{requisition}

roles.manage 4 endpoints

- POST /roles
- PUT /roles/{role}
- PATCH /roles/{role}
- DELETE /roles/{role}

roles.view 3 endpoints

- GET /permissions
- GET /roles
- GET /roles/{role}

sales_orders.approve 1 endpoint

- POST /sales-orders/{salesOrder}/approve

sales_orders.manage 11 endpoints

- POST /quotations/{quotation}/convert
- POST /sales-orders
- PUT /sales-orders/{salesOrder}
- PATCH /sales-orders/{salesOrder}
- DELETE /sales-orders/{salesOrder}
- POST /sales-orders/{salesOrder}/confirm
- POST /sales-orders/{salesOrder}/cancel
- POST /sales-orders/{salesOrder}/deliveries
- POST /deliveries/{delivery}/ship
- POST /deliveries/{delivery}/deliver
- POST /deliveries/{delivery}/cancel

sales_orders.view 4 endpoints

- GET /sales-orders
- GET /sales-orders/{salesOrder}
- GET /deliveries
- GET /deliveries/{delivery}

shifts.manage 14 endpoints

- GET /employees/{employee}/shifts
- POST /employees/{employee}/shifts
- GET /shifts
- POST /shifts
- GET /shifts/{shift}
- PUT /shifts/{shift}
- PATCH /shifts/{shift}
- DELETE /shifts/{shift}
- GET /holidays
- POST /holidays
- GET /holidays/{holiday}
- PUT /holidays/{holiday}
- PATCH /holidays/{holiday}
- DELETE /holidays/{holiday}

suppliers.manage 9 endpoints

- POST /suppliers/{supplier}/approve
- POST /suppliers
- PUT /suppliers/{supplier}
- PATCH /suppliers/{supplier}
- DELETE /suppliers/{supplier}
- POST /suppliers/{supplier}/contacts
- PUT /suppliers/{supplier}/contacts/{contact}
- PATCH /suppliers/{supplier}/contacts/{contact}
- DELETE /suppliers/{supplier}/contacts/{contact}

suppliers.view 6 endpoints

- GET /suppliers/all
- GET /suppliers/map
- GET /suppliers/{supplier}/summary
- GET /suppliers
- GET /suppliers/{supplier}
- GET /suppliers/{supplier}/contacts

tasks.manage 6 endpoints

- POST /projects/{project}/tasks
- POST /tasks/{task}/subtasks
- PATCH /tasks/{task}/move
- PUT /tasks/{task}
- PATCH /tasks/{task}
- DELETE /tasks/{task}

tasks.view 14 endpoints

- GET /projects/overview
- GET /projects/{project}/summary
- GET /projects/{project}/time-summary
- GET /projects/{project}/board
- GET /projects
- GET /projects/{project}
- GET /projects/{project}/members
- GET /projects/{project}/milestones
- GET /milestones/{milestone}
- GET /my-tasks
- GET /projects/{project}/tasks
- GET /tasks/{task}
- GET /tasks/{task}/comments
- POST /tasks/{task}/comments

tax.manage 6 endpoints

- GET /tax-rates
- POST /tax-rates
- GET /tax-rates/{tax_rate}
- PUT /tax-rates/{tax_rate}
- PATCH /tax-rates/{tax_rate}
- DELETE /tax-rates/{tax_rate}

time_entries.manage 6 endpoints

- GET /time-entries
- POST /time-entries
- GET /time-entries/{time_entry}
- PUT /time-entries/{time_entry}
- PATCH /time-entries/{time_entry}
- DELETE /time-entries/{time_entry}

users.manage 5 endpoints

- POST /users
- PUT /users/{user}
- PATCH /users/{user}
- DELETE /users/{user}
- POST /users/{user}/resend-invite

users.view 2 endpoints

- GET /users
- GET /users/{user}

`warehouses.manage` 8 endpoints

- POST /warehouses
- PUT /warehouses/{warehouse}
- PATCH /warehouses/{warehouse}
- DELETE /warehouses/{warehouse}
- POST /warehouses/{warehouse}/locations
- PUT /locations/{location}
- PATCH /locations/{location}
- DELETE /locations/{location}

`warehouses.view` 5 endpoints

- GET /warehouses/all
- GET /warehouses
- GET /warehouses/{warehouse}
- GET /warehouses/{warehouse}/locations
- GET /locations/{location}