


- Understand what these advanced object-oriented (OO) concepts mean
- Know the benefits they provide developers of Java apps in Android
- Identify Java features that implement these OO concepts


- Understand what these advanced object-oriented (OO) concepts mean
- Know the benefits they provide developers of Java apps in Android
- Identify Java features that implement these OO concepts

- Understand what these advanced object-oriented (OO) concepts mean
- Know the benefits they provide developers of Java apps in Android
- Identify Java features that implement these OO concepts

- Understand what these advanced object-oriented (OO) concepts mean
- Know the benefits they provide developers of Java apps in Android
- Identify Java features that implement these OO concepts









Other lessons examine Java inheritance & polymorphism in detail

 OO languages enhance reuse by allowing classes to inherit commonly used state & behavior from other classes




See en.wikipedia.org/wiki/Inheritance_(object-oriented_programming)

 Inheritance in Java is specified via its extends keyword




- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class



- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class

ClassB inherits mField1

& foo() from ClassA




- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class

Class1 mField1 void foo() <<extends>> ClassB ClassB inherits mField1 Class2 mFieldA & foo() from ClassA void bar()


ClassA

- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class




- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class

```
Class B b = new ClassB();
b.foo();
b.bar();
```




- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class

```
Class B b = new ClassB();
b.foo();
b.bar();
```




- Inheritance in Java is specified via its extends keyword
 - Allows a subclass to inherit all non-private fields & methods from a super class

```
Class B b = new ClassB();
b.foo();
b.bar();
```




• Java Collections Framework demonstrates capabilities & benefits of inheritance




See docs.oracle.com/javase/8/docs/technotes/guides/collections

• Java Collections Framework demonstrates capabilities & benefits of inheritance




See docs.oracle.com/javase/8/docs/technotes/guides/collections


• Java Collections Framework demonstrates capabilities & benefits of inheritance




See the module on "Structured Data" for more on the Java Collections Framework




See developer.android.com/reference/java/util/List.html




See developer.android.com/reference/java/util/AbstractCollection.html



See developer.android.com/reference/java/util/AbstractList.html



See developer.android.com/reference/java/util/Vector.html



See developer.android.com/reference/java/util/ArrayList.html

<<Java Class>> • The List hierarchy are collections GAbstractCollection

E> that maintain an ordering for AbstractCollection() 22extend577 diterator() their elements <<Java Class>> size():int isEmpty():boolean Vector(int,int) clear():void <<Java Class>> G AbstractList<E> Vector() <<extends>> capacity():int <<extends>> <<Java Interface>> size():int set(int,E) List<E> isEmpty():boolean remove(int) (default package) contains(Object):boolean clear():void <<Java Class>> get(int) iterator() ArrayList<E> size():int set(int,E) equals(Object):boolean isEmpty():boolean remove(int) hashCode():int contains(Object):boolean ArrayList() clear():void iterator() Zzimplementszz size():int equals(Object):boolean clear():void isEmpty():boolean hashCode():int equals(Object):boolean get(int) iterator() hashCode():int set(int,E) sort(Comparator<? super E>):void qet(int) remove(int) set(int,E) clear():void remove(int) iterator() sort(Comparator<? super E>):void sort(Comparator<? super E>):void

This inheritance hierarchy enhances systematic reuse of data fields & methods

• All Java classes inherit from the package java.lang;

```
java.lang.Object super class
                                  public class Object {
                                    public int hashCode();
                                    public boolean equals
                                                   (Object o);
                                    public final void wait();
                                    public final void notify();
                                    public final void notifyAll();
```

- All Java classes inherit from the java.lang.Object super class
 - Defines methods that can be used by all non-primitive types

```
public class Object {
  public int hashCode();
  public boolean equals
                (Object o);
  public final void wait();
  public final void notify();
  public final void notifyAll();
```

package java.lang;

- All Java classes inherit from the java.lang.Object super class
 - Defines methods that can be used by all non-primitive types

```
public class Object {
  public int hashCode();
  public boolean equals
                (Object o);
  public final void wait();
  public final void notify();
  public final void notifyAll();
```

package java.lang;

- All Java classes inherit from the package java.lang;
 - java.lang.Object super classDefines methods that can be used by all non-primitive types

```
public final void wait();
public final void notify();
public final void notifyAll();
...
```

(Object o);

public class Object {

public int hashCode();

public boolean equals

See developer.android.com/reference/java/lang/Object.html#equals(java.lang.Object)

- All Java classes inherit from the java.lang.Object super class
 - Defines methods that can be used by all non-primitive types

```
public class Object {
  public int hashCode();
  public boolean equals
                (Object o);
  public final void wait();
  public final void notify();
  public final void notifyAll();
```

package java.lang;

 Subclasses that don't explicitly extend a super class implicitly inherit from java.lang.Object


```
package java.lang;

public abstract class Process {
    ...
    public abstract int waitFor()
    ...;
    ...;
}
```

- Subclasses that don't explicitly extend a super class implicitly inherit from java.lang.Object, e.g.
 - java.lang.Object, e.
 java.lang.Process implicitly extends java.lang.Object

```
package java.lang;
public abstract class Process {
    ...
    public abstract int waitFor()
    ...;
    ...;
```


- Subclasses that don't explicitly extend a super class implicitly inherit from java.lang.Object, e.g.
 - java.lang.Process implicitly extends java.lang.Object
 - All instances of java.lang.Process therefore also provide clients access to inherited java.lang.Object methods




• java.lang.Object is the most general of all classes

Object


- java.lang.Object is the most general of all classes
 - It serves as the root of a hierarchy of classes available to Java apps



- java.lang.Object is the most general of all classes
 - It serves as the root of a hierarchy of classes available to Java apps
 - Classes towards the bottom of the inheritance hierarchy are more specialized



- java.lang.Object is the most general of all classes
 - It serves as the root of a hierarchy of classes available to Java apps
 - Classes towards the bottom of the inheritance hierarchy are more specialized
 - e.g., List-related subclasses override methods inherited from super classes



 Subclass methods inherited from a super class are used for 3 purposes

```
public class Stack<E> {
    extends Vector<E> {
```



 Subclass methods inherited from a super class are used for 3 purposes

public class Stack<E> {
 extends Vector<E> {

Extends Vector to define a last-in/first-out data structure that enables apps to pop & push items to/from a stack



See developer.android.com/reference/java/util/Stack.html

 Subclass methods inherited from a super class are used for 3 purposes

public class Stack<E> {
 extends Vector<E> {

Extends Vector to define a last-in/first-out data structure that enables apps to pop & push items to/from a stack



See developer.android.com/reference/java/util/Vector.html

- Subclass methods inherited from a super class are used for 3 purposes
- 1. To augment the subclass API
- public class Stack<E> {
 extends Vector<E> {

- Subclass methods inherited from a super class are used for 3 purposes
- public class Stack<E> {
 extends Vector<E> {

- 1. To augment the subclass API
 - e.g., Stack subclass inherits fields
 & methods from Vector super class

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - e.g., Stack subclass inherits fields
 & methods from Vector super class

```
public class Stack<E> {
    extends Vector<E> {
```

```
e.g.,
Stack<Integer> s =
  new Stack<>();
```

```
if(!s.isEmpty())
s.pop();
```

isEmpty() method inherited from Vector can be invoked on a Stack instance

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods
 - e.g., Stack's push() method is implemented via addElement() method inherited from Vector

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods
 - e.g., Stack's push() method is implemented via addElement() method inherited from Vector

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods
 - 3. To override super class methods in subclass with same signatures

```
public abstract class
         AbstractMap<K,V> ...
public abstract
    Set<Entry<K,V>> entrySet();
public V put(K key, V value)
{ ... }
```

```
public HashMap<K,V> extends
    AbstractMap<K,V> ...
public Set<Entry<K,V>>
    entrySet() { ... }
public V put(K key, V value)
{ ... }
...
```

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods
 - 3. To override super class methods in subclass with same signatures
 - e.g., the HashMap subclass overrides AbstractMap super class methods

```
public HashMap<K,V> extends
        AbstractMap<K,V> ...
public Set<Entry<K,V>>
        entrySet() { ... }
public V put(K key, V value)
{ ... }
...
```

- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods
 - 3. To override super class methods in subclass with same signatures
 - e.g., the HashMap subclass overrides AbstractMap super class methods

```
public HashMap<K,V> extends
    AbstractMap<K,V> ...
public Set<Entry<K,V>>
    entrySet() { ... }
public V put(K key, V value)
{ ... }
...
```


- Subclass methods inherited from a super class are used for 3 purposes
 - 1. To augment the subclass API
 - 2. To implement subclass methods
 - 3. To override super class methods in subclass with same signatures
 - e.g., the HashMap subclass overrides AbstractMap super class methods

```
public HashMap<K,V> extends
    AbstractMap<K,V> ...
public Set<Entry<K,V>>
    entrySet() { ... }
public V put(K key, V value)
{ ... }
...
```


Method overriding is covered next in our discussion of Java Polymorphism

Overview of Java's Support for Polymorphism (Part 1)


 Inheritance is nearly always used in conjunction with polymorphism



 Inheritance is nearly always used in conjunction with polymorphism



 Polymorphism enables transparent customization of methods inherited from a super class



Polymorphism & inheritance are essential to the "open/closed principle"





See en.wikipedia.org/wiki/Open/closed_principle

- Polymorphism & inheritance are essential to the "open/closed principle"
 - "A class should be open for extension, but closed for modification"





See en.wikipedia.org/wiki/Open/closed_principle


- Polymorphism & inheritance are essential to the "open/closed principle"
 - "A class should be open for extension, but closed for modification"
 - Insulating a class from modifications helps make the class more robust, flexible, & reusable






See www.dre.vanderbilt.edu/~schmidt/OCP.pdf


• The "open/closed principle" can be applied in conjunction with patterns to enable extensions *without* modifying existing classes or apps




• The "open/closed principle" can be applied in conjunction with patterns to enable extensions *without* modifying existing classes or apps




 The "open/closed principle" can be applied in conjunction with patterns to enable extensions without modifying existing classes or apps




 The "open/closed principle" can be applied in conjunction with patterns to enable extensions without modifying existing classes or apps




 The "open/closed principle" can be applied in conjunction with patterns to enable extensions without modifying existing classes or apps



• The "open/closed principle" can be applied in conjunction with patterns to enable extensions *without* modifying existing classes or apps




 Subclasses defined in accordance with the open/closed principle can define their own custom behaviors that are more suitable for a particular use case



<<Java Class>>

 Subclasses defined in accordance with the open/closed principle can define their own custom behaviors that are more suitable for a particular use case


While still reusing structure
 & functionality from super class



<<Java Class>>

AbstractList<E>

- Subclasses defined in accordance with the open/closed principle can define their own custom behaviors that are more suitable for a particular use case
 - While still reusing structure
 & functionality from super class
 - e.g., Vector & ArrayList both inherit AbstractList methods




<<Java Class>>

GAbstractList<E>

^CAbstractList()

^Aget(int)

- Subclasses defined in accordance with the open/closed principle can define their own custom behaviors that are more suitable for a particular use case
 - While still reusing structure
 & functionality from super class
 - e.g., Vector & ArrayList both inherit AbstractList methods



<<Java Class>>


GAbstractList<E>

set(int,E)

Overview of Java's Support for Polymorphism (Part 2)

- Subclasses defined in accordance with the open/closed principle can define their own custom behaviors that are more suitable for a particular use case
 - While still reusing structure
 & functionality from super class
 - e.g., Vector & ArrayList both inherit AbstractList methods

Methods in each subclass emphasize different List properties



<<Java Class>>

GAbstractList<E>

AbstractList()


See beginnersbook.com/2013/12/difference-between-arraylist-and-vector-in-java

 Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass

TreeMap<K,V>

entrySet()

put()



- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods

AbstractMap<K,V>
...
entrySet()
put()

TreeMap<K,V>
...
entrySet()
put()

entrySet()
put()

HashMap<K,V

... entrySet() put()

Concurrent


HashMap<K,V

- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods

TreeMap<K,V>

entrySet()

put()




- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods

TreeMap<K,V>

entrySet()

put()




- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods


TreeMap<K,V>

entrySet()

put()



- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods




TreeMap<K,V>
...
entrySet()
put()

entrySet() put()

entrySet()
put()

- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods




TreeMap<K,V>
...
entrySet()
put()

entrySet()
put()

entrySet() put()

Subclasses of AbstractMap have different time & space tradeoffs

- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods



TreeMap<K,V>
...
entrySet()
put()


... entrySet() <mark>put()</mark>

entrySet()
put()

HashMap<K,V

See developer.android.com/reference/java/util/HashMap.html

- Polymorphism in Java occurs when a reference to a super class is used to refer to an object of a subclass
 - Subclass methods can override super class methods





TreeMap<K,V>
...
entrySet()
put()

... entrySet() put()

HashMap<K,V
...
entrySet()
put()


See developer.android.com/reference/java/util/TreeMap.html






The appropriate method is dispatched at runtime based on the subclass object


Overview of Java's Support for Polymorphism reate AbstractMap subclass




The appropriate method is dispatched at runtime based on the subclass object




The appropriate method is dispatched at runtime based on the subclass object





See en.wikipedia.org/wiki/Factory_method_pattern & en.wikipedia.org/wiki/Open/closed_principle



See en.wikipedia.org/wiki/Factory_method_pattern & en.wikipedia.org/wiki/Open/closed_principle









- Understand the key objectoriented (OO) concepts supported by Java
- Know the benefits that OO concepts provide developers of Java apps in Android
- Identify Java features that implement these OO concepts


- Understand the key objectoriented (OO) concepts supported by Java
- Know the benefits that OO concepts provide developers of Java apps in Android
- Identify Java features that implement these OO concepts


- Understand the key objectoriented (OO) concepts supported by Java
- Know the benefits that OO concepts provide developers of Java apps in Android
- Identify Java features that implement these OO concepts

- Understand the key objectoriented (OO) concepts supported by Java
- Know the benefits that OO concepts provide developers of Java apps in Android
- Identify Java features that implement these OO concepts









See download.oracle.com/javase/tutorial

Package Index These are the Android APIs. See all API classes.	
java.util.concurrent.atomic	A small toolkit of classes that support lock-free thread-safe programming on single variables.
java.util.concurrent.locks	Interfaces and classes providing a framework for locking and waiting for conditions that is distinct from built-in synchronization and monitors.
java.util.jar	
java.util.logging	
java.util.prefs	
java.util.regex	
java.util.zip	
javax.crypto	This package provides the classes and interfaces for cryptographic applications implementing algorithms for encryption, decryption, or key agreement.
javax.crypto.interfaces	This package provides the interfaces needed to implement the Diffie-Hellman (DH) key agreement's algorithm as specified by PKCS#3.
javax.crypto.spec	This package provides the classes and interfaces needed to specify keys and parameter for encryption.
javax.microedition.khronos.egl	
javax.microedition.khronos.opengles	Provides a standard OpenGL interface.

See <u>developer.android.com/</u> <u>reference/packages.html</u>

