



Migration Toolkit

Version migration_toolkit

1	What's New	3
2	Supported Operating Systems and Database Versions	3
3	Migration Methodology	4
4	Functionality Overview	8
5	Installing Migration Toolkit	10
6	Building the toolkit.properties File	24
7	Invoking Migration Toolkit	34
8	Migration Toolkit Command Options	38
9	Migration Errors	65
10	Error Codes	74
11	Unsupported Features	88

1 What's New

The following enhancement is added to the EDB Postgres Migration Toolkit for 53.0.1 release:

- Starting this release, Migration Toolkit supports CentOS or RHEL 8.

2 Supported Operating Systems and Database Versions

Database Versions

The following database product versions can be used with Migration Toolkit:

- PostgreSQL versions 9.5, 9.6, 10, 11, and 12
- Advanced Server versions 9.5, 9.6, 10, 11, and 12
- Oracle 10g Release 2
- Oracle 11g Release 2
- Oracle 12c Release 1
- SQL Server 2008
- SQL Server 2012
- SQL Server 2014
- MySQL 5.5.36
- Sybase Adaptive Server Enterprise 15.7

Please contact your EnterpriseDB Account Manager or sales@enterprisedb.com if you require support for other platforms.

Note: EnterpriseDB does not support the use of Migration Toolkit with

Oracle Real Application Clusters (RAC) and Oracle Exadata; these Oracle products have not been evaluated nor certified with this EnterpriseDB product.

Supported Operating Systems Versions

- Centos or RHEL 6, 7 and 8
 - SLES 12 SP4 and SP5
 - Debian 9
 - Ubuntu 18.04
 - Windows (64 bit) 2012 and 2016
-

3 Migration Methodology

There are many reasons to consider migrating from one database to another. Migration can allow you to take advantage of new or better technology. If your current database does not offer the right set of capabilities to allow you to scale the system, moving to a database that offers the functionality you need is the best move for your company.

Migration can also be very cost effective. Migrating systems with significant maintenance costs can save money spent on system upkeep. By consolidating the number of databases in use, you can also reduce in-house administrative costs. By using fewer database platforms (or possibly taking advantage of database compatibility), you can do more with your IT budget.

Using more than one database platform can offer you a graceful migration path should a vendor raise their pricing or change their company directive. EnterpriseDB has helped companies migrate their existing database systems to Postgres for years.

We recommend following the methodology detailed in The Migration Process <the_migration_process>.

The Migration Process

The migration path to Postgres includes the following main steps:

1. Start the migration process by determining which database objects and data will be included in the migration. Form a migration team that includes someone with solid knowledge of the architecture and implementation of the source system.
2. Identify potential migration problems. If it is an Oracle-to-Advanced Server migration, consult the [EnterpriseDB documentation](#) for complete details about the compatibility features supported in Advanced Server. Consider using EnterpriseDB's migration assessment service to assist in this review.
3. Prepare the migration environment. Obtain and install the necessary software, and establish connectivity between the servers.
4. If the migration involves a large body of data, consider migrating the schema definition before moving the data. Verify the results of the DDL migration and resolve any problems reported in the migration summary. The [Migration Errors section <mtk_errors>](#) of this document includes information about resolving migration problems.
5. Migrate the data. For small data sets, use Migration Toolkit. If it is an Oracle migration (into Advanced Server), and the data set is large or if you notice slow data transfer, take advantage of one of the other data movement methods available:
 - Use the Advanced Server database link feature compatible with Oracle databases.
 - If your data has BLOB or CLOB data, use the `dblink_ora` style database links instead of the Oracle style database links.

Both of these methods use the Oracle Call Interface (OCI) to connect to Oracle. After connecting, use an SQL statement to select the data from the 'linked' Oracle database and insert the data into the Advanced Server database.

6. Confirm the results of the data migration and resolve any problems reported in the migration summary.
7. Convert applications to work with the newly migrated Postgres

database. Applications that use open standard connectivity such as JDBC or ODBC normally only require changes to the database connection strings and selection of the EnterpriseDB driver. See [Connecting an Application to Postgres](#) for more information.

8. Test the system performance, and tune the new server. If you are migrating into an Advanced Server database, take advantage of Advanced Server's performance tuning utilities:

- Use Dynatune to dynamically adjust database configuration resources.
- Use Optimizer Hints to direct the query path.
- Use the ANALYZE command to retrieve database statistics.

The *EDB Postgres Advanced Server Guide* and *Database Compatibility for Oracle Developer's Guide* (both available through the EnterpriseDB website) offer information about the performance tuning tools available with Advanced Server.

Connecting an Application to Postgres

To convert a client application to use a Postgres database, you must modify the connection properties to specify the new target database. In the case of a Java application, change the JDBC driver name (`Class.forName`) and JDBC URL.

A Java application running on Oracle might have the following connection properties:

```
Class.forName("oracle.jdbc.driver.OracleDriver");
Connection con =
DriverManager.getConnection("jdbc:oracle:thin:@localhost:1521:xe",
"user",
"password")
```

Modify the connection string to connect to a Postgres server:

```
Class.forName("com.edb.Driver")
```

```
Connection con =
DriverManager.getConnection("jdbc:edb://localhost:5444/edb",
"user","password");
```

Converting an ODBC application to connect to an instance of Postgres is a two-step process. To connect an ODBC application, use an ODBC data source administrator to create a data source that defines the connection properties for the new target database.

Most Linux and Windows systems include graphical tools that allow you to create and edit ODBC data sources. After installing ODBC, check the Administrative Tools menu for a link to the ODBC Data Source Administrator. Click the Add button to start the Create New Data Source wizard; complete the dialogs to define the new target data source.

Then, change the application to use the new data source.

The application will contain a call to `SQLConnect` (or possibly `SQLDriverConnect`); edit the invocation to change the data source name. In the following example, the data source is named `OracleDSN`:

```
result = SQLConnect(conHandle, // Connection handle (returned)
"OracleDSN", SQL_NTS, // Data source name
username, SQL_NTS, // User name
password, SQL_NTS); // Password
```

To connect to an instance of Postgres defined in a data source named `PostgresDSN`, change the data source name:

```
result = SQLConnect(conHandle, // Connection handle (returned)
"PostgresDSN", SQL_NTS, // Data source name
username, SQL_NTS, // User name
password, SQL_NTS); // Password
```

After establishing a connection between the application and the server, test the application to find any compatibility problems between the application and the migrated schema. In most cases, a simple change will resolve any

incompatibility that the application encounters. In cases where a feature is not supported, use a workaround or third party tool to provide the functionality required by the application. See [Migration Errors <mtk_errors>](#), for information about some common problems and their workarounds.

4 Functionality Overview

Migration Toolkit is a powerful command-line tool that offers granular control of the migration process. Using Migration Toolkit is a two-step process:

1. Edit the [toolkit.properties](#) file to specify the source and target database.
2. Invoke Migration Toolkit at the command line, specifying migration options.

Migration Toolkit facilitates migration of database objects and data to an Advanced Server or PostgreSQL database from:

- Oracle
- MySQL
- SQL Server

Migration Toolkit also allows you to migrate database objects and data to an Advanced Server database from Sybase. You can also use Migration Toolkit to migrate between Advanced Server and PostgreSQL. Migration Toolkit includes a number of options, allowing you granular control of the migration process:

- Use the [-safeMode](#) option to commit each row as it is migrated.
- Use the [-fastCopy](#) option to bypass WAL logging to optimize migration.
- Use the [-batchSize](#) option to control the batch size of bulk inserts.
- Use the [-cpBatchSize](#) option to specify the batch size used with the COPY command.

- Use the `-lobBatchSize` option to specify the batch size used for large object data types.
- Use the `-filterProp` option to migrate only those rows that meet a user-defined condition.
- Use the `-customColTypeMapping` option to change the data type of selected columns.
- Use the `-dropSchema` option to drop the existing schema and create a new schema prior to migration.
- On Advanced Server, use the `-allDBLinks` option to migrate all Oracle database links.
- On Advanced Server, use the `-copyViaDBLinkOra` option to enable the `dblink_ora` module.

Object Migration Support

Migration Toolkit migrates object definitions (DDL), table data, or both. The following table contains a platform-specific list of the types of database objects that Migration Toolkit can migrate:

Object	Oracle	Sybase	SQL Server	MySQL
Schemas	X	X	X	X
Tables List-Partitioned Tables Range-Partitioned Table	X X X	X	X	X
Constraints	X	X	X	X
Indexes Triggers	X X	X	X	X
Table Data Views Materialized Views	X X X			
Packages Procedures Functions	X X X			
Sequences Users/Roles Profiles	X X X	X	X X	X
Object Types Object Type Methods	X X X			
Database Links Queues	X			

For detailed information about the commands that offer granular control of the objects imported, please see Schema Object Selection Options `<schema_select>`.

Online Migration vs. Offline Migration

Migration Toolkit can migrate immediately and directly into a Postgres database (*online migration*), or you can also choose to generate scripts to use at a later time to recreate object definitions in a Postgres database (*offline migration*).

By default, Migration Toolkit creates objects directly into a Postgres database; in contrast, include the `-offlineMigration` option to generate SQL scripts you can use at a later time to reproduce the migrated objects or data in a new database. You can alter migrated objects by customizing the migration scripts generated by Migration Toolkit before you execute them. With the `-offlineMigration` option, you can schedule the actual migration at a time that best suits your system load.

For more information about the `-offlineMigration` option, see Offline Migration Options `<offline_migration>`.

5 Installing Migration Toolkit

This chapter describes how to install Migration Toolkit.

Before installing the Migration Toolkit, you must have:

- Java 1.7.0 installed on your system; you can download a Java installer that matches your environment from the Oracle Java Downloads website.
- Credentials to access EnterpriseDB repository. For information about requesting credentials, visit:

<https://info.enterprisedb.com/rs/069-ALB-339/images/Repository%20Access%2004-09-2019.pdf>

The following are the various installation methods:

- [Installing Migration Toolkit on a CentOS or RHEL host](#)
- [Installing Migration Toolkit on a SLES Host](#)
- [Installing Migration Toolkit on a Debian or Ubuntu Host](#)
- [Installing Migration Toolkit on Windows](#)

Installing Migration Toolkit on a CentOS or RHEL 6,7, and 8 host

You can use an RPM package to install Migration Toolkit on a CentOS or RHEL host.

After receiving your repository credentials you can:

1. Create the repository configuration file.
2. Modify the file, providing your user name and password.
3. Install Migration Toolkit.

Creating a Repository Configuration File

To create the repository configuration file, assume superuser privileges and invoke the following command:

On RHEL or CentOS 6 and 7

```
yum -y install https://yum.enterprisedb.com/edb-repo-rpms/edb-repo-latest.noarch.rpm
```

On RHEL or CentOS 8

```
dnf -y install https://yum.enterprisedb.com/edb-repo-rpms/edb-repo-latest.noarch.rpm
```

The repository configuration file is named `edb.repo`. The file resides in `/etc/yum.repos.d`.

After creating the `edb.repo` file, use your choice of editor to ensure that the value of the `enabled` parameter is `1`, and replace the `username` and `password` placeholders in the `baseurl` specification with the name and password of a registered EnterpriseDB user.

```
[edb]
name=EnterpriseDB RPMs $releasever - $basearch
baseurl=https://<username>:
<password>@yum.enterprisedb.com/edb/redhat/rhel-$releasever-
$basearch
enabled=1
gpgcheck=1
gpgkey=file:///etc/pki/rpm-gpg/ENTERPRISEDB-GPG-KEY
```

After saving your changes to the configuration file, you can use the **yum install** command to install Migration Toolkit:

On RHEL or CentOS 6 and 7

```
yum install edb-migrationtoolkit
```

On RHEL or CentOS 8

```
dnf install edb-migrationtoolkit
```

When you install an RPM package that is signed by a source that is not recognized by your system, yum may ask for your permission to import the key to your local server. If prompted, and you are satisfied that the packages come from a trustworthy source, enter a **y**, and press **Return** to continue.

During the installation, yum may encounter a dependency that it cannot resolve. If it does, it will provide a list of the required dependencies that you must manually resolve.

After installing Migration Toolkit, you must configure the installation. Perform the following steps before invoking Migration Toolkit.

Using Migration Toolkit with IDENT Authentication

By default, the **pg_hba.conf** file for the RPM installer enforces **IDENT** authentication for remote clients. Before invoking Migration Toolkit, you must either modify the **pg_hba.conf** file, changing the authentication

method to a form other than **IDENT** (and restarting the server), or perform the following steps to ensure that an **IDENT** server is accessible:

1. Confirm that an **identd** server is installed and running. You can use the yum package manager to install an **identd** server by invoking the command:

```
yum install xinetd authd
```

The command should create a file named **/etc/xinetd.d/auth** that contains:

```
service auth
{
  disable = yes
  socket_type = stream
  wait = no
  user = ident
  cps = 4096 10
  instances = UNLIMITED
  server = /usr/sbin/in.authd
  server_args = -t60 --xerror --os
}
```

Note: if the file includes a **-E** argument at the end of **server_args**, please erase the **-E**.

Then, to start the **identd** server, invoke the commands:

```
systemctl enable xinetd
systemctl start xinetd
```

2. Open the **pg_ident.conf** file and create a user mapping:

```
### map_name system_username postgres_username
edbas enterprisedb enterprisedb
```

Where:

The name specified in the `map_name` column is a user-defined name that will identify the mapping in the `pg_hba.conf` file.

The name specified in the `system_username` column is `enterprisedb`.

The name specified in the `postgres_username` column is `enterprisedb`.

3. Open the `pg_hba.conf` file and modify the `IDENT` entries.

On an IPv4 host:

```
host all all 127.0.0.0/0 ident map=edbas
```

On an IPv6 host:

```
host all all ::1/128 ident map=edbas
```

4. Restart the Advanced Server service before invoking Migration Toolkit.

Upgrading an RPM Installation

If you have an existing RPM installation, you can use `yum` to upgrade your repository configuration file and update to a more recent product version. To update the `edb.repo` file, assume superuser privileges and enter:

```
yum upgrade edb-repo
```

`yum` will update the `edb.repo` file to enable access to the current EnterpriseDB repository, configured to connect with the credentials specified in your `edb.repo` file. Then, you can use `yum` to upgrade Migration toolkit:

```
yum upgrade edb-migrationtoolkit
```

Installing Migration Toolkit on a SLES Host

For detailed information about installing Advanced Server and supporting components on a SLES host, refer the [EDB Postgres Advanced Server Installation Guide](#).

SLES packages are available at <https://zypp.enterprisedb.com>.

Before installing Migration Toolkit, you must also add SUSEConnect and the SUSE Package Hub extension to the SLES host and register the host with SUSE, allowing access to SUSE repositories. Use the commands:

```
zypper install SUSEConnect
```

```
SUSEConnect -p PackageHub/12/x86_64
```

```
SUSEConnect -p sle-sdk/12/x86_64
```

For detailed information about registering a SUSE host, visit: <https://www.suse.com/support/kb/doc/?id=7016626>

The following sections provide information about the specific repositories that are not hosted by EnterpriseDB, but provides software that satisfies dependencies for each listed component. After adding repository access, you must use the zypper refresh command to process the repository content:

```
zypper refresh
```

Java Components:

Note

Only OpenJDK (version 1.7) is supported on SLES hosts of Java components. Before using an RPM package to add Advanced Server or a supporting component that requires Java, use zypper to add supporting repository locations to your system.

Use the commands:

```
zypper addrepo
```

```
https://zypp.enterprisedb.com/suse/edb-sles.repo
```

```
zypper refresh
```

Then, you can use the zypper utility to install Migration Toolkit:

```
zypper install edb-migrationtoolkit
```

Installing Migration Toolkit on a Debian or Ubuntu Host

To install a Debian package using the EnterpriseDB apt, complete the following steps. In addition, when using the commands, replace the `username` and `password` with the credentials provided by EnterpriseDB.

1. Assume superuser privileges:

```
sudo su -
```

2. Configure the EnterpriseDB repository:

```
sh -c 'echo "deb
https://username:password@apt.enterprisedb.com/$(lsb_release -
cs)-edb/ $(lsb_release -cs) main" >
/etc/apt/sources.list.d/edb-$(lsb_release -cs).list'
```

3. Add support to your system for secure APT repositories:

```
apt-get install apt-transport-https
```

4. Add the EBD signing key:

```
wget -q -O - https://username:password @apt.enterprisedb.com/edb-
deb.gpg.key | apt-key add -
```

5. Update the repository metadata:


```
apt-get update
```

6. Install Debian package:

```
apt-get install edb-migrationtoolkit
```

Installing Migration Toolkit on Windows

You can use the graphical installer to install the Migration Toolkit on Windows. You can download the installer from www.enterprisedb.com.

Once you download the installer, right-click the installer icon, and select **Run As Administrator** from the context menu. When the **Language Selection** popup opens, select an installation language and click **OK** to continue to the **Setup** window.

Note

This guide uses the term Stack Builder to refer to either StackBuilder Plus (distributed with Advanced Server) or Stack Builder (distributed with the PostgreSQL one-click installer from EnterpriseDB).

You must have a Java JVM (version 1.7.0) in place before Stack Builder can perform a Migration Toolkit installation.

The Java executable must be in your search path (**%PATH%** on Windows). Use the following commands to set the search path (substituting the name of the directory that holds the Java executable for javadir):

On Windows, use the command: **SET PATH=javadir;%PATH%**

After setting the search path, you can use the Stack Builder installation wizard to install Migration Toolkit into either Advanced Server or PostgreSQL.

The Java executable must be in your search path (**%PATH%** on Windows, **\$PATH** on Linux/Unix). Use the following commands to set the search path (substituting the name of the directory that holds the Java executable for

javadir):

On Windows, use the command:

```
SET PATH=\ *javadir*; %PATH%
```

On Linux, use the command:

```
PATH=\ *javadir*: $PATH
```

After setting the search path, you can use the Stack Builder installation wizard to install Migration Toolkit into either Advanced Server or PostgreSQL.

Launching StackBuilder Plus from Advanced Server

To launch StackBuilder Plus from an existing Advanced Server installation, navigate through the **Start** (or **Applications**) menu to the EDB Postgres menu; open the **EDB Add-ons** menu, and select the **StackBuilder Plus** menu option.

Launching Stack Builder from PostgreSQL

To launch Stack Builder from a PostgreSQL installation, navigate through the **Start** (or **Applications**) menu to the PostgreSQL menu, and select the **Application StackBuilder Plus** menu option.

Stack Builder opens as shown below.




Use the drop-down listbox to select the target server installation from the list of available servers. If your network requires you to use a proxy server to access the Internet, use the **Proxy servers** button to open the **Proxy servers** dialog and specify a server; if you do not need to use a proxy server, click **Next** to open the application selection window.


If you are using StackBuilder Plus to add Migration Toolkit to your Advanced Server installation, expand the **Add-ons, tools and utilities** node of the tree control, and check the box next to **EnterpriseDB Migration Toolkit**. Click **Next** to continue.

Note


If you are using Stack Builder to add Migration Toolkit to your PostgreSQL installation, expand the **EnterpriseDB Tools** node of the tree control (located under the **Registration-required and trial products** node), and select **Migration Toolkit** checkbox. Click **Next** to continue.



Confirm that Migration Toolkit is included in the **Selected Packages** list and that the **Download directory** field contains an acceptable download location.



Click **Next** to start the Migration Toolkit download.



When the download completes, Stack Builder confirms that the installation files have been successfully downloaded. Choose **Next** to open the Migration Toolkit installation wizard.


When prompted by the Migration Toolkit installation wizard, specify a language for the installation and click **OK** to continue.

The Migration Toolkit installation wizard opens. Click **Next** to continue.




Carefully review the license agreement before highlighting the appropriate


radio button; click **Next** to continue.




By default, Migration Toolkit will be installed in the **mtk** directory; accept the default installation directory as displayed, or modify the directory, and click **Next** to continue.



The installation wizard confirms that the **Setup** program is ready to install Migration Toolkit; click **Next** to start the installation.



A dialog confirms that the Migration Toolkit installation is complete; click **Finish** to exit the Migration Toolkit installer.



When Stack Builder finalizes installation of the last selected component, it displays the **Installation Completed** window. Click **Finish** to close Stack Builder.



After installing Migration Toolkit with Stack Builder, you must install the appropriate source-specific drivers before performing a migration; please see [Installing Source-Specific Drivers](#) for more information.

Installing Source-Specific Drivers

Before invoking Migration Toolkit, you must download and install a freely available source-specific driver. To download a driver, or for a link to a vendor download site, visit the [Third Party JDBC Drivers](#) section of the [Advanced Downloads](#) page at the EnterpriseDB website:

<https://www.enterprisedb.com/advanced-downloads>

After downloading the source-specific driver, move the driver file into the [JAVA_HOME/jre/lib/ext](#) directory.

6 Building the toolkit.properties File


Migration Toolkit uses the configuration and connection information stored in the `toolkit.properties` file during the migration process to identify and connect to the source and target databases. On Linux, the `toolkit.properties` file is located in:

```
/usr/edb/migrationtoolkit/etc
```

On Windows, the file is located in:

```
C:\Program Files\edb\mtk\etc
```

A sample `toolkit.properties` file is shown below:



Before executing Migration Toolkit commands, modify the `toolkit.properties` file with the editor of your choice. Update the file to include the following information:

- `SRC_DB_URL` specifies how Migration Toolkit should connect to the source database. See the section corresponding to your source database for details about forming the URL.
- `SRC_DB_USER` specifies a user name (with sufficient privileges) in the source database.
- `SRC_DB_PASSWORD` specifies the password of the source database user.
- `TARGET_DB_URL` specifies the JDBC URL of the target database.
- `TARGET_DB_USER` specifies the name of a privileged target database user.
- `TARGET_DB_PASSWORD` specifies the password of the target database user.

Defining an Advanced Server URL

Migration Toolkit facilitates migration from the following platforms to Advanced Server:

- Oracle
- MySQL
- Sybase
- SQL Server
- PostgreSQL

For a definitive list of the objects migrated from each database type, please refer to the [Functionality Overview <functionality_overview>](#).

Migration Toolkit reads connection specifications for the source and the target database from the `toolkit.properties` file. Connection information for each must include:

- The URL of the database
- The name of a privileged user
- The password associated with the specified user.

The URL conforms to JDBC standards and takes the form:

```
> {TARGET_DB_URL|SRC_DB_URL}=jdbc:edb://<host>:
<port>/<database_id>
```

An Advanced Server URL contains the following information:

`jdbc`

The protocol is always `jdbc`.

`edb`

If you are using Advanced Server, specify `edb` for the sub-protocol value.

`<host>`

The name or IP address of the host where the Postgres instance is running.

`<port>`

The port number that the Advanced Server database listener is monitoring. The default port number is `5444`.

`<database_id>`

The name of the source or target database.

`{TARGET_DB_USER|SRC_DB_USER}` must specify a user with privileges to CREATE each type of object migrated. If migrating data into a table, the specified user may also require `INSERT`, `TRUNCATE`, and `REFERENCES` privileges for each target table.

`{TARGET_DB_PASSWORD|SRC_DB_PASSWORD}` is set to the password of the privileged Advanced Server user.

Defining a PostgreSQL URL

Migration Toolkit facilitates migration from the following platforms to PostgreSQL:

- Oracle
- MySQL
- SQL Server
- Advanced Server

For a definitive list of the objects migrated from each database type, please refer to the [Functionality Overview <functionality_overview>](#).

Migration Toolkit reads connection specifications for the source and the target database from the `toolkit.properties` file. Connection information for each must include:

- The URL of the database

- The name of a privileged user
- The password associated with the specified user.

A PostgreSQL URL conforms to JDBC standards and takes the form:

```
> {SRC_DB_URL|TARGET_DB_URL}=jdbc:postgresql://<host>:
<port>/<database_id>
```

The URL contains the following information:

`jdbc`

The protocol is always `jdbc`.

`postgresql`

If you are using PostgreSQL, specify `postgresql` for the sub-protocol value.

`<host>`

The name or IP address of the host where the Postgres instance is running.

`<port>`

The port number that the Postgres database listener is monitoring. The default port number is `5432`.

`<database_id>`

The name of the source or target database.

`{SRC_DB_USER|TARGET_DB_USER}` must specify a user with privileges to `CREATE` each type of object migrated. If migrating data into a table, the specified user may also require `INSERT`, `TRUNCATE`, and `REFERENCES` privileges for each target table.

`{SRC_DB_PASSWORD|TARGET_DB_PASSWORD}` is set to the password of the privileged PostgreSQL user.

Defining an Oracle URL

Migration Toolkit facilitates migration from an Oracle database to a PostgreSQL or Advanced Server database. When migrating from Oracle, you must specify connection specifications for the Oracle source database in the `toolkit.properties` file. The connection information must include:

- The URL of the Oracle database
- The name of a privileged user
- The password associated with the specified user.

When migrating from an Oracle database, SRC_DB_URL should contain a JDBC URL, specified in one of two forms. The first form is:

```
jdbc:oracle:thin:@<host_name>:<port>:<database_id>
```

The second form is:

```
> jdbc:oracle:thin:@//<host_name>:<port>{<database_id|service_name>}
```

An Oracle URL contains the following information:

`jdbc`

The protocol is always `jdbc`.

`oracle`

The sub-protocol is always `oracle`.

`thin`

The driver type. Specify a driver type of `thin`.

`<host_name>`

The name or IP address of the host where the Oracle server is running.

<port>

The port number that the Oracle database listener is monitoring.

<database_id>

The database SID of the Oracle database.

<service_name>

The name of the Oracle service.

SRC_DB_USER should specify the name of a privileged Oracle user. The Oracle user should have DBA privilege to migrate objects from Oracle to Advanced Server. The DBA privilege can be granted to the Oracle user with the Oracle **GRANT DBA TO user** command to ensure all of the desired database objects are migrated.

SRC_DB_PASSWORD must contain the password of the specified user.

Defining a MySQL URL

Migration Toolkit facilitates migration from a MySQL database to an Advanced Server or PostgreSQL database. When migrating from MySQL, you must specify connection specifications for the MySQL source database in the **toolkit.properties** file. The connection information must include:

- The URL of the source database
- The name of a privileged user
- The password associated with the specified user.

When migrating from MySQL, **SRC_DB_URL** takes the form of a JDBC URL. For example:

jdbc:mysql://<host_name>[:<port>]/<database_id>

The URL contains the following information:

`jdbc`

The protocol is always `jdbc`.

`mysql`

The sub-protocol is always `mysql`.

`<host_name>`

The name or IP address of the host where the source server is running.

`[<port>]`

The port number that the MySQL database listener is monitoring.

`<database_id>`

The name of the source database.

`SRC_DB_USER` should specify the name of a privileged MySQL user.

`SRC_DB_PASSWORD` must contain the password of the specified user.

Defining a Sybase URL

Migration Toolkit facilitates migration from a Sybase database to an Advanced Server database. When migrating from Sybase, you must specify connection specifications for the Sybase source database in the `toolkit.properties` file. The connection information must include:

- The URL of the source database
- The name of a privileged user
- The password associated with the specified user.

When migrating from Sybase, `SRC_DB_URL` takes the form of a JTDS URL. For example:

```
jdbc:jtds:sybase://<host_name>[:<port>]/<database_id>
```

A Sybase URL contains the following information:

jdbc

The protocol is always **jdbc**.

jtds

The driver name is always **jtds**.

sybase

The server type is always **sybase**.

<host_name>

The name or IP address of the host where the source server is running.

<port>

The port number that the Sybase database listener is monitoring.

<database_id>

The name of the source database.

SRC_DB_USER should specify the name of a privileged Sybase user.

SRC_DB_PASSWORD must contain the password of the specified user.

Defining a SQL Server URL

Migration Toolkit facilitates migration from a SQL Server database to a PostgreSQL or Advanced Server database. Migration Toolkit supports migration of the following object definitions:

- schemas
- tables
- table data
- constraints
- indexes

Migration Toolkit reads connection specifications for the source database from the `toolkit.properties` file. The connection information must include:

- The URL of the source database
- The name of a privileged user
- The password associated with the specified user.

If you are connecting to a SQL Server database, `SRC_DB_URL` takes the form of a JTDS URL. For example:

```
jdbc:jtds:sqlserver:\<server_name>\[:<port>]\<database_id>
```

A SQL Server URL contains the following information:

`jdbc`

The protocol is always `jdbc`.

`jtds`

The driver name is always `jtds`.

`sqlserver`

The server type is always `sqlserver`.

`<server_name>`

The name or IP address of the host where the source server is running.

`<port>`

The port number that the source database listener is monitoring.

`<database_id>`

The name of the source database.

`SRC_DB_USER` should specify the name of a privileged SQL Server user.

`SRC_DB_PASSWORD` must contain the password of the specified user.

7 Invoking Migration Toolkit

After installing Migration Toolkit, and specifying connection properties for the source and target databases in the `toolkit.properties` file `<building_toolkit.properties_file>`, Migration Toolkit is ready to perform migrations.

The Migration Toolkit executable is named `runMTK.sh` on Linux systems and `runMTK.bat` on Windows systems. On a Linux system, the executable is located in:

`/usr/edb/migrationtoolkit/bin`

On Windows, the executable is located in:

`C:\Program Files\edb\mtk\bin`

Note: If the following error appears upon invoking the Migration Toolkit, check the file permissions of the `toolkit.properties` file.

MTK-11015: The connection credentials file `../etc/toolkit.properties` is not secure and accessible to group/others users. This file contains plain passwords and should be restricted to Migration Toolkit owner user only.

The operating system user account running the Migration Toolkit must be the owner of the toolkit.properties file with a minimum of read permission on the file. In addition, there must be no permissions of any kind for group and other users. The following is an example of the recommended file permissions where user enterprisedb is running the Migration Toolkit.

```
-rw----- 1 enterprisedb enterprisedb 191 Aug 1 09:59
toolkit.properties
```

Importing Character Data with Embedded Binary Zeros (NULL characters)

Migration Toolkit properly supports importation of a column with a value of NULL.

However, Migration Toolkit does not support importation of NULL character values (embedded binary zeros 0x00) with the JDBC connection protocol. If you are importing data that includes the NULL character, use the `-replaceNullChar` option to replace the NULL character with a single, non-NULL, replacement character.

Note:

- MTK implicitly replaces `NULL` characters with an empty string.
- The `-replaceNullChar` option does not work with `-copyViaDBLinkOra` option.

Once the data has been migrated, use a SQL statement to replace the character specified by `-replaceNullChar` with binary zeros.

Migrating a Schema from Oracle

Unless specified in the command line, Migration Toolkit expects the source database to be Oracle and the target database to be Advanced Server. To migrate a complete schema on Linux, navigate to the executable and invoke the following command:

```
$ ./runMTK.sh <schema_name>
```

To migrate a complete schema on Windows, navigate to the executable and invoke the following command:

```
> .\runMTK.bat <schema_name>
```

Where:

schema_name

schema_name is the name of the schema within the source database (specified in the toolkit.properties file) that you wish to migrate. You must include at least one **schema_name**.

Note: When the default database user of a migrated schema is automatically migrated, the custom profile of the default database user is also migrated if such a custom profile exists. A custom profile is a user-created profile. For example, custom profiles exclude Oracle profiles DEFAULT and MONITORING_PROFILE.

You can migrate multiple schemas by following the command name with a comma-delimited list of schema names.

On Linux, execute the following command:

```
$ ./runMTK.sh <schema_name1>,<schema_name2>,<schema_name3>
```

On Windows, execute the following command:

```
> .\runMTK.bat <schema_name1>,<schema_name2>,<schema_name3>
```

Migrating from a Non-Oracle Source Database

If you do not specify a source database type and a target database type, Postgres assumes the source database to be Oracle, and the target

database to be Advanced Server.

To invoke Migration Toolkit, open a command window, navigate to the executable, and invoke the following command:

```
$ ./runMTK.sh -sourcedbtype <db_type> -targetdbtype <target_type>
[options, ...] schema_name;
```

Where:

-sourcedbtype source_type

source_type specifies the server type of the source database.
source_type is case-insensitive. By default, **source_type** is oracle.
source_type may be one of the following values:

To migrate from:	Specify:
Oracle	oracle (the default value)
MySQL	mysql
SQL Server	sqlserver
Sybase	sybase
PostgreSQL	postgres or postgresql
Advanced Server	enterprisedb

-targetdbtype target_type

target_type specifies the server type of the target database.
target_type is case-insensitive. By default, **target_type** is **enterprisedb**. **target_type** may be one of the following values:

To migrate to:	Specify:
Advanced Server	enterprisedb
PostgreSQL	postgres or postgresql

schema_name

`schema_name` is the name of the schema within the source database (specified in the `toolkit.properties` file) that you wish to migrate. You must include at least one `schema_name`.

The following example migrates a schema (table definitions and table content) named `HR` from a MySQL database on a Linux system to an Advanced Server host. Note that the command includes the `-sourcedbtype` and `-targetdbtype` options:

```
$ ./runMTK.sh -sourcedbtype mysql -targetdbtype enterprisedb HR
```

On Windows, use the following command:

```
> .\runMTK.bat -sourcedbtype mysql -targetdbtype enterprisedb HR
```

You can migrate multiple schemas from a source database by including a comma-delimited list of schemas at the end of the Migration Toolkit command. The following example migrates multiple schemas (named `HR` and `ACCTG`) from a MySQL database to a PostgreSQL database:

On Linux, use the following command to migrate multiple schemas from a MySQL database:

```
$ ./runMTK.sh -sourcedbtype mysql -targetdbtype postgres  
HR,ACCTG
```

On Windows, use the following command form:

```
> .\runMTK.bat -sourcedbtype mysql -targetdbtype postgres  
HR,ACCTG
```

8 Migration Toolkit Command Options

Append migration options when you run Migration Toolkit to conveniently

control details of the migration. For example, to migrate all schemas within a database, append the `-allSchemas` option to the command:

```
$ ./runMTK.sh -allSchemas
```

The sections that follow contain reference material for each of the command options that work with Migration Toolkit; options are grouped by their behavior. The table below lists Migration Toolkit options and the sections that they are grouped in.

Feature:	Relevant Options:
Offline Migration Options	-offlineMigration
Import Options	-sourcedbtype, -targetdbtype, -schemaOnly, -dataOnly
Schema Creation Options	-dropSchema, -targetSchema
Schema Object Selection Options	-allTables, -tables, -constraints, -ignoreCheckConstFilter, -skipCKConst, -skipFKConst, -skipColDefaultClause, -indexes, -triggers, -allViews, -views, -allSequences, -sequences, -allProcs, -procs, -allFuncs, -funcs, -checkFunctionBodies, -allPackages, -packages, -allDomains, -allQueues, -queues, -allRules,
Migration Options	-truncLoad, -enableConstBeforeDataLoad, -retryCount, -safeMode, -fastCopy, -analyze, vacuumAnalyze, -replaceNullChar, -copyDelimiter, -batchSize, -cpBatchSize, -lobBatchSize, -fetchSize, -filterProp - customColTypeMapping, -customColTypeMappingFile
Oracle Specific Options	-allUsers, -users, -allProfiles, -profiles, -importPartitionAsTable, -objectTypes, -copyViaDBLinkOra, -allDBLinks -allSynonyms, -allPublicSynonyms, -allPrivateSynonyms, -useOraCase, -skipUserSchemaCreation

Feature:	Relevant Options:
Miscellaneous Options	-help, -logDir, -logFileCount, -logFileSize, -logBadSQL -verbose, -version

Offline Migration Options

If you specify the `-offlineMigration` option in the command line, Migration Toolkit performs an *offline* migration. During an offline migration, Migration Toolkit reads the definition of each selected object and creates an SQL script that, when executed at a later time, replicates each object in Postgres.

Note: The following examples demonstrate invoking Migration Toolkit in Linux; to invoke Migration Toolkit in Windows, substitute the `runMTK.bat` command for the `runMTK.sh` command.

To perform an offline migration of both schema and data, specify the `-offlineMigration` keyword, followed by the schema name:

```
$ ./runMTK.sh -offlineMigration <schema_name>
```

Each database object definition is saved in a separate file with a name derived from the schema name and object type in the user's home folder. To specify an alternative file destination, include a directory name after the `-offlineMigration` option:

```
$ ./runMTK.sh -offlineMigration <file_dest> <schema_name>
```

To perform an offline migration of schema objects only (creating empty tables), specify the `-schemaOnly` keyword in addition to the `-offlineMigration` keyword when invoking Migration Toolkit:

```
$ ./runMTK.sh -offlineMigration -schemaOnly <schema_name>
```

To perform an offline migration of data only (omitting any schema object definitions), specify the `-dataOnly` keyword and the `-offlineMigration` keyword when invoking Migration Toolkit


```
$ ./runMTK.sh -offlineMigration -dataOnly <schema_name>
```

By default, data is written in COPY format; to write the data in a plain SQL format, include the `-safeMode` keyword:

```
$ ./runMTK.sh -offlineMigration -dataOnly -safeMode  
<schema_name>
```

By default, when you perform an offline migration that contains table data, a separate file is created for each table. To create a single file that contains the data from multiple tables, specify the `-singleDataFile` keyword:

```
./runMTK.sh -offlineMigration -dataOnly -singleDataFile -safeMode  
<schema_name>
```

Please note: the `-singleDataFile` option is available only when migrating data in a plain SQL format; you must include the `-safeMode` keyword if you include the `-singleDataFile` option.

Executing Offline Migration Scripts

You can use the `edb-psql` (or `psql`) command line to execute the scripts generated during an offline migration. The following example describes restoring a schema (named *hr*) into a new database (named *acctg*) stored in Advanced Server.

1. Use the `createdb` command to create the *acctg* database, into which we will restore the migrated database objects:

```
createdb -U enterprisedb acctg
```

2. Connect to the new database with `edb-psql`:

```
edb-psql -U enterprisedb acctg
```

3. Use the `\i` meta-command to invoke the migration script that creates the object definitions:

```
acctg=# \i ./mtk_hr_ddl.sql
```

4. If the `-offlineMigration` command included the `-singleDataFile` keyword, the `mtk_hr_data.sql` script will contain the commands required to recreate all of the objects in the new target database. Populate the database with the command:

```
acctg=# \i ./mtk_hr_data.sql
```

Import Options

By default, Migration Toolkit assumes the source database to be Oracle and the target database to be Advanced Server; include the `-sourcedbtype` and `-targetdbtype` keywords to specify a non-default source or target database.

By default, Migration Toolkit imports both the data and the object definition when migrating a schema; alternatively you can choose to import either the data or the object definitions.

`-sourcedbtype <source_type>`

The `-sourcedbtype` option specifies the source database type. `<source_type>` may be one of the following values: `mysql`, `oracle`, `sqlserver`, `sybase`, `postgresql` or `enterprisedb`. `<source_type>` is case-insensitive. By default, `<source_type>` is `oracle`.

`-targetdbtype <target_type>`

The `-targetdbtype` option specifies the target database type. `<target_type>` may be one of the following values: `enterprisedb`, `postgres`, or `postgresql`. `<target_type>` is case-insensitive. By default, `<target_type>` is `enterprisedb`.

`-schemaOnly`

This option imports the schema definition and creates all selected schema objects in the target database. This option cannot be used in

conjunction with `-dataOnly` option.

`-dataOnly`

This option copies the data only. When used with the `-tables` option, Migration Toolkit will only import data for the selected tables (see usage details below). This option cannot be used with `-schemaOnly` option.

Schema Creation Options

By default, Migration Toolkit imports the source schema objects and/or data into a schema of the same name. If the target schema does not exist, Migration Toolkit creates a new schema. Alternatively, you may specify a custom schema name via the `-targetSchema` option. You can choose to drop the existing schema and create a new schema using the following option:

`-dropSchema [true|false]`

When set to true, Migration Toolkit drops the existing schema (and any objects within that schema) and creates a new schema. (By default, `-dropSchema` is `false`).

`-targetSchema schema_name>`

Use the `-targetSchema` option to specify the name of the migrated schema. If you are migrating multiple schemas, specify a name for each schema in a comma-separated list with no intervening space characters. If the command line does not include the `-targetSchema` option, the name of the new schema will be the same as the name of the source schema.

You cannot specify `information-schema`, `dbo`, `sys`, or `pg_catalog` as target schema names. These schema names are reserved for meta-data storage in Advanced Server.

Schema Object Selection Options

Use the following options to select specific schema objects to migrate:

`-allTables`

Import all tables from the source schema.

`-tables <table_list>`

Import the selected tables from the source schema. `<table_list>` is a comma-separated list (with no intervening space characters) of table names (e.g., `-tables emp,dept,acctg`).

`-constraints`

Import the table constraints. This option is valid only when importing an entire schema or when you specify the `-allTables` or `-tables <table_list>` options.

`-ignoreCheckConstFilter`

By default, Migration Toolkit does not implement migration of check constraints and default clauses from a Sybase database. Include the `-ignoreCheckConstFilter` parameter when specifying the `-constraints` parameter to migrate constraints and default clauses from a Sybase database.

`-skipCKConst`

Omit the migration of check constraints. This option is useful when migrating check constraints that are based on built-in functions (in the source database) that are not supported in the target database.

This option is valid only when importing an entire schema or when the `-allTables` or `-tables <table_list>` options are specified.

`-skipFKConst`

Omit the migration of foreign key constraints. This option is valid only when importing an entire schema or when the `-allTables` or `-tables <table_list>` options are specified.

`-skipColDefaultClause`

Omit the migration of the column `DEFAULT` clause.

`-indexes`

Import the table indexes. This option is valid when importing an entire schema or when the `-allTables` or `-tables <table_list>` option is specified.

`-triggers`

Import the table triggers. This option is valid when importing an entire schema or when the `allTables` or `-tables <table_list>` option is specified.

`-allViews`

Import the views from the source schema. Please note that this option will migrate both dynamic *and* materialized views from the source. (Oracle and Postgres materialized views are supported.)

`-views <view_list>`

Import the specified materialized or dynamic views from the source schema. (Oracle and Postgres materialized views are supported.) `<view_list>` is a comma-separated list (with no intervening space characters) of view names (e.g., `-views all_emp,mgmt_list,acct_list`).

`-allSequences`

Import all sequences from the source schema.

`-sequences <sequence_list>`

Import the selected sequences from the source schema.

`<sequence_list>` is a comma-separated list (with no intervening space characters) of sequence names.

`-allProcs`

Import all stored procedures from the source schema.

`-procs <procedures_list>`

Import the selected stored procedures from the source schema.

`<procedures_list>` is a comma-separated list (with no intervening space characters) of procedure names.

`-allFuncs`

Import all functions from the source schema.

`-funcs <function_list>`

Import the selected functions from the source schema. `<function_list>` is a comma-separated list (with no intervening space characters) of function names.

`-checkFunctionBodies [true/false]`

When `false`, disables validation of the function body during function creation (to avoid errors if the function contains forward references). The default value is `true`.

`-allPackages`

Import all packages from the source schema.

`-packages <package_list>`

Import the selected packages from the source schema.

`<package_list>` is a comma-separated list (with no intervening space characters) of package names.

`-allDomains`

Import all domain, enumeration and composite types from the source database; this option is only valid when both the source and target are stored on a Postgres host.

-allQueues

Import all queues from the source schema. These are queues created and managed by the DBMS_AQ and DBMS_AQADM built-in packages. When Oracle is the source database, the **-objectTypes** option must also be specified. When Advanced Server is the source database, the **-allDomains** and **-allTables** options must also be specified. (Oracle and Advanced Server queues are supported.)

-queues <queue_list>

Import the selected queues from the source schema. **<queue_list>** is a comma-separated list (with no intervening space characters) of queue names. These are queues created and managed by the DBMS_AQ and DBMS_AQADM built-in packages. When Oracle is the source database, the **-objectTypes** option must also be specified. When Advanced Server is the source database, the **-allDomains** and **-allTables** options must also be specified. (Oracle and Advanced Server queues are supported.)

-allRules

Import all rules from the source database; this option is only valid when both the source and target are stored on a Postgres host.

Migration Options

Use the migration options listed below to control the details of the migration process.

-loaderCount [<value>]

Use the **-loaderCount** option to specify the number of parallel threads that Migration Toolkit should use when importing data. This option is

particularly useful if the source database contains a large volume of data, and the Postgres host (that is running Migration Toolkit) has high-end CPU and RAM resources. While `<value>` may be any non-zero, positive number, we recommend that `<value>` should not exceed the number of CPU cores; a dual core CPU should have an optimal `<value>` of 2.

Please note that specifying too large of a `<value>` could cause Migration Toolkit to terminate, generating a `'Out of heap space'` error.

`-truncLoad`

Truncate the data from the table before importing new data. This option can only be used in conjunction with the `-dataOnly` option.

`-enableConstBeforeDataLoad`

Include the `-enableConstBeforeDataLoad` option if a non-partitioned source table is mapped to a partitioned table. This option enables all triggers on the target table (including any triggers that redirect data to individual partitions) before the data migration. `-enableConstBeforeDataLoad` is valid only if the `-truncLoad` parameter is also specified.

`-retryCount [<value>]`

If you are performing a multiple-schema migration, objects that fail to migrate during the first migration attempt due to cross-schema dependencies may successfully migrate during a subsequent migration. Use the `-retryCount` option to specify the number of attempts that Migration Toolkit will make to migrate an object that has failed during an initial migration attempt. Specify a `<value>` that is greater than 0; the default value is 2.

`-safeMode`

If you include the `-safeMode` option, Migration Toolkit commits each row as migrated; if the migration fails to transfer all records, rows inserted prior to the point of failure will remain in the target database.

`-fastCopy`

Including the `-fastCopy` option specifies that Migration Toolkit should bypass WAL logging to perform the COPY operation in an optimized way, default disabled. If you choose to use the `-fastCopy` option, migrated data may not be recoverable (in the target database) if the migration is interrupted.

`-replaceNullChar <value>`

The Migration Toolkit properly supports importation of a column with a value of NULL.

However, the Migration Toolkit does not support importation of NULL character values (embedded binary zeros 0x00) with the JDBC connection protocol. If you are importing data that includes the NULL character, use the `-replaceNullChar` option to replace the NULL character with a single, non-NULL, replacement character. Do not enclose the replacement character in quotes or apostrophes.

Note:

- MTK implicitly replaces `NULL` characters with an empty string.
- The `-replaceNullChar` option does not work with `-copyViaDBLinkOra` option.

Once the data has been migrated, use a SQL statement to replace the character specified by `-replaceNullChar` with binary zeros.

`-analyze`

Include the `-analyze` option to invoke the Postgres ANALYZE operation against a target database. The optimizer consults the statistics collected by the ANALYZE operation, utilizing the information to construct efficient query plans.

`-vacuumAnalyze`

Include the `-vacuumAnalyze` option to invoke both the VACUUM and

ANALYZE operations against a target database. The optimizer consults the statistics collected by the ANALYZE operation, utilizing the information to construct efficient query plans. The VACUUM operation reclaims any storage space occupied by dead tuples in the target database.

-copyDelimiter

Specify a single character to be used as a delimiter in the copy command when loading table data. The default value is `'\t'` (tab).

-batchSize

Specify the batch size of bulk inserts. Valid values are 1-1000. The default batch size is 1000; reduce the value of `-batchSize` if `Out of Memory` exceptions occur.

-cpBatchSize

Specify the batch Size in MB to be used in the COPY command. Any value greater than 0 is valid; the default batch size is 8 MB.

-lobBatchSize

Specify the number of rows to be loaded in a batch for LOB data types. The data migration for a table containing a large object type (LOB) column such as BYTEA, BLOB, or CLOB, etc., is performed one row at a time by default. This is to avoid an out of heap space error in case an individual LOB column holds hundreds of megabytes of data. In case the LOB column average data size is at a lower end, you can customize the LOB batch size by specifying the number of rows in each batch with any value greater than 0.

-fetchSize

Use the `-fetchSize` option to specify the number of rows fetched in a result set. If the designated `-fetchSize` is too large, you may encounter `Out of Memory` exceptions; include the `-fetchSize` option to avoid this pitfall when migrating large tables. The default fetch size is specific to the JDBC driver implementation, and varies by database.

MySQL users note: By default, the MySQL JDBC driver will fetch all of the rows that reside in a table into the client application (Migration Toolkit) in a single network round-trip. This behavior can easily exceed available memory for large tables. If you encounter an 'out of heap space' error, specify `-fetchSize 1` as a command line argument to force Migration Toolkit to load the table data one row at a time.

`-filterProp <file_name>`

`<file_name>` specifies the name of a file that contains constraints in key=value pairs. Each record read from the database is evaluated against the constraints; those that satisfy the constraints are migrated. The left side of the pair lists a table name; please note that the table name should *not* be schema-qualified. The right side specifies a condition that must be true for each row migrated. For example, including the following constraints in the property file:

```
countries=country_id<>'AR'
```

migrates only those countries with a `country_id` value that is not equal to `AR`; this constraint applies to the countries table.

`-customColTypeMapping <column_list>`

Use custom type mapping to change the data type of migrated columns. The left side of each pair specifies the columns with a regular expression; the right side of each pair names the data type that column should assume. You can include multiple pairs in a semi-colon separated `<column_list>`. For example, to map any column whose name ends in `ID` to type `INTEGER`, use the following custom mapping entry:

```
.*ID=INTEGER
```

Custom mapping is applied to all table columns that match the criteria unless the column is table-qualified.

The `'\'` characters act as an escape string; since `'.'` is a reserved character in regular expressions, on Linux use `'\\.'` to represent the `'.'` character. For example, to use custom mapping to select rows from

the `EMP_ID` column in the `EMP` table, specify the following custom mapping entry:

```
EMP\EMP_ID=INTEGER
```

On Windows, use `\.` to represent the `'.'` character:

```
EMP\EMP_ID=INTEGER
```

```
-customColTypeMappingFile <property_file>
```

You can include multiple custom type mappings in a `<property_file>`; specify each entry in the file on a separate line, in a key=value pair. The left side of each pair selects the columns with a regular expression; the right side of each pair names the data type that column should assume.

Oracle Specific Options

The following options apply only when the source database is Oracle.

```
-objectTypes
```

Import the user-defined object types from the schema list specified at the end of the `runMTK.sh` command.

```
-allUsers
```

Import all users and roles from the source database. Please note that the `-allUsers` option is only supported when migrating from an Oracle database to an Advanced Server database.

```
-users <user_list>
```

Import the selected users or roles from the source Oracle database. `<user_list>` is a comma-separated list (with no intervening space characters) of user/role names (e.g., `-users MTK, SAMPLE, acctg`). Please note that the `-users` option is only supported when migrating

from an Oracle database to an Advanced Server database.

`-allProfiles`

Import all custom (that is, user-created) profiles from the source database. Other Oracle non-custom profiles such as `DEFAULT` and `MONITORING_PROFILE` are not imported.

For the imported profiles, only the following password parameters associated with the profiles are imported:

`FAILED_LOGIN_ATTEMPTS`

`PASSWORD_LIFE_TIME`

`PASSWORD_REUSE_TIME`

`PASSWORD_REUSE_MAX`

`PASSWORD_LOCK_TIME`

`PASSWORD_GRACE_TIME`

`PASSWORD_VERIFY_FUNCTION`

All other profile parameters such as the Oracle resource parameters are not imported. The Oracle database user specified by `SRC_DB_USER` must have `SELECT` privilege on the Oracle data dictionary view `DBA_PROFILES`.

Please note that the `-allProfiles` option is only supported when migrating from an Oracle database to an Advanced Server database.

`-profiles <profile_list>`

Import the selected, custom (that is, user-created) profiles from the source Oracle database. `<profile_list>` is a comma-separated list (with no intervening space characters) of profile names (e.g., `-profiles ADMIN_PROFILE,USER_PROFILE`). Oracle non-custom profiles such as `DEFAULT` and `MONITORING_PROFILE` are not imported.

As with the `-allProfiles` option, only the password parameters are imported. The Oracle database user specified by `SRC_DB_USER` must have SELECT privilege on the Oracle data dictionary view `DBA_PROFILES`.

Please note that the `-profiles` option is only supported when migrating from an Oracle database to an Advanced Server database.

`-importPartitionAsTable <table_list>`

Include the `-importPartitionAsTable` parameter to import the contents of a partitioned table that resides on an Oracle host into a single non-partitioned table. `<table_list>` is a comma-separated list (with no intervening space characters) of table names (e.g., `-importPartitionAsTable emp,dept,acctg`).

`-copyViaDBLinkOra`

The `dblink_ora` module provides Advanced Server-to-Oracle connectivity at the SQL level. `dblink_ora` is bundled and installed as part of the Advanced Server database installation. `dblink_ora` utilizes the COPY API method to transfer data between databases. This method is considerably faster than the JDBC COPY method.

The following example uses the `dblink_ora` COPY API to migrate all tables from the HR schema:

```
$.runMTK.sh -copyViaDBLinkOra -allTables HR
```

The target Advanced Server database must have `dblink_ora` installed and configured. For information about `dblink_ora`, please see the [Database Compatibility for Oracle Developer's Guide](#).

`-allDBLinks [link_Name_1=password_1,link_Name_2=password_2,...]`

Choose this option to migrate Oracle database links. The password information for each link connection in the source database is encrypted, so unless specified, a dummy password (`edb`) is substituted.

To migrate all database links using edb as the dummy password for the connected user:

```
$/runMTK.sh -allDBLinks HR
```

You can alternatively specify the password for each of the database links through a comma-separated list (with no intervening space characters) of name=value pairs. Specify the link name on the left side of the pair and the password value on the right side.

To migrate all database links with the actual passwords specified on the command-line:

```
$/runMTK.sh -allDBLinks LINK_NAME1=abc,LINK_NAME2=xyz HR
```

Migration Toolkit migrates only the database link types that are currently supported by EnterpriseDB; this includes fixed user links of public and private type.

-allSynonyms

Include the **-allSynonyms** option to migrate all public and private synonyms from an Oracle database to an Advanced Server database. If a synonym with the same name already exists in the target database, the existing synonym will be replaced with the migrated version.

-allPublicSynonyms

Include the **-allPublicSynonyms** option to migrate all public synonyms from an Oracle database to an Advanced Server database. If a synonym with the same name already exists in the target database, the existing synonym will be replaced with the migrated version.

-allPrivateSynonyms

Include the **-allPrivateSynonyms** option to migrate all private synonyms from an Oracle database to an Advanced Server database. If a synonym with the same name already exists in the target database, the existing synonym will be replaced with the migrated

version.

-useOraCase

Include the **-useOraCase** option to preserve the Oracle default, uppercase naming convention for all database objects when migrating from an Oracle database to an Advanced Server database.

The uppercase naming convention is preserved for tables, views, sequences, procedures, functions, triggers, packages, etc. For these database objects, the uppercase naming convention is applied to a) the names of the database objects, b) the column names, key names, index names, constraint names, etc., of the tables and views, c) the SELECT column list for a view, and d) the parameter names that are part of the procedure or function header.

Note: Within the procedural code body of a procedure, function, trigger or package, identifier references may have to be manually edited in order for the program to execute properly without an error. Such corrections are in regard to the proper case conversion of identifier references that may or may not have occurred.

Note: When the **-useOraCase** option is specified, the **-skipUserSchemaCreation** option may need to be specified as well. For information, see the description of the **-skipUserSchemaCreation** option in this section.

The default behavior of the Migration Toolkit (without using the **-useOraCase** option) is that database object names are extracted from Oracle without enclosing quotation marks (unless the database object was explicitly created in Oracle with enclosing quotation marks). The following is a portion of a table command generated by the Migration Toolkit with the **-offlineMigration** option:

```
CREATE TABLE DEPT (
DEPTNO NUMBER(2) NOT NULL,
DNAME VARCHAR2(14),
LOC VARCHAR2(13)
);
```



```
ALTER TABLE DEPT ADD CONSTRAINT DEPT_PK PRIMARY KEY
(DEPTNO);
ALTER TABLE DEPT ADD CONSTRAINT DEPT_DNAME_UQ UNIQUE
(DNAME);
```

When this table is then migrated to, and created in Advanced Server, all unquoted object names are converted to lowercase letters, so the table appears in Advanced Server as follows:

```
Table "edb.dept"
Column | Type                | Modifiers
-----+-----+-----
deptno | numeric(2,0)         | not null
dname  | character varying(14) |
loc    | character varying(13) |
Indexes:
"dept_pk" PRIMARY KEY, btree (deptno)
"dept_dname_uq" UNIQUE CONSTRAINT, btree (dname)
```

If your Advanced Server applications are referencing the migrated database objects using quoted uppercase identifiers, the applications will fail since the database object names are now in lowercase.

```
usepostcase=# SELECT * FROM "DEPT";
ERROR: relation "DEPT" does not exist
LINE 1: SELECT * FROM "DEPT";
```

If your application uses quoted upper-case identifiers, perform the migration with the `-useOracleCase` option. The DDL will enclose all database object names in quotes:

```
CREATE TABLE "DEPT" (
"DEPTNO" NUMBER(2) NOT NULL,
"DNAME" VARCHAR2(14),
"LOC" VARCHAR2(13)
```

```
);
ALTER TABLE "DEPT" ADD CONSTRAINT "DEPT_PK" PRIMARY KEY
("DEPTNO");
ALTER TABLE "DEPT" ADD CONSTRAINT "DEPT_DNAME_UQ"
UNIQUE ("DNAME");
```

When this table is migrated to, and created in Advanced Server, all object names are maintained in uppercase letters, so the table appears in Advanced Server as follows:

Table "EDB.DEPT"

Column	Type	Modifiers
DEPTNO	numeric(2,0)	not null
DNAME	character varying(14)	
LOC	character varying(13)	

Indexes:

"DEPT_PK" PRIMARY KEY, btree ("DEPTNO")

"DEPT_DNAME_UQ" UNIQUE CONSTRAINT, btree ("DNAME")

Applications can then access the object using quoted uppercase names.

```
useoracase=# SELECT * FROM "DEPT";
```

DEPTNO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON

(4 rows)

-skipUserSchemaCreation

When an Oracle user is migrated, a role (that is, a user name) is created in the target database server for this Oracle user if this role does not already exist. The role name is created in lowercase letters.

When a new role is created, a schema with the same name is also created in lowercase letters.

Specification of the `-skipUserSchemaCreation` option prevents this automatic, schema creation for a migrated Oracle user name. This option is particularly useful when the `-useOracleCase` option is specified in order to prevent creation of two schemas with the same name except for one schema name in lowercase letters and the other in uppercase letters. Specifying the `-useOracleCase` option results in the creation of a schema in the Oracle naming convention of uppercase letters for the source schema specified following the options list when Migration Toolkit is invoked.

Thus, if the `-useOracleCase` option is specified without the `-skipUserSchemaCreation` option, the target database results in having two identically named schemas with one in lowercase letters and the other in uppercase letters. If the `-useOracleCase` option is specified along with the `-skipUserSchemaCreation` option, the target database results in having just the schema in uppercase letters.

Miscellaneous Options

Use the migration options listed below to view Migration Toolkit help and version information; you can also use the options in this section to control Migration Toolkit feedback and logging options.

`-help`

Display the application command-line usage information.

`-logDir <log_path>`

Include this option to specify where the log files will be written; `<log_path>` represents the path where application log files are saved. By default, on Linux log files are written to:

`$HOME/.enterprisedb/migration-toolkit/logs`

On Windows, the log files are saved to:

```
%HOMEDRIVE%%HOMEPATH%\enterprisedb\migration-toolkit\logs
```

-logFileCount <file_count>

Include this option to specify the number of files used in log file rotation. Specify a value of 0 to disable log file rotation and create a single log file (it will be truncated when it reaches the value specified using the logFileSize option). **<file_count>** must be greater than or equal to 0; the default is 20.

-logFileSize <file_size>

Include this option to specify the maximum file size limit (in MB) before rotating to a new log file. **<file_size>** must be greater than 0; the default is 50 MB.

-logBadSQL

Include this option to have the schema definition (DDL script) of any failed objects saved to a file. The file is saved under the same path that is used for the error logs and is named in the format **mtk_bad_sql_<schema_name_timestamp>.sql** where **schema_name** is the name of the schema and **timestamp** is the timestamp of the Migration Toolkit run.

-verbose [on|off]

Display application log messages on standard output (By default, verbose is **on**).

-version

Display the Migration Toolkit version.

Example

The following example demonstrates performing an Oracle to Advanced Server migration.

The following is the content of the toolkit.properties file.

```
SRC_DB_URL=jdbc:oracle:thin:@192.168.2.6:1521:xe
SRC_DB_USER=edb
SRC_DB_PASSWORD=password
TARGET_DB_URL=jdbc:edb://localhost:5444/edb
TARGET_DB_USER=enterprisedb
TARGET_DB_PASSWORD=password
```

The following command invokes Migration Toolkit:

```
$ ./runMTK.sh EDB
```

```
Running EnterpriseDB Migration Toolkit (Build 48.0.0) ...
Source database connectivity info...
conn =jdbc:oracle:thin:@192.168.2.6:1521:xe
user =edb
password=*****
Target database connectivity info...
conn =jdbc:edb://localhost:5444/edb
user =enterprisedb
password=*****
Connecting with source Oracle database server...
Connected to Oracle, version 'Oracle Database 10g Express Edition
Release 10.2.0.1.0 - Production'
Connecting with target EnterpriseDB database server...
Connected to EnterpriseDB, version '9.4.0.0'
Importing redwood schema EDB...
Creating Schema...edb
Creating Sequence: NEXT_EMPNO
Creating Tables...
Creating Table: BAD_TABLE
```

MTK-15013: Error Creating Table BAD_TABLE

DB-42704: ERROR: type "binary_double" does not exist at position 58

```
-- CREATE TABLE BAD_TABLE (
```

```
-- F1 NUMBER NOT NULL,
```

```
-- Line 3: F2 BINARY_DOUBLE
```

```
-- ^
```

Creating Table: DEPT

Creating Table: EMP

Creating Table: JOBHIST

Creating Table: "MixedCase"

Creating Table: "lowercase"

Created 5 tables.

Loading Table Data in 8 MB batches...

Loading Table: DEPT ...

[DEPT] Migrated 4 rows.

[DEPT] Table Data Load Summary: Total Time(s): 0.147 Total Rows: 4

Loading Table: EMP ...

[EMP] Migrated 14 rows.

[EMP] Table Data Load Summary: Total Time(s): 0.077 Total Rows: 14

Loading Table: JOBHIST ...

[JOBHIST] Migrated 17 rows.

[JOBHIST] Table Data Load Summary: Total Time(s): 0.042 Total Rows: 17

Total Size(MB): 9.765625E-4

Loading Table: "MixedCase" ...

["MixedCase"] Table Data Load Summary: Total Time(s): 0.098 Total Rows:0

Loading Table: "lowercase" ...

["lowercase"] Table Data Load Summary: Total Time(s): 0.066 Total Rows:0

Data Load Summary: Total Time (sec): 0.806 Total Rows: 35 Total Size(MB): 0.001

Creating Constraint: DEPT_PK

Creating Constraint: DEPT_DNAME_UQ

Creating Constraint: EMP_PK

Creating Constraint: JOBHIST_PK

Creating Constraint: SYS_C008958

MTK-15001: Error Creating Constraint SYS_C008958

DB-42P01: com.edb.util.PSQLException: ERROR: relation "bad_table"
does
not exist

Creating Constraint: EMP_REF_DEPT_FK

Creating Constraint: EMP_SAL_CHK

Creating Constraint: JOBHIST_REF_DEPT_FK

Creating Constraint: JOBHIST_REF_EMP_FK

Creating Constraint: JOBHIST_DATE_CHK

Creating Trigger: USER_AUDIT_TRIG

Creating Trigger: EMP_SAL_TRIG

MTK-13009:Warning! Skipping migration of trigger DROP_TRIGGER,
currently

non-table triggers are not supported in target database.

Creating View: SALESEMP

Creating Function: EMP_COMP

Creating Package: EMP_ADMIN

MTK-16005:Package Body is Invalid, Skipping...

Schema EDB imported with errors.

MTK-12001: The user/role migration failed due to insufficient
privileges.

Grant the user SELECT privilege on the following Oracle catalogs:

DBA_ROLES

DBA_USERS

DBA_TAB_PRIVS

DBA_PROFILES

DBA_ROLE_PRIVS

ROLE_ROLE_PRIVS

DBA_SYS_PRIVS

One or more schema objects could not be imported during the migration
process. Please review the migration output for more details.

Migration logs have been saved to

/home/user/.enterprisedb/migration-toolkit/logs

***** Migration Summary *****

Sequences: 1 out of 1

Tables: 5 out of 6

Constraints: 9 out of 10

Triggers: 2 out of 3 (skipped 1)

Views: 1 out of 1

Functions: 1 out of 1

Packages: 1 out of 1

Total objects: 30

Successful count: 20

Failed count: 2

Skipped count: 1

Invalid count: 7

List of failed objects

=====

Tables

1. EDB.BAD_TABLE

Constraints

1. EDB.BAD_TABLE.SYS_C008958

List of invalid objects

=====

1. EDB.HIRE_CLERK (FUNCTION)

2. EDB.NEW_EMPNO (FUNCTION)

3. EDB.EMP_ADMIN (PACKAGE BODY)

4. EDB.EMP_QUERY (PROCEDURE)

5. EDB.EMP_QUERY_CALLER (PROCEDURE)

6. EDB.LIST_EMP (PROCEDURE)

7. EDB.SELECT_EMP (PROCEDURE)

Note the omission of skipped and unsupported database objects. The migration information is summarized in the Migration Summary at the end of the run.

9 Migration Errors

During the migration process, the migration summary displays the progress of the migration. If an error occurs, the summary will display information about the error. The migration summary is also written to a log file. The default locations for the log files are:

On Linux:

```
$HOME/.enterisedb/migration-toolkit/logs
```

On Windows, the log files are saved to:

```
%HOMEDRIVE%%HOMEPATH%\enterisedb\migration-toolkit\logs
```

You can specify an alternate log file directory with the `-logdir *log_path*` option in Migration Toolkit.

Connection Errors

Migration Toolkit uses information from the `toolkit.properties` file `<building_toolkit.properties_file>` to connect to the source and target databases. Most of the connection errors that occur when using Migration Toolkit are related to the information specified in the `toolkit.properties` file. Use the following section to identify common connection errors, and learn how to resolve them.

Invalid username/password

When I try to perform a migration from an Oracle database with Migration Toolkit, I get the following error:

```
MTK-11009: Error Connecting Database "Oracle"
DB-1017: java.sql.SQLException: ORA-01017: invalid
username/password;
logon denied
The user name or password specified in the toolkit.properties file is
not valid to use to connect to the Oracle source database.
```

To resolve this error, edit the `toolkit.properties` file, specifying the name and password of a valid user with sufficient privileges to perform the migration in the `SRC_DB_USER` and `SRC_DB_PASSWORD` properties.

Connection rejected: FATAL: password

When I try to perform a migration with Migration Toolkit, I get the following error:

```
MTK-11009: Error Connecting Database "Advanced Server"
DB-28P01: com.edb.util.PSQLException: FATAL: password authentication
failed for user "*name*"
```

The user name or password specified in the `toolkit.properties` file is not valid to use to connect to the Postgres database.

To resolve this error, edit the `toolkit.properties` file, specifying the name and password of a valid user with sufficient privileges to perform the migration in the `TARGET_DB_USER` and `TARGET_DB_PASSWORD` properties.

Exception: ORA-28000: the account is locked

When I try to perform a migration from an Oracle database with Migration Toolkit, I get the following error message:

```
MTK-11009: Error Connecting Database "Oracle"  
DB-28000: java.sql.SQLException: ORA-28000: the account is locked  
The Oracle account associated with the user name specified in the  
toolkit.properties file is locked.
```

To resolve this error, you can either unlock the user account on the Oracle server or edit the `toolkit.properties` file, specifying the name and password of a valid user with sufficient privileges to perform the migration in the `SRC_DB_USER` and `SRC_DB_PASSWORD` parameters.

Exception: oracle.jdbc.driver.OracleDriver

When I try to perform a migration with Migration Toolkit, the migration fails and I get the error message:

```
MTK-11009: Error Connecting Database "Oracle"  
java.lang.ClassNotFoundException: oracle.jdbc.driver.OracleDriver
```

Before using Migration Toolkit, you must download and install the appropriate JDBC driver for the database that you are migrating from. See [Installing Source-Specific Drivers](#) for complete instructions.

I/O exception: The Network Adapter could not establish the connection

When I try to perform a migration with Migration Toolkit, I get the following error:

MTK-11009: Error Connecting Database "Oracle"
 DB-17002: java.sql.SQLException: Io exception: The Network Adapter could not establish the connection

The *JDBC URL* for the source database specified in the `toolkit.properties` file contains invalid connection properties.

To resolve this error, edit the `toolkit.properties` file `<building_toolkit.properties_file>` specifying valid connection information for the source database in the `SRC_DB_URL` property. Please note that the `SRC_DB_URL` value is database-specific; consult the table of contents for detailed information for your source database type.

Exception: The URL specified for the “target” database is invalid

When I try to perform a migration with Migration Toolkit, I get the following error:

MTK-10045: The URL specified for the "target" database is invalid.
 Check the connectivity credentials.

The JDBC URL for the target database (Advanced Server) specified in the `toolkit.properties` file contains invalid connection properties.

To resolve this error, edit the `toolkit.properties` file, specifying valid connection information for the target database in the `TARGET_DB_URL` property. For information about forming a JDBC URL for Advanced Server, see [Defining an Advanced Server URL](#).

Migration Errors

The following errors may occur after Migration Toolkit has successfully connected to the target and source database servers.

ERROR: Extra Data after last expected column

When migrating a table online, I get the error message:

```
MTK-17001: Error Loading Data into Table: *table_name*
DB-22P04: com.edb.util.PSQLException: ERROR: extra data after last
expected column
Where: COPY *table_name*, line 5: "50|HR|LOS|ANGELES"
```

This error occurs when the data in a column in *table_name* includes the delimiter character. To correct this error, change the delimiter character to a character not found in the table contents.

Note: In this example, the pipe character (|) occurs in the text, **LOS|ANGELES**, intended for insertion into the last column, and the Migration Toolkit is run using the **-copyDelimiter '|'** option, which results in the error.

Error Loading Data into Table: *TABLE_NAME*

When performing a data-only migration, I get the following error:

```
MTK-17001: Error Loading Data into Table: *TABLE_NAME*
DB-42P01: com.edb.util.PSQLException: ERROR: relation
"*schema*.\ *table_name*" does not exist
*I also get the error:*
Trying to reload table: *TABLE_NAME* through bulk inserts with a batch
size of 100
MTK-17001: Error Loading Data into Table: *TABLE_NAME*
DB-42P01: com.edb.util.PSQLException: ERROR: relation
"*schema*.\ *table_name*" does not exist
```

You must create a table to receive the data in the target database before you can migrate the data. Verify that a table (with a name of *TABLE_NAME*

) exists in the target database; create the table if necessary and re-try the data migration.

Error Creating Constraint CONS_NAME_FK

When I perform a table migration that includes indexes and constraints, I get the following error message:

```
MTK-15001: Error Creating Constraint EMP_DEPT_FK
DB-42P01: com.edb.util.PSQLException: ERROR: relation
"hr.departments"
does not exist
Creating Constraint: EMP_JOB_FK
MTK-15001: Error Creating Constraint EMP_JOB_FK
DB-42P01: com.edb.util.PSQLException: ERROR: relation "hr.jobs" does
not exist
Creating Constraint: EMP_MANAGER_FK
Schema HR imported with errors.
One or more schema objects could not be imported during the migration
process. Please review the migration output for more details.
Migration logs have been saved to
/home/user/.enterprisedb/migration-toolkit/logs
***** Migration Summary *****
Tables: 1 out of 1
Constraints: 4 out of 6
Total objects: 7
Successful count: 5
Failed count: 2
Invalid count: 0
List of failed objects
=====
Constraints
-----
```

1. HR.EMPLOYEES.EMP_DEPT_FK
2. HR.EMPLOYEES.EMP_JOB_FK

The table you are migrating includes a foreign key constraint on a table that does not exist in the target database. Migration Toolkit creates the table, omitting the foreign key constraint.

You can avoid generating the error message by including the `- skipFKConst` option in the Migration Toolkit command.

Error Loading Data into Table

I've already migrated the table definition; when I try to migrate the data into the table, I get an error:

```
MTK-17001: Error Loading Data into Table: DEPARTMENTS
DB-22P04: com.edb.util.PSQLException: ERROR: extra data after last
expected column
Where: COPY departments, line 1: "10 Administration 200 1700"
Trying to reload table: DEPARTMENTS through bulk inserts with a batch
size of 100
MTK-17000: Batch entry 0 INSERT INTO hr.DEPARTMENTS VALUES
(10,
'Administration', 200, 1700); was aborted. Call getNextException to see
the cause.
DB-42601: java.sql.BatchUpdateException: Batch entry 0 INSERT INTO
hr.DEPARTMENTS VALUES (10, 'Administration', 200, 1700); was
aborted.
Call getNextException to see the cause., Skipping Batch
MTK-17000:ERROR: INSERT has more expressions than target columns
Position: 48
[DEPARTMENTS] Table Data Load Summary: Total Time(s): 0.037 Total
Rows:0
Data Load Summary: Total Time (sec): 0.168 Total Rows: 0 Total
```

Size(MB):0.0

Schema HR imported with errors.

The table definition (in the target database) does not match the migrated data. If you've altered the target or source table, confirm that the table definition and the data are compatible.

ERROR: value too long for type

I've already migrated the table definition; when I try to migrate the data into the table, I get the following error:

```
MTK-17001: Error Loading Data into Table: DEPARTMENTS
DB-22001: com.edb.util.PSQLException: ERROR: value too long for type
character(1)
Where: COPY departments, line 1, column location_id: "1700"
Trying to reload table: DEPARTMENTS through bulk inserts with a batch
size of 100
MTK-17000: Batch entry 0 INSERT INTO hr.DEPARTMENTS VALUES
(10,
'Administration', 200, 1700); was aborted. Call getNextException to see
the cause.
DB-22001: java.sql.BatchUpdateException: Batch entry 0 INSERT INTO
hr.DEPARTMENTS VALUES (10, 'Administration', 200, 1700); was
aborted.
Call getNextException to see the cause., Skipping Batch
MTK-17000:ERROR: value too long for type character(1)
```

A column in the target database is not large enough to receive the migrated data; this problem could occur if the table definition is altered after migration. The column name (in our example, `location_id`) is identified in the line that begins with **Where:**.

Where: COPY departments, line 1, column location_id: "1700"

To correct the problem, adjust the column size and re-try the migration.

ERROR: Exception in thread:OutOfMemoryError

When migrating from a MySQL database, I encounter the following error:

```

Loading Table: big_range ...
Exception in thread "dataload_job_1" java.lang.OutOfMemoryError: Java
heap space
at com.mysql.jdbc.MysqlIO.nextRow(MysqlIO.java:1370)
at com.mysql.jdbc.MysqlIO.readSingleRowSet(MysqlIO.java:2369)
at com.mysql.jdbc.MysqlIO.getResultSet(MysqlIO.java:451)
at
com.mysql.jdbc.MysqlIO.readResultsForQueryOrUpdate(MysqlIO.java:2076
)
at com.mysql.jdbc.MysqlIO.readAllResults(MysqlIO.java:1451)
at com.mysql.jdbc.MysqlIO.sqlQueryDirect(MysqlIO.java:1787)
at com.mysql.jdbc.Connection.execSQL(Connection.java:3277)
at com.mysql.jdbc.Connection.execSQL(Connection.java:3206)
at com.mysql.jdbc.Statement.executeQuery(Statement.java:1232)
at com.edb.dbhandler.mysql.Data.getTableData(Data.java:90)
at com.edb.DataLoader.loadDataInFastMode(DataLoader.java:594)
at com.edb.DataLoader.run(DataLoader.java:186)
at java.lang.Thread.run(Thread.java:722)

```

By default, the MySQL JDBC driver will fetch all of the rows that reside in a table into the client application (Migration Toolkit) in a single network round-trip. This behavior can easily exceed available memory for large tables.

To correct the problem, specify `-fetchSize 1` as a command line argument when you re-try the migration.

10 Error Codes

When Migration Toolkit encounters a problem, it issues a notification in the form of an error code and a message.

This chapter describes the error codes, messages, and their resolutions.

Each error code begins with the prefix MTK- followed by five digits. The first two digits denote the error class, which is a general classification of the error. The last three digits represent the specific error condition.

The following table lists the error classes.

Error Class	Description
00	Successful Completion
01	Information
02	Warning
03	General Error
0x	Reserved
10	Invalid User Input
11	Configuration Error
12	Insufficient Privileges
13	Unsupported Feature
14	Missing Object
15	Schema Migration
16	Procedural Language Migration
17	Data Loading

If there is an error reported back by a specific database server, this error message is prefixed with DB-. For example, if table creation fails due to an existing table in a Postgres database server, the error code 42P07 is returned by the database server. The specific error in the Migration Toolkit log appears as **DB-42P07**.

Error Code Summary

The following sections summarize the Migration Toolkit error codes. In the following tables, column Error Code lists the Migration Toolkit error codes. The Message and Resolution column contains the message displayed with the error code. The message explains the cause of the error and how it is to be resolved.

In the Message and Resolution column, `$NAME` is a placeholder for information that is substituted at run time with the appropriate value.

Class 02 - Warning

This class represents the warning messages.

Error Code	Message and Resolution
MTK-02000	All the warnings that relate to this class and do not have a specific error code binding will use this error code.
MTK-02001	Run 'runMTK -help' to see the usage details.
MTK-02002	Warning! The offline migration path <code>\$OFFLINE_PATH</code> does not exist, the scripts will be created under the user home folder.

Class 10 - Invalid User Input

This class represents invalid user input values.

Error Code	Message and Resolution
MTK-10000	All the errors that relate to this class and do not have a specific error code binding will use this error code.

Error Code	Message and Resolution
MTK-10001	You cannot select information_schema, dbo, sys, or pg_catalog as target schemas. These are used to store metadata information in <i>\$DATABASE</i> .
MTK-10002	The '-schemaOnly' and '-dataOnly' options cannot be specified at the same time.
MTK-10003	The "\t" is required as a copyDelimiter, when using escapeTabDelimiter option.
MTK-10004	The -truncLoad option can only be given with the -dataOnly option.
MTK-10005	The '-dataOnly' option is applicable only for -allTables/-tables option. Schema DDL cannot be copied when this option is in place.
MTK-10006	The -constraints, -indexes and -triggers options are applicable only in the context of -allTables/-tables option.
MTK-10007	The '-vacuumAnalyze' and '-analyze' options cannot be specified at the same time.
MTK-10008	The -skipFKConst option can only be given with -constraints option.
MTK-10009	The -skipCKConst option can only be given with -constraints option.
MTK-10010	The -fastCopy option cannot be specified with -schemaOnly option.
MTK-10011	The -skipColDefaultClause cannot be specified with -dataOnly option.
MTK-10012	The '-customColTypeMapping' and '-customColTypeMappingFile' options cannot be specified at the same time.
MTK-10013	Provided default date time must be in following format 'yyyy-MM-dd_HH:mm:ss'. Time portion is optional, to specify time, the underscore symbol '_' is necessary.
MTK-10014	You cannot select MySQL and Sybase as the target database for migration.
MTK-10015	Copy delimiter should be a single character.

Error Code	Message and Resolution
MTK-10017	Invalid number for batch size, use a number from 1-50000.
MTK-10018	Copy Batch Size should be greater than 0.
MTK-10019	Invalid number for Copy Batch Size, use a number > 0.
MTK-10020	Fetch Size should be greater than 0.
MTK-10021	Invalid number for Fetch Size, use a number > 0.
MTK-10022	One or more of the command-line arguments is invalid.
MTK-10023	The -targetDBVersion value should be specified using <i>major.minor</i> pattern.
MTK-10024	The -targetDBVersion can only be used with -offlineMigration mode.
MTK-10025	Options (-constraints
MTK-10026	The -allSchemas option should be specified as the last option in the command-line options list.
MTK-10027	You have specified invalid command-line arguments. Run 'runMTK -help' to see the usage details.
MTK-10028	The -replaceNullChar cannot be specified with -schemaOnly option.
MTK-10029	The -nullReplacementChar can only be specified with -replaceNullChar option.
MTK-10030	The -ignoreCheckConstFilter can only be given with -constraints option.
MTK-10031	The -enableConstBeforeDataLoad can only be given with -truncLoad option.
MTK-10032	The retryCount value should be greater than 0.

Error Code	Message and Resolution
MTK-10033	Invalid number for retryCount, use a number > 0.
MTK-10034	The loaderCount value should be greater than 0.
MTK-10035	Invalid number for loaderCount, use a number > 0.
MTK-10036	Cannot use singleDataFile option for offline data migration in COPY format.
MTK-10037	The offline data migration in COPY format is supported only when PostgreSQL or EnterpriseDB (EDB Postgres Advanced Server) is the target database.
MTK-10038	The <i>\$SCHEMA</i> cannot be used as schema name in <i>\$DATABASE</i> . Choose a different schema name via -targetSchema option.
MTK-10039	Log file size should be greater than 0.
MTK-10040	Log file count should be greater than or equal to 0.
MTK-10041	Offline migration can only be used with schema only option.
MTK-10042	The copyViaDBLinkOra option can only be used for copying data from Oracle to EnterpriseDB.
MTK-10043	The -recreateConst option can only be given with the -dataOnly option.
MTK-10044	The <i>\$DATABASE</i> database type is not supported by Migration Toolkit. Specify a valid database type string (i.e., EnterpriseDB, Postgres, Oracle, SQLServer, Sybase, or MySQL).
MTK-10045	The URL specified for the <i>\$DATABASE</i> database is invalid. Check the connectivity credentials.
MTK-10046	The -escapeKeywords value may be true or false.
MTK-10047	The -useOraCase option can only be used for migration from Oracle.

Error Code	Message and Resolution
MTK-10048	The Postgres exported snapshot id is invalid.
MTK-10049	The URL specified for the Oracle database is not supported by dblink_ora. Check the connectivity credentials and provide a valid URL.
MTK-10050	The schema <i>\$SCHEMA</i> not found on source database.
MTK-10051	The skipUserSchemaCreation option can only be used for user migration from Oracle to EnterpriseDB.

Class 11 - Configuration Issues

This class represents invalid configuration settings provided in the toolkit.properties file or in any other configuration file used by the Migration Toolkit.

Error Code	Message and Resolution
MTK-11000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-11001	The properties file containing table filter clause cannot be loaded.
MTK-11002	The custom type mapping file couldn't be loaded. Reason: <i>\$REASON</i> .
MTK-11003	The custom type mapping file contains an invalid mapping entry.
MTK-11004	The custom type mapping file doesn't contain any mapping entry.

Error Code	Message and Resolution
MTK-11005	Connectivity information for source database is not available.
MTK-11006	Connectivity information for target database is not available.
MTK-11007	Unable to create the logs directory. <i>\$PATH</i> .
MTK-11008	The properties file containing table columns filter list cannot be loaded.
MTK-11009	Error Connecting Database <i>\$DATABASE</i> .
MTK-11010	Error loading <i>\$DBLINKORA_FILE</i> file.
MTK-11011	Error while loading DBLink Ora module. <i>\$DBLINKORA_MODULE</i> . Verify that dblink_ora is installed/configured on target EnterpriseDB server. Please see the Database Compatibility for Oracle Developer's Guide for more information about installing and configuring the dblink_ora module.
MTK-11012	Error while loading given DBLink_Ora module. <i>\$DBLINKORA_MODULE</i> . Verify that dblink_ora is installed/configured on target EnterpriseDB server. Please see the Database Compatibility for Oracle Developer's Guide for more information about installing and configuring the dblink_ora module.
MTK-11013	Could not load DBLinkOra Module.
MTK-11014	Error connecting to DBLinkOra.
MTK-11015	The connection credentials file <i>\$TOOLKIT_PROP_FILE</i> is not secure and accessible to group/others users. This file contains plain passwords and should be restricted to Migration Toolkit owner user only.

Class 12 - Insufficient Privileges

This class represents insufficient privilege errors for loading database user/role information.

Error Code	Message and Resolution
MTK-12000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-12001	The user/role migration failed due to insufficient privileges. Grant the user SELECT privilege on the following Oracle catalogs: DBA_ROLES, DBA_USERS, DBA_TAB_PRIVS, DBA_PROFILES, DBA_ROLE_PRIVS, ROLE_ROLE_PRIVS, DBA_SYS_PRIVS.
MTK-12002	The migration of privileges failed due to insufficient privileges. Grant the user SELECT privilege on the following Oracle catalog: dba_tab_privs.

Class 13 - Unsupported Features

This class represents errors related with the migration of unsupported objects and clauses. Either the target database has not provided the implementation for the given object, or the Migration Toolkit does not handle its migration.

Error Code	Message and Resolution
MTK-13000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-13001	Skipping index as Oracle does not allow multiple indexes against same column list.
MTK-13002	For <i>\$DATABASE</i> views migration is not supported.

Error Code	Message and Resolution
MTK-13003	For <i>\$DATABASE</i> roles migration is not supported.
MTK-13004	You cannot migrate triggers, sequences, procedures, functions, packages and synonyms for MySQL, SQL Server, and Sybase databases.
MTK-13005	You cannot migrate sequences and packages for SQL Server database.
MTK-13006	Given trigger is not migrated, the trigger is owned by a different user schema and cross-schema triggers are not supported by EnterpriseDB.
MTK-13007	The given trigger is not migrated, the trigger has WHEN clause which is not supported by EnterpriseDB.
MTK-13008	Skipping Database Link <i>\$DATABASE_LINK</i> . EnterpriseDB currently does not support this type of Database Link.
MTK-13009	Warning! Skipping migration of trigger <i>\$TRIGGER</i> , currently non-table triggers are not supported in target database.
MTK-13010	You cannot migrate procedures, packages, synonyms and database links to PostgreSQL database.
MTK-13011	Domain objects are not supported in target database.
MTK-13012	Rules are not supported in <i>\$DATABASE</i> database.
MTK-13013	The database type is not supported.
MTK-13014	Hash partition is not supported in EnterpriseDB.
MTK-13015	<i>\$TYPE</i> is Not Supported by COPY.
MTK-13016	The migration to PostgreSQL is supported only when Oracle or PostgreSQL is the source database.
MTK-13017	Groups are not supported in <i>\$DATABASE</i> database.

Error Code	Message and Resolution
MTK-13018	Profile migration is not supported in <i>\$SRC_DB</i> to <i>\$TARGET_DB</i> permutation.
MTK-13019	Cannot migrate unknown Profile <i>\$PROFILE</i> .
MTK-13020	Profiles cannot be migrated to database version <i>\$VERSION</i> .
MTK-13021	Password Profile verify function <i>\$MY_VERIFICATION_FUNCTION</i> must be explicitly migrated.
MTK-13022	Advanced Queues migration is not supported from <i>\$SRC_DB</i> database to <i>\$TARGET_DB</i> database.
MTK-13023	Advanced Queues cannot be migrated to database version <i>\$VERSION</i> .
MTK-13024	The INTERVAL partition is not supported in <i>\$DATABASE</i> , the table will be migrated without INTERVAL definition.
MTK-13025	Warning! User profile migration is not supported in target database version <i>\$VERSION</i> . The profile " <i>\$PROFILE</i> " for user " <i>\$USER</i> " will be skipped.
MTK-13026	Object Type migration is not supported from <i>\$SRC_DB</i> to <i>\$TARGET_DB</i> .

Class 14 - Missing Objects

This class represents failures to find metadata information in the source database.

Error Code	Message and Resolution
MTK-14000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-14001	One or more tables are missing from the source <i>\$DATABASE</i> database.

Error Code	Message and Resolution
MTK-14002	One or more tables couldn't be found in the source <i>\$DATABASE</i> database. With -tables mode, the table name should be in uppercase unless it is case-sensitive.
MTK-14003	One or more users couldn't be found in the source <i>\$DATABASE</i> database. With -users mode, the user name should be in uppercase unless it is case-sensitive.

Class 15 - Schema Migration

The class represents migration issues related to non-procedural database objects such as tables, constraints, indexes, synonyms, views, users, and roles.

Error Code	Message and Resolution
MTK-15000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-15001	Error creating constraint <i>\$CONSTRAINT</i> .
MTK-15002	Error creating role <i>\$ROLE</i> .
MTK-15003	Error granting given privilege <i>\$PRIVILEGE</i> on <i>\$OBJECT</i> to <i>\$USER</i> .
MTK-15004	Error granting <i>\$ROLE</i> to <i>\$USER</i> .
MTK-15005	Error granting privilege <i>\$REASON</i> .
MTK-15006	Error creating user <i>\$USER</i> .
MTK-15007	Error creating index <i>\$INDEX</i> .

Error Code	Message and Resolution
MTK-15008	Error creating view <i>\$VIEW</i> .
MTK-15009	Error creating materialized view <i>\$MVIEW</i> .
MTK-15010	Error creating public synonym <i>\$SYNONYM</i> .
MTK-15011	Error creating private synonym <i>\$SYNONYM</i> .
MTK-15012	Error creating sequence <i>\$SEQUENCE</i> .
MTK-15013	Error creating table <i>\$TABLE</i> .
MTK-15014	Error creating database link <i>\$DATABASE_LINK</i> .
MTK-15015	Error creating given object type <i>\$OBJECT_TYPE</i> .
MTK-15016	The table <i>\$TABLE</i> could not be created in <i>\$DATABASE</i> database.
MTK-15017	The linked schema <i>\$LINKED_SCHEMA</i> doesn't exist in the target database. Create the schema and then retry.
MTK-15018	Error creating domain <i>\$DOMAIN</i> .
MTK-15019	Error creating custom data type <i>\$DATA_TYPE</i> .
MTK-15020	Error creating membership for group <i>\$GROUP</i> .
MTK-15021	Table name <i>\$TABLE</i> does not have a schema qualifier. With multiple schema migration context, each table should be schema qualified.
MTK-15022	Schema qualifier <i>\$SCHEMA</i> does not match the schema list.

Error Code	Message and Resolution
MTK-15023	The table metadata information is not available.
MTK-15024	Tables list is not initialized yet.
MTK-15025	Error while getting database metadata information.
MTK-15026	Error creating group <i>\$GROUP</i> .
MTK-15027	Error creating Profile <i>\$PROFILE</i> .

Class 16 - Procedural Language Migration

The class represents migration issues related to database objects that are based on procedural languages such as procedures, functions, packages, anonymous blocks, triggers, and rules.

Error Code	Message and Resolution
MTK-16000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-16001	Error Creating Trigger <i>\$TRIGGER</i> .
MTK-16002	Error Creating Rule <i>\$RULE</i> .
MTK-16003	Error Creating Package Spec <i>\$PACKAGE</i> .
MTK-16004	Error Creating Package Body <i>\$PACKAGE</i> .

Error Code	Message and Resolution
MTK-16005	Package Body is invalid, skipping... Note: This error message also appears when a package specification is successfully migrated, but there is no corresponding package body in the source database. In this case, the package specification should function properly in the target database despite the appearance of the error message.
MTK-16006	Error Creating Procedure <i>\$PROCEDURE</i> .
MTK-16007	Error Creating Function <i>\$FUNCTION</i> .
MTK-16008	Error Creating Anonymous Block <i>\$BLOCK</i> .
MTK-16009	Error creating Queue <i>\$QUEUE</i> .

Class 17 - Data Loading

This class represents errors that may occur while copying data from the source to the target database.

Error Code	Message and Resolution
MTK-17000	All the errors that relate to this class and do not have a specific error code binding will use this error code.
MTK-17001	Error Loading Data into Table: <i>\$TABLE</i>
MTK-17002	Encoding Conversion encountered some characters that will be loaded using Bulk Inserts instead.
MTK-17003	Error in copy tables <i>\$REASON</i> .

Error Code	Message and Resolution
MTK-17004	Invalid DataType.
MTK-17005	This Table Contains CLOB data, Marked for Bulk Insert Loading.

11 Unsupported Features

Advanced Server offers complete support for some Oracle features and partial support for others. Migration Toolkit cannot migrate any object that uses an unsupported feature.

In some cases, Migration Toolkit can migrate objects that use features that offer partial compatibility. In other cases, Advanced Server supports suitable workarounds.

Full-text search is an example of functionality that is not fully compatible with Oracle. The Advanced Server database has included support for full-text search for quite some time, but the implementation is quite different than Oracle's; Migration Toolkit is unable to migrate objects that utilize this feature.

There are also features that Advanced Server does not yet support. Features in this category include Automated Storage Management, table compression, and external tables. You can often orchestrate a successful workaround:

- Automated Storage Management can be replaced with (system specific) volume management software.
- Table compression can be implemented by storing data in a tablespace that resides on a compressed filesystem.
- External tables don't exist in Advanced Server, but you *can* load flat text

files into staging tables in the database. We recommend using the EDB Loader utility to load the data into an Advanced Server database quickly.

- When migrating multiple profiles from an Oracle database into Advanced server, you must manually assign the profile to a user (or users) when the migration completes.

Unsupported Postgres Features

Migration Toolkit does not support migration of the following Postgres features:

OPERATOR CLASS

OPERATOR FAMILY

For information about **OPERATOR CLASS** and **OPERATOR FAMILY**, see the PostgreSQL core documentation available at:

<https://www.postgresql.org/docs/11/static/indexes-opclass.html>

Frequently Asked Questions

Does Migration Toolkit support the migration of packages?

Migration Toolkit supports the migration of packages from an Oracle database into Advanced Server. See the **Functionality Overview Section** [<functionality_overview>](#) for information about the migration support offered by Advanced Server.

Is there a way to transfer only the data from the source database?

Yes. Data transfer is supported as part of an online or offline migration.

Does Migration Toolkit support migration of tables that contain data of the CLOB data type?

Migration Toolkit does support migration of tables containing data of the **CLOB** type.

Does Advanced Server support the enum data type?

Advanced Server does not currently support the enum data type, but will support them in future releases. Until then, you can use a check constraint to restrict the data added to an Advanced Server database. A check constraint defines a list of valid values that a column may take.

The following code sample includes a simple example of a check constraint that restricts the value of a column to one of three dept types; **sales**, **admin** or **technical**.

```
CREATE TABLE emp (
emp_id INT NOT NULL PRIMARY KEY,
dept VARCHAR(255) NOT NULL,
CHECK (dept IN ('sales', 'admin', 'technical'))
);
```

If we test the check constraint by entering a valid dept type, the INSERT statement works without error:

```
test=# INSERT INTO emp VALUES (7324, 'sales');
```

```
INSERT 0 1
```

If we try to insert a value not included in the constraint (support), Advanced Server throws an error:

```
test=# INSERT INTO emp VALUES (7325, 'support');
```

```
ERROR: new row for relation "emp" violates check constraint
"emp_dept_check"
```

Does Advanced Server support materialized views?

Postgres does not support materialized views compatible with Oracle

databases. To setup a materialized view/summary table in Postgres you must manually create the triggers that maintain the summary table. Automatic query rewrite is not currently supported; the application must be made aware of the summary table's existence.

When I try to migrate from a MySQL database that includes a TIME data type, I get the following error: Error Loading Data into Table: Bad format for Time. Does Postgres support MySQL ``TIME`` data types?

Postgres will have no problem storing **TIME** data types as long as the value of the hour component is not greater than 24.

Unlike Postgres, the MySQL **TIME** data type will allow you to store a value that represents either a **TIME** or an **INTERVAL** value. A value stored in a MySQL **TIME** column that represents an **INTERVAL** value could potentially be out of the accepted range of a valid Postgres **TIMESTAMP** value. If, during the migration process, Postgres encounters a value stored in a **TIME** data column that it perceives as out of range, it will return an error.