Unit 10 Module Wiki: Practical Applications and Challenges in Disaster Recovery Implementation

Module: Security and Risk Management (SRM)
Unit: 10 – Practical Applications and Issues in DR Implementations
Topic: Recovery Objectives, Disaster Recovery Architectures, DRaaS, Vendor Lock-in and Network Security

---

1. Introduction

Disaster Recovery (DR) refers to the strategies, processes and technologies used to restore critical IT infrastructure, applications and data following disruptive incidents such as cyberattacks, hardware failures, natural disasters and network outages.

DR forms an important part of Business Continuity Management (BCM), although the two concepts are not interchangeable. Business continuity focuses on maintaining essential organisational operations, whereas disaster recovery concentrates on restoring the technology services that support those operations.

According to NIST (2016), effective cybersecurity recovery requires appropriate planning, testing, coordination and continuous improvement.

The practical implementation of DR depends on Recovery Time Objectives (RTO), Recovery Point Objectives (RPO), infrastructure availability, cost and cybersecurity requirements.

2. Recovery Time Objective and Recovery Point Objective

Two fundamental considerations in disaster recovery design are RTO and RPO.

Recovery Time Objective (RTO) defines the maximum targeted period within which a disrupted system or service should be restored.

Recovery Point Objective (RPO) defines the maximum acceptable period of data loss measured backwards from the point of disruption.

For example, consider a telecommunications organisation managing Fibre-to-the-Premises (FTTP) services.

If the organisation establishes an RTO of two hours and an RPO of 15 minutes:

- Its critical customer management systems should be restored within two hours of disruption.
- It should be able to recover data to a point no more than 15 minutes before the incident.
- Replication or backup arrangements must support these objectives.

The distinction is important because a system may be restored quickly but still experience unacceptable data loss.

Furthermore, achieving a shorter RTO or RPO generally requires greater investment in infrastructure, automation, data replication and technical support.

Therefore, recovery objectives should be established through a Business Impact Analysis (BIA), considering financial losses, operational disruption, contractual commitments and reputational consequences.

3. Disaster Recovery Architectures and Standby Solutions

Organisations can implement several recovery architectures depending on their operational requirements.

3.1 Backup and Restore (Cold Recovery)

This approach involves maintaining backup copies of critical data and restoring systems after a disaster.

Advantages: Relatively inexpensive, straightforward to implement and appropriate for non-critical services.

Disadvantages: Restoration may take several hours or days, depending on the volume of data, infrastructure availability and recovery procedures.

3.2 Pilot Light

A pilot-light solution maintains the essential components of a system in a secondary environment while other resources are provisioned when recovery becomes necessary.

Advantages: Lower operating costs than a fully operational standby environment and potentially faster recovery than traditional backup restoration.

Disadvantages: Additional infrastructure must be deployed or scaled before services can resume.

3.3 Warm Standby

Warm standby involves maintaining a smaller but operational version of the production environment at a secondary location.

Advantages: Faster recovery, continuous replication capabilities and reduced operational disruption.

Disadvantages: Higher infrastructure costs, additional management requirements and potential replication vulnerabilities.

3.4 Hot Standby and Active-Active Architecture

Hot standby maintains a recovery environment with sufficient capacity to assume production operations rapidly. Active-active architecture allows multiple environments to process workloads simultaneously.

Advantages: Very short recovery times, improved service availability and reduced dependence on a single operational site.

Disadvantages: High implementation costs, infrastructure complexity and challenges involving data consistency, synchronisation and network configuration.

AWS (n.d.) identifies backup and restore, pilot light, warm standby and multi-site active-active as principal DR strategies, with different cost, complexity and recovery characteristics.

Importantly, these architectural approaches do not automatically guarantee particular recovery objectives. Actual performance must be demonstrated through testing.

4. Disaster Recovery as a Service (DRaaS)

Disaster Recovery as a Service (DRaaS) is a cloud-based approach in which a third-party provider supplies infrastructure and services to support disaster recovery.

DRaaS may include automated replication, virtual machine recovery, failover orchestration, backup management and recovery testing.

Advantages of DRaaS

1. Reduced requirement for organisations to maintain dedicated secondary data centres.
2. Scalable infrastructure that can accommodate changing workloads.
3. Automated failover and recovery procedures.
4. Access to specialist disaster recovery technologies and expertise.
5. Potentially improved recovery speed compared with manually managed recovery processes.

Limitations of DRaaS

Despite its advantages, DRaaS introduces several operational and security concerns.

Firstly, organisations may become dependent on the availability and technical capabilities of their cloud provider.

Secondly, recovery may be affected by internet connectivity, bandwidth constraints and network latency.

Thirdly, subscription charges, data transfer fees, storage costs and recovery testing expenses can increase the overall cost of the service.

Finally, shared responsibility arrangements must be clearly defined to prevent gaps in cybersecurity accountability.

Therefore, DRaaS should be evaluated against organisational recovery objectives rather than selected solely because of its perceived convenience or lower initial expenditure.

5. Vendor Lock-in, Resilience and Network Security

5.1 Vendor Lock-in

Vendor lock-in occurs when an organisation becomes heavily dependent on a particular technology provider, making migration to alternative systems difficult or expensive.

In DRaaS environments, lock-in may arise from proprietary backup formats, specialised replication software, provider-specific automation tools and complex data migration requirements.

Mitigation measures include negotiating exit arrangements, documenting infrastructure configurations, assessing workload portability and testing data export and restoration processes.

5.2 Resilience and Single Points of Failure

A major assumption in disaster recovery planning is that secondary infrastructure will remain available when the primary environment fails.

However, both environments may depend on shared services such as DNS, identity management, network connectivity or cloud control planes.

A failure affecting these shared dependencies could prevent recovery even where secondary infrastructure remains operational.

Organisations should therefore identify common-mode failures and implement appropriate geographical, technological and operational separation.

5.3 Network Security Considerations

Disaster recovery environments must maintain security controls equivalent to those protecting production systems.

Key measures include:

- Encryption of replicated data in transit and at rest.
- Network segmentation between production and recovery systems.
- Multi-factor authentication and least-privilege access.
- Secure administrative interfaces and monitoring.
- Immutable or isolated backups to protect against ransomware.
- Regular vulnerability assessments and recovery testing.

The UK National Cyber Security Centre (NCSC, n.d.) emphasises the importance of protecting backup systems against destructive attacks and ensuring that restoration to a known good state remains possible.

An important consideration is that continuous replication may also replicate corrupted or encrypted data following a ransomware incident. Consequently, replication alone should never be treated as a substitute for secure, independently recoverable backups.

6. Practical Disaster Recovery Design: FTTP Telecommunications Scenario

Consider a hypothetical FTTP service provider operating customer provisioning, billing, authentication and fault management systems.

A Business Impact Analysis establishes the following recovery requirements:

Critical system	RTO	RPO	Proposed DR solution
Customer authentication	15 minutes	5 minutes	Hot standby
Network fault management	30 minutes	10 minutes	Warm standby
Customer provisioning	2 hours	15 minutes	Warm standby with frequent replication
Billing system	8 hours	4 hours	Backup and restore

These are illustrative design targets rather than measured recovery performance.

The proposed architecture would involve a geographically separated recovery environment, encrypted data replication, independent administrative access and automated failover for highly critical services.

Immutable backups would provide additional protection against ransomware and accidental data corruption.

To validate the design, the organisation should conduct scheduled recovery exercises, including simulated network outages, failed replication, unavailable cloud services and ransomware incidents.

The results should be measured against the specified RTO and RPO requirements.

If the recovery procedures fail to meet the targets, the architecture and operational arrangements should be revised.

7. Critical Evaluation of Disaster Recovery Assumptions

Several assumptions frequently influence disaster recovery design.

Assumption 1: Cloud infrastructure guarantees availability.

Cloud platforms provide resilience capabilities, but outages, configuration errors and shared dependencies can still interrupt services.

Assumption 2: Replication guarantees data protection.

Replication improves availability but may reproduce data corruption or malicious changes. Versioned, isolated or immutable backups remain necessary.

Assumption 3: Lower RTO and RPO are always preferable.

Although shorter recovery objectives reduce potential disruption, they may introduce disproportionate costs. Recovery requirements should reflect actual business priorities.

Assumption 4: Successful backups guarantee successful recovery.

A completed backup does not establish that data can be restored within the required timeframe. Testing must include restoration, application functionality, data integrity and security validation.

Assumption 5: DRaaS transfers recovery responsibility to the provider.

The organisation remains responsible for defining recovery requirements, understanding contractual limitations, protecting sensitive information and validating recovery outcomes.

These considerations demonstrate that effective disaster recovery requires not only appropriate technology but also realistic assumptions, governance and continuous testing.

8. Personal Reflection and Conclusion

In my view, effective disaster recovery is a fundamental component of organisational cyber resilience rather than simply an IT infrastructure requirement.

My experience in fibre optic telecommunications highlights the importance of network availability, service restoration and infrastructure dependencies. A failure affecting customer provisioning, network management or authentication services may create operational and financial consequences even when the physical fibre network remains functional.

The study of RTO and RPO has strengthened my understanding of how organisations should select recovery architectures based on business requirements instead of technological preferences.

DRaaS presents valuable opportunities for flexibility and scalability, but its effectiveness depends on provider reliability, secure configuration, transparent contractual agreements and independent recovery validation.

I consider the integration of geographically separated infrastructure, appropriate standby arrangements, secure backups and regular recovery testing to be particularly important.

Ultimately, a disaster recovery strategy should be judged by its demonstrated ability to restore secure, functional services within agreed recovery objectives, rather than by the sophistication of its infrastructure alone.

References

Amazon Web Services (AWS) (n.d.) *REL13-BP02: Use defined recovery strategies to meet the recovery objectives*. AWS Well-Architected Framework. Available at: https://docs.aws.amazon.com/wellarchitected/latest/framework/rel_planning_for_recovery_disaster_recovery.html (Accessed: 18 October 2026).

National Cyber Security Centre (NCSC) (2023) *Cloud security guidance: The cloud security principles*. Available at: https://www.ncsc.gov.uk/collection/cloud/the-cloud-security-principles (Accessed: 18 October 2026).

National Cyber Security Centre (NCSC) (n.d.) *Ransomware-resistant backups*. Available at: https://www.ncsc.gov.uk/collection/ransomware-resistant-backups (Accessed: 18 October 2026).

National Institute of Standards and Technology (NIST) (2016) *Guide for Cybersecurity Event Recovery*. Special Publication 800-184. Gaithersburg, MD: NIST. Available at: https://doi.org/10.6028/NIST.SP.800-184 (Accessed: 18 October 2026).