Optimised Dense and Sparse Matrix Multiplication in Java: Loop Reordering, Cache Blocking and CSR

Big Data – Individual Assignment 2 · Grado en Ciencia e Ingeniería de Datos, ULPGC

Amai Suárez Navarro
October 2026

Abstract

I studied two ways of making the basic triple-loop matrix multiplication from Assignment 1 faster in Java. In Part A, I compared the Assignment 1 i-j-k loop with two sequential optimisations, loop reordering (i-k-j) and cache blocking, on the same dense float64 inputs for n = 64 to 2048. In Part B, I compared my own sparse multiplication in CSR format (Gustavson's algorithm) with dense blocked multiplication on exactly the same matrices, for densities from 0.1 % to 50 % at n = 1024 and 2048. All methods give bitwise-identical results. For n ≥ 1024 both optimisations were 10 to 15 times faster than the baseline, and the cost of one multiply-add fell from about 13 ns to about 1 ns. At n = 2048 the baseline did not finish one multiplication within the 60 s budget, while the optimised versions took 7.7 to 8.5 s. Blocking was not consistently faster than plain loop reordering: their differences (−8 % to +25 %) were of the same size as the variation between separate runs of the same configuration (up to 1.28×). Turning off the JIT's auto-vectorisation made no consistent difference (it only helped clearly at n = 1024). The sparse kernel was 24 to 32 000 times faster than dense up to 5 % density, 1.8 to 2.2 times faster at 35 %, and as fast or slightly slower at 50 %. The product of two random sparse matrices fills in quickly: at 5 % input density the output is already 92–99 % nonzero. The CSR arrays were smaller than the dense ones up to 35 % density and the same size at 50 %. These results apply to the tested implementations, inputs and laptop (Intel Core i5-5350U, 2 cores, 8 GB RAM, macOS).

1. Introduction and objective

In Assignment 1 the time per multiply-add of the Java i-j-k loop grew about 9 times between small and large matrices, because the inner loop reads B down a column and stops using the caches well once B no longer fits in them. Assignment 2 tests whether changing only the memory-access pattern removes that penalty, and whether skipping zeros helps when most entries are zero.

Research questions.

- **A.** How much do loop reordering and cache blocking reduce the runtime of the Assignment 1 baseline in Java, and how does the gain depend on n?
- **B.** For matrices with a uniform random pattern of nonzeros, below which density is a CSR multiplication faster and smaller than dense multiplication of the same matrices, and how much do the conversion to CSR and the fill-in of the product change that?

Hypotheses (written before running the study):

- H1: for small n (data in cache) the three dense kernels take similar time; the speedup of ikj and blocked over the baseline grows once B no longer fits in the caches.
- H2: blocking beats plain ikj only for the largest n, where a row of B and C no longer fits in the caches between uses; with intermediate n the two are close.
- H3: part of the ikj gain comes from the JIT vectorising the contiguous inner loop, which the column access of the baseline prevents; disabling auto-vectorisation reduces but does not remove the gain.
- H4: the sparse kernel's time grows roughly with the number of products n^3d^2 (d = density), while dense time does not depend on d; sparse wins below some density d* and loses above. Because

CSR needs 12 bytes per stored entry against 8 for dense, and the product fills in, sparse storage stops being smaller at a lower density for C than for A and B.

2. Background

Loop order. C = AB can be computed with the three loops in any order. In the i-j-k order each C[i][j] is a dot product, and B is read with a stride of n elements. In the i-k-j order the inner loop computes C[i][:] += A[i][k] · B[k][:], so B and C are read with unit stride, which uses whole cache lines and lets the hardware prefetcher work [1], [2]. A contiguous loop of this form can also be vectorised; the HotSpot C2 compiler does this automatically ("SuperWord"), and it can be turned off with `-XX:-UseSuperWord`.

Blocking (tiling). Even in i-k-j order, every row i of C streams the whole of B through the caches. Blocking splits the loops into tiles of bs × bs so that the tiles in use stay in cache and are reused before being evicted [3], [4]. With three tiles of $8 \cdot bs^2$ bytes, bs = 64 needs 96 KiB, which fits in the 256 KiB L2 cache per core of my CPU [5]. The best block size depends on the machine, so I also measured several sizes.

Sparse matrices and CSR. Compressed Sparse Row stores, for each row, the column indices and values of its nonzero entries, plus an array of n + 1 row pointers [6]. With 32-bit indices and 64-bit values it needs 12 bytes per nonzero plus 4(n+1) bytes, so it only saves memory below about 2/3 density. Gustavson's algorithm [7] computes C one row at a time: row i of C is the sum of the rows k of B weighted by the nonzeros A[i][k]. Its work is proportional to the number of nonzero products, not to n^3. Like SciPy's implementation [8], mine first counts the nonzeros of each row of C (symbolic pass), then allocates C exactly and computes the values (numeric pass), using a dense accumulator and a marker array of length n. For a uniform pattern with density d, the expected number of products is n^3d^2, and the expected density of C is $1 - (1 - d^2)^n$, which approaches 1 when nd^2 is large: the product fills in [9].

Correctness. As in Assignment 1, I used the forward error bound of a dot product, $|\hat{c} - c| \le \gamma_n \, |a|^T|b|$ with $\gamma_n = nu/(1 - nu)$, $u = 2^{-53}$ [10], to compare with NumPy. Because Java does not reassociate floating-point operations or fuse them into FMA (JEP 306), kernels that add the same products in the same order give bitwise-identical results.

3. Methodology

3.1 Implementations

All code is Java 17 (compiled with `javac --release 17`), sequential, float64, with matrices stored as one contiguous row-major `double[]`.

Table 1. Implementations.

Method	Description	Timed region includes
`baseline`	Assignment 1 i-j-k loop, copied unchanged (repo `amaisuarez/assignment1`, commit `754ec23`)	the three loops
`ikj`	loops j and k swapped; A[i][k] kept in a register	zeroing C ($O(n^2)$) + loops
`blocked`	i-k-j inside 64 × 64 tiles, tile loops ii → kk → jj; edge tiles for any n	zeroing C + loops
`ikj_novec`, `blocked_novec`	same code, JVM flag `-XX:-UseSuperWord` (auxiliary, to isolate SIMD)	as above
`sparse`	CSR × CSR → CSR, Gustavson, two passes, dense accumulator; own code	allocation of C and work arrays + both passes

For every C[i][j], all dense kernels add the products in increasing k starting from 0.0, so they only change the order in which different entries of C are computed. The sparse kernel adds the same non-zero products in the same order (only the ±0.0 terms are missing), so it gives the same values. The sparse output keeps column indices in order of first appearance (not sorted) and keeps entries that cancel to exactly zero.

3.2 Inputs

- **Part A:** the dense Assignment 1 inputs, regenerated with the same script and seed (`20262027`); values uniform in [−1, 1); SHA-256 checked against the Assignment 1 manifest.
- **Part B:** for each n ∈ {1024, 2048} and density d ∈ {0.001, 0.005, 0.01, 0.05, 0.1, 0.25, 0.35, 0.5}, two matrices where every position is nonzero independently with probability d (uniform random pattern), with values uniform in [−1, 1) and no exact zeros. Seeds are `20262027:n:d:A|B`. They are stored once in COO format and **both** the sparse and the dense method read the same file: the dense method expands it into a dense array before the timer starts, and the sparse method builds CSR. The realised nnz (Table 5) is within 1.4 % of $d \cdot n^2$ in every case except the smallest one (n = 1024, d = 0.001: 1007 and 1027 nonzeros against 1049 expected, about one standard deviation of the binomial count).

3.3 Environment

Intel Core i5-5350U (2 physical cores, 4 logical processors, 1.8 GHz), 8 GB RAM, macOS, on mains power. Java: OpenJDK 21.0.6 (JetBrains Runtime build 21.0.6+9-b895.97), the same JVM as in Assignment 1. Harness and analysis: Python 3.13.5. Each configuration ran in a new JVM with `-XX:+UseSerialGC -Xms256m -Xmx4g`. Besides the single application thread, the JVM runs its own threads (JIT compiler, garbage collector); no library with its own thread pool is used. As in Assignment 1, macOS did not let me pin the process to a core or disable Turbo Boost. The benchmark processes ran for about 25 minutes in total (run `results/run_20261026-153110`).

3.4 Correctness

`tests/validate.py` ran before the benchmarks: 112 checks, all passed (`results/validation_report.txt`). It checks identity, zero and a hand-computed 2 × 2 for every method; that ikj and blocked (block sizes 1, 3, 7, 16, 64, 128, including sizes that do not divide n) are **bitwise equal** to the baseline for n from 1 to 130; that the baseline is within $2\gamma_n|A||B|$ of NumPy; and that, for n up to 200 and densities 0 to 1 (including empty rows), the sparse result equals the dense baseline value by value and its nnz equals the nnz of the boolean product of the patterns. In the benchmark itself, all Part A methods produced the same checksum at every n (one distinct value per n), and in Part B the sparse and dense methods reported the same nnz of C.

3.5 Measurement protocol

- **Timing boundary:** the multiplication kernel only (Table 1). Reading files and creating the dense C array are outside. The COO → CSR conversion of A and B is timed separately, 5 times per configuration, and reported both alone and added to the sparse time.
- **Timer and dead-code protection:** `System.nanoTime()`; the sum of C is printed after every repetition.
- **Warm-up:** 3 rounds for n ≤ 512 and 1 for larger n, each lasting at least 100 ms, excluded from the statistics. The batch size (multiplications per repetition) comes from the last warm-up round so that each repetition lasts about 100 ms; for n ≥ 384 it is 1 or 2.
- **Repetitions and statistics:** 5 measured repetitions per configuration; I report the median and the interquartile range (IQR) of the time per multiplication. All raw values are in `raw_measurements.csv`.
- **Order:** method order shuffled with a fixed seed for each size (and each density).

- **Budgets, declared before running:** 60 s per repetition and 4 GB of estimated array storage. Failures are recorded as `timeout` or `skipped_memory_budget`, and larger n (or, in Part B, higher densities) are then not attempted for that method.
- **Memory:** (1) analytical array storage of A, B and C (dense $8n^2$ bytes each; CSR 12·nnz + 4(n+1) each); (2) peak RSS of the process (`ru_maxrss` on macOS), which includes the JVM and the heap it reserves. I compare (1) across methods and report (2) as a process-level measure with its limitation.
- **Block size:** fixed at 64 for Parts A and B; a separate sweep at n = 1024 measured bs ∈ {8, 16, 32, 64, 128, 256, 512}.

4. Results

4.1 Part A: dense optimisations

Table 2. Time per multiplication (median of 5 repetitions), IQR relative to the median, and speedup = median(baseline) / median(method). At n = 2048 the baseline's warm-up multiplication had not finished after 60 s, so only a lower bound of the speedup is given.

n	Baseline	IQR/med.	ikj	IQR/med.	Speedup	Blocked	IQR/med.	Speedup
64	0.910 ms	78 %	0.771 ms	850 %	1.2	0.444 ms	6 %	2.0
128	7.11 ms	64 %	7.18 ms	163 %	1.0	5.64 ms	22 %	1.3
256	94.0 ms	79 %	44.7 ms	42 %	2.1	32.8 ms	13 %	2.9
384	410 ms	16 %	102 ms	30 %	4.0	97.6 ms	5 %	4.2
512	1.71 s	8 %	224 ms	0.5 %	7.7	251 ms	8 %	6.8
768	3.95 s	4 %	687 ms	9 %	5.7	618 ms	4 %	6.4
1024	13.72 s	2 %	1.10 s	2 %	12.5	1.38 s	1 %	10.0
1536	47.31 s	23 %	3.43 s	6 %	13.8	3.17 s	4 %	14.9
2048	timeout	–	7.69 s	2 %	> 7.8	8.54 s	8 %	> 7.0




Figure 1. Time per multiplication against n (log–log). Points: median; bars: IQR. Dashed lines: the same kernels with auto-vectorisation disabled.




Figure 2. Speedup over the baseline. The baseline has no value at n = 2048 (timeout).




Figure 3. Time per multiply-add (median / n^3).

The baseline's cost per multiply-add rose from 3.4 ns at n = 64–128 to 12.8–13.1 ns for n ≥ 1024. The ikj and blocked kernels went the other way: from 1.7–3.4 ns at small n down to 0.9–1.3 ns for n ≥ 1024, so the speedup over the baseline grew with n, from about 1–2 at n ≤ 128 to 4 at n = 384, 6–8 at n = 512–768 and 10–15 at n = 1024–1536 (Figure 2). At n = 2048 the baseline exceeded the 60 s budget in its warm-up multiplication; at its n = 1536 cost per multiply-add it would need about 112 s. Its largest completed size was n = 1536; every optimised method completed n = 2048.

Variability. For n ≥ 768 the IQR was small (median 3.6 % of the median time, at most 25 %). For n ≤ 384 it was large (median 24 %, up to 850 %): in 15 of the 25 Part A configurations with n ≤ 512 the slowest repetition was more than 1.5 times the fastest, with isolated repetitions up to 24 times slower than the others in the same process (`raw_measurements.csv`). Speedups for n ≤ 384 in Table 2 are therefore only indicative.

Loop reordering against blocking. Blocked/ikj ratios of the medians were 1.12, 0.90, 1.25, 0.92 and 1.11 for n = 512, 768, 1024, 1536 and 2048: neither was consistently faster. To see how large a difference has to be to mean something, I compared the runs of exactly the same configuration (blocked, bs = 64) in separate JVMs, which the study already contains: Part A, the block sweep and the dense side of Part B (the inputs differ but the dense kernel does the same n^3 work on them).

Table 3. The same kernel (blocked, bs = 64) measured in separate JVMs.

n	Processes	Range of medians	Max / min	Part A run
1024	10	1.078 – 1.376 s	1.28	1.376 s (slowest)
2048	9	7.068 – 8.543 s	1.21	8.543 s (slowest)

In both cases the Part A process was the slowest of its group; the other nine (eight) were within 1.078–1.156 s (7.07–8.25 s).

Auto-vectorisation. With `-XX:-UseSuperWord`, the ratio vectorised / not vectorised was 0.98, 1.01, 0.80, 1.03 and 1.06 for ikj and 1.07, 1.02, 0.69, 0.99 and 1.14 for blocked (n = 512 … 2048). Only n = 1024 clearly favoured the vectorised code. For ikj the difference there (1.25×) is about the size of the process-to-process range in Table 3; for blocked, `blocked_novec` took 2.00 s, outside the 1.08–1.38 s range of the vectorised kernel at that size. At the other sizes the differences were within ±14 % and changed sign.

4.2 Block size

Table 4. Blocked kernel at n = 1024 with different block sizes.

bs	8	16	32	64	128	256	512
Tile memory $3 \cdot 8 \cdot bs^2$	1.5 KiB	6 KiB	24 KiB	96 KiB	384 KiB	1.5 MiB	6 MiB
Median time	2.266 s	1.291 s	1.251 s	1.134 s	1.022 s	1.189 s	1.099 s
IQR	178 ms	34 ms	12 ms	56 ms	20 ms	23 ms	39 ms




Figure 4. Effect of the block size at n = 1024 (median, IQR bars).

Only bs = 8 was clearly worse (2.27 s). From bs = 16 to 512 the medians stayed between 1.02 and 1.29 s, a 1.26× range, similar to the process-to-process range in Table 3. The fastest was bs = 128

(1.02 s), 10 % faster than the bs = 64 used in the study.

4.3 Part B: sparse vs dense

Table 5. Sparse (CSR) against dense (blocked, bs = 64) on the same inputs: medians of 5 repetitions per multiplication. “incl. conv.” adds the median COO → CSR conversion time of A and B to the sparse time. nnz B is within 2 % of nnz A in every case (`report/tables/part_b_time.md`).

n	d	nnz A	nnz C	Out. dens.	Sparse	Conversion	Dense	Dense / sparse	incl. conv.
1024	0.001	1 007	1 052	0.001	38.2 µs	195 µs	1.104 s	28 890	4 732
1024	0.005	5 210	26 500	0.025	376 µs	1.22 ms	1.104 s	2 935	694
1024	0.01	10 340	100 489	0.096	1.19 ms	1.04 ms	1.100 s	928	494
1024	0.05	52 478	966 873	0.922	45.8 ms	1.41 ms	1.080 s	23.6	22.9
1024	0.1	104 502	1 048 535	1.000	94.4 ms	1.68 ms	1.088 s	11.5	11.3
1024	0.25	262 641	1 048 576	1.000	424 ms	5.95 ms	1.156 s	2.73	2.69
1024	0.35	366 738	1 048 576	1.000	489 ms	10.3 ms	1.078 s	2.20	2.16
1024	0.5	524 860	1 048 576	1.000	1.106 s	7.45 ms	1.086 s	0.98	0.98
2048	0.001	4 226	8 646	0.002	230 µs	704 µs	7.436 s	32 315	7 959
2048	0.005	21 076	211 204	0.050	4.88 ms	827 µs	7.422 s	1 520	1 300
2048	0.01	41 889	772 611	0.184	26.7 ms	2.52 ms	7.104 s	266	243
2048	0.05	209 658	4 169 290	0.994	265 ms	4.11 ms	7.686 s	29.0	28.5
2048	0.1	419 278	4 194 304	1.000	633 ms	9.95 ms	7.068 s	11.2	11.0
2048	0.25	1 046 876	4 194 304	1.000	2.036 s	9.51 ms	7.161 s	3.52	3.50
2048	0.35	1 467 865	4 194 304	1.000	4.024 s	15.7 ms	7.182 s	1.78	1.78
2048	0.5	2 099 432	4 194 304	1.000	9.003 s	24.0 ms	8.245 s	0.92	0.91




Figure 5. Time per multiplication against input density, sparse and dense, on the same inputs (medians, log–log).

The dense time did not depend on the density (1.08–1.16 s at n = 1024; 7.07–7.69 s at n = 2048, plus 8.25 s at d = 0.5). The sparse time grew by more than four orders of magnitude between d = 0.001 and 0.5. Sparse was faster up to d = 0.35 at both sizes (by 2.20× and 1.78×) and as fast or slightly slower at d = 0.5 (0.98× and 0.92×), so the crossover lies between 35 % and 50 % density. The conversion took between 0.2 and 24 ms. It was longer than the kernel itself for d ≤ 0.005 at n = 1024 and d = 0.001 at n = 2048, and including it lowered the dense/sparse ratio by 47–84 % at n = 1024 for d ≤ 0.01 and at n = 2048 for d = 0.001, by 9–14 % at n = 2048 for d = 0.005–0.01, and by at most

3 % from d = 0.05 on. Even with the conversion, sparse stayed more than 240 times faster for d ≤ 0.01.

Table 6. Work of the sparse kernel. Products = Σ_k nnz(A[:,k]) · nnz(B[k,:]), counted exactly from the input files. Last column: the density at which sparse and dense would take the same time if the cost per operation stayed as measured at that density (all densities in `report/tables/part_b_work.md`).

n	d	Products	n^3d^2	Sparse ns / product	Dense ns / multiply-add	√(dense / sparse cost)
1024	0.01	105 569	$1.07 \cdot 10^5$	11.2	1.02	0.30
1024	0.1	10 652 662	$1.07 \cdot 10^7$	8.86	1.01	0.34
1024	0.25	67 107 547	$6.71 \cdot 10^7$	6.31	1.08	0.41
1024	0.35	131 221 905	$1.32 \cdot 10^8$	3.73	1.00	0.52
1024	0.5	268 850 250	$2.68 \cdot 10^8$	4.11	1.01	0.50
2048	0.01	854 031	$8.59 \cdot 10^5$	31.3	0.83	0.16
2048	0.1	85 867 807	$8.59 \cdot 10^7$	7.37	0.82	0.33
2048	0.25	535 923 952	$5.37 \cdot 10^8$	3.80	0.83	0.47
2048	0.35	1 052 732 442	$1.05 \cdot 10^9$	3.82	0.84	0.47
2048	0.5	2 151 013 765	$2.15 \cdot 10^9$	4.19	0.96	0.48

The exact number of products matched n^3d^2 within 1.5 % (Table 6). The sparse cost per product was not constant: it was between 11 and 36 ns for d ≤ 0.05 (without a clear trend inside that range), 7.4–8.9 ns at d = 0.1 and 3.7–4.2 ns at d ≥ 0.35. The dense cost per multiply-add stayed between 0.82 and 1.08 ns. At high density one sparse product therefore cost about 4–5 dense multiply-adds, and the density at which the two balance, √(dense cost / sparse cost), came out as 0.47–0.52 for d ≥ 0.35.




Figure 6. Fill-in: density of C against the density of A and B. Dashed: same density as the inputs.

The output density matched $1 - (1 - d^2)^n$: 0.096 and 0.184 at d = 0.01 (expected 0.097 and 0.185), 0.92 and 0.99 at d = 0.05, and 1.000 from d = 0.1 on (Figure 6).

Table 7. Memory. Array storage is analytical (dense 8 bytes per element; CSR 12 bytes per nonzero + row pointers). A dense C needs 8 MiB (n = 1024) or 32 MiB (n = 2048). Peak RSS is per process and includes the JVM. All densities in `report/tables/part_b_memory.md`.

n	d	nnz C	CSR A+B+C	of which C	Dense A+B+C	Sparse peak RSS	Dense peak RSS
1024	0.001	1 052	0.05 MiB	0.02 MiB	24.0 MiB	107.1 MiB	62.4 MiB
1024	0.01	100 489	1.4 MiB	1.2 MiB	24.0 MiB	111.8 MiB	63.2 MiB
1024	0.05	966 873	12.3 MiB	11.1 MiB	24.0 MiB	141.5 MiB	66.3 MiB
1024	0.35	1 048 576	20.4 MiB	12.0 MiB	24.0 MiB	163.7 MiB	90.4 MiB
1024	0.5	1 048 576	24.0 MiB	12.0 MiB	24.0 MiB	184.4 MiB	102.5 MiB
2048	0.001	8 646	0.2 MiB	0.1 MiB	96.0 MiB	109.2 MiB	136.3 MiB
2048	0.01	772 611	9.8 MiB	8.9 MiB	96.0 MiB	102.9 MiB	138.3 MiB
2048	0.05	4 169 290	52.5 MiB	47.7 MiB	96.0 MiB	276.4 MiB	145.8 MiB
2048	0.35	4 194 304	81.6 MiB	48.0 MiB	96.0 MiB	408.3 MiB	263.7 MiB
2048	0.5	4 194 304	96.1 MiB	48.0 MiB	96.0 MiB	523.6 MiB	312.6 MiB




Figure 7. Array storage of A, B and C in CSR (lines with markers) and dense (dashed).

In array storage, CSR was smaller than dense up to d = 0.35 and equal at d = 0.5 (Table 7). For C alone, CSR was already larger than dense from d = 0.05 (11.1 against 8 MiB at n = 1024; 47.7 against 32 MiB at n = 2048), because C was almost full and CSR needs 12 instead of 8 bytes per entry; the total stayed smaller only because A and B were small. Peak RSS did not follow the array storage: the sparse processes had a higher peak than the dense ones in every case except n = 2048 with d ≤ 0.01.

Variability and warm-up in Part B. The dense side was stable (IQR at most 9 % of the median). The sparse side was less so (IQR up to 70 %). In three configurations (n = 1024, d = 0.35 and n = 2048, d = 0.25 and 0.35) the first two measured repetitions were about 1.7 times slower than the last three (e.g. n = 2048, d = 0.35: 6.48 and 6.94 s, then 3.83, 3.83 and 4.02 s), which gives IQRs of 63–66 %; the median fell on the faster group. The other large IQRs (n = 1024, d = 0.001; n = 2048, d = 0.005 and 0.01) belong to kernels that took between 0.04 and 27 ms, where single slow repetitions weigh more.

5. Discussion

H1 – the gain grows with n (supported)

For $n \leq 128$ the optimised kernels were at most about 2 times faster than the baseline, and these numbers are noisy; from $n = 256$ the speedup grew steadily to 10–15 for $n \geq 1024$. This matches the cost per multiply-add: the baseline's grew about four times between $n = 128$ and $n \geq 1024$, as in Assignment 1, while the i-k-j kernels got cheaper with n and reached about 1 ns. The penalty of the baseline is therefore caused by its access pattern and not by the amount of arithmetic, which is the same in all three. Reading B along rows instead of down columns removed almost all of it.

H2 – blocking beats ikj at large n (not supported)

Blocking with bs = 64 was not consistently faster than plain i-k-j: it was 8–10 % faster at $n = 768$ and 1536 and 11–25 % slower at $n = 512$, 1024 and 2048. These differences are of the same size as the spread between separate runs of the same configuration (1.21–1.28×, Table 3), so this study cannot tell the two apart. The block-size sweep agrees: everything between bs = 16 and 512 fell within a similar range. My interpretation, which I did not test directly (for example with hardware counters), is that in the i-k-j order the inner loop already streams two contiguous rows (16 KiB each at $n = 2048$), which the hardware prefetcher handles well, so the remaining misses cost little on this CPU, while blocking shortens the inner loop to 64 iterations and adds loop overhead. Blocking matters more when the kernel is also register-blocked and vectorised, as in optimised libraries [4].

H3 – vectorisation explains part of the gain (not supported)

Disabling auto-vectorisation did not reduce the gain in a consistent way. At $n = 512$, 768, 1536 and 2048 the non-vectorised kernels were within ±14 % of the vectorised ones, in both directions, and they were still 7–15 times faster than the baseline. Only at $n = 1024$ did the vectorised kernels do clearly better (1.25× for ikj and 1.45× for blocked). So almost all of the gain over the baseline came from the memory-access pattern, not from SIMD code, with the single exception of $n = 1024$, which I cannot explain from these data. I did not inspect the generated machine code, so I cannot say whether C2 actually vectorised these loops in the default runs; the result only shows that the flag made no consistent difference here. At about 1 ns per multiply-add (about 2 GFLOP/s), the kernels are far from the CPU's peak, which is consistent with memory access, not arithmetic, being the limit.

H4 – sparse wins below a crossover density (partly supported)

The dense time was independent of the density and the sparse time followed the number of products, which was exactly n^3d^2. The crossover was between 35 % and 50 %, much higher than I expected. Table 6 explains why: on these inputs one sparse product cost only about 4 dense multiply-adds at high density, so sparse wins while d^2 is below about 1/4, that is d below about 0.5. The cost per product was higher at low density because the per-row work (marker checks, writing column indices, the O(n) arrays) is spread over fewer products, and this did not change the conclusion because sparse was hundreds or thousands of times faster there. The conversion to CSR is O(nnz), so it only mattered when the kernel itself took under a few milliseconds. For one multiplication of matrices that already arrive in a sparse format, the conversion is a negligible cost.

The memory part of H4 was supported: the product fills in so fast that C was 92–99 % full at 5 % input density, and from there a CSR C was 1.5 times larger than a dense one. The total CSR storage was still smaller up to 35 % only because A and B stayed sparse. In practice, the output of a random sparse product is only worth storing as sparse when nd^2 is small (here, $d \leq 0.01$). Peak RSS mostly showed how much heap the JVM had reserved: the sparse process held the COO input and the CSR copies and allocated a new C in every multiplication, so the heap grew with garbage until it was collected. A comparison of memory between methods therefore has to use the array storage, not the process RSS.

Warm-up and variability

One warm-up round of at least 100 ms was not always enough for large n: in 36 of the 58 configurations with n > 512 the first measured repetition was more than 10 % above the median, and for the sparse kernel at d = 0.25–0.35 the first two were. With 5 repetitions the median stayed on the steady state in every case, but the IQRs are inflated. Georges et al. recommend detecting steady state instead of using a fixed number of warm-up runs [11]; I will use more warm-up rounds, or steady-state detection, in Assignment 3.

The baseline was also slower than the same code in Assignment 1 on the same laptop and JVM (1.2–1.3 times at n = 1024–1536 and 2–3 times at n ≤ 768). The cause is not known: the machine state on the two days differed (the large variability at small n suggests background activity during this run), and the A2 driver calls the kernel through a dispatch object instead of directly. For this reason I compared methods only within the same run, where they were interleaved in random order and shared the same conditions.

Limitations

- One laptop and one run; absolute times and the crossover density are specific to it.
- Differences below about 1.3× between dense methods are not resolved by this design.
- The JIT decides by itself what to vectorise; the novec runs only switch off one optimisation.
- Peak RSS mostly reflects heap reserved by the JVM, not live data.
- Uniform random sparsity only; banded, block or power-law patterns change the number of products and the fill-in for the same density.
- The sparse output is not sorted by column; sorting would add cost.

6. Conclusions

- Changing only the loop order of the Assignment 1 multiplication made it 10–15 times faster for n ≥ 1024 on my laptop, and brought the cost of a multiply-add from about 13 ns to about 1 ns. With it, n = 2048 takes about 8 s, while the baseline did not finish within 60 s.
- Cache blocking on top of that did not add a measurable gain in this setting, and auto-vectorisation only made a clear difference at one size (n = 1024): the improvement came from reading memory contiguously.
- For random sparse matrices, the CSR multiplication was faster than dense multiplication of the same matrices up to 35 % density, by factors from 1.8 to more than 30 000, and equal or slightly slower at 50 %. The crossover follows from the number of products (n^3d^2) and the cost per product, about 4 times the cost of a dense multiply-add.
- The product fills in quickly (C almost full from 5 % input density), so storing C as CSR costs more than storing it dense from that point; CSR saved memory overall up to 35 % density, but only thanks to A and B.
- A good choice therefore depends on the input: for dense matrices, i-k-j order; for sparse ones, CSR while nd^2 stays small, and dense (or a dense output) once the product fills in.

Use of generative AI

I used Claude (Anthropic) to help design the experiment, to explain the techniques, to generate the first versions of the code and scripts, and to help draft this report from my results. I reviewed and ran all the code, I ran every experiment on my own laptop, and every number in this report comes from those runs (`results/run_20261026-153110/`). I checked that each reference exists and supports what I cite it for.

References

[1] J. L. Hennessy and D. A. Patterson, *Computer Architecture: A Quantitative Approach*, 6th ed. Cambridge, MA, USA: Morgan Kaufmann, 2017.

[2] U. Drepper, “What every programmer should know about memory,” Red Hat, Inc., Tech. Rep., 2007.

[3] M. D. Lam, E. E. Rothberg, and M. E. Wolf, “The cache performance and optimizations of blocked algorithms,” in *Proc. ASPLOS IV*, 1991, pp. 63–74.

[4] K. Goto and R. A. van de Geijn, “Anatomy of high-performance matrix multiplication,” *ACM Trans. Math. Softw.*, vol. 34, no. 3, Art. 12, 2008.

[5] TechPowerUp, “Intel Core i5-5350U,” CPU Database. [Online]. Available: https://www.techpowerup.com/cpu-specs/core-i5-5350u.c1812

[6] Y. Saad, *Iterative Methods for Sparse Linear Systems*, 2nd ed. Philadelphia, PA, USA: SIAM, 2003.

[7] F. G. Gustavson, “Two fast algorithms for sparse matrices: Multiplication and permuted transposition,” *ACM Trans. Math. Softw.*, vol. 4, no. 3, pp. 250–269, 1978.

[8] P. Virtanen *et al.*, “SciPy 1.0: Fundamental algorithms for scientific computing in Python,” *Nature Methods*, vol. 17, pp. 261–272, 2020.

[9] T. A. Davis, *Direct Methods for Sparse Linear Systems*. Philadelphia, PA, USA: SIAM, 2006.

[10] N. J. Higham, *Accuracy and Stability of Numerical Algorithms*, 2nd ed. Philadelphia, PA, USA: SIAM, 2002.

[11] A. Georges, D. Buytaert, and L. Eeckhout, “Statistically rigorous Java performance evaluation,” in *Proc. OOPSLA*, 2007, pp. 57–76.

Reproducibility materials. Code, raw data and analysis are in the folder `matmul-assignment2/` that accompanies this report. The study is `results/run_20261026-153110/`; `python3 scripts/analyze.py results/run_20261026-153110` regenerates every table and figure from the raw data.

GitHub repository: https://github.com/amaisuarez/assignment2