

Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

Class: S.Y.B.Tech Sem.: IV Course: IT206 Operating Systems

Name: Amal Thundiyil

UID: 2020400066

Class: IT (Batch-D)

Experiment No.: 8

Title: Deadlock

Aim: Write a multithreaded program for preventing race conditions and deadlock avoidance for the banker's algorithm as follows. Panashikar supplies sweets, snacks and Indian food traces. Customer thread will request the particular product. The shop will release and grant the product only if it leaves the system in safe state. A request that leaves the federation in an unsafe state will be denied. Take the Allocation and Available from the user. Print the Allocation, Max and Available. Find and print the Need. Find the safe sequence if any and print it and tell whether federation is in safe state or not. Take a request from a user thread and tell whether this request will be granted immediately or not.

Code:

```
import java.util.concurrent.locks.ReentrantLock;
import static java.lang.System.out;
import java.io.FileInputStream;
import java.util.*;

public class Main {
    static Scanner fs;
    static int[][] allocation, max, need;
    static List<Integer> safeSequence = new ArrayList<>();
    static HashSet<Integer> safeSet = new HashSet<>();
    static boolean safe = true;
    static int[] available, work, request;
    static int requestingThread, threads, products;
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
static volatile ReentrantLock rl;
static class ProcessExecution implements Runnable {
  int t no;
  public ProcessExecution(int t no) {
     this.t no = t no;
  }
  @Override
  public void run() {
     rl.lock();
     try {
       out.println("Acquired the lock: " + t no);
       try {
          Thread.sleep(1000);
        } catch (Exception e) {
       out.println("Current Available: ");
       for (int i = 0; i < allocation[t no].length; <math>i++) {
          work[i] += allocation[t no][i];
        }
       out.println(Arrays.toString(work));
     } finally {
       rl.unlock();
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
public static int findThreadWithMinNeed() {
  for (int i = 0; i < \text{need.length}; i++) {
     if (safeSet.contains(i)) {
        continue;
     boolean min = true;
     for (int j = 0; j < \text{need}[i].length; j++) {
       if (need[i][j] > work[j]) {
          min = false;
          break;
     if (min == true) {
        safeSet.add(i);
        safeSequence.add(i);
        return i;
  return -1;
public static void calcSafeSequence() {
  work = Arrays.copyOf(available, available.length);
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
for (int i = 0; i < \text{need.length}; i++) {
     int threadNo = findThreadWithMinNeed();
     if (threadNo == -1) {
        System.out.println("No safe sequence found!");
        safe = false;
        return;
     for (int j = 0; j < allocation[i].length; <math>j++) {
        work[j] += allocation[threadNo][j];
public static void calcNeed() {
  need = new int[allocation.length][allocation[0].length];
  for (int i = 0; i < allocation.length; <math>i++) {
     for (int j = 0; j < allocation[i].length; <math>j++) {
        need[i][j] = max[i][j] - allocation[i][j];
     }
public static boolean grantRequest() {
  if (!safe) {
     return false;
  }
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
for (int i = 0; i < available.length; <math>i++) {
     if (request[i] > available[i]
           || request[i] > need[requestingThread][i]) {
        return false;
  return true;
public static void display() {
  System.out.println("");
  System.out.println("Available: " + Arrays.toString(available));
  System.out.println("Allocation\tMax\t\tNeed");
  for (int i = 0; i < allocation.length; <math>i++) {
     for (int j = 0; j < allocation[i].length; <math>j++) {
        System.out.print(allocation[i][j] + " ");
     System.out.print("\t\t");
     for (int j = 0; j < max[i].length; j++) {
        System.out.print(max[i][j] + " ");
     }
     System.out.print("\t\t");
     for (int j = 0; j < \text{need}[i].length; j++) {
        System.out.print(need[i][j] + " ");
     }
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
System.out.println("");
  }
  if (safe) {
     System.out.println("Safe Sequence: " + safeSequence.toString());
public static void banker() throws Exception {
  safeSequence.clear();
  safeSet.clear();
  calcNeed();
  calcSafeSequence();
  display();
  Thread th[] = new Thread[threads];
  ProcessExecution processes[] = new ProcessExecution[threads];
  work = Arrays.copyOf(available, products);
  if (!safe) {
     return;
  for (int i = 0; i < threads; i++) {
     processes[i] = new ProcessExecution(safeSequence.get(i));
     th[i] = new Thread(processes[i]);
     th[i].setPriority(i + 1);
     th[i].start();
     th[i].join();
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
public static void main(String args[]) throws Exception {
  System.setIn(new FileInputStream("./input.txt"));
  fs = new Scanner(System.in);
  rl = new ReentrantLock();
  threads = fs.nextInt();
  products = fs.nextInt();
  allocation = new int[threads][products];
  for (int i = 0; i < threads; i++) {
     for (int j = 0; j < products; j++) {
       allocation[i][j] = fs.nextInt();
  }
  max = new int[threads][products];
  for (int i = 0; i < threads; i++) {
     for (int j = 0; j < products; j++) {
       max[i][j] = fs.nextInt();
     }
  }
  available = new int[products];
  for (int i = 0; i < products; i++) {
     available[i] = fs.nextInt();
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

```
}
     banker();
     System.out.println("");
     request = new int[products];
     for (int i = 0; i < products; i++) {
       request[i] = fs.nextInt();
     }
     requestingThread = fs.nextInt();
     System.out.println("Request of thread " + requestingThread + " is " +
Arrays.toString(request));
     boolean grant = grantRequest();
     if (!grant) {
       System.out.println("Request cannot be granted.");
     } else {
       System.out.println("Request granted ...");
       for (int i = 0; i < products; i++) {
          allocation[requestingThread][i] += request[i];
       for (int i = 0; i < products; i++) {
          available[i] -= request[i];
       banker();
     fs.close();
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

Class: S.Y.B.Tech Sem.: IV Course: IT206 Operating Systems

Output:

```
javac Main.java
                                                          main ±
                                                          main ±
                                                                    java Main
Available: [5, 3, 2]
Allocation
                 Max
                                    Need
0 1 0
                                    7 4 3
                                    1 2 2 6 0 0
200
3 0 2
                  9 0 2
                                    0 1 1
0 0 2
                                    4 3 1
Safe Sequence: [1, 2, 3, 0, 4]
Acquired the lock: 1
Current Available:
[7, 3, 2]
Acquired the lock: 2
Current Available:
[10, 3, 4]
Acquired the lock: 3
Current Available:
[12, 4, 5]
Acquired the lock: 0
Current Available:
[12, 5, 5]
Acquired the lock: 4
Current Available:
[12, 5, 7]
```



Bhavan's Campus, Munshi Nagar, Andheri (West), Mumbai-400058-India (Autonomous College Affiliated to University of Mumbai)

Information Technology Department

Academic Year: 2021-2022

Class: S.Y.B.Tech Sem.: IV Course: IT206 Operating Systems

```
Request of thread 1 is [1, 0, 0]
Request granted ...
                   Max
                                       Need
                                       7 4 3
0 2 2
6 0 0
                   7 5 3
0 1 0
3 0 0
                   3 2 2
9 0 2
3 0 2
                                       0 1 1
                                       4 3 1
0 0 2
Safe Sequence: [1, 2, 3, 0, 4]
Acquired the lock: 1
Current Available:
[7, 3, 2]
Acquired the lock: 2
Current Available:
[10, 3, 4]
Acquired the lock: 3
Current Available:
[12, 4, 5]
Acquiréd the lock: 0
[12, 5, 5]
Acquired the lock: 4
Current Available:
[12, 5, 7]
```

Input (from file - input.txt)

