

```
import os
import re
import time
import json
import pandas as pd
import numpy as np
from collections import Counter
from tqdm import tqdm
from openai import OpenAI
import matplotlib.pyplot as plt
```

```
# API setup
# Put your NVIDIA API key here or set it as an environment variable

os.environ["NVIDIA_API_KEY"] = ""

client = OpenAI(
    base_url="https://integrate.api.nvidia.com/v1",
    api_key=os.environ["NVIDIA_API_KEY"],
)

MODEL_NAME = "openai/gpt-oss-120b"
```

```
def get_completion(prompt, temperature=0, max_tokens=800):
    try:
        response = client.chat.completions.create(
            model=MODEL_NAME,
            messages=[
                {"role": "user", "content": prompt}
            ],
            temperature=temperature,
            max_tokens=max_tokens
        )

        content = response.choices[0].message.content

        if content is None or content.strip() == "":
            return None

        return content.strip()

    except Exception as e:
        print("Error:", e)
        return None
```

```
def run_reasoning_gene_annotation(up_genes, down_genes, max_retries=3):
    start_time = time.time()

    prompt = f"""
You are a biomedical genomics expert.

Given the following differentially expressed genes from colorectal adenoma:

Upregulated genes:
{", ".join(up_genes)}

Downregulated genes:
{", ".join(down_genes)}

Task:
Generate a structured biomedical interpretation of the gene lists.

STRICT OUTPUT FORMAT:
Return only a markdown table.
The first line must be:
| Pathway_or_Process | Direction | Supporting_Genes | Biological_Rationale | Confidence |

Do not write any text before the table.
Do not write any text after the table.
Do not explain your reasoning process.
Do not include phrases such as "We need to", "Let's propose", or "Potential processes".

Rules:
```

```

- Use only genes provided in the input lists.
- Do not add genes that were not provided.
- Do not claim statistical significance for pathways.
- Avoid broad claims unless supported by multiple genes.
- Confidence must be High, Medium, or Low.
- Return exactly 10 rows only.
"""

final_raw = None

for attempt in range(1, max_retries + 1):
    raw = get_completion(prompt, temperature=0, max_tokens=3000)

    if raw is not None and "| Pathway_or_Process |" in raw:
        table_rows = [
            line for line in raw.splitlines()
            if line.strip().startswith("|") and not line.strip().startswith("|---")
        ]

        # header + 10 rows = at least 11 table rows
        if len(table_rows) >= 11:
            final_raw = raw
            break

    print(f"Structured reasoning attempt {attempt} failed. Retrying...")

if final_raw is None:
    final_raw = "FAILED_TO_GENERATE_STRUCTURED_REASONING_TABLE"

duration = time.time() - start_time
return final_raw, duration

```

```

def run_self_consistency_gene_annotation(up_genes, down_genes, k=3, max_retries=12):
    start_time = time.time()
    outputs = []

    input_genes = set(up_genes + down_genes)
    run_number = 1
    total_attempts = 0
    max_total_attempts = k * max_retries

    while len(outputs) < k and total_attempts < max_total_attempts:
        final_raw = None

        prompt = f"""
You are a biomedical genomics expert.

Given these differentially expressed genes from colorectal adenoma:

Upregulated genes in adenoma:
{", ".join(up_genes)}

Downregulated genes in adenoma:
{", ".join(down_genes)}

Task:
Generate 8 to 10 biological themes represented by these genes.

Return ONLY numbered lines.
Do not write introduction.
Do not write explanation before or after the list.

Format:
1. Biological process name: GENE1, GENE2, GENE3
2. Biological process name: GENE1, GENE2, GENE3

Rules:
- Return at least 8 numbered lines.
- Use only genes from the provided gene lists.
- Do not invent genes.
- Each line must contain at least 2 supporting genes.
- Use specific biological names, not Pathway1 or Biological_Process_Name.
- Do not claim statistical significance.
"""

        for attempt in range(1, max_retries + 1):

```

```

total_attempts += 1

raw = get_completion(prompt, temperature=0, max_tokens=3000)

if raw is not None:
    numbered_lines = [
        line.strip()
        for line in raw.splitlines()
        if re.match(r"^\s*\d+[\.\.]", line.strip())
    ]

    valid_lines = []

    for line in numbered_lines:
        if ":" not in line:
            continue

        theme_part, genes_part = line.split(":", 1)

        genes = [
            g.strip().replace(".", "").replace(",", "")
            for g in re.split(r",|;|\s+", genes_part)
            if g.strip()
        ]

        genes_in_input = [
            g for g in genes
            if g in input_genes
        ]

        if len(genes_in_input) >= 2:
            clean_line = theme_part.strip() + ": " + ", ".join(genes_in_input)
            valid_lines.append(clean_line)

    if len(valid_lines) >= 7:
        final_raw = "\n".join(valid_lines[:10])
        break

    print(f"Self-consistency valid run {len(outputs)+1}, attempt {attempt} failed. Retrying...")

if final_raw is not None:
    outputs.append(final_raw)
    print(f"Valid self-consistency run {len(outputs)} generated successfully.")
else:
    print("One attempted run was skipped because it did not produce valid output.")

if len(outputs) < k:
    print(f"Warning: only {len(outputs)} valid self-consistency runs were generated.")

duration = time.time() - start_time
return outputs, duration

```

```

# Phase 2: Load pre-filtered Top 50 gene lists
# These files should be the SAME gene lists used for GO/KEGG enrichment.

import pandas as pd
import os

up_file = "/content/UP-50-VALIDATION.xlsx"
down_file = "/content/DOWN-50-VALIDATION.xlsx"

def load_gene_symbols(file_path):
    """
    Load gene symbols from a pre-filtered Top gene list.
    Works with .xlsx, .csv, and .txt/.tsv files.
    """
    ext = os.path.splitext(file_path)[1].lower()

    if ext in [".xlsx", ".xls"]:
        df = pd.read_excel(file_path)
    elif ext == ".csv":
        df = pd.read_csv(file_path)
    else:
        df = pd.read_csv(file_path, sep="\t")

    print(f"\nPreview of {file_path}:")
    display(df.head())

```

```

# Try to find a gene symbol column
possible_cols = ["Gene.symbol", "Gene Symbol", "gene.symbol", "gene_symbol", "Symbol", "Gene"]
gene_col = None

for col in possible_cols:
    if col in df.columns:
        gene_col = col
        break

# If no named column exists, use the second column if available, otherwise first column
if gene_col is None:
    if df.shape[1] > 1:
        gene_series = df.iloc[:, 1]
    else:
        gene_series = df.iloc[:, 0]
else:
    gene_series = df[gene_col]

genes = (
    gene_series
    .dropna()
    .astype(str)
    .str.strip()
    .tolist()
)

# Remove header-like values and duplicates
genes = [
    g for g in genes
    if g.lower() not in ["gene.symbol", "gene symbol", "symbol", "gene", "nan", ""]
]

genes = list(dict.fromkeys(genes))
return genes

top_up_genes = load_gene_symbols(up_file)
top_down_genes = load_gene_symbols(down_file)

print("Number of top upregulated genes:", len(top_up_genes))
print(top_up_genes)

print("\nNumber of top downregulated genes:", len(top_down_genes))
print(top_down_genes)

# Final LLM input
input_genes = set(top_up_genes + top_down_genes)

print("\nTotal unique input genes for LLM:", len(input_genes))

```

Preview of /content/UP-50-VALIDATION.xlsx:

	ID	Gene.symbol	Gene.title	log2(fold change)	-log10(Pvalue)
0	A_23_P100344	ORC6	origin recognition complex subunit 6	1.151	5.704
1	A_23_P100469	TXNL4B	thioredoxin like 4B	1.142	9.404
2	A_23_P100963	SPNS3	sphingolipid transporter 3 (putative)	1.470	10.030
3	A_23_P101374	CYP2S1	cytochrome P450 family 2 subfamily S member 1	1.889	10.530
4	A_23_P10194	SEZ6L2	seizure related 6 homolog like 2	1.703	8.219

Preview of /content/DOWN-50-VALIDATION.xlsx:

	ID	Gene.symbol	Gene.title	log2(fold change)	-log10(Pvalue)
0	A_23_P100263	CMIP	c-Maf inducing protein	-2.124	2.206
1	A_23_P100660	SERPINF1	serpin family F member 1	-1.653	8.689
2	A_23_P100711	PMP22	peripheral myelin protein 22	-1.917	10.815
3	A_23_P101093	COPZ2	coatomer protein complex subunit zeta 2	-1.146	6.434
4	A_23_P101407	C3	complement component 3	-2.556	5.643

Number of top upregulated genes: 50
['ORC6', 'TXNL4B', 'SPNS3', 'CYP2S1', 'SEZ6L2', 'PNO1', 'SMOX', 'RAB36', 'CTPS2', 'OVGP1', 'LARGE2', 'CDCA5', 'POC1B', 'ER01A',

Number of top downregulated genes: 50
['CMIP', 'SERPINF1', 'PMP22', 'COPZ2', 'C3', 'PTPRH', 'CXCR4', 'WNT10A', 'RMDN2', 'CFHR3', 'GBP4', 'GPR161', 'MAN1C1', 'A1CF',

Total unique input genes for LLM: 100

```
from pathlib import Path
import re

def extract_dataset_name(file_path, prefix):
    """
    Extract dataset name from file name.

    Examples:
    UP-50-VALIDATION.xlsx -> VALIDATION
    DOWN-50-VALIDATION.xlsx -> VALIDATION
    UP_50_GSE8671.xlsx -> GSE8671
    """

    file_name = Path(file_path).stem # remove extension

    pattern = rf"(?i)^(prefix)[-_]50[-_](.+)$"
    match = re.search(pattern, file_name)

    if not match:
        raise ValueError(
            f"File name '{file_name}' does not follow the required format.\n"
            f"Expected format: {prefix}-50-DATASETNAME.xlsx or {prefix}_50-DATASETNAME.xlsx"
        )

    dataset_name = match.group(1).strip()

    if dataset_name == "":
        raise ValueError(f"No dataset name found in file: {file_name}")

    return dataset_name

# Extract dataset names
up_dataset_name = extract_dataset_name(up_file, "UP")
down_dataset_name = extract_dataset_name(down_file, "DOWN")

# Check if both belong to same dataset
if up_dataset_name != down_dataset_name:
    raise ValueError(
        "UP and DOWN files do not belong to the same dataset!\n"
        f"UP dataset : {up_dataset_name}\n"
        f"DOWN dataset : {down_dataset_name}"
    )
```

```
# Final dataset name
DATASET_NAME = up_dataset_name
SAFE_DATASET_NAME = DATASET_NAME.lower()

print("Detected dataset name:", DATASET_NAME)
print("Safe dataset name:", SAFE_DATASET_NAME)
print("UP and DOWN files match correctly.")
```

```
Detected dataset name: VALIDATION
Safe dataset name: validation
UP and DOWN files match correctly.
```

```
def run_gene_annotation_verification(up_genes, down_genes, annotation_output):
    start_time = time.time()

    prompt = f"""
You are a strict biomedical verification assistant.

Input gene lists:

Upregulated genes:
{", ".join(up_genes)}

Downregulated genes:
{", ".join(down_genes)}

Proposed LLM annotation:
{annotation_output}

Task:
Verify each pathway/process in the proposed annotation.

Return ONLY a markdown table.
Do not write any text before or after the table.

The table must have exactly these columns:
Pathway_or_Process | Verification_Status | Problem_Found | Corrected_Comment

Verification_Status must be one of:
Supported, Partially Supported, Unsupported

Rules:
- Check whether the supporting genes are present in the input lists.
- Check whether the gene-pathway relationship is biologically plausible.
- Mark broad or weakly supported claims as Partially Supported.
- Mark unsupported or invented claims as Unsupported.
- Do not add new pathways.
"""

    raw = get_completion(prompt, temperature=0, max_tokens=1800)
    duration = time.time() - start_time

    return raw, duration
```

```
pd.DataFrame({"Gene.symbol": top_up_genes}).to_csv(
    f"input_{SAFE_DATASET_NAME}_top50_upregulated_genes.csv",
    index=False
)

pd.DataFrame({"Gene.symbol": top_down_genes}).to_csv(
    f"input_{SAFE_DATASET_NAME}_top50_downregulated_genes.csv",
    index=False
)

print("Saved input Top 50 gene lists for:", DATASET_NAME)
```

```
Saved input Top 50 gene lists for: VALIDATION
```

```
reasoning_output, reasoning_time = run_reasoning_gene_annotation(top_up_genes, top_down_genes)

print("Running time:", round(reasoning_time, 2), "seconds")
print(reasoning_output)
```

```
Running time: 18.0 seconds
| Pathway_or_Process | Direction | Supporting_Genes | Biological_Rationale | Confidence |
|-----|-----|-----|-----|-----|
```

Cell Cycle Progression | Up | CCNB1, BUB1, CENPH, CEP55, CDCA5, ORC6, TK1, GINS2, KIAA0101, BIRC5 | Multiple cyclins, checkpoint
 DNA Replication & Nucleotide Synthesis | Up | ORC6, TK1, DTYMK, CTPS2, GINS2, KIAA0101 | Genes encoding origin recognition, th
 Anti-apoptotic / Survival Signaling | Up | BIRC5, MDK, PTP4A3, ANXA3, AGT | Survivin (BIRC5) blocks caspase activation; midkin
 Polyamine & Oxidative Metabolism | Up | SMOX, SRD5A3, CYP2S1 | SMOX drives polyamine catabolism producing H₂O₂; SRD5A3 partici
 Wnt/Hedgehog Signaling Suppression | Down | WNT10A, GLI1, FRZB, LRIG1, DUSP1 | Down-regulation of the Wnt ligand (WNT10A), Hed
 Immune & Complement Pathway Downregulation | Down | C3, CSF1R, CXCR4, VWF, SERPINF1 | Reduced expression of complement compone
 Extracellular Matrix Remodeling (Down) | Down | ITIH5, PDLIM3, LYNX1, GPR34 | Lower levels of ITIH5 (matrix stabilizer), PDLIM
 Angiogenesis Inhibition (Down) | Down | SERPINF1, VWF, C3 | SERPINF1 (PEDF) and VWF are anti-angiogenic factors; their reduced
 Metabolic Transport & Detoxification (Up) | Up | CYP2S1, AQP3, SRD5A3, AGT | Up-regulated cytochrome P450 (CYP2S1), water chan
 Stem/Progenitor Cell Marker Downregulation | Down | LRIG1, KIT, GLI1, FOXF2 | Decreased expression of LRIG1 (stem-cell regulat

```
sc_outputs, sc_time = run_self_consistency_gene_annotation(top_up_genes, top_down_genes, k=3)
```

```
print("Running time:", round(sc_time, 2), "seconds")
```

```
for i, output in enumerate(sc_outputs, 1):
    print(f"\n--- Run {i} ---")
    print(output)
```

Valid self-consistency run 1 generated successfully.
 Valid self-consistency run 2 generated successfully.
 Valid self-consistency run 3 generated successfully.
 Running time: 22.88 seconds

--- Run 1 ---

1. DNA replication initiation and S-phase synthesis: ORC6, GINS2, TK1, CTPS2
2. Mitotic spindle assembly and cytokinesis: CCNB1, BUB1, CEP55, CENPH, CDCA5
3. Cell survival and apoptosis inhibition: BIRC5, ANXA3, PTP4A3, ZNF485
4. Growth factor-driven proliferative signaling: MDK, INHBA, AGT, PTP4A3
5. Metabolic reprogramming and oxidative stress response: SMOX, CYP2S1, SRD5A3, AQP3
6. Extracellular matrix remodeling and cell-adhesion modulation: LARGE2, ZG16B, ANXA3, PTP4A3
7. Downregulation of Wnt/Hedgehog developmental pathways: WNT10A, GLI1, FRZB, KIT
8. Suppression of immune and inflammatory signaling: C3, CSF1R, DUSP1, CXCR4
9. Ion transport and membrane permeability alterations: AQP3, S100A11, SRD5A3

--- Run 2 ---

1. DNA replication and origin licensing: ORC6, GINS2, CTPS2, TK1
2. Cell cycle progression and mitosis: CCNB1, BUB1, CEP55, KIAA0101
3. Inhibition of apoptosis and promotion of cell survival: BIRC5, MDK, PTP4A3, ANXA3
4. Metabolic reprogramming and oxidative stress handling: CYP2S1, SMOX, AQP3, SRD5A3
5. Extracellular matrix remodeling and mucosal barrier alteration: ZG16B, LARGE2, OVGP1, ANXA3
6. Downregulation of Wnt/Hedgehog signaling pathways: WNT10A, GLI1, FRZB, LRIG1
7. Suppressed immune and inflammatory responses: C3, CXCR4, CSF1R, SERPINF1
8. Reduced growth factor and receptor tyrosine kinase signaling: KIT, FGF9, GPR161, PTPRH
9. Enhanced ribosome biogenesis and protein synthesis: NOB1, MRPS23, TSR1, GTF2IRD1

--- Run 3 ---

1. Cell cycle progression and mitosis: CCNB1, BUB1, CEP55, CDCA5, GINS2, ORC6, TK1
2. DNA replication and nucleotide biosynthesis: ORC6, CTPS2, TK1, DTYMK, GINS2, MRPS23
3. Inhibition of apoptosis and pro-survival signaling: BIRC5, MDK, PTP4A3, ANXA3, PARP8
4. Extracellular matrix remodeling and cell adhesion: ANXA3, AQP3, PTP4A3, ZG16B, LARGE2
5. Metabolic reprogramming and oxidative stress response: SMOX, CYP2S1, SRD5A3, S100A11, AGT
6. Chromatin organization and transcription regulation: GTF2IRD1, ZNF485, NOB1, SRSF6, BFSP1
7. Attenuation of Wnt/ β -catenin signaling: WNT10A, FRZB, LRIG1, GLI1, CXCR4
8. Immune and inflammatory response modulation: C3, CSF1R, DUSP1, GBP4, FGF9
9. Angiogenesis and vascular function: VWF, KIT, CSF1R, CXCR4

```
results = {
    "dataset": DATASET_NAME,
    "input_summary": {
        "top_upregulated_genes": len(top_up_genes),
        "top_downregulated_genes": len(top_down_genes),
        "total_input_genes": len(top_up_genes) + len(top_down_genes),
        "total_unique_input_genes": len(set(top_up_genes + top_down_genes))
    },
    "top_up_genes": top_up_genes,
    "top_down_genes": top_down_genes,
    "reasoning_output": reasoning_output,
    "reasoning_time": reasoning_time,
    "self_consistency_outputs": sc_outputs,
    "self_consistency_time": sc_time,
}
```

```
json_filename = f"llm_gene_reasoning_outputs_{SAFE_DATASET_NAME}_top50.json"
```

```
with open(json_filename, "w", encoding="utf-8") as f:
    json.dump(results, f, ensure_ascii=False, indent=4)

print("Saved JSON file:", json_filename)
```

Saved JSON file: llm_gene_reasoning_outputs_validation_top50.json

```
with open(json_filename, "r", encoding="utf-8") as f:
    saved_results = json.load(f)
```

```
print("Dataset:", saved_results["dataset"])
print(saved_results["reasoning_output"])
```

```
Dataset: VALIDATION
| Pathway_or_Process | Direction | Supporting_Genes | Biological_Rationale | Confidence |
|-----|-----|-----|-----|-----|
| Cell Cycle Progression | Up | CCNB1, BUB1, CENPH, CEP55, CDCA5, ORC6, TK1, GINS2, KIAA0101, BIRC5 | Multiple cyclins, checkpoi
| DNA Replication & Nucleotide Synthesis | Up | ORC6, TK1, DTYMK, CTPS2, GINS2, KIAA0101 | Genes encoding origin recognition, th
| Anti-apoptotic / Survival Signaling | Up | BIRC5, MDK, PTP4A3, ANXA3, AGT | Survivin (BIRC5) blocks caspase activation; midkin
| Polyamine & Oxidative Metabolism | Up | SMOX, SRD5A3, CYP2S1 | SMOX drives polyamine catabolism producing H2O2; SRD5A3 partici
| Wnt/Hedgehog Signaling Suppression | Down | WNT10A, GLI1, FRZB, LRIG1, DUSP1 | Down-regulation of the Wnt ligand (WNT10A), Hed
| Immune & Complement Pathway Downregulation | Down | C3, CSF1R, CXCR4, VWF, SERPINF1 | Reduced expression of complement compone
| Extracellular Matrix Remodeling (Down) | Down | ITIH5, PDLIM3, LYNX1, GPR34 | Lower levels of ITIH5 (matrix stabilizer), PDLIM
| Angiogenesis Inhibition (Down) | Down | SERPINF1, VWF, C3 | SERPINF1 (PEDF) and VWF are anti-angiogenic factors; their reduced
| Metabolic Transport & Detoxification (Up) | Up | CYP2S1, AQP3, SRD5A3, AGT | Up-regulated cytochrome P450 (CYP2S1), water chan
| Stem/Progenitor Cell Marker Downregulation | Down | LRIG1, KIT, GLI1, FOXF2 | Decreased expression of LRIG1 (stem-cell regulat
```

```
def run_direct_gene_annotation(up_genes, down_genes):
    start_time = time.time()

    prompt = f"""
You are a biomedical genomics expert.

You will receive two gene lists from differential expression analysis comparing
normal colorectal mucosa and colorectal adenoma.

Upregulated genes in adenoma:
{", ".join(up_genes)}

Downregulated genes in adenoma:
{", ".join(down_genes)}

Task:
Identify the main biological pathways or processes represented by these genes.

Return ONLY a markdown table.
Do not write explanations before or after the table.
Do not write your reasoning process.

The table must have exactly these columns:
Pathway_or_Process | Direction | Supporting_Genes | Explanation | Confidence

Rules:
- Use only genes from the provided lists.
- Do not invent genes.
- Do not claim causality.
- Do not claim statistical significance for pathways.
- Keep each explanation one sentence only.
- Confidence must be High, Medium, or Low.
- Return exactly 10 rows only.
"""

    raw = get_completion(prompt, temperature=0, max_tokens=3000)
    duration = time.time() - start_time

    return raw, duration
```

Phase 6: Additional Evaluation Metrics

✦ Phase 6.2: Hallucinated Gene Check

```
direct_output, direct_time = run_direct_gene_annotation(top_up_genes, top_down_genes)

print("Direct annotation running time:", round(direct_time, 2), "seconds")
print(direct_output)
```


Direct annotation running time: 16.92 seconds

Pathway_or_Process	Direction	Supporting_Genes
Cell Cycle Progression	Up	CCNB1, BUB1, CEP55, CDCA5, KIAA0101, CENPH, BIRC5, TK1, DTYMK, GINS2, ORC
DNA Replication & Nucleotide Metabolism	Up	ORC6, TK1, DTYMK, CTPS2, MRPS23, NOB1, TSR1, GINS2
Polyamine & Steroid Metabolism	Up	SMOX, SRD5A3, CYP2S1
Growth Factor & Proliferative Signaling	Up	MDK, INHBA, AGT, PTP4A3, AQP3
Calcium-Binding & Stress Response	Up	S100A11, ANXA3, BFSP1, ZG16B
Wnt/Hedgehog Signaling Suppression	Down	WNT10A, GLI1, FRZB, LRIG1, KIT
Immune & Inflammatory Mediators	Down	C3, SERPINF1, VWF, CSF1R, CXCR4, GBP4
Lipid Metabolism & Transport	Down	OSBPL1A, OSBPL6, PIP4K2A, GPR161, GPR34
Extracellular Matrix & Cell Adhesion	Down	ITIH5, PMP22, SERPINF1, PDLIM3
Protein Folding & Stress Chaperones	Down	DNAJB5, FKBP5, DUSP1

```
# Phase 6.3: Method Comparison Table with Runtime

method_comparison_df = pd.DataFrame([
    {
        "Method": "Direct Gene Annotation",
        "Output_Type": "Biological themes table",
        "Reasoning_Component": "Low",
        "Verification_Used": "No",
        "Runtime_seconds": round(direct_time, 2) if "direct_time" in globals() else "Not recorded",
        "Main_Strength": "Fast baseline interpretation"
    },
    {
        "Method": "Structured Reasoning Annotation",
        "Output_Type": "Themes with supporting genes, rationale, and confidence",
        "Reasoning_Component": "High",
        "Verification_Used": "No",
        "Runtime_seconds": round(reasoning_time, 2) if "reasoning_time" in globals() else "Not recorded",
        "Main_Strength": "Provides interpretable biological rationale"
    },
    {
        "Method": "Self-Consistency",
        "Output_Type": "Repeated candidate biological themes",
        "Reasoning_Component": "Medium",
        "Verification_Used": "Partial",
        "Runtime_seconds": round(sc_time, 2) if "sc_time" in globals() else "Not recorded",
        "Main_Strength": "Tests stability of repeated LLM outputs"
    },
    {
        "Method": "Verification-Enhanced Reasoning",
        "Output_Type": "Verification status for each LLM theme",
        "Reasoning_Component": "High",
        "Verification_Used": "Yes",
        "Runtime_seconds": round(verification_time, 2) if "verification_time" in globals() else "Not recorded",
        "Main_Strength": "Checks gene presence and biological plausibility"
    }
])

method_comparison_df
```

	Method	Output_Type	Reasoning_Component	Verification_Used	Runtime_seconds	Main_Strength
0	Direct Gene Annotation	Biological themes table	Low	No	16.92	Fast baseline interpretation
1	Structured Reasoning Annotation	Themes with supporting genes, rationale, and c...	High	No	18.0	Provides interpretable biological rationale
		Repeated candidate				Tests stability of repeated

Next steps:

[Generate code with method_comparison_df](#)

[New interactive sheet](#)

Phase 6.4: Best-of-K Reasoning Selection

```
# Phase 6.4: API-Based Best-of-K Reasoning Selection

import json
import re
import time
import pandas as pd
```

```

def parse_json_output(raw_output):
    """
    Extract JSON list from LLM output.
    If JSON parsing fails, try to parse Theme/Supporting genes text format.
    """
    if raw_output is None:
        return None

    cleaned = raw_output.strip()

    # Remove markdown fences if present
    cleaned = cleaned.replace("```json", "").replace("```", "").strip()

    # Try to extract valid JSON array
    start = cleaned.find("[")
    end = cleaned.rfind("]")

    if start != -1 and end != -1 and end > start:
        json_part = cleaned[start:end+1]
        try:
            parsed = json.loads(json_part)
            if isinstance(parsed, list):
                return parsed
        except Exception:
            pass

    # Fallback parser if model returns text like:
    # Theme 1: "...
    # Supporting genes: GENE1, GENE2
    fallback_items = []

    theme_pattern = r'Theme\s*\d+\s*:\s*"?(^"\n)+"?'
    themes = re.findall(theme_pattern, cleaned, flags=re.IGNORECASE)

    gene_pattern = r'Supporting genes\s*:\s*([A-Za-z0-9_,\-\s]+)'
    gene_groups = re.findall(gene_pattern, cleaned, flags=re.IGNORECASE)

    if themes:
        for i, theme in enumerate(themes[:10]):
            genes = []
            if i < len(gene_groups):
                genes = [
                    g.strip()
                    for g in re.split(r",|\s+", gene_groups[i])
                    if g.strip() and len(g.strip()) > 1
                ]

                fallback_items.append({
                    "theme": theme.strip(),
                    "direction": "Mixed",
                    "supporting_genes": genes[:5]
                })

        if fallback_items:
            return fallback_items

    print("Parsing failed. Raw output:")
    print(raw_output)
    return None

def generate_candidate_gene_themes(up_genes, down_genes, candidate_id):
    """
    Generate one candidate set of biological themes using the LLM.
    """
    prompt = f"""
    You are a biomedical genomics expert.

    Given these differentially expressed genes from colorectal adenoma:

    Upregulated genes in adenoma:
    {", ".join(up_genes)}

    Downregulated genes in adenoma:
    {", ".join(down_genes)}

    Task:
    """

```

Generate exactly 10 biological themes represented by these genes.

Return valid JSON only.

Do not write any text before or after the JSON.

Do not use markdown fences.

JSON format:

```
[
  {
    "theme": "theme name",
    "direction": "Upregulated",
    "supporting_genes": ["GENE1", "GENE2", "GENE3"]
  }
]
```

Rules:

- Return exactly 10 objects.
- Use only genes from the provided gene lists.
- Do not invent genes.
- Each theme must use 2 to 5 supporting genes only.
- Theme names must be specific and biologically informative.
- Direction must be one of: Upregulated, Downregulated, Mixed.

```
"""
    start_time = time.time()
    raw = get_completion(prompt, temperature=0, max_tokens=3000)
    runtime = time.time() - start_time

    parsed = parse_json_output(raw)

    return {
        "candidate_id": candidate_id,
        "raw_output": raw,
        "parsed_output": parsed,
        "runtime_seconds": runtime
    }
"""
```

```
def classify_theme_against_go_kegg(theme):
```

```
    """
```

```
    Simple rule-based mapping based on the final GO/KEGG comparison matrix.
```

```
    """
```

```
    theme_lower = theme.lower()
```

```
    if "wnt" in theme_lower or "β-catenin" in theme_lower or "beta-catenin" in theme_lower:
        return "Partial"
```

```
    if (
        "adhesion" in theme_lower or
        "emt" in theme_lower or
        "junction" in theme_lower or
        "ecm" in theme_lower or
        "remodeling" in theme_lower or
        "invasion" in theme_lower
    ):
        return "Match"
```

```
    if (
        "cell cycle" in theme_lower or
        "cell-cycle" in theme_lower or
        "proliferation" in theme_lower or
        "mitotic" in theme_lower
    ):
        return "Match"
```

```
    if (
        "metabolic" in theme_lower or
        "metabolism" in theme_lower or
        "glycolysis" in theme_lower or
        "fructose" in theme_lower or
        "amino acid" in theme_lower
    ):
        return "Partial"
```

```
    if (
        "barrier" in theme_lower or
        "transport" in theme_lower or
        "epithelial" in theme_lower or

```

```

        "ion" in theme_lower
    ):
        return "Partial"

    return "Unsupported"

def calculate_candidate_metrics(candidate, input_genes):
    """
    Calculate descriptive candidate metrics without converting
    Match/Partial/Unsupported into 2/1/0 scores.
    """
    parsed = candidate["parsed_output"]

    if parsed is None:
        return {
            "Candidate": candidate["candidate_id"],
            "Number_of_Themes": 0,
            "Match_Count": 0,
            "Partial_Count": 0,
            "Unsupported_Count": 0,
            "Match_Rate_%": 0,
            "Partial_or_Match_Rate_%": 0,
            "Unsupported_Rate_%": 100,
            "Hallucination_Rate_%": 100,
            "Runtime_seconds": round(candidate["runtime_seconds"], 2),
            "Themes": "Parsing failed"
        }

    statuses = []
    all_used_genes = []
    themes = []

    for item in parsed:
        theme = item.get("theme", "")
        genes = item.get("supporting_genes", [])

        if isinstance(genes, str):
            genes = [g.strip() for g in genes.split(",")]

        themes.append(theme)
        all_used_genes.extend(genes)

        status = classify_theme_against_go_kegg(theme)
        statuses.append(status)

    total_themes = len(themes)

    match_count = statuses.count("Match")
    partial_count = statuses.count("Partial")
    unsupported_count = statuses.count("Unsupported")

    hallucinated_genes = [
        gene for gene in all_used_genes
        if gene not in input_genes
    ]

    hallucination_rate = (
        len(hallucinated_genes) / len(all_used_genes) * 100
    ) if all_used_genes else 100

    return {
        "Candidate": candidate["candidate_id"],
        "Number_of_Themes": total_themes,
        "Match_Count": match_count,
        "Partial_Count": partial_count,
        "Unsupported_Count": unsupported_count,
        "Match_Rate_%": round(match_count / total_themes * 100, 2) if total_themes else 0,
        "Partial_or_Match_Rate_%": round((match_count + partial_count) / total_themes * 100, 2) if total_themes else 0,
        "Unsupported_Rate_%": round(unsupported_count / total_themes * 100, 2) if total_themes else 100,
        "Hallucination_Rate_%": round(hallucination_rate, 2),
        "Runtime_seconds": round(candidate["runtime_seconds"], 2),
        "Themes": "; ".join(themes)
    }

# Run API-based Best-of-K safely

```

```

# Only valid parsed candidates are allowed to enter the final selection

K = 3
max_retries = 5
input_genes = set(top_up_genes + top_down_genes)

api_candidates = []
failed_candidates = []

for i in range(1, K + 1):
    candidate_id = f"Candidate_{i}"
    print(f"Generating {candidate_id}...")

    valid_candidate = None

    for attempt in range(1, max_retries + 1):
        candidate = generate_candidate_gene_themes(
            top_up_genes,
            top_down_genes,
            candidate_id=candidate_id
        )

        parsed = candidate.get("parsed_output")

        if parsed is not None and isinstance(parsed, list) and len(parsed) == 10:
            valid_candidate = candidate
            print(f"{candidate_id} parsed successfully on attempt {attempt}.")
            break

        print(f"{candidate_id} parsing failed on attempt {attempt}. Retrying...")

    if valid_candidate is not None:
        api_candidates.append(valid_candidate)
    else:
        failed_candidates.append(candidate_id)
        print(f"{candidate_id} was skipped because it did not produce valid parsed output.")

if len(api_candidates) == 0:
    raise RuntimeError(
        "No valid Best-of-K candidates were generated. Re-run this cell or increase max_retries."
    )

# Descriptive candidate comparison without 2/1/0 scoring
api_best_of_k_results = []

for candidate in api_candidates:
    result = calculate_candidate_metrics(candidate, input_genes)
    api_best_of_k_results.append(result)

api_best_of_k_df = pd.DataFrame(api_best_of_k_results)

best_api_candidate = api_best_of_k_df.sort_values(
    by=[
        "Hallucination_Rate_%",
        "Unsupported_Count",
        "Match_Count",
        "Partial_or_Match_Rate_%",
    ],
    ascending=[True, True, False, False]
).iloc[0]

selected_candidate_id = best_api_candidate["Candidate"]

selected_candidate = None
for candidate in api_candidates:
    if candidate["candidate_id"] == selected_candidate_id:
        selected_candidate = candidate
        break

if selected_candidate is None:
    raise ValueError("Selected candidate was not found among valid api_candidates.")

selected_parsed_output = selected_candidate["parsed_output"]

if selected_parsed_output is None:
    raise ValueError("Selected candidate still has no parsed output.")

```

```
print("API Best-of-K selected output:", selected_candidate_id)
print("Selection rule: lowest hallucination, lowest unsupported count, highest match count.")

if failed_candidates:
    print("Skipped failed candidates:", failed_candidates)

display(api_best_of_k_df)
```

```
Generating Candidate_1...
Candidate_1 parsed successfully on attempt 1.
Generating Candidate_2...
Candidate_2 parsed successfully on attempt 1.
Generating Candidate_3...
Candidate_3 parsed successfully on attempt 1.
API Best-of-K selected output: Candidate_3
Selection rule: lowest hallucination, lowest unsupported count, highest match count.
```

	Candidate	Number_of_Themes	Match_Count	Partial_Count	Unsupported_Count	Match_Rate_%	Partial_or_Match_Rate_%	Unsupport
0	Candidate_1	10	1	4	5	10.0		50.0

Next steps: [Generate code with api_best_of_k_df](#) [New interactive sheet](#)

```
# Phase 6.4b: Automatic Hallucination Check from selected API Best-of-K candidate
```

```
import re
import pandas as pd

# Get selected candidate ID from best-of-k result
selected_candidate_id = best_api_candidate["Candidate"]

# Find the selected candidate object inside api_candidates
selected_candidate = None

for candidate in api_candidates:
    if candidate["candidate_id"] == selected_candidate_id:
        selected_candidate = candidate
        break

if selected_candidate is None:
    raise ValueError("Selected candidate was not found in api_candidates.")

selected_parsed_output = selected_candidate["parsed_output"]

if selected_parsed_output is None:
    raise ValueError("Selected candidate has no parsed output.")

# Build llm_theme_genes automatically from selected candidate
llm_theme_genes = {}

for item in selected_parsed_output:
    theme = str(item.get("theme", "")).strip()
    genes = item.get("supporting_genes", [])

    # If genes came as one string, split them
    if isinstance(genes, str):
        genes = re.split(r",|\s+", genes)

    # Clean gene names
    cleaned_genes = []
    for gene in genes:
        gene = str(gene).strip()
        gene = gene.replace("[", "").replace("]", "")
        gene = gene.replace("'", "").replace('"', "")
        gene = gene.strip()

        if gene:
            cleaned_genes.append(gene)

    llm_theme_genes[theme] = cleaned_genes

print("Selected Candidate:", selected_candidate_id)

print("\nAutomatically extracted LLM theme genes:")
```

```

display(pd.DataFrame([
    {
        "LLM_Theme": theme,
        "Supporting_Genes": ", ".join(genes)
    }
    for theme, genes in llm_theme_genes.items()
]))

# Hallucination check
input_genes = set(top_up_genes + top_down_genes)

hallucination_results = []

for theme, genes in llm_theme_genes.items():
    hallucinated_genes = [gene for gene in genes if gene not in input_genes]
    hallucination_rate = len(hallucinated_genes) / len(genes) * 100 if genes else 0

    hallucination_results.append({
        "LLM_Theme": theme,
        "Total_Genes_Used": len(genes),
        "Hallucinated_Genes": hallucinated_genes if hallucinated_genes else "None",
        "Hallucination_Rate_%": round(hallucination_rate, 2)
    })

hallucination_df = pd.DataFrame(hallucination_results)

overall_genes_used = sum(len(genes) for genes in llm_theme_genes.values())

overall_hallucinated = sum(
    len([gene for gene in genes if gene not in input_genes])
    for genes in llm_theme_genes.values()
)

overall_hallucination_rate = (
    overall_hallucinated / overall_genes_used * 100
) if overall_genes_used else 0

print("\nOverall Hallucination Rate:", round(overall_hallucination_rate, 2), "%")

display(hallucination_df)

```

Selected Candidate: Candidate_3

Automatically extracted LLM theme genes:

	LLM_Theme	Supporting_Genes	
0	Cell cycle and mitotic progression	CCNB1, BIRC5, CEP55, KIAA0101, TK1	
1	DNA replication licensing and origin firing	ORC6, GINS2, NOB1	
2	Metabolic reprogramming and oxidative stress	CYP2S1, SMOX, SRD5A3, ANXA3	
3	Growth factor signaling and angiogenesis	MDK, PTP4A3, AGT, AQP3	
4	Suppression of Wnt/Hedgehog and stemness pathways	WNT10A, GLI1, LRIG1, FRZB	
5	Downregulation of immune and inflammatory medi...	C3, CSF1R, CXCR4, SERPINF1	
6	Loss of extracellular matrix and adhesion prot...	ITIH5, VWF, PDLIM3, KIT	
7	Downregulation of tumor suppressor and differe...	FOXF2, DUSP1, GPR161, PRNP	
8	Mixed transcriptional regulation alterations	GTF2IRD1, ZNF485, GPR161, FOXF2	
9	DNA damage response and repair activation	PARP8, BUB1, DTYMK	

Overall Hallucination Rate: 0.0 %

	LLM_Theme	Total_Genes_Used	Hallucinated_Genes	Hallucination_Rate_%	
0	Cell cycle and mitotic progression	5	None	0.0	
1	DNA replication licensing and origin firing	3	None	0.0	
2	Metabolic reprogramming and oxidative stress	4	None	0.0	
3	Growth factor signaling and angiogenesis	4	None	0.0	
4	Suppression of Wnt/Hedgehog and stemness pathways	4	None	0.0	
5	Downregulation of immune and inflammatory medi...	4	None	0.0	
6	Loss of extracellular matrix and adhesion prot...	4	None	0.0	
7	Downregulation of tumor suppressor and differe...	4	None	0.0	
8	Mixed transcriptional regulation alterations	4	None	0.0	
9	DNA damage response and repair activation	3	None	0.0	

Next steps: [Generate code with hallucination_df](#) [New interactive sheet](#)

```
# Phase 6.4c: REAL GO/KEGG Agreement Scoring using enrichment files

import pandas as pd
import numpy as np
import re
import os

# Automatically build GO/KEGG filenames from DATASET_NAME
GO_UP_FILE = f"/content/GO-up-{DATASET_NAME}.txt"
GO_DOWN_FILE = f"/content/GO-down-{DATASET_NAME}.txt"
KEGG_UP_FILE = f"/content/KEGG-up-{DATASET_NAME}.txt"
KEGG_DOWN_FILE = f"/content/KEGG-down-{DATASET_NAME}.txt"

def find_column(df, possible_names):
    for name in possible_names:
        if name in df.columns:
            return name
    return None

def parse_genes(value):
    if pd.isna(value):
        return []
    value = str(value)
    genes = re.split(r"[;,\s]+", value)
    genes = [g.strip() for g in genes if g.strip()]
    return genes

def load_enrichment_file(file_path, source_name, direction):
```



```

df = pd.read_csv(file_path, sep="\t")

term_col = find_column(df, ["Term", "Description", "Pathway", "Name"])
genes_col = find_column(df, ["Genes", "genes", "Gene.symbol", "geneID", "gene"])
adj_col = find_column(df, ["Adjusted P-value", "Adjusted.P.Value", "adj.P.Val", "FDR", "qvalue"])

if term_col is None:
    raise ValueError(f"No term column found in {file_path}")
if genes_col is None:
    raise ValueError(f"No genes column found in {file_path}")
if adj_col is None:
    raise ValueError(f"No adjusted p-value column found in {file_path}")

out = df.copy()
out["Source"] = source_name
out["Enrichment_Direction"] = direction
out["Term_Text"] = out[term_col].astype(str)
out["Enrichment_Genes_List"] = out[genes_col].apply(parse_genes)
out["Adjusted_P_value"] = pd.to_numeric(out[adj_col], errors="coerce")

return out

# Load real GO/KEGG files
go_up = load_enrichment_file(GO_UP_FILE, "GO Upregulated", "Upregulated")
go_down = load_enrichment_file(GO_DOWN_FILE, "GO Downregulated", "Downregulated")
kegg_up = load_enrichment_file(KEGG_UP_FILE, "KEGG Upregulated", "Upregulated")
kegg_down = load_enrichment_file(KEGG_DOWN_FILE, "KEGG Downregulated", "Downregulated")

all_enrichment_real = pd.concat(
    [go_up, go_down, kegg_up, kegg_down],
    ignore_index=True
)

def tokenize_text(text):
    text = str(text).lower()
    tokens = re.findall(r"[a-zA-Z0-9]+", text)

    stopwords = {
        "and", "or", "of", "in", "to", "the", "a", "an",
        "process", "pathway", "signaling", "regulation",
        "positive", "negative", "response"
    }

    return set([t for t in tokens if t not in stopwords and len(t) > 2])

def expand_theme_keywords(theme):
    tokens = tokenize_text(theme)
    expanded = set(tokens)

    theme_lower = str(theme).lower()

    if "cell cycle" in theme_lower or "mitotic" in theme_lower or "proliferation" in theme_lower:
        expanded.update(["cell", "cycle", "mitotic", "mitosis", "division", "proliferation"])

    if "dna" in theme_lower or "replication" in theme_lower:
        expanded.update(["dna", "replication", "nucleotide", "synthesis"])

    if "apoptosis" in theme_lower or "survival" in theme_lower:
        expanded.update(["apoptosis", "apoptotic", "survival", "death"])

    if "immune" in theme_lower or "inflammatory" in theme_lower or "inflammation" in theme_lower:
        expanded.update(["immune", "inflammatory", "inflammation", "cytokine", "leukocyte", "chemokine"])

    if "extracellular matrix" in theme_lower or "ecm" in theme_lower or "adhesion" in theme_lower or "invasion" in theme_lower:
        expanded.update(["extracellular", "matrix", "adhesion", "migration", "invasion", "collagen"])

    if "metabolic" in theme_lower or "metabolism" in theme_lower or "oxidative" in theme_lower:
        expanded.update(["metabolic", "metabolism", "oxidative", "redox", "biosynthesis"])

    if "angiogenesis" in theme_lower or "vascular" in theme_lower:
        expanded.update(["angiogenesis", "vascular", "vessel", "blood"])

    if "wnt" in theme_lower:
        expanded.update(["wnt", "catenin"])

    return expanded

```

```

def compare_theme_to_real_go_kegg(theme, supporting_genes, enrichment_df, adj_p_cutoff=0.10):
    theme_keywords = expand_theme_keywords(theme)

    if isinstance(supporting_genes, str):
        llm_genes = parse_genes(supporting_genes)
    else:
        llm_genes = [str(g).strip() for g in supporting_genes if str(g).strip()]

    llm_genes_set = set(llm_genes)

    best_record = None
    best_score = -1

    for _, row in enrichment_df.iterrows():
        term = row["Term_Text"]
        term_tokens = tokenize_text(term)
        enrichment_genes = set(row["Enrichment_Genes_List"])
        adj_p = row["Adjusted_P_value"]

        term_overlap = theme_keywords.intersection(term_tokens)
        gene_overlap = llm_genes_set.intersection(enrichment_genes)

        term_score = len(term_overlap)
        gene_score = len(gene_overlap) * 2

        # Similarity is based only on gene overlap and term-keyword overlap.
        # Adjusted p-value is kept for reporting, not for similarity scoring.
        total_score = term_score + gene_score

        if total_score > best_score:
            best_score = total_score
            best_record = {
                "Best_Enrichment_Source": row["Source"],
                "Best_Enrichment_Term": term,
                "Best_Adjusted_P_value": adj_p,
                "Overlapping_Genes": sorted(list(gene_overlap)),
                "Term_Keyword_Overlap": sorted(list(term_overlap)),
                "Term_Overlap_Count": term_score,
                "Gene_Overlap_Count": len(gene_overlap),
                "Total_Match_Score": total_score
            }

    if best_record is None:
        return {
            "GO_KEGG_Match_Status": "Unsupported",
            "Interpretation": "No GO/KEGG enrichment record was available for comparison."
        }

    gene_overlap_count = best_record["Gene_Overlap_Count"]
    term_overlap_count = best_record["Term_Overlap_Count"]
    adj_p = best_record["Best_Adjusted_P_value"]

    if (
        gene_overlap_count >= 2
        and term_overlap_count >= 1
        and not pd.isna(adj_p)
        and adj_p <= adj_p_cutoff
    ):
        status = "Match"
        interpretation = "The theme matched a real GO/KEGG enrichment term using both keyword overlap and supporting-gene overlap"
    elif gene_overlap_count >= 1 or term_overlap_count >= 1:
        status = "Partial"
        interpretation = "The theme showed partial support from real GO/KEGG enrichment terms, but the overlap was limited or incomplete"
    else:
        status = "Unsupported"
        interpretation = "No clear support was found in the real GO/KEGG enrichment results."

    best_record["GO_KEGG_Match_Status"] = status
    best_record["Interpretation"] = interpretation
    return best_record

# Build real GO/KEGG categorical comparison table for selected Best-of-K candidate
comparison_records = []

for item in selected_parsed_output:
    theme = item.get("theme", "")
    genes = item.get("supporting_genes", [])

```

```

direction = item.get("direction", "Not specified")

match_result = compare_theme_to_real_go_kegg(
    theme=theme,
    supporting_genes=genes,
    enrichment_df=all_enrichment_real,
    adj_p_cutoff=0.10
)

status = match_result["GO_KEGG_Match_Status"]

comparison_records.append({
    "LLM_Theme": theme,
    "Direction": direction,
    "Supporting_Genes": ", ".join(genes) if isinstance(genes, list) else genes,
    "GO_KEGG_Match_Status": status,
    "Best_Enrichment_Source": match_result.get("Best_Enrichment_Source", "None"),
    "Best_Enrichment_Term": match_result.get("Best_Enrichment_Term", "None"),
    "Best_Adjusted_P_value": match_result.get("Best_Adjusted_P_value", np.nan),
    "Overlapping_Genes": ", ".join(match_result.get("Overlapping_Genes", [])),
    "Gene_Overlap_Count": match_result.get("Gene_Overlap_Count", 0),
    "Term_Keyword_Overlap": ", ".join(match_result.get("Term_Keyword_Overlap", [])),
    "Term_Overlap_Count": match_result.get("Term_Overlap_Count", 0),
    "Interpretation": match_result["Interpretation"]
})

comparison_df = pd.DataFrame(comparison_records)

go_kegg_summary_df = pd.DataFrame([
    {
        "Selected_Candidate": selected_candidate_id,
        "Total_Themes": len(comparison_df),
        "Match_Count": (comparison_df["GO_KEGG_Match_Status"] == "Match").sum(),
        "Partial_Count": (comparison_df["GO_KEGG_Match_Status"] == "Partial").sum(),
        "Unsupported_Count": (comparison_df["GO_KEGG_Match_Status"] == "Unsupported").sum()
    }
])

go_kegg_summary_df["Partial_or_Match_Count"] = (
    go_kegg_summary_df["Match_Count"] +
    go_kegg_summary_df["Partial_Count"]
)

go_kegg_summary_df["Match_Rate_%"] = (
    go_kegg_summary_df["Match_Count"] /
    go_kegg_summary_df["Total_Themes"] * 100
).round(2)

go_kegg_summary_df["Partial_or_Match_Rate_%"] = (
    go_kegg_summary_df["Partial_or_Match_Count"] /
    go_kegg_summary_df["Total_Themes"] * 100
).round(2)

go_kegg_summary_df["Unsupported_Rate_%"] = (
    go_kegg_summary_df["Unsupported_Count"] /
    go_kegg_summary_df["Total_Themes"] * 100
).round(2)

print("Selected Candidate:", selected_candidate_id)
print("GO/KEGG categorical support summary:")
display(go_kegg_summary_df)

print("Detailed GO/KEGG comparison:")
display(comparison_df)

comparison_df.to_csv(
    f"real_go_kegg_categorical_comparison_{SAFE_DATASET_NAME}.csv",
    index=False
)

go_kegg_summary_df.to_csv(
    f"real_go_kegg_categorical_summary_{SAFE_DATASET_NAME}.csv",
    index=False
)

print("Saved categorical GO/KEGG comparison files.")

```

Selected Candidate: Candidate_3
GO/KEGG categorical support summary:

	Selected_Candidate	Total_Themes	Match_Count	Partial_Count	Unsupported_Count	Partial_or_Match_Count	Match_Rate_%	Partial
0	Candidate_3	10	3	7	0	10	30.0	

Detailed GO/KEGG comparison:

	LLM_Theme	Direction	Supporting_Genes	GO_KEGG_Match_Status	Best_Enrichment_Source	Best_Enrichment_Term	Best_Adjus
0	Cell cycle and mitotic progression	Upregulated	CCNB1, BIRC5, CEP55, KIAA0101, TK1	Match	GO Upregulated	Positive Regulation of Mitotic Cell Cycle (GO:...	
1	DNA replication licensing and origin firing	Upregulated	ORC6, GINS2, NOB1	Partial	GO Upregulated	DNA Metabolic Process (GO:0006259)	
2	Metabolic reprogramming and oxidative stress	Upregulated	CYP2S1, SMOX, SRD5A3, ANXA3	Partial	GO Upregulated	Spermine Metabolic Process (GO:0008215)	
3	Growth factor signaling and angiogenesis	Upregulated	MDK, PTP4A3, AGT, AQP3	Partial	GO Upregulated	Positive Regulation of Morphogenesis of an Epi...	
4	Suppression of Wnt/Hedgehog and stemness pathways	Downregulated	WNT10A, GLI1, LRIG1, FRZB	Match	GO Downregulated	Wnt Signaling Pathway (GO:0016055)	
5	Downregulation of immune and inflammatory medi...	Downregulated	C3, CSF1R, CXCR4, SERPINF1	Match	GO Downregulated	Cellular Response to Cytokine Stimulus (GO:007...	
6	Loss of extracellular matrix and adhesion prot...	Downregulated	ITIH5, VWF, PDLIM3, KIT	Partial	GO Downregulated	Positive Regulation of Intracellular Signal Tr...	
7	Downregulation of tumor suppressor and differe...	Downregulated	FOXF2, DUSP1, GPR161, PRNP	Partial	GO Downregulated	Regulation of Transcription by RNA Polymerase ...	
8	Mixed transcriptional regulation alterations	Mixed	GTF2IRD1, ZNF485, GPR161, FOXF2	Partial	GO Upregulated	Regulation of DNA-templated Transcription (GO:...	
9	DNA damage response and repair activation	Upregulated	PARP8, BUB1, DTYMK	Partial	GO Upregulated	DNA Synthesis Involved in DNA Replication (GO:...	

Saved categorical GO/KEGG comparison files.

Next steps: [Generate code with comparison_df](#) [New interactive sheet](#)

```
# Phase 6.4d: LLM-predicted GO/KEGG-like profiles
# Goal:
# Ask the LLM to predict Top 10 GO-like and KEGG-like results
# separately for upregulated and downregulated genes,
# then compare them with real GO/KEGG enrichment results.

import re
import time
import pandas as pd
import numpy as np

def generate_single_llm_predicted_profile(
    gene_list,
    reference_type,
    direction,
    max_retries=5
):
```

```

"""
Generate one LLM-predicted profile:
- Top 10 GO Biological Process-like terms
  OR
- Top 10 KEGG-like pathways

for either upregulated or downregulated genes.
"""

if reference_type == "GO_Biological_Process":
    reference_instruction = """
Predict GO Biological Process-like terms.
Use biological process names such as:
cell cycle progression, regulation of Wnt signaling, cell adhesion,
immune response, ion transport, metabolic process.
Do not use KEGG-style pathway names.
"""
    elif reference_type == "KEGG_Pathway":
        reference_instruction = """
Predict KEGG pathway-like names.
Use pathway names such as:
Wnt signaling pathway, Cell cycle, Metabolic pathways,
Cytokine-cytokine receptor interaction, Tight junction.
Do not use broad GO-style descriptions if a pathway-style name is possible.
"""
    else:
        raise ValueError("reference_type must be GO_Biological_Process or KEGG_Pathway")

prompt = f"""
You are a biomedical genomics expert.

Gene direction:
{direction}

Gene list:
{"", ".join(gene_list)}

Task:
Predict the Top 10 {reference_type} results that are most likely represented by this gene list.

{reference_instruction}

Return valid JSON only.
Do not write any text before or after the JSON.
Do not use markdown fences.

JSON format:
[
  {{
    "rank": 1,
    "predicted_term_or_pathway": "specific biological process or pathway name",
    "supporting_genes": ["GENE1", "GENE2", "GENE3"],
    "confidence": "High",
    "biological_rationale": "One short sentence explaining why these genes support this result."
  }}
]

Rules:
- Return exactly 10 objects.
- Use only genes from the provided gene list.
- Do not invent genes.
- Each result must use 2 to 5 supporting genes.
- Do not provide p-values or adjusted p-values.
- Do not claim statistical significance.
- Confidence must be High, Medium, or Low.
- Do not use generic names such as Pathway1, Theme1, Process1, or Term1.
"""

gene_set = set(gene_list)
generic_pattern = re.compile(
    r"\b(Pathway|Theme|Process|Term)\s*_?\s*\d+\b",
    re.IGNORECASE
)

final_records = None
start_time = time.time()

```

```

for attempt in range(1, max_retries + 1):
    raw = get_completion(prompt, temperature=0, max_tokens=8000)
    parsed = parse_json_output(raw)

    if parsed is not None and isinstance(parsed, list) and len(parsed) == 10:
        records = []
        valid = True

        for idx, item in enumerate(parsed, 1):
            term = (
                item.get("predicted_term_or_pathway")
                or item.get("term")
                or item.get("pathway")
                or item.get("theme")
                or ""
            )

            term = str(term).strip()

            genes = item.get("supporting_genes", [])

            if isinstance(genes, str):
                genes = re.split(r",|;|\s+", genes)

            genes = [
                str(g).strip()
                for g in genes
                if str(g).strip()
            ]

            invalid_genes = [g for g in genes if g not in gene_set]

            if (
                term == ""
                or generic_pattern.search(term)
                or len(genes) < 2
                or len(genes) > 5
                or len(invalid_genes) > 0
            ):
                valid = False
                break

            confidence = str(item.get("confidence", "Low")).strip()
            if confidence not in ["High", "Medium", "Low"]:
                confidence = "Low"

            records.append({
                "Reference_Type": reference_type,
                "Direction": direction,
                "Rank": idx,
                "LLM_Predicted_Term_or_Pathway": term,
                "Supporting_Genes_List": genes,
                "LLM_Supporting_Genes": ", ".join(genes),
                "LLM_Confidence": confidence,
                "Biological_Rationale": str(
                    item.get("biological_rationale", "")
                ).strip()
            })

        if valid:
            final_records = records
            break

    print(
        f"LLM prediction failed for {reference_type} {direction}, "
        f"attempt {attempt}. Retrying..."
    )

    print("Parsed type:", type(parsed))
    print("Parsed length:", len(parsed) if isinstance(parsed, list) else "Not a list")
    print("Raw output preview:")
    print(str(raw)[:1500])

runtime = time.time() - start_time

```

```

    if final_records is None:
        raise ValueError(
            f"Failed to generate valid Top 10 LLM predictions for "
            f"{reference_type} {direction}."
        )

    return pd.DataFrame(final_records), runtime

# Generate LLM-predicted Top 10 profiles separately
llm_go_up_df, llm_go_up_time = generate_single_llm_predicted_profile(
    top_up_genes,
    reference_type="GO_Biological_Process",
    direction="Upregulated"
)

llm_go_down_df, llm_go_down_time = generate_single_llm_predicted_profile(
    top_down_genes,
    reference_type="GO_Biological_Process",
    direction="Downregulated"
)

llm_kegg_up_df, llm_kegg_up_time = generate_single_llm_predicted_profile(
    top_up_genes,
    reference_type="KEGG_Pathway",
    direction="Upregulated"
)

llm_kegg_down_df, llm_kegg_down_time = generate_single_llm_predicted_profile(
    top_down_genes,
    reference_type="KEGG_Pathway",
    direction="Downregulated"
)

# Combine all LLM-predicted profiles
llm_predicted_go_kegg_profiles_df = pd.concat(
    [
        llm_go_up_df,
        llm_go_down_df,
        llm_kegg_up_df,
        llm_kegg_down_df
    ],
    ignore_index=True
)

display(llm_predicted_go_kegg_profiles_df)

print("LLM-predicted profiles generated successfully.")
print("Total LLM-predicted results:", len(llm_predicted_go_kegg_profiles_df))
print("GO Up:", len(llm_go_up_df))
print("GO Down:", len(llm_go_down_df))
print("KEGG Up:", len(llm_kegg_up_df))
print("KEGG Down:", len(llm_kegg_down_df))

# Save LLM-predicted profiles
llm_predicted_go_kegg_profiles_df.drop(
    columns=["Supporting_Genes_List"]
).to_csv(
    f"LLM_predicted_GO_KEGG_profiles_{SAFE_DATASET_NAME}.csv",
    index=False
)

print("Saved LLM-predicted GO/KEGG profiles.")

```

Next steps: [Generate code with llm_predicted_go_kegg_profiles_df](#)

[New interactive sheet](#)


```

# Phase 6.4e: Compare LLM-predicted GO/KEGG profiles with real enrichment Top 10 results

def get_real_top10_enrichment(enrichment_df):
    """
    Select real Top 10 enrichment terms/pathways by adjusted p-value.
    """
    temp = enrichment_df.copy()
    temp["Adjusted_P_value"] = pd.to_numeric(
        temp["Adjusted_P_value"],
        errors="coerce"
    )

    temp = temp.sort_values(
        by="Adjusted_P_value",
        ascending=True
    )

    return temp.head(10).copy()

# Real Top 10 enrichment results
real_go_up_top10 = get_real_top10_enrichment(go_up)
real_go_down_top10 = get_real_top10_enrichment(go_down)
real_kegg_up_top10 = get_real_top10_enrichment(kegg_up)
real_kegg_down_top10 = get_real_top10_enrichment(kegg_down)

real_enrichment_top10_map = {
    ("GO_Biological_Process", "Upregulated"): real_go_up_top10,
    ("GO_Biological_Process", "Downregulated"): real_go_down_top10,
    ("KEGG_Pathway", "Upregulated"): real_kegg_up_top10,
    ("KEGG_Pathway", "Downregulated"): real_kegg_down_top10
}

# Categorical comparison without 2/1/0 scoring
comparison_records = []

for _, row in llm_predicted_go_kegg_profiles_df.iterrows():
    reference_type = row["Reference_Type"]
    direction = row["Direction"]
    predicted_term = row["LLM_Predicted_Term_or_Pathway"]
    supporting_genes = row["Supporting_Genes_List"]

    real_df = real_enrichment_top10_map[(reference_type, direction)]

    match_result = compare_theme_to_real_go_kegg(
        theme=predicted_term,
        supporting_genes=supporting_genes,
        enrichment_df=real_df,
        adj_p_cutoff=0.10
    )

    status = match_result["GO_KEGG_Match_Status"]

    comparison_records.append({
        "Reference_Type": reference_type,
        "Direction": direction,
        "LLM_Rank": row["Rank"],
        "LLM_Predicted_Term_or_Pathway": predicted_term,
        "LLM_Supporting_Genes": row["LLM_Supporting_Genes"],
        "LLM_Confidence": row["LLM_Confidence"],
        "Match_Status": status,
        "Best_Real_Enrichment_Source": match_result.get("Best_Enrichment_Source", "None"),
        "Best_Real_Enrichment_Term": match_result.get("Best_Enrichment_Term", "None"),
        "Best_Adjusted_P_value": match_result.get("Best_Adjusted_P_value", np.nan),
        "Overlapping_Genes": " ", ".join(match_result.get("Overlapping_Genes", [])),
        "Term_Keyword_Overlap": " ", ".join(match_result.get("Term_Keyword_Overlap", [])),
        "Interpretation": match_result["Interpretation"]
    })

llm_predicted_vs_real_comparison_df = pd.DataFrame(comparison_records)

```

```

display(llm_predicted_vs_real_comparison_df)

# Summary by source and direction without composite scoring
llm_predicted_vs_real_summary_df = (
    llm_predicted_vs_real_comparison_df
    .groupby(["Reference_Type", "Direction"])
    .agg(
        Number_of_LLM_Predictions=("LLM_Predicted_Term_or_Pathway", "count"),
        Match_Count=("Match_Status", lambda x: (x == "Match").sum()),
        Partial_Count=("Match_Status", lambda x: (x == "Partial").sum()),
        Unsupported_Count=("Match_Status", lambda x: (x == "Unsupported").sum())
    )
    .reset_index()
)

llm_predicted_vs_real_summary_df["Partial_or_Match_Count"] = (
    llm_predicted_vs_real_summary_df["Match_Count"] +
    llm_predicted_vs_real_summary_df["Partial_Count"]
)

llm_predicted_vs_real_summary_df["Match_Rate_%"] = (
    llm_predicted_vs_real_summary_df["Match_Count"] /
    llm_predicted_vs_real_summary_df["Number_of_LLM_Predictions"] * 100
).round(2)

llm_predicted_vs_real_summary_df["Partial_or_Match_Rate_%"] = (
    llm_predicted_vs_real_summary_df["Partial_or_Match_Count"] /
    llm_predicted_vs_real_summary_df["Number_of_LLM_Predictions"] * 100
).round(2)

llm_predicted_vs_real_summary_df["Unsupported_Rate_%"] = (
    llm_predicted_vs_real_summary_df["Unsupported_Count"] /
    llm_predicted_vs_real_summary_df["Number_of_LLM_Predictions"] * 100
).round(2)

display(llm_predicted_vs_real_summary_df)

# Save categorical comparison outputs
llm_predicted_vs_real_comparison_df.to_csv(
    f"LLM_predicted_vs_real_GO_KEGG_categorical_comparison_{SAFE_DATASET_NAME}.csv",
    index=False
)

llm_predicted_vs_real_summary_df.to_csv(
    f"LLM_predicted_vs_real_GO_KEGG_categorical_summary_{SAFE_DATASET_NAME}.csv",
    index=False
)

print("Saved categorical LLM-predicted vs real GO/KEGG comparison files.")

```


	Reference_Type	Direction	LLM_Rank	LLM_Predicted_Term_or_Pathway	LLM_Supporting_Genes	LLM_Confidence	Match_Stat
0	GO_Biological_Process	Upregulated	1	DNA replication initiation	ORC6, GINS2, CTPS2, TK1	High	Unsupport
1	GO_Biological_Process	Upregulated	2	Mitotic cell cycle progression	CCNB1, BUB1, CENPH, CEP55	High	Ma
2	GO_Biological_Process	Upregulated	3	Chromosome segregation	BUB1, CENPH, CDCA5, POC1B	High	Par
3	GO_Biological_Process	Upregulated	4	DNA repair and damage response	UBE2T, PARP8, KIAA0101	High	Unsupport
4	GO_Biological_Process	Upregulated	5	Regulation of apoptosis	BIRC5, ANXA3, S100A11	Medium	Par
5	GO_Biological_Process	Upregulated	6	Cell proliferation and growth signaling	MDK, INHBA, PTP4A3, AGT	Medium	Par
6	GO_Biological_Process	Upregulated	7	Protein ubiquitination and proteasomal targeting	UBE2T, WDR77, ZNF485	Medium	Unsupport
7	GO_Biological_Process	Upregulated	8	Oxidative stress response	SMOX, ERO1A, S100A11	Medium	Par
8	GO_Biological_Process	Upregulated	9	Nucleotide biosynthesis	CTPS2, TK1, DTYMK, MRPS23	Medium	Unsupport
9	GO_Biological_Process	Upregulated	10	RNA processing and splicing	SRSF6, ZCCHC7, NOB1	Low	Par
10	GO_Biological_Process	Downregulated	1	regulation of Wnt signaling pathway	WNT10A, FRZB, GLI1, GPR161	High	Unsupport
11	GO_Biological_Process	Downregulated	2	innate immune response	C3, CSF1R, CXCR4, GBP4	High	Ma
12	GO_Biological_Process	Downregulated	3	extracellular matrix organization	ITIH5, SERPINF1, VWF	Medium	Unsupport
13	GO_Biological_Process	Downregulated	4	myelination and peripheral nerve development	PMP22, LYNX1, PRNP	Medium	Par
14	GO_Biological_Process	Downregulated	5	lipid transport and metabolism	CD36, OSBPL1A, OSBPL6, PIP4K2A	Medium	Unsupport
15	GO_Biological_Process	Downregulated	6	cell chemotaxis and migration	CXCR4, CSF1R, CORO1A, GPR34	Medium	Par
16	GO_Biological_Process	Downregulated	7	angiogenesis	SERPINF1, VWF, FGF9	Medium	Par
17	GO_Biological_Process	Downregulated	8	Hedgehog signaling regulation	GLI1, GPR161, DUSP1	Low	Par
18	GO_Biological_Process	Downregulated	9	MAPK signaling pathway regulation	DUSP1, PTPRH, CSF1R	Medium	Par

19	GO_Biological_Process	Downregulated	10	hemostasis and platelet activation	VWF, CD36, SERPINF1	Low	Unsupport
20	KEGG_Pathway	Upregulated	1	Cell cycle	CCNB1, BUB1, CDCA5, BIRC5, ORC6	High	Ma
21	KEGG_Pathway	Upregulated	2	DNA replication	ORC6, GINS2, CENPH, CEP55, KIAA0101	High	Par
22	KEGG_Pathway	Upregulated	3	Pyrimidine metabolism	TK1, DTYMK, CTPS2	High	Ma
23	KEGG_Pathway	Upregulated	4	Ribosome biogenesis in eukaryotes	NOB1, TSR1, MRPS23, PNO1	Medium	Unsupport
24	KEGG_Pathway	Upregulated	5	RNA transport	NUPL2, PNO1, SRSF6	Medium	Unsupport
25	KEGG_Pathway	Upregulated	6	Spliceosome	SRSF6, ZCCHC7	Medium	Unsupport
26	KEGG_Pathway	Upregulated	7	PI3K-Akt signaling pathway	PTP4A3, MDK, AGT	Medium	Unsupport
27	KEGG_Pathway	Upregulated	8	Cytokine-cytokine receptor interaction	INHBA, AGT, AQP3	Low	Par
28	KEGG_Pathway	Upregulated	9	Metabolic pathways	CYP2S1, SRD5A3, AGT	Low	Par
29	KEGG_Pathway	Upregulated	10	Pathways in cancer	BIRC5, MDK, PTP4A3, KIAA0101	Medium	Par
30	KEGG_Pathway	Downregulated	1	Wnt signaling pathway	WNT10A, FRZB, GLI1	High	Par
31	KEGG_Pathway	Downregulated	2	Complement and coagulation cascades	C3, VWF, SERPINF1, CFHR3	High	Ma
Next steps:	Generate code with llm_predicted_vs_real_comparison_df New interactive sheet Generate code with llm_predicted_vs_real_summary						
32	KEGG_Pathway	Downregulated	3	Chemokine signaling pathway	CXCR4, CSF1R, GNG11, GPR34	High	Par
33	KEGG_Pathway	Downregulated	4	PI3K-Akt signaling pathway	KIT, CSF1R, PIP4K2A, CD36	Medium	Par
34	KEGG_Pathway	Downregulated	5	Metabolic pathways	PAPSS2, GAMT, OSBPL1A, OSBPL6	Medium	Par
35	KEGG_Pathway	Downregulated	6	Cell adhesion molecules (CAMs)	VWF, ITIH5, CD36, PMP22	Medium	Par
36	KEGG_Pathway	Downregulated	7	Hedgehog signaling pathway	GLI1, GPR161, DUSP1	Low	Par

```

# Phase 6.4d: Automatic Verification of selected Best-of-K candidate

def format_hallucinated_genes(value):
    if value is None:
        return "None"
    if isinstance(value, list):
        return ", ".join(value) if value else "None"
    if str(value) == "None":
        return "None"
    return str(value)

verification_records = []

for _, row in comparison_df.iterrows():
    theme = row["LLM_Theme"]
    match_status = row["GO_KEGG_Match_Status"]
    supporting_genes = row["Supporting_Genes"]

    # Get hallucination info for the same theme
    hallucination_row = hallucination_df[
        hallucination_df["LLM_Theme"] == theme
    ]

    if not hallucination_row.empty:
        hallucination_rate = hallucination_row.iloc[0]["Hallucination_Rate_%"]
        hallucinated_genes = format_hallucinated_genes(
            hallucination_row.iloc[0]["Hallucinated_Genes"]
        )
    else:
        hallucination_rate = None
        hallucinated_genes = "Not checked"

    # Automatic verification logic
    if hallucination_rate is not None and hallucination_rate > 0:
        verification_status = "Unsupported"
        problem_found = f"Non-input genes detected: {hallucinated_genes}"
        corrected_comment = "This theme should be revised because at least one supporting gene was not present in the input genes"

    elif match_status == "Match":
        verification_status = "Supported"
        problem_found = "None"
        corrected_comment = "All supporting genes were present in the input lists, and the theme showed direct GO/KEGG-related support"

    elif match_status == "Partial":
        verification_status = "Partially Supported"
        problem_found = "Only partial or indirect GO/KEGG support was detected."
        corrected_comment = "All supporting genes were present in the input lists, but the biological theme should be interpreted with caution"

    else:
        verification_status = "Unsupported"
        problem_found = "No clear GO/KEGG keyword-level support was detected."
        corrected_comment = "The theme should not be treated as a final supported interpretation without additional evidence."

    verification_records.append({
        "LLM_Theme": theme,
        "Supporting_Genes": supporting_genes,
        "Gene_Presence_Check": "Passed" if hallucinated_genes == "None" else "Failed",
        "GO_KEGG_Match_Status": match_status,
        "Verification_Status": verification_status,
        "Problem_Found": problem_found,
        "Corrected_Comment": corrected_comment
    })

verification_df = pd.DataFrame(verification_records)

print("Automatic verification results:")
display(verification_df)

```

Automatic verification results:

	LLM_Theme	Supporting_Genes	Gene_Presence_Check	GO_KEGG_Match_Status	Verification_Status	Problem_Found	Corrected_Comm
0	Cell cycle and mitotic progression	CCNB1, BIRC5, CEP55, KIAA0101, TK1	Passed	Match	Supported	None	All supporting ge were present in inp
1	DNA replication licensing and origin firing	ORC6, GINS2, NOB1	Passed	Partial	Partially Supported	Only partial or indirect GO/KEGG support was d...	All supporting ge were present in inp
2	Metabolic reprogramming and oxidative stress	CYP2S1, SMOX, SRD5A3, ANXA3	Passed	Partial	Partially Supported	Only partial or indirect GO/KEGG support was d...	All supporting ge were present in inp
3	Growth factor signaling and angiogenesis	MDK, PTP4A3, AGT, AQP3	Passed	Partial	Partially Supported	Only partial or indirect GO/KEGG support was d...	All supporting ge were present in inp
4	Suppression of Wnt/Hedgehog and stemness pathways	WNT10A, GLI1, LRIG1, FRZB	Passed	Match	Supported	None	All supporting ge were present in inp
5	Downregulation of immune and inflammatory medi...	C3, CSF1R, CXCR4, SERPINF1	Passed	Match	Supported	None	All supporting ge were present in inp

Next steps:

Generate code with verification_df

New interactive sheet

```
# Phase 6.5: Theme Stability Score

import pandas as pd
import re

def normalize_theme(theme):
    """
    Convert different theme names into common biological categories.
    """
    theme_lower = theme.lower()

    # 1. Wnt / beta-catenin signaling
    if (
        "wnt" in theme_lower or
        "β-catenin" in theme_lower or
        "beta-catenin" in theme_lower or
        "catenin" in theme_lower
    ):
        return "Wnt/β-catenin signaling"

    # 2. EMT / adhesion / remodeling
    if (
        "adhesion" in theme_lower or
        "emt" in theme_lower or
        "epithelial-mesenchymal" in theme_lower or
        "junction" in theme_lower or
        "ecm" in theme_lower or
        "extracellular matrix" in theme_lower or
        "remodeling" in theme_lower or
        "invasion" in theme_lower or
        "migration" in theme_lower or
        "polarity" in theme_lower or
        "matrix metalloproteinase" in theme_lower
    ):
        return "EMT / adhesion / remodeling"

    # 3. Cell cycle / proliferation
    if (
        "cell cycle" in theme_lower or
        "cell-cycle" in theme_lower or
        "proliferation" in theme_lower or
        "mitotic" in theme_lower or
        "mitosis" in theme_lower or
        "division" in theme_lower or
```

```

        "g2/m" in theme_lower
    ):
        return "Cell-cycle / proliferation"

# 4. Metabolic reprogramming
if (
    "metabolic" in theme_lower or
    "metabolism" in theme_lower or
    "glycolysis" in theme_lower or
    "gluconeogenesis" in theme_lower or
    "fructose" in theme_lower or
    "mannose" in theme_lower or
    "amino acid" in theme_lower or
    "biosynthesis" in theme_lower or
    "biosynthetic" in theme_lower or
    "serine" in theme_lower or
    "glycine" in theme_lower or
    "threonine" in theme_lower or
    "redox" in theme_lower or
    "oxidative" in theme_lower or
    "pentose" in theme_lower or
    "glucuronate" in theme_lower or
    "vitamin" in theme_lower
):
    return "Metabolic reprogramming"

# 5. Epithelial barrier / transport
if (
    "barrier" in theme_lower or
    "transport" in theme_lower or
    "epithelial differentiation" in theme_lower or
    "intestinal barrier" in theme_lower or
    "chloride" in theme_lower or
    "sodium" in theme_lower or
    "tight junction" in theme_lower or
    re.search(r"\bion\b", theme_lower)
):
    return "Epithelial barrier / transport"

# 6. Immune / inflammatory signaling
if (
    "immune" in theme_lower or
    "inflammatory" in theme_lower or
    "inflammation" in theme_lower or
    "cytokine" in theme_lower or
    "interferon" in theme_lower or
    "leukocyte" in theme_lower
):
    return "Immune / inflammatory signaling"

return "Other"

# Extract themes from API Best-of-K candidates
theme_records = []

for candidate in api_candidates:
    candidate_id = candidate["candidate_id"]
    parsed = candidate["parsed_output"]

    if parsed is not None:
        for item in parsed:
            raw_theme = item.get("theme", "")
            normalized_theme = normalize_theme(raw_theme)

            theme_records.append({
                "Candidate": candidate_id,
                "Raw_Theme": raw_theme,
                "Normalized_Theme": normalized_theme
            })

theme_records_df = pd.DataFrame(theme_records)

print("Raw themes mapped to normalized categories:")
display(theme_records_df)

# Count in how many candidates each normalized theme appeared

```



```
stability_results = []

for theme in theme_records_df["Normalized_Theme"].unique():
    candidate_count = theme_records_df[
        theme_records_df["Normalized_Theme"] == theme
    ][["Candidate"]].nunique()

    stability_score = candidate_count / K * 100

    if stability_score == 100:
        stability_label = "High"
    elif stability_score >= 66:
        stability_label = "Moderate"
    elif stability_score >= 33:
        stability_label = "Low"
    else:
        stability_label = "Very Low"

    stability_results.append({
        "Normalized_Theme": theme,
        "Candidate_Frequency": f"{candidate_count}/{K}",
        "Stability_Score_%": round(stability_score, 2),
        "Stability_Label": stability_label
    })

theme_stability_df = pd.DataFrame(stability_results).sort_values(
    by="Stability_Score_%",
    ascending=False
)

print("\nTheme Stability Summary:")
theme_stability_df
```

Raw themes mapped to normalized categories:

	Candidate	Raw_Theme	Normalized_Theme	
0	Candidate_1	Cell cycle and mitotic checkpoint activation	Cell-cycle / proliferation	
1	Candidate_1	DNA replication licensing and synthesis	Other	
2	Candidate_1	Polyamine catabolism and oxidative stress	Metabolic reprogramming	
3	Candidate_1	Growth factor and pro-proliferative signaling	Other	
4	Candidate_1	RNA processing and spliceosome components	Other	
5	Candidate_1	Suppression of Wnt/Hedgehog signaling pathways	Wnt/β-catenin signaling	
6	Candidate_1	Loss of tumor suppressor and negative regulato...	Other	
7	Candidate_1	Reduced immune and inflammatory signaling	Immune / inflammatory signaling	
8	Candidate_1	Downregulation of extracellular matrix and str...	EMT / adhesion / remodeling	
9	Candidate_1	Metabolic and metal ion homeostasis downregula...	Metabolic reprogramming	
10	Candidate_2	Cell cycle and mitotic spindle assembly	Cell-cycle / proliferation	
11	Candidate_2	DNA replication initiation	Other	
12	Candidate_2	Polyamine catabolism and oxidative stress	Metabolic reprogramming	
13	Candidate_2	Growth factor and angiogenic signaling	Other	
14	Candidate_2	Suppressed Wnt/Hedgehog pathway components	Wnt/β-catenin signaling	
15	Candidate_2	Reduced innate immune and complement activity	Immune / inflammatory signaling	
16	Candidate_2	Decreased chemokine and GPCR signaling	Other	
17	Candidate_2	Loss of tumor suppressor and differentiation r...	Other	
18	Candidate_2	Mixed ubiquitin-mediated DNA damage response	Other	
19	Candidate_2	Mixed water transport and lipid metabolism alt...	Metabolic reprogramming	
20	Candidate_3	Cell cycle and mitotic progression	Cell-cycle / proliferation	
21	Candidate_3	DNA replication licensing and origin firing	Other	
22	Candidate_3	Metabolic reprogramming and oxidative stress	Metabolic reprogramming	
23	Candidate_3	Growth factor signaling and angiogenesis	Other	
24	Candidate_3	Suppression of Wnt/Hedgehog and stemness pathways	Wnt/β-catenin signaling	
25	Candidate_3	Downregulation of immune and inflammatory medi...	Immune / inflammatory signaling	
26	Candidate_3	Loss of extracellular matrix and adhesion prot...	EMT / adhesion / remodeling	
27	Candidate_3	Downregulation of tumor suppressor and differe...	Other	
28	Candidate_3	Mixed transcriptional regulation alterations	Other	
29	Candidate_3	DNA damage response and repair activation	Other	

Theme Stability Summary:

	Normalized_Theme	Candidate_Frequency	Stability_Score_%	Stability_Label	
0	Cell-cycle / proliferation	3/3	100.00	High	
1	Other	3/3	100.00	High	
2	Metabolic reprogramming	3/3	100.00	High	
3	Wnt/β-catenin signaling	3/3	100.00	High	
4	Immune / inflammatory signaling	3/3	100.00	High	
5	EMT / adhesion / remodeling	2/3	66.67	Moderate	

Next steps:

[Generate code with theme_records_df](#)

[New interactive sheet](#)

[Generate code with theme_stability_df](#)

[New interactive sheet](#)

Phase 6.6: GO/KEGG Significance Caution Flag

import pandas as pd

```
def add_significance_flag(df, source_name):  
    """
```

```

Add significance caution labels based on Adjusted P-value.
"""
df = df.copy()
df["Source"] = source_name

def classify_significance(adj_p):
    if adj_p < 0.05:
        return "Significant after correction"
    elif adj_p < 0.10:
        return "Suggestive / borderline"
    else:
        return "Not significant after correction"

df["Significance_Caution"] = df["Adjusted P-value"].apply(classify_significance)

return df

# Load GO/KEGG enrichment result files
go_up = pd.read_csv(f"/content/GO-up-{DATASET_NAME}.txt", sep="\t")
go_down = pd.read_csv(f"/content/GO-down-{DATASET_NAME}.txt", sep="\t")

kegg_up = pd.read_csv(f"/content/KEGG-up-{DATASET_NAME}.txt", sep="\t")
kegg_down = pd.read_csv(f"/content/KEGG-down-{DATASET_NAME}.txt", sep="\t")

# Add significance caution flags
go_up_flagged = add_significance_flag(go_up, "GO Upregulated")
go_down_flagged = add_significance_flag(go_down, "GO Downregulated")
kegg_up_flagged = add_significance_flag(kegg_up, "KEGG Upregulated")
kegg_down_flagged = add_significance_flag(kegg_down, "KEGG Downregulated")

# Combine all enrichment results
all_enrichment_flagged = pd.concat(
    [go_up_flagged, go_down_flagged, kegg_up_flagged, kegg_down_flagged],
    ignore_index=True
)

# Count significance categories by source
significance_summary = (
    all_enrichment_flagged
    .groupby(["Source", "Significance_Caution"])
    .size()
    .reset_index(name="Number_of_Terms")
)

print("Significance caution summary:")
display(significance_summary)

# Display top terms from each source with caution labels
top_flagged_terms = (
    all_enrichment_flagged
    .sort_values(["Source", "Adjusted P-value"])
    .groupby("Source")
    .head(10)
    [["Source", "Term", "Adjusted P-value", "Significance_Caution", "Genes"]]
)

print("\nTop enrichment terms with significance caution flags:")
top_flagged_terms

```

Next

[Generate code with chat](#) [New interactive chart](#) [Generate code with text](#) [New interactive chart](#)

steps:

Generate code with Significance_Summary

New interactive sheet

Generate code with top_flagged_terms

New interactive sheet

```
# Separate GO and KEGG enrichment results
# Top 10 Upregulated + Top 10 Downregulated for each source

TOP_N = 10

display_cols = ["Source", "Term", "Adjusted P-value", "Significance_Caution", "Genes"]

# GO Biological Process terms
go_up_top10 = (
    go_up_flagged
    .sort_values("Adjusted P-value", ascending=True)
    .head(TOP_N)
    [display_cols]
)

go_down_top10 = (
    go_down_flagged
    .sort_values("Adjusted P-value", ascending=True)
    .head(TOP_N)
    [display_cols]
)

go_top20_terms = pd.concat(
    [go_up_top10, go_down_top10],
    ignore_index=True
)

# KEGG pathway terms
kegg_up_top10 = (
    kegg_up_flagged
    .sort_values("Adjusted P-value", ascending=True)
    .head(TOP_N)
    [display_cols]
)

kegg_down_top10 = (
    kegg_down_flagged
    .sort_values("Adjusted P-value", ascending=True)
    .head(TOP_N)
    [display_cols]
)

kegg_top20_pathways = pd.concat(
    [kegg_up_top10, kegg_down_top10],
    ignore_index=True
)

print("GO Biological Process terms: Top 10 Upregulated + Top 10 Downregulated")
print("Total GO terms displayed:", len(go_top20_terms))
display(go_top20_terms)

print("\nKEGG pathways: Top 10 Upregulated + Top 10 Downregulated")
print("Total KEGG pathways displayed:", len(kegg_top20_pathways))
display(kegg_top20_pathways)
```

2	GO Upregulated	Maturation of SSU-rRNA (GO:0030490)	0.059380	Suggestive / borderline	NOB1;PNO1;TSR1
3	GO Upregulated	Microtubule Cytoskeleton Organization Involved...	0.059380	Suggestive / borderline	CCNB1;CENPH;BIRC5
4	GO Upregulated	Positive Regulation of Smooth Muscle Cell Migr...	0.082014	Suggestive / borderline	MDK;S100A11
5	GO Upregulated	Mitotic Spindle Organization	0.092945	Suggestive / borderline	CCNB1;CENPH;BIRC5

	Upregulated	(GO:0007052)				
6	GO Upregulated	Positive Regulation of Morphogenesis of an Epi...	0.092945	Suggestive / borderline		MDK;AGT
7	GO Upregulated	Spindle Assembly Checkpoint Signaling (GO:0071...	0.092945	Suggestive / borderline		BIRC5;BUB1
8	GO Upregulated	Mitotic Spindle Assembly Checkpoint Signaling ...	0.092945	Suggestive / borderline		BIRC5;BUB1
9	GO Upregulated	Mitotic Spindle Checkpoint Signaling (GO:0071174)	0.092945	Suggestive / borderline		BIRC5;BUB1
1140	KEGG Downregulated	PATHWAYS IN CANCER	0.005610	Significant after correction	CSF1R;WNT10A;FGF9;KIT;PLCG2;CXCR4;GLI1;GNG11	
1141	KEGG Downregulated	RAS SIGNALING PATHWAY	0.017614	Significant after correction	CSF1R;FGF9;KIT;PLCG2;GNG11	
1142	KEGG Downregulated	COMPLEMENT AND COAGULATION CASCADES	0.048639	Significant after correction		C3;VWF;CFHR3
1143	KEGG Downregulated	HEMATOPOIETIC CELL LINEAGE	0.048639	Significant after correction		CSF1R;KIT;CD36
1144	KEGG Downregulated	PI3K-AKT SIGNALING PATHWAY	0.048639	Significant after correction	CSF1R;FGF9;VWF;KIT;GNG11	
1145	KEGG Downregulated	BREAST CANCER	0.109940	Not significant after correction		WNT10A;FGF9;KIT
1146	KEGG Downregulated	PHAGOCYTOSIS	0.018287	Significant after correction		C3;CD36;CORO1A;KIT;PLCG2
12	GO Downregulated	Positive Regulation of Dendritic Cell Cytokine...	0.020409	Significant after correction		KIT;PLCG2
13	KEGG Downregulated	Cellular Response to Erythropoietin (GO:0036018)	0.020409	Significant after correction		MT2A;KIT;GPR161;GLI1
1148	KEGG Downregulated	ERK1/2 SIGNALING	0.109940	Not significant after correction		
14	GO Downregulated	Cellular Response to Cytokine Stimulus (GO:007...	0.020409	Significant after correction	CSF1R;MT2A;DUSP1;KIT;CXCR4;GBP4	
1149	KEGG Downregulated	PATHWAY	0.109940	Not significant after correction		
15	GO Downregulated	Positive Regulation of Membrane Invagination (...)	0.020409	Significant after correction		C3;PLCG2
1007	KEGG Downregulated	PYRIMIDINE	0.014403	Significant after correction		DTYMK;CTPS2;TK1
16	GO Downregulated	Regulation of Vascular Associated Smooth Muscl...	0.020409	Significant after correction		FGF9;KIT
1000	GO Upregulated	CELL CYCLE	0.014403	Significant after correction		CCNB1;ORC6;CDCA5;BUB1
17	GO Downregulated	Positive Regulation of Phagocytosis Engulfmen...	0.020409	Significant after correction		C3;PLCG2
1000	KEGG Downregulated	P53 SIGNALING	0.247363	Not significant after correction		CCNB1;PPP1R13L
18	GO Downregulated	Regulation of Phagocytosis, Engulfment (GO:006...	0.022138	Significant after correction		C3;PLCG2
1090	KEGG Upregulated	MEDIATED OOCYTE MATURATION	0.367475	Not significant after correction		CCNB1;BUB1;PRNP;MT2A
19	GO Downregulated	Intracellular Copper Ion Homeostasis (GO:0006878)	0.025605	Significant after correction		
1091	KEGG Upregulated	OOCYTE MEIOSIS	0.426855	Not significant after correction		CCNB1;BUB1
KEGG pathways displayed: 20						
Total KEGG pathways displayed: 20						
1092	KEGG Upregulated	MANNOSE TYPE O-GLYCAN BIOSYNTHESIS	0.426855	Not significant after correction		LARGE2
0	KEGG Upregulated	PYRIMIDINE METABOLISM	0.014403	Significant after correction		DTYMK;CTPS2;TK1
1	KEGG Upregulated	CELL CYCLE	0.014403	Significant after correction		CCNB1;ORC6;CDCA5;BUB1
2	KEGG Upregulated	P53 SIGNALING PATHWAY	0.247363	Not significant after correction		CCNB1;PPP1R13L
3	KEGG Upregulated	PROGESTERONE-MEDIATED OOCYTE MATURATION	0.367475	Not significant after correction		CCNB1;BUB1
4	KEGG Upregulated	OOCYTE MEIOSIS	0.426855	Not significant after correction		CCNB1;BUB1

Next steps:

Generate code with kegg_top20_terms

New interactive sheet

Generate code with kegg_top20_pathways

New interactive sheet