

SENTINEL DOORSTATION



The **Sentinel** Range gives occupants of apartments and office buildings a safe means to communicate with visitors and a secure way of allowing entry.

The Sentinel Series is designed for unguarded apartments and office buildings. It offers code access door release, with auto answer and termination of calls. Users can communicate with visitors and allow keyless entry.

*“Designed for a multi-story high rise,
with hardware upgrade options”*

Externally Powered Mk4

Designed for general purpose situations, a PSTN doorstation featuring an interactive voice prompt for quick and easy programming (power pack supplied).

VoIP

An Ethernet connected doorstation that provides Voice over Internet communication technology. Giving you the power of our PSTN base units in a IP format.



Australian
Made



User
Friendly



Low Cost
Ownership



Vandal
Resistant



Weather
Resistant

The SENTINEL (Keypad & Directory)

A Name & Phone Number capacity of 1000 (16 digits max)

Directory Service

Two on board relays with unique codes (standard)

Half Duplex hands free operation

Keyless door entry

Dual line LCD with back light

Non volatile memory

Backup battery circuitry built in (MK4 only)

Programmable company logo / building name

Auto hang up and auto answer facilities

Flexible 1 to 6 digit room numbers

RTC recording and storing of gate events (MK4 only)

Loud speaker output of 1 watt peak, one phone line required

Power pack supplied

Remote operating features (speaker and mic level control) (MK4 only)

Dual remote relay activation (door/gate release)

Local programming facilities

RFID card reader for gate release (optional)



Stainless Steel
Enclosure



Acrylic Enclosure
(Weather shield)



Stainless Steel Enclosure
Inside an Acrylic Enclosure



Stainless Steel
Hood Enclosure



Flush Mount
Wall Box



Stainless Steel Enclosure



Acrylic Enclosure (Weather shield)



Stainless Steel inside an Acrylic Enclosure



Stainless Steel
Hood Enclosure



Flush Mount Wall Box

ENCLOSURE OPTIONS

Choose the right enclosure to suit the location, our range includes:

- Stainless Steel Surface Mount Enclosure

- Stainless Steel Surface Mount with Acrylic Enclosure

- Stainless Steel Weather Hood

- Flush Mount Wall Box (internal zinc plated mild steel)

SENTINEL Series



The standard panel size for all Sentinel units is 130mm x 270mm, custom panel sizes and layouts can be tailor made to your needs. Panels are available in either vertical or horizontal, and can be anodised aluminium or stainless steel. If you require the panel to be made of different material or powder coated, this too is available upon request.

Sentinel VoIP

The VoIP model is standard IP-based communications network and uses the SIP protocol for a fast and reliable connection to modern PBX systems. Sentinel VoIP can be PoE or externally powered. It provides the same remote door/gate release features as the Sentinel Mk3 & Mk4. Programming is via a web browser interface on a connected network.

Sentinel Mk4

(This unit must be installed by qualified personnel)

Sentinel Mk4 Doorstations are a **analogue** telephone unit, that controls the main gate from an apartment/office using the telecommunication network.

The MK4 can be programmed via USB using the Sent-pro software interface (included).

Remote & Wi-Fi programming options available.

- Externally powered PSTN
- 90 seconds ringer time out
- On board name search directory
- Back lit LCD.
- Vandal resistant 4x3 metal keypad
- Loud speaking and hands-free functions.
- Door Release & gate control



FEATURE	MK4 Model	VoIP Model
Power Requirements	6 Volts (min) - 24 Volts (max)	PoE / PSU 9-50Vdc 300mA
Standby Current	41mA(minimum)	60mA @ 13Vdc
In use Current	110mA @ 12Vdc (max)	300mA @ 13Vdc
Relay Rating(Non Inductive Voltage Free)	1A@30Vdc / 1A SELVorTNV	1A@60Vdc/40Vac SELVorTNV
Dimensions Vertical Units	H 270mm W 130mm D 40mm	H 270mm W 130mm D 40mm
Dimensions Horizontal Units	H 130mm W 270mm D 40mm	H 130mm W 270mm D 40mm
Wall Cut-out (mm)	225 x 115 x 40	225 x 115 x 40
Speaker Level	1Watt	1Watt
Operating Temperature Range	0°C to +70°C	0°C to +50°C
Call Buttons	keypad + name search	keypad + name search
PoE Class Requirements	N/A	PoE class 1 IEEE802.3af



Sentinel Doorstation (vertical)

Dimensions (mm) W130 x H270

Designed to be versatile in installation, it can be fitted to a vandal resistant, weather shielding stainless steel enclosure

(not included)
(Surface mount installation)

Vertical Stainless Steel Enclosure
(304 grade material)

Dimensions (mm) H 275 mm W 133 D 85



Sentinel Doorstation (horizontal)

Dimensions (mm) W 270 X H 130

Horizontal Stainless Steel Enclosure
(304 grade material)

Dimensions (mm) H 133 X W 275 D 85