

SENTRY CAMERA

**Night vision
camera**

**Optional Stainless
Steel Enclosure**

**Vandal
resistant
glass**

**Aluminium
Lens Guard**

**Stainless Steel
Buttons**

Loud speaker



The SENTRY CAMERA series outdoor doorstations are engineered for extreme durability and vandal resistance, featuring a robust front panel made from high-grade stainless steel that resists impacts, scratches, corrosion, and deliberate damage – making longevity and security the top priorities in every design decision.

Fully weatherproof to IP65, the SENTRY can withstand rain and temperature extremes while the panel, impact-resistant buttons.

Thanks to the vandal-resistant stainless steel construction and customizable user interface, layouts can be supplied ready-made or fully defined by the user – perfectly adapted for gate or door entry, information kiosks, emergency call points, control desks, or internal communication stations.

Designed to suit any high-traffic, high-risk locations where durability and security cannot be compromised.

“Designed to suit any high-traffic, high-risk locations where durability and security cannot be compromised.”



Australian
Made



User
Friendly



Low Cost
Ownership



Vandal
Resistant



Weather
Resistant



Choose from vertical stainless steel panels, 1 , 2, 4 buttons & keypad



Stainless Steel
Enclosure



Acrylic Enclosure
(Weather shield)



Stainless Steel Enclosure
Inside an Acrylic Enclosure



Stainless Steel
Hood Enclosure



Flush Mount
Wall Box

ENCLOSURE OPTIONS

Choose the right enclosure to suit the location, our range includes:

- Stainless Steel Surface Mount Enclosure
- Stainless Steel Surface Mount with Acrylic Enclosure
- Stainless Steel Weather Hood
- Flush Mount Wall Box (internal zinc plated mild steel)

SENTRY CAMERA

The Sentry Doorstation ranges from one to six buttons and can be expanded up to sixteen buttons on a custom panel. The standard panel (130mm X 270mm) is made from 304 stainless steel. The metal buttons and keypad (4x3) are made to be vandal resistant.

Panels are available in either vertical or horizontal, and can be anodised aluminium or stainless steel. If you require the panel to be made of different material (ie. Brass, gold-plated, etc), this too is available upon request.

With programmable auto dial buttons, the Sentry doorstations are a user friendly solution for controlled entry. In the event of noisy environments a push-to-talk feature can be implemented in order to overcome the background noise level while on a call. (Available on all models).

Options / Upgrades

The Master / Slave configuration, designed for two units to run at different heights for a combined car & truck gate entrance.

Two gate release option, when you require a remote release of two independent gates or doors from a single unit. This option is the inclusion of an additional relay, which can be fitted on request.

Engraving is a permanent way to label a call destination next to each button, or include the company logo.

Additional Features

Speed dialer option

Vandal resistant buttons or keypad

Battery backup and solar panel (optional)

Remote programming facilities

Remote operating features

Remote diagnostic testing

Remote relay activation

Self identification

Push to talk for noisy environments

Up to 10 keyless entries

Low power operation mode

Handset or hands-free operation

Keypad or button operation (up to 24 buttons)

Stores up to 12 phone numbers (primary numbers)

Two alternative numbers per primary number (local alt. number)

1000-number Caller Line Identification (CLI) for door access control

Two global alternative numbers if required (over-rides local alt. numbers)



Line Powered

A completely PSTN line powered unit that will supply sufficient audio level for low noise environments. It features easy programming for quick installation.

Externally Powered

Designed for general purpose situations, a PSTN doorstation featuring an interactive voice prompt for quick and easy programming (power pack supplied).

VoIP

An Ethernet connected doorstation that provides Voice over Internet communication technology. Giving you the power of our PSTN base units in an IP format.

4G/GSM

A wireless mobile phone intercom system using the 4G network. Powered by external 12V DC Power supply or Battery & Solar Powered.

FEATURE	Line Powered	Externally powered	VoIP
Power Requirements	Line Powered 24-50dc 100mA	PSU 9-20Vdc 250mA	PoE / PSU 9-50Vdc 300mA
Standby Current	22mA(minimum)	10mA @ 18Vdc	60mA @ 13Vdc
Off Hook Current	PABX dependant	40mA @ 18Vdc	300mA @ 13Vdc
Relay Rating (Non Inductive Voltage Free)	0.5A@60Vdc/40Vac SELVorTNV	1A@50Vdc/30Vac SELVorTNV	1A@60Vdc/40Vac SELVorTNV
Dimensions Vertical Units	H 270mm W 130mm D 45mm	H 270mm W 130mm D 45mm	H 270mm W 130mm D 45mm
Dimensions Horizontal Units	H 130mm W 270mm D 45mm	H 130mm W 270mm D 45mm	H 130mm W 270mm D 45mm
Wall Cut-Out (mm)	225 x 115 x 40	225 x 115 x 40	225 x 115 x 40
SPL Ringer Output Level	>78dBa @ 1 metre	>85dBa @ 1 metre	>85dBa @ 1 metre
REN	0.7	<1	N/A
Operating Temperature Range	-10 to +60	-10 to +60	0°C to +50°C
Maximum Call Buttons	6	8	16 (custom panel)