

WEATHER TOUGH RANGE



FIRE RED



GENERAL INDUSTRIAL YELLOW



BLUE

ENCLOSURE

The WeatherTough enclosure is rated **IP65**. Made from vandal resistant cast Aluminium Alloy with heavy duty powder coating on the enclosure. You have a choice of powder coated colours: Signal Red, Yellow and Space Blue.

Size: H 321 mm x W 205 mm x D 123.5 mm - **Weight material:** 5kg cast aluminium



IP RATING



IP is an acronym for **Ingress Protection**.

Each IP rating has 2 numbers. The first number refers to the protection against solid objects (dust, etc) and the second number refers to liquid protection.

The **Weather Tough range** is rated at: **6** (Dust tight) **5** (Protection against water jets)



Ingress Protection
Marking



SOLID
Protection WATER
Protection

01 Australian
Made

02 User
Friendly

03 Low Cost
Ownership

04 Vandal
Resistant

05 Weather
Tough

The Weather Tough Range is designed for Australia's rugged locations and toughest conditions.

It is well suited to motorways, tunnels, bridges, mining and construction sites as well as many business and commercial settings.

The WeatherTough enclosure is rated **IP65**. Made from vandal resistant cast Aluminium Alloy with heavy duty powder coating on the enclosure.

Choose from the following options: VoIP, Line Powered and 3G/GSM - Handset or Loud speaking - Armoured Cord or Rugged Curly Cord. The Weather Tough can be customised to any requirements. Please contact us for more information and to discuss the options.

FEATURES

Auto dialling

Remote level control speaker & microphone

Remote relay activation door release (standard on VoIP, LP, 3G/GSM & DCOM)

Remote programming facilities

Remote diagnostic testing (optional)

Self identification

Powder coated (space blue or emergency yellow as standard)

Door locks-open 180° & auto-closes 150°

Stainless Steel Spring Hinge

