


# 3. Shannon's Secrecy System

## 3. Shannon's Secrecy System

- Coding scheme
- Perfect secrecy
- Crypto lemma
- One-time pad

# Shannon's Secrecy System




- Shannon proposed the idea of measuring quantitatively the secrecy level of encryption systems
- Shannon's model is often called *Shannon's secrecy system* or *Shannon's cypher system*



C. E. Shannon, "Communication Theory of Secrecy Systems," *Bell Syst. Tech. J.*, vol. 28, no. 4, pp. 656–715, Oct. 1949


## Shannon's Secrecy System (2)

---



- Transmitter (Alice) communicates with a legitimate receiver (Bob) over a **noiseless channel**, while an eavesdropper (Eve) overhears all signals sent over the channel
- To prevent Eve from retrieving any information, Alice encodes her messages into codewords by means of a secret key, which is **known to Bob**, but **unknown to Eve**

# Coding Scheme



- Quantities represented by random variables


- messages  $M \in \mathcal{M}$
- codewords  $X \in \mathcal{X}$
- secret keys  $K \in \mathcal{K}$

- Encoder  $e$  and decoder  $d$  are functions

$$e : \mathcal{M} \times \mathcal{K} \rightarrow \mathcal{X} \quad \text{and} \quad d : \mathcal{X} \times \mathcal{K} \rightarrow \mathcal{M}$$

► The pair  $(e, d)$  is called *coding scheme*

## Coding Scheme (2)



- The legitimate receiver is assumed to *retrieve message without error*, i.e.,

$$M = d(X, K) \quad \text{and} \quad X = e(M, K)$$

- Although Eve has no knowledge about the secret key  $K$ , she is assumed to know the **encoding function  $e$**  and the **decoding function  $d$**

# Perfect Secrecy

---

- Secrecy is measured in terms of the conditional entropy  $H(M|X)$ , which we call eavesdropper's *equivocation*
- Intuitively, equivocation represents Eve's uncertainty about the messages after intercepting the codewords
- A coding scheme achieves *perfect secrecy* if

$$H(M|X) = H(M) \quad \text{or, equivalently,} \quad I(M; X) = 0$$

- We call  $I(M; X)$  the *leakage of information* to the eavesdropper
- In other words, perfect secrecy is achieved if codewords  $X$  are statistically independent of messages  $M$
- This differs from the traditional assessment based on computational complexity: it provides a *quantitative metric to measure secrecy* and it *disregards the computational power of Eve*
- Perfect secrecy guarantees that Eve's optimal attack is to **guess the message  $M$  at random** and that **there exists no algorithm that could extract any information about  $M$  from  $X$**

# Perfect Secrecy

---

- Secrecy is measured in terms of the conditional entropy  $H(M|X)$ , which we call eavesdropper's *equivocation*
- Intuitively, equivocation represents Eve's uncertainty about the messages after intercepting the codewords
- A coding scheme achieves *perfect secrecy* if

$$H(M|X) = H(M) \quad \text{or, equivalently,} \quad I(M; X) = 0$$

- We call  $I(M; X)$  the *leakage of information* to the eavesdropper
- In other words, perfect secrecy is achieved if codewords  $X$  are statistically independent of messages  $M$
- This differs from the traditional assessment based on computational complexity: it provides a *quantitative metric to measure secrecy* and it *disregards the computational power of Eve*
- Perfect secrecy guarantees that Eve's optimal attack is to *guess the message  $M$  at random* and that *there exists no algorithm that could extract any information about  $M$  from  $X$*



# Perfect Secrecy

---

- Secrecy is measured in terms of the conditional entropy  $H(M|X)$ , which we call eavesdropper's *equivocation*
- Intuitively, equivocation represents Eve's uncertainty about the messages after intercepting the codewords
- A coding scheme achieves *perfect secrecy* if

$$H(M|X) = H(M) \quad \text{or, equivalently,} \quad I(M; X) = 0$$

- We call  $I(M; X)$  the *leakage of information* to the eavesdropper
- In other words, perfect secrecy is achieved if codewords  $X$  are statistically independent of messages  $M$
- This differs from the traditional assessment based on computational complexity: it provides a *quantitative metric to measure secrecy* and it *disregards the computational power of Eve*
- Perfect secrecy guarantees that Eve's optimal attack is to **guess the message  $M$  at random** and that **there exists no algorithm that could extract any information about  $M$  from  $X$**

## Perfect Secrecy (2)

### Proposition

If a coding scheme for Shannon's secrecy system achieves *perfect secrecy*, then

$$H(K) \geq H(M).$$

### Proof:

- Consider a coding scheme that achieves perfect secrecy; then by assumption

$$H(M|X) = H(M)$$

- In addition, since messages  $M$  are decoded without errors upon observing  $X$  and  $K$ , *Fano's inequality* ensures that

$$H(M|X, K) = 0$$

## Perfect Secrecy (2)

### Proposition

If a coding scheme for Shannon's secrecy system achieves *perfect secrecy*, then

$$H(K) \geq H(M).$$

### Proof:

- Consider a coding scheme that achieves perfect secrecy; then by assumption

$$H(M|X) = H(M)$$

- In addition, since messages  $M$  are decoded without errors upon observing  $X$  and  $K$ , *Fano's inequality* ensures that

$$H(M|X, K) = 0$$

## Perfect Secrecy (2)

### Proposition

If a coding scheme for Shannon's secrecy system achieves *perfect secrecy*, then

$$H(K) \geq H(M).$$

### Proof:

- Consider a coding scheme that achieves perfect secrecy; then by assumption

$$H(M|X) = H(M)$$

- In addition, since messages  $M$  are decoded without errors upon observing  $X$  and  $K$ , *Fano's inequality* ensures that

$$H(M|X, K) = 0$$

## Perfect Secrecy (3)

---

- We have

$$\begin{aligned} H(K) &\geq H(K) - H(K|X, M) && \text{(since } H(K|X, M) \geq 0\text{)} \\ &\geq H(K|X) - H(K|X, M) && \text{(conditioning reduces entropy)} \\ &= I(K; M|X) \\ &= H(M|X) - H(M|K, X) \\ &= H(M|X) && \text{(Fano's inequality)} \\ &= H(M) && \text{(perfect secrecy)} \end{aligned}$$

□

## Perfect Secrecy (3)

---

- We have

$$\begin{aligned} H(K) &\geq H(K) - H(K|X, M) && \text{(since } H(K|X, M) \geq 0\text{)} \\ &\geq H(K|X) - H(K|X, M) && \text{(conditioning reduces entropy)} \\ &= I(K; M|X) \\ &= H(M|X) - H(M|K, X) \\ &= H(M|X) && \text{(Fano's inequality)} \\ &= H(M) && \text{(perfect secrecy)} \end{aligned}$$



## Perfect Secrecy (3)

---

- We have

$$\begin{aligned} H(K) &\geq H(K) - H(K|X, M) && \text{(since } H(K|X, M) \geq 0\text{)} \\ &\geq H(K|X) - H(K|X, M) && \text{(conditioning reduces entropy)} \\ &= I(K; M|X) \\ &= H(M|X) - H(M|K, X) \\ &= H(M|X) && \text{(Fano's inequality)} \\ &= H(M) && \text{(perfect secrecy)} \end{aligned}$$



## Perfect Secrecy (3)

---

- We have

$$\begin{aligned} H(K) &\geq H(K) - H(K|X, M) && \text{(since } H(K|X, M) \geq 0\text{)} \\ &\geq H(K|X) - H(K|X, M) && \text{(conditioning reduces entropy)} \\ &= I(K; M|X) \\ &= H(M|X) - H(M|K, X) \\ &= H(M|X) && \text{(Fano's inequality)} \\ &= H(M) && \text{(perfect secrecy)} \end{aligned}$$





## Perfect Secrecy (3)

---

- We have

$$\begin{aligned} H(K) &\geq H(K) - H(K|X, M) && \text{(since } H(K|X, M) \geq 0\text{)} \\ &\geq H(K|X) - H(K|X, M) && \text{(conditioning reduces entropy)} \\ &= I(K; M|X) \\ &= H(M|X) - H(M|K, X) \\ &= H(M|X) && \text{(Fano's inequality)} \\ &= H(M) && \text{(perfect secrecy)} \end{aligned}$$



## Perfect Secrecy (3)

---

- We have

$$\begin{aligned} H(K) &\geq H(K) - H(K|X, M) && \text{(since } H(K|X, M) \geq 0\text{)} \\ &\geq H(K|X) - H(K|X, M) && \text{(conditioning reduces entropy)} \\ &= I(K; M|X) \\ &= H(M|X) - H(M|K, X) \\ &= H(M|X) && \text{(Fano's inequality)} \\ &= H(M) && \text{(perfect secrecy)} \end{aligned}$$



## Perfect Secrecy (4)

---

- Result states that it is **necessary to use at least one secret-key bit for each message bit to achieve perfect secrecy**
- If the number of possible messages, keys, and codewords is the same, we obtain a more precise result and establish **necessary and sufficient** conditions for perfect secrecy

### Theorem

*If  $|\mathcal{M}| = |\mathcal{X}| = |\mathcal{K}|$ , a coding scheme for Shannon's secrecy system achieves perfect secrecy if and only if*

- *for each pair  $(m, k) \in \mathcal{M} \times \mathcal{K}$  there exists a **unique key  $k \in \mathcal{K}$  such that  $x = e(m, k)$***
- *the **key  $k$  is uniformly distributed in  $\mathcal{K}$***

## Perfect Secrecy (4)

- Result states that it is **necessary to use at least one secret-key bit for each message bit to achieve perfect secrecy**
- If the number of possible messages, keys, and codewords is the same, we obtain a more precise result and establish **necessary and sufficient** conditions for perfect secrecy

### Theorem

If  $|\mathcal{M}| = |\mathcal{X}| = |\mathcal{K}|$ , a coding scheme for Shannon's secrecy system achieves perfect secrecy if and only if

- for each pair  $(m, k) \in \mathcal{M} \times \mathcal{K}$  there exists a **unique key  $k \in \mathcal{K}$**  such that  $x = e(m, k)$
- the **key  $k$  is uniformly distributed in  $\mathcal{K}$**

## Perfect Secrecy (5)

---

### Proof:

- First, we prove that conditions are **necessary**:
- Consider coding scheme achieving perfect secrecy with  $|\mathcal{M}| = |\mathcal{X}| = |\mathcal{K}|$
- Note that  $P_X(x) > 0$  for all  $x \in \mathcal{X}$  since otherwise some codewords would never be used and could be removed from  $\mathcal{X}$  which would violate the assumption  $|\mathcal{M}| = |\mathcal{X}|$
- Since  $M$  and  $X$  are independent, this implies  $P_{X|M}(x|m) = P_X(x) > 0$  for all pairs  $(m, x) \in \mathcal{M} \times \mathcal{X}$ .
- In other words, for all messages  $m \in \mathcal{M}$ , the encoder can output all possible codewords in  $\mathcal{X}$ , thus,

$$\forall m \in \mathcal{M} : \quad \mathcal{X} = \{e(m, k) : k \in \mathcal{K}\}$$

- Because  $|\mathcal{X}| = |\mathcal{K}|$ , for all  $(m, x) \in \mathcal{M} \times \mathcal{X}$  there must be a **unique key**  $k \in \mathcal{K}$  such that  $x = e(m, k)$

## Perfect Secrecy (5)

---

### Proof:

- First, we prove that conditions are **necessary**:
- Consider coding scheme achieving perfect secrecy with  $|\mathcal{M}| = |\mathcal{X}| = |\mathcal{K}|$
- Note that  $P_X(x) > 0$  for all  $x \in \mathcal{X}$  since otherwise some codewords would never be used and could be removed from  $\mathcal{X}$  which would violate the assumption  $|\mathcal{M}| = |\mathcal{X}|$
- Since  $M$  and  $X$  are independent, this implies  $P_{X|M}(x|m) = P_X(x) > 0$  for all pairs  $(m, x) \in \mathcal{M} \times \mathcal{X}$ .
- In other words, for all messages  $m \in \mathcal{M}$ , the encoder can output all possible codewords in  $\mathcal{X}$ , thus,

$$\forall m \in \mathcal{M} : \quad \mathcal{X} = \{e(m, k) : k \in \mathcal{K}\}$$

- Because  $|\mathcal{X}| = |\mathcal{K}|$ , for all  $(m, x) \in \mathcal{M} \times \mathcal{X}$  there must be a **unique key**  $k \in \mathcal{K}$  such that  $x = e(m, k)$

## Perfect Secrecy (5)

---

### Proof:

- First, we prove that conditions are **necessary**:
- Consider coding scheme achieving perfect secrecy with  $|\mathcal{M}| = |\mathcal{X}| = |\mathcal{K}|$
- Note that  $P_X(x) > 0$  for all  $x \in \mathcal{X}$  since otherwise some codewords would never be used and could be removed from  $\mathcal{X}$  which would violate the assumption  $|\mathcal{M}| = |\mathcal{X}|$
- Since  $M$  and  $X$  are independent, this implies  $P_{X|M}(x|m) = P_X(x) > 0$  for all pairs  $(m, x) \in \mathcal{M} \times \mathcal{X}$ .
- In other words, for all messages  $m \in \mathcal{M}$ , the encoder can output all possible codewords in  $\mathcal{X}$ , thus,

$$\forall m \in \mathcal{M} : \quad \mathcal{X} = \{e(m, k) : k \in \mathcal{K}\}$$

- Because  $|\mathcal{X}| = |\mathcal{K}|$ , for all  $(m, x) \in \mathcal{M} \times \mathcal{X}$  there must be a **unique key**  $k \in \mathcal{K}$  such that  $x = e(m, k)$

## Perfect Secrecy (6)

---

- Now, fix an arbitrary codeword  $x^* \in \mathcal{X}$ . For every message  $m \in \mathcal{M}$ , let  $k_m$  be the unique key such that  $x^* = e(m, k_m)$
- Then  $P_K(k_m) = P_{X|M}(x^*|m)$  and  $\mathcal{K} = \{k_m : m \in \mathcal{M}\}$ . Using Bayes' rule, we obtain

$$\begin{aligned}P_K(k_m) &= P_{X|M}(x^*|m) \\&= \frac{P_{M|X}(m|x^*)P_X(x^*)}{P_M(m)} \\&= P_X(x^*)\end{aligned}$$

where the last equality follows from  $P_{M|X}(m|x^*) = P_M(m)$  due to independence of  $M$  and  $X$

⇒  $P_K(k_m)$  takes on the same values for all  $m \in \mathcal{M}$  which implies that  $K$  is *uniformly distributed in  $\mathcal{K}$*



## Perfect Secrecy (6)

---

- Now, fix an arbitrary codeword  $x^* \in \mathcal{X}$ . For every message  $m \in \mathcal{M}$ , let  $k_m$  be the unique key such that  $x^* = e(m, k_m)$
- Then  $P_K(k_m) = P_{X|M}(x^*|m)$  and  $\mathcal{K} = \{k_m : m \in \mathcal{M}\}$ . Using Bayes' rule, we obtain

$$\begin{aligned}P_K(k_m) &= P_{X|M}(x^*|m) \\&= \frac{P_{M|X}(m|x^*)P_X(x^*)}{P_M(m)} \\&= P_X(x^*)\end{aligned}$$

where the last equality follows from  $P_{M|X}(m|x^*) = P_M(m)$  due to independence of  $M$  and  $X$

⇒  $P_K(k_m)$  takes on the same values for all  $m \in \mathcal{M}$  which implies that  $K$  is uniformly distributed in  $\mathcal{K}$

## Perfect Secrecy (6)

---


- Now, fix an arbitrary codeword  $x^* \in \mathcal{X}$ . For every message  $m \in \mathcal{M}$ , let  $k_m$  be the unique key such that  $x^* = e(m, k_m)$
- Then  $P_K(k_m) = P_{X|M}(x^*|m)$  and  $\mathcal{K} = \{k_m : m \in \mathcal{M}\}$ . Using Bayes' rule, we obtain

$$\begin{aligned}P_K(k_m) &= P_{X|M}(x^*|m) \\&= \frac{P_{M|X}(m|x^*)P_X(x^*)}{P_M(m)} \\&= P_X(x^*)\end{aligned}$$

where the last equality follows from  $P_{M|X}(m|x^*) = P_M(m)$  due to independence of  $M$  and  $X$

➡  $P_K(k_m)$  takes on the same values for all  $m \in \mathcal{M}$  which implies that  $K$  is *uniformly distributed in  $\mathcal{K}$*

## Perfect Secrecy (7)



- Now, we show that the conditions are also **sufficient**
- Since  $|\mathcal{M}| = |\mathcal{X}| = |\mathcal{K}|$ , we can assume w.l.o.g. that  $\mathcal{M} = \mathcal{X} = \mathcal{K} = \{0, 1, 2, \dots, |\mathcal{M}| - 1\}$
- Consider a coding scheme shown above which is also called *Vernam cipher* or *one-time pad*
- To send a message  $m \in \mathcal{M}$ , Alice transmits  $x = m \oplus k$  with  $k$  is the realization of a key  $K$ , which is independent of the message and uniformly distributed on  $\mathcal{M}$  and  $\oplus$  is the modulo- $|\mathcal{M}|$  addition

## Perfect Secrecy (8)

- Since  $k$  is known to Bob, he can decode the message  $m$  from the codeword  $x$  without error by computing

$$x \oplus k = m \oplus k \ominus k = m$$

where  $\ominus$  is the modulo- $|\mathcal{M}|$  subtraction

- In addition, this guarantees that for all  $x \in \mathcal{X}$

$$P_X(x) = \sum_{k \in \mathcal{M}} P_{X|K}(x|k)P_K(k) = \sum_{k \in \mathcal{M}} P_M(x \oplus k) \frac{1}{|\mathcal{M}|} = \frac{1}{|\mathcal{M}|}$$

and consequently

$$\begin{aligned} I(M; X) &= H(X) - H(X|M) \\ &= H(X) - H(K|M) \quad (\text{one-to-one mapping between } X \text{ and } K) \\ &= H(X) - H(K) \quad (M \text{ and } K \text{ are independent}) \\ &= \log |\mathcal{M}| - \log |\mathcal{M}| = 0 \end{aligned}$$

- Note that this result holds for any probability distribution of the message  $P_M$  for which  $\forall m \in \mathcal{M} : P_M(m) > 0$  □

## Perfect Secrecy (8)

- Since  $k$  is known to Bob, he can decode the message  $m$  from the codeword  $x$  without error by computing

$$x \oplus k = m \oplus k \ominus k = m$$

where  $\ominus$  is the modulo- $|\mathcal{M}|$  subtraction

- In addition, this guarantees that for all  $x \in \mathcal{X}$

$$P_X(x) = \sum_{k \in \mathcal{M}} P_{X|K}(x|k)P_K(k) = \sum_{k \in \mathcal{M}} P_M(x \oplus k) \frac{1}{|\mathcal{M}|} = \frac{1}{|\mathcal{M}|}$$

and consequently

$$\begin{aligned} I(M; X) &= H(X) - H(X|M) \\ &= H(X) - H(K|M) \quad (\text{one-to-one mapping between } X \text{ and } K) \\ &= H(X) - H(K) \quad (M \text{ and } K \text{ are independent}) \\ &= \log |\mathcal{M}| - \log |\mathcal{M}| = 0 \end{aligned}$$

- Note that this result holds for any probability distribution of the message  $P_M$  for which  $\forall m \in \mathcal{M} : P_M(m) > 0$  □

## Perfect Secrecy (8)

- Since  $k$  is known to Bob, he can decode the message  $m$  from the codeword  $x$  without error by computing

$$x \oplus k = m \oplus k \ominus k = m$$

where  $\ominus$  is the modulo- $|\mathcal{M}|$  subtraction

- In addition, this guarantees that for all  $x \in \mathcal{X}$

$$P_X(x) = \sum_{k \in \mathcal{M}} P_{X|K}(x|k)P_K(k) = \sum_{k \in \mathcal{M}} P_M(x \oplus k) \frac{1}{|\mathcal{M}|} = \frac{1}{|\mathcal{M}|}$$

and consequently

$$\begin{aligned} I(M; X) &= H(X) - H(X|M) \\ &= H(X) - H(K|M) \quad (\text{one-to-one mapping between } X \text{ and } K) \\ &= H(X) - H(K) \quad (M \text{ and } K \text{ are independent}) \\ &= \log |\mathcal{M}| - \log |\mathcal{M}| = 0 \end{aligned}$$

- Note that this result holds for any probability distribution of the message  $P_M$  for which  $\forall m \in \mathcal{M} : P_M(m) > 0$  □

## Perfect Secrecy (8)

- Since  $k$  is known to Bob, he can decode the message  $m$  from the codeword  $x$  without error by computing

$$x \oplus k = m \oplus k \ominus k = m$$

where  $\ominus$  is the modulo- $|\mathcal{M}|$  subtraction

- In addition, this guarantees that for all  $x \in \mathcal{X}$

$$P_X(x) = \sum_{k \in \mathcal{M}} P_{X|K}(x|k)P_K(k) = \sum_{k \in \mathcal{M}} P_M(x \oplus k) \frac{1}{|\mathcal{M}|} = \frac{1}{|\mathcal{M}|}$$

and consequently

$$\begin{aligned} I(M; X) &= H(X) - H(X|M) \\ &= H(X) - H(K|M) \quad (\text{one-to-one mapping between } X \text{ and } K) \\ &= H(X) - H(K) \quad (M \text{ and } K \text{ are independent}) \\ &= \log |\mathcal{M}| - \log |\mathcal{M}| = 0 \end{aligned}$$

- Note that this result holds for any probability distribution of the message  $P_M$  for which  $\forall m \in \mathcal{M} : P_M(m) > 0$  □

## Perfect Secrecy (8)

- Since  $k$  is known to Bob, he can decode the message  $m$  from the codeword  $x$  without error by computing

$$x \oplus k = m \oplus k \ominus k = m$$

where  $\ominus$  is the modulo- $|\mathcal{M}|$  subtraction

- In addition, this guarantees that for all  $x \in \mathcal{X}$

$$P_X(x) = \sum_{k \in \mathcal{M}} P_{X|K}(x|k)P_K(k) = \sum_{k \in \mathcal{M}} P_M(x \oplus k) \frac{1}{|\mathcal{M}|} = \frac{1}{|\mathcal{M}|}$$

and consequently

$$\begin{aligned} I(M; X) &= H(X) - H(X|M) \\ &= H(X) - H(K|M) \quad (\text{one-to-one mapping between } X \text{ and } K) \\ &= H(X) - H(K) \quad (M \text{ and } K \text{ are independent}) \\ &= \log |\mathcal{M}| - \log |\mathcal{M}| = 0 \end{aligned}$$

- Note that this result holds for any probability distribution of the message  $P_M$  for which  $\forall m \in \mathcal{M} : P_M(m) > 0$





# Crypto Lemma

- One-time pad guarantees perfect secrecy; so-called “*crypto lemma*”
- Holds under very general conditions (in particular, the finite alphabet  $\mathcal{M}$  can be replaced by a compact abelian group  $\mathcal{G}$ )

## Lemma (Crypto Lemma)

*Let  $(\mathcal{G}, +)$  be a compact abelian group with binary operation  $+$  and let  $X = M + K$  where  $M$  and  $K$  are random variables over  $\mathcal{G}$  and  $K$  is independent of  $M$  and uniform over  $\mathcal{G}$ . Then  $X$  is independent of  $M$  and uniform over  $\mathcal{G}$ .*

- Although previous analysis shows existence of coding schemes that achieve perfect secrecy, it is an unsatisfactory result. In fact, since *one-time pad requires a new key bit for each message bit*, it essentially replaces the problem of secure communication by that of secret-key distribution.
- Next, we show that this stems from the absence of noise at the physical layer. In particular, noise affects Eve's observation

# Crypto Lemma

- One-time pad guarantees perfect secrecy; so-called “*crypto lemma*”
- Holds under very general conditions (in particular, the finite alphabet  $\mathcal{M}$  can be replaced by a compact abelian group  $\mathcal{G}$ )

## Lemma (Crypto Lemma)

*Let  $(\mathcal{G}, +)$  be a compact abelian group with binary operation  $+$  and let  $X = M + K$  where  $M$  and  $K$  are random variables over  $\mathcal{G}$  and  $K$  is independent of  $M$  and uniform over  $\mathcal{G}$ . Then  $X$  is independent of  $M$  and uniform over  $\mathcal{G}$ .*

- Although previous analysis shows **existence of coding schemes that achieve perfect secrecy**, it is an unsatisfactory result. In fact, since **one-time pad requires a new key bit for each message bit**, it essentially replaces the problem of secure communication by that of secret-key distribution.
- Next, we show that this stems from the **absence of noise at the physical layer**. In particular, noise affects Eve's observation