

Keeyon Ebrahimi
HW1

Problem 1

a) $W = [woof, meow, squeak]$
 $D1 = [2, 1, 0]$
 $D2 = [2, 0, 1]$

$$\cos \text{ similarity} = \frac{D1 \cdot D2}{||D1|| * ||D2||}$$

$$||D1|| = ||D2|| = \sqrt{2^2 + 1^2 + 0^2} = \sqrt{5}$$

$$D1 \cdot D2 = 4$$

$$\text{Solution} = \frac{4}{5}$$

b) $IDF = \log(\frac{N}{n_i})$
 $W = [woof, meow, squeak]$
 $IDF \text{ Vector} = [\log(\frac{2}{2}), \log(\frac{2}{1}), \log(\frac{2}{1})]$
 $\mu D1 = [0, 0.6931, 0]$
 $\mu D2 = [0, 0, 0.6931]$

$$\cos \text{ similarity} = \frac{\mu D1 \cdot \mu D2}{||\mu D1|| * ||\mu D2||}$$

$$\mu D1 \cdot \mu D2 = 0$$

$$\text{Solution} = 0$$

c) $W = [woof, meow, squeak]$
 $IDF \text{ Vector} = [\log(\frac{3}{2}), \log(\frac{3}{2}), \log(\frac{3}{2})]$
 $\mu D1 = [0.811, 0.405465, 0]$
 $\mu D2 = [0.811, 0, 0.405465]$

$$\mu D1 \cdot \mu D2 = 0.65761$$

$$||\mu D1|| = \sqrt{5} \log(\frac{3}{2})$$

$$||\mu D2|| = \sqrt{5} \log\left(\frac{3}{2}\right)$$

$$Solution = 0.800003$$

Problem 2

a) $P(+ | \text{"great food served"}) =$

$$P(+)*P(\text{"great"} | +)*P(\text{"food"} | +)*P(\text{"served"} | +) =$$

$$\left(\frac{5}{10}\right) * \left(\frac{5}{10}\right) * \left(\frac{5}{10}\right) * \left(\frac{0}{10}\right) =$$

$$Solution = 0$$

$$P(- | \text{"great food served"}) =$$

$$P(-)*P(\text{"great"} | -)*P(\text{"food"} | -)*P(\text{"served"} | -) =$$

$$\left(\frac{5}{10}\right) * \left(\frac{0}{11}\right) * \left(\frac{5}{11}\right) * \left(\frac{1}{11}\right) =$$

$$Solution = 0$$

b) **If we were to apply Laplace smoothing, then $P(+ | \text{"great food served"})$ will be larger**

c) Using Jet