



Localhost Scan

Report generated by Tenable Nessus™

Mon, 17 Nov 2025 16:56:34 India Standard Time

TABLE OF CONTENTS

Vulnerabilities by Plugin

• 51192 (1) - SSL Certificate Cannot Be Trusted.....	5
• 14272 (35) - Netstat Portscanner (SSH).....	7
• 10736 (8) - DCE Services Enumeration.....	11
• 11154 (7) - Unknown Service Detection: Banner Retrieval.....	16
• 22964 (4) - Service Detection.....	19
• 11011 (2) - Microsoft Windows SMB Service Detection.....	20
• 10107 (1) - HTTP Server Type and Version.....	21
• 10147 (1) - Nessus Server Detection.....	22
• 10150 (1) - Windows NetBIOS / SMB Remote Host Information Disclosure.....	23
• 10785 (1) - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure.....	24
• 10863 (1) - SSL Certificate Information.....	25
• 11936 (1) - OS Identification.....	27
• 12053 (1) - Host Fully Qualified Domain Name (FQDN) Resolution.....	28
• 19506 (1) - Nessus Scan Information.....	29
• 21643 (1) - SSL Cipher Suites Supported.....	31
• 24260 (1) - HyperText Transfer Protocol (HTTP) Information.....	33
• 42410 (1) - Microsoft Windows NTLMSSP Authentication Request Remote Network Name Disclosure.....	35
• 42822 (1) - Strict Transport Security (STS) Detection.....	36
• 45590 (1) - Common Platform Enumeration (CPE).....	37
• 46180 (1) - Additional DNS Hostnames.....	38
• 54615 (1) - Device Type.....	39
• 56984 (1) - SSL / TLS Versions Supported.....	40
• 57041 (1) - SSL Perfect Forward Secrecy Cipher Suites Supported.....	41
• 64582 (1) - Netstat Connection Information.....	43
• 97993 (1) - OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library).....	44
• 100871 (1) - Microsoft Windows SMB Versions Supported (remote check).....	45

• 106716 (1) - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check).....	46
• 110723 (1) - Target Credential Status by Authentication Protocol - No Credentials Provided.....	47
• 117886 (1) - OS Security Patch Assessment Not Available.....	49
• 136318 (1) - TLS Version 1.2 Protocol Detection.....	51
• 138330 (1) - TLS Version 1.3 Protocol Detection.....	52
• 209654 (1) - OS Fingerprints Detected.....	53

Vulnerabilities by Plugin

51192 (1) - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

192.168.1.27 (tcp/8834/www)

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : O=Nessus Users United/OU=Nessus Server/L=New York/C=US/ST=NY/CN=AMAL  
| -Issuer  : O=Nessus Users United/OU=Nessus Certification Authority/L=New York/C=US/ST=NY/CN=Nessus  
            Certification Authority
```

14272 (35) - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin runs on Windows using netstat.exe if the target is localhost (scanner scanning itself) or a Windows host authenticated via SSH with the ability to run netstat.exe.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/10/29

Plugin Output

192.168.1.27 (udp/123)

```
Port 123/udp was found to be open
```

192.168.1.27 (tcp/135/epmap)

```
Port 135/tcp was found to be open
```

192.168.1.27 (udp/137)

```
Port 137/udp was found to be open
```

192.168.1.27 (udp/138)

Port 138/udp was found to be open

192.168.1.27 (tcp/139/smb)

Port 139/tcp was found to be open

192.168.1.27 (tcp/445/cifs)

Port 445/tcp was found to be open

192.168.1.27 (udp/500)

Port 500/udp was found to be open

192.168.1.27 (udp/1900)

Port 1900/udp was found to be open

192.168.1.27 (udp/4500)

Port 4500/udp was found to be open

192.168.1.27 (tcp/5040)

Port 5040/tcp was found to be open

192.168.1.27 (udp/5050)

Port 5050/udp was found to be open

192.168.1.27 (udp/5353)

Port 5353/udp was found to be open

192.168.1.27 (udp/5355)

Port 5355/udp was found to be open

192.168.1.27 (tcp/7070)

Port 7070/tcp was found to be open

192.168.1.27 (tcp/8834/www)

Port 8834/tcp was found to be open

192.168.1.27 (tcp/49664/dce-rpc)

Port 49664/tcp was found to be open

192.168.1.27 (tcp/49665/dce-rpc)

Port 49665/tcp was found to be open

192.168.1.27 (tcp/49668/dce-rpc)

Port 49668/tcp was found to be open

192.168.1.27 (tcp/49669/dce-rpc)

Port 49669/tcp was found to be open

192.168.1.27 (tcp/49670/dce-rpc)

Port 49670/tcp was found to be open

192.168.1.27 (tcp/49680)

Port 49680/tcp was found to be open

192.168.1.27 (tcp/49683)

Port 49683/tcp was found to be open

192.168.1.27 (tcp/49686/dce-rpc)

Port 49686/tcp was found to be open

192.168.1.27 (tcp/49687)

Port 49687/tcp was found to be open

192.168.1.27 (tcp/49704)

Port 49704/tcp was found to be open

192.168.1.27 (tcp/49709)

Port 49709/tcp was found to be open

192.168.1.27 (tcp/49710)

Port 49710/tcp was found to be open

192.168.1.27 (tcp/49712)

Port 49712/tcp was found to be open

192.168.1.27 (tcp/49717)

Port 49717/tcp was found to be open

192.168.1.27 (tcp/49718)

Port 49718/tcp was found to be open

192.168.1.27 (udp/50001)

Port 50001/udp was found to be open

192.168.1.27 (udp/57313)

Port 57313/udp was found to be open

192.168.1.27 (udp/57315)

Port 57315/udp was found to be open

192.168.1.27 (udp/64220)

Port 64220/udp was found to be open

192.168.1.27 (udp/64221)

Port 64221/udp was found to be open

10736 (8) - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

192.168.1.27 (tcp/135/epmap)

The following DCERPC services are available locally :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : samss lpc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : SidKey Local End Point

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : protected_storage

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service

```

Type : Local RPC service
Named pipe : lsasspirpc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : lsapolicylookup

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : LSA_EAS_ENDPOINT

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : LSA_IDPEXT_ENDPOINT

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : lsacap

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc [...]

```

192.168.1.27 (tcp/445/cifs)

```

The following DCERPC services are available remotely :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 650a7e26-eab8-5533-ce43-9cldfcell1511, version 1.0
Description : Unknown RPC service
Annotation : Vpn APIs
Type : Remote RPC service
Named pipe : \PIPE\ROUTER
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 7f1343fe-50a9-4927-a778-0c5859517bac, version 1.0
Description : Unknown RPC service
Annotation : DfsDs service
Type : Remote RPC service
Named pipe : \PIPE\wkssvc
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Windows Event Log
Type : Remote RPC service
Named pipe : \pipe\eventlog
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service

```

```

Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 33d84484-3626-47ee-8c6f-e7e98b113be1, version 2.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\AMAL

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3a9ef155-691d-4449-8d05-09ad57031823, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\AMAL

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : U [...]

```

192.168.1.27 (tcp/49664/dce-rpc)

The following DCERPC services are available on TCP port 49664 :

```

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.1.27

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.1.27

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2.0
Description : Unknown RPC service
Annotation : KeyIso
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.1.27

Object UUID : 00000000-0000-0000-0000-000000000000

```

```
UUID : 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.1.27
```

192.168.1.27 (tcp/49665/dce-rpc)

The following DCERPC services are available on TCP port 49665 :

```
Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49665
IP : 192.168.1.27
```

192.168.1.27 (tcp/49668/dce-rpc)

The following DCERPC services are available on TCP port 49668 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49668
IP : 192.168.1.27
```

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3a9ef155-691d-4449-8d05-09ad57031823, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49668
IP : 192.168.1.27
```

192.168.1.27 (tcp/49669/dce-rpc)

The following DCERPC services are available on TCP port 49669 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Windows Event Log
Type : Remote RPC service
TCP Port : 49669
IP : 192.168.1.27
```

192.168.1.27 (tcp/49670/dce-rpc)

The following DCERPC services are available on TCP port 49670 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
```

```
UUID : 12345678-1234-abcd-ef00-0123456789ab, version 1.0
Description : IPsec Services (Windows XP & 2003)
Windows process : lsass.exe
Type : Remote RPC service
TCP Port : 49670
IP : 192.168.1.27
```

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 0b6edbfa-4a24-4fc6-8a23-942bleca65dl, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49670
IP : 192.168.1.27
```

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : ae33069b-a2a8-46ee-a235-ddfd339be281, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49670
IP : 192.168.1.27
```

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 4a452661-8290-4b36-8fbe-7f4093a94978, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49670
IP : 192.168.1.27
```

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 76f03f96-cdfd-44fc-a22c-64950a001209, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49670
IP : 192.168.1.27
```

192.168.1.27 (tcp/49686/dce-rpc)

The following DCERPC services are available on TCP port 49686 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 367abb81-9844-35f1-ad32-98f038001003, version 2.0
Description : Service Control Manager
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 49686
IP : 192.168.1.27
```

11154 (7) - Unknown Service Detection: Banner Retrieval

Synopsis

There is an unknown service running on the remote host.

Description

Nessus was unable to identify a service on the remote host even though it returned a banner of some type.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2022/07/26

Plugin Output

192.168.1.27 (tcp/49680)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port      : 49680
Type      : help
Banner    :
0x00:  01 00 03 01 05 00 07 00 09 00 0D C8 0D 00 0F 00 .....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00 .....
      0x20:
```

192.168.1.27 (tcp/49683)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port      : 49683
Type      : spontaneous
Banner    :
0x00:  01 00 03 01 05 00 07 00 09 00 0D C8 0D 00 0F 00 .....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00 .....
      0x20:
```


192.168.1.27 (tcp/49704)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port    : 49704
Type    : get_http
Banner  :
0x00:  8E 27 E5 AC 05 00 07 00 09 00 0D C8 0D 00 0F 00  .'.....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00  .....
      0x20:
```

192.168.1.27 (tcp/49709)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port    : 49709
Type    : get_http
Banner  :
0x00:  8E 27 E5 AC 05 00 07 00 09 00 0D C8 0D 00 0F 00  .'.....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00  .....
      0x20:
```

192.168.1.27 (tcp/49710)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port    : 49710
Type    : get_http
Banner  :
0x00:  8E 27 E5 AC 05 00 07 00 09 00 0D C8 0D 00 0F 00  .'.....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00  .....
      0x20:
```

192.168.1.27 (tcp/49712)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port    : 49712
Type    : get_http
Banner  :
0x00:  8E 27 E5 AC 05 00 07 00 09 00 0D C8 0D 00 0F 00  .'.....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00  .....
      0x20:
```

192.168.1.27 (tcp/49717)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port    : 49717
Type    : get_http
Banner  :
0x00:  8E 27 E5 AC 05 00 07 00 09 00 0D C8 0D 00 0F 00  .'.....
      0x10:  11 00 13 00 15 00 17 00 19 00 1B 00 1D 00 1F 00  .....
      0x20:
```

22964 (4) - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

192.168.1.27 (tcp/8834/www)

```
A TLSv1.2 server answered on this port.
```

192.168.1.27 (tcp/8834/www)

```
A web server is running on this port through TLSv1.2.
```

192.168.1.27 (tcp/49687)

```
The service closed the connection without sending any data.  
It might be protected by some sort of TCP wrapper.
```

192.168.1.27 (tcp/49718)

```
The service closed the connection without sending any data.  
It might be protected by some sort of TCP wrapper.
```

11011 (2) - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

192.168.1.27 (tcp/139/smb)

```
An SMB server is running on this port.
```

192.168.1.27 (tcp/445/cifs)

```
A CIFS server is running on this port.
```

10107 (1) - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

192.168.1.27 (tcp/8834/www)

```
The remote web server type is :
```

```
NessusWWW
```

10147 (1) - Nessus Server Detection

Synopsis

A Nessus daemon is listening on the remote port.

Description

A Nessus daemon is listening on the remote port.

See Also

<https://www.tenable.com/products/nessus/nessus-professional>

Solution

Ensure that the remote Nessus installation has been authorized.

Risk Factor

None

References

XREF IAVT:0001-T-0673

Plugin Information

Published: 1999/10/12, Modified: 2025/11/03

Plugin Output

192.168.1.27 (tcp/8834/www)

```
URL      : https://192.168.1.27:8834/  
Version  : unknown
```

10150 (1) - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

192.168.1.27 (tcp/445/cifs)

The following 2 NetBIOS names have been gathered :

AMAL	= Computer name
AMAL	= Workgroup / Domain name

10785 (1) - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

192.168.1.27 (tcp/445/cifs)

```
Nessus was able to obtain the following information about the host, by  
parsing the SMB2 Protocol's NTLM SSP message:
```

```
Target Name: AMAL  
NetBIOS Domain Name: AMAL  
NetBIOS Computer Name: AMAL  
DNS Domain Name: AMAL  
DNS Computer Name: AMAL  
DNS Tree Name: unknown  
Product Version: 10.0.26100
```


10863 (1) - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

192.168.1.27 (tcp/8834/www)

Subject Name:

Organization: Nessus Users United
Organization Unit: Nessus Server
Locality: New York
Country: US
State/Province: NY
Common Name: AMAL

Issuer Name:

Organization: Nessus Users United
Organization Unit: Nessus Certification Authority
Locality: New York
Country: US
State/Province: NY
Common Name: Nessus Certification Authority

Serial Number: 3A 61

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Nov 17 10:15:05 2025 GMT

Not Valid After: Nov 16 10:15:05 2029 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits

```
Public Key: 00 BF BC 66 83 51 C9 CA 87 D2 D5 94 CA 9C 9F 92 2E 42 EC 58
            15 86 38 3B CE BD 8F 28 C9 77 A2 3A A8 5F 4B 66 8A 41 94 5F
            6B E7 E8 86 8F 96 66 DA D3 2A E0 F5 A5 5E 81 EF D7 7F 36 39
            19 B5 D0 7D AB 1F 1B DB EB 64 2D D1 8B 13 AC 65 09 E9 A1 9E
            44 D4 CA AF F8 16 30 4F 55 82 AA 69 E6 A0 7E 74 EF 09 75 A5
            04 96 A1 FF 12 24 F6 0D 38 B4 DB 61 58 12 8A 74 B5 70 A3 16
            A4 15 7B 86 69 F2 1B 3C B6 DF 52 63 52 CB C5 B1 99 D4 52 15
            85 8B DE 95 33 22 CB 3F AA B5 9D 1D D9 A5 59 5F 86 60 36 CE
            84 7C AD AC A0 BF 2A AB FB A9 EE 1E D6 6D F9 E0 E5 3A 85 73
            6E D4 57 54 78 AA D0 2B 6A AC 9A 69 05 30 4E 02 8E 47 45 8C
            AF 3D D4 82 B7 A2 86 F0 A6 53 B2 75 2E 4A 5C 7D EF F9 87 BC
            7F 7F 83 89 75 7B CF 7E 05 A2 7E 20 36 6A 5A F1 35 B6 A9 69
            F1 99 E8 CF 63 6E EB A2 35 29 C0 5D 13 9C BE EF A9
Exponent: 01 00 01
```

```
Signature Length: 256 bytes / 2048 bits
Signature: 00 A0 18 D7 5E BE 1A B5 88 02 F7 83 9B 07 27 A2 D0 EA 86 98
            45 76 6E 68 1F 88 69 9B 12 17 4C D6 19 D8 D6 53 29 C0 E6 25
            30 1D 71 CE E9 79 0F 3C 88 EB A4 0F 96 7B 44 29 83 50 BC D1
            AC 9F B6 B6 3C 7B 02 4C 4D F3 C0 A9 4A B9 3D 0E F2 3E C5 9D
            38 9D 9C 9E 3E 57 01 02 28 64 E0 9E 39 8B 7F 29 C7 69 88 33
            A4 85 85 2E E0 55 99 1E 46 0C 28 A5 FA A9 E2 88 90 57 E7 08
            5A D5 B7 86 96 9A 95 [...]
```

11936 (1) - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

192.168.1.27 (tcp/0)

```
Remote operating system : Windows 11  
Confidence level : 70  
Method : Misc
```

```
The remote host is running Windows 11
```

12053 (1) - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

192.168.1.27 (tcp/0)

```
192.168.1.27 resolves as AMAL.
```

19506 (1) - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/10/29

Plugin Output

192.168.1.27 (tcp/0)

Information about this scan :

```
Nessus version : 10.10.1
Nessus build : 20010
Plugin feed version : 202511161854
Scanner edition used : Nessus Home
Scanner OS : WINDOWS
Scanner distribution : win-x86-64
Scan type : Normal
```

```
Scan name : Localhost Scan
Scan policy used : Basic Network Scan
Scanner IP : 192.168.1.27
Ping RTT : Unavailable
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/11/17 16:48 India Standard Time (UTC +05:30)
Scan duration : 460 sec
Scan for malware : no
```

21643 (1) - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2024/09/11

Plugin Output

192.168.1.27 (tcp/8834/www)

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv13

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
TLS_AES_128_GCM_SHA256	0x13, 0x01	-	-	AES-GCM(128)	
AEAD					
TLS_AES_256_GCM_SHA384	0x13, 0x02	-	-	AES-GCM(256)	
AEAD					
TLS_CHACHA20_POLY1305_SHA256	0x13, 0x03	-	-	ChaCha20-Poly1305(256)	
AEAD					

SSL Version : TLSv12

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---

ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x2F	ECDH	RSA	AES-GCM(128)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x30	ECDH	RSA	AES-GCM(256)

The fields above are :

```
{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```


24260 (1) - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

192.168.1.27 (tcp/8834/www)

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : yes

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Cache-Control: must-revalidate

X-Frame-Options: DENY

Content-Type: text/html

ETag: 3d486b371cacebd11d40ecec34c5bc09

Connection: close

X-XSS-Protection: 1; mode=block

Server: NessusWWW

Date: Mon, 17 Nov 2025 11:20:44 GMT

X-Content-Type-Options: nosniff

Content-Length: 1217

Content-Security-Policy: upgrade-insecure-requests; block-all-mixed-content; form-action 'self'; frame-ancestors 'none'; frame-src https://store.tenable.com; default-src 'self'; connect-src 'self' www.tenable.com; script-src 'self' www.tenable.com; img-src 'self' data:; style-src 'self' www.tenable.com; object-src 'none'; base-uri 'self';

Strict-Transport-Security: max-age=31536000; includeSubDomains

Expect-CT: max-age=0

Response Body :

```
<!doctype html>
<html lang="en">
  <head>
    <meta http-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
    <meta http-equiv="Content-Security-Policy" content="upgrade-insecure-requests; block-all-
mixed-content; form-action 'self'; frame-src https://store.tenable.com; default-src 'self'; connect-
src 'self' www.tenable.com; script-src 'self' www.tenable.com; img-src 'self' data;; style-src
'self' www.tenable.com; object-src 'none'; base-uri 'self';" />
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <meta charset="utf-8" />
    <title>Nessus</title>
    <link rel="stylesheet" href="nessus6.css?v=1761337788773" id="theme-link" />
    <link rel="stylesheet" href="tenable_links.css?v=ac05d80f1e3731b79d12103cdf9367fc" />
    <link rel="stylesheet" href="wizard_templates.css?v=0e2ae10949ed6782467b3810ccce69c5" />
    <!--[if lt IE 11]>
      <script>
        window.location = '/unsupported6.html';
      </script>
    <![endif]-->
    <script src="nessus6.js?v=1761337788773"></script>
    <script src="p [...]
```

42410 (1) - Microsoft Windows NTLMSSP Authentication Request Remote Network Name Disclosure

Synopsis

It is possible to obtain the network name of the remote host.

Description

The remote host listens on tcp port 445 and replies to SMB requests.

By sending an NTLMSSP authentication request it is possible to obtain the name of the remote system and the name of its domain.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/06, Modified: 2019/11/22

Plugin Output

192.168.1.27 (tcp/445/cifs)

The following 2 NetBIOS names have been gathered :

AMAL	= Computer name
AMAL	= Workgroup / Domain name

42822 (1) - Strict Transport Security (STS) Detection

Synopsis

The remote web server implements Strict Transport Security.

Description

The remote web server implements Strict Transport Security (STS).

The goal of STS is to make sure that a user does not accidentally downgrade the security of his or her browser.

All unencrypted HTTP connections are redirected to HTTPS. The browser is expected to treat all cookies as 'secure' and to close the connection in the event of potentially insecure situations.

See Also

<http://www.nessus.org/u?2fb3aca6>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/16, Modified: 2019/11/22

Plugin Output

192.168.1.27 (tcp/8834/www)

The STS header line is :

```
Strict-Transport-Security: max-age=31536000; includeSubDomains
```

45590 (1) - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/09/29

Plugin Output

192.168.1.27 (tcp/0)

The remote operating system matched the following CPE :

cpe:/o:microsoft:windows -> Microsoft Windows

Following application CPE matched on the remote system :

cpe:/a:tenable:nessus -> Tenable Nessus

46180 (1) - Additional DNS Hostnames

Synopsis

Nessus has detected potential virtual hosts.

Description

Hostnames different from the current hostname have been collected by miscellaneous plugins. Nessus has generated a list of hostnames that point to the remote host. Note that these are only the alternate hostnames for vhosts discovered on a web server.

Different web servers may be hosted on name-based virtual hosts.

See Also

https://en.wikipedia.org/wiki/Virtual_hosting

Solution

If you want to test them, re-scan using the special vhost syntax, such as :

`www.example.com[192.0.32.10]`

Risk Factor

None

Plugin Information

Published: 2010/04/29, Modified: 2022/08/15

Plugin Output

192.168.1.27 (tcp/0)

```
The following hostnames point to the remote host :  
- amal
```

54615 (1) - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

192.168.1.27 (tcp/0)

```
Remote device type : general-purpose  
Confidence level : 70
```

56984 (1) - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

192.168.1.27 (tcp/8834/www)

```
This port supports TLSv1.3/TLSv1.2.
```


57041 (1) - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

192.168.1.27 (tcp/8834/www)

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA256	0xC0, 0x2F	ECDH	RSA	AES-GCM(128)	
SHA256					
ECDHE-RSA-AES256-SHA384	0xC0, 0x30	ECDH	RSA	AES-GCM(256)	
SHA384					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}

```
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

64582 (1) - Netstat Connection Information

Synopsis

Nessus was able to parse the results of the 'netstat' command on the remote host.

Description

The remote host has listening ports or established connections that Nessus was able to extract from the results of the 'netstat' command.

Note: The output for this plugin can be very long, and is not shown by default. To display it, enable verbose reporting in scan settings.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/02/13, Modified: 2023/05/23

Plugin Output

192.168.1.27 (tcp/0)

97993 (1) - OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library)

Synopsis

Information about the remote host can be disclosed via an authenticated session.

Description

Nessus was able to login to the remote host using SSH or local commands and extract the list of installed packages.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/05/30, Modified: 2025/02/11

Plugin Output

192.168.1.27 (tcp/0)

Nessus can run commands on localhost to check if patches are applied.

Credentialed checks of Windows are not supported using SSH.

The remote host is not currently supported by this plugin.

Runtime : 1.47933 seconds

100871 (1) - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

192.168.1.27 (tcp/445/cifs)

```
The remote host supports the following versions of SMB :  
SMBv2
```

106716 (1) - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

192.168.1.27 (tcp/445/cifs)

The remote host supports the following SMB dialects :

version	_introduced in windows version_
2.0.2	Windows 2008
2.1	Windows 7
3.0	Windows 8
3.0.2	Windows 8.1
3.1.1	Windows 10

The remote host does NOT support the following SMB dialects :

version	_introduced in windows version_
2.2.2	Windows 8 Beta
2.2.4	Windows 8 Beta
3.1	Windows 10

110723 (1) - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

192.168.1.27 (tcp/0)

SMB was detected on port 445 but no credentials were provided.

SMB local checks were not enabled.

117886 (1) - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

192.168.1.27 (tcp/0)

The following issues were reported :

```
- Plugin      : ssh_get_info2.nasl
  Plugin ID   : 97993
  Plugin Name : OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH
  Library)
  Protocol    : LOCALHOST
  Message     :
  Credentialed checks of Windows are not supported using SSH.

- Plugin      : no_local_checks_credentials.nasl
```

Plugin ID : 110723
Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
Message :
Credentials were not provided for detected SMB service.

136318 (1) - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2020/05/04

Plugin Output

192.168.1.27 (tcp/8834/www)

```
TLShv1.2 is enabled and the server supports at least one cipher.
```

138330 (1) - TLS Version 1.3 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.3.

See Also

<https://tools.ietf.org/html/rfc8446>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/07/09, Modified: 2023/12/13

Plugin Output

192.168.1.27 (tcp/8834/www)

```
TLShv1.3 is enabled and the server supports at least one cipher.
```

209654 (1) - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

192.168.1.27 (tcp/0)

Following OS Fingerprints were found

Remote operating system : Windows 11
Confidence level : 70
Method : Misc
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :
HTTP!:Server: NessusWWW

SSLcert!:i/CN:Nessus Certification Authorityi/O:Nessus Users Unitedi/OU:Nessus Certification
Authoritys/CN:AMALs/O:Nessus Users Uniteds/OU:Nessus Server
819a22d58e786424813e60550b8183dfbfd6dled