Burp Suite Pro Edition Exploration & Traffic Analysis

Time Used

Approximately 2–3 hours

---

1. Introduction

In this task, I learned the basic features of **Burp Suite** and used it with the authorized website **demo.testfire.net**.

I mainly worked with Proxy, HTTP History, Target/Site Map, Repeater, Decoder, Comparer, and Intruder.


---


2. Proxy Configuration


I configured Firefox to send website traffic through Burp Suite.

- Proxy: `127.0.0.1`
- Port: `8080`
- Burp Proxy listener was running successfully.
- I confirmed that browser traffic was captured in Burp.

Evidence:







---

3. HTTP Traffic Analysis


I captured and checked different requests from the target website.

One of the requests I analyzed was:

- Method: `GET`
- URL: `/login.jsp`
- Host: `demo.testfire.net` Status: `200 OK`
- Server: `Apache-Coyote/1.1`

I also checked the request headers and response information in Burp HTTP History.

Evidence:



---

4. Site Map


I used **Target → Site Map** to see the pages discovered from the website.

Some pages observed were:

- `/`
- `/login.jsp`
- `/feedback.jsp`
- `/index.jsp`
- `/default.jsp`

This helped me understand the structure and available functionality of the application.

Evidence:



---

5. Repeater Testing

I sent the `/login.jsp` request to **Repeater**.

I changed the following header:

Original:

`Accept-Language: en-US,en;q=0.5` **Modified:**

`Accept-Language: en-US`


After sending the modified request, the response was still:

`HTTP/1.1 200 OK`

No major change was observed in the response.

Evidence:

6. Decoder



I used Burp Decoder with the text:

`CyberSecurity123`

URL Encoding

`%43%79%62%65%72%53%65%63%75%72%69%74%79%31%32%33`

URL Decoding

`CyberSecurity123` **Base64**

Encoding


`Q3liZXJTZWN1cml0eTEyMw==`


Base64 Decoding

`CyberSecurity123`

This helped me understand how data can be encoded and decoded during web traffic analysis.

Evidence:





7. Comparer

I used Burp Comparer to compare two HTTP requests.


I compared:


`GET /` with:

```
GET /login.jsp
```

The main differences were the requested URL and some request headers such as the Referer. This feature can help identify differences between two requests or responses.

Evidence:





8. Intruder


I explored the Burp Intruder module.

I learned about:

- **Sniper** – works with one payload position at a time.
- **Battering Ram** – uses the same payload in multiple positions.
- **Pitchfork** – uses different payload sets together.
- **Cluster Bomb** – tests combinations of different payload sets.

I only explored the feature. **No attack was executed.**

Evidence:



---

9. Main Findings

During the task, I observed:

- Burp successfully captured browser traffic.
- The target website was visible in HTTP History and Site Map.
- The login page returned `200 OK`.
- The server identified itself as `Apache-Coyote/1.1`.
- A `JSESSIONID` cookie with the `HttpOnly` attribute was observed.
- The website was accessible through HTTP and the browser displayed it as **Not Secure**.
- Repeater allowed me to modify and resend a request.
- Decoder, Comparer, and Intruder were successfully explored.

---

10. Conclusion

This task helped me understand the basic use of Burp Suite for web application traffic analysis. I learned how to capture requests, view application pages, modify requests using Repeater, encode and decode data, compare requests, and understand the basic Intruder options.

No exploitation or brute-force testing was performed.