AI-Assisted On-Call Queue: Budgeted Incident Detection for Cloud Microservices

Aishah Mohamed Alyammahi

Abstract

On-call engineers can read only a few alerts a day, and 82% of GAIA faults never write a log line. The system shows at most K items a day, in the order they become known, using memory jumps, slow leaks, and monitoring gaps. At K = 20 the jump detector catches 72.6% of 1,223 test faults, against 68.9% for a Prometheus rate rule and 0% for log severity. The jump detector wins all 8 walk-forward weeks against that rate rule, with fewer false items a day.

1. Motivation and objectives

A platform of many small services raises more alerts than one person can read. Real faults are missed because attention runs out, not because the metrics were silent. The users are the on-call engineer, who needs a short list that still contains the real faults, and the operator who turns Live on, who needs nothing paged by accident and a way to put a model back. The practical value is the daily budget. The queue shows at most K items, in the order a live system learns about them, so the team is not left choosing between a flood of pages and a pager that stays quiet.

Teams already cut repetition. Alertmanager groups alerts that share labels. PagerDuty and Opsgenie merge alerts that look alike or share an alias. None of those tools chooses which incidents fit into K readings a day, and none treats a rise in memory as an incident before a log alert has fired. The engineer reads the day's queue and marks an item Real or Noise. The operator installs the service, leaves shadow mode on until a pilot agrees, and is the only person who can turn Live on.

Each objective below is paired with the measurement this submission reports. The comparison that decides success is the budgeted jump queue against the rules a team already runs.

Objective	Target	Measured result
Beat the rate rule at K = 20	More faults caught than a Prometheus rate rule, with fewer false items	72.6% against 68.9%, and 1.0 against 2.1 false items a day. The jump detector (`jumps_tuned`) wins 8 of 8 walk-forward weeks against the Prometheus rate rule
Decide with no future data	No decision uses a later point, the end of a jump, or its peak	A jump is shown at the second confirming point. `tests/test_causality.py` checks that rule
Ship with shadow paging and a versioned model	Record what would have been paged until Live is armed. Models are versioned and can be rolled back	Shadow is the default. Live needs `APP_PASSWORD`, a channel, and the typed word LIVE, and only an ingest job may page. Models load as skops
Let another team run the tests	The checks run from the README on the committed results, with no paid API	450 passed, 10 skipped; line coverage 86%; `run_validate.py` matches the printed figures

2. Architecture and implementation

2.1 Architecture




Figure 1. Alertmanager and Prometheus feed app/product. Detection is in app/src. The queue is stored in SQLite. Pages leave only from ingest jobs

Alertmanager posts firing alerts into `app/product`. Prometheus supplies the memory series, and the same series can be uploaded as CSV. The product is a FastAPI service. It checks the caller, drops duplicate webhook rows, runs one scoring job, and writes the queue to SQLite. Detection lives in `app/src`: the jump rule, the slow-leak rule, the monitoring-gap rule, and the daily budget. A page is sent only from an ingest job, and only after Live is armed. Appendix H lists the HTTP routes.

The stack is Python, FastAPI, scikit-learn, pandas, SQLite, Docker and GitHub Actions. Dependencies are locked with uv. Each job stores the queue it built and the model version that scored the alerts. A Real or Noise mark is kept as a label. It does not itself send a page.

2.2 How the queue decides

The queue is first come, first served, and the day stops at K. A memory reading more than 0.5 GB above the previous 15-minute median is hot. The jump is shown at the second hot point within two minutes, and only when the rise known at that moment meets the threshold learned on the first week (0.62 GB on GAIA). A slow leak uses a three-hour median. A monitoring gap is ten minutes with no point. Log alerts may use at most a quarter of K. An alert that arrives while a jump on the same service is still open rides on that jump and takes no extra slot. No decision uses a later reading, the time the jump eventually ends, or the height it eventually reaches. A saved model is loaded as skops. A pickle file is refused even when its name still ends in `.pkl`. Shadow stays on until the operator sets `APP_PASSWORD`, names a channel, and types the word LIVE.

2.3 Change from the proposal

The significant change from the proposal is that the submitted system is the **budgeted jump queue**. An early hope of catching 95% of faults does not fit this data. GAIA injects about 22 faults a day, so 84.9% is the best that K = 20 can reach, and 82% of the faults never write a log line. The log classifier is trained and gated. On GAIA it is not what catches the faults. An LLM summary of an incident stayed out of scope, as the proposal said.

3. Testing, evaluation and results

Training uses the first 7 days only. The test period is the next 55 days and holds 1,223 faults. Days are not shuffled. A fault label scores a queue that has already been built. It is not an input to the decision. A fault counts as caught when a shown jump or leak on its service overlaps the injection, or a shown alert carries its id. A monitoring-gap item does not count as a catch.

Table 1. Method at K = 20 on the GAIA test period (1,223 faults). Counts are in `app/results/queue_eval_gaia.csv`.

Method at K = 20	Faults caught	False items a day
Log severity	0%	—
Prometheus rate rule	68.9%	2.1
Jump detector	72.6%	1.0
Best possible on this data	84.9%	—

The jump detector is the row `jumps_tuned`: 888 of 1,223 faults (72.6%) and 1.0 false item a day. The Prometheus rate rule is `delta_5m`: 843 of 1,223 (68.9%) and 2.1 false items a day. Log severity catches 0 of 1,223. The jump detector (`jumps_tuned`) wins all 8 walk-forward weeks against the Prometheus rate rule (`delta_5m`), and on the 55-day test it shows 1.0 false item a day against the rate rule's 2.1. Walk-forward learns every threshold again from the past only, then scores the next week once. Appendix D plots that detector and, separately, the full queue on the same weeks. The full queue is a different comparison, and it does not win every week. Median time from the start of a fault to the confirming point is 0.72 minutes.

About 22 faults are injected a day, more than 20 slots on 34 of the 55 test days, which is why the best possible result at this budget is 84.9% rather than 100%. When the full queue misses, Appendix D shows that the misses are mostly a monitoring gap or a day whose 20 slots were already full. The jump rule itself fails on only a small share of those misses.

On this commit, `uv run pytest -q` in `app/` reported 450 passed and 10 skipped. Line coverage is 86%. A load test of 50 concurrent users recorded p95 0.32 s and no errors (Appendix C). `uv run python run_validate.py` matched the printed figures (195 checked numbers).

The classifier on GAIA catches fewer faults than the same queue with no log alerts, so the gate leaves it inactive. Results on RCAEval, NAB and SMD are in the appendices.

4. Deliverables, setup and use

The repository is https://github.com/amamsy90/alert-fatigue-reduction. Submitted commit: `c179440316d98cee4082eaf7ffc4bc4a7e5b5980`. The delivery is the application, the tests, and this report. From a checkout, run the four commands below. Exact steps are in the README. Shadow mode is the default, so a job records what it would have paged, and an evaluation does not page. The tests and `run_validate.py` read the committed files in `app/results/`. GAIA itself is not in git. `tools/fetch_gaia.py` downloads it (about 1.8 GB) and checks each file by SHA-256. No paid API is required. PagerDuty, Slack and Opsgenie stay unused while shadow mode is on.

```
cd app
uv sync --group dev
uv run pytest -q
uv run python run_validate.py
```

5. Conclusion

The budgeted jump queue beats the rules a team already runs, under a limit of K items a day, without using later data. The main finding is that log severity catches none of these faults, because most of them never log.

Appendix A. Requirements, users and design detail

2. Problem definition

What the problem is. A cloud platform made of many small services raises thousands of alerts a day, but the engineer on call can read only a few. Real faults are missed because attention runs out, not because monitoring was silent.

Who experiences it. On-call engineers and small operations teams (primary), and the users of the platform when a fault is found late.

Why it matters. A fault that is noticed late lasts longer. Engineers who are paged for noise stop trusting the pager and start ignoring it ("alert fatigue").

How it is handled today. In a typical team, alerts come from two places. Log-based alerts are escalated when their severity label is high enough, for example "critical" or "error". Metric-based alerts are fixed rules written in Prometheus, such as "memory above a set level" or "memory rose by more than 0.5 GB in five minutes" (`delta(memory[5m]) > 0.5 GB`). Alertmanager then reduces repetition. It groups alerts that share chosen labels into one notification, mutes some alerts while related ones are firing, and routes each group to a receiver. Paging services add their own merging: Opsgenie merges alerts with the same alias, and PagerDuty's Intelligent Alert Grouping uses machine learning to merge similar alerts into one incident. All of these tools decide which alerts belong together. None of them decides which alerts are worth a person's limited time. Section B7 measures that difference on the homelab.

Limits of the current approach. Severity rules read only logs. On the public GAIA microservice benchmark, **82% of injected faults never write a log line**; they show up only as a jump in a metric such as memory, so a log-severity rule catches **0%** of them at 20 items a day (§B1). Fixed metric thresholds either miss faults or flood the queue, and none of these rules knows that a person can read only K items a day.

How often. GAIA injects about 22 faults a day on ten services, more than a 20-item budget on 34 of 55 days (§B1).

If nothing changes. Teams keep choosing between missed faults and ignored pagers. More monitoring makes it worse, because every new signal competes for the same attention.

Why this is a software engineering project. The answer is not one model. It is a system: ingest alerts and metrics from existing tools, decide under a budget in real time, page safely, learn from engineers' feedback, and be deployable, testable, monitored and reversible.

Problem statement. On-call engineers can read only a few alerts a day, but the rules that choose those alerts read log severity, which most real faults never trigger, so faults are missed while noise still reaches the pager.

3. Objectives and expected outcomes

Main objective. Design, build and evaluate an AI-assisted on-call queue that shows each engineer at most K items a day, in real time, and catches more real faults with fewer false items than the rules teams already run.

Specific objectives (measurable).

#	Objective	Target	Result
O1	Beat the rules a team already runs at a realistic budget	More faults caught at K = 20 than log severity, a static threshold and a Prometheus rate rule, with fewer false items	Detector 72.6% vs 68.9% (rate rule), 1.0 vs 2.1 false items a day; wins 8/8 walk-forward weeks (§B1, §B2)
O2	Decide in real time	No decision uses later data; confirmation within about a minute	Median 0.72 min; `tests/test_causality.py` (§B1)
O3	Engineer it for production	Authentication, safe paging, versioned models with rollback, monitoring endpoints, Docker	Done (§7, §9, §10)
O4	Test it properly	≥ 90% of tests passing, coverage ≥ 85%, p95 ≤ 1 s at 50 users	450 passed, 10 skipped, line coverage 86%, 0.32 s (§8)
O5	Let another team check it on its own data before trusting it	Evaluate my data works end to end without code, against a chance line	Done; NAB, SMD and RCAEval results reported, including failures (§B5)

Expected final product. A working web application and REST API (FastAPI) with a queue page, Connectors page and *Evaluate my data* page; a backend scoring service; an AI component (a cost-sensitive alert classifier with a model registry) next to rule-based metric detectors; a SQLite store; connectors for Alertmanager, Prometheus, PagerDuty, Slack and Opsgenie; a command-line tool; 450 passed and 10 skipped on Python 3.12.3 at the submission re-run (an earlier draft said 296 tests) and CI; a Docker deployment with per-environment settings; `/metrics` and `/monitoring`; technical documentation (`docs/`); and this report.

4. Target users and use case

Primary users. On-call engineers (site reliability or operations) on a team running microservices.


Secondary users. The team lead or operator, who installs the tool, decides when it may page and which model is active; platform owners who read the monitoring page; an evaluating team trying it on past data; examiners and researchers reproducing the results.

User	Needs
On-call engineer	A short list, in order, that contains the real faults; a reason for each item; a way to say "this was noise"
Operator / team lead	Safe installation; nothing paged by accident; secrets kept safe; a way to undo a bad model; health at a glance
Evaluating team	Proof on its own data, with a fair baseline and a chance line, before trusting it

System usage. Alertmanager posts alerts to the app all day; the app pulls memory metrics from Prometheus; a scoring job runs on each webhook batch (or on demand). The engineer opens the queue page during the shift and receives pages in Live mode. They provide nothing but marks: Real or Noise on items. The system produces the day's queue (metric jumps, slow leaks, monitoring gaps and escalated or "ask a person" alerts, at most K), each with a reason. After that, the engineer investigates the item; the mark becomes a label for the next model.

Use-case flow.

UML use-case diagram. Actors on the left are people; actors on the right are the systems the tool talks to. Scoring a batch always includes training and gating a model when labels exist, and paging (which sends only in Live mode); a Real / Noise mark extends training with a new label. The figure is drawn by `app/make_figures.py`.



UML use-case diagram of the on-call queue

5. Why use AI?

What needs AI. Deciding which *log alerts* are worth a slot. Their text, source, severity and timing interact in ways fixed rules do not capture, and the right answer differs per team. A classifier trained on the team's own labels (and later its own Real / Noise marks) learns that, with a miss weighted ten times a false alarm.

What traditional software handles. Everything else, deliberately: ingesting webhooks, the metric detectors (a rise above the recent median is a rule, chosen on week 1 only), monitoring-gap detection, the daily budget, paging, storage and security. On GAIA the rules do most of the work: where metric data exists, the jump rule overlaps 99.6% of faults (§B6).

Why a rule-based approach alone is insufficient for alerts. Severity is noisy: "high" alerts are often benign and "info" lines appear during real faults. A fixed severity rule cannot use message text or the fact that an alert arrived during a memory jump, and it cannot adapt when engineers mark items as noise.

AI technology. Supervised classification: logistic regression on TF-IDF text features, source, severity, recent alert counts and an inside-a-jump flag (scikit-learn). A second learned piece, the confirmation threshold, is a cost-minimising cut on the training window. Two different rankers need to be kept apart. The experimental jump ranker in §B4 replaces the rise threshold with a logistic regression on jump features. On GAIA at K = 20 it catches 69.7% against the full queue's 69.6%, which is no gain, and it stays an experiment. The later learned ranker (PR #26, commit `2b78bbb`, flag `LEARNED_RANKER`) chooses among the day's candidates. A re-run on 3 November 2026, `run_model_ablation.py --data gaia --device cuda --`

`backend xgboost --epochs 8` (seed 42, 4,000 bootstrap draws), on master `20d5664`, is in `docs/results/gaia_ranker_rerun/`. At K = 20 it caught 887 of 1,223 faults against that run's baseline of 851. The baseline is the current causal queue and matches the `proposed` row of `app/results/queue_eval_gaia.csv` (851 of 1,223, precision 0.895, 1.82 false items a day). The per-fault catch difference is +0.0294, interval [0.0147, 0.0442], KEEP. Precision is 0.9416 against 0.895, and false items a day are 1.0 against 1.82. K = 5, 10 and 50 are DROP. Walk-forward pooled is KEEP, +0.0262 with interval [0.0131, 0.0401] (`walk_forward_pooled.json`). GAIA has no companies, so this is a time split, not leave-one-company-out. The 887 on the `delta_5m_carryover` row of `queue_eval_gaia.csv` is a different queue. `LEARNED_RANKER` stays off. The homelab measurement is §B7.

Existing model or API. An existing, well-understood model family (scikit-learn logistic regression) trained locally; no external AI API or LLM, so no data leaves the server and there is no per-call cost.

What the classifier adds, measured. An ablation on GAIA (`run_classifier_ablation.py`, §B4) keeps the whole queue and changes only how log alerts are chosen for their quarter of the slots. At K = 20 the queue with the classifier catches 69.6% with 1.8 false items a day; with log severity instead it catches 71.0% (1.4 false a day); with no log alerts at all, 71.2% (1.2 false a day). **On GAIA the classifier adds no catches; it costs about 1.6 points and 0.6 false items a day**, because 82% of GAIA faults write no log line and the alerts it escalates spend slots that jumps would have used. Its value is therefore not shown on this benchmark. It is kept for teams whose faults *do* log: it is the only part that learns from that team's Real / Noise marks (a Noise mark becomes a negative label at the next retrain), and alerts can never take more than a quarter of the budget. **It is not on by default.** A trained model is used only if, on the held-out part of its batch, it beats the same queue *without* log alerts and the queue it would fall back to by at least one missed fault's worth of cost (§9). The first model has to pass too. On GAIA it does not (848 vs 872 of 1,223 held-out faults caught, §B4), so the tool keeps it as a candidate and scores GAIA with rules only. **On a second dataset it does add catches where faults log.** On RCAEval RE2 Train Ticket the classifier lifts the queue from 60.0% to 73.3% of 45 test faults at K = 10: +13.3 points over no log alerts (95% interval +4.4 to +24.4), +2.2 over severity alerts (71.1%, one case). The gate promotes it there, by exactly its margin, but it was run on the same 45 cases that are scored, so that decision is not an independent test (§B5); on Online Boutique, Sock Shop and the RE3 code faults it adds no catch beyond one case, and the gate keeps it out (§B5).

Limitations of AI here. It needs labels of both classes, so a new team starts in rules-only mode; learned thresholds do not transfer between datasets (one learned on GAIA's 1 GB faults rejects 0.5 GB faults, §B3); and 82% of GAIA faults leave no log, which caps a log-only model near 18% (§B6).

6. AI component and technical approach

Question	Answer
AI technology	Cost-sensitive logistic regression for log alerts; rule-based metric

Question	Answer
	detectors beside it
Existing model or own?	An existing model family, trained on the team's own labelled data; not a new algorithm
Input	Each alert: time, source, severity, type, message; whether it fell inside a confirmed memory jump; recent counts from the same source
Output	P(alert is a real fault), turned into an action: escalate, ask a person, or hide, with a reason
Data needed	Past alerts with incident windows, or Real / Noise marks; memory series for the detectors
How the software talks to it	In-process: `pipeline.score_alerts` calls the classifier; models are loaded from the registry (`product/model_store.py`)
If it is wrong	The queue is capped at K; uncertain alerts go to a person; engineers mark Noise; a model is not promoted unless it beats the queue without log alerts and the queue it replaces by at least one missed fault's worth (and is no worse than the active model) on held-out data, and the operator can roll back
Main limitation	Label-hungry; helps only services that log

How the queue decides (details in §B1 and `design_specification.md`). One queue, at most K items a day, first come, first served:

1. **Metric jumps.** For every new memory reading, the system compares the value with the median of the same service's readings over the previous **15 minutes**. If the reading is more than **0.5 GB** above that median, it is marked as hot. One hot reading could be noise, so a jump is confirmed only when a second hot reading follows within two minutes. At that moment the jump becomes a candidate for the queue. It is shown only if the rise measured at confirmation is at least as large as a threshold learned from the first week. On GAIA that threshold is **0.62 GB**: the size that, on week-1 data, gave the lowest combined cost of missed faults and false items.
2. **Slow leaks.** The same rule with a **3-hour** median and 10 minutes of hot points catches memory that climbs over hours. A leak is dropped only when a fast jump on the same series was already shown when the leak was confirmed.
3. **Monitoring gaps.** A service with no metric point for **10 minutes** is shown as a gap item ("we are blind here"), also while the feed is still dead.
4. **Log alerts** may use at most **a quarter** of the slots (5 of 20), first come. An alert on a service whose shown jump is still open rides on that jump and uses no slot.

Every decision uses only information that existed at the moment the decision was made. In particular, the queue never uses a reading from later in the day, never waits to see when a jump ends, and never uses how high a jump eventually peaks. All three would make the results look better than a live system could achieve. This rule is recorded as design decision ADR 0001 and checked by `tests/test_causality.py`. For metrics that are not bytes, a relative mode (a share of the median) and a unit-free robust mode exist.

Training on GAIA. GAIA MicroSS (CloudWise), July–August 2021: 34,863 log lines, 1,367 injected faults, each holding **1 GB of extra memory for 600 s** on one service. Train on the first 7 days; test on the next 55 days (**1,223 faults**); days are never shuffled.

What is learned	How
Jump size 0.5 GB	Chosen on week 1 only (`run_memory.py --sweep`)
Jump confirmation threshold	Rise at confirmation with the lowest week-1 cost → **0.62 GB**
Alert classifier and its threshold	Logistic regression on week-1 alerts; threshold with the lowest week-1 cost (a miss = 10 false alarms)
Static-rule baseline	Week-1 99th percentile per service

Production design. Two layers: a library that knows nothing about HTTP (`app/src/`) and a product layer (`app/product/`) with the web app (`product/web/`: security middleware, three route modules), the job pipeline (inputs, labels, paging), storage, connectors, the model registry and monitoring. Diagrams (context, components, ingest-to-page sequence, deployment, data model): `docs/architecture.md`. Decisions: `docs/adr/`. Threats and mitigations: `docs/threat_model.md`.

12. Project scope and limitations

In scope (built): the causal budgeted queue (jumps, leaks, gaps, alerts); the alert classifier with a model registry, promotion gate and rollback; the web app, API and CLI; Alertmanager, Prometheus, PagerDuty, Slack and Opsgenie connectors; *Evaluate my data*; shadow mode and marks; security hardening; monitoring endpoints; Docker and per-environment settings; CI; the GAIA, NAB, SMD and RCAEval evaluations.

Out of scope (not built): automatic remediation; multi-tenant hosting and user roles; LLM summaries of incidents; dedicated CPU, disk or network fault detectors inside microservices (the unit-free jump rule is measured on such faults on SMD servers and RCAEval RE2, §B5); a managed cloud deployment; browser UI tests; a live pilot with a real team (the next step).

Limitations (say these if asked):

5. **Every GAIA fault is the same 1 GB, 600 s memory program.** The robustness replay (§B3) tests other sizes and shapes. §B5 tests other domains (NAB, a shop, SMD servers) and, on three other microservice applications, the same memory injection and CPU, disk, network and code faults with logs (RCAEval), with small test sets and a chance line.
6. **The win over a plain Prometheus rate rule is modest** (+3.7 points for the detector, 8/8 weeks; +0.7 for the full queue, which ties it week by week). The larger gains are fewer false items, a real-time queue, and leak and gap coverage. Carry-over lifts both rules about equally.
7. **K = 20 is below the fault rate** (22 a day), so no method can exceed 84.9%.
8. **Learned thresholds do not transfer.** One learned on GAIA's 1 GB faults rejects 0.5 GB faults. Rules-only mode works without labels; the per-series confirm levels (§B4) are measured but not in the headline.

9. **The alert classifier adds no catches on GAIA.** With log alerts chosen by severity, or left out, the queue catches slightly more (71.0% and 71.2% vs 69.6% at K = 20) with fewer false items (§5, §B4). The later learned ranker is a separate model and is reported in §B7. The classifier is kept for teams whose faults log and who mark items: on RCAEval RE2 Train Ticket, where faults log on the broken service, it adds 13.3 points over no log alerts (95% interval +4.4 to +24.4) and 2.2 over severity alerts (one case), and the gate promotes it, by exactly its one-fault margin over severity alerts, judged on the same 45 cases that are scored (§B5); on the other five RCAEval application suites it adds at most one case, and the gate keeps it out (§B5). The promotion gate now checks this on every batch, and on GAIA it keeps the classifier out (§9, §B4).
10. The scripts in `app/experiments/legacy_alerts_only/` are alerts-only milestone experiments. Do not quote them as the system result.
11. **The homelab ranker does not transfer to a held-out company.** On the day-12 snapshot the pooled ranker is a KEEP against `proposed` and `static_p99` at K = 5, 10 and 20, and against tuned jumps at K = 10 and 20. K = 5 against tuned jumps is a DROP, because the interval includes zero. At K = 50 it is a DROP against the proposed queue, which catches more. Leave-one-company-out is a DROP for acme, borealis and cassini, with the same catches as the baseline (§B7). `LEARNED_RANKER` stays off.

Future work. Linking the homelab's Tempo spans to the trace-graph model, so network faults whose symptoms land on another service can be tied to a call graph rather than to co-firing alone (§B7.3). A gate window separate from the scored window on RCAEval (it needs more cases per application than the 45 used here), and a live, continuous log stream (RCAEval recordings are 24–30 minutes, replayed one a day) to confirm the RE2 result for the classifier; a pilot with one team in shadow mode, measuring precision from marks. R1 through R8 in `docs/threat_model.md` are closed and tested: the Prometheus fetch uses the address it checked, login locks out (behind a trusted proxy the client is read from the right of `X-Forwarded-For`, across every header line; a code review on 10 October found the leftmost, client-written value was used, which let a client dodge the lock, and that only the first header line was read; both are fixed with regression tests), paging is by item key, models load through skops, sign-in sets a session cookie, a viewer password cannot change settings, the audit log is also a file, and paging secrets stay out of `ops.json`.

Appendix B. Deployment, MLOps, monitoring and privacy

7. Deployment strategy

One Docker container per team, on the team's own server or VM, behind a TLS reverse proxy; SQLite and the model registry on a Docker volume; the model runs in-process; alerts arrive from Alertmanager and metrics are pulled from Prometheus; pages go to PagerDuty, Slack or Opsgenie. The image is built from a hash-pinned lock file.

	Development	Test	Production
Where	Laptop	GitHub Actions; a shadow instance next to production	Team server

	Development	Test	Production
Settings	`app/deploy/dev.env`	`app/deploy/test.env`	`app/deploy/prod.env` (from the example; not in git)
Paging	Never	Never (records *would have paged*)	Only after a shadow period and a deliberate Live switch

Measured capacity: 50 concurrent users at 228 requests/s with p95 0.32 s; a 400-alert webhook batch scores in 0.2 s and the full GAIA month in about a minute (54.9 s, below; target ≤ 5 min). The design runs one worker per team; the scaling path is one container per team, or PostgreSQL with shared locks for a shared deployment (ADR 0003). Sign-in sessions, the login lock and the ingest rate counters are kept in `auth.db` (SQLite beside `ops.json`; session tokens stored as SHA-256), not in process memory, so a restart or redeploy no longer signs everyone out or clears a lock earned by guessing passwords (version 1.0.2; `test_auth_store.py` starts the app twice in separate processes). The job, evaluation and `ops.json` locks are still in-process, so the app stays one worker.

Resources and operating cost (learning objective 11). Measured with `app/perf/resources.py`, which runs the product's own scoring job on the GAIA month (34,863 alerts, 62 days, shadow mode) against a throw-away database on the author's Windows laptop (20 logical CPUs, Python 3.12; `results/resources_gaia.json`):

Resource	Measured
Wall time for the whole month in one job (load, score, train and gate, store)	54.9 s (median of 3 runs: 53.7, 54.9, 55.7 s)
Peak memory of the process	505 MB (173 MB of it is Python and the libraries before the job)
Database growth	13.0 MB for 62 days: about 215 KB per day at GAIA's alert volume
One saved model version	0.02 MB
Calls to an external AI service	none, so $0 per call

One timing, one machine. Earlier versions of this report gave two times for the GAIA month: 27 s (a manual timing from 28 September, with no record of the machine or code version) and 35.7 s (one run of `perf/resources.py` on 11 October). Both were re-measured on 11 October on the same laptop with the same code, three runs of `perf/resources.py`: 53.7, 54.9 and 55.7 s. The laptop was on battery power (Windows *Balanced* plan) with other programs open, which may explain why it was slower than the earlier run; the 27 s figure cannot be reproduced and is no longer used. Every document now gives this one measurement. Wall time depends on the machine; the target (≤ 5 min) holds either way.

The cost estimate below rests on **assumptions**, stated so they can be changed: one container per team, running all month (730 hours), on a 2 vCPU / 4 GiB cloud VM (the measured peak of 505 MB leaves room for the web app and the operating system), with a 20 GB disk. Prices are AWS list prices for US East (N. Virginia), Linux, read on 11 October 2026: t3.medium $0.0418 an hour on demand and $0.025 an hour with a 1-year reservation (AWS T3 page); gp3 disk at $0.08 per GB-month (the rate in AWS's EBS pricing examples). Other providers and regions differ; a team's own server costs only its share of an existing machine.

Item	Per team per month
VM, on demand (0.0418 × 730)	$30.51
VM, 1-year reservation (0.025 × 730)	$18.25
Disk, 20 GB gp3 (one year of jobs at GAIA's volume is about 78 MB)	$1.60
AI inference	$0 (in-process scikit-learn model)
Total	**about $20–32**

Not priced: data transfer (pages are a few KB), backups (a copy of a 13 MB database), and the largest cost, people: the queue exists to spend on-call hours on at most K items a day.

AI governance. The operator is responsible for the AI. It may only order and select items in the queue (escalate, ask a person, hide with a reason); it never acts on infrastructure. Humans review everything in shadow mode, answer "ask a person" items, and mark Real / Noise. Every decision records its reason, score and the model version. New models pass a promotion gate and can be rolled back; the change is audited. No data is sent to an external AI service. Full answers: `docs/deployment.md`.

9. MLOps

- **Versioning.** Code in Git through pull requests; dependencies in `uv.lock` and a hash-pinned `requirements.lock`; configuration in `src/config.py` and per-environment files; data by fingerprint in the experiment log; **models as numbered versions with model cards** in `models/registry.json` (training time, data fingerprint, code version, held-out results, gate decision). No prompts (no LLM).
- **Reproducibility.** `uv sync --group dev`, `uv run pytest`, `uv run python run_validate.py`, `docker compose up`; every environment variable is documented; the public datasets are fetched by scripts (`tools/fetch_gaia.py`, `fetch_nab.py`, `fetch_smd.py`, `fetch_rcaeval_mem.py`, `fetch_rcaeval_re23.py`), and `fetch_gaia.py` and `fetch_rcaeval_re23.py` check the SHA-256 of every file used.
- **Model updates.** A new model is trained when a batch has labels of both classes, on the batch's first 7 days, and tested on the rest. It becomes active, and scores the batch, only if on that held-out window (1) it costs less than showing no log alerts (a miss = 10, a false alarm = 1); (2) the whole queue with its alerts costs less (a missed fault = 10, a false item = 1) than both the queue without log alerts and the queue the batch falls back to if the model is refused (the active model, or rules only = severity), by at least a margin of one missed fault (10; `PROMOTION_MIN_SAVING_MISSES`, default 1), so the model is tested against what would actually run and a saving that one held-out case could produce on its own does not promote it; and (3) it costs no more than the active model on the same held-out alerts. The first model is not promoted just because none is active. A model that fails stays a candidate, and the batch is scored by the active model, or by rules only. On GAIA the classifier passes (1) and fails (2) (§B4), so rules only stays. The operator can roll back to any version (`POST /models/{version}/activate`, hash-checked, audited). Precision from engineers'

marks and alert-volume drift are monitored, and a retrain is suggested after 7 days or new Real marks.

- **Why the margin is one missed fault.** The held-out queue cost is counted in whole faults (10 each) and false items (1 each), so a single held-out case that flips moves it by 10. A saving smaller than that could come from one case alone, and the held-out windows are small (14–45 faults on RCAEval). Before the margin, the classifier was promoted on RCAEval RE2 Online Boutique for 3 false items fewer in 45 days (cost 283 against 286 by severity and 291 without log alerts); it is now kept as a candidate. The margin is a setting, not a fit: 0 restores the earlier rule (any strict saving), and a team that wants more evidence can raise it. It was, however, chosen after the RCAEval gate results were seen, so the RCAEval decisions in §B5 are not an independent test of it. The setting is named in missed faults (`PROMOTION_MIN_SAVING_MISSES`), but it is a cost: on RE2 Train Ticket the saving of 10 comes from 10 fewer false items (212 against 222 by severity), not from a missed fault saved; both queues catch 32 of 45. On RCAEval the gate was also run on the same cases that are scored (the later half of each application's recordings), so "promoted on Train Ticket" was decided on its own test set and says what the gate does for that half, not that the decision would hold on later cases (§B5 caveats).
- **Retrain and rollback triggers.** Numeric, from the signals the tool already records. *Automatic* rows are enforced by code; *operator* rows are the runbook (the tool shows the signal, a person acts; it never rolls back on its own).

Trigger	Threshold	Action	Who
Model age	≥ 7 days since training (`RETRAIN_AFTER_DAYS`)	`retrain_due` reminder on the Queue page: run a job with labels (every such job trains and gates a new model)	Automatic flag
New labels	≥ 1 new Real mark since training	Same reminder	Automatic flag
Alert-volume drift	last batch ÷ median of earlier batches outside 0.5–2	Retrain on the next batch; check the alert sources	Operator, from `/monitoring`
Precision from marks	< 0.70 with ≥ 20 marks	Retrain; if it stays < 0.70 for the next 20 marks, roll back	Operator, from `/monitoring`
Promotion gate	new model's held-out queue does not cost at least one missed fault (10) less than both the fallback queue and the no-log-alerts queue	Model is not activated (kept as a candidate)	Automatic
After an activation	precision from the first 20 marks < 0.70, or more than 0.10 below the previous version's	Roll back: `POST /models/{version}/activate` with the previous version	Operator
After an activation	escalated alerts per job more than twice the median of the 7 jobs before it, or a failed scoring job	Roll back as above, then investigate	Operator

- **Testing before release.** CI for code; the promotion gate and shadow mode for models.
- **Experiment tracking.** Every experiment script appends to `app/results/experiments.jsonl`: commit, library versions, configuration, data fingerprint, output hashes, headline metrics and the reason for the run.

Details: `docs/mlops.md`.

10. Monitoring and evaluation

`GET /metrics` (Prometheus) and `GET /monitoring` (checked summary) cover:

Area	Signals	Target
AI performance	Precision from Real / Noise marks; model used and version per job; promotion decisions	≥ 0.70 with ≥ 20 marks
Software / system	Latency by route, 5xx rate, job duration and outcome, pages sent and failed, `/health`	p95 ≤ 1 s; 5xx ≤ 2%; 0 failed pages
Data	Alert-volume drift (last batch vs median), monitoring gaps, rejected and duplicate rows, buffer size	ratio 0.5–2; ≤ 3 gaps
AI / model	Output mix per job (escalated / asked / hidden), items by kind	Watch for sudden shifts

Evaluation criteria with measured values, justification for each target and example alert rules: `docs/monitoring.md`. Offline evaluation is Part B.

11. Privacy and responsible AI

Privacy. Alert messages may contain host names or user IDs. All data stays on the team's server (SQLite and a volume), behind the login. Messages are cut to 300 characters, and IDs and numbers are normalised before learning. Jobs and evaluations are pruned; marks keep only service and time (retention table below). No data is sent to an external AI service; only paging summaries go to the team's own paging tools, in Live mode.

Data retention. Most limits are counts, set by environment variables; the period they give depends on how often jobs run. The periods below assume one scoring job an hour (Alertmanager batches) where a count is converted; rows marked *policy* are what the operator should enforce, because the code does not delete them.

Data	Kept by the code	Period (assumption: one job an hour)	Policy
Ingest buffer (raw webhook rows)	until the next successful job	≤ 1 hour	—
Duplicate fingerprints	`INGEST_DEDUP_HOURS` = 24	24 hours	—
Jobs: alerts, decisions, items	newest `JOB_RETENTION` = 200 jobs	about 8 days (200 days at one job a day)	—
Evaluate my data uploads	newest `EVAL_RETENTION` = 30	depends on use	delete uploads after 30 days
Real / Noise marks (kind, service, time window; no message)	kept	—	12 months, the training window a team needs
Model versions and model cards	every version that was ever active is kept; refused candidates keep their file only for the newest `MODEL_CANDIDATE_KEEP` = 20; every card is kept	size-bound for candidates	keep the active version and the last 5; delete older after 12 months
Audit log file	rotated at `AUDIT_LOG_MAX_BYTE`	size-bound	ship to the team's log store and keep 12 months

Data	Kept by the code	Period (assumption: one job an hour)	Policy
	S = 1 MB, one old file kept		
Backups (`product.backup`)	in a folder the operator owns	—	30 days

Finding and deleting one person's data (a data-subject request). People named in logs have no table of their own: their ID (user ID, e-mail, host name) can only appear in text the team sent. Everything is on the app's volume (`/app/product/data`). Stop the app (`docker compose stop`), open a shell on the same volume (`docker compose run --rm oncall-queue sh`, then `cd product/data`), and for an ID `X`:

- **queue.db** (`python -m sqlite3 queue.db`). Find it with `instr(column, 'X')` in `decisions.message`, `decisions.alert_id` and `decisions.source`; `jobs.meta_json` (the *would have paged* summaries carry up to 200 characters of a message); and `ingest_buffer.payload_json` (raw webhook rows not yet scored). Erase with `UPDATE decisions SET message = replace(message, 'X', '[erased]') WHERE instr(message, 'X');`, the same `replace` on `jobs.meta_json`, and `DELETE FROM ingest_buffer WHERE instr(payload_json, 'X');`. Redacting keeps the queue history and the item ids that Real / Noise marks point to. `jumps` and `feedback` hold no message text (kind, service and times only); `ingest_seen` holds SHA-256 fingerprints that expire after 24 hours.
- **auth.db** (operators, not people in the logs): `sessions.user` is the login name (`DELETE FROM sessions WHERE user = 'X';` signs them out); `events.client` and `locks.client` are client IP addresses.
- **Files.** `grep -rl 'X' audit.log* evals/` finds audit lines (`user=`, `client=`) and *Evaluate my data* uploads (`evals/<id>/*.csv`): delete that evaluation folder and edit the audit file. `model.pkl` and `models/*.pkl` hold a text vocabulary of at most 300 terms, learned after IDs and numbers are normalised, so an ID is normally not in it; if a name is, train a new version on the cleaned data, activate it and delete the old file.
- **Copies.** Backups from `product.backup` hold the same files (apply the same steps, or let them expire after 30 days); summaries already paged to PagerDuty, Slack or Opsgenie must be deleted there.

Responsible AI. Fairness between services: metric rules treat every service the same, and alerts are capped at a quarter of the budget, so services that log a lot cannot crowd out the rest. Every item carries a reason. Humans oversee through shadow mode, "ask a person" and marks. Hidden alerts stay visible. The system never acts on infrastructure. Queue data should not be used to rate engineers. Details: `docs/privacy_responsible_ai.md`.

Appendix C. Testing detail and success criteria

8. Testing strategy

Level	What	Examples
Unit	Detectors, queue, policy, scoring, settings	first come beats biggest first; a jump is confirmed at its second point
Integration	Frontend routes ↔ backend ↔ database, with outbound calls mocked	webhook → buffer → job → queue; Live fans out to every channel; model rollback through the API
System	The whole pipeline on GAIA, NAB, SMD and RCAEval; `experiment.py` on a synthetic run	walk-forward over 8 weeks; later data changes nothing
AI-specific	Wrong or poor outputs, unexpected input, edge cases	a malformed webhook row is rejected instead of blocking every later job; one-class labels fall back to rules; a worse model is not activated; hidden alerts stay visible
Security	Login, SSRF, CSRF, DNS rebinding, secrets, body limits	loopback tricks refused; forwarded requests need a password
Performance	Latency, concurrent users, throughput	`perf/load_test.py`: 20 and 50 users

An optional local LLM can write a shadow note when `LLM_EXPLAIN` is set. That flag is off. The note is written after the page decision and is not sent to a channel. Prompt-injection cases for the note are tested (`test_llm.py`, `test_llm_lora.py`). With the flag off, untrusted webhook content cannot break or steer the queue, and wrong model outputs are bounded by the budget and the promotion gate.

Criterion	Target	Result
Tests passing	100% of tests that run	450 passed, 10 skipped
Line coverage	≥ 85%	86%
Type errors	0	0
p95 latency at 50 users	≤ 1 s	0.32 s
Error rate under load	≤ 1%	0%
Report numbers match results	every checked number	195 / 195

CI runs lint, type checks, the tests on two Python versions with coverage, `run_validate.py`, a dependency audit (`pip-audit` on the hash-pinned lock) and a Docker build with a health check on every push. The audit step was added on 7 October with an option `pip-audit` does not have, so that job failed on that commit; it was corrected on 10 October (a hand run of the corrected command found no known vulnerabilities). Details: `docs/test_plan.md`.

A bug only a real-service test found (version 1.0.2). Live Prometheus data could never confirm a jump. The ingest job fetched 14 days of memory in one query; to stay under Prometheus' point limit, that query used a 121 s step, and the jump rule links hot points at most 2 minutes apart, so no live jump was ever confirmed. The unit tests fed the detector data directly and missed it. A new integration test (`app/integration/docker-compose.yml`, `tests/integration/test_compose.py`) runs the app beside a real Prometheus and Alertmanager and checks webhook → ingest job with Prometheus series → nothing paged in

shadow mode; it found the bug. The fetch now reads the window at 60 s in several non-overlapping queries (`test_a_14_day_fetch_keeps_one_minute_points_so_live_jumps_are_confirmed`), and CI runs the integration test in its own job. The GAIA, NAB, SMD and RCAEval results do not use the Prometheus fetch, so no published number changed.

13. Success criteria

Criterion	Measured	Met?
The main workflow (webhook → queue → page → mark → retrain) completes	Integration tests and the demo	Yes
At least 90% of predefined test cases pass	450 passed, 10 skipped	Yes
The system handles the agreed concurrent users	50 users, 0 errors	Yes
Average response time below the threshold	p50 0.21 s, p95 0.32 s (target 1 s)	Yes
AI output meets the predefined quality criteria	Detector beats the rate rule in 8/8 weeks with fewer false items; the full queue ties it; the alert classifier adds no catches on GAIA (§B4 ablation), and the promotion gate keeps it out there; on RCAEval RE2 Train Ticket it adds +13.3 points over no log alerts, with an interval above zero (+2.2 over severity alerts), and the gate promotes it, at its margin, judged on the same 45 cases that are scored (§B5)	Partly: the detector, yes; the full queue, a tie; the classifier, on one of six RCAEval application suites, not on GAIA
No critical security vulnerabilities in testing	0 critical. R1 through R8 are closed and tested	Yes
Deployable from documented instructions	`docker compose up`, `docs/deployment.md`, CI Docker job	Yes
Another person can reproduce the environment	`uv sync`, lock files, `run_validate.py`	Yes
The agreed functional requirements are met	26 FR, each traced to tests (`docs/requirements.md`)	Yes

Appendix D. GAIA detailed results

B1. Test-period results (K items a day, 55 days, 1,223 faults)

A fault counts as **caught** when the engineer would have seen evidence of it in the queue. There are two ways this can happen. A jump or leak item shown in the queue may be on the same service as the fault and overlap the time the fault was injected. Or a log alert shown in the queue may have been matched to that fault, meaning it came from the faulty service during the fault. Monitoring-gap items never count as catches, even when a fault happens during the gap. They

tell the engineer that the system is blind, not that something is broken, and counting them would reward the queue for missing data.

Baselines are the rules a team would already have, all scored with the same causal queue:

System (K = 20 items a day)	Caught	Share of best possible	Items / day	False / day	Precision
Log severity + exact duplicates	0.0%	0%	0.8	0.8	0%
Static rule: memory > week-1 p99	57.2%	67%	16.0	3.0	81%
Rate rule: `delta(mem[5m]) > 0.5 GB`	68.9%	81%	17.4	2.1	88%
Jump rule, first come	67.8%	80%	17.5	2.4	86%
Jump rule + learned threshold (detector alone)	**72.6%**	**86%**	17.1	**1.0**	**94%**
Full queue with the classifier (jumps + leaks + gaps + classifier alerts; refused by the gate on GAIA)	**69.6%**	**82%**	17.7	1.8	90%
Shipped configuration (the gate keeps the classifier out: jumps + leaks + gaps + log alerts by severity)	**71.0%**	**84%**	17.6	1.4	92%
Old headline: day's jumps ranked by final peak (not real time)	*72.9 %*	*86%*	*17.5*	*1.3*	*93%*

What the tool runs on GAIA is the shipped row. The promotion gate refuses the classifier on GAIA (§B4), so the tool scores log alerts by severity; that row is the same queue with severity alerts (`run_classifier_ablation.py`, `severity`). The full-queue row is kept because every later comparison (walk-forward, options, ablation) was measured on it.

Best possible at K = 20 is 84.9%: GAIA injects 22 faults a day, more than 20 on 34 of 55 days.

At K = 5 / 10 / 50 the full queue catches 19.5% / 38.8% / 85.8% (rate rule: 19.3% / 38.6% / 86.0%). Its advantage is at the realistic budget K = 20, where slots are scarce, and in false items (1.0–1.8 a day vs 2.1).

Removing the last look-ahead. A code review found five places where the queue still used information from later in the day, although the text said it did not. The per-day alert filters kept each day's *most severe* (or highest-scoring) K alerts, which needs the whole day; an overlapping jump that arrived *after* a leak was confirmed could still remove that leak; the robust score used the spread of the whole series; and an alert "rode on" a jump using the jump's final end. All five now use only what is known at the moment of the decision: alerts spend the budget first come, first served; a leak is dropped only by a jump already shown; the robust spread uses earlier points only; and an alert rides on a jump only while the jump's last hot point is within its gap (`Spike.open_at`). `tests/test_causality.py` checks each one. The honest cost is small: the full queue drops from 70.2% to 69.6% at K = 20 and shows 1.8 false items a day instead of 1.6. The detector alone is unchanged (72.6%), because none of the five touched it.


Why the full queue scores below the detector alone on GAIA. Every GAIA fault is a 1 GB memory fault, so leak items (0.2 a day), gap items (0.4 a day) and log alerts spend slots that jumps would have used. On a platform with leaks, outages, and CPU, disk or code faults, those

are the parts that catch them (§B3). Both rows are reported; the detector comparison is the first claim. The full queue is the published configuration with the classifier on; the tool's promotion gate turns the classifier off on GAIA (§B4).

The old ranking needed the whole day in advance. Replacing it with a learned confirmation threshold keeps the score (72.6% vs 72.9%), cuts false items (1.0 vs 1.3 a day), and makes the queue usable live.

Time to confirm. Median **0.72 minutes** from fault start to the confirming point (p90 0.93). Metrics are sampled every 30 seconds.

Chance check. If each service's jumps are shifted by a random 1–6 hours, only **2.6%** of faults still overlap one.



Faults caught versus daily budget K

Where the misses come from

The full queue misses 372 of the 1,223 test faults at K = 20 (`results/miss_causes_gaia.csv`):

Cause	Faults	Share of misses
No metric data during the fault (monitoring outage)	166	45%
A qualifying jump existed, but the day's 20 slots were used	198	53%
Metric data, but no jump overlapped	4	1%
A jump overlapped, but below the confirmation threshold	4	1%

When a fault is missed, the table above shows why. In only 8 of 372 missed faults (2%) did the detector itself fail, either because no jump occurred or because the jump was too small to pass the threshold. The other misses had two causes outside the detector's control. In 166 cases, the service sent no metric data during the fault, and the queue reports such periods as monitoring-

gap items. In 198 cases, a valid jump existed but the day's 20 places were already full. GAIA injects about 22 faults a day, so even a perfect detector would have to leave some out at K = 20.


B2. Validation (walk-forward)

Before each later week, **everything learned is re-learned from the past only** — the classifier, its threshold, the jump ranker and the jump confirmation threshold (0.62–0.75 GB across folds). That week is then scored once. `run_walkforward.py`, K = 20.

Fold	Test week	Faults	With metric data	Rate rule	Detector alone	Full queue
1	8–15 Jul	161	100%	77.6%	84.5%	82.0%
2	15–22 Jul	134	91%	73.9%	81.3%	74.6%
3	22–29 Jul	162	94%	72.2%	77.2%	71.0%
4	29 Jul–5 Aug	163	82%	67.5%	69.3%	67.5%
5	5–12 Aug	162	84%	69.1%	71.6%	71.0%
6	12–19 Aug	139	92%	75.5%	79.1%	74.1%
7	19–26 Aug	173	**61%**	51.4%	52.0%	50.9%
8	26–31 Aug	129	91%	78.3%	83.7%	79.1%
Mean				**70.7%**	**74.8%**	**71.3%** (95% CI 64.5–76.7%)

- The **detector** (jump rule + learned threshold) beats the rate rule in **8/8** weeks (sign test p = 0.0039).
- The **full queue** does **not** beat the rate rule week by week: 4 wins, 3 losses, 1 tie (p = 0.5). Before the look-ahead fixes in §B1 it won 6 of 8; part of that margin came from choosing each day's alerts with hindsight. On GAIA its extra item types cost slots; see §B1.
- The comparison is against a real rule. The log-severity rule scores 0% every week, so a test against it would prove nothing.

Fold 7 is weak because of a **monitoring outage**: every service's metrics stop from 20 Aug 13:18 UTC for 2 days 12 hours, so only 61% of that week's faults have any metric data. The full queue shows this outage as a gap item within 10 minutes. No metric-based method could catch those faults.



Walk-forward detection by later week

B3. Robustness: does it only work because every fault is 1 GB?

`run_robustness.py` adds synthetic faults of other shapes to the **real** GAIA memory series (120 per shape, at least an hour from any real fault) and asks whether each detector fires, with no budget:

Injected shape	Jump rule 0.5 GB	+ learned threshold	Relative +30%	Rate rule	Jump + leak rule
Step +0.25 GB, 10 min	1%	0%	8%	1%	1%
Step +0.5 GB, 10 min	99%	**0%**	58%	99%	99%
Step +1 GB, 10 min (GAIA shape)	100%	98%	95%	100%	100%
Step +2 GB, 10 min	100%	100%	100%	100%	100%
Spike +1 GB, 1 min	98%	98%	92%	100%	98%
Ramp +1 GB over 30 min	1%	1%	6%	0%	**99%**
Leak +1 GB over 3 h	12%	3%	6%	8%	**73%**
Nothing injected (control)	6%	3%	6%	6%	6%

What this shows:

- **Faults smaller than the jump size are invisible** (0.25 GB). A team must set the size for its own services.
- **The learned threshold over-fits the benchmark**: trained on 1 GB faults, it rejects every 0.5 GB fault. The tool therefore uses **no** confirmation threshold unless it is trained on the team's own incidents.
- **Leaks and ramps defeat both the jump rule and the Prometheus rate rule.** The leak rule catches 99% of 30-minute ramps and 73% of 3-hour leaks, at a cost of 0.3 extra items a day on real GAIA data (none of them near a fault), and no extra hits on the control windows.

B4. Queue options

Option (K = 20)	Caught	Items / day	Walk-forward mean	Verdict
Full queue (reference)	69.6 %	17.7	71.3%	—
Learned jump ranker instead of the rise threshold	69.7 %	17.7	71.8%	No gain on this experiment: the rise threshold already gives 94% precision, so there is little left to learn from service, time of day or nearby logs. This row is `p3_ranker` in `queue_eval_gaia.csv`. It is not the later learned ranker (`LEARNED_RANKER`). That ranker, re-run in `docs/results/gaia_ranker_rerun/`, caught 887 against a baseline of 851 of 1,223 at K = 20, KEEP (§B7.2). The flag stays off
Group metric items within 2 min on other services into one slot	70.7 %	17.6	72.6%	Small gain; one item may then name two services
Confirm level per series (learned on week 1; off in the headline)	69.3 %	17.6	70.5%	Mixed: the detector alone keeps 72.6% with fewer false items (0.8 vs 1.0 a day), but the levels reject real faults — 26 misses below threshold instead of 4, and 84.1% vs 85.8% at K = 50. The web app uses it; the published tables use the single gate
Carry over up to 10 unused slots to the next day	**72.6 %**	18.6	**74.8%**	Largest gain; the average stays under K. But the same carry-over lifts the rate rule to 72.5% (walk-forward 74.3%), and the full queue then wins only 3 of 6 decided weeks (p = 0.66). Before the look-ahead fixes this row read 74.4% and 8/8 weeks; that margin did not survive

Ablation: what the alert classifier adds (`run_classifier_ablation.py`, `results/classifier_ablation_gaia.csv`). Same full queue, same week-1 training; only the choice of log alerts for their quarter of the slots changes. The classifier row reproduces the published full-queue numbers exactly.

Log alerts in the queue (K = 20)	Caught	Items / day	False / day	Precision
Chosen by the classifier (the full queue)	69.6%	17.7	1.8	90%
Chosen by log severity + exact duplicates	71.0%	17.6	1.4	92%
None (metric items only)	71.2%	17.4	1.2	93%

On GAIA the classifier does not earn its slots: on net, the alerts it escalates catch fewer faults than the metric items they push out of a full day. At K = 50, where slots are not scarce, all three catch 85.8%. This is why the detector alone is the first claim (§B1) and why the classifier is described as an option for teams whose faults log (§5).

Grouping lets two metric items that are confirmed within two minutes of each other, on different services, share one place in the queue. The idea is that one fault often disturbs a service and its

neighbours at almost the same moment. On GAIA this lifts detection slightly, from 69.6% to 70.7% at K = 20, because the freed places go to other faults. The cost is that one queue item may now point to two services, so the engineer has to check both. Grouping is off by default, because it changes what "20 items a day" means for the team.

Carry-over and grouping are off by default (`CARRY_OVER_MAX`, `GROUP_MINUTES`): they change what "20 a day" means for the on-call team, so it is their choice. The learned ranker flag (`LEARNED_RANKER`) is also off. Its GAIA keep and the homelab measurement are in §B7, and turning the flag on is not part of this report.

Why the severity row attaches no alerts. An alert rides on a jump (no slot of its own) only if it arrives while a shown metric item on *its own service* is still open (`build_queue`). The classifier row attaches 280 alerts that way. The severity row attaches none, and the data explains why (`results/classifier_ablation_gaia.json`). The 507 test alerts that carry a fault are all `warning` (471) or `info` (36); no test alert is `critical` or `high`. So the severity rule never escalates a fault's alert. It escalates 44 `error` lines, with 14 more cut by its own 20-a-day limit. All 44 fall on 4 days, none carries a fault, and they are nightly jobs reporting that a log upload failed. None arrives while a shown metric item on its service is open: the nearest one on the same service is at least 199 minutes away (median 617). So 11 of them take a slot of their own, the rest find the day's alert share or budget used, and the row ends up close to "no log alerts".

What the shipped gate does with this. The tool trains the classifier on the first 7 days of a batch and tests it on the rest (§9). A model must cost less than showing no log alerts on the held-out alerts, and the whole held-out queue with its alerts must cost less than both the same queue without log alerts and the queue that runs if the model is refused (here rules only, log alerts by severity), by at least one missed fault (10). The first model is not promoted just because no model is active. On GAIA the classifier passes the first test: it finds 339 of the 507 fault-bearing held-out alerts. It fails the second: with its alerts the queue catches 848 of 1,223 held-out faults with 95 false items, against 871 with 70 false items with severity alerts and 872 with 58 false items without log alerts. So it is registered as a candidate, and GAIA is scored by rules only (log alerts by severity, as in the second row). The gate's queue is the tool's, not this table's (it uses the tool's own confirm settings), so its counts differ a little from the rows above; the direction is the same. `run_classifier_ablation.py` records the decision in the same JSON file.

B6. What "success" means on this data

`run_stats.py` splits the 1,223 test faults by the signal they left:

Signal	Count	Share	What can catch it
Jump, no log	868	**71.0%**	Metric rule only
Log and jump	185	15.1%	Either path
Log, no jump	34	2.8%	Alerts only
No log, no metric data (monitoring gap)	132	10.8%	Nothing — shown as a gap item
No log, data but no jump	4	0.3%	Nothing

- **Where metric data exists, the jump rule overlaps 99.6% of faults** (1,053 / 1,057).

- 170 test faults start inside a monitoring gap. At K = 20 the gap items shown cover 159 of them (all 170 at K = 50).
- **False jumps are not mislabelled faults.** 24.6% of the 256 false jumps start within 10 minutes of a fault on another service; random times do so 27.2% of the time. There is no sign that GAIA logged faults under the wrong service.
- A log-only classifier is capped near **17.9%** (the faults that leave any log). That is why the early 95% target was wrong.

Early target	Measured	Verdict
95% detection at K=20	69.6–72.6% (ceiling 84.9%)	Not possible at K=20: more faults per day than slots. 82–86% of the ceiling
Beat the usual rule	Detector +3.7 points over a rate rule, 8/8 weeks; full queue +0.7 points, 4 of 8 weeks; log severity 0%	Met by the detector, against a fair rule; the full queue ties it
Fewer false items	1.0–1.8 vs 2.1 a day (rate rule)	Met
Works on every service	Jump overlap 81–91% on all ten	Met
Walk-forward not lucky	Means 71.3–74.8%, CI 64.5–76.7%	Met
Real-time	Confirmed in 0.72 min; no look-ahead, checked by `tests/test_causality.py`	Met
Works beyond 1 GB faults	0.5–2 GB steps and spikes ≥ 98%; leaks 73–99% with the leak rule; 0.25 GB not	Partly — stated

Per service (test period):

Service	Faults	With a log	With a jump
dbservice1	129	0.8%	91.5%
dbservice2	148	2.0%	81.1%
logservice1	126	2.4%	87.3%
logservice2	108	1.8%	87.0%
mobservice1	124	84.7%	83.9%
mobservice2	116	87.1%	87.1%
redisservice1	111	2.7%	82.0%
redisservice2	114	0.0%	86.0%
webservice1	122	0.8%	85.2%
webservice2	125	0.0%	90.4%

Appendix E. Home-lab day-12 detail

B7. Homelab: proposal feedback and the day-12 run

This section answers the four points raised on the proposal, using the frozen day-12 snapshot `day12-rebuilt-20261103T150116Z`. The files are in `docs/results/homelab_day12/`. The snapshot holds 1,184 rebuilt alert episodes (`rebuild_summary.json`), of which 1,182 fall inside the metric window and are evaluated (`topology_stats.json`), plus 1,205 closed faults. The model trains on the first 7 days. `summary.json` records `train_end` `2026-10-28T19:15:11Z` and `test_end` `2026-`

11-02T19:15:03Z: 6 on-call days and 559 test faults. A comparison is a KEEP only when the 95% paired bootstrap interval on the per-fault catch difference, 4,000 draws and seed 42, has a lower bound above zero. That is the same rule as the rest of this report. Intervals below are rounded to four decimal places from the CSV. Product flags stay off: summary.json records LEARNED_RANKER, METRIC_MODEL and LLM_EXPLAIN as off, and flags_changed false. Nothing in this evaluation pages. Three clocks are not the same instant. summary.json records test_end 2026-11-02T19:15:03Z. The snapshot cutoff described with the run is 2026-11-02T19:15:11Z. rebuild_summary.json records end 2026-11-02T19:15:00Z.

B7.1 What this adds over existing tools

Prometheus Alertmanager, PagerDuty and Opsgenie reduce noise by merging alerts that look alike. None of them decides which alerts a person should read when there are more alerts than that person can handle.

Alertmanager "takes care of deduplicating, grouping, and routing" alerts. Grouping "categorizes alerts of similar nature into a single notification". Inhibition mutes some alerts while another alert is firing, and silences mute alerts for a set time (Alertmanager concepts). How often it sends is set by group_wait, group_interval and repeat_interval. Alerts that miss the first group_wait are "sent at the next group_interval instead" (Alertmanager configuration).

PagerDuty Intelligent Alert Grouping "automatically consolidates related alerts into a single, actionable incident, using machine learning". It groups an alert into an open incident when the alert arrives within a time window, the incident is under 24 hours old, and the algorithm finds the alerts similar. It learns from responders merging and moving alerts by hand. By default it looks at one service at a time, and it is part of a paid AIOps add-on (PagerDuty docs).

Opsgenie deduplicates on a user-defined alias: "There can be at most one open alert with the same alias at any time", and a repeat raises the open alert's count instead of creating a new alert (Opsgenie de-duplication).

Capability	Alertmanager (homelab config)	PagerDuty Intelligent Alert Grouping	Opsgenie alias dedup	This system
Merge repeats of one alert	Yes, by group labels	Yes, similarity plus a time window	Yes, the same alias while the alert is open	Yes: an episode ends after a gap of more than 120 seconds, and an alert can ride on an open jump
Learn which signals matter from past incidents	No	Learns how to group, from manual merges	No	Learns how to rank: the classifier and the ranker are trained on labelled past faults
Respect a daily reading budget K	No: every group flush is sent	No	No	Yes: at most K items a day, and log alerts use at most a quarter of K
Use metric behaviour, not only fired alerts	No: it only receives alerts	No: it only receives alerts and events	No	Yes: memory jumps, leaks and monitoring gaps are queue items

Capability	Alertmanager (homelab config)	PagerDuty Intelligent Alert Grouping	Opsgenie alias dedup	This system
Confidence and abstention	No	No	No	Yes: each alert gets a probability; uncertain ones go to a person; a model that does not beat the fallback on held-out data is not promoted
Shadow mode: decide and record, and do not page	No	No	No	Yes, and it is the default. Live paging needs a password, a channel and the typed word LIVE

The homelab's Alertmanager route is in `homelab/config/kps-values.yaml`: group by `alertname`, `company` and `service`; `group_wait` 10 seconds; `group_interval` 2 minutes; `repeat_interval` 1 hour; Watchdog and InfoInhibitor go to the null receiver.

The published queues did not include an Alertmanager baseline. `feedback_analysis.py` replays that route on the rebuilt episodes. Watchdog and InfoInhibitor are dropped. The remaining episodes are grouped by alert name, company and service. A group's first notification goes out 10 seconds after its first episode. Later episodes join a notification that has not been sent yet, or they trigger the next notification at least 2 minutes after the previous one. Each notification is one queue item. It counts as a catch if any episode in it is aligned to a fault by the evaluator's own rule: the same service, and a start inside the fault window. To give Alertmanager the same daily budget K, notifications are cut in two ways. Severity-first sorts each day by the severity label, critical before warning, and then by time. That sort needs the whole day in advance, so it is generous to the baseline. First-come takes them in time order, which is what a live system could do.

The rebuilt episodes record only start times, so `repeat_interval` (re-sending a group every hour while it still fires) cannot be replayed. The notification counts below are therefore a lower bound on what Alertmanager would send.

Volume on the pooled test window, from `feedback_bootstrap.json` key `alertmanager_unbounded`:

	Count
Alert episodes in the test window	547
After the null route	362
Alertmanager groups	31
Notifications (lower bound)	362, which is 60.33 a day (331 warning, 31 critical)
Faults with any aligned routed episode	90 of 559
Notifications that caught a fault, with no budget	precision 0.2486; 45.33 false notifications a day
This system's ranker queue (`p3_ranker`) at K = 20	17.3 items a day, precision 0.673, 5.67 false a day, 68 faults caught

Grouping merged nothing here: the 362 notifications equal the 362 routed episodes. Every episode already ends after a gap of more than 120 seconds, and `group_interval` is 2

minutes, so no two episodes of one group land in the same flush. Even on the most favourable reading, an alert-only tool can catch at most 90 of 559 test faults (16.1%), because only those faults have an aligned alert at all.

Paired bootstrap of the ranker against the Alertmanager-style queues (`feedback_bootstrap.csv`). AM is the baseline. Column heads are kept short so they stay on one line: Set is the population, CI is the 95% interval, Keep is the decision, and the two AM columns are severity-first and first-come.

Set	K	Ranker	AM severity	CI	Keep	AM time order	CI	Keep
Pooled	5	18	0	[0.0179, 0.0483]	KEEP	4	[0.0107, 0.0411]	KEEP
Pooled	10	38	2	[0.0447, 0.0859]	KEEP	13	[0.0233, 0.0662]	KEEP
Pooled	20	68	21	[0.0555, 0.1127]	KEEP	28	[0.0429, 0.1002]	KEEP
Pooled	50	75	69	[−0.0197, 0.0411]	DROP	73	[−0.0268, 0.0340]	DROP
acme	5	19	3	[0.0364, 0.1136]	KEEP	13	[−0.0136, 0.0636]	DROP
acme	10	28	16	[0.0045, 0.1045]	KEEP	23	[−0.0273, 0.0773]	DROP
acme	20	29	36	[−0.0864, 0.0227]	DROP	38	[−0.0955, 0.0136]	DROP
acme	50	29	49	[−0.1500, −0.0318]	DROP (AM better)	49	[−0.1500, −0.0318]	DROP (AM better)
cassini	5	19	2	[0.0556, 0.1444]	KEEP	2	[0.0556, 0.1444]	KEEP
cassini	10	24	8	[0.0389, 0.1444]	KEEP	8	[0.0389, 0.1444]	KEEP
cassini	20	24	26	[−0.0611, 0.0444]	DROP	26	[−0.0611, 0.0444]	DROP
cassini	50	24	39	[−0.1389, −0.0333]	DROP (AM better)	39	[−0.1389, −0.0333]	DROP (AM better)

Borealis could not be scored on its own. Its training week has no alert that overlaps a fault (`summary.json`: "Training data needs both fault and noise alerts").

When the budget is tight, the learned queue is clearly better than Alertmanager grouping. With all three companies sharing 20 slots a day, it catches 68 faults against 21 or 28, at roughly three to four times the precision (0.6731 against 0.175 and 0.2333) and about a third of the false items (5.67 against 16.5 for severity-first and 15.33 for first-come). The advantage disappears once the budget is about as large as the alert stream. A single company sends 23.0 (acme) or 35.33 (cassini) notifications a day. At K = 20 to 50, Alertmanager can therefore show almost all of them, and at K = 50 the interval lies entirely below zero for both companies, so grouping catches more faults than the ranker. The ranker does not fill its budget: acme uses 6.5 items a day out of 20 (1.5 false a day), against Alertmanager severity-first at 17.33 items a day (11.33 false a day). The ranker gives up some catches to keep the queue short. The claim that the files support is this:

the system wins when attention is scarce, which is the alert-fatigue setting. When a team can read every alert, plain grouping catches more.

B7.2 Beating severity ranking

The examiner asked whether the trained model beats simply ranking log alerts by severity. The project's severity baseline, `logs_severity`, escalates `critical`, `error` or `high` alerts, suppresses exact repeats, and fills the day first come. It is run inside the same queue and scored the same way.

Paired bootstrap of `p3_ranker` against `logs_severity` (`feedback_bootstrap.csv`; 559 pooled test faults, 220 acme, 180 cassini). Set is the population, CI is the 95% interval, Keep is the decision, and P / false is precision and false items a day.

Set	K	Ranker	Severity	CI	Keep	Ranker P / false	Severity P / false
Pooled	5	18	0	[0.0179, 0.0483]	KEEP	0.600 / 2.00	0.000 / 0.33
Pooled	10	38	0	[0.0465, 0.0894]	KEEP	0.672 / 3.17	0.000 / 0.33
Pooled	20	68	0	[0.0948, 0.1485]	KEEP	0.673 / 5.67	0.000 / 0.33
Pooled	50	75	0	[0.1055, 0.1610]	KEEP	0.675 / 6.17	0.000 / 0.33
acme	5	19	0	[0.0500, 0.1228]	KEEP	0.704 / 1.33	0.000 / 0.17
acme	10	28	0	[0.0864, 0.1773]	KEEP	0.763 / 1.50	0.000 / 0.17
acme	20	29	0	[0.0909, 0.1818]	KEEP	0.769 / 1.50	0.000 / 0.17
acme	50	29	0	[0.0909, 0.1818]	KEEP	0.769 / 1.50	0.000 / 0.17
cassini	5	19	0	[0.0611, 0.1556]	KEEP	0.679 / 1.50	none shown
cassini	10	24	0	[0.0833, 0.1833]	KEEP	0.615 / 2.50	none shown
cassini	20	24	0	[0.0833, 0.1833]	KEEP	0.615 / 2.50	none shown
cassini	50	24	0	[0.0833, 0.1833]	KEEP	0.615 / 2.50	none shown

The ranker is a KEEP over severity in all 12 comparisons. Severity catches nothing here because of what the lab actually emits (`topology_stats.json`). The only critical alert is `HomelabErrorRateHigh` (75 episodes), and none of those episodes is aligned to a fault. All 215 alert episodes that are aligned to a fault are warnings (214 `HomelabCpuHigh`, 1 `HomelabMemoryHigh`). Cassini (Sock Shop) emits no traces, so its trace-based error-rate rule never fires and it has no critical alerts at all. A severity rule therefore never escalates an alert that belongs to a fault. This repeats the GAIA finding, where log severity also caught 0% at K = 20 (§B1).

Beating a rule that shows almost nothing is a weak test, so the Alertmanager severity-first queue in §B7.1 was also run. It ranks every routed alert by severity and then by time, and it fills the whole budget. Pooled, the ranker still wins at K = 20 (68 against 21, interval [0.0555, 0.1127]). Within a single company it loses at generous budgets, as §B7.1 says.

On GAIA, the learned ranker added in PR #26 was re-run on 3 November 2026 (`docs/results/gaia_ranker_rerun/summary_by_k.csv`, time split, seed 42, 4,000 draws). At K = 20 it caught 887 of 1,223 faults (72.5%) against the baseline variant's 851, a difference of +0.0294 with interval [0.0147, 0.0442], KEEP. That 72.5% is not the jump

detector's 72.6% in §3. Precision is 0.9416 against 0.895, and false items a day are 1.0 against 1.82. That baseline equals the `proposed` row in `app/results/queue_eval_gaia.csv`. K = 5, 10 and 50 are DROP. Walk-forward pooled is KEEP, +0.0262 with interval [0.0131, 0.0401]. GAIA has no companies, so this is not leave-one-company-out. `queue_eval_gaia.csv` also has 887 catches at K = 20 on the row `delta_5m_carryover`. That is a different queue, the rate rule with unused slots carried over, and it is not this ranker. `LEARNED_RANKER` stays off.

B7.3 Fault topology and deduplication

Prometheus re-evaluates a firing alert every scrape, and the original collector wrote a new row on every pass while an alert stayed firing. By 31 October the live `alerts.csv` held 87,501 rows and only 979 distinct firing episodes. That pair was reported with the collector fix. The text file named in the analysis notes was not in the day-12 archive, so it is not among the files in `docs/results/homelab_day12/`. The fix, and the rebuild from Prometheus `ALERTS{alertstate="firing"}` history, apply one rule. An episode is one continuous firing of one alert series. A gap of more than 120 seconds with no firing sample ends it, and the next firing sample starts a new episode with a new id. An episode that is still firing keeps its id across collector passes, because it is tracked in `.alerts.episodes.json`. The day-12 snapshot rebuilt this way holds 1,184 episodes from 44 alert series (`rebuild_summary.json`).

The 1,182 evaluated episodes, from `topology_stats.json`, break down as follows.

Category	Alert name(s)	Episodes	Severity
CPU	HomelabCpuHigh	444	warning
Meta, routed to null	InfoInhibitor	420	none
Memory	HomelabMemoryHigh	159	warning
Latency	HomelabLatencyP95High	76	warning
Error rate	HomelabErrorRateHigh	75	critical
Pod restart	HomelabRestarted (2), KubePodCrashLooping (1)	3	warning
Cluster or node	NodeMemoryMajorPagesFaults (3), KubePodNotReady (1), KubeDeploymentRolloutStuck (1)	5	warning

Company (application, rule profile)	Episodes	Mix
cassini (Sock Shop, noisy)	619	CPU 285, meta 202, memory 132
acme (Online Boutique, noisy)	523	meta 218, CPU 159, latency 76, error rate 42, memory 27, restart 1
borealis (OpenTelemetry Demo, strict)	34	error rate 33, restart 1
cluster	6	node 3, Kubernetes 2, restart 1

The alert stream is shaped by the rule profile, not only by the faults. The strict profile (borealis) has no CPU or memory rules and needs a longer breach before it fires. It produced 34 episodes for 308 injected faults. The noisy profiles fire on smaller moves. The busiest sources are `acme/unknown` (218) and `cassini/unknown` (202), which are InfoInhibitor, followed by `acme/otel-collector` (118), `cassini/front-end` (107) and

`cassini/loadgenerator` (91). None of these five is a service that faults were injected into.

The evaluator's strict rule, same service and episode start inside the fault window, links only 215 of 1,182 episodes to a fault, covering 214 of 1,205 faults. To study topology, a looser window was used: any routed episode in the same company that starts between the fault's start and 10 minutes after its end (`fault_fanout.csv`). Because faults are frequent, a chance line was also computed by shifting every fault window by a random 1 to 6 hours, 20 repeats, seed 42 (`fanout_chance.json`).

	Real windows	Shifted windows (mean, min–max)
Faults with at least one episode in the window	512	239.2 (220–256)
Faults with an episode on the faulted service itself	369	17.4 (10–21)
Faults with episodes on two or more services	26	9.7 (5–16)
Faults with episodes only on other services	143	—

Fault type	Faults	Any episode	On the faulted service	Only elsewhere	Two or more services
cpu-stress	284	284	284	0	17
pod-kill	292	102	84	18	8
network-delay	321	117	1	116	1
memory-stress (borealis only)	128	3	0	3	0
network-loss (borealis only)	125	5	0	5	0
http-abort (borealis only)	55	1	0	1	0

Alerts land on the faulted service far above chance (369 against a shifted mean of 17.4). Every CPU-stress fault (284 of 284) produced an episode on its own service. Network faults appear somewhere else. A network-delay fault fires an alert on its own service only once in 321 faults, while 116 alert on other services. The most common pairs are infrastructure, not business call edges: `acme/cartservice` to `acme/otel-collector` (27) and `acme/frontend` to `acme/otel-collector` (21), and cassini services to `cassini/loadgenerator` or `cassini/front-end`. In acme, the shared OpenTelemetry collector is a hub that many faults show up on. Real multi-service fan-out is rare. Only 26 faults, all in cassini, light up two or more services, against a shifted mean of 9.7. Most faults that alert at all produce one episode (1.14 on average when any episode is present).

No dependency graph is available to the evaluation. Neither the homelab manifests nor `companies.yaml` encode service dependencies. The three applications have public call graphs, but those graphs are not in this repository. The trace-graph model (`src/trace_graph.py`) builds call graphs from spans, and it was evaluated on RCAEval, not on the homelab. The pairs above are observed co-firing only. They are not proven dependencies.

How the same episodes fold down (`topology_stats.json`, `fold_down`; all 1,182 evaluated episodes):

Step	Items	Reduction
Live collector rows before the fix (to 31 October)	87,501	—

Step	Items	Reduction
Firing episodes (120-second gap rule)	1,182	the main deduplication step
After Alertmanager's null route	762	420 InfoInhibitor episodes removed
Alertmanager groups (alert name, company, service)	41 groups	—
Alertmanager notifications (lower bound, no repeats)	762	none: `group_interval` merges nothing once episodes exist
Same-company bursts (episodes chained within 2 minutes, any service)	713	49 fewer (6.4%)

Inside the queue, `p3_grouped` attaches a metric item that is confirmed within 2 minutes of a shown metric item on another service, so the two share one slot. Pooled at K = 20, `topology_stats.json` records 11 attached alerts for `p3_grouped` against 5 for `proposed`, 53 faults caught against 51, and 9.83 against 9.67 false items a day. `p3_carryover` catches 54. Neither change is tested for significance here. Both stay off by default, as on GAIA (§B4).

In this lab, deduplication is mostly a matter of time, one episode per continuous firing, not of topology. Cross-service grouping saves about 6% of episodes. The faults that most need topology are the network faults, because their symptoms appear on a different service from the cause. Those symptoms land on shared infrastructure, the telemetry collector and the load generator, rather than along a call graph. Linking the homelab's Tempo spans to the trace-graph model is the clear next step. That link is not built here.

B7.4 Homelab final evaluation (day 12)

Three simulated companies run in one k3d cluster in shadow mode, with Chaos Mesh injecting faults. Acme runs Online Boutique, with steady load and noisy rules. Borealis runs the OpenTelemetry demo, with a daily load and strict rules. Cassini runs Sock Shop, with bursty load and noisy rules. Nothing is paged. The learned ranker is trained on the first 7 days and scored on the next 6. Alerts are the 1,184 episodes rebuilt from Prometheus, which is why this run is called rebuilt.

Two data bugs were found and fixed before the final run, in draft PR #30, with tests. The evaluator could read `metrics.csv` while the collector was still writing it, and then saw metrics that stopped before the alerts, so two runs on the same data disagreed. Tables are now written to a temporary file and renamed into place, and the evaluator refuses to run if the metrics end more than 30 minutes before the alerts. Evaluations run on a frozen snapshot. Separately, the collector wrote one row per pass for each alert that was still firing. It now tracks open episodes, and the day-12 alerts were rebuilt from Prometheus history with the same 120-second rule.

Pooled result, all three companies in one queue (`pooled_bootstrap.csv`). The ranker is the candidate. Each block is caught faults, the 95% interval, and the keep decision, against proposed, tuned jumps, and static p99.

K	Ranker	Proposed	CI	Keep	Tuned jumps	CI	Keep	Static p99	CI	Keep
5	18	12	[0.0036, 0.0197]	KEEP	14	[−0.0018, 0.0179]	DROP	2	[0.0143, 0.0447]	KEEP
10	38	31	[0.0018, 0.0250]	KEEP	28	[0.0054, 0.0322]	KEEP	12	[0.0233, 0.0698]	KEEP
20	68	51	[0.0161, 0.0465]	KEEP	54	[0.0107, 0.0411]	KEEP	15	[0.0644, 0.1234]	KEEP
50	75	81	[−0.0215, −0.0018]	DROP (proposed better)	70	[−0.0054, 0.0250]	DROP	27	[0.0555, 0.1181]	KEEP

At K = 20 the ranker shows 17.3 items a day with precision 0.6731 and 5.67 false items a day. The proposed queue has precision 0.4775 and 9.67 false items a day (`pooled_bootstrap.csv`). At K = 50 the proposed queue catches 6 more faults, and the interval excludes zero. The ranker stops near 19 items a day, so it gives up catches for precision. Against `logs_severity` the same ranker is a KEEP at K = 5, 10, 20 and 50 (§B7.2). The K = 5 comparison with tuned jumps is the exception inside the tight budgets: 18 against 14, with an interval that includes zero, so that one cell is a DROP.

Within each company, trained and tested on its own data (`pooled_bootstrap.csv`), the ranker ties or slightly trails `proposed` at acme at every K. At K = 20 it catches 29 against 31, and the decision is DROP. At cassini it is a KEEP against `proposed` at K = 5 and 10, and at K = 20 and 50 both catch 24, so the decision is DROP. Against tuned jumps, cassini is a KEEP at every listed K, including K = 20 (24 against 20).

The strict test is leave-one-company-out: train the ranker on the other two companies and test it on the held-out company, at K = 20 (`ranker/leave_one_company_out.json`).

Company	Baseline	Ranker	CI	Keep
acme	32 of 220	32	[0.0, 0.0]	DROP
borealis	25 of 159	25	[0.0, 0.0]	DROP
cassini	21 of 180	21	[0.0, 0.0]	DROP

What this run shows, and what it does not show, follows from those files.

The pooled KEEP is in distribution. The ranker was trained on the same three companies, in an earlier week. At K = 5, 10 and 20 it catches more than `proposed` and `static_p99`, and at K = 10 and 20 it also catches more than tuned jumps, with the K = 5 tuned-jump cell a DROP as above. It also beats severity ranking at every listed K. It shows that the learned queue is cleaner, and catches more, than those rule queues at a scarce budget on a platform it has already seen.

It does not transfer to a company it has never seen. Leave-one-company-out is a DROP for all three companies, with exactly the same catches as the baseline.

When the budget is generous (K = 50), the simpler `proposed` queue catches more, and Alertmanager-style grouping wins inside a single company (§B7.1).

Detection is low overall: 68 of 559 test faults at K = 20, about 12%. Many faults leave no alert, and the strict profile hides most of borealis.

On GAIA the same ranker caught 887 against 851 of 1,223 at K = 20 and was a KEEP (§B7.2, `docs/results/gaia_ranker_rerun/`). The homelab therefore supports that keep inside one platform it has already seen. It does not yet show that the ranker generalises to a company that was held out of training. GAIA itself has no companies, so its split is by time, not leave-one-company-out.

B7.5 One alert through the pipeline

This example is taken from `worked_example.json` (pooled run, K = 20). Times are UTC.

At 23:32:49 on 28 October, Chaos Mesh starts a CPU-stress experiment on the `catalogue` service of cassini. It ends at 23:36:49. The fault id is `cassini-20261028T233249Z-cpu-stress-catalogue`. It falls in the test window, so no model has seen it.

The collector reads `catalogue`'s memory working set. The jump rule, relative mode at 30% above the recent median, marks a jump starting at 23:32:53, four seconds after the fault began. The jump is shown in the queue at 23:33:15. Its rise at confirmation is 3,436,544 bytes. The learned ranker keeps it, so it takes one of the day's 20 places. `worked_example.json` records `ranker_metric_items_catching` as 62. This jump's fault list contains this fault.

Prometheus's `HomelabCpuHigh` rule starts firing at 23:36:00. The collector turns that firing into one episode, id `96e96f9c0538ee2a`, source `cassini/catalogue`, severity warning. Later samples of the same firing extend this episode rather than adding rows, because a new episode starts only after a gap of more than 120 seconds.

For evaluation only, the alert started on the faulted service inside the fault window, so the evaluator links it to the fault. The model does not see that label for test alerts.

The alert classifier, trained on the first 7 days, gives this alert a probability of 0.9890 (file value 0.988979). The file's `alert_threshold` is 0.6658. The decision is escalate, with reason "policy top-k". One input is that the alert arrived while a memory jump on the same service was open (`during_memory_spike` is 1).

The jump on `cassini/catalogue` is still open at 23:36:00, and `attached_to_jump` is true. The alert is attached to the jump rather than given its own place. The engineer sees one incident, and it uses one place out of 20.

The severity rule suppresses the same alert, with the reason "severity 'warning' below threshold". An Alertmanager-style group for this alert name, company and service would send its first notification 10 seconds after the episode start, at 23:36:10, because `group_wait` is 10 seconds. That is later than the jump the queue had already shown. Across the test window that grouping sends 60.33 notifications a day, so this one would compete with the rest of them.

The learned queue surfaced the fault from a metric, before this alert had fired. When the alert arrived, the queue merged it into the same incident. The severity rule ignored the alert. Plain grouping would have delivered it later, as one notification among many.

Appendix F. Generality beyond GAIA

B5. Beyond microservices: any metric, any team

The engine is not tied to GAIA. `src/generic.py` takes any **metrics** table (time, value, optional series; long or wide; column names detected), optional **events** (alerts, tickets, notifications) and optional **past problems** (start, end, series). For each series it tunes on the first part and scores the rest once, and every system — static threshold, rate rule, a unit-free robust jump rule, the user's own alerts — is tuned with the same cost and scored through the same causal queue. The detector with the lowest training cost becomes the user's queue. A **chance line** (the same items at random times) is reported so wide labels cannot flatter the result.

This runs from the web app (**Evaluate my data**: upload or pick a dataset → read the report → *Use these settings for my live queue* → *Show this data in the queue*) and from the CLI (`evaluate`, `tune`). The guide for end users is `USE_YOUR_DATA.md`.

Results on data that is not microservices (tuned on the first half of each series, K = 2 items a day; `run_nab.py`, `results/nab_eval.csv`):

Dataset	Domain	Test problems	Queue caught	Chance	Items / day
Online shop (synthetic; K = 5, 30% tuning)	e-commerce orders + notifications	11	91%	1%	1.3
NAB realAWSCloudwatch	cloud servers	17	71%	58%	0.3
NAB realAdExchange	online advertising	6	83%	58%	1.4
NAB realKnownCause	machine temperature, taxi demand, CPU	13	38% (static rule 54%)	15%	0.04
NAB realTraffic	road traffic sensors	11	36% (rate rule 45%)	12%	0.3
NAB realTweets	Twitter mention volume	11	36%	36%	1.7

On the shop data the monitoring view catches 10 of 11 problems where the notification stream by severity catches 3. On NAB the queue is clearly above chance on traffic and machine data, modestly on cloud servers and ads (NAB's anomaly windows are wide, so chance is high), and **no better than chance on Twitter volume**. The test sets are small (6–17 problems), and on one dataset the detector chosen on the tuning part was not the best on the test part. These are exactly the facts a new user needs before relying on it, which is why the app shows them.

Other fault types: the Server Machine Dataset (SMD). GAIA has one fault type. SMD (OmniAnomaly, KDD 2019) has 28 real servers, five weeks of one-minute samples, 38 metrics each — CPU, memory, disk, network, TCP — and 196 labelled test incidents, each with the metrics that moved. Each machine is one dataset: tuned on the first half of every series, scored on the second half, K items a day per machine (`run_smd.py`, `results/smd_eval.csv`):

Budget K per machine	Incidents caught (196)	Metric movements shown (1,536)	Items / day	False / day	Chance (per movement)
5	60 (30.6%)	10.1%	4.2	3.5	12.4%
10	83 (42.3%)	19.3%	7.9	6.5	12.4%
20	108 (55.1%)	33.9%	13.8	11.0	12.4%

An incident counts once and is caught if any metric that moved was shown while it lasted; the movement column counts every flagged metric on its own. Half of the incidents are found at 20 items a day per machine on real mixed-metric faults, well above the 12.4% chance line, but with low precision: SMD labels only some of the 38 metrics per incident, so a correlated movement on an unlabelled metric counts as false. Where a series had three or more tuning incidents the jump rule learned its own size (Section 4 of `USE_YOUR_DATA.md`). This is a harder benchmark than GAIA and it is reported as it is.

Same memory fault, three applications (RCAEval RE1). RE1 injects one memory fault, five times on each of five services, into Online Boutique, Sock Shop and Train Ticket (75 recordings; RCAEval). Each recording is scored on its own. The first 12 recordings of an application tune the queue; the later 13 are scored once. Those later recordings are then laid end to end, about one day, and the daily cap is applied. Thresholds come from that application's own training recordings (`run_rcaeval.py`, `results/rcaeval_mem.csv`).

The labelled service's memory series does move: median rise 0.51 GB, 0.30 GB and 0.33 GB. With the cap off, the jump rule overlaps 100%, 92.3% and 61.5% of the later injections, each above that rule's chance line (28.5%, 47.1%, 40.9%).

Application	Memory series	Median rise	Jump episodes on the test recordings	Jump, no cap	Chance	Queue at K = 5
Online Boutique	12	0.51 GB	744	100%	28.5%	0%
Sock Shop	15	0.30 GB	235	92.3%	47.1%	0%
Train Ticket	64	0.33 GB	1,512	61.5%	40.9%	0%

The queue that would page someone catches 0 of 13 faults on every application at K = 2, 5 and 10. On the training recordings the jump rule caught all 12 faults and also raised 679, 220 and 1,323 other episodes. At the usual cost (a miss counts 10, a false episode counts 1) that is more expensive than a rate rule which raises nothing, so the tuner keeps the rate rule. Under the same cap the jump rule still misses: the test day contains hundreds of episodes and five slots, and the slots go to episodes that miss the injection. The fault is visible on all three applications. This budget and this cost leave it off the page.

Second dataset for the AI component: RCAEval RE2 and RE3 (logs and metrics). On GAIA the alert classifier adds no catches (§B4), so it is tested again on the 360 RCAEval cases that have logs: RE2 (cpu, memory, disk, delay, packet loss and socket faults; 90 cases per application) and RE3 (code-level faults F1–F5; 30 per application), in Online Boutique, Sock Shop and Train Ticket (RCAEval, MIT licence). `tools/fetch_rcaeval_re23.py` downloads the logs and metrics (about 570 MB; traces are not used) and checks the SHA-256 of all 720 files; `run_rcaeval_logs.py` scores them (`results/rcaeval_logs.csv`, `results/rcaeval_logs.json`).

How the recordings were used (a documented subset, fixed before scoring): cases in start order, the first half trains (classifier, its threshold and the jump confirm gates) and the later half is scored once (the promotion gate is run on that same later half, see the caveats); each recording is laid on its own on-call day, so K is per case; the fault is the root-cause service from the injection to the end of the recording. Metrics: the product's unit-free jump rule (robust mode) on each

service's cpu, memory, disk I/O, socket, p90 latency and error series; leaks and gaps are off, and jumps that start in the first 5 minutes of a recording (a short rolling baseline that live data never has: 43% of all jumps) are dropped. Logs: a line is an alert only at warning or error level (from its level token, or error words when it has none); identical lines from one service within 60 s are one alert. **An alert counts as a catch only if it comes from the root-cause service after the injection**, the same rule as GAIA; on Online Boutique many faults log at the caller (`frontend`) as well as, or instead of, the broken service, so this rule is strict. Every variant shares the same metric items; only the log alerts change, as in §B4. Daily budget K = 10 (2 alert slots; K = 5 and 20 are in the CSV). Rates have 95% Wilson intervals; the difference to "no log alerts" has a 95% bootstrap interval over test cases. The *placebo* column scores the same no-log-alerts queue against a fake fault on the root-cause service in the quiet part of each recording (7 minutes; 10 on RE3 Train Ticket): metric catches by chance are rare.

Suite	Application	Test cases	No log alerts	Severity	Classifier (95% CI)	Classifier − no log alerts, points (95% CI)	False items / day: none / severity / classifier	Placebo catches	Gate
RE2	Online Boutique	45	44.4 %	46.7 %	46.7% (32.9%–60.9%)	+2.2 pts (+0.0 to +6.7)	0.42 / 0.53 / 0.47	0 / 45	refused: saves 3, margin 10
RE2	Sock Shop	45	84.4 %	84.4 %	86.7% (73.8%–93.7%)	+2.2 pts (+0.0 to +6.7)	1.42 / 3.38 / 3.13	2 / 45	refused (rules only)
RE2	Train Ticket	45	60.0 %	71.1 %	73.3% (59.0%–84.0%)	+13.3 pts (+4.4 to +24.4)	3.27 / 3.87 / 3.56	2 / 45	**promoted**: saves 10, margin 10
RE3	Online Boutique	15	100.0 %	100.0 %	100.0% (79.6%–100.0%)	+0.0 pts (+0.0 to +0.0)	0.53 / 1.60 / 0.53	0 / 15	refused (rules only)
RE3	Sock Shop	15	93.3 %	93.3 %	93.3% (70.2%–98.8%)	+0.0 pts (+0.0 to +0.0)	4.07 / 5.40 / 4.67	1 / 15	refused (rules only)
RE3	Train Ticket	15	100.0 %	100.0 %	100.0% (79.6%–100.0%)	+0.0 pts (+0.0 to +0.0)	1.93 / 3.67 / 1.93	0 / 15	refused (rules only)

What this shows, with only 45 (RE2) or 15 (RE3) test cases per application:

- **The classifier does add catches on one application.** On RE2 Train Ticket, where faults leave error logs on the broken service, it catches 6 faults the metric items miss and loses none: +13.3 points, interval +4.4 to +24.4. Severity alerts gain 5 cases, with more false items a day (3.87 against 3.56). On RE2 Online Boutique and Sock Shop it adds one case each (interval includes 0).
- **On RE3 the metric items already catch 93–100%** of the code faults at K = 10, so log alerts cannot add catches there; the classifier keeps the false items at the metric-only level on two applications, where severity adds 1.1–1.7 a day.
- **Sock Shop logs are noisy:** both alert variants add 1.7–2.0 false items a day on RE2 (the classifier 1.71, severity 1.96).

- **The promotion gate decides per application, as designed.** With the margin of one missed fault (10, §9) it promotes the classifier only on RE2 Train Ticket. There the queue with its alerts catches 32 of 45 held-out faults with 212 false items, against 32 with 222 by severity and 28 with 198 without log alerts: cost 342 against 352 and 368, a saving of 10, **exactly the margin**. So against what would run instead (severity alerts) the classifier buys no extra catch on the gate's window, only 10 fewer false items in 45 days; the +13.3 points in the table are against no log alerts. A margin above one missed fault would refuse it too. On RE2 Online Boutique, which the gate promoted before the margin, the queue with its alerts costs 283 against 286 by severity and 291 without log alerts (18 of 44 held-out faults with 23 false items; 18 with 26; 17 with 21): a saving of 3, below the margin, so it is kept as a candidate. The gate refuses it on RE2 Sock Shop (more false items than it buys) and on all of RE3 (no catch to buy). The gate splits at the first alert's time of day, so on RE2 Online Boutique and RE3 Online Boutique and Train Ticket its held-out window starts after one test case's injection (one held-out fault fewer); its queue check also keeps the early-recording jumps, which cost all three of its queues the same slots.

Caveats: small test sets (the 95% intervals are 20–30 points wide); one train/test split per application; recordings are short (24–30 minutes) and replayed one per day, which is not a live stream; labels are the dataset's root-cause service, so a caller's error log counts as noise; the level rule for logs without a level token is a keyword list. The classifier's value is therefore **shown on one of six application suites, with a confidence interval that excludes zero** against no log alerts, and the gate keeps it out where it does not pay; against severity alerts its gain there is small (no extra catch on the gate's window). **The gate's window is the scored window.** `run_rcaeval_logs.py` runs the product's gate (`product_gate()`) with its split set to the same case boundary as the ablation, so the gate's held-out window is the set of test cases that is scored (45 of 45 on RE2 Train Ticket; 44 of 45 on RE2 Online Boutique, whose gate window starts after one test case's injection) and the model it tests is trained on the same first half. "Promoted on RE2 Train Ticket" was therefore decided on its own test set: it says what the gate does for this half of the recordings, not that the same decision would hold on later cases, and the table's +13.3 points were measured on the same cases. In the product the gate's window is the tail of a batch and later batches are scored, so the live design does not overlap; only this evaluation does. It was left as it is because the test sets are small (a further split of 45 cases would leave about 22 on each side, too few to decide anything) and a separate gate window would change every gate result in this section; it is listed under future work.

Appendix G. Reproduction and checked numbers

C1. How to reproduce

```
python tools/fetch_gaia.py
cd app
uv sync --group dev
uv run pytest -q
uv run python run_memory.py --metrics data/gaia_metrics --gaia-run
data/gaia_raw/run/run --sweep
uv run python run_queue_eval.py
uv run python run_classifier_ablation.py
uv run python run_walkforward.py
```

```
uv run python run_stats.py
uv run python run_robustness.py
uv run python ../tools/fetch_nab.py
uv run python run_nab.py
uv run python ../tools/fetch_smd.py
uv run python run_smd.py
uv run python ../tools/fetch_rcaeval_mem.py
uv run python run_rcaeval.py
uv run python ../tools/fetch_rcaeval_re23.py
uv run python run_rcaeval_logs.py
uv run python perf/resources.py
uv run python make_figures.py
uv run python run_validate.py
```

On PowerShell, set `$env:PYTHONPATH` to the `app` directory and call `python` instead of `uv run python`. The GAIA ranker re-run is `docs/results/gaia_ranker_rerun/commands.sh`. The day-12 snapshot is `homelab/snapshots/day12/day12-rebuilt-20261103T150116Z.tar.xz` (xz SHA-256 `378dc71f3ef4143662acc1d0a3dda8c5e32f7752f3ceb77efe9b88bf0985c56e`; the original gzip SHA-256 is `968940267defb49a6f92c93824369560c417fa8df4546d85c3009938cf9da782`). Reproduce Table 2 with `./homelab/scripts/reproduce_day12.sh`.

Needs the GAIA files at `app/data/gaia_raw/run/run` and `app/data/gaia_metrics` (not in git; they are large). `python tools/fetch_gaia.py` (from the repository root) downloads them from the GAIA MicroSS dataset (https://github.com/CloudWise-OpenSource/GAIA-DataSet, `MicroSS/run/run.zip` and the split archive `MicroSS/metric/metric_split.*`, about 1.8 GB), extracts the two run tables and the 37 `docker_memory_usage_total` series into that layout, and checks each file's SHA-256 against the copy used for these results (`check` verifies files already in place). Without GAIA: `python examples/make_example.py`, then `python -m product.cli score --alerts examples/alerts.csv --metrics examples/metrics.csv`.

A faster check without GAIA: `cd app && uv sync --group dev && uv run pytest -q && uv run python run_validate.py` (the result files are in git). Every experiment run is logged in `app/results/experiments.jsonl` (`docs/mlops.md`).

C1a. Use of AI tools

AI coding assistants were used while building this project: for code review, refactoring, test writing and drafting documentation (visible in the repository history as the `claude/*` branches merged through pull requests #2 to #5, and in `AGENTS.md`). The runtime system uses no generative AI or external AI service. Every number in this report comes from the scripts in and is checked against `app/results/` by `run_validate.py`; the test suite, lint, type checks and the dependency audit run in CI. Design decisions, the evaluation method and the claims made here are the author's responsibility.

C2. Deliverables

Item	Where
Design	`design_specification.md`
Requirements and traceability	`docs/requirements.md`
Architecture diagrams	`docs/architecture.md`
Design decisions	`docs/adr/`
Threat model	`docs/threat_model.md`
Test plan and CI gates	`docs/test_plan.md`, `.github/workflows/ci.yml`
Deployment, environments, AI governance	`docs/deployment.md`, `app/deploy/*.env`
MLOps: versioning, updates, experiment tracking	`docs/mlops.md`, `app/results/experiments.jsonl`
Monitoring and evaluation	`docs/monitoring.md`, `/metrics`, `/monitoring`
Privacy and responsible AI	`docs/privacy_responsible_ai.md`
Performance results	`app/perf/load_test.py`, `app/results/perf/`
Retrospective	`docs/retrospective.md`
Change history	`CHANGELOG.md`
Plan / roadmap	`project_plan.md`, `ROADMAP.md`
Validation record	`VALIDATION.md`
Review of the earlier version	`CODE_REVIEW.md`
This report	`FINAL_REPORT.md`
Code + tests	`app/`
Result tables	`app/results/`
Figures	`figures/detection_vs_k.svg`, `figures/walkforward.svg`, `figures/use_cases.svg` (UML use cases)
Tool	Web app `docker compose up` (http://127.0.0.1:8080/, **/evaluate** for your own data), CLI `python -m product.cli`
End-user guide	`USE_YOUR_DATA.md`

Checked numbers

`python run_validate.py` (in `app/`) recomputes every value below from `app/results/` and fails if one no longer rounds to what is printed here, if a key is missing, or if a sentence it guards (for example "the detector wins 8/8 weeks") stops being true. Rates are shares of test faults; `false` is false items a day.

Key	Value	Where in this report
`queue.K20.logs_severity`	0.0%	§B1 table
`queue.K20.static_p99`	57.2%	§B1 table
`queue.K20.delta_5m`	68.9%	§B1 table
`queue.K20.jumps_online`	67.8%	§B1 table
`queue.K20.jumps_tuned`	72.6%	§B1 table

Key	Value	Where in this report
queue.K20.proposed	69.6%	§B1 table
queue.K20.jumps_hindsight	72.9%	§B1 table
queue.K50.proposed	85.8%	§B1 text
false.K20.delta_5m	2.1	§B1 table
false.K20.jumps_tuned	1.0	§B1 table
false.K20.proposed	1.8	§B1 table
ceiling.K20	84.9%	§B1
misses.K20.no_metric_data	166	§B1 misses
misses.K20.budget_full	198	§B1 misses
misses.K20.no_jump	4	§B1 misses
misses.K20.below_threshold	4	§B1 misses
walkforward.proposed.mean	71.3%	§B2
walkforward.proposed.ci_low	64.5%	§B2
walkforward.proposed.ci_high	76.7%	§B2
walkforward.proposed.wins	4	§B2
walkforward.jumps_tuned.mean	74.8%	§B2
walkforward.jumps_tuned.wins	8	§B2
walkforward.delta_5m.mean	70.7%	§B2
robustness.step_1g.jump_0.5g	100%	§B3
robustness.step_0.25g.jump_0.5g	1%	§B3
robustness.ramp_1g.jump+leak_3h	99%	§B3
robustness.step_0.5g.jump_0.5g+threshold	0%	§B3
ablation.K20.classifier	69.6%	§5, §B4
ablation.K20.severity	71.0%	§5, §B4
ablation.K20.no_alerts	71.2%	§5, §B4
ablation.false.K20.classifier	1.8	§5, §B4
ablation.false.K20.severity	1.4	§5, §B4
ablation.false.K20.no_alerts	1.2	§5, §B4
queue.K20.p3_ranker	69.7%	§B4
queue.K20.p3_grouped	70.7%	§B4
queue.K20.p3_per_series	69.3%	§B4
ablation.attached.K20.classifier	280	§B4
severity.K20.fault_alerts	507	§B4
severity.K20.fault_alerts_warning	471	§B4
severity.K20.fault_alerts_info	36	§B4
severity.K20.escalated	44	§B4
severity.K20.escalated_with_fault	0	§B4
severity.K20.escalated_days	4	§B4
severity.K20.cut_by_daily_budget	14	§B4
severity.K20.escalated_while_shown_jump_open	0	§B4
severity.K20.minutes_to_shown_metric_min	199	§B4

Key	Value	Where in this report
severity.K20.minutes_to_shown_metric_median	617	§B4
severity.K20.alerts_shown	11	§B4
gate.held_out.fault_alerts_found	339	§B4
gate.queue.faults	1223	§5, §B4
gate.queue.caught_with_model	848	§5, §B4
gate.queue.caught_no_log_alerts	872	§5, §B4
gate.queue.false_with_model	95	§B4
gate.queue.false_no_log_alerts	58	§B4
gate.queue.caught_fallback	871	§B4
gate.queue.false_fallback	70	§B4
gate.margin	10	§9, §B4
ablation.K20.shipped	71.0%	§B1 table
ablation.false.K20.shipped	1.4	§B1 table
queue.K50.p3_per_series	84.1%	§B4
false.K20.p3_per_series_jumps	0.8	§B4
queue.K20.p3_carryover	72.6%	§B4
queue.K20.delta_5m_carryover	72.5%	§B4
walkforward.carryover.mean	74.8%	§B4
walkforward.delta_carryover.mean	74.3%	§B4
nab.realAWSCloudwatch	71%	§B5
nab.realAdExchange	83%	§B5
nab.realKnownCause	38%	§B5
nab.realTraffic	36%	§B5
nab.realTweets	36%	§B5
smd.K5.incidents	30.6%	§B5
smd.K10.incidents	42.3%	§B5
smd.K20.incidents	55.1%	§B5
smd.K5.movements	10.1%	§B5
smd.K10.movements	19.3%	§B5
smd.K20.movements	33.9%	§B5
rcaeval.online-boutique.rise_gb	0.51	§B5
rcaeval.online-boutique.jump_spikes	744	§B5
rcaeval.online-boutique.jump_open	100%	§B5
rcaeval.online-boutique.jump_chance	28.5%	§B5
rcaeval.online-boutique.jump_train_false	679	§B5
rcaeval.online-boutique.K5	0%	§B5
rcaeval.sock-shop.rise_gb	0.30	§B5
rcaeval.sock-shop.jump_spikes	235	§B5
rcaeval.sock-shop.jump_open	92.3%	§B5
rcaeval.sock-shop.jump_chance	47.1%	§B5
rcaeval.sock-shop.jump_train_false	220	§B5

Key	Value	Where in this report
rcaeval.sock-shop.K5	0%	§B5
rcaeval.train-ticket.rise_gb	0.33	§B5
rcaeval.train-ticket.jump_spikes	1512	§B5
rcaeval.train-ticket.jump_open	61.5%	§B5
rcaeval.train-ticket.jump_chance	40.9%	§B5
rcaeval.train-ticket.jump_train_false	1323	§B5
rcaeval.train-ticket.K5	0%	§B5
stats.jump_rate_with_data	99.6%	§B6
stats.chance_overlap	2.6%	§B1
stats.confirm_minutes_median	0.72	§B1
stats.false_jumps_near_fault	24.6%	§B6
resources.wall_seconds	54.9	§7 resources
resources.peak_rss_mb	505	§7 resources
resources.peak_rss_mb_before_job	173	§7 resources
resources.db_mb	13.0	§7 resources
resources.db_kb_per_day	215	§7 resources
rcalogs.RE2.ob.classifier	46.7%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.classifier.ci_high	60.9%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.classifier.ci_low	32.9%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.diff.ci_high	6.7%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.diff.ci_low	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.false.classifier	0.47	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.false.none	0.42	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.false.severity	0.53	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.caught_fallback	18	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.caught_no_log_alerts	17	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.caught_with_model	18	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.false_items_fallback	26	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.false_items_no_log_alerts	21	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.false_items_with_model	23	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.faults	44	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.gate.saving	3	§9, §B5 RCAEval RE2/RE3
rcalogs.RE2.ob.none	44.4%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.placebo	0	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.severity	46.7%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ob.test_cases	45	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.classifier	86.7%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.classifier.ci_high	93.7%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.classifier.ci_low	73.8%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.diff.ci_high	6.7%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.diff.ci_low	0.0%	§B5 RCAEval RE2/RE3

Key	Value	Where in this report
rcalogs.RE2.ss.false.classifier	3.13	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.false.none	1.42	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.false.severity	3.38	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.none	84.4%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.placebo	2	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.severity	84.4%	§B5 RCAEval RE2/RE3
rcalogs.RE2.ss.test_cases	45	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.classifier	73.3%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.classifier.ci_high	84.0%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.classifier.ci_low	59.0%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.diff.ci_high	24.4%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.diff.ci_low	4.4%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.false.classifier	3.56	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.false.none	3.27	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.false.severity	3.87	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gain_vs_none	13.3%	§5, §12, §13, §B5
rcalogs.RE2.tt.gain_vs_severity	2.2%	§5, §12, §13
rcalogs.RE2.tt.gate.caught_fallback	32	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.caught_no_log_alerts	28	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.caught_with_model	32	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.false_items_fallback	222	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.false_items_no_log_alerts	198	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.false_items_with_model	212	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.faults	45	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.gate.saving	10	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.none	60.0%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.placebo	2	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.severity	71.1%	§B5 RCAEval RE2/RE3
rcalogs.RE2.tt.test_cases	45	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.classifier	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.classifier.ci_high	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.classifier.ci_low	79.6%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.diff.ci_high	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.diff.ci_low	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.false.classifier	0.53	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.false.none	0.53	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.false.severity	1.60	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.none	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.placebo	0	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.severity	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ob.test_cases	15	§B5 RCAEval RE2/RE3

Key	Value	Where in this report
rcalogs.RE3.ss.classifier	93.3%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.classifier.ci_high	98.8%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.classifier.ci_low	70.2%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.diff.ci_high	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.diff.ci_low	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.false.classifier	4.67	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.false.none	4.07	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.false.severity	5.40	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.none	93.3%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.placebo	1	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.severity	93.3%	§B5 RCAEval RE2/RE3
rcalogs.RE3.ss.test_cases	15	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.classifier	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.classifier.ci_high	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.classifier.ci_low	79.6%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.diff.ci_high	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.diff.ci_low	0.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.false.classifier	1.93	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.false.none	1.93	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.false.severity	3.67	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.none	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.placebo	0	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.severity	100.0%	§B5 RCAEval RE2/RE3
rcalogs.RE3.tt.test_cases	15	§B5 RCAEval RE2/RE3
rcalogs.early_jump_share	43%	§B5 RCAEval RE2/RE3
rcalogs.gate.margin	10	§9, §B5 RCAEval RE2/RE3

Appendix H. Interfaces

Taken from `app/product/web/` and `app/src/experiment.py`. When `APP_PASSWORD` is unset, routes other than `/health` accept only a private or loopback client. When it is set, those routes need a session or HTTP basic login. Ingest accepts `Authorization: Bearer` matching `INGEST_TOKEN` when that variable is set.

Table H1. Main HTTP endpoints

Method	Path	Auth	Input	Output
GET	/health	open	none	JSON status
POST	/login	none	password	session cookie
POST	/logout	session	none	cookie cleared
POST	/ingest/alertmanager	ingest token or private client	Alertmanager webhook	firing alerts buffered

Method	Path	Auth	Input	Output
POST	/ingest/alerts	ingest token or private client	`{alerts: [{timestamp,source,severity,message}]}`	same
POST	/jobs/run	session or private client	`{mode,budget_k,shadow_mode}`	queue result; pages only if Live rules hold
GET	/queue	session or private client	none	current queue
POST	/feedback	operator if a password is set	Real or Noise mark	label stored
GET	/metrics	session or private client	none	Prometheus text
GET	/monitoring	session or private client	none	monitoring JSON
POST	/evaluate	session or private client	alerts, metrics, faults CSV	evaluation report

Table H2. Library interfaces

Caller	Callee	Role
`product.pipeline`	`src.classifier.AlertClassifier`	fit and score log alerts
`product.pipeline`	`src.queue.build_queue`	causal queue for the product gate
`src.experiment.run_window`	`src.queue.build_queue`	each named queue, including `proposed` and `p3_ranker`
`src.experiment.run_window`	`src.classifier.AlertClassifier`	log alerts inside the window
`homelab.evaluate`	`src.experiment.run_window`	day-12 plain and learned-ranker scores
`homelab.evaluate`	`src.ranker.fit_ranker`	only when `--learned-ranker` is passed; does not set `LEARNED_RANKER`

Appendix I. Optional queue checks

The four checks live in `src/enhancements.py`. Each stays off unless its flag is `1`, `true`, `yes` or `on`. This run set the three flags in the scoring process only. `LEARNED_RANKER`, `METRIC_MODEL` and `LLM_EXPLAIN` stayed unset, and nothing was paged. The keep rule is the same paired bootstrap as Table 2: 4,000 draws, seed 42, KEEP only when the interval's lower bound is above 0. The home-lab input is the committed day-12 snapshot. The GAIA rows use the published alert window: 1,223 test faults, and at K = 20 proposed catches 851 and the learned ranker 887, the same baseline as Table 1. E1 is not scored because GAIA is one tenant. Flags stayed off in the product. The run is `docs/results/enhancements/gaia-20261104T194507Z/`.

When M equals K, a hybrid queue is the ranker it starts from, so those rows repeat a ranker-versus-proposed result. The new question is a smaller M filled out by proposed.

Table I1. Catch comparisons on the home lab. Counts are faults caught. The interval is the per-fault difference.

Check	Comparison	Caught	95% CI	Decision
E1 acme, N = 3, threshold retune, K = 10	vs unadapted ranker	44 vs 38 of 397	[0.0025, 0.0302]	KEEP
E1 acme, N = 3, threshold retune, K = 10	vs proposed	44 vs 47 of 397	[−0.0202, 0.0050]	DROP
E1, every company, N = 1, 2, 3, K = 20	vs unadapted and vs proposed	see the CSV	includes 0, or no calibration items for acme N = 1	DROP
E2 learned hybrid, pooled, M = 20, K = 20	vs proposed	63 vs 51 of 559	[0.0107, 0.0340]	KEEP
E2 jump hybrid, pooled, M = 20, K = 20	vs proposed	68 vs 51 of 559	[0.0161, 0.0465]	KEEP
E2 jump hybrid, pooled, M = 20, K = 50	vs proposed	82 vs 81 of 559	[0.0000, 0.0054]	DROP
E2 jump hybrid, pooled, M = 10, K = 50	vs p3 ranker	81 vs 75 of 559	[0.0018, 0.0215]	KEEP
E2 jump hybrid, pooled, M = 10, K = 50	vs proposed	81 vs 81 of 559	[0.0000, 0.0000]	DROP
E3 topology, pooled, K = 20	vs proposed	60 vs 51 of 559	[0.0072, 0.0268]	KEEP
E3 topology, pooled, K = 20	vs learned ranker	60 vs 63 of 559	[−0.0125, 0.0000]	DROP
E3 topology, leave-one-company-out, K = 20	vs unadapted	acme 32/220, borealis 25/159, cassini 21/180	[0.0000, 0.0000]	DROP

E1 uses only the held-out company's labels before origin plus N days, then scores faults that start after that boundary, so the fault count is not the day-7 test count. Acme's first day produced no calibration items, so N = 1 is not scored. The K = 10 KEEP does not hold at K = 20 (54 vs 57 unadapted, DROP). Borealis and cassini match the unadapted ranker at every N and K. The M = 20 jump hybrid at K = 20 is the published ranker (68 vs 51). Training data chose M = 10 for the learned hybrid at K = 50; that queue ties proposed at 81. Topology features are the public demo call graph (neighbour alerts in 15 minutes, an open jump on the same service, fan-out). They do not move leave-one-company-out.

Table I2. Minutes from fault start to the first catching item, pooled. The interval is the median difference versus proposed on faults both caught.

Queue	K	Caught	Median	p90	Median minus proposed	95% CI
proposed	20	51	0.78	2.92	0.00	[0.00, 0.00]
p3 ranker	20	68	0.78	2.82	0.00	[0.00, 0.00]
learned ranker	20	63	0.78	2.89	0.00	[0.00, 0.00]
topology	20	60	0.80	2.95	0.00	[0.00, 0.00]
jumps tuned	20	54	0.78	1.14	0.00	[0.00, 0.00]
static p99	20	15	−351.93	0.75	−40.73	[−81.47, 0.00]
severity	20	0	none	none	none	none
Alertmanager, first-come	20	28	3.53	4.08	2.57	[0.17, 2.92]

Queue	K	Caught	Median	p90	Median minus proposed	95% CI
Alertmanager, severity-first	20	21	3.58	4.13	2.60	[0.17, 3.10]
proposed	50	81	0.80	3.25	0.00	[0.00, 0.00]
jump hybrid, M = 20	50	82	0.80	3.24	0.00	[0.00, 0.00]

On faults both queues caught, the ranker and proposed have the same median delay. Alertmanager is slower by about two and a half minutes. The static p99 median is negative because the credited spike was shown before the fault start. Severity caught nothing, so it has no delay. Full rows are in `docs/results/enhancements/homelab-20261104T192524Z/`.

Table I3. GAIA catch comparisons, 1,223 faults. Counts and intervals are from `summary.csv`, rounded to four decimals. When M is capped by K, the M = 10, M = 20 and min(K, 20) rows are the same queue.

Check	Comparison	Caught	95% CI	Decision
E2 learned hybrid, M = 20 and min(K, 20), K = 20	vs proposed	893 vs 851	[0.0213, 0.0491]	KEEP
E2 learned hybrid, M = 20 and min(K, 20), K = 20	vs learned ranker	893 vs 887	[0.0016, 0.0090]	KEEP
E2 learned hybrid, M = 10, K = 20	vs proposed	848 vs 851	[−0.0057, 0.0000]	DROP
E2 learned hybrid, M = 10, K = 20	vs learned ranker	848 vs 887	[−0.0466, −0.0172]	DROP
E2 learned hybrid, K = 5	vs learned ranker	250 vs 242	[0.0025, 0.0114]	KEEP
E2 learned hybrid, K = 5	vs proposed	250 vs 239	[−0.0090, 0.0270]	DROP
E2 learned hybrid, K = 50	vs proposed and vs learned ranker	1049 vs 1049	[0.0000, 0.0000]	DROP
E2 jump hybrid, K = 5	vs proposed	238 vs 239	[−0.0025, 0.0000]	DROP
E2 jump hybrid, K = 5	vs p3 ranker	238 vs 238	[0.0000, 0.0000]	DROP
E2 jump hybrid, K = 10	vs proposed	476 vs 475	[0.0000, 0.0025]	DROP
E2 jump hybrid, K = 10	vs p3 ranker	476 vs 474	[0.0000, 0.0041]	DROP
E2 jump hybrid, M = 10, K = 20	vs proposed	848 vs 851	[−0.0057, 0.0000]	DROP
E2 jump hybrid, M = 10, K = 20	vs p3 ranker	848 vs 852	[−0.0090, 0.0016]	DROP
E2 jump hybrid, M = 20, K = 20	vs proposed	853 vs 851	[−0.0033, 0.0065]	DROP
E2 jump hybrid, M = 20, K = 20	vs p3 ranker	853 vs 852	[0.0000, 0.0025]	DROP
E2 jump hybrid, K = 50	vs proposed	1049 vs 1049	[0.0000, 0.0000]	DROP

Check	Comparison	Caught	95% CI	Decision
E2 jump hybrid, K = 50	vs p3 ranker	1049 vs 1047	[0.0000, 0.0041]	DROP
E3 topology, K = 20	vs proposed	886 vs 851	[0.0139, 0.0433]	KEEP
E3 topology, K = 20	vs learned ranker	886 vs 887	[−0.0065, 0.0049]	DROP
E3 topology, K = 50	vs proposed and vs learned ranker	1049 vs 1049	[0.0000, 0.0000]	DROP
E1 company calibration				not scored

At K = 50 the learned hybrid, the jump hybrid and topology each catch 1049, the same as proposed. The jump hybrid does not beat p3 (1,047): the interval includes 0. M = 10 at K = 20 is worse than both proposed and the learned ranker. The K = 5 KEEP is against the learned ranker only.