

## Homework 2

Instructor: Subodh Sharma

Due: March 24, 23:55 hrs

NOTE: All submissions must be made in the pdf format. Hand written assignments will not be accepted.

## Problem 1: Sequential Consistency, Linearizability

- For each of the histories shown in Figs 1a and 1b, are they Sequentially consistent? Linearizable? Justify your answer. (4 marks)




Figure 1: Traces

- Let *strict consistency* be defined in the following way: *Any read on a data item  $x$  returns a value corresponding to the result of the most recent write.* In class we had discussed the definitions of *sequential consistency* (SC) and *linearizability*. Assuming, we have a binary relation  $\mathcal{W}$  that is irreflexive, antisymmetric and transitive which captures *Weaker-than* relationship among consistency models. Thus, if  $(a, b) \in \mathcal{W}$  then model  $a$  is weaker than model  $b$ . Establish a  $\mathcal{W}$  relationship among SC, strict consistency and linearizability. Justify your answer. (4 marks)
- A way to realize logical clocks (for establishing happens-before relation or causality among events that are necessary for SC or linearizability) is by either *Lamport clocks* or *Vector clocks*. Explain a cardinal difference between Lamport clocks and Vector clocks [Reference: [Lamport clock video](#); [Vector clock video](#)]. Show at each event the associated vector clocks for a sequentially consistent execution history of example in Figure 1(a). (4 marks)

## Problem 2: OpenMP

Consider the loop:

```
a[0] = 0;
for (i = 1; i < n; i++)
    a[i] = a[i - 1] + i;
```

Is the loop parallelizable (with or without loop transformation)? If so, then write snippet of OpenMP code for the parallel version of this loop. (4 marks)

### Problem 3: OpenMP Debug

Consider the following program. Identify correctness issues in the program and specify the solutions (SHOW ONLY RELEVANT CHANGES): the **for** loop must be parallelized on 2 threads collectively calling `foo()` 10 times and then each thread prints “Hello World” in an *ordered* fashion. (6 marks)

```
#pragma omp parallel
{
    omp_set_num_threads(2);
    #pragma omp parallel for
    for (int i = 0; i < 10; i++)
    {
        foo();
    }
    printf(“hello world from %d \n ”, omp_get_thread_num());
}
```

### Problem 4: OpenMP Performance

Find all performance issues with the program listed below and provide an alternate implementation addressing all the issues: (4 marks)

```
#pragma omp parallel for
for ( i = 0 ; i < N ; ++i ) {
    #pragma omp critical
    {
        if ( arr[i] > max) max = arr[i] ;
    }
}
```