Synopsis

Project Title

Problem Id:

Design and develop a K-Means clustering–based analytical system to group agricultural regions based on crop yield characteristics and environmental factors. The project should use a structured dataset consisting of 20 region-level features, including: average rainfall (mm), average temperature (°C), soil moisture level (%), soil pH, nitrogen content, phosphorus content, potassium content, irrigation coverage (%), crop area (hectares), fertilizer usage (kg/hectare), pesticide usage (kg/hectare), sunlight hours, humidity (%), altitude (meters), wind speed (km/h), groundwater level (meters), crop diversity index, farming mechanization score, historical yield variance, and average crop yield (tons/hectare). The project should begin with Exploratory Data Analysis (EDA) to understand feature distributions, correlations across regions, followed by data preprocessing steps such as handling missing values and normalization to ensure all features are on comparable scales. Forward or backward feature elimination should then be applied to identify the most relevant features contributing to meaningful clustering. The processed data should be visualized in a suitable feature space before clustering. The program must determine the optimal number of clusters (K) using the Elbow Method, followed by application of the K-Means clustering algorithm to group agricultural regions. Post-clustering visualization should be performed to interpret the identified clusters. The effectiveness of clustering should be evaluated using the Silhouette Score. Additionally, the trained clustering model should be used to assign (predict) the cluster label for new or unseen regional data points, demonstrating practical applicability of the model.

Student Name 1 : Aman Pratap Rana

University Roll number 2028635

Section L

Student Name 2 : Akshank Chauhan

University Roll number 2028630

Section L

Student Name 3 : Dev Dhoundiyal

University Roll number : 2028411

Section : L

- **Problem Description:**

Agriculture is highly dependent on environmental and soil conditions, which vary significantly across regions. Identifying patterns among agricultural regions can help improve crop productivity, optimize resource allocation, and support better decision-making. However, manually analyzing multiple factors such as rainfall, soil nutrients, temperature, and yield is complex and inefficient.

This project proposes a data-driven approach using K-Means Clustering to group agricultural regions based on similarities in environmental and crop-related features. By analyzing parameters like rainfall, soil pH, fertilizer usage, and crop yield, the system will automatically identify clusters of regions with similar agricultural characteristics.

Such clustering can assist farmers, policymakers, and agricultural experts in understanding regional patterns, improving irrigation planning, selecting suitable crops, and enhancing

productivity. The system also allows prediction of cluster membership for new regions, making it useful for real-world agricultural planning and sustainable farming strategies.

- **Steps of Implementation:**



Fig. 1 Sample architecture

1. **Data Collection**
   Gather dataset with 20 agricultural features.
2. **Exploratory Data Analysis (EDA)**
   Analyze distributions, detect patterns, and visualize correlations.
3. **Data Preprocessing**
   - Handle missing values
   - Normalize data using scaling techniques
4. **Feature Selection**
   Apply forward/backward elimination or variance threshold.
5. **Optimal K Selection**
   Use Elbow Method to determine number of clusters.
6. **Model Building**
   Apply K-Means clustering algorithm.
7. **Evaluation**
   Use Silhouette Score to measure clustering quality.
8. **Visualization**
   Plot clusters for interpretation.

9. **Prediction Module**
   Predict cluster for new/unseen data.

- **Expected Modules/ Libraries to be used :**
- • **NumPy** – For numerical computations and array operations
- • **Pandas** – For dataset handling and data manipulation
- • **Matplotlib** – For basic data visualization
- • **Seaborn** – For advanced statistical visualization
- • **Scikit-learn (sklearn)** – For implementing K-Means, scaling, and evaluation
- • **StandardScaler** – To normalize features
- • **KMeans** – Core clustering algorithm
- • **Silhouette Score** – To evaluate clustering quality

- **Expected Evaluation metrics and Plots to be used:**

- **Silhouette Score**
  Measures how well data points fit within their cluster. Higher value means better clustering.
- **Elbow Method Plot**
  Helps determine optimal number of clusters (K).
- **Scatter Plots**
  Used to visualize clusters in 2D feature space.
- **Heatmap (Correlation Matrix)**
  Shows relationships between features.

These metrics and plots ensure both **quantitative and visual validation** of clustering performance.

- **Required topics from the subject:**

- **Strings**
  Used for handling dataset column names and labels.
- **Pointers**
  Helps in understanding memory handling (especially if implemented in C-based logic concepts).
- **Files**
  Used to read/write datasets (CSV files) and store results.
- **Arrays**
  Used to store and manipulate numerical data efficiently.
- **Functions**
  Modular approach for implementing different ML steps.

- **Platform Required:**
- **Jupyter Notebook**

- **Books and Link Sources:**

- **"Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow"** – Aurélien Géron
- **"Pattern Recognition and Machine Learning"** – Christopher M. Bishop
- **"Machine Learning: A Probabilistic Perspective"** – Kevin P. Murphy
- **"Data Mining: Concepts and Techniques"** – Jiawei Han, Micheline Kamber
- Scikit-learn Documentation
  https://scikit-learn.org/stable/
- Kaggle (Datasets & ML Practice)
  https://www.kaggle.com/
- UCI Machine Learning Repository
  https://archive.ics.uci.edu/ml/index.php
- Towards Data Science (Articles & Tutorials)
  https://towardsdatascience.com/