

```
require('dotenv').config();
const express = require('express');
const nodemailer = require('nodemailer');
const path = require('path');

const app = express();
const PORT = process.env.PORT || 3000;

app.use(express.json());
app.use(express.static(path.join(__dirname,
'public')));

// Gmail transporter – uses an App
// Password, not your normal Gmail password.
// See README.md for how to generate one.
const transporter =
nodemailer.createTransport({
  service: 'gmail',
  auth: {
    user: process.env.GMAIL_USER,
    pass: process.env.GMAIL_APP_PASSWORD,
  },
});

app.post('/api/order', async (req, res) =>
{
  const { customer, items, total } =
req.body;

  if (!customer || !customer.email ||
```

```

!items || items.length === 0) {
  return res.status(400).json({ error:
'Missing order details.' });
}

const itemsHtml = items
  .map(
    (i) =>
      `<tr>
        <td style="padding:6px
10px;border-bottom:1px solid
#eee;">${i.name}</td>
        <td style="padding:6px
10px;border-bottom:1px solid
#eee;">${i.qty}</td>
        <td style="padding:6px
10px;border-bottom:1px solid
#eee;">${(i.price * i.qty).toFixed(2)}
</td>
      </tr>`
  )
  .join('');

const orderHtml = `
  <h2>New order received</h2>
  <p><b>Customer:</b> ${customer.name}
(${customer.email})</p>
  <p><b>Phone:</b> ${customer.phone ||
'N/A'}</p>
  <p><b>Shipping address:</b>
${customer.address || 'N/A'}</p>
  <table style="border-
collapse:collapse;width:100%;max-
width:480px;">

```

```

        <tr style="background:#f4f4f4;">
            <th style="padding:6px 10px;text-align:left;">Item</th>
            <th style="padding:6px 10px;text-align:left;">Qty</th>
            <th style="padding:6px 10px;text-align:left;">Subtotal</th>
        </tr>
        ${itemsHtml}
    </table>
    <p style="margin-top:12px;"><b>Total:
    ${total.toFixed(2)}</b></p>
    `;

```

```

    try {
        // 1. Notify the store owner (you)
        await transporter.sendMail({
            from: `Ahlaat.Pk Orders`
            <${process.env.GMAIL_USER}>`,
            to: process.env.GMAIL_USER,
            subject: `New order from
            ${customer.name} – ${total.toFixed(2)}`,
            html: orderHtml,
        });

        // 2. Send a confirmation to the
        customer (optional but recommended)
        await transporter.sendMail({
            from: `Ahlaat.Pk`
            <${process.env.GMAIL_USER}>`,
            to: customer.email,
            subject: 'Your order confirmation',
            html: `<p>Thanks for your order,
            ${customer.name}!</p>${orderHtml}`,

```

```
});

    res.json({ success: true });
  } catch (err) {
    console.error('Email send failed:',
err);
    res.status(500).json({ error: 'Could
not send order email.' });
  }
});

app.listen(PORT, () => {
  console.log(`Store running at
http://localhost:${PORT}`);
});
```