

Daily Drilling Report: SHIFT-06 (2026-09-22 NIGHT (18:00 - 06:00)) (illustrative)

Document ID: DDR-MN-SM-DW-01-SHIFT-06 | Type: DDR | Well: MN-SM-DW-01 | Date: 2026-09-22

1. General Well & Shift Data

- **Well Identifier**: MN-SM-DW-01 (Mahanadi Offshore Deepwater)
- **Operator**: ONGC Deepwater Operations (Project Samudra Manthan)
- **Date**: 2026-09-22
- **Tour**: NIGHT (18:00 - 06:00)
- **Depth Interval**: 4195.0 m to 4235.0 m MD
- **Progress**: 40.0 m (Average ROP: 12.0 m/hr)
- **Current Hole Section**: 12-1/4 in open hole (13-3/8 in casing shoe at 3,850 m MD, FIT 12.10 ppg)

2. Drilling Fluid & Hydraulic Summary

- **Active Mud Weight In**: 11.65 ppg (1.40 SG)
- **Active Mud Weight Out**: 11.65 ppg (1.40 SG)
- **Annular Equivalent Circulating Density (ECD)**: 11.86 ppg
- **Margin to Casing Shoe FIT (12.10 ppg)**: +0.24 ppg
- **Active System Volume**: 3,100 bbl SOBM

3. 12-Hour Operational Chronology

- **06:00 - 18:00 / 18:00 - 06:00**: Tagged U3 main turbidite gas sand at 4,195 m. Encountered drilling break at 4,205 m (instantaneous ROP 34 m/hr). Immediately capped ROP at 12 m/hr as per SOP-04 recommendation to prevent annular overloading. ECD controlled at 11.86 ppg (safe by 0.24 ppg below 12.10 shoe FIT).
- **LWD Telemetry**: Continuous decoding of GR, RDEP, DT, RHOB, NPHI.

4. Handover Notes & Safety Observation

- **Handover Summary**: Preempted offset MN-DW-03 loss precedent (28 bbl/hr). Mud losses 0 bbl. Excellent sand quality: 24.2% porosity, dry gas C1 > 88%.
- **Well Control Status**: Normal / No unmanaged influx.
- **Tour Supervisor**: K. Das (Tour B) (Role: Tour Driller)
- **Approval Sign-off**: Drilling Superintendent & Company Man