

# CS270: Digital Image Processing

Dr. Xavier LAGORCE

Email: [xavier@shanghaitech.edu.cn](mailto:xavier@shanghaitech.edu.cn)

Office: SIST 1D-301B

ShanghaiTech University



上海科技大学  
ShanghaiTech University

# Lecture 4


## Intensity transformation & Spatial Filtering II

Dr. Xavier LAGORCE

Email: [xavier@shanghaitech.edu.cn](mailto:xavier@shanghaitech.edu.cn)

Office: 1D-301.B, SIST

ShanghaiTech University



立志成才 报国裕民

## Intensity transforms (2)



上海科技大学  
ShanghaiTech University

- ☐ Adaptive Histogram Equalization (AHE)
- ☐ Contrast Limited Adaptive Histogram Equalization (CLAHE)






立志成才 报 国 裕 民

# Key problem of Histogram Equalization (HE)



上海科技大学  
ShanghaiTech University

$$s = T(r) = (L - 1) \int_0^r p_r(w) dw = (L - 1) \sum_{j=0}^k p_r(r_j) = (L - 1) \sum_{j=0}^k \frac{n_j}{MN} = \frac{L - 1}{MN} \sum_{j=0}^k n_j$$





立志成才 报國裕民

# Key problem of Histogram Equalization (HE)



上海科技大学  
ShanghaiTech University




立志成才 报國裕民

# Adaptive Histogram Equalization (AHE)



上海科技大学  
ShanghaiTech University

- ❑ Traverse every pixel with a  $W * W$  patch, process histogram equalization within each patch and update the center pixel.
- ❑ Advantage: better uniform distributed histogram.
- ❑ Disadvantage: high complexity
- ❑  $O(W * W + L)$  within each patch
- ❑  $O(M * N * (W * W + L))$  for whole image




立志成才 报國裕民

# Adaptive Histogram Equalization (AHE)



上海科技大学  
ShanghaiTech University

- ❑ For faster processing AHE, it is proposed to update a center patch of size  $M * M$  instead of just the center pixel in each HE within the  $W * W$  patch HE.
- ❑ Pixels near the image boundary have to be treated specially, This can be solved by extending the image by mirroring pixel lines and columns with respect to the image boundary.






立志成才 报国强民



# Effect of AHE



上海科技大学  
ShanghaiTech University



- ☐ AHE has a tendency to overamplify noise in homogeneous areas
- ☐ Better at improving local contrast and edge information

立志成才 报国强民



# Contrast Limited Adaptive Histogram Equalization (CLAHE)



上海科技大学  
ShanghaiTech University

- ❑ CLAHE differs from naive AHE because it limits local contrast.
- ❑ CLAHE was developed to prevent the over amplification of noise that AHE can give rise to.
- ❑ This feature can also be applied to global histogram equalization, giving rise to contrast limited histogram equalization.




立志成才 报国强民

# Contrast Limited Adaptive Histogram Equalization (CLAHE)



上海科技大学  
ShanghaiTech University

- ❑ CLAHE limits the amplification by clipping the histogram at a predefined value before computing the CDF.
- ❑ This limits the slope of the CDF and therefore of the transformation function.
- ❑ The so-called clip limit depends on the normalization of the histogram and thereby on the size of the neighborhood region.







立志成才 报國裕民

# CLAHE



上海科技大学  
ShanghaiTech University




立志成才 报国裕民

## Take home message



上海科技大学  
ShanghaiTech University

- ❑ Key idea: AHE&CLAHE were developed to prevent the over amplification of noise.
  - AHE: Fragments the bins to spread them
  - CLAHE: cuts-off the head of the histogram and distributes it




立志成才 报國裕民

## Spatial filtering (2)



上海科技大学  
ShanghaiTech University

- ❑ Some other perspectives on spatial filtering
- ❑ Sobel Filter
- ❑ Unsharp Masking (非锐化掩蔽)
- ❑ LoG Filter (Laplacian of Gaussian)
  - useful for finding edges
  - also useful for finding blobs




立志成才 报国裕民


# Filtering in frequency domain and spatial domain



上海科技大学  
ShanghaiTech University



Ideal 1D Low-Pass filter



Ideal 1D Low-Pass filter kernel in spatial domain

**Q: Is ideal filter really ideal for image processing?**



立志成才 报国裕民




# Filtering in frequency domain and spatial domain




上海科技大学  
ShanghaiTech University

□ 4 types of filters



Filter type	Spatial kernel in terms of lowpass kernel, $lp$
Lowpass	$lp(x, y)$
Highpass	$hp(x, y) = \delta(x, y) - lp(x, y)$
Bandreject	$br(x, y) = lp_1(x, y) + hp_2(x, y)$ $= lp_1(x, y) + [\delta(x, y) - lp_2(x, y)]$
Bandpass	$bp(x, y) = \delta(x, y) - br(x, y)$ $= \delta(x, y) - [lp_1(x, y) + [\delta(x, y) - lp_2(x, y)]]$



立志成才 报国裕民



# Unsharp Mask (非锐化掩蔽)



上海科技大学  
ShanghaiTech University

$$g_{\text{mask}}(x, y) = f(x, y) - \bar{f}(x, y)$$

$$g(x, y) = f(x, y) + k * g_{\text{mask}}(x, y)$$



立志成才 报国裕民

# Separable filter kernels



上海科技大学  
ShanghaiTech University


□ Example: 
$$\begin{bmatrix} 3 & 6 & 9 \\ 4 & 8 & 12 \\ 5 & 10 & 15 \end{bmatrix} = \begin{bmatrix} 3 \\ 4 \\ 5 \end{bmatrix} \times [1 \ 2 \ 3]$$

□  $\mathbf{w} = \mathbf{a}\mathbf{b}^T$ : outer product of 2 vectors      equivalent to convolution !

□ If  $\mathbf{w} = \mathbf{w}_1 \star \mathbf{w}_2$ , then

➤  $\mathbf{w} \star \mathbf{f} = (\mathbf{w}_1 \star \mathbf{w}_2) \star \mathbf{f} = (\mathbf{w}_2 \star \mathbf{w}_1) \star \mathbf{f} = \mathbf{w}_2 \star (\mathbf{w}_1 \star \mathbf{f}) = (\mathbf{w}_1 \star \mathbf{f}) \star \mathbf{w}_2$


Simple Convolution



Computational advantage:

$$C = \frac{MNmn}{MN(m+n)} = \frac{mn}{(m+n)}$$

Spatial Separable Convolution




立志成才 报国强民

## Recall: First & Second-Derivative filters



上海科技大学  
ShanghaiTech University

- ❑ Sharp changes in gray level of the input image corresponds to “peaks or valleys” of the first-derivative of the input signal.
- ❑ Peaks or valleys of the first derivative of the input signal, correspond to “zero-crossings” of the second-derivative of the input signal.



立志成才 报国强民


□ For an image function  $f(x, y)$ :

➤ X direction :  $\frac{\partial^2 f}{\partial x^2} = f(x+1, y) + f(x-1, y) - 2f(x, y)$

➤ Y direction :  $\frac{\partial^2 f}{\partial y^2} = f(x, y+1) + f(x, y-1) - 2f(x, y)$

$$\nabla^2 f(x, y) = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2} \quad \text{Discrete Laplacian}$$

$$= f(x, y+1) + f(x, y-1) + f(x+1, y) + f(x-1, y) - 4f(x, y)$$



# Laplacian Filter Masks




上海科技大学  
ShanghaiTech University

□ Laplacian as a filter kernel

$$\nabla^2 f(x, y) = f(x, y + 1) + f(x, y - 1) + f(x + 1, y) + f(x - 1, y) - 4f(x, y)$$

0	1	0	1	1	1	0	-1	0	-1	-1	-1
1	-4	1	1	-8	1	-1	4	-1	-1	8	-1
0	1	0	1	1	1	0	-1	0	-1	-1	-1


$$\begin{aligned}\nabla^2 f(x, y) = & f(x, y + 1) + f(x, y - 1) + f(x + 1, y) + f(x - 1, y) \\ & + f(x + 1, y + 1) + f(x + 1, y - 1) + f(x - 1, y - 1) + f(x - 1, y + 1) \\ & - 8f(x, y)\end{aligned}$$

立志成才 报国强民



# Laplacian (拉普拉斯算子)




上海科技大学  
ShanghaiTech University

□ For an image function  $f(x, y)$ ,

➤ X direction:  $\frac{\partial^2 f}{\partial x^2} = f(x+1, y) + f(x-1, y) - 2f(x, y)$

➤ Y direction:  $\frac{\partial^2 f}{\partial y^2} = f(x, y+1) + f(x, y-1) - 2f(x, y)$

$$\begin{array}{|c|c|c|} \hline & I_{yy} & \\ \hline 1 & -2 & 1 \\ \hline \end{array} \quad \begin{array}{|c|} \hline 1 \\ \hline -2 \\ \hline 1 \\ \hline \end{array} I_{xx}$$





$\begin{bmatrix} 1 & -2 & 1 \end{bmatrix}$

2nd Partial deriv wrt y

$\begin{bmatrix} 1 \\ -2 \\ 1 \end{bmatrix}$

2nd Partial deriv wrt x







1. Impact of edge direction
2. Impact of edge contrast

立志成才 报国强民

# Laplacian



上海科技大学  
ShanghaiTech University



立志成才 报国裕民

# Gradient (梯度)



上海科技大学

ShanghaiTech University

The first-order derivative of  $f(x, y)$ :  $\nabla f \equiv \mathbf{grad}(f) \equiv \begin{Bmatrix} g_x \\ g_y \end{Bmatrix} = \begin{Bmatrix} \frac{\partial f}{\partial x} \\ \frac{\partial f}{\partial y} \end{Bmatrix}$


points in the direction of  
the greatest rate of change of  $f$  at  
location  $(x, y)$

The amplitude :  $M(x, y) = \mathbf{mag}(\nabla f) = \sqrt{g_x^2 + g_y^2}$

$$M(x, y) \approx |g_x| + |g_y|$$

To help computation complexity !

But keeps the main properties of the amplitude



立志成才 报國裕民

# Gradient (梯度)



上海科技大学  
ShanghaiTech University

## □ Simplest possibility

➤  $g_x = (z_8 - z_5)$  and  $g_y = (z_6 - z_5)$

## □ Roberts cross-gradient operator (罗伯特交叉梯度算子)

➤ Uses cross differences

➤  $M(x, y) \approx |g_x| + |g_y|$

➤  $= |z_9 - z_5| + |z_8 - z_6|$

-1	0	0	-1
0	1	1	0

$z_1$	$z_2$	$z_3$
$z_4$	$z_5$	$z_6$
$z_7$	$z_8$	$z_9$

□ But the kernel does not have an odd size, we prefer at least a 3x3 kernel...



立志成才 报国裕民

# Gradient (梯度)



上海科技大学  
ShanghaiTech University

❑ Sobel operator (Sobel算子)

$$\text{❑ } M(x, y) = \underbrace{|(z_7 + 2z_8 + z_9) - (z_1 + 2z_2 + z_3)|}_{g_x} + \underbrace{|(z_3 + 2z_6 + z_9) - (z_1 + 2z_4 + z_7)|}_{g_y}$$

$z_1$	$z_2$	$z_3$
$z_4$	$z_5$	$z_6$
$z_7$	$z_8$	$z_9$

-1	-2	-1
0	0	0
1	2	1

$g_x$

-1	0	1
-2	0	2
-1	0	1

$g_y$

Averaging

Partial  
derivative

Q: How to really understand Sobel operator? What are the functions?

立志成才 报国强民



# Sobel operator



上海科技大学  
ShanghaiTech University



$g_x$

-1	-2	-1
0	0	0
1	2	1


Horizontal edges



$g_y$

-1	0	1
-2	0	2
-1	0	1

Vertical edges



立志成才 报国强民



# Sobel operator



上海科技大学  
ShanghaiTech University





立志成才报国裕民

# Notes about the Laplacian



上海科技大学  
ShanghaiTech University

□  $\nabla^2 I(x, y)$  is a SCALAR

-  Can be found using a SINGLE mask
-  Orientation information is lost

□  $\nabla^2 I(x, y)$  is the sum of SECOND-order derivatives

- But taking derivatives increases noise.
- Very noise sensitive!

□ It is always combined with a smoothing operation.



立志成才 报國裕民

# Laplacian of Gaussian (LoG) Filter



上海科技大学  
ShanghaiTech University


- First smooth (Gaussian filter),
- Then, find zero-crossings (Laplacian filter):

$$\nabla^2 (G(x, y))$$


$$G(x, y) = e^{-\frac{x^2+y^2}{2\sigma^2}}$$

$$G'(x, y) = -\frac{1}{2\sigma^2} 2(x + y) e^{-\frac{x^2+y^2}{2\sigma^2}} = -\frac{x + y}{\sigma^2} e^{-\frac{x^2+y^2}{2\sigma^2}}$$


$$G''(x, y) = -\frac{1}{\pi\sigma^4} \left(1 - \frac{x^2+y^2}{2\sigma^2}\right) e^{-\frac{x^2+y^2}{2\sigma^2}}$$



$G(x, y)$



$G'(x, y)$





$G''(x, y)$

# Second derivative of a Gaussian




上海科技大学  
ShanghaiTech University


$$G''(x, y) = -\frac{1}{\pi\sigma^4} \left(1 - \frac{x^2+y^2}{2\sigma^2}\right) e^{-\frac{x^2+y^2}{2\sigma^2}}$$



2D  
analog  
➡



LoG "Mexican Hat"



立志成才 报国裕民

# Effect of LoG Filter



上海科技大学  
ShanghaiTech University

$\Sigma = 1$



$\Sigma = 4$



$\Sigma = 10$



Band-Pass Filter (suppresses both high and low frequencies)




立志成才 报 国 裕 民



# Application of LoG Filter



上海科技大学  
ShanghaiTech University



Gesture recognition for  
the ultimate couch potato

立志成才 报国裕民



# Matlab practice: spatial filtering



上海科技大学  
ShanghaiTech University

- ☐ `w = fspecial('type', parameters)`
- ☐ `g = imfilter(f, w, 'replicate')`
- ☐ See some examples.
- ☐ Then practice by yourself...



立志成才 报国裕民


## Take home message




上海科技大学  
ShanghaiTech University

- Key idea: Cross correlation with a filter can be viewed as comparing a little “picture” of what you want to find against all local regions in the image.

LoG



Derivative of Gaussian



立志成才 报國裕民


# Take home message




上海科技大学  
ShanghaiTech University



\*



=



立志成才 报國裕民