

CS150A Database

Wenjie Wang

School of Information Science and Technology

ShanghaiTech University

Oct. 18, 2024

Today:

- Relational Algebra:
 - Basic Operators
 - Compound Operators

Readings:

- Database Management Systems (DBMS), Chapters 4.1-4.2

Review

- Buffer Manager provides a level of indirection
 - Connects RAM and Disk
 - Maps disk page Ids to RAM addresses

Files and Index Management

RAM


Buffer Management

Disk

Disk Space Management

Review

- Buffer Manager provides a level of indirection
 - Connects RAM and Disk
 - Maps disk page Ids to RAM addresses
- Ensures that each requested page is “pinned” in RAM
 - To be (briefly) manipulated in-memory
 - And then unpinned by the caller!
- Attempts to minimize “cache misses”
 - By replacing pages unlikely to be referenced
 - By prefetching pages likely to be referenced




Review

- Pin Counts and Dirty Bits:
 - When do they get set/unset?
 - By what layer of the system?
- LRU, MRU and Clock
 - Be able to run each by hand
 - For Clock:
 - What pages are eligible for replacement
 - When is reference bit set/unset
 - What is the point of the reference bit?
- Sequential flooding
 - And how it behaves for LRU (Clock), MRU


FrameId	PageId	Dirty?	Pin Count
1	1	N	0
2	2	Y	1
3	3	N	0
4	6	N	2
5	4	N	0
6	5	N	0

Review

- Pin Counts and Dirty Bits:
 - When do they get set/unset?
 - By what layer of the system?
- LRU, MRU and Clock
 - Be able to run each by hand
 - For Clock:
 - What pages are eligible for replacement
 - When is reference bit set/unset
 - What is the point of the reference bit?
- Sequential flooding
 - And how it behaves for LRU (Clock), MRU



Architecture of a DBMS: What we've learned



- Finished all the storage issues
- Getting to the parts of query processing

Today:

- *definitions* of the relational operators that we will execute to evaluate queries.
- *implementations* of these operators

An Overview of the Layer Above

SQL Query

```
SELECT S.name  
FROM Reserves R, Sailors S  
WHERE R.sid = S.sid  
AND R.bid = 100  
AND S.rating > 5
```

Query Parser
& Optimizer

Relational Algebra

$\pi_{S.name}(\sigma_{bid=100 \wedge rating > 5}(\text{Reserves} \bowtie_{R.sid=S.sid} \text{Sailors}))$

The parser translate the query into a form that the optimizer is going to manipulate

The operator is going to work with operations that look like these, and these are in a language called the relational algebra

An Overview of the Layer Above

SQL Query

```
SELECT S.name
FROM Reserves R, Sailors S
WHERE R.sid = S.sid
AND R.bid = 100
AND S.rating > 5
```

Query Parser
& Optimizer

Relational Algebra

$$\pi_{S.name}(\sigma_{R.bid=100 \wedge S.rating > 5}(\text{Reserves} \bowtie_{R.sid=S.sid} \text{Sailors}))$$


Equivalent to...

The relational algebra expression can be represented as a tree of operators

A logical query plan is a strategy for executing the query expressed in terms of these operators

These operators are a logical representation of what we want to do and in what order

(Logical) Query Plan:



An Overview of the Layer Above

SQL Query

```
SELECT S.name
FROM Reserves R, Sailors S
WHERE R.sid = S.sid
AND R.bid = 100
AND S.rating > 5
```

Query Parser
& Optimizer

Relational Algebra

$$\pi_{S.name}(\sigma_{bid=100 \wedge rating > 5}(\text{Reserves} \bowtie_{R.sid=S.sid} \text{Sailors}))$$

Equivalent to...

Optimized (Physical) Query Plan:

On-the-fly
Project Iterator


On-the-fly
Select Iterator

Indexed Nested
Loop Join Iterator

Heap Scan
Iterator

But actually will
produce...

Operator Code
B+-Tree
Indexed Scan
Iterator



The optimizer itself is actually going to produce a physical optimized query plan.

Every operator in this tree is going to generate an actual algorithm to pump data up through these edges.

SQL vs Relational Algebra

SQL Query

```
SELECT S.name
FROM Reserves R, Sailors S
WHERE R.sid = S.sid
AND R.bid = 100
AND S.rating > 5
```

Query Parser
& Optimizer


Relational Algebra

$$\pi_{S.name}(\sigma_{bid=100 \wedge rating > 5}(\text{Reserves} \bowtie_{R.sid=S.sid} \text{Sailors}))$$

Equivalent to...

SQL

A **declarative** expression
of the query result



Relational Algebra

Operational description of
a computation.

But actually will
produce...

Operator Code

B+-Tree
Indexed
Iterator

Systems execute relational algebra
query plan.

SQL (Structured Query Language)

```
SELECT S.name
FROM Reserves R, Sailors S
WHERE R.sid = S.sid
AND R.bid = 100
AND S.rating > 5
```

- Key **System** Features: *Why do we like SQL*
 - Declarative:
 - Say **what** you want, not **how** to get it
 - Enables system to optimize the **how**
- Foundation in formal Query Languages
 - **Relational Calculus**

History: Formal Relational QL's

- **Relational Calculus:** (Basis for SQL)

- Describe the result of computation
- Based on first order logic: logic in which the predicate of a sentence or statement can only refer to a single subject
- Tuple Relational Calculus (**TRC**)
 - $\{S \mid S \in \text{Sailors} \exists R \in \text{Reserves} (R.\text{sid} = S.\text{sid} \wedge R.\text{bid} = 103)\}$

Are these equivalent?

Can we go from one to the other?




- **Relational Algebra:**

- Algebra on sets
- It comes from a different branch of mathematics
- It is an algebra, not a logic.
- Operational description of transformations

Codd's Theorem

- Established equivalence in expressivity between :
 - Relational Calculus
 - Relational Algebra
- Why an important result?
 - Connects declarative representation of queries with operational description
 - Constructive: we can compile SQL into relational algebra



Edgar F. "Ted" Codd
(1923 - 2003)
Turing Award 1981

Relational Algebra Preliminaries

- Algebra of operators on relation instances
- Can cascade these operators in nested expressions like the ones here

$$\pi_{S.name}(\sigma_{R.bid=100 \wedge S.rating>5}(R \bowtie_{R.sid=S.sid} S))$$

- Closed: result is also a relation instance
 - Enables rich composition!
- Typed: input schema determines output
 - Can statically check whether queries are legal.

Relational Algebra and Sets

- Pure relational algebra has set semantics
 - No duplicate tuples in a relation instance
 - vs. SQL, which has multiset (bag) semantics

Relational Algebra Operators: Unary

- Unary Operators: on **single relation**
- **Projection** (π): Retains only desired columns (vertical)
- **Selection** (σ): Selects a subset of rows (horizontal)
- **Renaming** (ρ): Rename attributes and relations.

Relational Algebra Operators: Binary

- Binary Operators: on **pairs of relations**
- **Union** (\cup): Tuples in r_1 or in r_2 .
- **Set-difference** ($-$): Tuples in r_1 , but not in r_2 .
- **Cross-product** (\times): Allows us to combine two relations.

Relational Algebra Operators: Compound

- Compound Operators: common “*macros*” for the above
- **Intersection** (\cap): Tuples in r_1 and in r_2 .
- **Joins** (\bowtie_{θ} , \bowtie): Combine relations that satisfy predicates

Projection (π)

- Corresponds to the SELECT list in SQL
- Schema determined by schema of attribute list
 - Names and types correspond to input attributes
- *Selects a subset of columns (vertical)*

$$\pi_{\text{sname, age}}(S2)$$

Relational Instance S2

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

List of Attributes



sname	age
yuppy	35.0
lubber	55.5
guppy	35.0
rusty	35.0

Projection (π), cont.

- Set semantics \rightarrow results in fewer rows
 - Real systems don't automatically remove duplicates
 - Why? (Semantics and Performance reasons)
 - *Selects a subset of columns (vertical)*

$$\pi_{\text{age}}(S2)$$

Relational Instance S2

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

Multiset

age
35.0
55.5
35.0
35.0

Set

age
35.0
55.5

Selection(σ)


- Corresponds to the WHERE clause in SQL
- Output schema same as input
- Duplicate Elimination? Not needed.
- *Selects a subset of rows (horizontal)*

$$\sigma_{\text{rating} > 8}(\text{S2})$$

Relational Instance S2

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0


Selection Condition (Boolean Expression)



<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
58	rusty	10	35.0

Composing Select and Project

- Names of sailors with rating > 8: $\pi_{\text{sname}}(\sigma_{\text{rating}>8}(S2))$




- What about: $\sigma_{\text{rating}>8}(\pi_{\text{sname}}(S2))$
 - Invalid types. Input to $\sigma_{\text{rating}>8}$ does not contain rating.*

Union (\cup)

- Two input relations, must be *compatible*:
 - Same number of fields
 - Fields in corresponding positions have same **type**
- SQL Expression: UNION

$S1 \cup S2$



Union (U) VS Union ALL

- Duplicate elimination in practice?
 - SQL's UNION vs UNION ALL

Relational Instance **S1**

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

Relational Instance **S2**


<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

S1 U S2

<u>sid</u>	sname	rating	age
22	dustin	7	45
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

Set Difference ($-$)

- Same as with union, both input relations must be *compatible*.
- SQL Expression: EXCEPT



Set Difference (–), cont.

- Duplicate elimination?
 - Not required
- EXCEPT vs EXCEPT ALL

Relational Instance **S1**

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

Relational Instance **S2**

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

S1 – S2

<u>sid</u>	sname	rating	age
22	dustin	7	45

S2 – S1

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
44	guppy	5	35.0

Cross-Product (\times)

- **$R1 \times S1$** : *Each row of $R1$ paired with each row of $S1$*

R1:

<u>sid</u>	<u>bid</u>	<u>day</u>
22	101	10/10/96
58	103	11/12/96

\times

S1:

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

$=$

sid	bid	day	sid	sname	rating	age
22	101	10/10/96	22	dustin	7	45.0
22	101	10/10/96	31	lubber	8	55.5
22	101	10/10/96	58	rusty	10	35.0
58	103	11/12/96	22	dustin	7	45.0
58	103	11/12/96	31	lubber	8	55.5
58	103	11/12/96	58	rusty	10	35.0

- **How many rows in result?** $|R1| \times |R2|$
- **Schema compatability?** Not needed.
- **Duplicates?** None generated.

Renaming (ρ)

- *Renames relations and their attributes:*
- Note that relational algebra doesn't require names.
 - We could just use positional arguments.

$$\rho(\underbrace{\text{Temp1}}_{\substack{\text{Output Relation} \\ \text{Name}}}, \underbrace{(1 \rightarrow \text{sid1}, 4 \rightarrow \text{sid2})}_{\substack{\text{Renaming List} \\ \text{position} \rightarrow \text{New Name}}}, \underbrace{\text{R1} \times \text{S1}}_{\substack{\text{Input} \\ \text{Relation}}})$$

R1 × S1

sid	bid	day	sid	sname	rating	age
22	101	10/10/96	22	dustin	7	45.0
22	101	10/10/96	31	lubber	8	55.5
22	101	10/10/96	58	rusty	10	35.0
58	103	11/12/96	22	dustin	7	45.0
58	103	11/12/96	31	lubber	8	55.5
58	103	11/12/96	58	rusty	10	35.0




Temp1

sid1	bid	day	sid2	sname	rating	age
22	101	10/10/96	22	dustin	7	45.0
22	101	10/10/96	31	lubber	8	55.5
22	101	10/10/96	58	rusty	10	35.0
58	103	11/12/96	22	dustin	7	45.0
58	103	11/12/96	31	lubber	8	55.5
58	103	11/12/96	58	rusty	10	35.0

Compound Operator: Intersection

- Same as with union, both input relations must be *compatible*.
- SQL Expression: INTERSECT

$$S1 \cap S2$$



Intersection (\cap)

- Equivalent to:
 $S1 - (S1 - S2)$

$S1 \cap S2$

<u>sid</u>	sname	rating	age
31	lubber	8	55.5
58	rusty	10	35.0

Relational Instance **S1**


<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

Relational Instance **S2**

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0



Intersection (\cap), Pt 2

- $S1 \cap S2 = ?$





Intersection (\cap), Pt 3

- $S1 \cap S2 = S1 - ?$



Intersection (\cap), Pt 4

- $S1 \cap S2 = S1 - (S1 - S2)$



- Is intersection monotonic?

$$R_1 \subseteq R_2 \Rightarrow S \cap R_1 \subseteq S \cap R_2$$

Compound Operator: Join

- Joins are compound operators (like intersection):
 - Generally, $\sigma_{\theta}(R \times S)$
- Hierarchy of common kinds:
 - **Theta Join** (\bowtie_{θ}): join on logical expression θ
 - **Equi-Join**: theta join with theta being a conjunction of equalities
 - **Natural Join** (\bowtie): equi-join on all matching column names

Note: we will need to learn a good join algorithm.

Avoid cross-product if we can!!

Another Theta Join (\bowtie_{θ}) Example ^{S1:}

- $R \bowtie_{\theta} S = \sigma_{\theta}(R \times S)$
- **Example:** *More senior sailors for each sailor.*
- $S1 \bowtie_{f4 < f8} S1$

<u>f1</u>	f2	f3	f4
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

S1				S1			
f1	f2	f3	f4	f5	f6	f7	f8
22	dustin	7	45.0	22	dustin	7	45.0
22	dustin	7	45.0	31	lubber	8	55.5
22	dustin	7	45.0	58	rusty	10	35.0
31	lubber	8	55.5	22	dustin	7	45.0
31	lubber	8	55.5	31	lubber	8	55.5
31	lubber	8	55.5	58	rusty	10	35.0
58	rusty	10	35.0	22	dustin	7	45.0
58	rusty	10	35.0	31	lubber	8	55.5
58	rusty	10	35.0	58	rusty	10	35.0

Another Theta Join (\bowtie_{θ}), Pt 2

- $R \bowtie_{\theta} S = \sigma_{\theta}(R \times S)$
- **Example:** *More senior sailors for each sailor.*
- $S1 \bowtie_{\text{age} < \text{age2}} S1$

S1:

f1	f2	f3	f4
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

S1				S1			
f1	f2	f3	f4	f5	f6	f7	f8
22	dustin	7	45.0	22	dustin	7	45.0
22	dustin	7	45.0	31	lubber	8	55.5
22	dustin	7	45.0	58	rusty	10	35.0
31	lubber	8	55.5	22	dustin	7	45.0
31	lubber	8	55.5	31	lubber	8	55.5
31	lubber	8	55.5	58	rusty	10	35.0
58	rusty	10	35.0	22	dustin	7	45.0
58	rusty	10	35.0	31	lubber	8	55.5
58	rusty	10	35.0	58	rusty	10	35.0

Another Theta Join (\bowtie_{θ}), Pt 3

- $R \bowtie_{\theta} S = \sigma_{\theta}(R \times S)$
- **Example:** *More senior sailors for each sailor.*
- $S1 \bowtie_{f4 < f8} S1$

S1:

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

S1				S1			
sid	sname	rating	age	sid	sname	rating	age2
22	dustin	7	45.0	31	lubber	8	55.5
58	rusty	10	35.0	22	dustin	7	45.0
58	rusty	10	35.0	31	lubber	8	55.5

- Result *schema* same as that of cross-product.
- Special Case:
 - **Equi-Join:** *theta join with AND of = predicates*
 - Special special case **Natural Join** ...

Natural Join (\bowtie)

- Special case of equi-join in which equalities are specified for all matching fields and duplicate fields are projected away

$$\mathbf{R} \bowtie \mathbf{S} = \pi_{\text{unique fld.}} \sigma_{\text{eq. matching fld.}}(\mathbf{R} \times \mathbf{S})$$

- Compute $\mathbf{R} \times \mathbf{S}$
- Select rows where fields appearing in both relations have equal values
- Project onto the set of all unique fields.

Natural Join (\bowtie) Pt 2

- $R \bowtie S = \pi_{\text{unique fld.}} \sigma_{\text{eq. matching fld.}} (R \times S)$

$R1 \bowtie S1$

sid	bid	day	sid	sname	rating	age
22	101	10/10/96	22	dustin	7	45.0
22	101	10/10/96	31	lubber	8	55.5
22	101	10/10/96	58	rusty	10	35.0
58	103	11/12/96	22	dustin	7	45.0
58	103	11/12/96	31	lubber	8	55.5
58	103	11/12/96	58	rusty	10	35.0

R1:

<u>sid</u>	<u>bid</u>	<u>day</u>
22	101	10/10/96
58	103	11/12/96

S1:

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

Natural Join (\bowtie), Pt 3

- $R \bowtie S = \pi_{\text{unique fld.}} \sigma_{\text{eq. matching fld.}} (R \times S)$

$R1 \bowtie S1$

sid	bid	day	sname	rating	age
22	101	10/10/96	dustin	7	45.0
58	103	11/12/96	rusty	10	35.0

R1:

<u>sid</u>	<u>bid</u>	<u>day</u>
22	101	10/10/96
58	103	11/12/96

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

- Commonly used for foreign key joins (as above).

Extended Relational Algebra

- Group By / Aggregation Operator (γ):
 - $\gamma_{\text{age, AVG(rating)}}(\text{Sailors})$
 - With selection (HAVING clause):
 - $\gamma_{\text{age, AVG(rating), COUNT(*) > 2}}(\text{Sailors})$

Summary

- Relational Algebra: a small set of operators mapping relations to relations
 - Operational, in the sense that you specify the explicit order of operations
 - A closed set of operators! Mix and match.
- Basic ops include: σ , π , \times , \cup , $-$
- Important compound ops: \cap , \bowtie