


Maven Multi-Module Assignment

Steps:

```
>> mvn archetype:generate
```

```
// command to create maven project
```



```
15:20 • knoldus@knoldus-Vostro-3590: ~/Assignments
knoldus@knoldus-Vostro-3590:~/Assignments$ mvn archetype:generate
WARNING: An illegal reflective access operation has occurred
WARNING: Illegal reflective access by com.google.inject.internal.cglib.core.$ReflectUtils$1 (file:/usr/share/maven/lib/guice.jar) to method java.lang.ClassLoader.defineClass(java.lang.String,byte[],int,int,java.security.ProtectionDomain)
WARNING: Please consider reporting this to the maintainers of com.google.inject.internal.cglib.core.$ReflectUtils$1
WARNING: Use --illegal-access=warn to enable warnings of further illegal reflective access operations
WARNING: All illegal access operations will be denied in a future release
[INFO] Scanning for projects...
[INFO]
```

Now it will ask for to choose architecture type for creating a project:

```
>> 2007
```

```
// command to choose architecture type
```

Now it will ask for maven archetype version:

```
>> 8
```

```
// this command will choose 1.4 version from given list
```

Now it will ask for groupId: We will Enter the name of Whatever Organization we are creating project for.

```
>> com.knoldus
```

```
// command is used the enter the name of Organization
```

Now it will ask for artifactId: We will Enter the Project Name here.

```
>> stringmanipulation
```

```
// command is used the enter the name of Project
```

Now it will ask for version: We will Enter the Version here.

```
>> 1.0-SNAPSHOT
```

```
// command is used the enter the version of Project.
```

Now it will ask for package name: We will Enter the package name here.

```
>> com.knoldus
```

```
// command is used the enter the package name..
```

Above Commands Output:

```
3225: remote -> za.co.absa.hyperdrive:component-archetype_2.11 (-)
3226: remote -> za.co.absa.hyperdrive:component-archetype_2.12 (-)
Choose a number or apply filter (format: [groupId:]artifactId, case sensitive contains): 2007: 2007
Choose org.apache.maven.archetypes:maven-archetype-quickstart version:
1: 1.0-alpha-1
2: 1.0-alpha-2
3: 1.0-alpha-3
4: 1.0-alpha-4
5: 1.0
6: 1.1
7: 1.3
8: 1.4
Choose a number: 8: 8
Define value for property 'groupId': com.knoldus
Define value for property 'artifactId': stringmanipulation
Define value for property 'version' 1.0-SNAPSHOT: : 1.0-SNAPSHOT
Define value for property 'package' com.knoldus: : com.knoldus
Confirm properties configuration:
groupId: com.knoldus
artifactId: stringmanipulation
version: 1.0-SNAPSHOT
package: com.knoldus
Y: : Y
[INFO] -----
[INFO] Using following parameters for creating project from Archetype: maven-archetype-quickstart:1.4
[INFO] -----
[INFO] Parameter: groupId, Value: com.knoldus
[INFO] Parameter: artifactId, Value: stringmanipulation
[INFO] Parameter: version, Value: 1.0-SNAPSHOT
[INFO] Parameter: package, Value: com.knoldus
[INFO] Parameter: packageInPathFormat, Value: com/knoldus
[INFO] Parameter: package, Value: com.knoldus
[INFO] Parameter: groupId, Value: com.knoldus
[INFO] Parameter: artifactId, Value: stringmanipulation
[INFO] Parameter: version, Value: 1.0-SNAPSHOT
[INFO] Project created from Archetype in dir: /home/knoldus/Assignments/stringmanipulation
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 05:36 min
[INFO] Finished at: 2023-02-24T15:21:58+05:30
[INFO] -----
knoldus@knoldus-Vostro-3590:~/Assignments$
```

Now we will edit pom.xml file of project we created earlier:

In the pom.xml file we will add the line `<packaging>pom</packaging>` as you can see in screenshot below:

We have mentioned this line because now this will work as container of sub-modules.

```
1 <?xml version="1.0" encoding="UTF-8"?>
2
3 <project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XM
4   xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/xsd/mav
5   <modelVersion>4.0.0</modelVersion>
6
7   <groupId>com.knoldus</groupId>
8   <artifactId>stringmanipulation</artifactId>
9   <version>1.0-SNAPSHOT</version>
10  <packaging>pom</packaging>
11
12  <name>stringmanipulation</name>
13  <!-- FIXME change it to the project's website -->
14  <url>http://www.example.com</url>
15
16  <properties>
```

Now we will create the next module in stringmanipulation directory:

Module Name: `modify-strings`

```
>> mvn archetype:generate  
// command to create another module in stringmanipulation project.
```

Now it will again ask to choose architecture type for this module:

We will use the same command as we did earlier

```
>> 2007  
  
// command to choose architecture type  
  
>> 8  
  
// this command will choose 1.4 version from given list  
  
>> com.knoldus  
  
// command is used to enter the name of Organization
```

>> modify-strings

// command is used the enter the name of another module

>> 1.0-SNAPSHOT

// command is used the enter the version of Project.

>> com.knoldus

// command is used the enter the package name.

Above Commands Output:

```
3223: remote -> za.co.absa.hyperdrive:component-archetype_2.11 (-)
3226: remote -> za.co.absa.hyperdrive:component-archetype_2.12 (-)
Choose a number or apply filter (format: [groupId:]artifactId, case sensitive contains): 2007: 2007
Choose org.apache.maven.archetypes:maven-archetype-quickstart version:
1: 1.0-alpha-1
2: 1.0-alpha-2
3: 1.0-alpha-3
4: 1.0-alpha-4
5: 1.0
6: 1.1
7: 1.3
8: 1.4
Choose a number: 8: 8
Define value for property 'groupId': com.knoldus
Define value for property 'artifactId': modify-strings
Define value for property 'version' 1.0-SNAPSHOT: : 1.0-SNAPSHOT
Define value for property 'package' com.knoldus: : com.knoldus
Confirm properties configuration:
groupId: com.knoldus
artifactId: modify-strings
version: 1.0-SNAPSHOT
package: com.knoldus
Y: : Y
[INFO] -----
[INFO] Using following parameters for creating project from Archetype: maven-archetype-quickstart:1.4
[INFO] -----
[INFO] Parameter: groupId, Value: com.knoldus
[INFO] Parameter: artifactId, Value: modify-strings
[INFO] Parameter: version, Value: 1.0-SNAPSHOT
[INFO] Parameter: package, Value: com.knoldus
[INFO] Parameter: packageInPathFormat, Value: com/knoldus
[INFO] Parameter: package, Value: com.knoldus
[INFO] Parameter: groupId, Value: com.knoldus
[INFO] Parameter: artifactId, Value: modify-strings
[INFO] Parameter: version, Value: 1.0-SNAPSHOT
[INFO] Project created from Archetype in dir: /home/knoldus/Assignments/stringmanipulation/modify-strings
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 26.949 s
[INFO] Finished at: 2023-02-24T15:52:37+05:30
[INFO] -----
knoldus@knoldus-Vostro-3590:~/Assignments/stringmanipulation$
```


Now we will again edit pom.xml file of module we created earlier(modify-strings):

In the pom.xml file we will again add the line `<packaging>pom</packaging>` as you can see in screenshot below:

We have mentioned this line because now this module will work as container of sub-modules.



```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocati
3 <modelVersion>4.0.0</modelVersion>
4 <parent>
5 <artifactId>stringmanipulation</artifactId>
6 <groupId>com.knoldus</groupId>
7 <version>1.0-SNAPSHOT</version>
8 </parent>
9
10 <groupId>com.knoldus</groupId>
11 <artifactId>modify-strings</artifactId>
12 <version>1.0-SNAPSHOT</version>
13 <packaging>pom</packaging>
14
15 <name>modify-strings</name>
16 <!-- FIXME change it to the project's website -->
17 <url>http://www.example.com</url>
18
```

Now we will create another modules in modify-strings module:

Module 1: string-api

```
>> mvn archetype:generate
```

```
// command to create maven project
```

```
>> 2007
```

```
// command to choose architecture type
```

```
>> 8
```

```
// this command will choose 1.4 version from given list
```

```
>> com.knoldus
```

```
// command is used to enter the name of Organization
```

```
>> string-api
```

```
// command is used to enter the name of child module created under modify-string module
```

```
>> 1.0-SNAPSHOT
```

// command is used to enter the version of Project.

```
>> com.knoldus
```

// command is used to enter the package name.

Above Commands Output:

```
3224: remote -> za.co.absa.hyperdrive:component-archetype (-)
3225: remote -> za.co.absa.hyperdrive:component-archetype_2.11 (-)
3226: remote -> za.co.absa.hyperdrive:component-archetype_2.12 (-)
Choose a number or apply filter (format: [groupId]:artifactId, case sensitive contains): 2007: 2007
Choose org.apache.maven.archetypes:maven-archetype-quickstart version:
1: 1.0-alpha-1
2: 1.0-alpha-2
3: 1.0-alpha-3
4: 1.0-alpha-4
5: 1.0
6: 1.1
7: 1.3
8: 1.4
Choose a number: 8: 8
Define value for property 'groupId': com.knoldus
Define value for property 'artifactId': string-api
Define value for property 'version' 1.0-SNAPSHOT: : 1.0-SNAPSHOT
Define value for property 'package' com.knoldus: : com.knoldus
Confirm properties configuration:
groupId: com.knoldus
artifactId: string-api
version: 1.0-SNAPSHOT
package: com.knoldus
Y: : Y
[INFO] -----
[INFO] Using following parameters for creating project from Archetype: maven-archetype-quickstart:1.4
[INFO] -----
[INFO] Parameter: groupId, Value: com.knoldus
[INFO] Parameter: artifactId, Value: string-api
[INFO] Parameter: version, Value: 1.0-SNAPSHOT
[INFO] Parameter: package, Value: com.knoldus
[INFO] Parameter: packageInPathFormat, Value: com/knoldus
[INFO] Parameter: package, Value: com.knoldus
[INFO] Parameter: groupId, Value: com.knoldus
[INFO] Parameter: artifactId, Value: string-api
[INFO] Parameter: version, Value: 1.0-SNAPSHOT
[INFO] Project created from Archetype in dir: /home/knoldus/Assignments/stringmanipulation/modify-strings
/string-api
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 33.522 s
[INFO] Finished at: 2023-02-24T15:59:13+05:30
[INFO] -----
knoldus@knoldus-Vostro-3590:~/Assignments/stringmanipulation/modify-strings$
```

Now we will create another modules in same directory(modify-strings) module:

Module 1: string-impl

```
>> mvn archetype:generate
```

```
// command to create maven project
```

```
>> 2007
```

```
// command to choose architecture type
```

```
>> 8
```

```
// this command will choose 1.4 version from given list
```

```
>> com.knoldus
```

```
// command is used the enter the name of Organization
```

```
>> string-impl
```

```
// command is used the enter the name of child module created under modify-string module
```

```
>> 1.0-SNAPSHOT
```

// command is used the enter the version of module.

```
>> com.knoldus
```

// command is used the enter the package name of string-impl module.

Project Hierarchy:

