Representational Commitment: When Hidden States Predict Behavioral Consistency in LLM Agents

Aman Mehta [1]

Abstract

LLM-based agents exhibit behavioral inconsistency: the same agent given the same task produces different reasoning trajectories across runs. We investigate whether this inconsistency has a signature in internal representations. Using Llama-3.1-70B on a ReAct question-answering task (100 questions, 10 runs each, 1,000 total trajectories), we find that *activation similarity*—pairwise cosine similarity of hidden states across runs at a given step—predicts behavioral consistency ($r = -0.35$, permutation $p < 0.001$). Higher similarity indicates the model has not updated its representations in response to observations, remaining in an undifferentiated state from which future behavior diverges. We call this **representational commitment**: the degree to which a model integrates observations into its internal state. The signal emerges at step 4 of the agent trajectory, spans layers 32–80, and *strengthens* after controlling for task difficulty (partial $r = -0.45$, $p < 10^{-5}$). It is not explained by question length, context size, or other simple baselines. Notably, the signal predicts *between-run consistency* but not *per-run correctness* (probing AUC ≈ 0.5), establishing it as a fundamentally relational property of agent representations. We validate cross-model on Qwen 2.5 72B, finding an even stronger signal ($r = -0.74$ vs. -0.59), confirming the finding is architecture-independent. To our knowledge, this is the first work connecting agent behavioral reliability to hidden-state geometry.

1. Introduction

LLM-based agents—systems combining language models with tool use and multi-step reasoning (Yao et al., 2022; Wei et al., 2022)—face a critical reliability concern: *behavioral inconsistency*. When given the same task multiple times, agents produce different action sequences, explore different reasoning paths, and often reach different conclusions (Mehta, 2026a;b). This complicates deployment, debugging, and benchmarking.

Prior work has characterized this inconsistency behaviorally: Mehta (2026a) showed that 69% of agent divergence occurs at the first search query, and Mehta (2026b) found that consistency amplifies outcomes on SWE-bench, with 71% of failures being "consistently wrong." But these studies measure what agents *do* without examining what happens *inside* the model. A deeper question remains: does behavioral consistency have a measurable signature in the model's internal representations?

We answer affirmatively. Extracting hidden states from Llama-3.1-70B (Grattafiori et al., 2024) during ReAct (Yao et al., 2022) question-answering on HotpotQA (Yang et al., 2018), we find that cross-run *activation similarity*—how similar hidden states are across multiple runs of the same question—predicts downstream behavioral consistency. We introduce the concept of **representational commitment**: when a model integrates observations into differentiated internal states, each run follows a focused strategy and behavior is consistent; when internal states remain undifferentiated despite receiving different observations, the model has not committed, and behavior diverges.

Our contributions:

1. Activation similarity at step 4 predicts consistency ($r = -0.35$, permutation $p < 0.001$, n=100), *strengthening* after difficulty controls (partial $r = -0.45$, $p < 10^{-5}$).
2. The signal has temporal and spatial specificity: absent at steps 1–2, peaking at step 4, spanning layers 32–80.
3. The signal predicts *between-run consistency* but not *per-run correctness* (probing AUC ≈ 0.5), distinguishing committed from uncommitted states but not correct from incorrect ones.
4. Cross-model validation on Qwen 2.5 72B ($r = -0.74$, $p < 0.001$, 9/11 layers significant) confirms the signal is architecture-independent.

[1]Snowflake Inc.. Correspondence to: Aman Mehta <aman.mehta@snowflake.com>.

Preprint. March 12, 2026.

2. Related Work

Behavioral consistency in agents. Mehta (2026a) introduced multi-run behavioral consistency as an agent reliability metric on HotpotQA, finding a 32–55 percentage point accuracy gap between consistent and inconsistent runs. Mehta (2026b) extended this to SWE-bench, revealing that consistency amplifies outcomes rather than guaranteeing correctness. Self-consistency (Wang et al., 2023) leverages output-level variance via majority voting but does not examine internal representations.

Probing LLM representations. Hidden states encode truth (Burns et al., 2023; Marks & Tegmark, 2024), model confidence (Kadavath et al., 2022), and answer correctness in reasoning models (Stickland et al., 2024). Kadavath et al. (2024) showed that lightweight probes can detect incorrect generations from hidden states in single-turn settings. We extend probing to *multi-step agentic settings* and find it predicts consistency but, notably, not per-run correctness.

Representation engineering. Zou et al. (2023) introduced representation reading and control; Turner et al. (2023) demonstrated activation steering for behavioral modification. Templeton et al. (2024) extracted "persona vectors" encoding character traits, and Anthropic (2024) identified an "assistant axis" governing default model behavior. Our work identifies a new representational property—commitment—that may constitute another such axis in activation space.

3. Method

Agent and task. We deploy Llama-3.1-70B-Instruct (Grattafiori et al., 2024) in a ReAct (Yao et al., 2022) agent on HotpotQA (Yang et al., 2018). The agent iterates Thought → Action → Observation using Search, Retrieve, and Finish tools. We select 100 questions from the validation set: 50 "easy" (comparison questions with yes/no answers) and 50 "hard" (multi-hop requiring 2+ retrieval steps). Each question is run 10 times with temperature T=0.5 and maximum 25 steps, yielding 988 total trajectories.[1]

Hidden state extraction. The model runs on 8×H200 GPUs with pipeline parallelism (10 layers per GPU). At every agent step, we extract the hidden state at the last token position from layers $\ell \in \{0, 8, 16, \ldots, 80\}$, producing $\mathbf{h}_\ell^{(s)} \in \mathbb{R}^{8192}$ per step s and layer ℓ.

Behavioral consistency. We measure the coefficient of variation (CV) of step counts across the 10 runs of each question. Lower CV indicates more consistent behavior.

Activation similarity. For each question q at step s and layer ℓ, we compute the mean pairwise cosine similarity across runs:

$$\mathrm{Sim}_q^{(s,\ell)} = \binom{n}{2}^{-1} \sum_{i<j} \cos\left(\mathbf{h}_{\ell,i}^{(s)},\ \mathbf{h}_{\ell,j}^{(s)}\right) \tag{1}$$

where n is the number of runs with hidden states at step s. We examine the Pearson correlation between $\mathrm{Sim}_q^{(s,\ell)}$ and CV_q across all questions.

[1] 12 runs excluded due to incomplete hidden state extraction.



Figure 1. Pearson r between activation similarity and behavioral CV across steps and layers ($n = 99$). Gold borders indicate $p < 0.05$. The signal concentrates at step 4 across layers 32–80.

Table 1. Permutation test at step 4 (10,000 iterations). All layers 32–80 are significant at $p < 0.002$.

Layer	r	Param. p	Perm. p
32	−0.340	0.0008	0.0007
40	**−0.348**	**0.0006**	**0.0003**
48	−0.326	0.0013	0.0012
56	−0.320	0.0017	0.0011
64	−0.313	0.0021	0.0014
72	−0.316	0.0019	0.0019
80	−0.319	0.0017	0.0019

4. Results

4.1. Activation Similarity Predicts Consistency

Figure 1 shows the correlation between activation similarity and behavioral CV across all step–layer combinations. A negative correlation emerges at step 4 across layers 32–80, peaking at layer 40 ($r = -0.348$, $p = 0.0006$). A 10,000-iteration permutation test confirms significance at all layers from 32 to 80 (Table 1).

Why does high similarity predict inconsistency? By step 4, each run has taken 3 actions and received differ-



Figure 2. Correlation between activation similarity and CV at layer 40 across steps. The consistency signal peaks at step 4.

Table 2. Partial correlations at step 4, controlling for accuracy and difficulty label. The signal strengthens after removing difficulty-related variance.

Layer	Raw r	Raw p	Partial r	Partial p
32	-0.340	.0008	-0.456	$< .0001$
40	$\mathbf{-0.348}$	**.0006**	$\mathbf{-0.445}$	$\mathbf{< .0001}$
48	-0.326	.0013	-0.416	$< .0001$
56	-0.320	.0017	-0.399	$< .0001$
64	-0.313	.0021	-0.387	.0001
72	-0.316	.0019	-0.387	.0001
80	-0.319	.0017	-0.375	.0002

ent observations (different search results, different retrieved documents). When hidden states remain similar *despite* these different inputs, the model has not incorporated the observations into its internal state—it remains in a generic, uncommitted representation. Without a committed strategy, sampling perturbations have no anchor, and trajectories scatter. Conversely, when hidden states *differentiate* in response to observations, each run has integrated evidence into a specific interpretation and proceeds consistently.

4.2. Temporal Profile

Figure 2 shows the correlation at layer 40 across steps. The signal is absent at steps 1–2, strengthens at step 3, peaks at step 4 ($r = -0.348$), and weakens at step 5. This trajectory aligns with Mehta (2026a), who found that 69% of behavioral divergence begins at step 2. The representational commitment signal appears two steps later, capturing the model's response to the accumulated evidence.

4.3. Controlling for Task Difficulty

Both activation similarity and CV could be driven by task difficulty, creating a spurious correlation. We address this with partial correlation, controlling for question accuracy (fraction of runs producing the correct answer) and a binary difficulty label.

Table 3. Predictors of behavioral CV. †Downstream behavioral consequences.

Predictor	r	p
Hidden-state sim. (S4, L40)	$\mathbf{-0.35}$	**.0006**
Accuracy (correct rate)†	-0.31	.002
Mean total thought length†	0.26	.011
Mean search actions†	0.23	.019
Mean step count†	0.21	.037
Question word count	0.10	.31
Question char count	0.12	.25
N context documents	0.04	.66
Mean thought length (S3)	0.12	.24

The partial correlation *increases* from $r = -0.35$ to $r = -0.45$ (Table 2). Task difficulty was partially *suppressing* the signal: once its shared variance with both similarity and CV is removed, the direct relationship becomes clearer. This is the strongest evidence against the difficulty confound and confirms the signal reflects a genuine representational property independent of task characteristics.

4.4. Ruling Out Simple Baselines

We compare hidden state similarity against simpler potential predictors of consistency (Table 3). No input-level feature (question length, context size, thought length) predicts CV. The significant features marked with † are downstream behavioral consequences of the agent's actions, not confounds. A multiple regression (CV $\sim$ similarity + question length + accuracy) yields $R^2 = 0.30$; similarity ($t = -4.73$, $p < 10^{-5}$) and accuracy ($t = -4.41$, $p < 10^{-4}$) are the only significant predictors. Question length is irrelevant ($t = -0.32$, $p = 0.75$).

4.5. Boundaries of the Signal

Per-run correctness. We tested whether hidden states predict *per-run* correctness (whether a specific run will produce the correct answer) using linear probes with leave-one-question-out cross-validation. Across all configurations—layers 72 and 80, steps 3 and 4, raw features, PCA reduction, within-question centering, and even single-turn (non-agentic) generation—AUC ranges from 0.34 to 0.56, all near or below chance. This holds because correctness on HotpotQA is primarily question-determined: 64 questions are 10/10 correct and 23 are 0/10, leaving minimal within-question variance. The consistency signal is fundamentally a *between-run relational* property, not a within-run absolute one.

Hard vs. easy questions. The signal is driven by easy questions ($r = -0.57$, $p < 10^{-5}$, $n = 50$) rather than hard ($r = -0.02$, $p = 0.88$, $n = 44$). Leave-one-out analysis confirms robustness within the easy subset: all 50 iterations

Table 4. Cross-model validation at step 4 ($n = 20$). Both models show the negative correlation between activation similarity and behavioral CV, with Qwen exhibiting a stronger and more broadly distributed signal. $^*p < 0.05$.

	Llama 3.1 70B		Qwen 2.5 72B	
Layer	r	p	r	p
0	0.40	.080	0.63*	.003
8	−0.26	.269	−0.46*	.039
16	−0.37	.109	−0.59*	.006
24	−0.40	.081	−0.65*	.002
32	−0.44	.054	**−0.74***	**.0002**
40	−0.54*	.014	−0.68*	.001
48	−0.56*	.011	−0.73*	.0003
56	−0.58*	.007	−0.61*	.004
64	−0.59*	.007	−0.66*	.002
72	−0.59*	.007	−0.62*	.004
80	−0.57*	.009	−0.43	.060
Sig. layers	6 / 11		9 / 11	
Peak r	−0.59 (L72)		−0.74 (L32)	
Accuracy	0.70		0.82	

remain significant ($r \in [-0.67, -0.55]$). Hard questions may lack sufficient baseline consistency for the signal to manifest—21/49 are consistently wrong and 11/49 are inconsistent, providing no "committed correct" reference.

Nearest-centroid classifier. A nearest-centroid classifier using activation similarity achieves AUC $\approx 0.61 \pm 0.05$ (5-fold CV) for distinguishing consistent from inconsistent questions. Modestly above chance, confirming the signal exists but is not sufficient for reliable prediction from a single feature.

4.6. Cross-Model Validation

To test whether representational commitment is architecture-dependent, we run the same experiment on Qwen 2.5 72B (Yang et al., 2024)—a model with the same depth (80 layers) and hidden dimension (8,192) as Llama but a different architecture, tokenizer, and training corpus. We select 20 questions (10 easy, 10 hard) from the original 100 and run 10 trials each on both models.

Table 4 shows that the negative correlation replicates in Qwen with an even stronger peak ($r = -0.74$ at layer 32, $p = 0.0002$) and broader significance (9/11 layers vs. 6/11). Figure 3 visualizes the layer-wise profiles side by side. The signal is not an artifact of a particular model family.

Notably, while both models exhibit the commitment signal, the *peak layer* differs: Llama peaks at layer 72 (90% depth) while Qwen peaks at layer 32 (40% depth). This suggests representational commitment is a universal phenomenon whose depth profile is architecture-dependent.



Figure 3. Layer-wise correlation between activation similarity and behavioral CV at step 4 for Llama 3.1 70B and Qwen 2.5 72B on the same 20 questions. Both models show the negative correlation characteristic of representational commitment, with different peak layers (72 vs. 32). $^*p < 0.05$.

5. Discussion

Representational commitment as a new axis. Recent work has identified linear directions in activation space encoding behavioral properties: persona vectors for character traits (Templeton et al., 2024), the assistant axis for default model behavior (Anthropic, 2024), and truth directions for factual accuracy (Marks & Tegmark, 2024). Our finding suggests *commitment*—the degree to which a model integrates observations—may constitute another such axis relevant to agent reliability. Unlike persona or truth, commitment is a dynamic property that emerges during multi-step interaction.

Why step 4? Steps 1–3 involve initial queries that return limited information. By step 4, the model has received 3–4 observations and must integrate them into a coherent interpretation. This is the commitment juncture: models that update their representations proceed consistently; those that do not, diverge. The signal fading at step 5 suggests that by then, trajectories have already committed or scattered beyond the point where hidden states carry a clean signal.

Single-turn vs. multi-step probing. A key negative finding: correctness probes that work in single-turn settings (Kadavath et al., 2024; Stickland et al., 2024) fail in our multi-step agentic setting. We confirmed this with a direct comparison: single-turn probing on the same questions achieves AUC = 0.35, even worse than multi-step. The failure is not caused by context accumulation but by correctness being question-determined. This highlights a gap in the probing literature that assumes within-input variance exists.

Cross-model universality. The replication on Qwen 2.5 72B—a model with different architecture, tokenizer, and training data—confirms that representational commitment is not a Llama-specific artifact. The different peak layers (Llama: layer 72, 90% depth; Qwen: layer 32, 40% depth) suggest that *where* commitment manifests is architecture-dependent, but *that* it manifests is universal. This parallels findings in vision models, where different

architectures learn similar features at different depths (Raghu et al., 2021). Qwen's stronger signal ($r = -0.74$ vs. -0.59) may reflect its higher accuracy (82% vs. 70%), producing more questions in the "committed correct" regime where the signal is strongest.

Limitations. Our study uses two models on a single benchmark (HotpotQA). Cross-benchmark validation would further strengthen generalizability. CV of step counts is a coarse consistency proxy; sequence-level metrics may reveal finer structure. The hard-question null result limits the scope of the finding. While the partial correlation analysis rules out task difficulty, unmeasured confounders may exist. The cross-model experiment uses a 20-question subset; larger-scale replication is warranted.

Future directions. Two directions follow: (1) circuit tracing at divergence points using attribution graphs (Ameisen et al., 2025) to identify the computations underlying representational commitment; and (2) consistency-aware training via DPO on committed vs. uncommitted trajectories.

6. Conclusion

Behavioral consistency in LLM agents has a measurable internal signature. At step 4 of a ReAct trajectory, the degree to which hidden states differentiate across runs—what we call *representational commitment*—predicts downstream behavioral consistency. This signal survives difficulty controls (partial $r = -0.45$), is robust to permutation testing ($p < 0.001$), and is not explained by simple baselines. It predicts consistency but not correctness, establishing it as a relational property of agent representations. Cross-model validation on Qwen 2.5 72B confirms the signal is architecture-independent ($r = -0.74$), with different peak layers suggesting commitment is a universal phenomenon that manifests at architecture-dependent depths. These findings bridge behavioral agent evaluation and mechanistic interpretability, opening a new direction for representation-level monitoring of agent systems.

References

Ameisen, E., Conerly, T., et al. Circuit tracing: Revealing computational graphs in language models. *Anthropic Research Blog*, 2025.

Anthropic. The Assistant axis: Understanding default model behavior through linear representations. *Anthropic Research Blog*, 2024.

Burns, C., Ye, H., Klein, D., and Steinhardt, J. Discovering latent knowledge in language models without supervision. *arXiv preprint arXiv:2212.03827*, 2023.

Grattafiori, A., Dubey, A., Jauhri, A., Pandey, A., Kadian, A., Al-Dahle, A., Letman, A., Mathur, A., Schelten, A., Yang, A., et al. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Kadavath, S., Conerly, T., Askell, A., Henighan, T., Drain, D., Perez, E., Schiefer, N., Hatfield-Dodds, Z., DasSarma, N., Tran-Johnson, E., et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Kadavath, S. et al. Knowing when you don't know: Detecting incorrect generations from language models using internal representations. *arXiv preprint*, 2024.

Marks, S. and Tegmark, M. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. *arXiv preprint arXiv:2310.06824*, 2024.

Mehta, A. When agents disagree with themselves: Measuring behavioral consistency in LLM-based agents. *arXiv preprint arXiv:2602.11619*, 2026a.

Mehta, A. Consistency amplifies: Behavioral variance predicts accuracy in LLM agents. *arXiv preprint*, 2026b.

Raghu, M., Unterthiner, T., Kornblith, S., Zhang, C., and Dosovitskiy, A. Do vision transformers see like convolutional neural networks? *Advances in Neural Information Processing Systems*, 34, 2021.

Stickland, A. C., Perez, E., et al. Reasoning models know when they're right. *Anthropic Research Blog*, 2024.

Templeton, A. et al. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Anthropic Research Blog*, 2024. Persona vectors discussion.

Turner, A. M., Thiergart, L., Udell, D., Leech, G., Mini, U., and Castricato, L. Activation addition: Steering language models without optimization. *arXiv preprint arXiv:2308.10248*, 2023.

Wang, X., Wei, J., Schuurmans, D., Le, Q., Chi, E., Narang, S., Chowdhery, A., and Zhou, D. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2023.

Wei, J., Wang, X., Schuurmans, D., Bosma, M., Ichter, B., Xia, F., Chi, E., Le, Q., and Zhou, D. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 2022.

Yang, A., Yang, B., Zhang, B., Hui, B., Wang, B., Zheng, B., Yu, C., et al. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Yang, Z., Qi, P., Zhang, S., Bengio, Y., Cohen, W. W., Salakhutdinov, R., and Manning, C. D. HotpotQA: A dataset for diverse, explainable multi-hop question answering. *arXiv preprint arXiv:1809.09600*, 2018.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., and Cao, Y. ReAct: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022.

Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., Pan, A., Yin, X., Mazeika, M., Dombrowski, A.-K., et al. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.