```
0x15 0x2C 0x00 0x0A 0x31 0x32 0x33 0x34 0x35 0x36 0x37 0x38 0x39 0x30 0x18

Data        Comments
=========== ===================================================
0x15        Control Byte for outermost container (structure)
              - Tag control 000xxxxxb: Anonymous tag
              - Elem type   xxx10101b: Structure

0x2C        Control Byte for next TLV
              - Tag control 001xxxxxb: Context-specific tag
              - Elem type   xxx01100b: UTF-8 String, 1-byte length
                            ---------
                            00101100b = 0x2C
0x00        Context-specific Matter-common Serial Number tag
              - Matter-common versus vendor tag 0xxxxxxxb: Matter-common tag
              - Tag number                      x0000000b: kTag_SerialNumber
                                                ---------
                                                00000000b = 0x00
0x0A        Length of Serial Number string (10 bytes)
0x31 0x32 0x33 0x34 0x35 0x36 0x37 0x38 0x39 0x30
            UTF-8 encoded Serial Number string "1234567890"

0x18        End of container
```

5.1.6. Concatenation

The Onboarding Payload MAY be concatenated with additional Onboarding Payloads to be placed in a single QR Code or NFC Tag:

```
QR code string := MT:<onboarding-base-38-content>*<onboarding-base-38-content2>
```

Where * is used as the delimiter.

Concatenation of multiple Matter Onboarding Payloads allows a single QR code (or NFC Tag) to provide the onboarding payload for a number of devices. Each <onboarding-base-38-content> represents the Onboarding Payload for a specific device, and can include its own TLV section (for the TLV content specific to that device). Each <onboarding-base-38-content> can have a length as described in Section 5.1.3.2.3, “Payload Limits”, so the overall length of the resulting concatenated QR code can be larger than such limits.

Example use case for this concatenation:

• Easy commissioning for multi-device packaging, e.g. for a package of light bulbs containing four separate bulbs. Each bulb will have its own Onboarding Payload code(s) printed on the bulb

